

## CFM Operator Installation

Date published: 2024-06-11

Date modified: 2025-04-28



# Legal Notice

© Cloudera Inc. 2025. All rights reserved.

The documentation is and contains Cloudera proprietary information protected by copyright and other intellectual property rights. No license under copyright or any other intellectual property right is granted herein.

Unless otherwise noted, scripts and sample code are licensed under the Apache License, Version 2.0.

Copyright information for Cloudera software may be found within the documentation accompanying each component in a particular release.

Cloudera software includes software from various open source or other third party projects, and may be released under the Apache Software License 2.0 (“ASLv2”), the Affero General Public License version 3 (AGPLv3), or other license terms. Other software included may be released under the terms of alternative open source licenses. Please review the license and notice files accompanying the software for additional licensing information.

Please visit the Cloudera software product page for more information on Cloudera software. For more information on Cloudera support services, please visit either the Support or Sales page. Feel free to contact us directly to discuss your specific needs.

Cloudera reserves the right to change any products at any time, and without notice. Cloudera assumes no responsibility nor liability arising from the use of products, except as expressly agreed to in writing by Cloudera.

Cloudera, Cloudera Altus, HUE, Impala, Cloudera Impala, and other Cloudera marks are registered or unregistered trademarks in the United States and other countries. All other trademarks are the property of their respective owners.

Disclaimer: EXCEPT AS EXPRESSLY PROVIDED IN A WRITTEN AGREEMENT WITH CLOUDERA, CLOUDERA DOES NOT MAKE NOR GIVE ANY REPRESENTATION, WARRANTY, NOR COVENANT OF ANY KIND, WHETHER EXPRESS OR IMPLIED, IN CONNECTION WITH CLOUDERA TECHNOLOGY OR RELATED SUPPORT PROVIDED IN CONNECTION THEREWITH. CLOUDERA DOES NOT WARRANT THAT CLOUDERA PRODUCTS NOR SOFTWARE WILL OPERATE UNINTERRUPTED NOR THAT IT WILL BE FREE FROM DEFECTS NOR ERRORS, THAT IT WILL PROTECT YOUR DATA FROM LOSS, CORRUPTION NOR UNAVAILABILITY, NOR THAT IT WILL MEET ALL OF CUSTOMER’S BUSINESS REQUIREMENTS. WITHOUT LIMITING THE FOREGOING, AND TO THE MAXIMUM EXTENT PERMITTED BY APPLICABLE LAW, CLOUDERA EXPRESSLY DISCLAIMS ANY AND ALL IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO IMPLIED WARRANTIES OF MERCHANTABILITY, QUALITY, NON-INFRINGEMENT, TITLE, AND FITNESS FOR A PARTICULAR PURPOSE AND ANY REPRESENTATION, WARRANTY, OR COVENANT BASED ON COURSE OF DEALING OR USAGE IN TRADE.

# Contents

<b>Installation artifacts.....</b>	<b>4</b>
<b>Installing Cloudera Flow Management - Kubernetes Operator (internet).....</b>	<b>4</b>
<b>Installing Cloudera Flow Management - Kubernetes Operator (air-gap).....</b>	<b>8</b>
<b>Uninstalling Cloudera Flow Management - Kubernetes Operator.....</b>	<b>13</b>

## Installation artifacts

Learn about installing the Cloudera Flow Management - Kubernetes Operator, the installation artifacts, and where these artifacts are hosted.

Installing the Cloudera Flow Management - Kubernetes Operator installs NiFi and optionally the NiFi Registry. It also installs the custom resources (CRs) required for deploying NiFi clusters with the Cloudera Flow Management - Kubernetes Operator after installation.

### Installation artifacts and artifact locations

Cloudera Flow Management - Kubernetes Operator comes with various installation artifacts. These artifacts are hosted at two locations, the Cloudera Docker registry and the Cloudera Archive.

Both the Cloudera Docker registry and the Cloudera Archive require Cloudera credentials (username and password) for access. These credentials are provided to you as part of your license and subscription agreement and can be used to access both the registry and the archive.

Artifact	Location
Cloudera Flow Management - Kubernetes Operator Docker image	container.repository.cloudera.com/cloudera/cfm-operator:2.10.0-b134
Cloudera Flow Management - Kubernetes Operator Tini Docker image	container.repository.cloudera.com/cloudera/cfm-tini:2.10.0-b134
Apache NiFi Docker images	container.repository.cloudera.com/cloudera/cfm-nifi-k8s:2.10.0-b134-nifi_1.28.1.2.3.15.0-29
	container.repository.cloudera.com/cloudera/cfm-nifi-k8s:2.10.0-b134-nifi_2.3.0.4.3.2.0-89
Apache NiFi Registry Docker images	container.repository.cloudera.com/cloudera/cfm-nifi-registry-k8s:2.10.0-b134-nifi_1.28.1.2.3.15.0-29
	container.repository.cloudera.com/cloudera/cfm-nifi-registry-k8s:2.10.0-b134-nifi_2.3.0.4.3.2.0-89
cfmctl binaries	<ul style="list-style-type: none"> <li><a href="https://archive.cloudera.com/p/cfm-operator/cfmctl-darwin-amd64">https://archive.cloudera.com/p/cfm-operator/cfmctl-darwin-amd64</a></li> <li><a href="https://archive.cloudera.com/p/cfm-operator/cfmctl-darwin-arm64">https://archive.cloudera.com/p/cfm-operator/cfmctl-darwin-arm64</a></li> <li><a href="https://archive.cloudera.com/p/cfm-operator/cfmctl-linux-amd64">https://archive.cloudera.com/p/cfm-operator/cfmctl-linux-amd64</a></li> <li><a href="https://archive.cloudera.com/p/cfm-operator/cfmctl-linux-arm64">https://archive.cloudera.com/p/cfm-operator/cfmctl-linux-arm64</a></li> <li><a href="https://archive.cloudera.com/p/cfm-operator/cfmctl-windows-amd64">https://archive.cloudera.com/p/cfm-operator/cfmctl-windows-amd64</a></li> <li><a href="https://archive.cloudera.com/p/cfm-operator/cfmctl-windows-arm64">https://archive.cloudera.com/p/cfm-operator/cfmctl-windows-arm64</a></li> </ul>
Cloudera Flow Management - Kubernetes Operator Helm chart	<a href="https://archive.cloudera.com/p/cfm-operator/cfm-operator-2.10.0-b134.tgz">https://archive.cloudera.com/p/cfm-operator/cfm-operator-2.10.0-b134.tgz</a>

### Related Tasks

[Installing Cloudera Flow Management - Kubernetes Operator \(internet\)](#)

[Installing Cloudera Flow Management - Kubernetes Operator \(air-gap\)](#)

## Installing Cloudera Flow Management - Kubernetes Operator (internet)

You can install Cloudera Flow Management - Kubernetes Operator after meeting all prerequisites and installing dependencies, either using the cfmctl CLI tool or Helm.

## Before you begin

- Ensure that your Kubernetes environment meets requirements listed in [System requirements](#).
- Your Kubernetes cluster requires internet connectivity to complete these steps. It must be able to reach the Cloudera Docker registry.
- Ensure that you have access to your Cloudera credentials (username and password). Credentials are required to access the Cloudera Archive and Cloudera Docker registry where installation artifacts are hosted.
- Ensure that you have access to a valid Cloudera license.
- Review the [Helm chart reference](#) before installation.

The Helm chart accepts various configuration properties that you can set during installation. Using these properties you can customize your installation.

## Procedure

1. Install cert-manager.

### For OpenShift

Follow the instructions for installing the [cert-manager Operator for RedHat OpenShift](#).

### For Helm

```
helm install cert-manager jetstack/cert-manager \
--version [***CERT MANAGER VERSION***] \
--namespace cert-manager \
--create-namespace \
--set installCRDs=true
```

Replace [\*\*\*CERT MANAGER VERSION\*\*\*] with the certificate manager version you want to install.

**Note:**

For Cloudera Flow Management - Kubernetes Operator, there is no specific version requirement.

2. Create a namespace for the Cloudera Flow Management - Kubernetes Operator if it does not already exist.

```
kubectl create namespace [***OPERATOR NAMESPACE***]
```

Replace [\*\*\*OPERATOR NAMESPACE\*\*\*] with the desired namespace for Cloudera Flow Management - Kubernetes Operator.

For example:

```
$ kubectl create namespace cfm-operator-system
```

3. Create a Kubernetes secret containing your Cloudera credentials.

```
kubectl create secret docker-registry [***SECRET NAME***] \
--namespace [***OPERATOR NAMESPACE***] \
--docker-server container.repository.cloudera.com \
--docker-username [***USERNAME***] \
--docker-password [***PASSWORD***]
```

Replace:

- [\*\*\*SECRET NAME\*\*\*] with the desired Kubernetes secret name.
- [\*\*\*OPERATOR NAMESPACE\*\*\*] with the Cloudera Flow Management - Kubernetes Operator installation namespace.
- [\*\*\*USERNAME\*\*\*] and [\*\*\*PASSWORD\*\*\*] with your internal registry credentials.

4. Install the `cfmctl` CLI tool. While installing the tool is not strictly required for the operation of Cloudera Flow Management - Kubernetes Operator, it makes performing common tasks more convenient. The examples in this documentation make heavy use of the `cfmctl` CLI tool.

The `cfmctl` tool allows you to:

- Manage your environment
  - Check the current state and existence of prerequisites in an environment
  - Install and uninstall the operator
  - Quickstart install NiFi clusters
  - Perform common configuration tasks using flags, with the ability to provide a `helmvalues.yaml` file
  - Install using default image location without the need to provide it manually
- a) Copy the CLI tool version appropriate for your environment to the Cloudera Flow Management - Kubernetes Operator installation directory and run it.
  - b) Make the tool executable.

```
chmod +x [***CFMCTL FILE***]
```

Replace `[***CFMCTL FILE***]` with the name of the executable file that you have downloaded.

5. Install Cloudera Flow Management - Kubernetes Operator.

#### For `cfmctl`

Install Cloudera Flow Management - Kubernetes Operator using the `cfmctl install` command:

```
./cfmctl install --license [***LICENSE***] \
--image-repository "[***IMAGE REPOSITORY***]" \
--image-tag "[***OPERATOR VERSION***]" \
--values [***VALUES.YAML***] \
--namespace [***OPERATOR NAMESPACE***]
```

Replace

- `[***LICENSE***]` with the license file. This flag is mandatory.
- `[***IMAGE REPOSITORY***]` Defaults to “`container.repository.cloudera.com/cloudera/cfm-operator`” unless a Helm values.yaml is provided. This flag is optional.
- `[***OPERATOR VERSION***]` Defaults to “`latest`” unless a Helm values.yaml is provided. This flag is optional.
- `[***VALUES.YAML***]` with a Helm values.yaml file to supply any variables to the underlying Helm chart that is not available through `cfmctl` command flags. This flag is optional.
- `[***OPERATOR NAMESPACE***]` with the desired operator installation namespace. Defaults to “`cfm-operator-system`”.

This command installs the CustomResourceDefinitions and Helm chart for the operator, and starts the operator.

```
$ ./cfmctl install --license ./license.txt --image-repository "container
.repository.cloudera.com/cloudera/cfm-operator" --image-tag "2.8.0-b94"
2024-06-11T21:22:19.678+0200 INFO cli.install cmd/install.go:90 install
ing chart {"namespace": "cfm-operator-system"}
2024-06-11T21:22:23.820+0200 INFO cli.install.helmclient cmd/install.
go:162 creating 1 resource(s)
2024-06-11T21:22:24.601+0200 INFO cli.install.helmclient cmd/install.g
o:162 creating 18 resource(s)
2024-06-11T21:22:26.063+0200 INFO cli.install.helmclient cmd/install.g
o:162 beginning wait for 18 resources with timeout of 10m0s
2024-06-11T21:22:26.697+0200 INFO cli.install.helmclient cmd/install.go:
162 Deployment is not ready: cfm-operator-system/cfm-operator. 0 out of
1 expected pods are ready
```

```
...
2024-06-11T21:24:28.414+0200 INFO cli.install.helmclient cmd/install.go:
162 release installed successfully: cfm-operator/cfm-operator-0.0.0-dev
```

### For Helm

- a. Create your license secret.

```
kubectl create secret generic cfm-operator-license --from-file=license.txt=[***PATH/TO/LICENSE.TXT***] -n [***OPERATOR NAMESPACE***]
```

Replace

- `[***PATH/TO/LICENSE.TXT***]` with the relative path to the license file
- `[***OPERATOR NAMESPACE***]` with the namespace where you install Cloudera Flow Management - Kubernetes Operator

- b. Run Helm install.

```
helm install cfm-operator [***PATH TO OPERATOR HELM CHART***] \
  --create-namespace \
  --namespace [***OPERATOR NAMESPACE***] \
  --set installCRDs=true \
  --set image.repository=[***IMAGE REPOSITORY***] \
  --set image.tag=[***OPERATOR VERSION***] \
  --set licenseSecret=cfm-operator-license
  --set "imagePullSecrets={ [***DOCKER PULL SECRET***] }"
```

Replace

- `[***PATH TO OPERATOR HELM CHART***]` with the path to the downloaded and unpacked Cloudera Flow Management - Kubernetes Operator Helm chart, for example,

```
./cfm-operator-2.10.0-b134.tgz
```

- `[***OPERATOR NAMESPACE***]` with the desired installation namespace, for example,

```
cfm-operator-system
```

- `[***IMAGE REPOSITORY***]` with the Cloudera Flow Management - Kubernetes Operator image repository.

- If you install from the Cloudera Docker Registry, replace it with

```
container.repository.cloudera.com/cloudera/cfm-operator
```

- If you install from a self-hosted private registry, replace it with your internal registry URL.
- `[***OPERATOR VERSION***]` with your desired Cloudera Flow Management - Kubernetes Operator version, for example,

```
2.10.0
```

- c. `[***DOCKER PULL SECRET***]` with the

## 6. Validate your installation.

- a) Check if CustomResourceDefinitions for NiFi were installed or updated:

```
kubectl get crds | grep nifi
```

Expect a similar output:

```
nifiregistries.cfm.cloudera.com 2024-01-25T21:31:28Z
nifis.cfm.cloudera.com 2024-01-25T21:31:29Z
```

b) Check if a Cloudera Flow Management - Kubernetes Operator pod is up and running:

```
kubect1 get pods -n [***OPERATOR NAMESPACE***]
```

Replace [\*\*\*OPERATOR NAMESPACE\*\*\*] with the namespace you created to deploy Cloudera Flow Management - Kubernetes Operator.

Expect a similar output:

NAME	READY	STATUS	RESTARTS	AGE
cfm-operator-545bfb96b-sx4jt	2/2	Running	0	18m

### What to do next

With the operator installed and running, you can create and manage instances of NiFi and NiFi Registry by manipulating the Kubernetes object definitions.

### Related Concepts

[Installation artifacts](#)

### Related Information

[Helm chart reference](#)

## Installing Cloudera Flow Management - Kubernetes Operator (air-gap)

You can install Cloudera Flow Management - Kubernetes Operator after meeting all prerequisites and installing dependencies, either using the cfmc1 CLI tool or Helm.

### About this task

Complete these steps to install Cloudera Flow Management - Kubernetes Operator if your Kubernetes cluster does not have internet access, or if you want to install it from a self-hosted registry. Installing Cloudera Flow Management - Kubernetes Operator installs the applications and resources that enable you to deploy and manage NiFi and NiFi Registry in Kubernetes.

### Before you begin

- Ensure that your Kubernetes environment meets requirements listed in [System requirements](#).
- A self-hosted Docker registry is required. Your registry must be accessible by your Kubernetes cluster.
- Access to docker or equivalent utility that you can use to pull and push images is required. The following steps use docker. Replace commands where necessary.
- Ensure that you have access to your Cloudera credentials (username and password). Credentials are required to access the Cloudera Archive and Cloudera Docker registry where installation artifacts are hosted.
- Ensure that you have access to a valid Cloudera license.
- Review the [Helm chart reference](#) before installation.

The Helm chart accepts various configuration properties that you can set during installation. Using these properties you can customize your installation.

- A machine with Internet connectivity is required. While the Kubernetes cluster does not need internet access, you will need a machine to pull the images from the Cloudera Docker registry.

- Obtain the installation artifacts that are relevant for your installation scenario and appropriate for your environment.



**Note:** Installing the `cfmctl` command line utility is optional. If you do not plan on using it, you do not need to download the binary.

Artifact	Location
Cloudera Flow Management - Kubernetes Operator Docker image	<code>container.repository.cloudera.com/cloudera/cfm-operator:2.10.0-b134</code>
Cloudera Flow Management Tini Docker image	<code>container.repository.cloudera.com/cloudera/cfm-tini:2.10.0-b134</code>
cfmctl binaries	<ul style="list-style-type: none"> <li><a href="https://archive.cloudera.com/p/cfm-operator/cfmctl-darwin-amd64">https://archive.cloudera.com/p/cfm-operator/cfmctl-darwin-amd64</a></li> <li><a href="https://archive.cloudera.com/p/cfm-operator/cfmctl-darwin-arm64">https://archive.cloudera.com/p/cfm-operator/cfmctl-darwin-arm64</a></li> <li><a href="https://archive.cloudera.com/p/cfm-operator/cfmctl-linux-amd64">https://archive.cloudera.com/p/cfm-operator/cfmctl-linux-amd64</a></li> <li><a href="https://archive.cloudera.com/p/cfm-operator/cfmctl-linux-arm64">https://archive.cloudera.com/p/cfm-operator/cfmctl-linux-arm64</a></li> <li><a href="https://archive.cloudera.com/p/cfm-operator/cfmctl-windows-amd64">https://archive.cloudera.com/p/cfm-operator/cfmctl-windows-amd64</a></li> <li><a href="https://archive.cloudera.com/p/cfm-operator/cfmctl-windows-arm64">https://archive.cloudera.com/p/cfm-operator/cfmctl-windows-arm64</a></li> </ul>
Cloudera Flow Management - Kubernetes Operator Helm chart	<a href="https://archive.cloudera.com/p/cfm-operator/cfm-operator-2.10.0-b134.tgz">https://archive.cloudera.com/p/cfm-operator/cfm-operator-2.10.0-b134.tgz</a>

## Procedure

- Copy the installation artifacts to a local registry using the `docker pull`, `docker tag`, and `docker push` commands.

```
docker pull container.repository.cloudera.com/cloudera/cfm-operator:[***OPERATOR VERSION***]
```

```
docker tag container.repository.cloudera.com/cloudera/cfm-operator:[***OPERATOR VERSION***] [***PRIVATE_REGISTRY[:PORT]/PATH/TAG:OPERATOR VERSION***]
```

```
docker push [***PATH TO SELF-HOSTED REGISTRY***]/cfm-operator:[***OPERATOR VERSION***]
```

For example:

```
docker pull container.repository.cloudera.com/cloudera/cfm-operator:2.10.0-b134
```

```
docker tag container.repository.cloudera.com/cloudera/cfm-operator:2.10.0-b134 us-centrall-docker.pkg.dev/nifi/cfm-k8s/cfm-operator:2.10.0-b134
```

```
docker push us-centrall-docker.pkg.dev/nifi/cfm-k8s/cfm-operator:2.10.0-b134
```



**Note:**

If Kubernetes is running on a different architecture than your local machine, you may need to specify a `--platform` option for your `docker pull`.

For more information on pulling, pushing, and tagging Docker images, see the Docker documentation.

2. Create a namespace for the Cloudera Flow Management - Kubernetes Operator if it does not already exist.

```
kubectl create namespace [***OPERATOR NAMESPACE***]
```

Replace `[***OPERATOR NAMESPACE***]` with the desired namespace for Cloudera Flow Management - Kubernetes Operator.

For example:

```
$ kubectl create namespace cfm-operator-system
```

3. Install cert-manager.

#### For OpenShift

Follow the instructions for installing the [cert-manager Operator for RedHat OpenShift](#).

#### For Helm

```
helm install cert-manager jetstack/cert-manager \
--version [***CERT MANAGER VERSION***] \
--namespace cert-manager \
--create-namespace \
--set installCRDs=true
```

Replace `[***CERT MANAGER VERSION***]` with the certificate manager version you want to install.



#### Note:

For Cloudera Flow Management - Kubernetes Operator, there is no specific version requirement.

4. Create a Kubernetes secret containing your Cloudera credentials.

```
kubectl create secret docker-registry [***SECRET NAME***] \
--namespace [***OPERATOR NAMESPACE***] \
--docker-server [***CONTAINER REGISTRY***] \
--docker-username [***USERNAME***] \
--docker-password [***PASSWORD***]
```

Replace:

- `[***SECRET NAME***]` with the desired Kubernetes secret name.
- `[***USERNAME***]` and `[***PASSWORD***]` with your internal registry credentials.
- `[***OPERATOR NAMESPACE***]` with the Cloudera Flow Management - Kubernetes Operator installation namespace.
- `[***CONTAINER REGISTRY***]` with your internal registry URL.

5. Install the `cfmctl` CLI tool. While installing the tool is not strictly required for the operation of Cloudera Flow Management - Kubernetes Operator, it makes performing common tasks more convenient. The examples in this documentation make heavy use of the `cfmctl` CLI tool.

The `cfmctl` tool allows you to:

- Manage your environment
  - Check the current state and existence of prerequisites in an environment
  - Install and uninstall the operator
  - Quickstart install NiFi clusters
  - Perform common configuration tasks using flags, with the ability to provide a `helmvalues.yaml` file
  - Install using default image location without the need to provide it manually
- a) Copy the CLI tool version appropriate for your environment to the Cloudera Flow Management - Kubernetes Operator installation directory and run it.
  - b) Make the tool executable.

```
chmod +x [***CFMCTL FILE***]
```

Replace `[***CFMCTL FILE***]` with the name of the executable file that you have downloaded.

6. Install Cloudera Flow Management - Kubernetes Operator.

#### For `cfmctl`

Install Cloudera Flow Management - Kubernetes Operator using the `cfmctl install` command:

```
./cfmctl install --license [***LICENSE***] \
--image-repository "[***IMAGE REPOSITORY***]" \
--image-tag "[***OPERATOR VERSION***]" \
--values [***VALUES.YAML***] \
--namespace [***OPERATOR NAMESPACE***]
```

Replace

- `[***LICENSE***]` with the license file. This flag is mandatory.
- `[***IMAGE REPOSITORY***]` Defaults to “`container.repository.cloudera.com/cloudera/cfm-operator`” unless a Helm values.yaml is provided. This flag is optional.
- `[***OPERATOR VERSION***]` Defaults to “`latest`” unless a Helm values.yaml is provided. This flag is optional.
- `[***VALUES.YAML***]` with a Helm values.yaml file to supply any variables to the underlying Helm chart that is not available through `cfmctl` command flags. This flag is optional.
- `[***OPERATOR NAMESPACE***]` with the desired operator installation namespace. Defaults to “`cfm-operator-system`”.

This command installs the CustomResourceDefinitions and Helm chart for the operator, and starts the operator.

```
$ ./cfmctl install --license ./license.txt --image-repository "container
.repository.cloudera.com/cloudera/cfm-operator" --image-tag "2.8.0-b94"
2024-06-11T21:22:19.678+0200 INFO cli.install cmd/install.go:90 install
ing chart {"namespace": "cfm-operator-system"}
2024-06-11T21:22:23.820+0200 INFO cli.install.helmclient cmd/install.
go:162 creating 1 resource(s)
2024-06-11T21:22:24.601+0200 INFO cli.install.helmclient cmd/install.g
o:162 creating 18 resource(s)
2024-06-11T21:22:26.063+0200 INFO cli.install.helmclient cmd/install.g
o:162 beginning wait for 18 resources with timeout of 10m0s
2024-06-11T21:22:26.697+0200 INFO cli.install.helmclient cmd/install.go:
162 Deployment is not ready: cfm-operator-system/cfm-operator. 0 out of
1 expected pods are ready
```

```
...
2024-06-11T21:24:28.414+0200 INFO cli.install.helmclient cmd/install.go:
162 release installed successfully: cfm-operator/cfm-operator-0.0.0-dev
```

### For Helm

- a. Create your license secret.

```
kubectl create secret generic cfm-operator-license --from-file=license.txt=[***PATH/TO/LICENSE.TXT***] -n [***OPERATOR NAMESPACE***]
```

Replace

- `[***PATH/TO/LICENSE.TXT***]` with the relative path to the license file
- `[***OPERATOR NAMESPACE***]` with the namespace where you install Cloudera Flow Management - Kubernetes Operator

- b. Run Helm install.

```
helm install cfm-operator [***PATH TO OPERATOR HELM CHART***] \
  --create-namespace \
  --namespace [***OPERATOR NAMESPACE***] \
  --set installCRDs=true \
  --set image.repository=[***IMAGE REPOSITORY***] \
  --set image.tag=[***OPERATOR VERSION***] \
  --set licenseSecret=cfm-operator-license
  --set "imagePullSecrets={ [***DOCKER PULL SECRET***] }"
```

Replace

- `[***PATH TO OPERATOR HELM CHART***]` with the path to the downloaded and unpacked Cloudera Flow Management - Kubernetes Operator Helm chart, for example,

```
./cfm-operator-2.10.0-b134.tgz
```

- `[***OPERATOR NAMESPACE***]` with the desired installation namespace, for example,

```
cfm-operator-system
```

- `[***IMAGE REPOSITORY***]` with the Cloudera Flow Management - Kubernetes Operator image repository.

- If you install from the Cloudera Docker Registry, replace it with

```
container.repository.cloudera.com/cloudera/cfm-operator
```

- If you install from a self-hosted private registry, replace it with your internal registry URL.
- `[***OPERATOR VERSION***]` with your desired Cloudera Flow Management - Kubernetes Operator version, for example,

```
2.10.0
```

- c. `[***DOCKER PULL SECRET***]` with the

## 7. Validate your installation.

- a) Check if CustomResourceDefinitions for NiFi were installed or updated:

```
kubectl get crds | grep nifi
```

Expect a similar output:

```
nifiregistries.cfm.cloudera.com 2024-01-25T21:31:28Z
nifis.cfm.cloudera.com 2024-01-25T21:31:29Z
```

- b) Check if a Cloudera Flow Management - Kubernetes Operator pod is up and running:

```
kubectl get pods -n [***OPERATOR NAMESPACE***]
```

Replace `[***OPERATOR NAMESPACE***]` with the namespace you created to deploy Cloudera Flow Management - Kubernetes Operator.

Expect a similar output:

NAME	READY	STATUS	RESTARTS	AGE
cfm-operator-545bfb9c96b-sx4jt	2/2	Running	0	18m

### What to do next

With the operator installed and running, you can create and manage instances of NiFi and NiFi Registry by manipulating the Kubernetes object definitions.

### Related Concepts

[Installation artifacts](#)

### Related Information

[Docker image pull](#)

[Docker image push](#)

[Docker image tag](#)

[Helm chart reference](#)

## Uninstalling Cloudera Flow Management - Kubernetes Operator

You can uninstall Cloudera Flow Management - Kubernetes Operator using Helm or the cfmctl CLI tool.

### About this task

By default, the uninstall command does not remove data containing resources. If you want to delete data containing resources, use the `--delete` flag with no arguments, which deletes NiFi and NiFi Registry instances in addition to uninstalling the operator and CRDs. Use the `--force` flag if the environment is unresponsive, and neither installation nor uninstallation is possible.

To uninstall Cloudera Flow Management - Kubernetes Operator, run the following command:

#### For cfmctl

```
cfmctl uninstall --namespace [***OPERATOR NAMESPACE***]
```

Replace `[***OPERATOR NAMESPACE***]` with the namespace where you installed the operator.

#### For Helm

```
helm uninstall cfm-operator --namespace [***OPERATOR NAMESPACE***]
```

Replace `[***OPERATOR NAMESPACE***]` with the namespace where you installed Cloudera Flow Management - Kubernetes Operator.