

cloudera[®]

Apache Impala Guide

Important Notice

© 2010-2021 Cloudera, Inc. All rights reserved.

Cloudera, the Cloudera logo, and any other product or service names or slogans contained in this document are trademarks of Cloudera and its suppliers or licensors, and may not be copied, imitated or used, in whole or in part, without the prior written permission of Cloudera or the applicable trademark holder. If this documentation includes code, including but not limited to, code examples, Cloudera makes this available to you under the terms of the Apache License, Version 2.0, including any required notices. A copy of the Apache License Version 2.0, including any notices, is included herein. A copy of the Apache License Version 2.0 can also be found here: <https://opensource.org/licenses/Apache-2.0>

Hadoop and the Hadoop elephant logo are trademarks of the Apache Software Foundation. All other trademarks, registered trademarks, product names and company names or logos mentioned in this document are the property of their respective owners. Reference to any products, services, processes or other information, by trade name, trademark, manufacturer, supplier or otherwise does not constitute or imply endorsement, sponsorship or recommendation thereof by us.

Complying with all applicable copyright laws is the responsibility of the user. Without limiting the rights under copyright, no part of this document may be reproduced, stored in or introduced into a retrieval system, or transmitted in any form or by any means (electronic, mechanical, photocopying, recording, or otherwise), or for any purpose, without the express written permission of Cloudera.

Cloudera may have patents, patent applications, trademarks, copyrights, or other intellectual property rights covering subject matter in this document. Except as expressly provided in any written license agreement from Cloudera, the furnishing of this document does not give you any license to these patents, trademarks copyrights, or other intellectual property. For information about patents covering Cloudera products, see <http://tiny.cloudera.com/patents>.

The information in this document is subject to change without notice. Cloudera shall not be liable for any damages resulting from technical errors or omissions which may be present in this document, or from use of this document.

Cloudera, Inc.

**395 Page Mill Road
Palo Alto, CA 94306
info@cloudera.com
US: 1-888-789-1488
Intl: 1-650-362-0488
www.cloudera.com**

Release Information

Version: Impala 2.7.x / CDH 5.9.x
Date: February 3, 2021

Table of Contents

Introducing Apache Impala.....	17
Impala Benefits.....	17
How Impala Works with CDH.....	17
Primary Impala Features.....	18
Impala Concepts and Architecture.....	19
Components of the Impala Server.....	19
<i>The Impala Daemon.....</i>	<i>19</i>
<i>The Impala Statestore.....</i>	<i>19</i>
<i>The Impala Catalog Service.....</i>	<i>20</i>
Developing Impala Applications.....	21
<i>Overview of the Impala SQL Dialect.....</i>	<i>21</i>
<i>Overview of Impala Programming Interfaces.....</i>	<i>22</i>
How Impala Fits Into the Hadoop Ecosystem.....	22
<i>How Impala Works with Hive.....</i>	<i>22</i>
<i>Overview of Impala Metadata and the Metastore.....</i>	<i>23</i>
<i>How Impala Uses HDFS.....</i>	<i>23</i>
<i>How Impala Uses HBase.....</i>	<i>23</i>
Planning for Impala Deployment.....	24
Impala Requirements.....	24
<i>Product Compatibility Matrix.....</i>	<i>24</i>
<i>Supported Operating Systems.....</i>	<i>24</i>
<i>Hive Metastore and Related Configuration.....</i>	<i>24</i>
<i>Java Dependencies.....</i>	<i>25</i>
<i>Networking Configuration Requirements.....</i>	<i>25</i>
<i>Hardware Requirements.....</i>	<i>25</i>
<i>User Account Requirements.....</i>	<i>26</i>
Guidelines for Designing Impala Schemas.....	26
Installing Impala.....	29
What is Included in an Impala Installation.....	29
Installing Impala with Cloudera Manager.....	29
Installing Impala without Cloudera Manager.....	30

Managing Impala.....32

Post-Installation Configuration for Impala.....32

Configuring Impala to Work with ODBC.....33

Downloading the ODBC Driver.....34

Configuring the ODBC Port.....34

Example of Setting Up an ODBC Application for Impala.....34

Notes about JDBC and ODBC Interaction with Impala SQL Features.....35

Configuring Impala to Work with JDBC.....36

Configuring the JDBC Port.....36

Choosing the JDBC Driver.....36

Enabling Impala JDBC Support on Client Systems.....36

Establishing JDBC Connections.....37

Notes about JDBC and ODBC Interaction with Impala SQL Features.....38

Kudu Considerations for DML Statements.....39

Upgrading Impala.....40

Upgrading Impala through Cloudera Manager - Parcels.....40

Upgrading Impala through Cloudera Manager - Packages.....41

Upgrading Impala without Cloudera Manager.....42

Starting Impala.....44

Starting Impala through Cloudera Manager.....44

Starting Impala from the Command Line.....44

Modifying Impala Startup Options.....45

Configuring Impala Startup Options through Cloudera Manager.....45

Configuring Impala Startup Options through the Command Line.....45

Checking the Values of Impala Configuration Options.....48

Startup Options for impalad Daemon.....48

Startup Options for statelord Daemon.....48

Startup Options for catalogd Daemon.....48

Impala Tutorials.....49

Tutorials for Getting Started.....49

Explore a New Impala Instance.....49

Load CSV Data from Local Files.....54

Point an Impala Table at Existing Data Files.....55

Describe the Impala Table.....57

Query the Impala Table.....57

Data Loading and Querying Examples.....58

Advanced Tutorials.....60

<i>Attaching an External Partitioned Table to an HDFS Directory Structure</i>	60
<i>Switching Back and Forth Between Impala and Hive</i>	62
<i>Cross Joins and Cartesian Products with the CROSS JOIN Operator</i>	63
<i>Dealing with Parquet Files with Unknown Schema</i>	64

Impala Administration.....77

<i>Admission Control and Query Queuing</i>	77
<i>Overview of Impala Admission Control</i>	78
<i>Concurrent Queries and Admission Control</i>	78
<i>Memory Limits and Admission Control</i>	78
<i>How Impala Admission Control Relates to Other Resource Management Tools</i>	79
<i>How Impala Schedules and Enforces Limits on Concurrent Queries</i>	79
<i>How Admission Control works with Impala Clients (JDBC, ODBC, HiveServer2)</i>	80
<i>SQL and Schema Considerations for Admission Control</i>	80
<i>Configuring Admission Control</i>	80
<i>Guidelines for Using Admission Control</i>	85
<i>Resource Management for Impala</i>	85
<i>How Resource Limits Are Enforced</i>	85
<i>impala-shell Query Options for Resource Management</i>	86
<i>Limitations of Resource Management for Impala</i>	86
<i>How to Configure Resource Management for Impala</i>	86
<i>Creating Static Service Pools</i>	86
<i>Using Admission Control</i>	87
<i>Setting Per-query Memory Limits</i>	87
<i>Creating Dynamic Resource Pools</i>	88
<i>Impala Resource Management Example</i>	90
<i>Setting Timeout Periods for Daemons, Queries, and Sessions</i>	91
<i>Increasing the Statestore Timeout</i>	92
<i>Setting the Idle Query and Idle Session Timeouts for impalad</i>	92
<i>Setting Timeout and Retries for Thrift Connections to the Backend Client</i>	93
<i>Cancelling a Query</i>	93
<i>Using Impala through a Proxy for High Availability</i>	93
<i>Overview of Proxy Usage and Load Balancing for Impala</i>	93
<i>Choosing the Load-Balancing Algorithm</i>	94
<i>Special Proxy Considerations for Clusters Using Kerberos</i>	95
<i>Example of Configuring HAProxy Load Balancer for Impala</i>	96
<i>Managing Disk Space for Impala Data</i>	98

Impala Security.....100

<i>Security Guidelines for Impala</i>	100
<i>Securing Impala Data and Log Files</i>	101
<i>Installation Considerations for Impala Security</i>	102

Securing the Hive Metastore Database.....	102
Securing the Impala Web User Interface.....	102
Configuring TLS/SSL for Impala.....	103
<i>Using Cloudera Manager.....</i>	103
<i>Using the Command Line.....</i>	104
<i>Using TLS/SSL with Business Intelligence Tools.....</i>	105
Enabling Sentry Authorization for Impala.....	105
<i>The Sentry Privilege Model.....</i>	105
<i>Starting the impalad Daemon with Sentry Authorization Enabled.....</i>	106
<i>Using Impala with the Sentry Service (CDH 5.1 or higher only).....</i>	107
<i>Using Impala with the Sentry Policy File.....</i>	107
Setting Up Schema Objects for a Secure Impala Deployment.....	112
<i>Privilege Model and Object Hierarchy.....</i>	112
<i>Debugging Failed Sentry Authorization Requests.....</i>	115
<i>Managing Sentry for Impala through Cloudera Manager.....</i>	115
<i>The DEFAULT Database in a Secure Deployment.....</i>	116
Impala Authentication.....	116
<i>Enabling Kerberos Authentication for Impala.....</i>	116
<i>Enabling LDAP Authentication for Impala.....</i>	119
<i>Using Multiple Authentication Methods with Impala.....</i>	122
<i>Configuring Impala Delegation for Hue and BI Tools.....</i>	122
Auditing Impala Operations.....	123
<i>Durability and Performance Considerations for Impala Auditing.....</i>	123
<i>Format of the Audit Log Files.....</i>	123
<i>Which Operations Are Audited.....</i>	124
<i>Reviewing the Audit Logs.....</i>	124
Viewing Lineage Information for Impala Data.....	124
Impala SQL Language Reference.....	126
Comments.....	126
Data Types.....	126
<i>ARRAY Complex Type (CDH 5.5 or higher only).....</i>	127
<i>BIGINT Data Type.....</i>	130
<i>BOOLEAN Data Type.....</i>	131
<i>CHAR Data Type (CDH 5.2 or higher only).....</i>	132
<i>DECIMAL Data Type (CDH 5.1 or higher only).....</i>	135
<i>DOUBLE Data Type.....</i>	143
<i>FLOAT Data Type.....</i>	144
<i>INT Data Type.....</i>	145
<i>MAP Complex Type (CDH 5.5 or higher only).....</i>	146
<i>REAL Data Type.....</i>	149
<i>SMALLINT Data Type.....</i>	150
<i>STRING Data Type.....</i>	151

<i>STRUCT Complex Type (CDH 5.5 or higher only)</i>	153
<i>TIMESTAMP Data Type</i>	158
<i>TINYINT Data Type</i>	164
<i>VARCHAR Data Type (CDH 5.2 or higher only)</i>	165
<i>Complex Types (CDH 5.5 or higher only)</i>	167
Literals.....	195
<i>Numeric Literals</i>	195
<i>String Literals</i>	196
<i>Boolean Literals</i>	197
<i>Timestamp Literals</i>	197
NULL.....	198
SQL Operators.....	199
<i>Arithmetic Operators</i>	199
<i>BETWEEN Operator</i>	201
<i>Comparison Operators</i>	202
<i>EXISTS Operator</i>	203
<i>ILIKE Operator</i>	206
<i>IN Operator</i>	207
<i>IREGEXP Operator</i>	210
<i>IS DISTINCT FROM Operator</i>	211
<i>IS NULL Operator</i>	212
<i>LIKE Operator</i>	213
<i>Logical Operators</i>	214
<i>REGEXP Operator</i>	216
<i>RLIKE Operator</i>	217
Impala Schema Objects and Object Names.....	218
<i>Overview of Impala Aliases</i>	219
<i>Overview of Impala Databases</i>	219
<i>Overview of Impala Functions</i>	220
<i>Overview of Impala Identifiers</i>	221
<i>Overview of Impala Tables</i>	222
<i>Overview of Impala Views</i>	224
Impala SQL Statements.....	228
<i>DDL Statements</i>	228
<i>DML Statements</i>	229
<i>ALTER TABLE Statement</i>	230
<i>ALTER VIEW Statement</i>	240
<i>COMPUTE STATS Statement</i>	241
<i>CREATE DATABASE Statement</i>	246
<i>CREATE FUNCTION Statement</i>	248
<i>CREATE ROLE Statement (CDH 5.2 or higher only)</i>	253
<i>CREATE TABLE Statement</i>	254
<i>CREATE VIEW Statement</i>	263
<i>DESCRIBE Statement</i>	264

<i>DROP DATABASE Statement</i>	273
<i>DROP FUNCTION Statement</i>	275
<i>DROP ROLE Statement (CDH 5.2 or higher only)</i>	277
<i>DROP STATS Statement</i>	277
<i>DROP TABLE Statement</i>	280
<i>DROP VIEW Statement</i>	282
<i>EXPLAIN Statement</i>	283
<i>GRANT Statement (CDH 5.2 or higher only)</i>	285
<i>INSERT Statement</i>	286
<i>INVALIDATE METADATA Statement</i>	294
<i>LOAD DATA Statement</i>	297
<i>REFRESH Statement</i>	300
<i>REVOKE Statement (CDH 5.2 or higher only)</i>	304
<i>SELECT Statement</i>	304
<i>SET Statement</i>	329
<i>SHOW Statement</i>	356
<i>TRUNCATE TABLE Statement (CDH 5.5 or higher only)</i>	370
<i>USE Statement</i>	372
Impala Built-In Functions	373
<i>Impala Mathematical Functions</i>	374
<i>Impala Bit Functions</i>	386
<i>Impala Type Conversion Functions</i>	395
<i>Impala Date and Time Functions</i>	398
<i>Impala Conditional Functions</i>	427
<i>Impala String Functions</i>	430
<i>Impala Miscellaneous Functions</i>	442
<i>Impala Aggregate Functions</i>	443
<i>Impala Analytic Functions</i>	470
<i>Impala User-Defined Functions (UDFs)</i>	487
SQL Differences Between Impala and Hive	502
<i>HiveQL Features not Available in Impala</i>	503
<i>Semantic Differences Between Impala and HiveQL Features</i>	504
Porting SQL from Other Database Systems to Impala	505
<i>Porting DDL and DML Statements</i>	505
<i>Porting Data Types from Other Database Systems</i>	505
<i>SQL Statements to Remove or Adapt</i>	508
<i>SQL Constructs to Double-check</i>	509
<i>Next Porting Steps after Verifying Syntax and Semantics</i>	510
Using the Impala Shell (impala-shell Command)	511
<i>impala-shell Configuration Options</i>	511
<i>Summary of impala-shell Configuration Options</i>	512
<i>impala-shell Configuration File</i>	514
<i>Connecting to impalad through impala-shell</i>	515

Running Commands and SQL Statements in impala-shell.....	517
impala-shell Command Reference.....	520

Tuning Impala for Performance.....523

Impala Performance Guidelines and Best Practices.....	523
Performance Considerations for Join Queries.....	526
<i>How Joins Are Processed when Statistics Are Unavailable.....</i>	<i>527</i>
<i>Overriding Join Reordering with STRAIGHT_JOIN.....</i>	<i>527</i>
<i>Examples of Join Order Optimization.....</i>	<i>528</i>
Table and Column Statistics.....	533
<i>Overview of Table Statistics.....</i>	<i>533</i>
<i>Overview of Column Statistics.....</i>	<i>534</i>
<i>How Table and Column Statistics Work for Partitioned Tables.....</i>	<i>535</i>
<i>Overview of Incremental Statistics.....</i>	<i>537</i>
<i>Generating Table and Column Statistics (COMPUTE STATS Statement).....</i>	<i>538</i>
<i>Detecting Missing Statistics.....</i>	<i>538</i>
<i>Keeping Statistics Up to Date.....</i>	<i>540</i>
<i>Setting the NUMROWS Value Manually through ALTER TABLE.....</i>	<i>540</i>
<i>Setting Column Stats Manually through ALTER TABLE.....</i>	<i>541</i>
<i>Examples of Using Table and Column Statistics with Impala.....</i>	<i>541</i>
Benchmarking Impala Queries.....	544
Controlling Impala Resource Usage.....	545
Runtime Filtering for Impala Queries.....	545
<i>Background Information for Runtime Filtering.....</i>	<i>545</i>
<i>Runtime Filtering Internals.....</i>	<i>546</i>
<i>File Format Considerations for Runtime Filtering.....</i>	<i>547</i>
<i>Wait Intervals for Runtime Filters.....</i>	<i>547</i>
<i>Query Options for Runtime Filtering.....</i>	<i>547</i>
<i>Runtime Filtering and Query Plans.....</i>	<i>548</i>
<i>Examples of Queries that Benefit from Runtime Filtering.....</i>	<i>548</i>
<i>Tuning and Troubleshooting Queries that Use Runtime Filtering.....</i>	<i>549</i>
<i>Limitations and Restrictions for Runtime Filtering.....</i>	<i>550</i>
Using HDFS Caching with Impala (CDH 5.1 or higher only).....	550
<i>Overview of HDFS Caching for Impala.....</i>	<i>550</i>
<i>Setting Up HDFS Caching for Impala.....</i>	<i>551</i>
<i>Enabling HDFS Caching for Impala Tables and Partitions.....</i>	<i>551</i>
<i>Loading and Removing Data with HDFS Caching Enabled.....</i>	<i>552</i>
<i>Administration for HDFS Caching with Impala.....</i>	<i>553</i>
<i>Performance Considerations for HDFS Caching with Impala.....</i>	<i>554</i>
Testing Impala Performance.....	555
Understanding Impala Query Performance - EXPLAIN Plans and Query Profiles.....	556
<i>Using the EXPLAIN Plan for Performance Tuning.....</i>	<i>557</i>
<i>Using the SUMMARY Report for Performance Tuning.....</i>	<i>557</i>

<i>Using the Query Profile for Performance Tuning</i>	558
Detecting and Correcting HDFS Block Skew Conditions.....	559

Scalability Considerations for Impala.....561

Impact of Many Tables or Partitions on Impala Catalog Performance and Memory Usage.....	561
Scalability Considerations for the Impala Statestore.....	561
SQL Operations that Spill to Disk.....	562
Limits on Query Size and Complexity.....	566
Scalability Considerations for Impala I/O.....	566
Scalability Considerations for Table Layout.....	566
Kerberos-Related Network Overhead for Large Clusters.....	567
Avoiding CPU Hotspots for HDFS Cached Data.....	567

Partitioning for Impala Tables.....568

When to Use Partitioned Tables.....	568
SQL Statements for Partitioned Tables.....	568
Static and Dynamic Partitioning Clauses.....	569
Refreshing a Single Partition.....	569
Permissions for Partition Subdirectories.....	570
Partition Pruning for Queries.....	570
<i>Checking if Partition Pruning Happens for a Query</i>	570
<i>What SQL Constructs Work with Partition Pruning</i>	571
<i>Dynamic Partition Pruning</i>	571
Partition Key Columns.....	573
Setting Different File Formats for Partitions.....	573
Managing Partitions.....	574

How Impala Works with Hadoop File Formats.....575

Choosing the File Format for a Table.....	576
Using Text Data Files with Impala Tables.....	576
<i>Query Performance for Impala Text Tables</i>	577
<i>Creating Text Tables</i>	577
<i>Data Files for Text Tables</i>	578
<i>Loading Data into Impala Text Tables</i>	579
<i>Using LZO-Compressed Text Files</i>	580
<i>Using gzip, bzip2, or Snappy-Compressed Text Files</i>	583
Using the Parquet File Format with Impala Tables.....	584
<i>Creating Parquet Tables in Impala</i>	584
<i>Loading Data into Parquet Tables</i>	585
<i>Query Performance for Impala Parquet Tables</i>	587

<i>Snappy and GZip Compression for Parquet Data Files.....</i>	<i>588</i>
<i>Parquet Tables for Impala Complex Types.....</i>	<i>590</i>
<i>Exchanging Parquet Data Files with Other Hadoop Components.....</i>	<i>591</i>
<i>How Parquet Data Files Are Organized.....</i>	<i>593</i>
<i>Compacting Data Files for Parquet Tables.....</i>	<i>594</i>
<i>Schema Evolution for Parquet Tables.....</i>	<i>595</i>
<i>Data Type Considerations for Parquet Tables.....</i>	<i>597</i>
<i>Using the Avro File Format with Impala Tables.....</i>	<i>597</i>
<i>Creating Avro Tables.....</i>	<i>597</i>
<i>Using a Hive-Created Avro Table in Impala.....</i>	<i>599</i>
<i>Specifying the Avro Schema through JSON.....</i>	<i>600</i>
<i>Loading Data into an Avro Table.....</i>	<i>600</i>
<i>Enabling Compression for Avro Tables.....</i>	<i>600</i>
<i>How Impala Handles Avro Schema Evolution.....</i>	<i>600</i>
<i>Data Type Considerations for Avro Tables.....</i>	<i>601</i>
<i>Query Performance for Impala Avro Tables.....</i>	<i>602</i>
<i>Using the RCFile File Format with Impala Tables.....</i>	<i>602</i>
<i>Creating RCFile Tables and Loading Data.....</i>	<i>603</i>
<i>Enabling Compression for RCFile Tables.....</i>	<i>603</i>
<i>Query Performance for Impala RCFile Tables.....</i>	<i>604</i>
<i>Using the SequenceFile File Format with Impala Tables.....</i>	<i>605</i>
<i>Creating SequenceFile Tables and Loading Data.....</i>	<i>605</i>
<i>Enabling Compression for SequenceFile Tables.....</i>	<i>606</i>
<i>Query Performance for Impala SequenceFile Tables.....</i>	<i>606</i>

Using Impala to Query HBase Tables.....608

<i>Overview of Using HBase with Impala.....</i>	<i>608</i>
<i>Configuring HBase for Use with Impala.....</i>	<i>608</i>
<i>Supported Data Types for HBase Columns.....</i>	<i>609</i>
<i>Performance Considerations for the Impala-HBase Integration.....</i>	<i>609</i>
<i>Use Cases for Querying HBase through Impala.....</i>	<i>613</i>
<i>Loading Data into an HBase Table.....</i>	<i>613</i>
<i>Limitations and Restrictions of the Impala and HBase Integration.....</i>	<i>613</i>
<i>Examples of Querying HBase Tables from Impala.....</i>	<i>614</i>

Using Impala with the Amazon S3 Filesystem.....617

<i>How Impala SQL Statements Work with S3.....</i>	<i>617</i>
<i>Specifying Impala Credentials to Access Data in S3.....</i>	<i>618</i>
<i>Loading Data into S3 for Impala Queries.....</i>	<i>618</i>
<i>Using Impala DML Statements for S3 Data.....</i>	<i>618</i>
<i>Manually Loading Data into Impala Tables on S3.....</i>	<i>618</i>
<i>Creating Impala Databases, Tables, and Partitions for Data Stored on S3.....</i>	<i>619</i>

Internal and External Tables Located on S3.....	620
Running and Tuning Impala Queries for Data Stored on S3.....	622
<i>Understanding and Tuning Impala Query Performance for S3 Data.....</i>	<i>622</i>
Restrictions on Impala Support for S3.....	623
Best Practices for Using Impala with S3.....	623

Using Impala with Isilon Storage.....625

Required Configurations.....	625
------------------------------	-----

Using Impala Logging.....627

Locations and Names of Impala Log Files.....	627
Managing Impala Logs through Cloudera Manager or Manually.....	628
Rotating Impala Logs.....	628
Reviewing Impala Logs.....	628
Understanding Impala Log Contents.....	629
Setting Logging Levels.....	629
Redacting Sensitive Information from Impala Log Files.....	630

Troubleshooting Impala.....631

Troubleshooting Impala SQL Syntax Issues.....	631
Troubleshooting I/O Capacity Problems.....	631
Impala Troubleshooting Quick Reference.....	632
Impala Web User Interface for Debugging.....	633
<i>Debug Web UI for impalad.....</i>	<i>634</i>
Breakpad Minidumps for Impala (CDH 5.8 or higher only).....	636
<i>Enabling or Disabling Minidump Generation.....</i>	<i>636</i>
<i>Specifying the Location for Minidump Files.....</i>	<i>636</i>
<i>Controlling the Number of Minidump Files.....</i>	<i>636</i>
<i>Detecting Crash Events.....</i>	<i>636</i>
<i>Using the Minidump Files for Problem Resolution.....</i>	<i>636</i>
<i>Demonstration of Breakpad Feature.....</i>	<i>637</i>

Ports Used by Impala.....639

Impala Reserved Words.....641

List of Current Reserved Words.....	641
Planning for Future Reserved Words.....	643

Impala Frequently Asked Questions.....646

Transition to Apache Governance.....646

Trying Impala.....646

Impala System Requirements.....647

Supported and Unsupported Functionality In Impala.....648

How do I?.....649

Impala Performance.....650

Impala Use Cases.....652

Questions about Impala And Hive.....653

Impala Availability.....654

Impala Internals.....654

SQL.....657

Partitioned Tables.....658

HBase.....658

Impala Release Notes.....660

Impala Release Notes.....660

New Features in Apache Impala.....660

New Features in Impala 2.7.x / CDH 5.9.x.....660

New Features in Impala 2.6.x / CDH 5.8.x.....661

New Features in Impala 2.5.x / CDH 5.7.x.....663

New Features in Impala 2.4.x / CDH 5.6.x.....666

New Features in Impala 2.3.x / CDH 5.5.x.....666

New Features in Impala 2.2.x for CDH 5.4.3 and 5.4.4.....668

New Features in Impala 2.2.x / CDH 5.4.x.....669

New Features in Impala 2.1.8 / CDH 5.3.10.....671

New Features in Impala 2.1.7 / CDH 5.3.9.....671

New Features in Impala 2.1.6 / CDH 5.3.8.....671

New Features in Impala 2.1.5 / CDH 5.3.6.....671

New Features in Impala 2.1.4 / CDH 5.3.4.....671

New Features in Impala 2.1.3 / CDH 5.3.3.....671

New Features in Impala 2.1.2 / CDH 5.3.2.....671

New Features in Impala 2.1.1 / CDH 5.3.1.....672

New Features in Impala 2.1.0 / CDH 5.3.0.....672

New Features in Impala 2.0.5 / CDH 5.2.6.....672

New Features in Impala 2.0.4 / CDH 5.2.5.....672

New Features in Impala 2.0.3 / CDH 5.2.4.....672

New Features in Impala 2.0.2 / CDH 5.2.3.....672

New Features in Impala 2.0.1 / CDH 5.2.1.....673

New Features in Impala 2.0.0 / CDH 5.2.0.....673

New Features in Impala 1.4.4 / CDH 5.1.5.....675

<i>New Features in Impala 1.4.3 / CDH 5.1.4</i>	675
<i>New Features in Impala 1.4.2 / CDH 5.1.3</i>	675
<i>New Features in Impala 1.4.1 / CDH 5.1.2</i>	675
<i>New Features in Impala 1.4.0 / CDH 5.1.0</i>	675
<i>New Features in Impala 1.3.3 / CDH 5.0.5</i>	677
<i>New Features in Impala 1.3.2 / CDH 5.0.4</i>	677
<i>New Features in Impala 1.3.1 / CDH 5.0.3</i>	677
<i>New Features in Impala 1.3.0 / CDH 5.0.0</i>	678
<i>New Features in Impala 1.2.4</i>	678
<i>New Features in Impala 1.2.3</i>	679
<i>New Features in Impala 1.2.2</i>	679
<i>New Features in Impala 1.2.1</i>	680
<i>New Features in Impala 1.2.0 (Beta)</i>	682
<i>New Features in Impala 1.1.1</i>	683
<i>New Features in Impala 1.1</i>	683
<i>New Features in Impala 1.0.1</i>	684
<i>New Features in Impala 1.0</i>	685
<i>New Features in Version 0.7 of the Impala Beta Release</i>	685
<i>New Features in Version 0.6 of the Impala Beta Release</i>	685
<i>New Features in Version 0.5 of the Impala Beta Release</i>	685
<i>New Features in Version 0.4 of the Impala Beta Release</i>	685
<i>New Features in Version 0.3 of the Impala Beta Release</i>	686
<i>New Features in Version 0.2 of the Impala Beta Release</i>	686
<i>Incompatible Changes and Limitations in Apache Impala</i>	686
<i>Incompatible Changes Introduced in Impala for CDH 5.9.x / Impala 2.7.x</i>	686
<i>Incompatible Changes Introduced in Impala for CDH 5.8.x / Impala 2.6.x</i>	686
<i>Incompatible Changes Introduced in Impala for CDH 5.7.x / Impala 2.5.x</i>	687
<i>Incompatible Changes Introduced in Impala for CDH 5.6.x / Impala 2.4.x</i>	688
<i>Incompatible Changes Introduced in Impala for CDH 5.5.x / Impala 2.3.x</i>	688
<i>Incompatible Changes Introduced in Impala for CDH 5.4.x</i>	689
<i>Incompatible Changes Introduced in Impala for CDH 5.3.x</i>	689
<i>Incompatible Changes Introduced in Impala 2.0.5 / CDH 5.2.6</i>	689
<i>Incompatible Changes Introduced in Impala 2.0.4 / CDH 5.2.5</i>	690
<i>Incompatible Changes Introduced in Impala 2.0.3 / CDH 5.2.4</i>	690
<i>Incompatible Changes Introduced in Impala 2.0.2 / CDH 5.2.3</i>	690
<i>Incompatible Changes Introduced in Impala 2.0.1 / CDH 5.2.1</i>	690
<i>Incompatible Changes Introduced in Impala 2.0.0 / CDH 5.2.0</i>	690
<i>Incompatible Changes Introduced in Impala 1.4.4 / CDH 5.1.5</i>	692
<i>Incompatible Changes Introduced in Impala 1.4.3 / CDH 5.1.4</i>	692
<i>Incompatible Changes Introduced in Impala 1.4.2 / CDH 5.1.3</i>	692
<i>Incompatible Changes Introduced in Impala 1.4.1 / CDH 5.1.2</i>	692
<i>Incompatible Changes Introduced in Impala 1.4.0 / CDH 5.1.0</i>	692
<i>Incompatible Changes Introduced in Impala 1.3.3 / CDH 5.0.5</i>	693
<i>Incompatible Changes Introduced in Impala 1.3.2 / CDH 5.0.4</i>	693
<i>Incompatible Changes Introduced in Impala 1.3.1 / CDH 5.0.3</i>	693

<i>Incompatible Changes Introduced in Impala 1.3.0 / CDH 5.0.0</i>	693
<i>Incompatible Changes Introduced in Impala 1.2.4</i>	694
<i>Incompatible Changes Introduced in Impala 1.2.3</i>	694
<i>Incompatible Changes Introduced in Impala 1.2.2</i>	694
<i>Incompatible Changes Introduced in Impala 1.2.1</i>	695
<i>Incompatible Changes Introduced in Impala 1.2.0 (Beta)</i>	695
<i>Incompatible Changes Introduced in Impala 1.1.1</i>	696
<i>Incompatible Change Introduced in Impala 1.1</i>	696
<i>Incompatible Changes Introduced in Impala 1.0</i>	696
<i>Incompatible Change Introduced in Version 0.7 of the Impala Beta Release</i>	696
<i>Incompatible Change Introduced in Version 0.6 of the Impala Beta Release</i>	697
<i>Incompatible Change Introduced in Version 0.4 of the Impala Beta Release</i>	697
<i>Incompatible Change Introduced in Version 0.3 of the Impala Beta Release</i>	697
<i>Known Issues and Workarounds in Impala</i>	697
<i>Impala Known Issues: Crashes and Hangs</i>	697
<i>Impala Known Issues: Performance</i>	698
<i>Impala Known Issues: Usability</i>	698
<i>Impala Known Issues: JDBC and ODBC Drivers</i>	698
<i>Impala Known Issues: Security</i>	699
<i>Impala Known Issues: Resources</i>	699
<i>Impala Known Issues: Correctness</i>	701
<i>Impala Known Issues: Metadata</i>	705
<i>Impala Known Issues: Interoperability</i>	705
<i>Impala Known Issues: Limitations</i>	707
<i>Impala Known Issues: Miscellaneous / Older Issues</i>	707
<i>Fixed Issues in Apache Impala</i>	708
<i>Issues Fixed in Impala for CDH 5.9.0</i>	708
<i>Issues Fixed in Impala for CDH 5.8.2</i>	711
<i>Issues Fixed in Impala for CDH 5.8.0</i>	711
<i>Issues Fixed in Impala for CDH 5.7.4</i>	713
<i>Issues Fixed in Impala for CDH 5.7.2</i>	713
<i>Issues Fixed in Impala for CDH 5.7.1</i>	713
<i>Issues Fixed in Impala for CDH 5.7.0</i>	714
<i>Issues Fixed in Impala for CDH 5.6.1</i>	717
<i>Issues Fixed in Impala for CDH 5.6.0</i>	717
<i>Issues Fixed in Impala for CDH 5.5.4</i>	717
<i>Issues Fixed in Impala for CDH 5.5.2</i>	719
<i>Issues Fixed in Impala for CDH 5.5.1</i>	721
<i>Issues Fixed in Impala for CDH 5.5.0</i>	721
<i>Issues Fixed in Impala for CDH 5.4.10</i>	721
<i>Issues Fixed in Impala for CDH 5.4.9</i>	722
<i>Issues Fixed in Impala for CDH 5.4.8</i>	723
<i>Issues Fixed in Impala for CDH 5.4.7</i>	724
<i>Issues Fixed in Impala for CDH 5.4.5</i>	726
<i>Issues Fixed in Impala for CDH 5.4.3</i>	727

<i>Issues Fixed in Impala for CDH 5.4.1</i>	727
<i>Issues Fixed in the 2.2.0 Release / CDH 5.4.0</i>	727
<i>Issues Fixed in Impala for CDH 5.3.10</i>	729
<i>Issues Fixed in the 2.1.7 Release / CDH 5.3.9</i>	729
<i>Issues Fixed in the 2.1.6 Release / CDH 5.3.8</i>	730
<i>Issues Fixed in the 2.1.5 Release / CDH 5.3.6</i>	731
<i>Issues Fixed in the 2.1.4 Release / CDH 5.3.4</i>	731
<i>Issues Fixed in the 2.1.3 Release / CDH 5.3.3</i>	732
<i>Issues Fixed in the 2.1.2 Release / CDH 5.3.2</i>	733
<i>Issues Fixed in the 2.1.1 Release / CDH 5.3.1</i>	733
<i>Issues Fixed in the 2.1.0 Release / CDH 5.3.0</i>	734
<i>Issues Fixed in the 2.0.5 Release / CDH 5.2.6</i>	734
<i>Issues Fixed in the 2.0.4 Release / CDH 5.2.5</i>	734
<i>Issues Fixed in the 2.0.3 Release / CDH 5.2.4</i>	735
<i>Issues Fixed in the 2.0.2 Release / CDH 5.2.3</i>	735
<i>Issues Fixed in the 2.0.1 Release / CDH 5.2.1</i>	736
<i>Issues Fixed in the 2.0.0 Release / CDH 5.2.0</i>	736
<i>Issues Fixed in the 1.4.4 Release / CDH 5.1.5</i>	738
<i>Issues Fixed in the 1.4.3 Release / CDH 5.1.4</i>	738
<i>Issues Fixed in the 1.4.2 Release / CDH 5.1.3</i>	738
<i>Issues Fixed in the 1.4.1 Release / CDH 5.1.2</i>	738
<i>Issues Fixed in the 1.4.0 Release / CDH 5.1.0</i>	739
<i>Issues Fixed in the 1.3.3 Release / CDH 5.0.5</i>	741
<i>Issues Fixed in the 1.3.2 Release / CDH 5.0.4</i>	741
<i>Issues Fixed in the 1.3.1 Release / CDH 5.0.3</i>	741
<i>Issues Fixed in the 1.3.0 Release / CDH 5.0.0</i>	743
<i>Issues Fixed in the 1.2.4 Release</i>	744
<i>Issues Fixed in the 1.2.3 Release</i>	746
<i>Issues Fixed in the 1.2.2 Release</i>	746
<i>Issues Fixed in the 1.2.1 Release</i>	747
<i>Issues Fixed in the 1.2.0 Beta Release</i>	747
<i>Issues Fixed in the 1.1.1 Release</i>	747
<i>Issues Fixed in the 1.1.0 Release</i>	748
<i>Issues Fixed in the 1.0.1 Release</i>	749
<i>Issues Fixed in the 1.0 GA Release</i>	750
<i>Issues Fixed in Version 0.7 of the Beta Release</i>	753
<i>Issues Fixed in Version 0.6 of the Beta Release</i>	754
<i>Issues Fixed in Version 0.5 of the Beta Release</i>	755
<i>Issues Fixed in Version 0.4 of the Beta Release</i>	755
<i>Issues Fixed in Version 0.3 of the Beta Release</i>	756
<i>Issues Fixed in Version 0.2 of the Beta Release</i>	756

Appendix: Apache License, Version 2.0.....758

Introducing Apache Impala

Impala provides fast, interactive SQL queries directly on your Apache Hadoop data stored in HDFS, HBase, or the Amazon Simple Storage Service (S3). In addition to using the same unified storage platform, Impala also uses the same metadata, SQL syntax (Hive SQL), ODBC driver, and user interface (Impala query UI in Hue) as Apache Hive. This provides a familiar and unified platform for real-time or batch-oriented queries.

Impala is an addition to tools available for querying big data. Impala does not replace the batch processing frameworks built on MapReduce such as Hive. Hive and other frameworks built on MapReduce are best suited for long running batch jobs, such as those involving batch processing of Extract, Transform, and Load (ETL) type jobs.



Note: Impala graduated from the Apache Incubator on November 15, 2017. In places where the documentation formerly referred to “Cloudera Impala”, now the official name is “Apache Impala”.


Impala Benefits

Impala provides:

- Familiar SQL interface that data scientists and analysts already know.
- Ability to query high volumes of data (“big data”) in Apache Hadoop.
- Distributed queries in a cluster environment, for convenient scaling and to make use of cost-effective commodity hardware.
- Ability to share data files between different components with no copy or export/import step; for example, to write with Pig, transform with Hive and query with Impala. Impala can read from and write to Hive tables, enabling simple data interchange using Impala for analytics on Hive-produced data.
- Single system for big data processing and analytics, so customers can avoid costly modeling and ETL just for analytics.

How Impala Works with CDH

The following graphic illustrates how Impala is positioned in the broader Cloudera environment:



The Impala solution is composed of the following components:

- Clients - Entities including Hue, ODBC clients, JDBC clients, and the Impala Shell can all interact with Impala. These interfaces are typically used to issue queries or complete administrative tasks such as connecting to Impala.

Introducing Apache Impala

- Hive Metastore - Stores information about the data available to Impala. For example, the metastore lets Impala know what databases are available and what the structure of those databases is. As you create, drop, and alter schema objects, load data into tables, and so on through Impala SQL statements, the relevant metadata changes are automatically broadcast to all Impala nodes by the dedicated catalog service introduced in Impala 1.2.
- Impala - This process, which runs on DataNodes, coordinates and executes queries. Each instance of Impala can receive, plan, and coordinate queries from Impala clients. Queries are distributed among Impala nodes, and these nodes then act as workers, executing parallel query fragments.
- HBase and HDFS - Storage for data to be queried.

Queries executed using Impala are handled as follows:

1. User applications send SQL queries to Impala through ODBC or JDBC, which provide standardized querying interfaces. The user application may connect to any `impalad` in the cluster. This `impalad` becomes the coordinator for the query.
2. Impala parses the query and analyzes it to determine what tasks need to be performed by `impalad` instances across the cluster. Execution is planned for optimal efficiency.
3. Services such as HDFS and HBase are accessed by local `impalad` instances to provide data.
4. Each `impalad` returns data to the coordinating `impalad`, which sends these results to the client.

Primary Impala Features

Impala provides support for:

- Most common SQL-92 features of Hive Query Language (HiveQL) including [SELECT](#), [joins](#), and [aggregate functions](#).
- HDFS, HBase, and Amazon Simple Storage System (S3) storage, including:
 - [HDFS file formats](#): delimited text files, Parquet, Avro, SequenceFile, and RCFile.
 - Compression codecs: Snappy, GZIP, Deflate, BZIP.
- Common data access interfaces including:
 - [JDBC driver](#).
 - [ODBC driver](#).
 - Hue Beeswax and the Impala Query UI.
- [impala-shell command-line interface](#).
- [Kerberos authentication](#).

Impala Concepts and Architecture

The following sections provide background information to help you become productive using Impala and its features. Where appropriate, the explanations include context to help understand how aspects of Impala relate to other technologies you might already be familiar with, such as relational database management systems and data warehouses, or other Hadoop components such as Hive, HDFS, and HBase.

Components of the Impala Server

The Impala server is a distributed, massively parallel processing (MPP) database engine. It consists of different daemon processes that run on specific hosts within your CDH cluster.

The Impala Daemon

The core Impala component is a daemon process that runs on each DataNode of the cluster, physically represented by the `impalad` process. It reads and writes to data files; accepts queries transmitted from the `impala-shell` command, Hue, JDBC, or ODBC; parallelizes the queries and distributes work across the cluster; and transmits intermediate query results back to the central coordinator node.

You can submit a query to the Impala daemon running on any DataNode, and that instance of the daemon serves as the **coordinator node** for that query. The other nodes transmit partial results back to the coordinator, which constructs the final result set for a query. When running experiments with functionality through the `impala-shell` command, you might always connect to the same Impala daemon for convenience. For clusters running production workloads, you might load-balance by submitting each query to a different Impala daemon in round-robin style, using the JDBC or ODBC interfaces.

The Impala daemons are in constant communication with the **statestore**, to confirm which nodes are healthy and can accept new work.

They also receive broadcast messages from the `catalogd` daemon (introduced in Impala 1.2) whenever any Impala node in the cluster creates, alters, or drops any type of object, or when an `INSERT` or `LOAD DATA` statement is processed through Impala. This background communication minimizes the need for `REFRESH` or `INVALIDATE METADATA` statements that were needed to coordinate metadata across nodes prior to Impala 1.2.

Related information: [Modifying Impala Startup Options](#) on page 45, [Starting Impala](#) on page 44, [Setting the Idle Query and Idle Session Timeouts for impalad](#) on page 92, [Ports Used by Impala](#) on page 639, [Using Impala through a Proxy for High Availability](#) on page 93

The Impala Statestore

The Impala component known as the **statestore** checks on the health of Impala daemons on all the DataNodes in a cluster, and continuously relays its findings to each of those daemons. It is physically represented by a daemon process named `statestored`; you only need such a process on one host in the cluster. If an Impala daemon goes offline due to hardware failure, network error, software issue, or other reason, the statestore informs all the other Impala daemons so that future queries can avoid making requests to the unreachable node.

Because the statestore's purpose is to help when things go wrong and to broadcast metadata to coordinators, it is not always critical to the normal operation of an Impala cluster. If the statestore is not running or becomes unreachable, the Impala daemons continue running and distributing work among themselves as usual when working with the data known to Impala. The cluster just becomes less robust if other Impala daemons fail, and metadata becomes less consistent as it changes while the statestore is offline. When the statestore comes back online, it re-establishes communication with the Impala daemons and resumes its monitoring and broadcasting functions.

If you issue a DDL statement while the statestore is down, the queries that access the new object the DDL created will fail.

Most considerations for load balancing and high availability apply to the `impalad` daemon. The `statestored` and `catalogd` daemons do not have special requirements for high availability, because problems with those daemons do not result in data loss. If those daemons become unavailable due to an outage on a particular host, you can stop the Impala service, delete the **Impala StateStore** and **Impala Catalog Server** roles, add the roles on a different host, and restart the Impala service.

Related information:

[Scalability Considerations for the Impala Statestore](#) on page 561, [Modifying Impala Startup Options](#) on page 45, [Starting Impala](#) on page 44, [Increasing the Statestore Timeout](#) on page 92, [Ports Used by Impala](#) on page 639

The Impala Catalog Service

The Impala component known as the **catalog service** relays the metadata changes from Impala SQL statements to all the Impala daemons in a cluster. It is physically represented by a daemon process named `catalogd`; you only need such a process on one host in the cluster. Because the requests are passed through the `statestore` daemon, it makes sense to run the `statestored` and `catalogd` services on the same host.

The catalog service avoids the need to issue `REFRESH` and `INVALIDATE METADATA` statements when the metadata changes are performed by statements issued through Impala. When you create a table, load data, and so on through Hive, you do need to issue `REFRESH` or `INVALIDATE METADATA` on an Impala node before executing a query there.

This feature touches a number of aspects of Impala:

- See [Installing Impala](#) on page 29, [Upgrading Impala](#) on page 40 and [Starting Impala](#) on page 44, for usage information for the `catalogd` daemon.
- The `REFRESH` and `INVALIDATE METADATA` statements are not needed when the `CREATE TABLE`, `INSERT`, or other table-changing or data-changing operation is performed through Impala. These statements are still needed if such operations are done through Hive or by manipulating data files directly in HDFS, but in those cases the statements only need to be issued on one Impala node rather than on all nodes. See [REFRESH Statement](#) on page 300 and [INVALIDATE METADATA Statement](#) on page 294 for the latest usage information for those statements.

Use `--load_catalog_in_background` option to control when the metadata of a table is loaded.

- If set to `false`, the metadata of a table will be loaded when it is referenced for the first time. This means that the first run of a particular query can be slower than subsequent runs. Starting in Impala 2.2, the default for `load_catalog_in_background` is `false`.
- If set to `true`, the catalog service will aim to load metadata for a table even if no query needed that metadata. So metadata will possibly be already loaded when the first query that would need it is run. However, for the following reasons, we recommend not to set the option to `true`.
 - Both on startup and after a global or a table-specific metadata invalidate, the metadata load for tables that actual queries can get backed up because the catalog service could spend time loading metadata for another table. During such load, a request for prioritized load by a query will be put on hold, and this can lead to seemingly random long-running queries that are difficult for you to diagnose.
 - Impala may load metadata for tables that are possibly never used, increasing catalog size and consequently memory usage for both `catalog` and `impalad`.

Most considerations for load balancing and high availability apply to the `impalad` daemon. The `statestored` and `catalogd` daemons do not have special requirements for high availability, because problems with those daemons do not result in data loss. If those daemons become unavailable due to an outage on a particular host, you can stop the Impala service, delete the **Impala StateStore** and **Impala Catalog Server** roles, add the roles on a different host, and restart the Impala service.

**Note:**

In Impala 1.2.4 and higher, you can specify a table name with `INVALIDATE METADATA` after the table is created in Hive, allowing you to make individual tables visible to Impala without doing a full reload of the catalog metadata. Impala 1.2.4 also includes other changes to make the metadata broadcast mechanism faster and more responsive, especially during Impala startup. See [New Features in Impala 1.2.4](#) on page 678 for details.

Related information: [Modifying Impala Startup Options](#) on page 45, [Starting Impala](#) on page 44, [Ports Used by Impala](#) on page 639

Developing Impala Applications

The core development language with Impala is SQL. You can also use Java or other languages to interact with Impala through the standard JDBC and ODBC interfaces used by many business intelligence tools. For specialized kinds of analysis, you can supplement the SQL built-in functions by writing [user-defined functions \(UDFs\)](#) in C++ or Java.

Overview of the Impala SQL Dialect

The Impala SQL dialect is highly compatible with the SQL syntax used in the Apache Hive component (HiveQL). As such, it is familiar to users who are already familiar with running SQL queries on the Hadoop infrastructure. Currently, Impala SQL supports a subset of HiveQL statements, data types, and built-in functions. Impala also includes additional built-in functions for common industry features, to simplify porting SQL from non-Hadoop systems.

For users coming to Impala from traditional database or data warehousing backgrounds, the following aspects of the SQL dialect might seem familiar:

- The [SELECT statement](#) includes familiar clauses such as `WHERE`, `GROUP BY`, `ORDER BY`, and `WITH`. You will find familiar notions such as [joins](#), [built-in functions](#) for processing strings, numbers, and dates, [aggregate functions](#), [subqueries](#), and [comparison operators](#) such as `IN()` and `BETWEEN`. The `SELECT` statement is the place where SQL standards compliance is most important.
- From the data warehousing world, you will recognize the notion of [partitioned tables](#). One or more columns serve as partition keys, and the data is physically arranged so that queries that refer to the partition key columns in the `WHERE` clause can skip partitions that do not match the filter conditions. For example, if you have 10 years worth of data and use a clause such as `WHERE year = 2015`, `WHERE year > 2010`, or `WHERE year IN (2014, 2015)`, Impala skips all the data for non-matching years, greatly reducing the amount of I/O for the query.
- In Impala 1.2 and higher, [UDFs](#) let you perform custom comparisons and transformation logic during `SELECT` and `INSERT . . . SELECT` statements.

For users coming to Impala from traditional database or data warehousing backgrounds, the following aspects of the SQL dialect might require some learning and practice for you to become proficient in the Hadoop environment:

- Impala SQL is focused on queries and includes relatively little DML. There is no `UPDATE` or `DELETE` statement. Stale data is typically discarded (by `DROP TABLE` or `ALTER TABLE . . . DROP PARTITION` statements) or replaced (by `INSERT OVERWRITE` statements).
- All data creation is done by `INSERT` statements, which typically insert data in bulk by querying from other tables. There are two variations, `INSERT INTO` which appends to the existing data, and `INSERT OVERWRITE` which replaces the entire contents of a table or partition (similar to `TRUNCATE TABLE` followed by a new `INSERT`). Although there is an `INSERT . . . VALUES` syntax to create a small number of values in a single statement, it is far more efficient to use the `INSERT . . . SELECT` to copy and transform large amounts of data from one table to another in a single operation.
- You often construct Impala table definitions and data files in some other environment, and then attach Impala so that it can run real-time queries. The same data files and table metadata are shared with other components of the Hadoop ecosystem. In particular, Impala can access tables created by Hive or data inserted by Hive, and Hive

can access tables and data produced by Impala. Many other Hadoop components can write files in formats such as Parquet and Avro, that can then be queried by Impala.

- Because Hadoop and Impala are focused on data warehouse-style operations on large data sets, Impala SQL includes some idioms that you might find in the import utilities for traditional database systems. For example, you can create a table that reads comma-separated or tab-separated text files, specifying the separator in the `CREATE TABLE` statement. You can create **external tables** that read existing data files but do not move or transform them.
- Because Impala reads large quantities of data that might not be perfectly tidy and predictable, it does not require length constraints on string data types. For example, you can define a database column as `STRING` with unlimited length, rather than `CHAR(1)` or `VARCHAR(64)`. (Although in Impala 2.0 and later, you can also use length-constrained `CHAR` and `VARCHAR` types.)

Related information: [Impala SQL Language Reference](#) on page 126, especially [Impala SQL Statements](#) on page 228 and [Impala Built-In Functions](#) on page 373

Overview of Impala Programming Interfaces

You can connect and submit requests to the Impala daemons through:

- The [impala-shell](#) interactive command interpreter.
- The [Hue](#) web-based user interface.
- [JDBC](#).
- [ODBC](#).

With these options, you can use Impala in heterogeneous environments, with JDBC or ODBC applications running on non-Linux platforms. You can also use Impala in combination with various Business Intelligence tools that use the JDBC and ODBC interfaces.

Each `impalad` daemon process, running on separate nodes in a cluster, listens to [several ports](#) for incoming requests. Requests from `impala-shell` and Hue are routed to the `impalad` daemons through the same port. The `impalad` daemons listen on separate ports for JDBC and ODBC requests.

How Impala Fits Into the Hadoop Ecosystem

Impala makes use of many familiar components within the Hadoop ecosystem. Impala can interchange data with other Hadoop components, as both a consumer and a producer, so it can fit in flexible ways into your ETL and ELT pipelines.

How Impala Works with Hive

A major Impala goal is to make SQL-on-Hadoop operations fast and efficient enough to appeal to new categories of users and open up Hadoop to new types of use cases. Where practical, it makes use of existing Apache Hive infrastructure that many Hadoop users already have in place to perform long-running, batch-oriented SQL queries.

In particular, Impala keeps its table definitions in a traditional MySQL or PostgreSQL database known as the **metastore**, the same database where Hive keeps this type of data. Thus, Impala can access tables defined or loaded by Hive, as long as all columns use Impala-supported data types, file formats, and compression codecs.

The initial focus on query features and performance means that Impala can read more types of data with the `SELECT` statement than it can write with the `INSERT` statement. To query data using the Avro, RCFile, or SequenceFile [file formats](#), you load the data using Hive.

The Impala query optimizer can also make use of [table statistics](#) and [column statistics](#). Originally, you gathered this information with the `ANALYZE TABLE` statement in Hive; in Impala 1.2.2 and higher, use the Impala [COMPUTE STATS](#) statement instead. `COMPUTE STATS` requires less setup, is more reliable, and does not require switching back and forth between `impala-shell` and the Hive shell.

Overview of Impala Metadata and the Metastore

As discussed in [How Impala Works with Hive](#) on page 22, Impala maintains information about table definitions in a central database known as the **metastore**. Impala also tracks other metadata for the low-level characteristics of data files:

- The physical locations of blocks within HDFS.

For tables with a large volume of data and/or many partitions, retrieving all the metadata for a table can be time-consuming, taking minutes in some cases. Thus, each Impala node caches all of this metadata to reuse for future queries against the same table.

If the table definition or the data in the table is updated, all other Impala daemons in the cluster must receive the latest metadata, replacing the obsolete cached metadata, before issuing a query against that table. In Impala 1.2 and higher, the metadata update is automatic, coordinated through the `catalogd` daemon, for all DDL and DML statements issued through Impala. See [The Impala Catalog Service](#) on page 20 for details.

For DDL and DML issued through Hive, or changes made manually to files in HDFS, you still use the `REFRESH` statement (when new data files are added to existing tables) or the `INVALIDATE METADATA` statement (for entirely new tables, or after dropping a table, performing an HDFS rebalance operation, or deleting data files). Issuing `INVALIDATE METADATA` by itself retrieves metadata for all the tables tracked by the metastore. If you know that only specific tables have been changed outside of Impala, you can issue `REFRESH table_name` for each affected table to only retrieve the latest metadata for those tables.

How Impala Uses HDFS

Impala uses the distributed filesystem HDFS as its primary data storage medium. Impala relies on the redundancy provided by HDFS to guard against hardware or network outages on individual nodes. Impala table data is physically represented as data files in HDFS, using familiar HDFS file formats and compression codecs. When data files are present in the directory for a new table, Impala reads them all, regardless of file name. New data is added in files with names controlled by Impala.

How Impala Uses HBase

HBase is an alternative to HDFS as a storage medium for Impala data. It is a database storage system built on top of HDFS, without built-in SQL support. Many Hadoop users already have it configured and store large (often sparse) data sets in it. By defining tables in Impala and mapping them to equivalent tables in HBase, you can query the contents of the HBase tables through Impala, and even perform join queries including both Impala and HBase tables. See [Using Impala to Query HBase Tables](#) on page 608 for details.

Planning for Impala Deployment

Before you set up Impala in production, do some planning to make sure that your hardware setup has sufficient capacity, that your cluster topology is optimal for Impala queries, and that your schema design and ETL processes follow the best practices for Impala.

Impala Requirements

To perform as expected, Impala depends on the availability of the software, hardware, and configurations described in the following sections.

Product Compatibility Matrix

The ultimate source of truth about compatibility between various versions of CDH, Cloudera Manager, and various CDH components is the online [Product Compatibility Matrix](#).

For Impala, see the [Impala compatibility matrix page](#).

Supported Operating Systems

The relevant supported operating systems and versions for Impala are the same as for the corresponding CDH 5 platforms. For details, see the *Supported Operating Systems* page for [CDH 5](#).

Hive Metastore and Related Configuration

Impala can interoperate with data stored in Hive, and uses the same infrastructure as Hive for tracking metadata about schema objects such as tables and columns. The following components are prerequisites for Impala:

- MySQL or PostgreSQL, to act as a metastore database for both Impala and Hive.



Note:

Installing and configuring a Hive metastore is an Impala requirement. Impala does not work without the metastore database. For the process of installing and configuring the metastore, see [Installing Impala](#) on page 29.

Always configure a **Hive metastore service** rather than connecting directly to the metastore database. The Hive metastore service is required to interoperate between possibly different levels of metastore APIs used by CDH and Impala, and avoids known issues with connecting directly to the metastore database. The Hive metastore service is set up for you by default if you install through Cloudera Manager 4.5 or higher.

A summary of the metastore installation process is as follows:

- Install a MySQL or PostgreSQL database. Start the database if it is not started after installation.
- Download the [MySQL connector](#) or the [PostgreSQL connector](#) and place it in the `/usr/share/java/` directory.
- Use the appropriate command line tool for your database to create the metastore database.
- Use the appropriate command line tool for your database to grant privileges for the metastore database to the `hive` user.
- Modify `hive-site.xml` to include information matching your particular database: its URL, username, and password. You will copy the `hive-site.xml` file to the Impala Configuration Directory later in the Impala installation process.

- **Optional:** Hive. Although only the Hive metastore database is required for Impala to function, you might install Hive on some client machines to create and load data into tables that use certain file formats. See [How Impala](#)

[Works with Hadoop File Formats](#) on page 575 for details. Hive does not need to be installed on the same DataNodes as Impala; it just needs access to the same metastore database.

Java Dependencies

Although Impala is primarily written in C++, it does use Java to communicate with various Hadoop components:

- The officially supported JVM for Impala is the Oracle JVM. Other JVMs might cause issues, typically resulting in a failure at `impalad` startup. In particular, the JamVM used by default on certain levels of Ubuntu systems can cause `impalad` to fail to start.
- Internally, the `impalad` daemon relies on the `JAVA_HOME` environment variable to locate the system Java libraries. Make sure the `impalad` service is not run from an environment with an incorrect setting for this variable.
- All Java dependencies are packaged in the `impala-dependencies.jar` file, which is located at `/usr/lib/impala/lib/`. These map to everything that is built under `fe/target/dependency`.

Networking Configuration Requirements

As part of ensuring best performance, Impala attempts to complete tasks on local data, as opposed to using network connections to work with remote data. To support this goal, Impala matches the **hostname** provided to each Impala daemon with the **IP address** of each DataNode by resolving the hostname flag to an IP address. For Impala to work with local data, use a single IP interface for the DataNode and the Impala daemon on each machine. Ensure that the Impala daemon's hostname flag resolves to the IP address of the DataNode. For single-homed machines, this is usually automatic, but for multi-homed machines, ensure that the Impala daemon's hostname resolves to the correct interface. Impala tries to detect the correct hostname at start-up, and prints the derived hostname at the start of the log in a message of the form:

```
Using hostname: impala-daemon-1.example.com
```

In the majority of cases, this automatic detection works correctly. If you need to explicitly set the hostname, do so by setting the `--hostname` flag.

Hardware Requirements

The memory allocation should be consistent across Impala executor nodes. A single Impala executor with a lower memory limit than the rest can easily become a bottleneck and lead to suboptimal performance.

This guideline does not apply to coordinator-only nodes.

Hardware Requirements for Optimal Join Performance

During join operations, portions of data from each joined table are loaded into memory. Data sets can be very large, so ensure your hardware has sufficient memory to accommodate the joins you anticipate completing.

While requirements vary according to data set size, the following is generally recommended:

- CPU

Impala version 2.2 and higher uses the SSE3 instruction set, which is included in newer processors.



Note: This required level of processor is the same as in Impala version 1.x. The Impala 2.0 and 2.1 releases had a stricter requirement for the SSE4.1 instruction set, which has now been relaxed.

- Memory

128 GB or more recommended, ideally 256 GB or more. If the intermediate results during query processing on a particular node exceed the amount of memory available to Impala on that node, the query writes temporary work data to disk, which can lead to long query times. Note that because the work is parallelized, and intermediate results for aggregate queries are typically smaller than the original data, Impala can query and join tables that are much larger than the memory available on an individual node.

- Storage

DataNodes with 12 or more disks each. I/O speeds are often the limiting factor for disk performance with Impala. Ensure that you have sufficient disk space to store the data Impala will be querying.

User Account Requirements

Impala creates and uses a user and group named `impala`. Do not delete this account or group and do not modify the account's or group's permissions and rights. Ensure no existing systems obstruct the functioning of these accounts and groups. For example, if you have scripts that delete user accounts not in a white-list, add these accounts to the list of permitted accounts.

For correct file deletion during `DROP TABLE` operations, Impala must be able to move files to the HDFS trashcan. You might need to create an HDFS directory `/user/impala`, writeable by the `impala` user, so that the trashcan can be created. Otherwise, data files might remain behind after a `DROP TABLE` statement.

Impala should not run as root. Best Impala performance is achieved using direct reads, but root is not permitted to use direct reads. Therefore, running Impala as root negatively affects performance.

By default, any user can connect to Impala and access all the associated databases and tables. You can enable authorization and authentication based on the Linux OS user who connects to the Impala server, and the associated groups for that user. [Impala Security](#) on page 100 for details. These security features do not change the underlying file permission requirements; the `impala` user still needs to be able to access the data files.

Guidelines for Designing Impala Schemas

The guidelines in this topic help you to construct an optimized and scalable schema, one that integrates well with your existing data management processes. Use these guidelines as a checklist when doing any proof-of-concept work, porting exercise, or before deploying to production.

If you are adapting an existing database or Hive schema for use with Impala, read the guidelines in this section and then see [Porting SQL from Other Database Systems to Impala](#) on page 505 for specific porting and compatibility tips.

Prefer binary file formats over text-based formats.

To save space and improve memory usage and query performance, use binary file formats for any large or intensively queried tables. Parquet file format is the most efficient for data warehouse-style analytic queries. Avro is the other binary file format that Impala supports, that you might already have as part of a Hadoop ETL pipeline.

Although Impala can create and query tables with the RCFile and SequenceFile file formats, such tables are relatively bulky due to the text-based nature of those formats, and are not optimized for data warehouse-style queries due to their row-oriented layout. Impala does not support `INSERT` operations for tables with these file formats.

Guidelines:

- For an efficient and scalable format for large, performance-critical tables, use the Parquet file format.
- To deliver intermediate data during the ETL process, in a format that can also be used by other Hadoop components, Avro is a reasonable choice.
- For convenient import of raw data, use a text table instead of RCFile or SequenceFile, and convert to Parquet in a later stage of the ETL process.

Use Snappy compression where practical.

Snappy compression involves low CPU overhead to decompress, while still providing substantial space savings. In cases where you have a choice of compression codecs, such as with the Parquet and Avro file formats, use Snappy compression unless you find a compelling reason to use a different codec.

Prefer numeric types over strings.

If you have numeric values that you could treat as either strings or numbers (such as `YEAR`, `MONTH`, and `DAY` for partition key columns), define them as the smallest applicable integer types. For example, `YEAR` can be `SMALLINT`, `MONTH` and `DAY` can be `TINYINT`. Although you might not see any difference in the way partitioned tables or text files are laid out on disk, using numeric types will save space in binary formats such as Parquet, and in memory when doing queries, particularly resource-intensive queries such as joins.

Partition, but do not over-partition.

Partitioning is an important aspect of performance tuning for Impala. Follow the procedures in [Partitioning for Impala Tables](#) on page 568 to set up partitioning for your biggest, most intensively queried tables.

If you are moving to Impala from a traditional database system, or just getting started in the Big Data field, you might not have enough data volume to take advantage of Impala parallel queries with your existing partitioning scheme. For example, if you have only a few tens of megabytes of data per day, partitioning by `YEAR`, `MONTH`, and `DAY` columns might be too granular. Most of your cluster might be sitting idle during queries that target a single day, or each node might have very little work to do. Consider reducing the number of partition key columns so that each partition directory contains several gigabytes worth of data.

For example, consider a Parquet table where each data file is 1 HDFS block, with a maximum block size of 1 GB. (In Impala 2.0 and later, the default Parquet block size is reduced to 256 MB. For this exercise, let's assume you have bumped the size back up to 1 GB by setting the query option `PARQUET_FILE_SIZE=1g`.) If you have a 10-node cluster, you need 10 data files (up to 10 GB) to give each node some work to do for a query. But each core on each machine can process a separate data block in parallel. With 16-core machines on a 10-node cluster, a query could process up to 160 GB fully in parallel. If there are only a few data files per partition, not only are most cluster nodes sitting idle during queries, so are most cores on those machines.

You can reduce the Parquet block size to as low as 128 MB or 64 MB to increase the number of files per partition and improve parallelism. But also consider reducing the level of partitioning so that analytic queries have enough data to work with.

Always compute stats after loading data.

Impala makes extensive use of statistics about data in the overall table and in each column, to help plan resource-intensive operations such as join queries and inserting into partitioned Parquet tables. Because this information is only available after data is loaded, run the `COMPUTE STATS` statement on a table after loading or replacing data in a table or partition.

Having accurate statistics can make the difference between a successful operation, or one that fails due to an out-of-memory error or a timeout. When you encounter performance or capacity issues, always use the `SHOW STATS` statement to check if the statistics are present and up-to-date for all tables in the query.

When doing a join query, Impala consults the statistics for each joined table to determine their relative sizes and to estimate the number of rows produced in each join stage. When doing an `INSERT` into a Parquet table, Impala consults the statistics for the source table to determine how to distribute the work of constructing the data files for each partition.

See [COMPUTE STATS Statement](#) on page 241 for the syntax of the `COMPUTE STATS` statement, and [Table and Column Statistics](#) on page 533 for all the performance considerations for table and column statistics.

Verify sensible execution plans with EXPLAIN and SUMMARY.

Before executing a resource-intensive query, use the `EXPLAIN` statement to get an overview of how Impala intends to parallelize the query and distribute the work. If you see that the query plan is inefficient, you can take tuning steps such as changing file formats, using partitioned tables, running the `COMPUTE STATS` statement, or adding query hints. For information about all of these techniques, see [Tuning Impala for Performance](#) on page 523.

After you run a query, you can see performance-related information about how it actually ran by issuing the `SUMMARY` command in `impala-shell`. Prior to Impala 1.4, you would use the `PROFILE` command, but its highly technical output

Planning for Impala Deployment

was only useful for the most experienced users. `SUMMARY`, new in Impala 1.4, summarizes the most useful information for all stages of execution, for all nodes rather than splitting out figures for each node.

Installing Impala

Impala is an open-source add-on to the Cloudera Enterprise Core that returns rapid responses to queries.

**Note:**

Under CDH 5, Impala is included as part of the CDH installation and no separate steps are needed. Therefore, the instruction steps in this section apply to CDH 4 only.

What is Included in an Impala Installation

Impala is made up of a set of components that can be installed on multiple nodes throughout your cluster. The key installation step for performance is to install the `impalad` daemon (which does most of the query processing work) on *all* DataNodes in the cluster.

The Impala package installs these binaries:

- `impalad` - The Impala daemon. Plans and executes queries against HDFS, HBase, and Amazon S3 data. [Run one impalad process](#) on each node in the cluster that has a DataNode.
- `statedored` - Name service that tracks location and status of all `impalad` instances in the cluster. [Run one instance of this daemon](#) on a node in your cluster. Most production deployments run this daemon on the namenode.
- `catalogd` - Metadata coordination service that broadcasts changes from Impala DDL and DML statements to all affected Impala nodes, so that new tables, newly loaded data, and so on are immediately visible to queries submitted through any Impala node. (Prior to Impala 1.2, you had to run the `REFRESH` or `INVALIDATE METADATA` statement on each node to synchronize changed metadata. Now those statements are only required if you perform the DDL or DML through an external mechanism such as Hive or by uploading data to the Amazon S3 filesystem.) [Run one instance of this daemon](#) on a node in your cluster, preferably on the same host as the `statedored` daemon.
- `impala-shell` - [Command-line interface](#) for issuing queries to the Impala daemon. You install this on one or more hosts anywhere on your network, not necessarily DataNodes or even within the same cluster as Impala. It can connect remotely to any instance of the Impala daemon.

Before doing the installation, ensure that you have all necessary prerequisites. See [Impala Requirements](#) on page 24 for details.

Installing Impala with Cloudera Manager

Before installing Impala through the Cloudera Manager interface, make sure all applicable nodes have the appropriate hardware configuration and levels of operating system and CDH. See [Impala Requirements](#) on page 24 for details.

**Note:**

To install the latest Impala under CDH 4, upgrade Cloudera Manager to 4.8 or higher. Cloudera Manager 4.8 is the first release that can manage the Impala catalog service introduced in Impala 1.2. Cloudera Manager 4.8 requires this service to be present, so if you upgrade to Cloudera Manager 4.8, also upgrade Impala to the most recent version at the same time.

For information on installing Impala in a Cloudera Manager-managed environment, see [Installing Impala](#).

Managing your Impala installation through Cloudera Manager has a number of advantages. For example, when you make configuration changes to CDH components using Cloudera Manager, it automatically applies changes to the copies of configuration files, such as `hive-site.xml`, that Impala keeps under `/etc/impala/conf`. It also sets up the Hive Metastore service that is required for Impala running under CDH 4.1.

In some cases, depending on the level of Impala, CDH, and Cloudera Manager, you might need to add particular component configuration details in some of the free-form option fields on the Impala configuration pages within Cloudera Manager. In Cloudera Manager 4, these fields are labelled **Safety Valve**; in Cloudera Manager 5, they are called **Advanced Configuration Snippet**.

Installing Impala without Cloudera Manager

Before installing Impala manually, make sure all applicable nodes have the appropriate hardware configuration, levels of operating system and CDH, and any other software prerequisites. See [Impala Requirements](#) on page 24 for details.

You can install Impala across many hosts or on one host:

- Installing Impala across multiple machines creates a distributed configuration. For best performance, install Impala on **all** DataNodes.
- Installing Impala on a single machine produces a pseudo-distributed cluster.

To install Impala on a host:

1. Install CDH as described in the Installation section of the [CDH 5 Installation Guide](#).
2. Install the Hive metastore somewhere in your cluster, as described in the Hive Installation topic in the [CDH 5 Installation Guide](#). As part of this process, you configure the Hive metastore to use an external database as a metastore. Impala uses this same database for its own table metadata. You can choose either a MySQL or PostgreSQL database as the metastore. The process for configuring each type of database is described in the CDH Installation Guide).

Cloudera recommends setting up a Hive metastore service rather than connecting directly to the metastore database; this configuration is required when running Impala under CDH 4.1. Make sure the `/etc/impala/conf/hive-site.xml` file contains the following setting, substituting the appropriate hostname for `metastore_server_host`:

```
<property>
<name>hive.metastore.uris</name>
<value>thrift://metastore_server_host:9083</value>
</property>
<property>
<name>hive.metastore.client.socket.timeout</name>
<value>3600</value>
<description>MetaStore Client socket timeout in seconds</description>
</property>
```

3. (Optional) If you installed the full Hive component on any host, you can verify that the metastore is configured properly by starting the Hive console and querying for the list of available tables. Once you confirm that the console starts, exit the console to continue the installation:

```
$ hive
Hive history file=/tmp/root/hive_job_log_root_201207272011_678722950.txt
hive> show tables;
table1
table2
hive> quit;
$
```

4. Confirm that your package management command is aware of the Impala repository settings, as described in [Impala Requirements](#) on page 24. (For CDH 4, this is a different repository than for CDH.) You might need to download a repo or list file into a system directory underneath `/etc`.
5. Use **one** of the following sets of commands to install the Impala package:

For RHEL, Oracle Linux, or CentOS systems:

```
$ sudo yum install impala # Binaries for daemons
$ sudo yum install impala-server # Service start/stop script
$ sudo yum install impala-state-store # Service start/stop script
$ sudo yum install impala-catalog # Service start/stop script
```

For SUSE systems:

```
$ sudo zypper install impala # Binaries for daemons
$ sudo zypper install impala-server # Service start/stop script
$ sudo zypper install impala-state-store # Service start/stop script
$ sudo zypper install impala-catalog # Service start/stop script
```

For Debian or Ubuntu systems:

```
$ sudo apt-get install impala # Binaries for daemons
$ sudo apt-get install impala-server # Service start/stop script
$ sudo apt-get install impala-state-store # Service start/stop script
$ sudo apt-get install impala-catalog # Service start/stop script
```



Note: Cloudera recommends that you not install Impala on any HDFS NameNode. Installing Impala on NameNodes provides no additional data locality, and executing queries with such a configuration might cause memory contention and negatively impact the HDFS NameNode.

- Copy the client `hive-site.xml`, `core-site.xml`, `hdfs-site.xml`, and `hbase-site.xml` configuration files to the Impala configuration directory, which defaults to `/etc/impala/conf`. Create this directory if it does not already exist.
- Use **one** of the following commands to install `impala-shell` on the machines from which you want to issue queries. You can install `impala-shell` on any supported machine that can connect to DataNodes that are running `impalad`.

For RHEL/CentOS systems:

```
$ sudo yum install impala-shell
```

For SUSE systems:

```
$ sudo zypper install impala-shell
```

For Debian/Ubuntu systems:

```
$ sudo apt-get install impala-shell
```

- Complete any required or recommended configuration, as described in [Post-Installation Configuration for Impala](#) on page 32. Some of these configuration changes are mandatory. (They are applied automatically when you install using Cloudera Manager.)

Once installation and configuration are complete, see [Starting Impala](#) on page 44 for how to activate the software on the appropriate nodes in your cluster.

If this is your first time setting up and using Impala in this cluster, run through some of the exercises in [Impala Tutorials](#) on page 49 to verify that you can do basic operations such as creating tables and querying them.

Managing Impala

This section explains how to configure Impala to accept connections from applications that use popular programming APIs:

- [Post-Installation Configuration for Impala](#) on page 32
- [Configuring Impala to Work with ODBC](#) on page 33
- [Configuring Impala to Work with JDBC](#) on page 36

This type of configuration is especially useful when using Impala in combination with Business Intelligence tools, which use these standard interfaces to query different kinds of database and Big Data systems.

You can also configure these other aspects of Impala:

- [Impala Security](#) on page 100
- [Modifying Impala Startup Options](#) on page 45

Post-Installation Configuration for Impala

This section describes the mandatory and recommended configuration settings for Impala. If Impala is installed using Cloudera Manager, some of these configurations are completed automatically; you must still configure short-circuit reads manually. If you installed Impala without Cloudera Manager, or if you want to customize your environment, consider making the changes described in this topic.

In some cases, depending on the level of Impala, CDH, and Cloudera Manager, you might need to add particular component configuration details in one of the free-form fields on the Impala configuration pages within Cloudera Manager. In Cloudera Manager 4, these fields are labelled **Safety Valve**; in Cloudera Manager 5, they are called **Advanced Configuration Snippet**.

- You must enable short-circuit reads, whether or not Impala was installed through Cloudera Manager. This setting goes in the Impala configuration settings, not the Hadoop-wide settings.
- If you installed Impala in an environment that is not managed by Cloudera Manager, you must enable block location tracking, and you can optionally enable native checksumming for optimal performance.
- If you deployed Impala using Cloudera Manager see [Testing Impala Performance](#) on page 555 to confirm proper configuration.

Mandatory: Short-Circuit Reads

Enabling short-circuit reads allows Impala to read local data directly from the file system. This removes the need to communicate through the DataNodes, improving performance. This setting also minimizes the number of additional copies of data. Short-circuit reads requires `libhadoop.so` (the Hadoop Native Library) to be accessible to both the server and the client. `libhadoop.so` is not available if you have installed from a tarball. You must install from an `.rpm`, `.deb`, or `parcel` to use short-circuit local reads.



Note: If you use Cloudera Manager, you can enable short-circuit reads through a checkbox in the user interface and that setting takes effect for Impala as well.

To configure DataNodes for short-circuit reads:

1. Copy the client `core-site.xml` and `hdfs-site.xml` configuration files from the Hadoop configuration directory to the Impala configuration directory. The default Impala configuration location is `/etc/impala/conf`.
2. On all Impala nodes, configure the following properties in Impala's copy of `hdfs-site.xml` as shown:

```
<property>
  <name>dfs.client.read.shortcircuit</name>
```



```

    <value>true</value>
  </property>

  <property>
    <name>dfs.domain.socket.path</name>
    <value>/var/run/hdfs-sockets/dn</value>
  </property>

  <property>
    <name>dfs.client.file-block-storage-locations.timeout.millis</name>
    <value>10000</value>
  </property>

```

3. If `/var/run/hadoop-hdfs/` is group-writable, make sure its group is `root`.



Note: If you are also going to enable block location tracking, you can skip copying configuration files and restarting DataNodes and go straight to [Optional: Block Location Tracking](#). Configuring short-circuit reads and block location tracking require the same process of copying files and restarting services, so you can complete that process once when you have completed all configuration changes. Whether you copy files and restart services now or during configuring block location tracking, short-circuit reads are not enabled until you complete those final steps.

4. After applying these changes, restart all DataNodes.

Mandatory: Block Location Tracking

Enabling block location metadata allows Impala to know which disk data blocks are located on, allowing better utilization of the underlying disks. Impala will not start unless this setting is enabled.

To enable block location tracking:

1. For each DataNode, adding the following to the `hdfs-site.xml` file:

```

<property>
  <name>dfs.datanode.hdfs-blocks-metadata.enabled</name>
  <value>true</value>
</property>

```

2. Copy the client `core-site.xml` and `hdfs-site.xml` configuration files from the Hadoop configuration directory to the Impala configuration directory. The default Impala configuration location is `/etc/impala/conf`.
3. After applying these changes, restart all DataNodes.

Optional: Native Checksumming

Enabling native checksumming causes Impala to use an optimized native library for computing checksums, if that library is available.

To enable native checksumming:

If you installed CDH from packages, the native checksumming library is installed and setup correctly. In such a case, no additional steps are required. Conversely, if you installed by other means, such as with tarballs, native checksumming may not be available due to missing shared objects. Finding the message "Unable to load native-hadoop library for your platform... using builtin-java classes where applicable" in the Impala logs indicates native checksumming may be unavailable. To enable native checksumming, you must build and install `libhadoop.so` (the Hadoop Native Library).

Configuring Impala to Work with ODBC

Third-party products can be designed to integrate with Impala using ODBC. For the best experience, ensure any third-party product you intend to use is supported. Verifying support includes checking that the versions of Impala,

ODBC, the operating system, and the third-party product have all been approved for use together. Before configuring your systems to use ODBC, download a connector. You may need to sign in and accept license agreements before accessing the pages required for downloading ODBC connectors.

Downloading the ODBC Driver



Important: As of late 2015, most business intelligence applications are certified with the 2.x ODBC drivers. Although the instructions on this page cover both the 2.x and 1.x drivers, expect to use the 2.x drivers exclusively for most ODBC applications connecting to Impala.

See the [documentation page](#) for installation instructions.

Configuring the ODBC Port

Versions 2.5 and 2.0 of the Cloudera ODBC Connector, currently certified for some but not all BI applications, use the HiveServer2 protocol, corresponding to Impala port 21050. Impala supports Kerberos authentication with all the supported versions of the driver, and requires ODBC 2.05.13 for Impala or higher for LDAP username/password authentication.

Version 1.x of the Cloudera ODBC Connector uses the original HiveServer1 protocol, corresponding to Impala port 21000.

Example of Setting Up an ODBC Application for Impala

To illustrate the outline of the setup process, here is a transcript of a session to set up all required drivers and a business intelligence application that uses the ODBC driver, under Mac OS X. Each .dmg file runs a GUI-based installer, first for the [underlying IODBC driver](#) needed for non-Windows systems, then for the Cloudera ODBC Connector, and finally for the BI tool itself.

```
$ ls -l
Cloudera-ODBC-Driver-for-Impala-Install-Guide.pdf
BI_Tool_Installer.dmg
iodbc-sdk-3.52.7-macosx-10.5.dmg
ClouderaImpalaODBC.dmg
$ open iodbc-sdk-3.52.7-macosx-10.dmg
Install the IODBC driver using its installer
$ open ClouderaImpalaODBC.dmg
Install the Cloudera ODBC Connector using its installer
$ installer_dir=$(pwd)
$ cd /opt/cloudera/impalaodbc
$ ls -l
Cloudera ODBC Driver for Impala Install Guide.pdf
Readme.txt
Setup
lib
ErrorMessages
Release Notes.txt
Tools
$ cd Setup
$ ls
odbc.ini  odbcinst.ini
$ cp odbc.ini ~/.odbc.ini
$ vi ~/.odbc.ini
$ cat ~/.odbc.ini
[ODBC]
# Specify any global ODBC configuration here such as ODBC tracing.

[ODBC Data Sources]
Sample Cloudera Impala DSN=Cloudera ODBC Driver for Impala

[Sample Cloudera Impala DSN]

# Description: DSN Description.
# This key is not necessary and is only to give a description of the data source.
Description=Cloudera ODBC Driver for Impala DSN
```

```

# Driver: The location where the ODBC driver is installed to.
Driver=/opt/cloudera/impalaodbc/lib/universal/libclouderaimpalaodbc.dylib

# The DriverUnicodeEncoding setting is only used for SimbaDM
# When set to 1, SimbaDM runs in UTF-16 mode.
# When set to 2, SimbaDM runs in UTF-8 mode.
#DriverUnicodeEncoding=2

# Values for HOST, PORT, KrbFQDN, and KrbServiceName should be set here.
# They can also be specified on the connection string.
HOST=hostname.sample.example.com
PORT=21050
Schema=default

# The authentication mechanism.
# 0 - No authentication (NOSASL)
# 1 - Kerberos authentication (SASL)
# 2 - Username authentication (SASL)
# 3 - Username/password authentication (SASL)
# 4 - Username/password authentication with SSL (SASL)
# 5 - No authentication with SSL (NOSASL)
# 6 - Username/password authentication (NOSASL)
AuthMech=0

# Kerberos related settings.
KrbFQDN=
KrbRealm=
KrbServiceName=

# Username/password authentication with SSL settings.
UID=
PWD=
CAIssuedCertNamesMismatch=1
TrustedCerts=/opt/cloudera/impalaodbc/lib/universal/cacerts.pem

# Specify the proxy user ID to use.
#DelegationUID=

# General settings
TSaslTransportBufSize=1000
RowsFetchedPerBlock=10000
SocketTimeout=0
StringColumnLength=32767
UseNativeQuery=0
$ pwd
/opt/cloudera/impalaodbc/Setup
$ cd $installer_dir
$ open BI_Tool_Installer.dmg
Install the BI tool using its installer
$ ls /Applications | grep BI_Tool
BI_Tool.app
$ open -a BI_Tool.app
In the BI tool, connect to a data source using port 21050

```

Notes about JDBC and ODBC Interaction with Impala SQL Features

Most Impala SQL features work equivalently through the `impala-shell` interpreter of the JDBC or ODBC APIs. The following are some exceptions to keep in mind when switching between the interactive shell and applications using the APIs:



Note: If your JDBC or ODBC application connects to Impala through a load balancer such as `haproxy`, be cautious about reusing the connections. If the load balancer has set up connection timeout values, either check the connection frequently so that it never sits idle longer than the load balancer timeout value, or check the connection validity before using it and create a new one if the connection has been closed.

Configuring Impala to Work with JDBC

Impala supports the standard JDBC interface, allowing access from commercial Business Intelligence tools and custom software written in Java or other programming languages. The JDBC driver allows you to access Impala from a Java program that you write, or a Business Intelligence or similar tool that uses JDBC to communicate with various database products.

Setting up a JDBC connection to Impala involves the following steps:

- Verifying the communication port where the Impala daemons in your cluster are listening for incoming JDBC requests.
- Installing the JDBC driver on every system that runs the JDBC-enabled application.
- Specifying a connection string for the JDBC application to access one of the servers running the `impalad` daemon, with the appropriate security settings.

Configuring the JDBC Port

The default port used by JDBC 2.0 and later (as well as ODBC 2.x) is 21050. Impala server accepts JDBC connections through this same port 21050 by default. Make sure this port is available for communication with other hosts on your network, for example, that it is not blocked by firewall software. If your JDBC client software connects to a different port, specify that alternative port number with the `--hs2_port` option when starting `impalad`. See [Starting Impala](#) on page 44 for details about Impala startup options. See [Ports Used by Impala](#) on page 639 for information about all ports used for communication between Impala and clients or between Impala components.

Choosing the JDBC Driver

In Impala 2.0 and later, you have the choice between the Cloudera JDBC Connector and the Hive 0.13 JDBC driver. Cloudera recommends using the Cloudera JDBC Connector where practical.

If you are already using JDBC applications with an earlier Impala release, you must update your JDBC driver to one of these choices, because the Hive 0.12 driver that was formerly the only choice is not compatible with Impala 2.0 and later.

Both the Cloudera JDBC 2.5 Connector and the Hive JDBC driver provide a substantial speed increase for JDBC applications with Impala 2.0 and higher, for queries that return large result sets.

Enabling Impala JDBC Support on Client Systems

Using the Cloudera JDBC Connector (recommended)

You download and install the Cloudera JDBC 2.5 connector on any Linux, Windows, or Mac system where you intend to run JDBC-enabled applications. From the [Cloudera Connectors download page](#), you choose the appropriate protocol (JDBC or ODBC) and target product (Impala or Hive). The ease of downloading and installing on non-CDH systems makes this connector a convenient choice for organizations with heterogeneous environments.

Using the Hive JDBC Driver

You install the Hive JDBC driver (`hive-jdbc` package) through the Linux package manager, on hosts within the CDH cluster. The driver consists of several Java JAR files. The same driver can be used by Impala and Hive.

To get the JAR files, install the Hive JDBC driver on each CDH-enabled host in the cluster that will run JDBC applications. Follow the instructions for [CDH 5](#).



Note: The latest JDBC driver, corresponding to Hive 0.13, provides substantial performance improvements for Impala queries that return large result sets. Impala 2.0 and later are compatible with the Hive 0.13 driver. If you already have an older JDBC driver installed, and are running Impala 2.0 or higher, consider upgrading to the latest Hive JDBC driver for best performance with JDBC applications.

If you are using JDBC-enabled applications on hosts outside the CDH cluster, you cannot use the CDH install procedure on the non-CDH hosts. Install the JDBC driver on at least one CDH host using the preceding procedure. Then download the JAR files to each client machine that will use JDBC with Impala:

```
commons-logging-X.X.X.jar
hadoop-common.jar
hive-common-X.XX.X-cdhX.X.X.jar
hive-jdbc-X.XX.X-cdhX.X.X.jar
hive-metastore-X.XX.X-cdhX.X.X.jar
hive-service-X.XX.X-cdhX.X.X.jar
httpclient-X.X.X.jar
httpcore-X.X.X.jar
libfb303-X.X.X.jar
libthrift-X.X.X.jar
log4j-X.X.XX.jar
slf4j-api-X.X.X.jar
slf4j-log4jXX-X.X.X.jar
```

To enable JDBC support for Impala on the system where you run the JDBC application:

1. Download the JAR files listed above to each client machine.



Note: For Maven users, see [this sample github page](#) for an example of the dependencies you could add to a `pom` file instead of downloading the individual JARs.

2. Store the JAR files in a location of your choosing, ideally a directory already referenced in your `CLASSPATH` setting. For example:

- On Linux, you might use a location such as `/opt/jars/`.
- On Windows, you might use a subdirectory underneath `C:\Program Files`.

3. To successfully load the Impala JDBC driver, client programs must be able to locate the associated JAR files. This often means setting the `CLASSPATH` for the client process to include the JARs. Consult the documentation for your JDBC client for more details on how to install new JDBC drivers, but some examples of how to set `CLASSPATH` variables include:

- On Linux, if you extracted the JARs to `/opt/jars/`, you might issue the following command to prepend the JAR files path to an existing classpath:

```
export CLASSPATH=/opt/jars/*.jar:$CLASSPATH
```

- On Windows, use the **System Properties** control panel item to modify the **Environment Variables** for your system. Modify the environment variables to include the path to which you extracted the files.



Note: If the existing `CLASSPATH` on your client machine refers to some older version of the Hive JARs, ensure that the new JARs are the first ones listed. Either put the new JAR files earlier in the listings, or delete the other references to Hive JAR files.

Establishing JDBC Connections

The JDBC driver class depends on which driver you select.



Note: If your JDBC or ODBC application connects to Impala through a load balancer such as `haproxy`, be cautious about reusing the connections. If the load balancer has set up connection timeout values, either check the connection frequently so that it never sits idle longer than the load balancer timeout value, or check the connection validity before using it and create a new one if the connection has been closed.

Using the Cloudera JDBC Connector (recommended)

Depending on the level of the JDBC API your application is targeting, you can use the following fully-qualified class names (FQCNs):

- `com.cloudera.impala.jdbc41.Driver`
- `com.cloudera.impala.jdbc41.DataSource`
- `com.cloudera.impala.jdbc4.Driver`
- `com.cloudera.impala.jdbc4.DataSource`
- `com.cloudera.impala.jdbc3.Driver`
- `com.cloudera.impala.jdbc3.DataSource`

The connection string has the following format:

```
jdbc:impala://Host:Port[/Schema];Property1=Value;Property2=Value;...
```

The `port` value is typically 21050 for Impala.

For full details about the classes and the connection string (especially the property values available for the connection string), download the appropriate driver documentation for your platform from [the Impala JDBC Connector download page](#).

Using the Hive JDBC Driver

For example, with the Hive JDBC driver, the class name is `org.apache.hive.jdbc.HiveDriver`. Once you have configured Impala to work with JDBC, you can establish connections between the two. To do so for a cluster that does not use Kerberos authentication, use a connection string of the form `jdbc:hive2://host:port/;auth=noSasl`. For example, you might use:

```
jdbc:hive2://myhost.example.com:21050/;auth=noSasl
```

To connect to an instance of Impala that requires Kerberos authentication, use a connection string of the form `jdbc:hive2://host:port/;principal=principal_name`. The principal must be the same user principal you used when starting Impala. For example, you might use:

```
jdbc:hive2://myhost.example.com:21050/;principal=impala/myhost.example.com@H2.EXAMPLE.COM
```

To connect to an instance of Impala that requires LDAP authentication, use a connection string of the form `jdbc:hive2://host:port/db_name;user=ldap_userid;password=ldap_password`. For example, you might use:

```
jdbc:hive2://myhost.example.com:21050/test_db;user=fred;password=xyz123
```



Note:

Prior to CDH 5.7 / Impala 2.5, the Hive JDBC driver did not support connections that use both Kerberos authentication and SSL encryption. If your cluster is running an older release that has this restriction, to use both of these security features with Impala through a JDBC application, use the [Cloudera JDBC Connector](#) as the JDBC driver.

Notes about JDBC and ODBC Interaction with Impala SQL Features

Most Impala SQL features work equivalently through the `impala-shell` interpreter of the JDBC or ODBC APIs. The following are some exceptions to keep in mind when switching between the interactive shell and applications using the APIs:

- **Complex type considerations:**

- Queries involving the complex types (`ARRAY`, `STRUCT`, and `MAP`) require notation that might not be available in all levels of JDBC and ODBC drivers. If you have trouble querying such a table due to the driver level or inability to edit the queries used by the application, you can create a view that exposes a “flattened” version of the complex columns and point the application at the view. See [Complex Types \(CDH 5.5 or higher only\)](#) on page 167 for details.
- The complex types available in CDH 5.5 / Impala 2.3 and higher are supported by the JDBC `getColumns()` API. Both `MAP` and `ARRAY` are reported as the JDBC SQL Type `ARRAY`, because this is the closest matching Java SQL type. This behavior is consistent with Hive. `STRUCT` types are reported as the JDBC SQL Type `STRUCT`.

To be consistent with Hive's behavior, the `TYPE_NAME` field is populated with the primitive type name for scalar types, and with the full `toSql()` for complex types. The resulting type names are somewhat inconsistent, because nested types are printed differently than top-level types. For example, the following list shows how `toSql()` for Impala types are translated to `TYPE_NAME` values:

```

DECIMAL(10,10)      becomes  DECIMAL
CHAR(10)            becomes  CHAR
VARCHAR(10)         becomes  VARCHAR
ARRAY<DECIMAL(10,10)> becomes  ARRAY<DECIMAL(10,10)>
ARRAY<CHAR(10)>      becomes  ARRAY<CHAR(10)>
ARRAY<VARCHAR(10)>  becomes  ARRAY<VARCHAR(10)>

```

Kudu Considerations for DML Statements

Currently, Impala `INSERT`, `UPDATE`, or other DML statements issued through the JDBC interface against a Kudu table do not return JDBC error codes for conditions such as duplicate primary key columns. Therefore, for applications that issue a high volume of DML statements, prefer to use the Kudu Java API directly rather than a JDBC application.

Upgrading Impala

Upgrading Impala involves stopping Impala services, using your operating system's package management tool to upgrade Impala to the latest version, and then restarting Impala services.



Note:

- Each version of CDH 5 has an associated version of Impala. When you upgrade from CDH 4 to CDH 5, you get whichever version of Impala comes with the associated level of CDH. Depending on the version of Impala you were running on CDH 4, this could install a lower level of Impala on CDH 5. For example, if you upgrade to CDH 5.0 from CDH 4 plus Impala 1.4, the CDH 5.0 installation comes with Impala 1.3. Always check the associated level of Impala before upgrading to a specific version of CDH 5. Where practical, upgrade from CDH 4 to the latest CDH 5, which also has the latest Impala.
- When you upgrade Impala, also upgrade Cloudera Manager if necessary:
 - Users running Impala on CDH 5 must upgrade to Cloudera Manager 5.0.0 or higher.
 - Users running Impala on CDH 4 must upgrade to Cloudera Manager 4.8 or higher. Cloudera Manager 4.8 includes management support for the Impala catalog service, and is the minimum Cloudera Manager version you can use.
 - Cloudera Manager is continually updated with configuration settings for features introduced in the latest Impala releases.
- If you are upgrading from CDH 5 beta to CDH 5.0 production, make sure you are using the appropriate CDH 5 repositories shown on the [CDH version and packaging](#) page, then follow the procedures throughout the rest of this section.
- Every time you upgrade to a new major or minor Impala release, see [Incompatible Changes and Limitations in Apache Impala](#) on page 686 in the *Release Notes* for any changes needed in your source code, startup scripts, and so on.
- Also check [Known Issues and Workarounds in Impala](#) on page 697 in the *Release Notes* for any issues or limitations that require workarounds.

Upgrading Impala through Cloudera Manager - Parcels

Parcels are an alternative binary distribution format available in Cloudera Manager 4.5 and higher.



Important: In CDH 5, there is not a separate Impala parcel; Impala is part of the main CDH 5 parcel. Each level of CDH 5 has a corresponding version of Impala, and you upgrade Impala by upgrading CDH. See the [CDH 5 upgrade instructions](#) and choose the instructions for parcels. The remainder of this section only covers parcel upgrades for Impala under CDH 4.

To upgrade Impala for CDH 4 in a Cloudera Managed environment, using parcels:

1. If you originally installed using packages and now are switching to parcels, remove all the Impala-related packages first. You can check which packages are installed using one of the following commands, depending on your operating system:

```
rpm -qa # RHEL, Oracle Linux, CentOS, Debian
dpkg --get-selections # Debian
```


and then remove the packages using one of the following commands:

```
sudo yum remove pkg_names # RHEL, Oracle Linux, CentOS
sudo zypper remove pkg_names # SLES
sudo apt-get purge pkg_names # Ubuntu, Debian
```

2. Connect to the Cloudera Manager Admin Console.
3. Go to the **Hosts > Parcels** tab. You should see a parcel with a newer version of Impala that you can upgrade to.
4. Click **Download**, then **Distribute**. (The button changes as each step completes.)
5. Click **Activate**.
6. When prompted, click **Restart** to restart the Impala service.

Upgrading Impala through Cloudera Manager - Packages

To upgrade Impala in a Cloudera Managed environment, using packages:

1. Connect to the Cloudera Manager Admin Console.
2. In the **Services** tab, click the **Impala** service.
3. Click **Actions** and click **Stop**.
4. Use **one** of the following sets of commands to update Impala on each Impala node in your cluster:

For RHEL, Oracle Linux, or CentOS systems:

```
$ sudo yum update impala
$ sudo yum update hadoop-lzo-cdh4 # Optional; if this package is already installed
```

For SUSE systems:

```
$ sudo zypper update impala
$ sudo zypper update hadoop-lzo-cdh4 # Optional; if this package is already installed
```

For Debian or Ubuntu systems:

```
$ sudo apt-get install impala
$ sudo apt-get install hadoop-lzo-cdh4 # Optional; if this package is already installed
```

5. Use **one** of the following sets of commands to update Impala shell on each node on which it is installed:

For RHEL, Oracle Linux, or CentOS systems:

```
$ sudo yum update impala-shell
```

For SUSE systems:

```
$ sudo zypper update impala-shell
```

For Debian or Ubuntu systems:

```
$ sudo apt-get install impala-shell
```

6. Connect to the Cloudera Manager Admin Console.
7. In the **Services** tab, click the Impala service.
8. Click **Actions** and click **Start**.

Upgrading Impala without Cloudera Manager

To upgrade Impala on a cluster not managed by Cloudera Manager, run these Linux commands on the appropriate hosts in your cluster:

1. Stop Impala services.

a. Stop `impalad` on each Impala node in your cluster:

```
$ sudo service impala-server stop
```

b. Stop any instances of the state store in your cluster:

```
$ sudo service impala-state-store stop
```

c. Stop any instances of the catalog service in your cluster:

```
$ sudo service impala-catalog stop
```

2. Check if there are new recommended or required configuration settings to put into place in the configuration files, typically under `/etc/impala/conf`. See [Post-Installation Configuration for Impala](#) on page 32 for settings related to performance and scalability.

3. Use **one of the following sets of commands to update Impala on each Impala node in your cluster:**

For RHEL, Oracle Linux, or CentOS systems:

```
$ sudo yum update impala-server
$ sudo yum update hadoop-lzo-cdh4 # Optional; if this package is already installed
$ sudo yum update impala-catalog # New in Impala 1.2; do yum install when upgrading from 1.1.
```

For SUSE systems:

```
$ sudo zypper update impala-server
$ sudo zypper update hadoop-lzo-cdh4 # Optional; if this package is already installed
$ sudo zypper update impala-catalog # New in Impala 1.2; do zypper install when upgrading from 1.1.
```

For Debian or Ubuntu systems:

```
$ sudo apt-get install impala-server
$ sudo apt-get install hadoop-lzo-cdh4 # Optional; if this package is already installed
$ sudo apt-get install impala-catalog # New in Impala 1.2.
```

4. Use **one of the following sets of commands to update Impala shell on each node on which it is installed:**

For RHEL, Oracle Linux, or CentOS systems:

```
$ sudo yum update impala-shell
```

For SUSE systems:

```
$ sudo zypper update impala-shell
```

For Debian or Ubuntu systems:

```
$ sudo apt-get install impala-shell
```

5. Depending on which release of Impala you are upgrading from, you might find that the symbolic links `/etc/impala/conf` and `/usr/lib/impala/sbin` are missing. If so, see [Known Issues and Workarounds in Impala](#) on page 697 for the procedure to work around this problem.

6. Restart Impala services:

- a. Restart the Impala state store service on the desired nodes in your cluster. Expect to see a process named `statestored` if the service started successfully.

```
$ sudo service impala-state-store start
$ ps ax | grep [s]tatestored
6819 ?          Sl      0:07 /usr/lib/impala/sbin/statestored -log_dir=/var/log/impala
-state_store_port=24000
```

Restart the state store service *before* the Impala server service to avoid “Not connected” errors when you run `impala-shell`.

- b. Restart the Impala catalog service on whichever host it runs on in your cluster. Expect to see a process named `catalogd` if the service started successfully.

```
$ sudo service impala-catalog restart
$ ps ax | grep [c]atalogd
6068 ?          Sl      4:06 /usr/lib/impala/sbin/catalogd
```

- c. Restart the Impala daemon service on each node in your cluster. Expect to see a process named `impalad` if the service started successfully.

```
$ sudo service impala-server start
$ ps ax | grep [i]mpalad
7936 ?          Sl      0:12 /usr/lib/impala/sbin/impalad -log_dir=/var/log/impala
-state_store_port=24000 -use_statestore
-state_store_host=127.0.0.1 -be_port=22000
```



Note:

If the services did not start successfully (even though the `sudo service` command might display [OK]), check for errors in the Impala log file, typically in `/var/log/impala`.

Starting Impala

To activate Impala if it is installed but not yet started:

1. Set any necessary configuration options for the Impala services. See [Modifying Impala Startup Options](#) on page 45 for details.
2. Start one instance of the Impala statestore. The statestore helps Impala to distribute work efficiently, and to continue running in the event of availability problems for other Impala nodes. If the statestore becomes unavailable, Impala continues to function.
3. Start one instance of the Impala catalog service.
4. Start the main Impala daemon services.

Once Impala is running, you can conduct interactive experiments using the instructions in [Impala Tutorials](#) on page 49 and try [Using the Impala Shell \(impala-shell Command\)](#) on page 511.

Starting Impala through Cloudera Manager

If you installed Impala with Cloudera Manager, use Cloudera Manager to start and stop services. The Cloudera Manager GUI is a convenient way to check that all services are running, to set configuration options using form fields in a browser, and to spot potential issues such as low disk space before they become serious. Cloudera Manager automatically starts all the Impala-related services as a group, in the correct order. See [the Cloudera Manager Documentation](#) for details.



Note:

In CDH 5.7 / Impala 2.5 and higher, Impala UDFs and UDAs written in C++ are persisted in the metastore database. Java UDFs are also persisted, if they were created with the new `CREATE FUNCTION` syntax for Java UDFs, where the Java function argument and return types are omitted. Java-based UDFs created with the old `CREATE FUNCTION` syntax do not persist across restarts because they are held in the memory of the `catalogd` daemon. Until you re-create such Java UDFs using the new `CREATE FUNCTION` syntax, you must reload those Java-based UDFs by running the original `CREATE FUNCTION` statements again each time you restart the `catalogd` daemon. Prior to CDH 5.7 / Impala 2.5, the requirement to reload functions after a restart applied to both C++ and Java functions.

Starting Impala from the Command Line

To start the Impala state store and Impala from the command line or a script, you can either use the `service` command or you can start the daemons directly through the `impalad`, `statestored`, and `catalogd` executables.

Start the Impala statestore and then start `impalad` instances. You can modify the values the service initialization scripts use when starting the statestore and Impala by editing `/etc/default/impala`.

Start the statestore service using a command similar to the following:

```
$ sudo service impala-state-store start
```

Start the catalog service using a command similar to the following:

```
$ sudo service impala-catalog start
```

Start the Impala daemon services using a command similar to the following:

```
$ sudo service impala-server start
```

**Note:**

In CDH 5.7 / Impala 2.5 and higher, Impala UDFs and UDAs written in C++ are persisted in the metastore database. Java UDFs are also persisted, if they were created with the new `CREATE FUNCTION` syntax for Java UDFs, where the Java function argument and return types are omitted. Java-based UDFs created with the old `CREATE FUNCTION` syntax do not persist across restarts because they are held in the memory of the `catalogd` daemon. Until you re-create such Java UDFs using the new `CREATE FUNCTION` syntax, you must reload those Java-based UDFs by running the original `CREATE FUNCTION` statements again each time you restart the `catalogd` daemon. Prior to CDH 5.7 / Impala 2.5, the requirement to reload functions after a restart applied to both C++ and Java functions.

If any of the services fail to start, review:

- [Reviewing Impala Logs](#) on page 628
- [Troubleshooting Impala](#) on page 631

Modifying Impala Startup Options

The configuration options for the Impala-related daemons let you choose which hosts and ports to use for the services that run on a single host, specify directories for logging, control resource usage and security, and specify other aspects of the Impala software.

Configuring Impala Startup Options through Cloudera Manager

If you manage your cluster through Cloudera Manager, configure the settings for all the Impala-related daemons by navigating to this page: **Clusters > Impala > Configuration > View and Edit**. See the Cloudera Manager documentation for [instructions about how to configure Impala through Cloudera Manager](#).

If the Cloudera Manager interface does not yet have a form field for a newly added option, or if you need to use special options for debugging and troubleshooting, the **Advanced** option page for each daemon includes one or more fields where you can enter option names directly. In Cloudera Manager 4, these fields are labelled **Safety Valve**; in Cloudera Manager 5, they are called **Advanced Configuration Snippet**. There is also a free-form field for query options, on the top-level **Impala Daemon** options page.

Configuring Impala Startup Options through the Command Line

When you run Impala in a non-Cloudera Manager environment, the Impala server, statestore, and catalog services start up using values provided in a defaults file, `/etc/default/impala`.

This file includes information about many resources used by Impala. Most of the defaults included in this file should be effective in most cases. For example, typically you would not change the definition of the `CLASSPATH` variable, but you would always set the address used by the statestore server. Some of the content you might modify includes:

```

IMPALA_STATE_STORE_HOST=127.0.0.1
IMPALA_STATE_STORE_PORT=24000
IMPALA_BACKEND_PORT=22000
IMPALA_LOG_DIR=/var/log/impala
IMPALA_CATALOG_SERVICE_HOST=...
IMPALA_STATE_STORE_HOST=...

export IMPALA_STATE_STORE_ARGS=${IMPALA_STATE_STORE_ARGS:- \
  -log_dir=${IMPALA_LOG_DIR} -state_store_port=${IMPALA_STATE_STORE_PORT}}
IMPALA_SERVER_ARGS=" \
-log_dir=${IMPALA_LOG_DIR} \
-catalog_service_host=${IMPALA_CATALOG_SERVICE_HOST} \
-state_store_port=${IMPALA_STATE_STORE_PORT} \
-use_statestore \
-state_store_host=${IMPALA_STATE_STORE_HOST} \
-be_port=${IMPALA_BACKEND_PORT}"
export ENABLE_CORE_DUMPS=${ENABLE_COREDUMPS:-false}

```

To use alternate values, edit the defaults file, then restart all the Impala-related services so that the changes take effect. Restart the Impala server using the following commands:

```
$ sudo service impala-server restart
Stopping Impala Server:           [ OK ]
Starting Impala Server:          [ OK ]
```

Restart the Impala statestore using the following commands:

```
$ sudo service impala-state-store restart
Stopping Impala State Store Server: [ OK ]
Starting Impala State Store Server: [ OK ]
```

Restart the Impala catalog service using the following commands:

```
$ sudo service impala-catalog restart
Stopping Impala Catalog Server:     [ OK ]
Starting Impala Catalog Server:     [ OK ]
```

Some common settings to change include:

- **Statestore address.** Cloudera recommends the statestore be on a separate host not running the `impalad` daemon. In that recommended configuration, the `impalad` daemon cannot refer to the statestore server using the loopback address. If the statestore is hosted on a machine with an IP address of `192.168.0.27`, change:

```
IMPALA_STATE_STORE_HOST=127.0.0.1
```

to:

```
IMPALA_STATE_STORE_HOST=192.168.0.27
```

- **Catalog server address (including both the hostname and the port number).** Update the value of the `IMPALA_CATALOG_SERVICE_HOST` variable. Cloudera recommends the catalog server be on the same host as the statestore. In that recommended configuration, the `impalad` daemon cannot refer to the catalog server using the loopback address. If the catalog service is hosted on a machine with an IP address of `192.168.0.27`, add the following line:

```
IMPALA_CATALOG_SERVICE_HOST=192.168.0.27:26000
```

The `/etc/default/impala` defaults file currently does not define an `IMPALA_CATALOG_ARGS` environment variable, but if you add one it will be recognized by the service startup/shutdown script. Add a definition for this variable to `/etc/default/impala` and add the option `-catalog_service_host=hostname`. If the port is different than the default `26000`, also add the option `-catalog_service_port=port`.

- **Memory limits.** You can limit the amount of memory available to Impala. For example, to allow Impala to use no more than 70% of system memory, change:

```
export IMPALA_SERVER_ARGS=${IMPALA_SERVER_ARGS:- \
  -log_dir=${IMPALA_LOG_DIR} \
  -state_store_port=${IMPALA_STATE_STORE_PORT} \
  -use_statestore -state_store_host=${IMPALA_STATE_STORE_HOST} \
  -be_port=${IMPALA_BACKEND_PORT}}
```

to:

```
export IMPALA_SERVER_ARGS=${IMPALA_SERVER_ARGS:- \
  -log_dir=${IMPALA_LOG_DIR} -state_store_port=${IMPALA_STATE_STORE_PORT} \
  -use_statestore -state_store_host=${IMPALA_STATE_STORE_HOST} \
  -be_port=${IMPALA_BACKEND_PORT} -mem_limit=70%}
```

You can specify the memory limit using absolute notation such as 500m or 2G, or as a percentage of physical memory such as 60%.



Note: Queries that exceed the specified memory limit are aborted. Percentage limits are based on the physical memory of the machine and do not consider cgroups.

- Core dump enablement. To enable core dumps on systems not managed by Cloudera Manager, change:

```
export ENABLE_CORE_DUMPS=${ENABLE_COREDUMPS:-false}
```

to:

```
export ENABLE_CORE_DUMPS=${ENABLE_COREDUMPS:-true}
```

On systems managed by Cloudera Manager, enable the **Enable Core Dump** setting for the Impala service.



Note:

- The location of core dump files may vary according to your operating system configuration.
- Other security settings may prevent Impala from writing core dumps even when this option is enabled.
- On systems managed by Cloudera Manager, the default location for core dumps is on a temporary filesystem, which can lead to out-of-space issues if the core dumps are large, frequent, or not removed promptly. To specify an alternative location for the core dumps, filter the Impala configuration settings to find the `core_dump_dir` option, which is available in Cloudera Manager 5.4.3 and higher. This option lets you specify a different directory for core dumps for each of the Impala-related daemons.

- Authorization using the open source Sentry plugin. Specify the `-server_name` and `-authorization_policy_file` options as part of the `IMPALA_SERVER_ARGS` and `IMPALA_STATE_STORE_ARGS` settings to enable the core Impala support for authentication. See [Starting the impalad Daemon with Sentry Authorization Enabled](#) on page 106 for details.
- Auditing for successful or blocked Impala queries, another aspect of security. Specify the `-audit_event_log_dir=directory_path` option and optionally the `-max_audit_event_log_file_size=number_of_queries` and `-abort_on_failed_audit_event` options as part of the `IMPALA_SERVER_ARGS` settings, for each Impala node, to enable and customize auditing. See [Auditing Impala Operations](#) on page 123 for details.
- Password protection for the Impala web UI, which listens on port 25000 by default. This feature involves adding some or all of the `--webserver_password_file`, `--webserver_authentication_domain`, and `--webserver_certificate_file` options to the `IMPALA_SERVER_ARGS` and `IMPALA_STATE_STORE_ARGS` settings. See [Security Guidelines for Impala](#) on page 100 for details.
- Another setting you might add to `IMPALA_SERVER_ARGS` is a comma-separated list of query options and values:

```
-default_query_options='option=value,option=value,...'
```

These options control the behavior of queries performed by this `impalad` instance. The option values you specify here override the default values for [Impala query options](#), as shown by the `SET` statement in `impala-shell`.

- During troubleshooting, Cloudera Support might direct you to change other values, particularly for `IMPALA_SERVER_ARGS`, to work around issues or gather debugging information.

**Note:**

These startup options for the `impalad` daemon are different from the command-line options for the `impala-shell` command. For the `impala-shell` options, see [impala-shell Configuration Options](#) on page 511.

Checking the Values of Impala Configuration Options

You can check the current runtime value of all these settings through the Impala web interface, available by default at `http://impala_hostname:25000/varz` for the `impalad` daemon, `http://impala_hostname:25010/varz` for the `statedored` daemon, or `http://impala_hostname:25020/varz` for the `catalogd` daemon. In the Cloudera Manager interface, you can see the link to the appropriate **service_name Web UI** page when you look at the status page for a specific daemon on a specific host.

Startup Options for `impalad` Daemon

The `impalad` daemon implements the main Impala service, which performs query processing and reads and writes the data files.

Startup Options for `statedored` Daemon

The `statedored` daemon implements the Impala statestore service, which monitors the availability of Impala services across the cluster, and handles situations such as nodes becoming unavailable or becoming available again.

Startup Options for `catalogd` Daemon

The `catalogd` daemon implements the Impala catalog service, which broadcasts metadata changes to all the Impala nodes when Impala creates a table, inserts data, or performs other kinds of DDL and DML operations.

Use `--load_catalog_in_background` option to control when the metadata of a table is loaded.

- If set to `false`, the metadata of a table will be loaded when it is referenced for the first time. This means that the first run of a particular query can be slower than subsequent runs. Starting in Impala 2.2, the default for `load_catalog_in_background` is `false`.
- If set to `true`, the catalog service will aim to load metadata for a table even if no query needed that metadata. So metadata will possibly be already loaded when the first query that would need it is run. However, for the following reasons, we recommend not to set the option to `true`.
 - Both on startup and after a global or a table-specific metadata invalidate, the metadata load for tables that actual queries can get backed up because the catalog service could spend time loading metadata for another table. During such load, a request for prioritized load by a query will be put on hold, and this can lead to seemingly random long-running queries that are difficult for you to diagnose.
 - Impala may load metadata for tables that are possibly never used, increasing catalog size and consequently memory usage for both catalog and `impalad`.

Impala Tutorials

This section includes tutorial scenarios that demonstrate how to begin using Impala once the software is installed. It focuses on techniques for loading data, because once you have some data in tables and can query that data, you can quickly progress to more advanced Impala features.



Note:

Where practical, the tutorials take you from “ground zero” to having the desired Impala tables and data. In some cases, you might need to download additional files from outside sources, set up additional software components, modify commands or scripts to fit your own configuration, or substitute your own sample data.

Before trying these tutorial lessons, install Impala using one of these procedures:

- If you already have a CDH environment set up and just need to add Impala to it, follow the installation process described in [Installing Impala](#) on page 29. Make sure to also install the Hive metastore service if you do not already have Hive configured.
- To set up Impala and all its prerequisites at once, in a minimal configuration that you can use for small-scale experiments, set up the Cloudera QuickStart VM, which includes CDH and Impala on CentOS. Use this single-node VM to try out basic SQL functionality, not anything related to performance and scalability. For more information, see [the Cloudera QuickStart VM](#).

Tutorials for Getting Started

These tutorials demonstrate the basics of using Impala. They are intended for first-time users, and for trying out Impala on any new cluster to make sure the major components are working correctly.

Explore a New Impala Instance

This tutorial demonstrates techniques for finding your way around the tables and databases of an unfamiliar (possibly empty) Impala instance.

When you connect to an Impala instance for the first time, you use the `SHOW DATABASES` and `SHOW TABLES` statements to view the most common types of objects. Also, call the `version()` function to confirm which version of Impala you are running; the version number is important when consulting documentation and dealing with support issues.

A completely empty Impala instance contains no tables, but still has two databases:

- `default`, where new tables are created when you do not specify any other database.
- `_impala_builtins`, a system database used to hold all the built-in functions.

The following example shows how to see the available databases, and the tables in each. If the list of databases or tables is long, you can use wildcard notation to locate specific databases or tables based on their names.

```
$ impala-shell -i localhost --quiet
Starting Impala Shell without Kerberos authentication
Welcome to the Impala shell. Press TAB twice to see a list of available commands.

Copyright (c) 2012 Cloudera, Inc. All rights reserved.

(Shell build version: Impala Shell v...
[localhost:21000] > select version();
+-----+
| version()
+-----+
| impalad version ...
| Built on ...
```

```

+-----+
[localhost:21000] > show databases;
+-----+
| name |
+-----+
|_impala_builtins
|ctas
|d1
|d2
|d3
|default
|explain_plans
|external_table
|file_formats
|tpc
+-----+
[localhost:21000] > select current_database();
+-----+
| current_database() |
+-----+
| default |
+-----+
[localhost:21000] > show tables;
+-----+
| name |
+-----+
| ex_t |
| t1 |
+-----+
[localhost:21000] > show tables in d3;
[localhost:21000] > show tables in tpc;
+-----+
| name |
+-----+
|city
|customer
|customer_address
|customer_demographics
|household_demographics
|item
|promotion
|store
|store2
|store_sales
|ticket_view
|time_dim
|tpc_tables
+-----+
[localhost:21000] > show tables in tpc like 'customer*';
+-----+
| name |
+-----+
|customer
|customer_address
|customer_demographics
+-----+

```

Once you know what tables and databases are available, you descend into a database with the `USE` statement. To understand the structure of each table, you use the `DESCRIBE` command. Once inside a database, you can issue statements such as `INSERT` and `SELECT` that operate on particular tables.

The following example explores a database named `TPC` whose name we learned in the previous example. It shows how to filter the table names within a database based on a search string, examine the columns of a table, and run queries to examine the characteristics of the table data. For example, for an unfamiliar table you might want to know the number of rows, the number of different values for a column, and other properties such as whether the column

contains any NULL values. When sampling the actual data values from a table, use a LIMIT clause to avoid excessive output if the table contains more rows or distinct values than you expect.

```
[localhost:21000] > use tpc;
[localhost:21000] > show tables like '*view*';
+-----+
| name |
+-----+
| ticket_view |
+-----+
[localhost:21000] > describe city;
+-----+-----+-----+
| name | type | comment |
+-----+-----+-----+
| id | int | |
| name | string | |
| countrycode | string | |
| district | string | |
| population | int | |
+-----+-----+-----+
[localhost:21000] > select count(*) from city;
+-----+
| count(*) |
+-----+
| 0 |
+-----+
[localhost:21000] > desc customer;
+-----+-----+-----+
| name | type | comment |
+-----+-----+-----+
| c_customer_sk | int | |
| c_customer_id | string | |
| c_current_demo_sk | int | |
| c_current_hdemo_sk | int | |
| c_current_addr_sk | int | |
| c_first_shipto_date_sk | int | |
| c_first_sales_date_sk | int | |
| c_salutation | string | |
| c_first_name | string | |
| c_last_name | string | |
| c_preferred_cust_flag | string | |
| c_birth_day | int | |
| c_birth_month | int | |
| c_birth_year | int | |
| c_birth_country | string | |
| c_login | string | |
| c_email_address | string | |
| c_last_review_date | string | |
+-----+-----+-----+
[localhost:21000] > select count(*) from customer;
+-----+
| count(*) |
+-----+
| 100000 |
+-----+
[localhost:21000] > select count(distinct c_birth_month) from customer;
+-----+
| count(distinct c_birth_month) |
+-----+
| 12 |
+-----+
[localhost:21000] > select count(*) from customer where c_email_address is null;
+-----+
| count(*) |
+-----+
| 0 |
+-----+
[localhost:21000] > select distinct c_salutation from customer limit 10;
+-----+
| c_salutation |
+-----+
| Mr. |
| Ms. |
+-----+
```

```

| Dr.          |
| Miss        |
| Sir         |
| Mrs.       |
+-----+

```

When you graduate from read-only exploration, you use statements such as `CREATE DATABASE` and `CREATE TABLE` to set up your own database objects.

The following example demonstrates creating a new database holding a new table. Although the last example ended inside the TPC database, the new `EXPERIMENTS` database is not nested inside TPC; all databases are arranged in a single top-level list.

```

[localhost:21000] > create database experiments;
[localhost:21000] > show databases;
+-----+
| name          |
+-----+
| _impala_builtins
| ctas
| d1
| d2
| d3
| default
| experiments
| explain_plans
| external_table
| file_formats
| tpc
+-----+
[localhost:21000] > show databases like 'exp*';
+-----+
| name          |
+-----+
| experiments
| explain_plans
+-----+

```

The following example creates a new table, `T1`. To illustrate a common mistake, it creates this table inside the wrong database, the TPC database where the previous example ended. The `ALTER TABLE` statement lets you move the table to the intended database, `EXPERIMENTS`, as part of a rename operation. The `USE` statement is always needed to switch to a new database, and the `current_database()` function confirms which database the session is in, to avoid these kinds of mistakes.

```

[localhost:21000] > create table t1 (x int);
[localhost:21000] > show tables;
+-----+
| name          |
+-----+
| city
| customer
| customer_address
| customer_demographics
| household_demographics
| item
| promotion
| store
| store2
| store_sales
| t1
| ticket_view
| time_dim
| tpc_tables
+-----+
[localhost:21000] > select current_database();
+-----+
| current_database() |
+-----+

```

```

+-----+
| tpc   |
+-----+
[localhost:21000] > alter table t1 rename to experiments.t1;
[localhost:21000] > use experiments;
[localhost:21000] > show tables;
+-----+
| name  |
+-----+
| t1    |
+-----+
[localhost:21000] > select current_database();
+-----+
| current_database() |
+-----+
| experiments        |
+-----+

```

For your initial experiments with tables, you can use ones with just a few columns and a few rows, and text-format data files.



Note: As you graduate to more realistic scenarios, you will use more elaborate tables with many columns, features such as partitioning, and file formats such as Parquet. When dealing with realistic data volumes, you will bring in data using `LOAD DATA` or `INSERT ... SELECT` statements to operate on millions or billions of rows at once.

The following example sets up a couple of simple tables with a few rows, and performs queries involving sorting, aggregate functions and joins.

```

[localhost:21000] > insert into t1 values (1), (3), (2), (4);
[localhost:21000] > select x from t1 order by x desc;
+----+
| x   |
+----+
| 4   |
| 3   |
| 2   |
| 1   |
+----+
[localhost:21000] > select min(x), max(x), sum(x), avg(x) from t1;
+-----+-----+-----+-----+
| min(x) | max(x) | sum(x) | avg(x) |
+-----+-----+-----+-----+
| 1       | 4       | 10      | 2.5     |
+-----+-----+-----+-----+

[localhost:21000] > create table t2 (id int, word string);
[localhost:21000] > insert into t2 values (1, "one"), (3, "three"), (5, 'five');
[localhost:21000] > select word from t1 join t2 on (t1.x = t2.id);
+-----+
| word  |
+-----+
| one   |
| three |
+-----+

```

After completing this tutorial, you should now know:

- How to tell which version of Impala is running on your system.
- How to find the names of databases in an Impala instance, either displaying the full list or searching for specific names.
- How to find the names of tables in an Impala database, either displaying the full list or searching for specific names.
- How to switch between databases and check which database you are currently in.
- How to learn the column names and types of a table.
- How to create databases and tables, insert small amounts of test data, and run simple queries.

Load CSV Data from Local Files

This scenario illustrates how to create some very small tables, suitable for first-time users to experiment with Impala SQL features. `TAB1` and `TAB2` are loaded with data from files in HDFS. A subset of data is copied from `TAB1` into `TAB3`.

Populate HDFS with the data you want to query. To begin this process, create one or more new subdirectories underneath your user directory in HDFS. The data for each table resides in a separate subdirectory. Substitute your own username for `cloudera` where appropriate. This example uses the `-p` option with the `mkdir` operation to create any necessary parent directories if they do not already exist.

```
$ whoami
cloudera
$ hdfs dfs -ls /user
Found 3 items
drwxr-xr-x  - cloudera cloudera          0 2013-04-22 18:54 /user/cloudera
drwxrwx---  - mapred  mapred            0 2013-03-15 20:11 /user/history
drwxr-xr-x  - hue    supergroup       0 2013-03-15 20:10 /user/hive

$ hdfs dfs -mkdir -p /user/cloudera/sample_data/tab1 /user/cloudera/sample_data/tab2
```

Here is some sample data, for two tables named `TAB1` and `TAB2`.

Copy the following content to `.csv` files in your local filesystem:

`tab1.csv`:

```
1,true,123.123,2012-10-24 08:55:00
2,false,1243.5,2012-10-25 13:40:00
3,false,24453.325,2008-08-22 09:33:21.123
4,false,243423.325,2007-05-12 22:32:21.33454
5,true,243.325,1953-04-22 09:11:33
```

`tab2.csv`:

```
1,true,12789.123
2,false,1243.5
3,false,24453.325
4,false,2423.3254
5,true,243.325
60,false,243565423.325
70,true,243.325
80,false,243423.325
90,true,243.325
```

Put each `.csv` file into a separate HDFS directory using commands like the following, which use paths available in the Impala Demo VM:

```
$ hdfs dfs -put tab1.csv /user/cloudera/sample_data/tab1
$ hdfs dfs -ls /user/cloudera/sample_data/tab1
Found 1 items
-rw-r--r--  1 cloudera cloudera          192 2013-04-02 20:08
/user/cloudera/sample_data/tab1/tab1.csv

$ hdfs dfs -put tab2.csv /user/cloudera/sample_data/tab2
$ hdfs dfs -ls /user/cloudera/sample_data/tab2
Found 1 items
-rw-r--r--  1 cloudera cloudera          158 2013-04-02 20:09
/user/cloudera/sample_data/tab2/tab2.csv
```

The name of each data file is not significant. In fact, when Impala examines the contents of the data directory for the first time, it considers all files in the directory to make up the data of the table, regardless of how many files there are or what the files are named.

To understand what paths are available within your own HDFS filesystem and what the permissions are for the various directories and files, issue `hdfs dfs -ls /` and work your way down the tree doing `-ls` operations for the various directories.

Use the `impala-shell` command to create tables, either interactively or through a SQL script.

The following example shows creating three tables. For each table, the example shows creating columns with various attributes such as Boolean or integer types. The example also includes commands that provide information about how the data is formatted, such as rows terminating with commas, which makes sense in the case of importing data from a `.csv` file. Where we already have `.csv` files containing data in the HDFS directory tree, we specify the location of the directory containing the appropriate `.csv` file. Impala considers all the data from all the files in that directory to represent the data for the table.

```
DROP TABLE IF EXISTS tab1;
-- The EXTERNAL clause means the data is located outside the central location
-- for Impala data files and is preserved when the associated Impala table is dropped.
-- We expect the data to already exist in the directory specified by the LOCATION clause.
CREATE EXTERNAL TABLE tab1
(
  id INT,
  col_1 BOOLEAN,
  col_2 DOUBLE,
  col_3 TIMESTAMP
)
ROW FORMAT DELIMITED FIELDS TERMINATED BY ','
LOCATION '/user/cloudera/sample_data/tab1';

DROP TABLE IF EXISTS tab2;
-- TAB2 is an external table, similar to TAB1.
CREATE EXTERNAL TABLE tab2
(
  id INT,
  col_1 BOOLEAN,
  col_2 DOUBLE
)
ROW FORMAT DELIMITED FIELDS TERMINATED BY ','
LOCATION '/user/cloudera/sample_data/tab2';

DROP TABLE IF EXISTS tab3;
-- Leaving out the EXTERNAL clause means the data will be managed
-- in the central Impala data directory tree. Rather than reading
-- existing data files when the table is created, we load the
-- data after creating the table.
CREATE TABLE tab3
(
  id INT,
  col_1 BOOLEAN,
  col_2 DOUBLE,
  month INT,
  day INT
)
ROW FORMAT DELIMITED FIELDS TERMINATED BY ',';
```



Note: Getting through these `CREATE TABLE` statements successfully is an important validation step to confirm everything is configured correctly with the Hive metastore and HDFS permissions. If you receive any errors during the `CREATE TABLE` statements:

- Make sure you followed the installation instructions closely, in [Installing Impala](#) on page 29.
- Make sure the `hive.metastore.warehouse.dir` property points to a directory that Impala can write to. The ownership should be `hive:hive`, and the `impala` user should also be a member of the `hive` group.
- If the value of `hive.metastore.warehouse.dir` is different in the Cloudera Manager dialogs and in the Hive shell, you might need to [designate the hosts running `impalad` with the “gateway” role for Hive](#), and [deploy the client configuration files](#) to those hosts.

Point an Impala Table at Existing Data Files

A convenient way to set up data for Impala to access is to use an external table, where the data already exists in a set of HDFS files and you just point the Impala table at the directory containing those files. For example, you might run in

impala-shell a *.sql file with contents similar to the following, to create an Impala table that accesses an existing data file used by Hive.

The following examples set up 2 tables, referencing the paths and sample data supplied with the Cloudera QuickStart VM. For historical reasons, the data physically resides in an HDFS directory tree under /user/hive, although this particular data is entirely managed by Impala rather than Hive. When we create an external table, we specify the directory containing one or more data files, and Impala queries the combined content of all the files inside that directory. Here is how we examine the directories and files within the HDFS filesystem:

```
$ cd ~/cloudera/datasets
$ ./tpcds-setup.sh
... Downloads and unzips the kit, builds the data and loads it into HDFS ...
$ hdfs dfs -ls /user/hive/tpcds/customer
Found 1 items
-rw-r--r--  1 cloudera supergroup  13209372 2013-03-22 18:09
/user/hive/tpcds/customer/customer.dat
$ hdfs dfs -cat /user/hive/tpcds/customer/customer.dat | more
1|AAAAAAAAABAAAAAAAA|980124|7135|32946|2452238|2452208|Mr.|Javier|Lewis|Y|9|12|1936|CHILE||Javie
r.Lewis@VFAxlnZEvOx.org|2452508|
2|AAAAAAAAACAAAAAAAA|819667|1461|31655|2452318|2452288|Dr.|Amy|Moses|Y|9|4|1966|TOGO||Amy.Moses@
Ovk9KjHH.com|2452318|
3|AAAAAAAAADAAAAAAAA|1473522|6247|48572|2449130|2449100|Miss|Latisha|Hamilton|N|18|9|1979|NIUE||
Latisha.Hamilton@V.com|2452313|
4|AAAAAAAAAEAAAAAAAA|1703214|3986|39558|2450030|2450000|Dr.|Michael|White|N|7|6|1983|MEXICO||Mic
hael.White@i.org|2452361|
5|AAAAAAAAAFAAAAAAAA|953372|4470|36368|2449438|2449408|Sir|Robert|Moran|N|8|5|1956|FIJI||Robert.
Moran@Hh.edu|2452469|
...
```

Here is a SQL script to set up Impala tables pointing to some of these data files in HDFS. (The script in the VM sets up tables like this through Hive; ignore those tables for purposes of this demonstration.) Save the following as customer_setup.sql:

```
--
-- store_sales fact table and surrounding dimension tables only
--
create database tpcds;
use tpcds;

drop table if exists customer;
create external table customer
(
  c_customer_sk          int,
  c_customer_id         string,
  c_current_cdemo_sk    int,
  c_current_hdemo_sk   int,
  c_current_addr_sk    int,
  c_first_shipto_date_sk int,
  c_first_sales_date_sk int,
  c_salutation         string,
  c_first_name         string,
  c_last_name         string,
  c_preferred_cust_flag string,
  c_birth_day         int,
  c_birth_month       int,
  c_birth_year        int,
  c_birth_country     string,
  c_login            string,
  c_email_address     string,
  c_last_review_date  string
)
row format delimited fields terminated by '|'
location '/user/hive/tpcds/customer';

drop table if exists customer_address;
create external table customer_address
(
  ca_address_sk        int,
  ca_address_id       string,
  ca_street_number     string,
```



```

ca_street_name      string,
ca_street_type      string,
ca_suite_number     string,
ca_city             string,
ca_county           string,
ca_state            string,
ca_zip              string,
ca_country          string,
ca_gmt_offset       float,
ca_location_type    string
)
row format delimited fields terminated by '|'
location '/user/hive/tpcds/customer_address';

```

We would run this script with a command such as:

```
impala-shell -i localhost -f customer_setup.sql
```

Describe the Impala Table

Now that you have updated the database metadata that Impala caches, you can confirm that the expected tables are accessible by Impala and examine the attributes of one of the tables. We created these tables in the database named `default`. If the tables were in a database other than the default, we would issue a command `use db_name` to switch to that database before examining or querying its tables. We could also qualify the name of a table by prepending the database name, for example `default.customer` and `default.customer_name`.

```

[impala-host:21000] > show databases
Query finished, fetching results ...
default
Returned 1 row(s) in 0.00s
[impala-host:21000] > show tables
Query finished, fetching results ...
customer
customer_address
Returned 2 row(s) in 0.00s
[impala-host:21000] > describe customer_address
+-----+-----+-----+
| name          | type   | comment |
+-----+-----+-----+
| ca_address_sk | int    |         |
| ca_address_id | string |         |
| ca_street_number | string |         |
| ca_street_name | string |         |
| ca_street_type | string |         |
| ca_suite_number | string |         |
| ca_city       | string |         |
| ca_county     | string |         |
| ca_state      | string |         |
| ca_zip        | string |         |
| ca_country    | string |         |
| ca_gmt_offset | float  |         |
| ca_location_type | string |         |
+-----+-----+-----+
Returned 13 row(s) in 0.01

```

Query the Impala Table

You can query data contained in the tables. Impala coordinates the query execution across a single node or multiple nodes depending on your configuration, without the overhead of running MapReduce jobs to perform the intermediate processing.

There are a variety of ways to execute queries on Impala:

- Using the `impala-shell` command in interactive mode:

```
$ impala-shell -i impala-host
Connected to localhost:21000
```

```
[impala-host:21000] > select count(*) from customer_address;
50000
Returned 1 row(s) in 0.37s
```

- Passing a set of commands contained in a file:

```
$ impala-shell -i impala-host -f myquery.sql
Connected to localhost:21000
50000
Returned 1 row(s) in 0.19s
```

- Passing a single command to the `impala-shell` command. The query is executed, the results are returned, and the shell exits. Make sure to quote the command, preferably with single quotation marks to avoid shell expansion of characters such as `*`.

```
$ impala-shell -i impala-host -q 'select count(*) from customer_address'
Connected to localhost:21000
50000
Returned 1 row(s) in 0.29s
```

Data Loading and Querying Examples

This section describes how to create some sample tables and load data into them. These tables can then be queried using the Impala shell.

Loading Data

Loading data involves:

- Establishing a data set. The example below uses `.csv` files.
- Creating tables to which to load data.
- Loading the data into the tables you created.

Sample Queries

To run these sample queries, create a SQL query file `query.sql`, copy and paste each query into the query file, and then run the query file using the shell. For example, to run `query.sql` on `impala-host`, you might use the command:

```
impala-shell.sh -i impala-host -f query.sql
```

The examples and results below assume you have loaded the sample data into the tables as described above.

Example: Examining Contents of Tables

Let's start by verifying that the tables do contain the data we expect. Because Impala often deals with tables containing millions or billions of rows, when examining tables of unknown size, include the `LIMIT` clause to avoid huge amounts of unnecessary output, as in the final query. (If your interactive query starts displaying an unexpected volume of data, press `Ctrl-C` in `impala-shell` to cancel the query.)

```
SELECT * FROM tab1;
SELECT * FROM tab2;
SELECT * FROM tab2 LIMIT 5;
```

Results:

id	col_1	col_2	col_3
1	true	123.123	2012-10-24 08:55:00
2	false	1243.5	2012-10-25 13:40:00
3	false	24453.325	2008-08-22 09:33:21.123000000
4	false	243423.325	2007-05-12 22:32:21.334540000

```

| 5 | true | 243.325 | 1953-04-22 09:11:33 |
+-----+-----+-----+-----+
| id | col_1 | col_2 |
+-----+-----+-----+
| 1 | true | 12789.123 |
| 2 | false | 1243.5 |
| 3 | false | 24453.325 |
| 4 | false | 2423.3254 |
| 5 | true | 243.325 |
| 60 | false | 243565423.325 |
| 70 | true | 243.325 |
| 80 | false | 243423.325 |
| 90 | true | 243.325 |
+-----+-----+-----+
| id | col_1 | col_2 |
+-----+-----+-----+
| 1 | true | 12789.123 |
| 2 | false | 1243.5 |
| 3 | false | 24453.325 |
| 4 | false | 2423.3254 |
| 5 | true | 243.325 |
+-----+-----+-----+

```

Example: Aggregate and Join

```

SELECT tab1.col_1, MAX(tab2.col_2), MIN(tab2.col_2)
FROM tab2 JOIN tab1 USING (id)
GROUP BY col_1 ORDER BY 1 LIMIT 5;

```

Results:

```

+-----+-----+-----+
| col_1 | max(tab2.col_2) | min(tab2.col_2) |
+-----+-----+-----+
| false | 24453.325 | 1243.5 |
| true | 12789.123 | 243.325 |
+-----+-----+-----+

```

Example: Subquery, Aggregate and Joins

```

SELECT tab2.*
FROM tab2,
(SELECT tab1.col_1, MAX(tab2.col_2) AS max_col2
 FROM tab2, tab1
 WHERE tab1.id = tab2.id
 GROUP BY col_1) subquery1
WHERE subquery1.max_col2 = tab2.col_2;

```

Results:

```

+-----+-----+-----+
| id | col_1 | col_2 |
+-----+-----+-----+
| 1 | true | 12789.123 |
| 3 | false | 24453.325 |
+-----+-----+-----+

```

Example: INSERT Query

```

INSERT OVERWRITE TABLE tab3
SELECT id, col_1, col_2, MONTH(col_3), DAYOFMONTH(col_3)
FROM tab1 WHERE YEAR(col_3) = 2012;

```

Query TAB3 to check the result:

```
SELECT * FROM tab3;
```

Results:

id	col_1	col_2	month	day
1	true	123.123	10	24
2	false	1243.5	10	25

Advanced Tutorials

These tutorials walk you through advanced scenarios or specialized features.

Attaching an External Partitioned Table to an HDFS Directory Structure

This tutorial shows how you might set up a directory tree in HDFS, put data files into the lowest-level subdirectories, and then use an Impala external table to query the data files from their original locations.

The tutorial uses a table with web log data, with separate subdirectories for the year, month, day, and host. For simplicity, we use a tiny amount of CSV data, loading the same data into each partition.

First, we make an Impala partitioned table for CSV data, and look at the underlying HDFS directory structure to understand the directory structure to re-create elsewhere in HDFS. The columns `field1`, `field2`, and `field3` correspond to the contents of the CSV data files. The `year`, `month`, `day`, and `host` columns are all represented as subdirectories within the table structure, and are not part of the CSV files. We use `STRING` for each of these columns so that we can produce consistent subdirectory names, with leading zeros for a consistent length.

```
create database external_partitions;
use external_partitions;
create table logs (field1 string, field2 string, field3 string)
  partitioned by (year string, month string, day string, host string)
  row format delimited fields terminated by ',';
insert into logs partition (year="2013", month="07", day="28", host="host1") values
("foo","foo","foo");
insert into logs partition (year="2013", month="07", day="28", host="host2") values
("foo","foo","foo");
insert into logs partition (year="2013", month="07", day="29", host="host1") values
("foo","foo","foo");
insert into logs partition (year="2013", month="07", day="29", host="host2") values
("foo","foo","foo");
insert into logs partition (year="2013", month="08", day="01", host="host1") values
("foo","foo","foo");
```

Back in the Linux shell, we examine the HDFS directory structure. (Your Impala data directory might be in a different location; for historical reasons, it is sometimes under the HDFS path `/user/hive/warehouse`.) We use the `hdfs dfs -ls` command to examine the nested subdirectories corresponding to each partitioning column, with separate subdirectories at each level (with `=` in their names) representing the different values for each partitioning column. When we get to the lowest level of subdirectory, we use the `hdfs dfs -cat` command to examine the data file and see CSV-formatted data produced by the `INSERT` statement in Impala.

```
$ hdfs dfs -ls /user/impala/warehouse/external_partitions.db
Found 1 items
drwxrwxrwt - impala hive          0 2013-08-07 12:24
/user/impala/warehouse/external_partitions.db/logs
$ hdfs dfs -ls /user/impala/warehouse/external_partitions.db/logs
Found 1 items
drwxr-xr-x - impala hive          0 2013-08-07 12:24
/user/impala/warehouse/external_partitions.db/logs/year=2013
$ hdfs dfs -ls /user/impala/warehouse/external_partitions.db/logs/year=2013
```

```

Found 2 items
drwxr-xr-x  - impala hive          0 2013-08-07 12:23
/user/impala/warehouse/external_partitions.db/logs/year=2013/month=07
drwxr-xr-x  - impala hive          0 2013-08-07 12:24
/user/impala/warehouse/external_partitions.db/logs/year=2013/month=08
$ hdfs dfs -ls /user/impala/warehouse/external_partitions.db/logs/year=2013/month=07
Found 2 items
drwxr-xr-x  - impala hive          0 2013-08-07 12:22
/user/impala/warehouse/external_partitions.db/logs/year=2013/month=07/day=28
drwxr-xr-x  - impala hive          0 2013-08-07 12:23
/user/impala/warehouse/external_partitions.db/logs/year=2013/month=07/day=29
$ hdfs dfs -ls
/user/impala/warehouse/external_partitions.db/logs/year=2013/month=07/day=28
Found 2 items
drwxr-xr-x  - impala hive          0 2013-08-07 12:21
/user/impala/warehouse/external_partitions.db/logs/year=2013/month=07/day=28/host=host1
drwxr-xr-x  - impala hive          0 2013-08-07 12:22
/user/impala/warehouse/external_partitions.db/logs/year=2013/month=07/day=28/host=host2
$ hdfs dfs -ls
/user/impala/warehouse/external_partitions.db/logs/year=2013/month=07/day=28/host=host1
Found 1 items
-rw-r--r--  3 impala hive          12 2013-08-07 12:21
/user/impala/warehouse/external_partitions.db/logs/year=2013/month=07/day=28/host=host1/3981726974111751120--8907184999369517436_822630111_data.0
$ hdfs dfs -cat
/user/impala/warehouse/external_partitions.db/logs/year=2013/month=07/day=28/\
host=host1/3981726974111751120--8 907184999369517436_822630111_data.0
foo,foo,foo

```

Still in the Linux shell, we use `hdfs dfs -mkdir` to create several data directories outside the HDFS directory tree that Impala controls (`/user/impala/warehouse` in this example, maybe different in your case). Depending on your configuration, you might need to log in as a user with permission to write into this HDFS directory tree; for example, the commands shown here were run while logged in as the `hdfs` user.

```

$ hdfs dfs -mkdir -p /user/impala/data/logs/year=2013/month=07/day=28/host=host1
$ hdfs dfs -mkdir -p /user/impala/data/logs/year=2013/month=07/day=28/host=host2
$ hdfs dfs -mkdir -p /user/impala/data/logs/year=2013/month=07/day=28/host=host1
$ hdfs dfs -mkdir -p /user/impala/data/logs/year=2013/month=07/day=29/host=host1
$ hdfs dfs -mkdir -p /user/impala/data/logs/year=2013/month=08/day=01/host=host1

```

We make a tiny CSV file, with values different than in the `INSERT` statements used earlier, and put a copy within each subdirectory that we will use as an Impala partition.

```

$ cat >dummy_log_data
bar,baz,bletch
$ hdfs dfs -mkdir -p
/user/impala/data/external_partitions/year=2013/month=08/day=01/host=host1
$ hdfs dfs -mkdir -p
/user/impala/data/external_partitions/year=2013/month=07/day=28/host=host1
$ hdfs dfs -mkdir -p
/user/impala/data/external_partitions/year=2013/month=07/day=28/host=host2
$ hdfs dfs -mkdir -p
/user/impala/data/external_partitions/year=2013/month=07/day=29/host=host1
$ hdfs dfs -put dummy_log_data /user/impala/data/logs/year=2013/month=07/day=28/host=host1
$ hdfs dfs -put dummy_log_data /user/impala/data/logs/year=2013/month=07/day=28/host=host2
$ hdfs dfs -put dummy_log_data /user/impala/data/logs/year=2013/month=07/day=29/host=host1
$ hdfs dfs -put dummy_log_data /user/impala/data/logs/year=2013/month=08/day=01/host=host1

```

Back in the `impala-shell` interpreter, we move the original Impala-managed table aside, and create a new *external* table with a `LOCATION` clause pointing to the directory under which we have set up all the partition subdirectories and data files.

```

use external_partitions;
alter table logs rename to logs_original;
create external table logs (field1 string, field2 string, field3 string)
  partitioned by (year string, month string, day string, host string)

```

```
row format delimited fields terminated by ','
location '/user/impala/data/logs';
```

Because partition subdirectories and data files come and go during the data lifecycle, you must identify each of the partitions through an `ALTER TABLE` statement before Impala recognizes the data files they contain.

```
alter table logs add partition (year="2013",month="07",day="28",host="host1")
alter table log_type add partition (year="2013",month="07",day="28",host="host2");
alter table log_type add partition (year="2013",month="07",day="29",host="host1");
alter table log_type add partition (year="2013",month="08",day="01",host="host1");
```

We issue a `REFRESH` statement for the table, always a safe practice when data files have been manually added, removed, or changed. Then the data is ready to be queried. The `SELECT *` statement illustrates that the data from our trivial CSV file was recognized in each of the partitions where we copied it. Although in this case there are only a few rows, we include a `LIMIT` clause on this test query just in case there is more data than we expect.

```
refresh log_type;
select * from log_type limit 100;
```

field1	field2	field3	year	month	day	host
bar	baz	bletch	2013	07	28	host1
bar	baz	bletch	2013	08	01	host1
bar	baz	bletch	2013	07	29	host1
bar	baz	bletch	2013	07	28	host2

Switching Back and Forth Between Impala and Hive

Sometimes, you might find it convenient to switch to the Hive shell to perform some data loading or transformation operation, particularly on file formats such as RCFile, SequenceFile, and Avro that Impala currently can query but not write to.

Whenever you create, drop, or alter a table or other kind of object through Hive, the next time you switch back to the `impala-shell` interpreter, issue a one-time `INVALIDATE METADATA` statement so that Impala recognizes the new or changed object.

Whenever you load, insert, or change data in an existing table through Hive (or even through manual HDFS operations such as the `hdfs` command), the next time you switch back to the `impala-shell` interpreter, issue a one-time `REFRESH table_name` statement so that Impala recognizes the new or changed data.

For examples showing how this process works for the `REFRESH` statement, look at the examples of creating RCFile and SequenceFile tables in Impala, loading data through Hive, and then querying the data through Impala. See [Using the RCFile File Format with Impala Tables](#) on page 602 and [Using the SequenceFile File Format with Impala Tables](#) on page 605 for those examples.

For examples showing how this process works for the `INVALIDATE METADATA` statement, look at the example of creating and loading an Avro table in Hive, and then querying the data through Impala. See [Using the Avro File Format with Impala Tables](#) on page 597 for that example.



Note:

Originally, Impala did not support UDFs, but this feature is available in Impala starting in Impala 1.2. Some `INSERT ... SELECT` transformations that you originally did through Hive can now be done through Impala. See [Impala User-Defined Functions \(UDFs\)](#) on page 487 for details.

Prior to Impala 1.2, the `REFRESH` and `INVALIDATE METADATA` statements needed to be issued on each Impala node to which you connected and issued queries. In Impala 1.2 and higher, when you issue either of those statements on any Impala node, the results are broadcast to all the Impala nodes in the cluster, making it truly a one-step operation after each round of DDL or ETL operations in Hive.

Cross Joins and Cartesian Products with the CROSS JOIN Operator

Originally, Impala restricted join queries so that they had to include at least one equality comparison between the columns of the tables on each side of the join operator. With the huge tables typically processed by Impala, any miscoded query that produced a full Cartesian product as a result set could consume a huge amount of cluster resources.

In Impala 1.2.2 and higher, this restriction is lifted when you use the `CROSS JOIN` operator in the query. You still cannot remove all `WHERE` clauses from a query like `SELECT * FROM t1 JOIN t2` to produce all combinations of rows from both tables. But you can use the `CROSS JOIN` operator to explicitly request such a Cartesian product. Typically, this operation is applicable for smaller tables, where the result set still fits within the memory of a single Impala node.

The following example sets up data for use in a series of comic books where characters battle each other. At first, we use an equijoin query, which only allows characters from the same time period and the same planet to meet.

```
[localhost:21000] > create table heroes (name string, era string, planet string);
[localhost:21000] > create table villains (name string, era string, planet string);
[localhost:21000] > insert into heroes values
> ('Tesla', '20th century', 'Earth'),
> ('Pythagoras', 'Antiquity', 'Earth'),
> ('Zopzar', 'Far Future', 'Mars');
Inserted 3 rows in 2.28s
[localhost:21000] > insert into villains values
> ('Caligula', 'Antiquity', 'Earth'),
> ('John Dillinger', '20th century', 'Earth'),
> ('Xibulor', 'Far Future', 'Venus');
Inserted 3 rows in 1.93s
[localhost:21000] > select concat(heroes.name, ' vs. ', villains.name) as battle
> from heroes join villains
> where heroes.era = villains.era and heroes.planet = villains.planet;
+-----+
| battle |
+-----+
| Tesla vs. John Dillinger |
| Pythagoras vs. Caligula |
+-----+
Returned 2 row(s) in 0.47s
```

Readers demanded more action, so we added elements of time travel and space travel so that any hero could face any villain. Prior to Impala 1.2.2, this type of query was impossible because all joins had to reference matching values between the two tables:

```
[localhost:21000] > -- Cartesian product not possible in Impala 1.1.
> select concat(heroes.name, ' vs. ', villains.name) as battle from
heroes join villains;
ERROR: NotImplementedException: Join between 'heroes' and 'villains' requires at least
one conjunctive equality predicate between the two tables
```

With Impala 1.2.2, we rewrite the query slightly to use `CROSS JOIN` rather than `JOIN`, and now the result set includes all combinations:

```
[localhost:21000] > -- Cartesian product available in Impala 1.2.2 with the CROSS JOIN
syntax.
> select concat(heroes.name, ' vs. ', villains.name) as battle from
heroes cross join villains;
+-----+
| battle |
+-----+
| Tesla vs. Caligula |
| Tesla vs. John Dillinger |
| Tesla vs. Xibulor |
| Pythagoras vs. Caligula |
| Pythagoras vs. John Dillinger |
| Pythagoras vs. Xibulor |
| Zopzar vs. Caligula |
| Zopzar vs. John Dillinger |
| Zopzar vs. Xibulor |
+-----+
```

```
+-----+
Returned 9 row(s) in 0.33s
```

The full combination of rows from both tables is known as the Cartesian product. This type of result set is often used for creating grid data structures. You can also filter the result set by including `WHERE` clauses that do not explicitly compare columns between the two tables. The following example shows how you might produce a list of combinations of year and quarter for use in a chart, and then a shorter list with only selected quarters.

```
[localhost:21000] > create table x_axis (x int);
[localhost:21000] > create table y_axis (y int);
[localhost:21000] > insert into x_axis values (1),(2),(3),(4);
Inserted 4 rows in 2.14s
[localhost:21000] > insert into y_axis values (2010),(2011),(2012),(2013),(2014);
Inserted 5 rows in 1.32s
[localhost:21000] > select y as year, x as quarter from x_axis cross join y_axis;
```

year	quarter
2010	1
2011	1
2012	1
2013	1
2014	1
2010	2
2011	2
2012	2
2013	2
2014	2
2010	3
2011	3
2012	3
2013	3
2014	3
2010	4
2011	4
2012	4
2013	4
2014	4

```
+-----+
Returned 20 row(s) in 0.38s
[localhost:21000] > select y as year, x as quarter from x_axis cross join y_axis where
x in (1,3);
```

year	quarter
2010	1
2011	1
2012	1
2013	1
2014	1
2010	3
2011	3
2012	3
2013	3
2014	3

```
+-----+
Returned 10 row(s) in 0.39s
```

Dealing with Parquet Files with Unknown Schema

As data pipelines start to include more aspects such as NoSQL or loosely specified schemas, you might encounter situations where you have data files (particularly in Parquet format) where you do not know the precise table definition. This tutorial shows how you can build an Impala table around data that comes from non-Impala or even non-SQL sources, where you do not have control of the table layout and might not be familiar with the characteristics of the data.

The data used in this tutorial represents airline on-time arrival statistics, from October 1987 through April 2008. See the details on the [2009 ASA Data Expo web site](#). You can also see the [explanations of the columns](#); for purposes of this exercise, wait until after following the tutorial before examining the schema, to better simulate a real-life situation where you cannot rely on assumptions and assertions about the ranges and representations of data values.

We will download Parquet files containing this data from the Ibis blog. First, we download and unpack the data files. There are 8 files totalling 1.4 GB. Each file is less than 256 MB.

```
$ wget -O airlines_parquet.tar.gz
https://www.dropbox.com/s/ol9x5ltqp6cv4yc/airlines_parquet.tar.gz?dl=0
...
Length: 1245204740 (1.2G) [application/octet-stream]
Saving to: "airlines_parquet.tar.gz"

2015-08-12 17:14:24 (23.6 MB/s) - "airlines_parquet.tar.gz" saved [1245204740/1245204740]

$ tar xvzf airlines_parquet.tar.gz
airlines_parquet/
airlines_parquet/93459d994898a9ba-77674173b331fa9a_2073981944_data.0.parq
airlines_parquet/93459d994898a9ba-77674173b331fa99_1555718317_data.1.parq
airlines_parquet/93459d994898a9ba-77674173b331fa99_1555718317_data.0.parq
airlines_parquet/93459d994898a9ba-77674173b331fa96_2118228804_data.0.parq
airlines_parquet/93459d994898a9ba-77674173b331fa97_574780876_data.0.parq
airlines_parquet/93459d994898a9ba-77674173b331fa96_2118228804_data.1.parq
airlines_parquet/93459d994898a9ba-77674173b331fa98_1194408366_data.0.parq
airlines_parquet/93459d994898a9ba-77674173b331fa9b_1413430552_data.0.parq
$ cd airlines_parquet/
$ du -kch *.parq
253M 93459d994898a9ba-77674173b331fa96_2118228804_data.0.parq
65M 93459d994898a9ba-77674173b331fa96_2118228804_data.1.parq
156M 93459d994898a9ba-77674173b331fa97_574780876_data.0.parq
240M 93459d994898a9ba-77674173b331fa98_1194408366_data.0.parq
253M 93459d994898a9ba-77674173b331fa99_1555718317_data.0.parq
16M 93459d994898a9ba-77674173b331fa99_1555718317_data.1.parq
177M 93459d994898a9ba-77674173b331fa9a_2073981944_data.0.parq
213M 93459d994898a9ba-77674173b331fa9b_1413430552_data.0.parq
1.4G total
```

Next, we put the Parquet data files in HDFS, all together in a single directory, with permissions on the directory and the files so that the `impala` user will be able to read them.



Note: After unpacking, we saw the largest Parquet file was 253 MB. When copying Parquet files into HDFS for Impala to use, for maximum query performance, make sure that each file resides in a single HDFS data block. Therefore, we pick a size larger than any single file and specify that as the block size, using the argument `-Ddfs.block.size=256m` on the `hdfs dfs -put` command.

```
$ hdfs dfs -mkdir -p hdfs://demo_host.example.com:8020/user/impala/staging/airlines
$ hdfs dfs -Ddfs.block.size=256m -put *.parq /user/impala/staging/airlines
$ hdfs dfs -ls /user/impala/staging
Found 1 items
drwxrwxrwx - hdfs supergroup          0 2015-08-12 13:52 /user/impala/staging/airlines
$ hdfs dfs -ls hdfs://demo_host.example.com:8020/user/impala/staging/airlines
Found 8 items
-rw-r--r--  3 jrussell supergroup    265107489 2015-08-12 17:18
/user/impala/staging/airlines/93459d994898a9ba-77674173b331fa96_2118228804_data.0.parq
-rw-r--r--  3 jrussell supergroup     67544715 2015-08-12 17:18
/user/impala/staging/airlines/93459d994898a9ba-77674173b331fa96_2118228804_data.1.parq
-rw-r--r--  3 jrussell supergroup    162556490 2015-08-12 17:18
/user/impala/staging/airlines/93459d994898a9ba-77674173b331fa97_574780876_data.0.parq
-rw-r--r--  3 jrussell supergroup    251603518 2015-08-12 17:18
/user/impala/staging/airlines/93459d994898a9ba-77674173b331fa98_1194408366_data.0.parq
-rw-r--r--  3 jrussell supergroup    265186603 2015-08-12 17:18
/user/impala/staging/airlines/93459d994898a9ba-77674173b331fa99_1555718317_data.0.parq
-rw-r--r--  3 jrussell supergroup    16663754 2015-08-12 17:18
/user/impala/staging/airlines/93459d994898a9ba-77674173b331fa99_1555718317_data.1.parq
-rw-r--r--  3 jrussell supergroup    185511677 2015-08-12 17:18
/user/impala/staging/airlines/93459d994898a9ba-77674173b331fa9a_2073981944_data.0.parq
```

```
-rw-r--r--  3 jrussell supergroup  222794621 2015-08-12 17:18
/user/impala/staging/airlines/93459d994898a9ba-77674173b331fa9b_1413430552_data.0.parq
```

With the files in an accessible location in HDFS, we create a database table that uses the data in those files. The `CREATE EXTERNAL` syntax and the `LOCATION` attribute point Impala at the appropriate HDFS directory. The `LIKE PARQUET 'path_to_any_parquet_file'` clause means we skip the list of column names and types; Impala automatically gets the column names and data types straight from the data files. (Currently, this technique only works for Parquet files.) We ignore the warning about lack of `READ_WRITE` access to the files in HDFS; the `impala` user can read the files, which will be sufficient for us to experiment with queries and perform some copy and transform operations into other tables.

```
$ impala-shell -i localhost
Starting Impala Shell without Kerberos authentication
Connected to localhost:21000
Server version: impalad version 2.2.0-cdh5 RELEASE (build
2ffd73a4255cefd521362ffefcfb37463f67f75c)
Welcome to the Impala shell. Press TAB twice to see a list of available commands.

Copyright (c) 2012 Cloudera, Inc. All rights reserved.

(Shell build version: Impala Shell v2.1.2-cdh5 (92438b7) built on Tue Feb 24 12:36:33
PST 2015)
[localhost:21000] > create database airline_data;
[localhost:21000] > use airline_data;
[localhost:21000] > create external table airlines_external
> like parquet
'hdfs://demo_host.example.com:8020/user/impala/staging/airlines/93459d994898a9ba-77674173b331fa96_2118228804_data.0.parq'
> stored as parquet location
'hdfs://demo_host.example.com:8020/user/impala/staging/airlines';
WARNINGS: Impala does not have READ_WRITE access to path
'hdfs://demo_host.example.com:8020/user/impala/staging'
```

With the table created, we examine its physical and logical characteristics to confirm that the data is really there and in a format and shape that we can work with. The `SHOW TABLE STATS` statement gives a very high-level summary of the table, showing how many files and how much total data it contains. Also, it confirms that the table is expecting all the associated data files to be in Parquet format. (The ability to work with all kinds of HDFS data files in different formats means that it is possible to have a mismatch between the format of the data files, and the format that the table expects the data files to be in.) The `SHOW FILES` statement confirms that the data in the table has the expected number, names, and sizes of the original Parquet files. The `DESCRIBE` statement (or its abbreviation `DESC`) confirms the names and types of the columns that Impala automatically created after reading that metadata from the Parquet file. The `DESCRIBE FORMATTED` statement prints out some extra detail along with the column definitions; the pieces we care about for this exercise are the containing database for the table, the location of the associated data files in HDFS, the fact that it's an external table so Impala will not delete the HDFS files when we finish the experiments and drop the table, and the fact that the table is set up to work exclusively with files in the Parquet format.

```
[localhost:21000] > show table stats airlines_external;
+-----+-----+-----+-----+-----+-----+-----+
| #Rows | #Files | Size   | Bytes Cached | Cache Replication | Format   | Incremental |
+-----+-----+-----+-----+-----+-----+-----+
| -1    | 8      | 1.34GB | NOT CACHED   | NOT CACHED        | PARQUET | false       |
+-----+-----+-----+-----+-----+-----+-----+
[localhost:21000] > show files in airlines_external;
+-----+-----+-----+-----+-----+-----+-----+
| path                                     | size      | partition |
+-----+-----+-----+-----+-----+-----+-----+
| /user/impala/staging/airlines/93459d994898a9ba-77674173b331fa96_2118228804_data.0.parq | 252.83MB |           |
| /user/impala/staging/airlines/93459d994898a9ba-77674173b331fa96_2118228804_data.1.parq | 64.42MB  |           |
| /user/impala/staging/airlines/93459d994898a9ba-77674173b331fa97_574780876_data.0.parq  | 155.03MB |           |
| /user/impala/staging/airlines/93459d994898a9ba-77674173b331fa98_1194408366_data.0.parq  |           |           |
+-----+-----+-----+-----+-----+-----+-----+
```

```

| 239.95MB |
| /user/impala/staging/airlines/93459d994898a9ba-77674173b331fa99_1555718317_data.0.parq
| 252.90MB |
| /user/impala/staging/airlines/93459d994898a9ba-77674173b331fa99_1555718317_data.1.parq
| 15.89MB |
| /user/impala/staging/airlines/93459d994898a9ba-77674173b331fa9a_2073981944_data.0.parq
| 176.92MB |
| /user/impala/staging/airlines/93459d994898a9ba-77674173b331fa9b_1413430552_data.0.parq
| 212.47MB |

```

```
[localhost:21000] > describe airlines_external;
```

name	type	comment
year	int	inferred from: optional int32 year
month	int	inferred from: optional int32 month
day	int	inferred from: optional int32 day
dayofweek	int	inferred from: optional int32 dayofweek
dep_time	int	inferred from: optional int32 dep_time
crs_dep_time	int	inferred from: optional int32 crs_dep_time
arr_time	int	inferred from: optional int32 arr_time
crs_arr_time	int	inferred from: optional int32 crs_arr_time
carrier	string	inferred from: optional binary carrier
flight_num	int	inferred from: optional int32 flight_num
tail_num	int	inferred from: optional int32 tail_num
actual_elapsed_time	int	inferred from: optional int32 actual_elapsed_time
crs_elapsed_time	int	inferred from: optional int32 crs_elapsed_time
airtime	int	inferred from: optional int32 airtime
arrdelay	int	inferred from: optional int32 arrdelay
depdelay	int	inferred from: optional int32 depdelay
origin	string	inferred from: optional binary origin
dest	string	inferred from: optional binary dest
distance	int	inferred from: optional int32 distance
taxi_in	int	inferred from: optional int32 taxi_in
taxi_out	int	inferred from: optional int32 taxi_out
cancelled	int	inferred from: optional int32 cancelled
cancellation_code	string	inferred from: optional binary cancellation_code
diverted	int	inferred from: optional int32 diverted
carrier_delay	int	inferred from: optional int32 carrier_delay
weather_delay	int	inferred from: optional int32 weather_delay
nas_delay	int	inferred from: optional int32 nas_delay
security_delay	int	inferred from: optional int32 security_delay
late_aircraft_delay	int	inferred from: optional int32 late_aircraft_delay

```
[localhost:21000] > desc formatted airlines_external;
```

name	type
# Detailed Table Information	NULL
Database:	airline_data
Owner:	jrussell
Location:	/user/impala/staging/airlines
Table Type:	EXTERNAL_TABLE
# Storage Information	NULL
SerDe Library:	parquet.hive.serde.ParquetHiveSerDe
InputFormat:	parquet.hive.DeprecatedParquetInputFormat
OutputFormat:	parquet.hive.DeprecatedParquetOutputFormat

Now that we are confident that the connections are solid between the Impala table and the underlying Parquet files, we run some initial queries to understand the characteristics of the data: the overall number of rows, and the ranges and how many different values are in certain columns. For convenience in understanding the magnitude of the `COUNT(*)` result, we run another query dividing the number of rows by 1 million, demonstrating that there are 123 million rows in the table.

```
[localhost:21000] > select count(*) from airlines_external;
```

```

+-----+
| count(*) |

```

```

+-----+
| 123534969 |
+-----+
Fetched 1 row(s) in 1.32s
[localhost:21000] > select count(*) / 1e6 as 'millions of rows' from airlines_external;
+-----+
| millions of rows |
+-----+
| 123.534969 |
+-----+
Fetched 1 row(s) in 1.24s

```

The `NDV()` function stands for “number of distinct values”, which for performance reasons is an estimate when there are lots of different values in the column, but is precise when the cardinality is less than 16 K. Use `NDV()` calls for this kind of exploration rather than `COUNT(DISTINCT colname)`, because Impala can evaluate multiple `NDV()` functions in a single query, but only a single instance of `COUNT DISTINCT`. Here we see that there are modest numbers of different airlines, flight numbers, and origin and destination airports. Two things jump out from this query: the number of `tail_num` values is much smaller than we might have expected, and there are more destination airports than origin airports. Let's dig further. What we find is that most `tail_num` values are `NULL`. It looks like this was an experimental column that wasn't filled in accurately. We make a mental note that if we use this data as a starting point, we'll ignore this column. We also find that certain airports are represented in the `ORIGIN` column but not the `DEST` column; now we know that we cannot rely on the assumption that those sets of airport codes are identical.



Note: A slight digression for some performance tuning. Notice how the first `SELECT DISTINCT DEST` query takes almost 40 seconds. We expect all queries on such a small data set, less than 2 GB, to take a few seconds at most. The reason is because the expression `NOT IN (SELECT origin FROM airlines_external)` produces an intermediate result set of 123 million rows, then runs 123 million comparisons on each data node against the tiny set of destination airports. The way the `NOT IN` operator works internally means that this intermediate result set with 123 million rows might be transmitted across the network to each data node in the cluster. Applying another `DISTINCT` inside the `NOT IN` subquery means that the intermediate result set is only 340 items, resulting in much less network traffic and fewer comparison operations. The more efficient query with the added `DISTINCT` is approximately 7 times as fast.

```

[localhost:21000] > select ndv(carrier), ndv(flight_num), ndv(tail_num),
> ndv(origin), ndv(dest) from airlines_external;
+-----+-----+-----+-----+-----+
| ndv(carrier) | ndv(flight_num) | ndv(tail_num) | ndv(origin) | ndv(dest) |
+-----+-----+-----+-----+-----+
| 29           | 9086            | 3             | 340         | 347       |
+-----+-----+-----+-----+-----+
[localhost:21000] > select tail_num, count(*) as howmany from airlines_external
> group by tail_num;
+-----+-----+
| tail_num | howmany |
+-----+-----+
| 715     | 1       |
| 0       | 406405 |
| 112     | 6562   |
| NULL    | 123122001 |
+-----+-----+
Fetched 1 row(s) in 5.18s
[localhost:21000] > select distinct dest from airlines_external
> where dest not in (select origin from airlines_external);
+-----+
| dest |
+-----+
| LBF  |
| CBM  |
| RCA  |
| SKA  |
| LAR  |
+-----+
Fetched 5 row(s) in 39.64s
[localhost:21000] > select distinct dest from airlines_external

```

```

> where dest not in (select distinct origin from airlines_external);
+-----+
| dest |
+-----+
| LBF  |
| RCA  |
| CBM  |
| SKA  |
| LAR  |
+-----+
Fetched 5 row(s) in 5.59s
[localhost:21000] > select distinct origin from airlines_external
> where origin not in (select distinct dest from airlines_external);
Fetched 0 row(s) in 5.37s

```

Next, we try doing a simple calculation, with results broken down by year. This reveals that some years have no data in the `AIRTIME` column. That means we might be able to use that column in queries involving certain date ranges, but we cannot count on it to always be reliable. The question of whether a column contains any `NULL` values, and if so what is their number, proportion, and distribution, comes up again and again when doing initial exploration of a data set.

```

[localhost:21000] > select year, sum(airtime) from airlines_external
> group by year order by year desc;
+-----+-----+
| year | sum(airtime) |
+-----+-----+
| 2008 | 713050445   |
| 2007 | 748015545   |
| 2006 | 720372850   |
| 2005 | 708204026   |
| 2004 | 714276973   |
| 2003 | 665706940   |
| 2002 | 549761849   |
| 2001 | 590867745   |
| 2000 | 583537683   |
| 1999 | 561219227   |
| 1998 | 538050663   |
| 1997 | 536991229   |
| 1996 | 519440044   |
| 1995 | 513364265   |
| 1994 | NULL        |
| 1993 | NULL        |
| 1992 | NULL        |
| 1991 | NULL        |
| 1990 | NULL        |
| 1989 | NULL        |
| 1988 | NULL        |
| 1987 | NULL        |
+-----+-----+

```

With the notion of `NULL` values in mind, let's come back to the `TAILNUM` column that we discovered had a lot of `NULL`s. Let's quantify the `NULL` and non-`NULL` values in that column for better understanding. First, we just count the overall number of rows versus the non-`NULL` values in that column. That initial result gives the appearance of relatively few non-`NULL` values, but we can break it down more clearly in a single query. Once we have the `COUNT(*)` and the `COUNT(colname)` numbers, we can encode that initial query in a `WITH` clause, then run a followon query that performs multiple arithmetic operations on those values. Seeing that only one-third of one percent of all rows have non-`NULL` values for the `TAILNUM` column clearly illustrates that that column is not of much use.

```

[localhost:21000] > select count(*) as 'rows', count(tail_num) as 'non-null tail numbers'
> from airlines_external;
+-----+-----+
| rows      | non-null tail numbers |
+-----+-----+
| 123534969 | 412968                |
+-----+-----+
Fetched 1 row(s) in 1.51s
[localhost:21000] > with t1 as

```

```

> (select count(*) as 'rows', count(tail_num) as 'nonnull'
> from airlines_external)
> select `rows`, `nonnull`, `rows` - `nonnull` as 'nulls',
> (`nonnull` / `rows`) * 100 as 'percentage non-null'
> from t1;

```

rows	nonnull	nulls	percentage non-null
123534969	412968	123122001	0.3342923897119365

By examining other columns using these techniques, we can form a mental picture of the way data is distributed throughout the table, and which columns are most significant for query purposes. For this tutorial, we focus mostly on the fields likely to hold discrete values, rather than columns such as `ACTUAL_ELAPSED_TIME` whose names suggest they hold measurements. We would dig deeper into those columns once we had a clear picture of which questions were worthwhile to ask, and what kinds of trends we might look for. For the final piece of initial exploration, let's look at the `YEAR` column. A simple `GROUP BY` query shows that it has a well-defined range, a manageable number of distinct values, and relatively even distribution of rows across the different years.

```
[localhost:21000] > select min(year), max(year), ndv(year) from airlines_external;
```

min(year)	max(year)	ndv(year)
1987	2008	22

Fetches 1 row(s) in 2.03s

```
[localhost:21000] > select year, count(*) howmany from airlines_external
> group by year order by year desc;
```

year	howmany
2008	7009728
2007	7453215
2006	7141922
2005	7140596
2004	7129270
2003	6488540
2002	5271359
2001	5967780
2000	5683047
1999	5527884
1998	5384721
1997	5411843
1996	5351983
1995	5327435
1994	5180048
1993	5070501
1992	5092157
1991	5076925
1990	5270893
1989	5041200
1988	5202096
1987	1311826

Fetches 22 row(s) in 2.13s

We could go quite far with the data in this initial raw format, just as we downloaded it from the web. If the data set proved to be useful and worth persisting in Impala for extensive queries, we might want to copy it to an internal table, letting Impala manage the data files and perhaps reorganizing a little for higher efficiency. In this next stage of the tutorial, we copy the original data into a partitioned table, still in Parquet format. Partitioning based on the `YEAR` column lets us run queries with clauses such as `WHERE year = 2001` or `WHERE year BETWEEN 1989 AND 1999`, which can dramatically cut down on I/O by ignoring all the data from years outside the desired range. Rather than reading all the data and then deciding which rows are in the matching years, Impala can zero in on only the data files from specific `YEAR` partitions. To do this, Impala physically reorganizes the data files, putting the rows from each year into data files in a separate HDFS directory for each `YEAR` value. Along the way, we'll also get rid of the `TAIL_NUM` column that proved to be almost entirely `NULL`.

The first step is to create a new table with a layout very similar to the original AIRLINES_EXTERNAL table. We'll do that by reverse-engineering a CREATE TABLE statement for the first table, then tweaking it slightly to include a PARTITION BY clause for YEAR, and excluding the TAIL_NUM column. The SHOW CREATE TABLE statement gives us the starting point.

```
[localhost:21000] > show create table airlines_external;
+-----+
| result |
+-----+
CREATE EXTERNAL TABLE airline_data.airlines_external (
  year INT COMMENT 'inferred from: optional int32 year',
  month INT COMMENT 'inferred from: optional int32 month',
  day INT COMMENT 'inferred from: optional int32 day',
  dayofweek INT COMMENT 'inferred from: optional int32 dayofweek',
  dep_time INT COMMENT 'inferred from: optional int32 dep_time',
  crs_dep_time INT COMMENT 'inferred from: optional int32 crs_dep_time',
  arr_time INT COMMENT 'inferred from: optional int32 arr_time',
  crs_arr_time INT COMMENT 'inferred from: optional int32 crs_arr_time',
  carrier STRING COMMENT 'inferred from: optional binary carrier',
  flight_num INT COMMENT 'inferred from: optional int32 flight_num',
  tail_num INT COMMENT 'inferred from: optional int32 tail_num',
  actual_elapsed_time INT COMMENT 'inferred from: optional int32 actual_elapsed_time',
  crs_elapsed_time INT COMMENT 'inferred from: optional int32 crs_elapsed_time',
  airtime INT COMMENT 'inferred from: optional int32 airtime',
  ardelay INT COMMENT 'inferred from: optional int32 ardelay',
  depdelay INT COMMENT 'inferred from: optional int32 depdelay',
  origin STRING COMMENT 'inferred from: optional binary origin',
  dest STRING COMMENT 'inferred from: optional binary dest',
  distance INT COMMENT 'inferred from: optional int32 distance',
  taxi_in INT COMMENT 'inferred from: optional int32 taxi_in',
  taxi_out INT COMMENT 'inferred from: optional int32 taxi_out',
  cancelled INT COMMENT 'inferred from: optional int32 cancelled',
  cancellation_code STRING COMMENT 'inferred from: optional binary cancellation_code',
  diverted INT COMMENT 'inferred from: optional int32 diverted',
  carrier_delay INT COMMENT 'inferred from: optional int32 carrier_delay',
  weather_delay INT COMMENT 'inferred from: optional int32 weather_delay',
  nas_delay INT COMMENT 'inferred from: optional int32 nas_delay',
  security_delay INT COMMENT 'inferred from: optional int32 security_delay',
  late_aircraft_delay INT COMMENT 'inferred from: optional int32 late_aircraft_delay'
)
STORED AS PARQUET
LOCATION 'hdfs://a1730.example.com:8020/user/impala/staging/airlines'
TBLPROPERTIES ('numFiles'='0', 'COLUMN_STATS_ACCURATE'='false',
  'transient_lastDdlTime'='1439425228', 'numRows'='-1', 'totalSize'='0',
  'rawDataSize'='-1')
+-----+
Fetched 1 row(s) in 0.03s
[localhost:21000] > quit;
```

Although we could edit that output into a new SQL statement, all the ASCII box characters make such editing inconvenient. To get a more stripped-down CREATE TABLE to start with, we restart the impala-shell command with the -B option, which turns off the box-drawing behavior.

```
[localhost:21000] > quit;
Goodbye jrussell
$ impala-shell -i localhost -B -d airline_data;
Starting Impala Shell without Kerberos authentication
Connected to localhost:21000
Server version: impalad version 2.2.0-cdh5 RELEASE (build
2fffd73a4255cefd521362ffefcfb37463f67f75c)
Welcome to the Impala shell. Press TAB twice to see a list of available commands.

Copyright (c) 2012 Cloudera, Inc. All rights reserved.

(Shell build version: Impala Shell v2.1.2-cdh5 (92438b7) built on Tue Feb 24 12:36:33
PST 2015)
[localhost:21000] > show create table airlines_external;
"CREATE EXTERNAL TABLE airline_data.airlines_external (
  year INT COMMENT 'inferred from: optional int32 year',
  month INT COMMENT 'inferred from: optional int32 month',
  day INT COMMENT 'inferred from: optional int32 day',
```

```

dayofweek INT COMMENT 'inferred from: optional int32 dayofweek',
dep_time INT COMMENT 'inferred from: optional int32 dep_time',
crs_dep_time INT COMMENT 'inferred from: optional int32 crs_dep_time',
arr_time INT COMMENT 'inferred from: optional int32 arr_time',
crs_arr_time INT COMMENT 'inferred from: optional int32 crs_arr_time',
carrier STRING COMMENT 'inferred from: optional binary carrier',
flight_num INT COMMENT 'inferred from: optional int32 flight_num',
tail_num INT COMMENT 'inferred from: optional int32 tail_num',
actual_elapsed_time INT COMMENT 'inferred from: optional int32 actual_elapsed_time',
crs_elapsed_time INT COMMENT 'inferred from: optional int32 crs_elapsed_time',
airtime INT COMMENT 'inferred from: optional int32 airtime',
arrdelay INT COMMENT 'inferred from: optional int32 arrdelay',
depdelay INT COMMENT 'inferred from: optional int32 depdelay',
origin STRING COMMENT 'inferred from: optional binary origin',
dest STRING COMMENT 'inferred from: optional binary dest',
distance INT COMMENT 'inferred from: optional int32 distance',
taxi_in INT COMMENT 'inferred from: optional int32 taxi_in',
taxi_out INT COMMENT 'inferred from: optional int32 taxi_out',
cancelled INT COMMENT 'inferred from: optional int32 cancelled',
cancellation_code STRING COMMENT 'inferred from: optional binary cancellation_code',
diverted INT COMMENT 'inferred from: optional int32 diverted',
carrier_delay INT COMMENT 'inferred from: optional int32 carrier_delay',
weather_delay INT COMMENT 'inferred from: optional int32 weather_delay',
nas_delay INT COMMENT 'inferred from: optional int32 nas_delay',
security_delay INT COMMENT 'inferred from: optional int32 security_delay',
late_aircraft_delay INT COMMENT 'inferred from: optional int32 late_aircraft_delay'
)
STORED AS PARQUET
LOCATION 'hdfs://a1730.example.com:8020/user/impala/staging/airlines'
TBLPROPERTIES ('numFiles'='0', 'COLUMN_STATS_ACCURATE'='false',
  'transient_lastDdlTime'='1439425228', 'numRows'='-1', 'totalSize'='0',
  'rawDataSize'='-1')"
Fetched 1 row(s) in 0.01s

```

After copying and pasting the `CREATE TABLE` statement into a text editor for fine-tuning, we quit and restart `impala-shell` without the `-B` option, to switch back to regular output.

Next we run the `CREATE TABLE` statement that we adapted from the `SHOW CREATE TABLE` output. We kept the `STORED AS PARQUET` clause because we want to rearrange the data somewhat but still keep it in the high-performance Parquet format. The `LOCATION` and `TBLPROPERTIES` clauses are not relevant for this new table, so we edit those out. Because we are going to partition the new table based on the `YEAR` column, we move that column name (and its type) into a new `PARTITIONED BY` clause.

```

[localhost:21000] > CREATE TABLE airline_data.airlines
> (
>   month INT,
>   day INT,
>   dayofweek INT,
>   dep_time INT,
>   crs_dep_time INT,
>   arr_time INT,
>   crs_arr_time INT,
>   carrier STRING,
>   flight_num INT,
>   actual_elapsed_time INT,
>   crs_elapsed_time INT,
>   airtime INT,
>   arrdelay INT,
>   depdelay INT,
>   origin STRING,
>   dest STRING,
>   distance INT,
>   taxi_in INT,
>   taxi_out INT,
>   cancelled INT,
>   cancellation_code STRING,
>   diverted INT,
>   carrier_delay INT,
>   weather_delay INT,
>   nas_delay INT,
>   security_delay INT,

```



```

>   late_aircraft_delay INT
> )
> STORED AS PARQUET
> PARTITIONED BY (year INT);
Fetched 0 row(s) in 0.10s

```

Next, we copy all the rows from the original table into this new one with an `INSERT` statement. (We edited the `CREATE TABLE` statement to make an `INSERT` statement with the column names in the same order.) The only change is to add a `PARTITION(year)` clause, and move the `YEAR` column to the very end of the `SELECT` list of the `INSERT` statement. Specifying `PARTITION(year)`, rather than a fixed value such as `PARTITION(year=2000)`, means that Impala figures out the partition value for each row based on the value of the very last column in the `SELECT` list. This is the first SQL statement that legitimately takes any substantial time, because the rows from different years are shuffled around the cluster; the rows that go into each partition are collected on one node, before being written to one or more new data files.

```

[localhost:21000] > INSERT INTO airline_data.airlines
> PARTITION (year)
> SELECT
>   month,
>   day,
>   dayofweek,
>   dep_time,
>   crs_dep_time,
>   arr_time,
>   crs_arr_time,
>   carrier,
>   flight_num,
>   actual_elapsed_time,
>   crs_elapsed_time,
>   airtime,
>   arrdelay,
>   depdelay,
>   origin,
>   dest,
>   distance,
>   taxi_in,
>   taxi_out,
>   cancelled,
>   cancellation_code,
>   diverted,
>   carrier_delay,
>   weather_delay,
>   nas_delay,
>   security_delay,
>   late_aircraft_delay,
>   year
> FROM airline_data.airlines_external;
Inserted 123534969 row(s) in 202.70s

```

Once partitioning or join queries come into play, it's important to have statistics that Impala can use to optimize queries on the corresponding tables. The `COMPUTE INCREMENTAL STATS` statement is the way to collect statistics for partitioned tables. Then the `SHOW TABLE STATS` statement confirms that the statistics are in place for each partition, and also illustrates how many files and how much raw data is in each partition.

```

[localhost:21000] > compute incremental stats airlines;
+-----+
| summary |
+-----+
| Updated 22 partition(s) and 27 column(s). |
+-----+
[localhost:21000] > show table stats airlines;
+-----+-----+-----+-----+-----+-----+-----+
| year | #Rows | #Files | Size | Bytes Cached | Cache Repl | Format |
Incremental stats |
+-----+-----+-----+-----+-----+-----+-----+
| 1987 | 1311826 | 1 | 9.32MB | NOT CACHED | NOT CACHED | PARQUET | true
| 1988 | 5202096 | 1 | 37.04MB | NOT CACHED | NOT CACHED | PARQUET | true
| 1989 | 5041200 | 1 | 36.25MB | NOT CACHED | NOT CACHED | PARQUET | true

```

1990	5270893	1	38.39MB	NOT CACHED	NOT CACHED	PARQUET	true
1991	5076925	1	37.23MB	NOT CACHED	NOT CACHED	PARQUET	true
1992	5092157	1	36.85MB	NOT CACHED	NOT CACHED	PARQUET	true
1993	5070501	1	37.16MB	NOT CACHED	NOT CACHED	PARQUET	true
1994	5180048	1	38.31MB	NOT CACHED	NOT CACHED	PARQUET	true
1995	5327435	1	53.14MB	NOT CACHED	NOT CACHED	PARQUET	true
1996	5351983	1	53.64MB	NOT CACHED	NOT CACHED	PARQUET	true
1997	5411843	1	54.41MB	NOT CACHED	NOT CACHED	PARQUET	true
1998	5384721	1	54.01MB	NOT CACHED	NOT CACHED	PARQUET	true
1999	5527884	1	56.32MB	NOT CACHED	NOT CACHED	PARQUET	true
2000	5683047	1	58.15MB	NOT CACHED	NOT CACHED	PARQUET	true
2001	5967780	1	60.65MB	NOT CACHED	NOT CACHED	PARQUET	true
2002	5271359	1	57.99MB	NOT CACHED	NOT CACHED	PARQUET	true
2003	6488540	1	81.33MB	NOT CACHED	NOT CACHED	PARQUET	true
2004	7129270	1	103.19MB	NOT CACHED	NOT CACHED	PARQUET	true
2005	7140596	1	102.61MB	NOT CACHED	NOT CACHED	PARQUET	true
2006	7141922	1	106.03MB	NOT CACHED	NOT CACHED	PARQUET	true
2007	7453215	1	112.15MB	NOT CACHED	NOT CACHED	PARQUET	true
2008	7009728	1	105.76MB	NOT CACHED	NOT CACHED	PARQUET	true
Total	123534969	22	1.30GB	0B			

At this point, we go through a quick thought process to sanity check the partitioning we did. All the partitions have exactly one file, which is on the low side. A query that includes a clause `WHERE year=2004` will only read a single data block; that data block will be read and processed by a single data node; therefore, for a query targeting a single year, all the other nodes in the cluster will sit idle while all the work happens on a single machine. It's even possible that by chance (depending on HDFS replication factor and the way data blocks are distributed across the cluster), that multiple year partitions selected by a filter such as `WHERE year BETWEEN 1999 AND 2001` could all be read and processed by the same data node. The more data files each partition has, the more parallelism you can get and the less probability of "hotspots" occurring on particular nodes, therefore a bigger performance boost by having a big CDH cluster.

However, the more data files, the less data goes in each one. The overhead of dividing the work in a parallel query might not be worth it if each node is only reading a few megabytes. 50 or 100 megabytes is a decent size for a Parquet data block; 9 or 37 megabytes is on the small side. Which is to say, the data distribution we ended up with based on this partitioning scheme is on the borderline between sensible (reasonably large files) and suboptimal (few files in each partition). The way to see how well it works in practice is to run the same queries against the original flat table and the new partitioned table, and compare times.

Spoiler: in this case, with my particular 4-node cluster with its specific distribution of data blocks and my particular exploratory queries, queries against the partitioned table do consistently run faster than the same queries against the unpartitioned table. But I could not be sure that would be the case without some real measurements. Here are some queries I ran to draw that conclusion, first against `AIRLINES_EXTERNAL` (no partitioning), then against `AIRLINES` (partitioned by year). The `AIRLINES` queries are consistently faster. Changing the volume of data, changing the size of the cluster, running queries that did or didn't refer to the partition key columns, or other factors could change the results to favor one table layout or the other.



Note: If you find the volume of each partition is only in the low tens of megabytes, consider lowering the granularity of partitioning. For example, instead of partitioning by year, month, and day, partition by year and month or even just by year. The ideal layout to distribute work efficiently in a parallel query is many tens or even hundreds of megabytes per Parquet file, and the number of Parquet files in each partition somewhat higher than the number of data nodes.

```
[localhost:21000] > select sum(airtime) from airlines_external;
+-----+
| sum(airtime) |
+-----+
| 8662859484   |
+-----+
Fetched 1 row(s) in 2.02s
[localhost:21000] > select sum(airtime) from airlines;
+-----+
| sum(airtime) |
+-----+
```

```

| 8662859484 |
+-----+
Fetched 1 row(s) in 1.21s

[localhost:21000] > select sum(airtime) from airlines_external where year = 2005;
+-----+
| sum(airtime) |
+-----+
| 708204026 |
+-----+
Fetched 1 row(s) in 2.61s
[localhost:21000] > select sum(airtime) from airlines where year = 2005;
+-----+
| sum(airtime) |
+-----+
| 708204026 |
+-----+
Fetched 1 row(s) in 1.19s

[localhost:21000] > select sum(airtime) from airlines_external where dayofweek = 1;
+-----+
| sum(airtime) |
+-----+
| 1264945051 |
+-----+
Fetched 1 row(s) in 2.82s
[localhost:21000] > select sum(airtime) from airlines where dayofweek = 1;
+-----+
| sum(airtime) |
+-----+
| 1264945051 |
+-----+
Fetched 1 row(s) in 1.61s

```

Now we can finally do some serious analysis with this data set that, remember, a few minutes ago all we had were some raw data files and we didn't even know what columns they contained. Let's see whether the "air time" of a flight tends to be different depending on the day of the week. We can see that the average is a little higher on day number 6; perhaps Saturday is a busy flying day and planes have to circle for longer at the destination airport before landing.

```

[localhost:21000] > select dayofweek, avg(airtime) from airlines
> group by dayofweek order by dayofweek;
+-----+-----+
| dayofweek | avg(airtime) |
+-----+-----+
| 1         | 102.1560425016671 |
| 2         | 102.1582931538807 |
| 3         | 102.2170009256653 |
| 4         | 102.37477661846   |
| 5         | 102.2697358763511 |
| 6         | 105.3627448363705 |
| 7         | 103.4144351202054 |
+-----+-----+
Fetched 7 row(s) in 2.25s

```

To see if the apparent trend holds up over time, let's do the same breakdown by day of week, but also split up by year. Now we can see that day number 6 consistently has a higher average air time in each year. We can also see that the average air time increased over time across the board. And the presence of NULL for this column in years 1987 to 1994 shows that queries involving this column need to be restricted to a date range of 1995 and higher.

```

[localhost:21000] > select year, dayofweek, avg(airtime) from airlines
> group by year, dayofweek order by year desc, dayofweek;
+-----+-----+-----+
| year | dayofweek | avg(airtime) |
+-----+-----+-----+
| 2008 | 1         | 103.1821651651355 |
| 2008 | 2         | 103.2149301386094 |
| 2008 | 3         | 103.0585076622796 |
| 2008 | 4         | 103.4671383539038 |
| 2008 | 5         | 103.5575385182659 |
+-----+-----+-----+

```

2008	6	107.4006306562128
2008	7	104.8648851041755
2007	1	102.2196114337825
2007	2	101.9317791906348
2007	3	102.0964767689043
2007	4	102.6215927201686
2007	5	102.4289399000661
2007	6	105.1477448215756
2007	7	103.6305945644095
...		
1996	1	99.33860750862108
1996	2	99.54225446396656
1996	3	99.41129336113134
1996	4	99.5110373340348
1996	5	99.22120745027595
1996	6	101.17174471111921
1996	7	99.95410136133704
1995	1	96.93779698300494
1995	2	96.93458674589712
1995	3	97.00972311337051
1995	4	96.90843832024412
1995	5	96.78382115425562
1995	6	98.70872826057003
1995	7	97.85570478374616
1994	1	NULL
1994	2	NULL
1994	3	NULL
...		
1987	5	NULL
1987	6	NULL
1987	7	NULL

Impala Administration

As an administrator, you monitor Impala's use of resources and take action when necessary to keep Impala running smoothly and avoid conflicts with other Hadoop components running on the same cluster. When you detect that an issue has happened or could happen in the future, you reconfigure Impala or other components such as HDFS or even the hardware of the cluster itself to resolve or avoid problems.

Related tasks:

As an administrator, you can expect to perform installation, upgrade, and configuration tasks for Impala on all machines in a cluster. See [Installing Impala](#) on page 29, [Upgrading Impala](#) on page 40, and [Managing Impala](#) on page 32 for details.

For security tasks typically performed by administrators, see [Impala Security](#) on page 100.

Administrators also decide how to allocate cluster resources so that all Hadoop components can run smoothly together. For Impala, this task primarily involves:

- Deciding how many Impala queries can run concurrently and with how much memory, through the admission control feature. See [Admission Control and Query Queuing](#) on page 77 for details.
- Dividing cluster resources such as memory between Impala and other components, using YARN for overall resource management, and Llama to mediate resource requests from Impala to YARN. See [Resource Management for Impala](#) on page 85 for details.

Admission Control and Query Queuing

Admission control is an Impala feature that imposes limits on concurrent SQL queries, to avoid resource usage spikes and out-of-memory conditions on busy CDH clusters. It is a form of “throttling”. New queries are accepted and executed until certain conditions are met, such as too many queries or too much total memory used across the cluster. When one of these thresholds is reached, incoming queries wait to begin execution. These queries are queued and are admitted (that is, begin executing) when the resources become available.

In addition to the threshold values for currently executing queries, you can place limits on the maximum number of queries that are queued (waiting) and a limit on the amount of time they might wait before returning with an error. These queue settings let you ensure that queries do not wait indefinitely, so that you can detect and correct “starvation” scenarios.

Queries, DML statements, and some DDL statements, including `CREATE TABLE AS SELECT` and `COMPUTE STATS` are affected by admission control.

Enable this feature if your cluster is underutilized at some times and overutilized at others. Overutilization is indicated by performance bottlenecks and queries being cancelled due to out-of-memory conditions, when those same queries are successful and perform well during times with less concurrent load. Admission control works as a safeguard to avoid out-of-memory conditions during heavy concurrent usage.



Note:

The use of the Llama component for integrated resource management within YARN is no longer supported with CDH 5.5 / Impala 2.3 and higher.

For clusters running Impala alongside other data management components, you define static service pools to define the resources available to Impala and other components. Then within the area allocated for Impala, you can create dynamic service pools, each with its own settings for the Impala admission control feature.

Overview of Impala Admission Control

On a busy CDH cluster, you might find there is an optimal number of Impala queries that run concurrently. For example, when the I/O capacity is fully utilized by I/O-intensive queries, you might not find any throughput benefit in running more concurrent queries. By allowing some queries to run at full speed while others wait, rather than having all queries contend for resources and run slowly, admission control can result in higher overall throughput.

For another example, consider a memory-bound workload such as many large joins or aggregation queries. Each such query could briefly use many gigabytes of memory to process intermediate results. Because Impala by default cancels queries that exceed the specified memory limit, running multiple large-scale queries at once might require re-running some queries that are cancelled. In this case, admission control improves the reliability and stability of the overall workload by only allowing as many concurrent queries as the overall memory of the cluster can accommodate.

The admission control feature lets you set an upper limit on the number of concurrent Impala queries and on the memory used by those queries. Any additional queries are queued until the earlier ones finish, rather than being cancelled or running slowly and causing contention. As other queries finish, the queued queries are allowed to proceed.

In CDH 5.7 / Impala 2.5 and higher, you can specify these limits and thresholds for each pool rather than globally. That way, you can balance the resource usage and throughput between steady well-defined workloads, rare resource-intensive queries, and ad hoc exploratory queries.

For details on the internal workings of admission control, see [How Impala Schedules and Enforces Limits on Concurrent Queries](#) on page 79.

Concurrent Queries and Admission Control

One way to limit resource usage through admission control is to set an upper limit on the number of concurrent queries. This is the initial technique you might use when you do not have extensive information about memory usage for your workload. This setting can be specified separately for each dynamic resource pool.

You can combine this setting with the memory-based approach described in [Memory Limits and Admission Control](#) on page 78. If either the maximum number of or the expected memory usage of the concurrent queries is exceeded, subsequent queries are queued until the concurrent workload falls below the threshold again.

See [Managing Dynamic Resource Pools](#) for information about all these dynamic resource pool settings, how to use them together, and how to divide different parts of your workload among different pools.

Memory Limits and Admission Control

Each dynamic resource pool can have an upper limit on the cluster-wide memory used by queries executing in that pool. This is the technique to use once you have a stable workload with well-understood memory requirements.

Always specify the **Default Query Memory Limit** for the expected maximum amount of RAM that a query might require on each host, which is equivalent to setting the `MEM_LIMIT` query option for every query run in that pool. That value affects the execution of each query, preventing it from overallocating memory on each host, and potentially activating the spill-to-disk mechanism or cancelling the query when necessary.

Optionally, specify the **Max Memory** setting, a cluster-wide limit that determines how many queries can be safely run concurrently, based on the upper memory limit per host multiplied by the number of Impala nodes in the cluster.

For example, consider the following scenario:

- The cluster is running `impalad` daemons on five DataNodes.
- A dynamic resource pool has **Max Memory** set to 100 GB.
- The **Default Query Memory Limit** for the pool is 10 GB. Therefore, any query running in this pool could use up to 50 GB of memory (default query memory limit * number of Impala nodes).
- The maximum number of queries that Impala executes concurrently within this dynamic resource pool is two, which is the most that could be accommodated within the 100 GB **Max Memory** cluster-wide limit.
- There is no memory penalty if queries use less memory than the **Default Query Memory Limit** per-host setting or the **Max Memory** cluster-wide limit. These values are only used to estimate how many queries can be run concurrently within the resource constraints for the pool.



Note: If you specify **Max Memory** for an Impala dynamic resource pool, you must also specify the **Default Query Memory Limit**. **Max Memory** relies on the **Default Query Memory Limit** to produce a reliable estimate of overall memory consumption for a query.

You can combine the memory-based settings with the upper limit on concurrent queries described in [Concurrent Queries and Admission Control](#) on page 78. If either the maximum number of or the expected memory usage of the concurrent queries is exceeded, subsequent queries are queued until the concurrent workload falls below the threshold again.

See [Managing Dynamic Resource Pools](#) for information about all these dynamic resource pool settings, how to use them together, and how to divide different parts of your workload among different pools.

How Impala Admission Control Relates to Other Resource Management Tools

The admission control feature is similar in some ways to the Cloudera Manager static partitioning feature, as well as the YARN resource management framework. These features can be used separately or together. This section describes some similarities and differences, to help you decide which combination of resource management features to use for Impala.

Admission control is a lightweight, decentralized system that is suitable for workloads consisting primarily of Impala queries and other SQL statements. It sets “soft” limits that smooth out Impala memory usage during times of heavy load, rather than taking an all-or-nothing approach that cancels jobs that are too resource-intensive.

Because the admission control system does not interact with other Hadoop workloads such as MapReduce jobs, you might use YARN with static service pools on CDH 5 clusters where resources are shared between Impala and other Hadoop components. This configuration is recommended when using Impala in a **multitenant** cluster. Devote a percentage of cluster resources to Impala, and allocate another percentage for MapReduce and other batch-style workloads. Let admission control handle the concurrency and memory usage for the Impala work within the cluster, and let YARN manage the work for other components within the cluster. In this scenario, Impala's resources are not managed by YARN.

The Impala admission control feature uses the same configuration mechanism as the YARN resource manager to map users to pools and authenticate them.

Although the Impala admission control feature uses a `fair-scheduler.xml` configuration file behind the scenes, this file does not depend on which scheduler is used for YARN. You still use this file, and Cloudera Manager can generate it for you, even when YARN is using the capacity scheduler.

How Impala Schedules and Enforces Limits on Concurrent Queries

The admission control system is decentralized, embedded in each Impala daemon and communicating through the statestore mechanism. Although the limits you set for memory usage and number of concurrent queries apply cluster-wide, each Impala daemon makes its own decisions about whether to allow each query to run immediately or to queue it for a less-busy time. These decisions are fast, meaning the admission control mechanism is low-overhead, but might be imprecise during times of heavy load across many coordinators. There could be times when the more queries were queued (in aggregate across the cluster) than the specified limit, or when number of admitted queries exceeds the expected number. Thus, you typically err on the high side for the size of the queue, because there is not a big penalty for having a large number of queued queries; and you typically err on the low side for configuring memory resources, to leave some headroom in case more queries are admitted than expected, without running out of memory and being cancelled as a result.

To avoid a large backlog of queued requests, you can set an upper limit on the size of the queue for queries that are queued. When the number of queued queries exceeds this limit, further queries are cancelled rather than being queued. You can also configure a timeout period per pool, after which queued queries are cancelled, to avoid indefinite waits. If a cluster reaches this state where queries are cancelled due to too many concurrent requests or long waits for query execution to begin, that is a signal for an administrator to take action, either by provisioning more resources, scheduling work on the cluster to smooth out the load, or by doing [Impala performance tuning](#) to enable higher throughput.

How Admission Control works with Impala Clients (JDBC, ODBC, HiveServer2)

Most aspects of admission control work transparently with client interfaces such as JDBC and ODBC:

- If a SQL statement is put into a queue rather than running immediately, the API call blocks until the statement is dequeued and begins execution. At that point, the client program can request to fetch results, which might also block until results become available.
- If a SQL statement is cancelled because it has been queued for too long or because it exceeded the memory limit during execution, the error is returned to the client program with a descriptive error message.

In Impala 2.0 and higher, you can submit a SQL `SET` statement from the client application to change the `REQUEST_POOL` query option. This option lets you submit queries to different resource pools, as described in [REQUEST_POOL Query Option](#) on page 351.

At any time, the set of queued queries could include queries submitted through multiple different Impala daemon hosts. All the queries submitted through a particular host will be executed in order, so a `CREATE TABLE` followed by an `INSERT` on the same table would succeed. Queries submitted through different hosts are not guaranteed to be executed in the order they were received. Therefore, if you are using load-balancing or other round-robin scheduling where different statements are submitted through different hosts, set up all table structures ahead of time so that the statements controlled by the queuing system are primarily queries, where order is not significant. Or, if a sequence of statements needs to happen in strict order (such as an `INSERT` followed by a `SELECT`), submit all those statements through a single session, while connected to the same Impala daemon host.

Admission control has the following limitations or special behavior when used with JDBC or ODBC applications:

- The other resource-related query options, `RESERVATION_REQUEST_TIMEOUT` and `V_CPU_CORES`, are no longer used. Those query options only applied to using Impala with Llama, which is no longer supported.

SQL and Schema Considerations for Admission Control

When queries complete quickly and are tuned for optimal memory usage, there is less chance of performance or capacity problems during times of heavy load. Before setting up admission control, tune your Impala queries to ensure that the query plans are efficient and the memory estimates are accurate. Understanding the nature of your workload, and which queries are the most resource-intensive, helps you to plan how to divide the queries into different pools and decide what limits to define for each pool.

For large tables, especially those involved in join queries, keep their statistics up to date after loading substantial amounts of new data or adding new partitions. Use the `COMPUTE STATS` statement for unpartitioned tables, and `COMPUTE INCREMENTAL STATS` for partitioned tables.

When you use dynamic resource pools with a **Max Memory** setting enabled, you typically override the memory estimates that Impala makes based on the statistics from the `COMPUTE STATS` statement. You either set the `MEM_LIMIT` query option within a particular session to set an upper memory limit for queries within that session, or a default `MEM_LIMIT` setting for all queries processed by the `impalad` instance, or a default `MEM_LIMIT` setting for all queries assigned to a particular dynamic resource pool. By designating a consistent memory limit for a set of similar queries that use the same resource pool, you avoid unnecessary query queuing or out-of-memory conditions that can arise during high-concurrency workloads when memory estimates for some queries are inaccurate.

Follow other steps from [Tuning Impala for Performance](#) on page 523 to tune your queries.

Configuring Admission Control

The configuration options for admission control range from the simple (a single resource pool with a single set of options) to the complex (multiple resource pools with different options, each pool handling queries for a different set of users and groups). Cloudera recommends configuring the settings through the Cloudera Manager user interface.



Important: Although the following options are still present in the Cloudera Manager interface under the **Admission Control** configuration settings dialog, Cloudera recommends you not use them in CDH 5.7 / Impala 2.5 and higher. These settings only apply if you enable admission control but leave dynamic resource pools disabled. In CDH 5.7 / Impala 2.5 and higher, prefer to set up dynamic resource pools and customize the settings for each pool, as described in [Creating an Impala Dynamic Resource Pool](#) and [Editing Dynamic Resource Pools](#).

Impala Service Flags for Admission Control (Advanced)

The following Impala configuration options let you adjust the settings of the admission control feature. When supplying the options on the `impalad` command line, prepend the option name with `--`.

`queue_wait_timeout_ms`

Purpose: Maximum amount of time (in milliseconds) that a request waits to be admitted before timing out.

Type: `int64`

Default: 60000

`default_pool_max_requests`

Purpose: Maximum number of concurrent outstanding requests allowed to run before incoming requests are queued. Because this limit applies cluster-wide, but each Impala node makes independent decisions to run queries immediately or queue them, it is a soft limit; the overall number of concurrent queries might be slightly higher during times of heavy load. A negative value indicates no limit. Ignored if `fair_scheduler_config_path` and `llama_site_path` are set.

Type: `int64`

Default: -1, meaning unlimited (prior to CDH 5.7 / Impala 2.5, the default was 200)

`default_pool_max_queued`

Purpose: Maximum number of requests allowed to be queued before rejecting requests. Because this limit applies cluster-wide, but each Impala node makes independent decisions to run queries immediately or queue them, it is a soft limit; the overall number of queued queries might be slightly higher during times of heavy load. A negative value or 0 indicates requests are always rejected once the maximum concurrent requests are executing. Ignored if `fair_scheduler_config_path` and `llama_site_path` are set.

Type: `int64`

Default: unlimited

`default_pool_mem_limit`

Purpose: Maximum amount of memory (across the entire cluster) that all outstanding requests in this pool can use before new requests to this pool are queued. Specified in bytes, megabytes, or gigabytes by a number followed by the suffix `b` (optional), `m`, or `g`, either uppercase or lowercase. You can specify floating-point values for megabytes and gigabytes, to represent fractional numbers such as `1.5`. You can also specify it as a percentage of the physical memory by specifying the suffix `%`. 0 or no setting indicates no limit. Defaults to bytes if no unit is given. Because this limit applies cluster-wide, but each Impala node makes independent decisions to run queries immediately or queue them, it is a soft limit; the overall memory used by concurrent queries might be slightly higher during times of heavy load. Ignored if `fair_scheduler_config_path` and `llama_site_path` are set.



Note: Impala relies on the statistics produced by the `COMPUTE STATS` statement to estimate memory usage for each query. See [COMPUTE STATS Statement](#) on page 241 for guidelines about how and when to use this statement.

Type: `string`

Default: `" "` (empty string, meaning unlimited)

`disable_admission_control`

Purpose: Turns off the admission control feature entirely, regardless of other configuration option settings.

Type: Boolean

Default: `false`

`disable_pool_max_requests`

Purpose: Disables all per-pool limits on the maximum number of running requests.

Type: Boolean

Default: `false`

`disable_pool_mem_limits`

Purpose: Disables all per-pool mem limits.

Type: Boolean

Default: `false`

`fair_scheduler_allocation_path`

Purpose: Path to the fair scheduler allocation file (`fair-scheduler.xml`).

Type: string

Default: `" "` (empty string)

Usage notes: Admission control only uses a small subset of the settings that can go in this file, as described below. For details about all the Fair Scheduler configuration settings, see the [Apache wiki](#).

`llama_site_path`

Purpose: Path to the configuration file used by admission control (`llama-site.xml`). If set, `fair_scheduler_allocation_path` must also be set.

Type: string

Default: `" "` (empty string)

Usage notes: Admission control only uses a few of the settings that can go in this file, as described below.

Configuring Admission Control Using Cloudera Manager

In Cloudera Manager, you can configure pools to manage queued Impala queries, and the options for the limit on number of concurrent queries and how to handle queries that exceed the limit. For details, see [Managing Resources with Cloudera Manager](#).

Configuring Admission Control Using the Command Line

To configure admission control, use a combination of startup options for the Impala daemon and edit or create the configuration files `fair-scheduler.xml` and `llama-site.xml`.

For a straightforward configuration using a single resource pool named `default`, you can specify configuration options on the command line and skip the `fair-scheduler.xml` and `llama-site.xml` configuration files.

For an advanced configuration with multiple resource pools using different settings, set up the `fair-scheduler.xml` and `llama-site.xml` configuration files manually. Provide the paths to each one using the `impalad` command-line options, `--fair_scheduler_allocation_path` and `--llama_site_path` respectively.

The Impala admission control feature only uses the Fair Scheduler configuration settings to determine how to map users and groups to different resource pools. For example, you might set up different resource pools with separate memory limits, and maximum number of concurrent and queued queries, for different categories of users within your organization. For details about all the Fair Scheduler configuration settings, see the [Apache wiki](#).

The Impala admission control feature only uses a small subset of possible settings from the `llama-site.xml` configuration file:

```
llama.am.throttling.maximum.placed.reservations.queue_name
llama.am.throttling.maximum.queued.reservations.queue_name
impala.admission-control.pool-default-query-options.queue_name
impala.admission-control.pool-queue-timeout-ms.queue_name
```

The `impala.admission-control.pool-queue-timeout-ms` setting specifies the timeout value for this pool, in milliseconds. The `impala.admission-control.pool-default-query-options` settings designates the default query options for all queries that run in this pool. Its argument value is a comma-delimited string of 'key=value' pairs, for example, 'key1=val1,key2=val2'. For example, this is where you might set a default memory limit for all queries in the pool, using an argument such as `MEM_LIMIT=5G`.

The `impala.admission-control.*` configuration settings are available in CDH 5.7 and higher.

Examples of Admission Control Configurations

Example Admission Control Configurations Using Cloudera Manager

For full instructions about configuring dynamic resource pools through Cloudera Manager, see http://www.cloudera.com/documentation/enterprise/latest/topics/cm_mc_resource_pools.html.

Example Admission Control Configurations Using Configuration Files

For clusters not managed by Cloudera Manager, here are sample `fair-scheduler.xml` and `llama-site.xml` files that define resource pools `root.default`, `root.development`, and `root.production`. These sample files are stripped down: in a real deployment they might contain other settings for use with various aspects of the YARN component. The settings shown here are the significant ones for the Impala admission control feature.

fair-scheduler.xml:

Although Impala does not use the `vcores` value, you must still specify it to satisfy YARN requirements for the file contents.

Each `<aclSubmitApps>` tag (other than the one for `root`) contains a comma-separated list of users, then a space, then a comma-separated list of groups; these are the users and groups allowed to submit Impala statements to the corresponding resource pool.

If you leave the `<aclSubmitApps>` element empty for a pool, nobody can submit directly to that pool; child pools can specify their own `<aclSubmitApps>` values to authorize users and groups to submit to those pools.

```
<allocations>
  <queue name="root">
    <aclSubmitApps> </aclSubmitApps>
    <queue name="default">
      <maxResources>50000 mb, 0 vcores</maxResources>
      <aclSubmitApps>*</aclSubmitApps>
    </queue>
    <queue name="development">
      <maxResources>200000 mb, 0 vcores</maxResources>
      <aclSubmitApps>user1,user2 dev,ops,admin</aclSubmitApps>
    </queue>
    <queue name="production">
      <maxResources>1000000 mb, 0 vcores</maxResources>
      <aclSubmitApps> ops,admin</aclSubmitApps>
    </queue>
  </queue>
  <queuePlacementPolicy>
    <rule name="specified" create="false"/>
    <rule name="default" />
  </queuePlacementPolicy>
</allocations>
```

llama-site.xml:

```

<?xml version="1.0" encoding="UTF-8"?>
<configuration>
  <property>
    <name>llama.am.throttling.maximum.placed.reservations.root.default</name>
    <value>10</value>
  </property>
  <property>
    <name>llama.am.throttling.maximum.queued.reservations.root.default</name>
    <value>50</value>
  </property>
  <property>
    <name>impala.admission-control.pool-default-query-options.root.default</name>
    <value>mem_limit=128m,query_timeout_s=20,max_io_buffers=10</value>
  </property>
  <property>
    <name>impala.admission-control.pool-queue-timeout-ms.root.default</name>
    <value>30000</value>
  </property>
  <property>
    <name>llama.am.throttling.maximum.placed.reservations.root.development</name>
    <value>50</value>
  </property>
  <property>
    <name>llama.am.throttling.maximum.queued.reservations.root.development</name>
    <value>100</value>
  </property>
  <property>
    <name>impala.admission-control.pool-default-query-options.root.development</name>
    <value>mem_limit=256m,query_timeout_s=30,max_io_buffers=10</value>
  </property>
  <property>
    <name>impala.admission-control.pool-queue-timeout-ms.root.development</name>
    <value>15000</value>
  </property>
  <property>
    <name>llama.am.throttling.maximum.placed.reservations.root.production</name>
    <value>100</value>
  </property>
  <property>
    <name>llama.am.throttling.maximum.queued.reservations.root.production</name>
    <value>200</value>
  </property>
<!--
  Default query options for the 'root.production' pool.
  THIS IS A NEW PARAMETER in CDH 5.7 / Impala 2.5.
  Note that the MEM_LIMIT query option still shows up in here even though it is a
  separate box in the UI. We do that because it is the most important query option
  that people will need (everything else is somewhat advanced).

  MEM_LIMIT takes a per-node memory limit which is specified using one of the
  following:
  - '<int>[bB]?' -> bytes (default if no unit given)
  - '<float>[mM(bB)]' -> megabytes
  - '<float>[gG(bB)]' -> in gigabytes
  E.g. 'MEM_LIMIT=12345' (no unit) means 12345 bytes, and you can append m or g
  to specify megabytes or gigabytes, though that is not required.
-->
  <property>
    <name>impala.admission-control.pool-default-query-options.root.production</name>
    <value>mem_limit=386m,query_timeout_s=30,max_io_buffers=10</value>
  </property>
<!--
  Default queue timeout (ms) for the pool 'root.production'.
  If this isn't set, the process-wide flag is used.
  THIS IS A NEW PARAMETER in CDH 5.7 / Impala 2.5.
-->
  <property>
    <name>impala.admission-control.pool-queue-timeout-ms.root.production</name>
    <value>30000</value>

```

```
</property>
</configuration>
```

Guidelines for Using Admission Control

To see how admission control works for particular queries, examine the profile output for the query. This information is available through the `PROFILE` statement in `impala-shell` immediately after running a query in the shell, on the **queries** page of the Impala debug web UI, or in the Impala log file (basic information at log level 1, more detailed information at log level 2). The profile output contains details about the admission decision, such as whether the query was queued or not and which resource pool it was assigned to. It also includes the estimated and actual memory usage for the query, so you can fine-tune the configuration for the memory limits of the resource pools.

Where practical, use Cloudera Manager to configure the admission control parameters. The Cloudera Manager GUI is much simpler than editing the configuration files directly.

Remember that the limits imposed by admission control are “soft” limits. The decentralized nature of this mechanism means that each Impala node makes its own decisions about whether to allow queries to run immediately or to queue them. These decisions rely on information passed back and forth between nodes by the statestore service. If a sudden surge in requests causes more queries than anticipated to run concurrently, then throughput could decrease due to queries spilling to disk or contending for resources; or queries could be cancelled if they exceed the `MEM_LIMIT` setting while running.

In `impala-shell`, you can also specify which resource pool to direct queries to by setting the `REQUEST_POOL` query option.

If you set up different resource pools for different users and groups, consider reusing any classifications you developed for use with Sentry security. See [Enabling Sentry Authorization for Impala](#) on page 105 for details.

For details about all the Fair Scheduler configuration settings, see [Fair Scheduler Configuration](#), in particular the tags such as `<queue>` and `<aclSubmitApps>` to map users and groups to particular resource pools (queues).

Resource Management for Impala



Note:

The use of the Llama component for integrated resource management within YARN is no longer supported with CDH 5.5 / Impala 2.3 and higher.

For clusters running Impala alongside other data management components, you define static service pools to define the resources available to Impala and other components. Then within the area allocated for Impala, you can create dynamic service pools, each with its own settings for the Impala admission control feature.

You can limit the CPU and memory resources used by Impala, to manage and prioritize workloads on clusters that run jobs from many Hadoop components.

How Resource Limits Are Enforced

- If Cloudera Manager Static Partitioning is used, it creates a cgroup in which Impala runs. This cgroup limits CPU, network, and IO according to the static partitioning policy.
- Limits on memory usage are enforced by Impala's process memory limit (the `MEM_LIMIT` query option setting). The admission control feature checks this setting to decide how many queries can be safely run at the same time. Then the Impala daemon enforces the limit by activating the spill-to-disk mechanism when necessary, or cancelling a query altogether if the limit is exceeded at runtime.

impala-shell Query Options for Resource Management

Before issuing SQL statements through the `impala-shell` interpreter, you can use the `SET` command to configure the following parameters related to resource management:

- [EXPLAIN_LEVEL Query Option](#) on page 336
- [MEM_LIMIT Query Option](#) on page 344

Limitations of Resource Management for Impala

The `MEM_LIMIT` query option, and the other resource-related query options, are settable through the ODBC or JDBC interfaces in Impala 2.0 and higher. This is a former limitation that is now lifted.

How to Configure Resource Management for Impala

Impala includes features that balance and maximize resources in your CDH cluster. This topic describes how you can enhance a CDH cluster using Impala to improve efficiency.

A typical deployment uses the following.

- Creating Static Service Pools
- Using Admission Control
 - Setting Per-query Memory Limits
 - Creating Dynamic Resource Pools

Creating Static Service Pools

Use Static Service Pools to allocate dedicated resources for Impala and other services to allow for predictable resource availability.

Static service pools isolate services from one another, so that high load on one service has bounded impact on other services. You can use Cloudera Manager to configure static service pools that control memory, CPU and Disk I/O.

The following screenshot shows a sample configuration for Static Service Pools in Cloudera Manager:

Service	Allocation %
HBase	5 %
HDFS	5 %
Impala	50 %
Kudu	5 %
Solr	5 %
YARN	30 %
Total	100 %

- HDFS always needs to have a minimum of 5-10% of the resources.
- Generally, YARN and Impala split the rest of the resources.
 - For mostly batch workloads, you might allocate YARN 60%, Impala 30%, and HDFS 10%.
 - For mostly ad hoc query workloads, you might allocate Impala 60%, YARN 30%, and HDFS 10%.

Using Admission Control

Within the constraints of the static service pool, you can further subdivide Impala's resources using Admission Control. You configure Impala Admission Control pools in the Cloudera Manager Dynamic Resource Pools page.

You use Admission Control to divide usage between Dynamic Resource Pools in multitenant use cases. Allocating resources judiciously allows your most important queries to run faster and more reliably.



Note: In this context, Impala Dynamic Resource Pools are different than the default YARN Dynamic Resource Pools. You can turn on Dynamic Resource Pools that are exclusively for use by Impala.

Admission Control is enabled by default.

A Dynamic Resource Pool has the following properties:

- **Max Running Queries:** Maximum number of concurrently executing queries in the pool before incoming queries are queued.
- **Max Memory Resources:** Maximum memory used by queries in the pool before incoming queries are queued. This value is used at the time of admission and is not enforced at query runtime.
- **Default Query Memory Limit:** Defines the maximum amount of memory a query can allocate on each node. This is enforced at runtime. If the query attempts to use more memory, it is forced to spill, if possible. Otherwise, it is cancelled. The total memory that can be used by a query is the `MEM_LIMIT` times the number of nodes.
- **Max Queued Queries:** Maximum number of queries that can be queued in the pool before additional queries are rejected.
- **Queue Timeout:** Specifies how long queries can wait in the queue before they are cancelled with a timeout error.

Setting Per-query Memory Limits

Use per-query memory limits to prevent queries from consuming excessive memory resources that impact other queries. Cloudera recommends that you set the query memory limits whenever possible.


If you set the **Pool Max Mem Resources** for a resource pool, Impala attempts to throttle queries if there is not enough memory to run them within the specified resources.

Only use admission control with maximum memory resources if you can ensure there are query memory limits. Set the pool **Default Query Memory Limit** to be certain. You can override this setting with the `query` option, if necessary.


Typically, you set query memory limits using the `set MEM_LIMIT=Xg;` query option. When you find the right value for your business case, memory-based admission control works well. The potential downside is that queries that attempt to use more memory might perform poorly or even be cancelled.

To find a reasonable default query memory limit:

1. Run the workload.
2. In Cloudera Manager, go to **Impala > Queries**.
3. Click **Select Attributes**.
4. Select **Per Node Peak Memory Usage** and click **Update**.
5. Allow the system time to gather information, then click the **Show Histogram** icon to see the results.



6. Use the histogram to find a value that accounts for most queries. Queries that require more resources than this limit should explicitly set the memory limit to ensure they can run to completion.



Creating Dynamic Resource Pools

A dynamic resource pool is a named configuration of resources and a policy for scheduling the resources among Impala queries running in the pool. Dynamic resource pools allow you to schedule and allocate resources to Impala queries based on a user's access to specific pools and the resources available to those pools.

This example creates both production and development resource pools or queues. It assumes you have 3 worker nodes with 24GiB of RAM each for an aggregate memory of 72000MiB. This pool configuration allocates the Production queue twice the memory resources of the Development queue, and a higher number of concurrent queries.

To create a Production dynamic resource pool for Impala:

1. In Cloudera Manager, select **Clusters > Dynamic Resource Pool Configuration**.
2. Click the **Impala Admission Control** tab.
3. Click **Create Resource Pool**.
4. Specify a name and resource limits for the Production pool:
 - In the **Resource Pool Name** field, enter `Production`.
 - In the **Max Memory** field, enter `48000`.
 - In the **Default Query Memory Limit** field, enter `1600`.
 - In the **Max Running Queries** field, enter `10`.
 - In the **Max Queued Queries** field, enter `200`.
5. Click **Create**.
6. Click **Refresh Dynamic Resource Pools**.

The Production queue runs up to 10 queries at once. If the total memory requested by these queries exceeds 48000 MiB, it holds the next query in the queue until the memory is released. It also prevents a query from running if it needs more memory than is currently available. Admission Control holds the next query if either Max Running Queries is reached, or the pool Max Memory limit is reached.

Here, Max Memory resources and Default Query Memory Limit throttle throughput to 10 queries, so setting Max Running Queries might not be necessary, though it does not hurt to do so. Most users set Max Running Queries when they cannot pick good numbers for memory. Since users can override the query option `mem_limit`, setting the Max Running Queries property might make sense.

To create a Development dynamic resource pool for Impala:

1. In Cloudera Manager, select **Clusters > Dynamic Resource Pool Configuration**.
2. Click the **Impala Admission Control** tab.

3. Click Create Resource Pool.**4. Specify a name and resource limits for the Development pool:**

- In the **Resource Pool Name** field, enter `Development`.
- In the **Max Memory** field, enter `24000`.
- In the **Default Query Memory Limit** field, enter `8000`.
- In the **Max Running Queries** field, enter `1`.
- In the **Max Queued Queries** field, enter `100`.

5. Click Create.**6. Click Refresh Dynamic Resource Pools.**

The Development queue runs one query at a time. If the total memory required by the query exceeds 24000 MiB, it holds the query until memory is released.

Understanding Placement Rules

Placement rules determine how queries are mapped to resource pools. The standard settings are to use a specified pool when specified; otherwise, use the default pool.

For example, you can use the SET statement to select the pool in which to run a query.

```
SET REQUEST_POOL=Production;
```

If you do not use a SET statement, queries are run in the default pool.

Setting Access Control on Pools

You can specify that only certain users and groups are allowed to use the pools you define.

To create a Development dynamic resource pool for Impala:

1. In Cloudera Manager, select **Clusters > Dynamic Resource Pool Configuration**.
2. Click the **Impala Admission Control** tab.
3. Click the **Edit** button for the Production pool.
4. Click the Submission Access Control tab.
5. Select **Allow these users and groups to submit to this pool**.
6. Enter a comma-separated list of users who can use the pool.

Edit Resource Pool
✕

Resource Pool Name

Configuration Sets

Submission Access Control

Fair Scheduler Access Control Lists control who can submit queries to pools.

Allow anyone to submit to this pool

Allow these users and groups to submit to this pool

Users

Groups

7. Click Save.

Impala Resource Management Example

Anne Chang is administrator for an enterprise data hub that runs a number of workloads, including Impala.

Anne has a 20-node cluster that uses Cloudera Manager static partitioning. Because of the heavy Impala workload, Anne needs to make sure Impala gets enough resources. While the best configuration values might not be known in advance, she decides to start by allocating 50% of resources to Impala. Each node has 128 GiB dedicated to each impalad. Impala has 2560 GiB in aggregate that can be shared across the resource pools she creates.

Next, Anne studies the workload in more detail. After some research, she might choose to revisit these initial values for static partitioning.

To figure out how to further allocate Impala’s resources, Anne needs to consider the workloads and users, and determine their requirements. There are a few main sources of Impala queries:

- Large reporting queries executed by an external process/tool. These are critical business intelligence queries that are important for business decisions. It is important that they get the resources they need to run. There typically are not many of these queries at a given time.
- Frequent, small queries generated by a web UI. These queries scan a limited amount of data and do not require expensive joins or aggregations. These queries are important, but not as critical, perhaps the client tries resending the query or the end user refreshes the page.
- Occasionally, expert users might run ad-hoc queries. The queries can vary significantly in their resource requirements. While Anne wants a good experience for these users, it is hard to control what they do (for example, submitting inefficient or incorrect queries by mistake). Anne restricts these queries by default and tells users to reach out to her if they need more resources.

To set up admission control for this workload, Anne first runs the workloads independently, so that she can observe the workload’s resource usage in Cloudera Manager. If they could not easily be run manually, but had been run in the past, Anne uses the history information from Cloudera Manager. It can be helpful to use other search criteria (for example, *user*) to isolate queries by workload. Anne uses the Cloudera Manager chart for Per-Node Peak Memory usage to identify the maximum memory requirements for the queries.

From this data, Anne observes the following about the queries in the groups above:

- Large reporting queries use up to 32 GiB per node. There are typically 1 or 2 queries running at a time. On one occasion, she observed that 3 of these queries were running concurrently. Queries can take 3 minutes to complete.
- Web UI-generated queries use between 100 MiB per node to usually less than 4 GiB per node of memory, but occasionally as much as 10 GiB per node. Queries take, on average, 5 seconds, and there can be as many as 140 incoming queries per minute.
- Anne has little data on ad hoc queries, but some are trivial (approximately 100 MiB per node), others join several tables (requiring a few GiB per node), and one user submitted a huge cross join of all tables that used all system resources (that was likely a mistake).

Based on these observations, Anne creates the admission control configuration with the following pools:

XL_Reporting

Property	Value
Max Memory	1280 GiB
Default Query Memory Limit	32 GiB
Max Running Queries	2
Queue Timeout	5 minutes

This pool is for large reporting queries. In order to support running 2 queries at a time, the pool memory resources are set to 1280 GiB (aggregate cluster memory). This is for 2 queries, each with 32 GiB per node, across 20 nodes. Anne sets the pool’s Default Query Memory Limit to 32 GiB so that no query uses more than 32 GiB on any given node. She sets Max Running Queries to 2 (though it is not necessary she do so). She increases the pool’s queue timeout to 5 minutes in case a third query comes in and has to wait. She does not expect more than 3 concurrent queries, and she

does not want them to wait that long anyway, so she does not increase the queue timeout. If the workload increases in the future, she might choose to adjust the configuration or buy more hardware.

HighThroughput_UI

Property	Value
Max Memory	960 GiB (inferred)
Default Query Memory Limit	4 GiB
Max Running Queries	12
Queue Timeout	5 minutes

This pool is used for the small, high throughput queries generated by the web tool. Anne sets the Default Query Memory Limit to 4 GiB per node, and sets Max Running Queries to 12. This implies a maximum amount of memory per node used by the queries in this pool: 48 GiB per node (12 queries * 4 GiB per node memory limit).

Notice that Anne does not set the pool memory resources, but does set the pool's Default Query Memory Limit. This is intentional: admission control processes queries faster when a pool uses the Max Running Queries limit instead of the peak memory resources.

This should be enough memory for most queries, since only a few go over 4 GiB per node. For those that do require more memory, they can probably still complete with less memory (spilling if necessary). If, on occasion, a query cannot run with this much memory and it fails, Anne might reconsider this configuration later, or perhaps she does not need to worry about a few rare failures from this web UI.

With regard to throughput, since these queries take around 5 seconds and she is allowing 12 concurrent queries, the pool should be able to handle approximately 144 queries per minute, which is enough for the peak maximum expected of 140 queries per minute. In case there is a large burst of queries, Anne wants them to queue. The default maximum size of the queue is already 200, which should be more than large enough. Anne does not need to change it.

Default

Property	Value
Max Memory	320 GiB
Default Query Memory Limit	4 GiB
Max Running Queries	Unlimited
Queue Timeout	60 Seconds

The default pool (which already exists) is a catch all for ad-hoc queries. Anne wants to use the remaining memory not used by the first two pools, 16 GiB per node (XL_Reporting uses 64 GiB per node, High_Throughput_UI uses 48 GiB per node). For the other pools to get the resources they expect, she must still set the Max Memory resources and the Default Query Memory Limit. She sets the Max Memory resources to 320 GiB (16 * 20). She sets the Default Query Memory Limit to 4 GiB per node for now. That is somewhat arbitrary, but satisfies some of the ad hoc queries she observed. If someone writes a bad query by mistake, she does not actually want it using all the system resources. If a user has a large query to submit, an expert user can override the Default Query Memory Limit (up to 16 GiB per node, since that is bound by the pool Max Memory resources). If that is still insufficient for this user's workload, the user should work with Anne to adjust the settings and perhaps create a dedicated pool for the workload.

Setting Timeout Periods for Daemons, Queries, and Sessions

Depending on how busy your CDH cluster is, you might increase or decrease various timeout values. Increase timeouts if Impala is cancelling operations prematurely, when the system is responding slower than usual but the operations

are still successful if given extra time. Decrease timeouts if operations are idle or hanging for long periods, and the idle or hung operations are consuming resources and reducing concurrency.

Increasing the Statestore Timeout

If you have an extensive Impala schema, for example with hundreds of databases, tens of thousands of tables, and so on, you might encounter timeout errors during startup as the Impala catalog service broadcasts metadata to all the Impala nodes using the statestore service. To avoid such timeout errors on startup, increase the statestore timeout value from its default of 10 seconds. Specify the timeout value using the `-statestore_subscriber_timeout_seconds` option for the statestore service, using the configuration instructions in [Modifying Impala Startup Options](#) on page 45. The symptom of this problem is messages in the `impalad` log such as:

```
Connection with state-store lost
Trying to re-register with state-store
```

See [Scalability Considerations for the Impala Statestore](#) on page 561 for more details about statestore operation and settings on clusters with a large number of Impala-related objects such as tables and partitions.

Setting the Idle Query and Idle Session Timeouts for `impalad`

To keep long-running queries or idle sessions from tying up cluster resources, you can set timeout intervals for both individual queries, and entire sessions.



Note:

The timeout clock for queries and sessions only starts ticking when the query or session is idle. For queries, this means the query has results ready but is waiting for a client to fetch the data. A query can run for an arbitrary time without triggering a timeout, because the query is computing results rather than sitting idle waiting for the results to be fetched. The timeout period is intended to prevent unclosed queries from consuming resources and taking up slots in the admission count of running queries, potentially preventing other queries from starting.

For sessions, this means that no query has been submitted for some period of time.

Specify the following startup options for the `impalad` daemon:

- The `--idle_query_timeout` option specifies the time in seconds after which an idle query is cancelled. This could be a query whose results were all fetched but was never closed, or one whose results were partially fetched and then the client program stopped requesting further results. This condition is most likely to occur in a client program using the JDBC or ODBC interfaces, rather than in the interactive `impala-shell` interpreter. Once the query is cancelled, the client program cannot retrieve any further results.

You can reduce the idle query timeout by using the `QUERY_TIMEOUT_S` query option. Any value specified for the `--idle_query_timeout` startup option serves as an upper limit for the `QUERY_TIMEOUT_S` query option. See [QUERY_TIMEOUT_S Query Option \(CDH 5.2 or higher only\)](#) on page 350 for details.

- The `--idle_session_timeout` option specifies the time in seconds after which an idle session is expired. A session is idle when no activity is occurring for any of the queries in that session, and the session has not started any new queries. Once a session is expired, you cannot issue any new query requests to it. The session remains open, but the only operation you can perform is to close it. The default value of 0 means that sessions never expire.

For instructions on changing `impalad` startup options, see [Modifying Impala Startup Options](#) on page 45.

**Note:**

To avoid excessive polling, Impala checks periodically for idle sessions and queries to cancel. The actual idle time before cancellation might be up to 50% greater than the specified configuration setting. For example, if the timeout setting was 60, the session or query might be cancelled after being idle between 60 and 90 seconds.

Setting Timeout and Retries for Thrift Connections to the Backend Client

Impala connections to the backend client are subject to failure in cases when the network is momentarily overloaded. To avoid failed queries due to transient network problems, you can configure the number of Thrift connection retries using the following option:

- The `--backend_client_connection_num_retries` option specifies the number of times Impala will try connecting to the backend client after the first connection attempt fails. By default, `impalad` will attempt three re-connections before it returns a failure.

You can configure timeouts for sending and receiving data from the backend client. Therefore, if for some reason a query hangs, instead of waiting indefinitely for a response, Impala will terminate the connection after a configurable timeout.

- The `--backend_client_rpc_timeout_ms` option can be used to specify the number of milliseconds Impala should wait for a response from the backend client before it terminates the connection and signals a failure. The default value for this property is 300000 milliseconds, or 5 minutes.

Cancelling a Query

Sometimes, an Impala query might run for an unexpectedly long time, tying up resources in the cluster. You can cancel the query explicitly, independent of the timeout period, by going into the web UI for the `impalad` host (on port 25000 by default), and using the link on the `/queries` tab to cancel the running query. Various client applications let you interactively cancel queries submitted or monitored through those applications. For example, by pressing `^C` in `impala-shell`, clicking the **Cancel** button from the **Watch** page in Hue, clicking **Actions > Cancel** from the **Queries** list in Cloudera Manager, and so on.

Using Impala through a Proxy for High Availability

For most clusters that have multiple users and production availability requirements, you might set up a proxy server to relay requests to and from Impala.

Currently, the Impala statestore mechanism does not include such proxying and load-balancing features. Set up a software package of your choice to perform these functions.

**Note:**

Most considerations for load balancing and high availability apply to the `impalad` daemon. The `statestored` and `catalogd` daemons do not have special requirements for high availability, because problems with those daemons do not result in data loss. If those daemons become unavailable due to an outage on a particular host, you can stop the Impala service, delete the **Impala StateStore** and **Impala Catalog Server** roles, add the roles on a different host, and restart the Impala service.

Overview of Proxy Usage and Load Balancing for Impala

Using a load-balancing proxy server for Impala has the following advantages:

- Applications connect to a single well-known host and port, rather than keeping track of the hosts where the `impalad` daemon is running.

- If any host running the `impalad` daemon becomes unavailable, application connection requests still succeed because you always connect to the proxy server rather than a specific host running the `impalad` daemon.
- The coordinator node for each Impala query potentially requires more memory and CPU cycles than the other nodes that process the query. The proxy server can schedule queries so that each connection uses a different coordinator node. This load-balancing technique lets the Impala nodes share this additional work, rather than concentrating it on a single machine.

The following setup steps are a general outline that apply to any load-balancing proxy software:

1. Select and download a load-balancing proxy software or other load-balancing hardware appliance. It should only need to be installed and configured on a single host, typically on an edge node. Pick a host other than the DataNodes where `impalad` is running, because the intention is to protect against the possibility of one or more of these DataNodes becoming unavailable.
2. Configure the load balancer (typically by editing a configuration file). In particular:
 - Set up a port that the load balancer will listen on to relay Impala requests back and forth.
 - See [Choosing the Load-Balancing Algorithm](#) on page 94 for load balancing algorithm options.
 - For Kerberized clusters, follow the instructions in [Special Proxy Considerations for Clusters Using Kerberos](#) on page 95.
3. If you are using Hue or JDBC-based applications, you typically set up load balancing for both ports 21000 and 21050, because these client applications connect through port 21050 while the `impala-shell` command connects through port 21000. See [Ports Used by Impala](#) on page 639 for when to use port 21000, 21050, or another value depending on what type of connections you are load balancing.
4. Run the load-balancing proxy server, pointing it at the configuration file that you set up.
5. On systems managed by Cloudera Manager, on the page **Impala > Configuration > Impala Daemon Default Group**, specify a value for the **Impala Daemons Load Balancer** field. Specify the address of the load balancer in `host:port` format. This setting lets Cloudera Manager route all appropriate Impala-related operations through the proxy server.
6. For any scripts, jobs, or configuration settings for applications that formerly connected to a specific datanode to run Impala SQL statements, change the connection information (such as the `-i` option in `impala-shell`) to point to the load balancer instead.



Note: The following sections use the HAProxy software as a representative example of a load balancer that you can use with Impala. For information specifically about using Impala with the F5 BIG-IP load balancer, see [Impala HA with F5 BIG-IP](#).

Choosing the Load-Balancing Algorithm

Load-balancing software offers a number of algorithms to distribute requests. Each algorithm has its own characteristics that make it suitable in some situations but not others.

Leastconn

Connects sessions to the coordinator with the fewest connections, to balance the load evenly. Typically used for workloads consisting of many independent, short-running queries. In configurations with only a few client machines, this setting can avoid having all requests go to only a small set of coordinators.

Recommended for Impala with F5.

Source IP Persistence

Sessions from the same IP address always go to the same coordinator. A good choice for Impala workloads containing a mix of queries and DDL statements, such as `CREATE TABLE` and `ALTER TABLE`. Because the metadata changes from a DDL statement take time to propagate across the cluster, prefer to use the Source IP Persistence algorithm in this case. If you are unable to choose Source IP Persistence, run the DDL and subsequent queries that depend on the results of the DDL through the same session, for example by running `impala-shell -f script_file` to submit several statements through a single session.

Required for setting up high availability with Hue.

Round-robin

Distributes connections to all coordinator nodes. Typically not recommended for Impala.

You might need to perform benchmarks and load testing to determine which setting is optimal for your use case. Always setup using two load-balancing algorithms: Source IP Persistence for Hue and Leastconn for others.

Special Proxy Considerations for Clusters Using Kerberos

In a cluster using Kerberos, applications check host credentials to verify that the host they are connecting to is the same one that is actually processing the request, to prevent man-in-the-middle attacks.



Note: Once you enable HAProxy for load balancing in a Kerberized cluster, users will not be able to connect to individual impala daemons directly from Impala shell.

To clarify that the load-balancing proxy server is legitimate, perform these extra Kerberos setup steps:

1. This section assumes you are starting with a Kerberos-enabled cluster. See [Enabling Kerberos Authentication for Impala](#) on page 116 for instructions for setting up Impala with Kerberos. See the *CDH Security Guide* for [general steps to set up Kerberos](#).
2. Choose the host you will use for the proxy server. Based on the Kerberos setup procedure, it should already have an entry `impala/proxy_host@realm` in its keytab. If not, go back over the initial Kerberos configuration steps for the keytab on each host running the `impalad` daemon.
3. For a cluster managed by Cloudera Manager (5.1 or higher), fill in the Impala configuration setting **Impala Daemons Load Balancer** with the appropriate host:port combination. Then restart the Impala service. For systems using a recent level of Cloudera Manager, this is all the configuration you need; you can skip the remaining steps in this procedure.
4. On systems not managed by Cloudera Manager, or systems using Cloudera Manager earlier than 5.1:
 - a. Copy the keytab file from the proxy host to all other hosts in the cluster that run the `impalad` daemon. (For optimal performance, `impalad` should be running on all DataNodes in the cluster.) Put the keytab file in a secure location on each of these other hosts.
 - b. Add an entry `impala/actual_hostname@realm` to the keytab on each host running the `impalad` daemon.
 - c. For each `impalad` node, merge the existing keytab with the proxy's keytab using `ktutil`, producing a new keytab file. For example:

```
$ ktutil
ktutil: read_kt proxy.keytab
ktutil: read_kt impala.keytab
ktutil: write_kt proxy_impala.keytab
ktutil: quit
```



Note:

On systems managed by Cloudera Manager 5.1.0 and later, the keytab merging happens automatically. To verify that Cloudera Manager has merged the keytabs, run the command:

```
klist -k keytabfile
```

The command lists the credentials for both `principal` and `be_principal` on all nodes.

- d. Make sure that the `impala` user has permission to read this merged keytab file.
- e. Change some configuration settings for each host in the cluster that participates in the load balancing. Follow the appropriate steps depending on whether you use Cloudera Manager or not:

- In the `impalad` option definition, or the advanced configuration snippet, add:

```
--principal=impala/proxy_host@realm
--be_principal=impala/actual_host@realm
--keytab_file=path_to_merged_keytab
```

**Note:**

On a cluster managed by Cloudera Manager 5.1 (or higher), when you set up Kerberos authentication using the wizard, you can choose to allow Cloudera Manager to deploy the `krb5.conf` on your cluster. In such a case, you do not need to explicitly modify safety valve parameters as directed above.

Every host has a different `--be_principal` because the actual hostname is different on each host.

Specify the fully qualified domain name (FQDN) for the proxy host, not the IP address. Use the exact FQDN as returned by a reverse DNS lookup for the associated IP address.

- On a cluster managed by Cloudera Manager, create a role group to set the configuration values from the preceding step on a per-host basis.
 - On a cluster not managed by Cloudera Manager, see [Modifying Impala Startup Options](#) on page 45 for the procedure to modify the startup options.
- f. Restart Impala to make the changes take effect. Follow the appropriate steps depending on whether you use Cloudera Manager or not:
- On a cluster managed by Cloudera Manager, restart the Impala service.
 - On a cluster not managed by Cloudera Manager, restart the `impalad` daemons on all hosts in the cluster, as well as the `statedored` and `catalogd` daemons.

Example of Configuring HAProxy Load Balancer for Impala

If you are not already using a load-balancing proxy, you can experiment with [HAProxy](#) a free, open source load balancer.

This example shows how you might install and configure that load balancer on a Red Hat Enterprise Linux system.

- Install the load balancer: `yum install haproxy`
- Set up the configuration file: `/etc/haproxy/haproxy.cfg`. See the following section for a sample configuration file.
- Run the load balancer (on a single host, preferably one not running `impalad`):

```
/usr/sbin/haproxy -f /etc/haproxy/haproxy.cfg
```

- In `impala-shell`, JDBC applications, or ODBC applications, connect to the listener port of the proxy host, rather than port 21000 or 21050 on a host actually running `impalad`. The sample configuration file sets haproxy to listen on port 25003, therefore you would send all requests to `haproxy_host:25003`.

This is the sample `haproxy.cfg` used in this example:

```
global
# To have these messages end up in /var/log/haproxy.log you will
# need to:
#
# 1) configure syslog to accept network log events. This is done
# by adding the '-r' option to the SYSLOGD_OPTIONS in
# /etc/sysconfig/syslog
#
```



```

# 2) configure local2 events to go to the /var/log/haproxy.log
# file. A line like the following can be added to
# /etc/sysconfig/syslog
#
# local2.* /var/log/haproxy.log
#
log 127.0.0.1 local0
log 127.0.0.1 local1 notice
chroot /var/lib/haproxy
pidfile /var/run/haproxy.pid
maxconn 4000
user haproxy
group haproxy
daemon

# turn on stats unix socket
#stats socket /var/lib/haproxy/stats

#-----
# common defaults that all the 'listen' and 'backend' sections will
# use if not designated in their block
#
# You might need to adjust timing values to prevent timeouts.
#-----
defaults
mode http
log global
option httplog
option dontlognull
option http-server-close
option forwardfor except 127.0.0.0/8
option redispatch
retries 3
maxconn 3000
contimeout 5000
clitimeout 50000
srvtimeout 50000

#
# This sets up the admin page for HA Proxy at port 25002.
#
listen stats :25002
balance
mode http
stats enable
stats auth username:password

# This is the setup for Impala. Impala client connect to load_balancer_host:25003.
# HAProxy will balance connections among the list of servers listed below.
# The list of Impalad is listening at port 21000 for beeswax (impala-shell) or original
# ODBC driver.
# For JDBC or ODBC version 2.x driver, use port 21050 instead of 21000.
listen impala :25003
mode tcp
option tcplog
balance leastconn

server symbolic_name_1 impala-host-1.example.com:21000 check
server symbolic_name_2 impala-host-2.example.com:21000 check
server symbolic_name_3 impala-host-3.example.com:21000 check
server symbolic_name_4 impala-host-4.example.com:21000 check

# Setup for Hue or other JDBC-enabled applications.
# In particular, Hue requires sticky sessions.
# The application connects to load_balancer_host:21051, and HAProxy balances
# connections to the associated hosts, where Impala listens for JDBC
# requests on port 21050.
listen impalajdbc :21051
mode tcp
option tcplog
balance source
server symbolic_name_5 impala-host-1.example.com:21050 check
server symbolic_name_6 impala-host-2.example.com:21050 check

```

```
server symbolic_name_7 impala-host-3.example.com:21050 check
server symbolic_name_8 impala-host-4.example.com:21050 check
```



Important: Hue requires the `check` option at the end of each line in the above file to ensure HAProxy can detect any unreachable Impalad server, and failover can be successful. Without the TCP check, you can hit an error when the `impalad` daemon to which Hue tries to connect is down.



Note: If your JDBC or ODBC application connects to Impala through a load balancer such as `haproxy`, be cautious about reusing the connections. If the load balancer has set up connection timeout values, either check the connection frequently so that it never sits idle longer than the load balancer timeout value, or check the connection validity before using it and create a new one if the connection has been closed.

Managing Disk Space for Impala Data

Although Impala typically works with many large files in an HDFS storage system with plenty of capacity, there are times when you might perform some file cleanup to reclaim space, or advise developers on techniques to minimize space consumption and file duplication.

- Use compact binary file formats where practical. Numeric and time-based data in particular can be stored in more compact form in binary data files. Depending on the file format, various compression and encoding features can reduce file size even further. You can specify the `STORED AS` clause as part of the `CREATE TABLE` statement, or `ALTER TABLE` with the `SET FILEFORMAT` clause for an existing table or partition within a partitioned table. See [How Impala Works with Hadoop File Formats](#) on page 575 for details about file formats, especially [Using the Parquet File Format with Impala Tables](#) on page 584. See [CREATE TABLE Statement](#) on page 254 and [ALTER TABLE Statement](#) on page 230 for syntax details.
- You manage underlying data files differently depending on whether the corresponding Impala table is defined as an [internal](#) or [external](#) table:
 - Use the `DESCRIBE FORMATTED` statement to check if a particular table is internal (managed by Impala) or external, and to see the physical location of the data files in HDFS. See [DESCRIBE Statement](#) on page 264 for details.
 - For Impala-managed (“internal”) tables, use `DROP TABLE` statements to remove data files. See [DROP TABLE Statement](#) on page 280 for details.
 - For tables not managed by Impala (“external” tables), use appropriate HDFS-related commands such as `hadoop fs`, `hdfs dfs`, or `distcp`, to create, move, copy, or delete files within HDFS directories that are accessible by the `impala` user. Issue a `REFRESH table_name` statement after adding or removing any files from the data directory of an external table. See [REFRESH Statement](#) on page 300 for details.
 - Use external tables to reference HDFS data files in their original location. With this technique, you avoid copying the files, and you can map more than one Impala table to the same set of data files. When you drop the Impala table, the data files are left undisturbed. See [External Tables](#) on page 223 for details.
 - Use the `LOAD DATA` statement to move HDFS files into the data directory for an Impala table from inside Impala, without the need to specify the HDFS path of the destination directory. This technique works for both internal and external tables. See [LOAD DATA Statement](#) on page 297 for details.
- Make sure that the HDFS trashcan is configured correctly. When you remove files from HDFS, the space might not be reclaimed for use by other files until sometime later, when the trashcan is emptied. See [DROP TABLE Statement](#) on page 280 and the FAQ entry [Why is space not freed up when I issue DROP TABLE?](#) on page 657 for details. See [User Account Requirements](#) on page 26 for permissions needed for the HDFS trashcan to operate correctly.
- Drop all tables in a database before dropping the database itself. See [DROP DATABASE Statement](#) on page 273 for details.

- Clean up temporary files after failed `INSERT` statements. If an `INSERT` statement encounters an error, and you see a directory named `.impala_insert_staging` or `_impala_insert_staging` left behind in the data directory for the table, it might contain temporary data files taking up space in HDFS. You might be able to salvage these data files, for example if they are complete but could not be moved into place due to a permission error. Or, you might delete those files through commands such as `hadoop fs` or `hdfs dfs`, to reclaim space before re-trying the `INSERT`. Issue `DESCRIBE FORMATTED table_name` to see the HDFS path where you can check for temporary files.
- By default, intermediate files used during large sort, join, aggregation, or analytic function operations are stored in the directory `/tmp/impala-scratch`. These files are removed when the operation finishes. (Multiple concurrent queries can perform operations that use the “spill to disk” technique, without any name conflicts for these temporary files.) You can specify a different location by starting the `impalad` daemon with the `--scratch_dirs="path_to_directory"` configuration option or the equivalent configuration option in the Cloudera Manager user interface. You can specify a single directory, or a comma-separated list of directories. The scratch directories must be on the local filesystem, not in HDFS. You might specify different directory paths for different hosts, depending on the capacity and speed of the available storage devices. In CDH 5.5 / Impala 2.3 or higher, Impala successfully starts (with a warning written to the log) if it cannot create or read and write files in one of the scratch directories. If there is less than 1 GB free on the filesystem where that directory resides, Impala still runs, but writes a warning message to its log. If Impala encounters an error reading or writing files in a scratch directory during a query, Impala logs the error and the query fails.
- If you use the Amazon Simple Storage Service (S3) as a place to offload data to reduce the volume of local storage, Impala 2.2.0 and higher can query the data directly from S3. See [Using Impala with the Amazon S3 Filesystem](#) on page 617 for details.

Impala Security

Impala includes a fine-grained authorization framework for Hadoop, based on the Sentry open source project. Sentry authorization was added in Impala 1.1.0. Together with the Kerberos authentication framework, Sentry takes Hadoop security to a new level needed for the requirements of highly regulated industries such as healthcare, financial services, and government. Impala also includes an auditing capability; Impala generates the audit data, the Cloudera Navigator product consolidates the audit data from all nodes in the cluster, and Cloudera Manager lets you filter, visualize, and produce reports. The auditing feature was added in Impala 1.1.1.

The Impala security features have several objectives. At the most basic level, security prevents accidents or mistakes that could disrupt application processing, delete or corrupt data, or reveal data to unauthorized users. More advanced security features and practices can harden the system against malicious users trying to gain unauthorized access or perform other disallowed operations. The auditing feature provides a way to confirm that no unauthorized access occurred, and detect whether any such attempts were made. This is a critical set of features for production deployments in large organizations that handle important or sensitive data. It sets the stage for multi-tenancy, where multiple applications run concurrently and are prevented from interfering with each other.

The material in this section presumes that you are already familiar with administering secure Linux systems. That is, you should know the general security practices for Linux and Hadoop, and their associated commands and configuration files. For example, you should know how to create Linux users and groups, manage Linux group membership, set Linux and HDFS file permissions and ownership, and designate the default permissions and ownership for new files. You should be familiar with the configuration of the nodes in your Hadoop cluster, and know how to apply configuration changes or run a set of commands across all the nodes.

The security features are divided into these broad categories:

authorization

Which users are allowed to access which resources, and what operations are they allowed to perform? Impala relies on the open source Sentry project for authorization. By default (when authorization is not enabled), Impala does all read and write operations with the privileges of the `impala` user, which is suitable for a development/test environment but not for a secure production environment. When authorization is enabled, Impala uses the OS user ID of the user who runs `impala-shell` or other client program, and associates various privileges with each user. See [Enabling Sentry Authorization for Impala](#) on page 105 for details about setting up and managing authorization.

authentication

How does Impala verify the identity of the user to confirm that they really are allowed to exercise the privileges assigned to that user? Impala relies on the Kerberos subsystem for authentication. See [Enabling Kerberos Authentication for Impala](#) on page 116 for details about setting up and managing authentication.

auditing

What operations were attempted, and did they succeed or not? This feature provides a way to look back and diagnose whether attempts were made to perform unauthorized operations. You use this information to track down suspicious activity, and to see where changes are needed in authorization policies. The audit data produced by this feature is collected by the Cloudera Manager product and then presented in a user-friendly form by the Cloudera Manager product. See [Auditing Impala Operations](#) on page 123 for details about setting up and managing auditing.

Security Guidelines for Impala

The following are the major steps to harden a cluster running Impala against accidents and mistakes, or malicious attackers trying to access sensitive data:

- Secure the `root` account. The `root` user can tamper with the `impalad` daemon, read and write the data files in HDFS, log into other user accounts, and access other system services that are beyond the control of Impala.

- Restrict membership in the `sudoers` list (in the `/etc/sudoers` file). The users who can run the `sudo` command can do many of the same things as the `root` user.
- Ensure the Hadoop ownership and permissions for Impala data files are restricted.
- Ensure the Hadoop ownership and permissions for Impala log files are restricted.
- Ensure that the Impala web UI (available by default on port 25000 on each Impala node) is password-protected. See [Impala Web User Interface for Debugging](#) on page 633 for details.
- Create a policy file that specifies which Impala privileges are available to users in particular Hadoop groups (which by default map to Linux OS groups). Create the associated Linux groups using the `groupadd` command if necessary.
- The Impala authorization feature makes use of the HDFS file ownership and permissions mechanism; for background information, see the [CDH HDFS Permissions Guide](#). Set up users and assign them to groups at the OS level, corresponding to the different categories of users with different access levels for various databases, tables, and HDFS locations (URIs). Create the associated Linux users using the `useradd` command if necessary, and add them to the appropriate groups with the `usermod` command.
- Design your databases, tables, and views with database and table structure to allow policy rules to specify simple, consistent rules. For example, if all tables related to an application are inside a single database, you can assign privileges for that database and use the `*` wildcard for the table name. If you are creating views with different privileges than the underlying base tables, you might put the views in a separate database so that you can use the `*` wildcard for the database containing the base tables, while specifying the precise names of the individual views. (For specifying table or database names, you either specify the exact name or `*` to mean all the databases on a server, or all the tables and views in a database.)
- Enable authorization by running the `impalad` daemons with the `-server_name` and `-authorization_policy_file` options on all nodes. (The authorization feature does not apply to the `statedored` daemon, which has no access to schema objects or data files.)
- Set up authentication using Kerberos, to make sure users really are who they say they are.

Securing Impala Data and Log Files

One aspect of security is to protect files from unauthorized access at the filesystem level. For example, if you store sensitive data in HDFS, you specify permissions on the associated files and directories in HDFS to restrict read and write permissions to the appropriate users and groups.

If you issue queries containing sensitive values in the `WHERE` clause, such as financial account numbers, those values are stored in Impala log files in the Linux filesystem and you must secure those files also. For the locations of Impala log files, see [Using Impala Logging](#) on page 627.

All Impala read and write operations are performed under the filesystem privileges of the `impala` user. The `impala` user must be able to read all directories and data files that you query, and write into all the directories and data files for `INSERT` and `LOAD DATA` statements. At a minimum, make sure the `impala` user is in the `hive` group so that it can access files and directories shared between Impala and Hive. See [User Account Requirements](#) on page 26 for more details.

Setting file permissions is necessary for Impala to function correctly, but is not an effective security practice by itself:

- The way to ensure that only authorized users can submit requests for databases and tables they are allowed to access is to set up Sentry authorization, as explained in [Enabling Sentry Authorization for Impala](#) on page 105. With authorization enabled, the checking of the user ID and group is done by Impala, and unauthorized access is blocked by Impala itself. The actual low-level read and write requests are still done by the `impala` user, so you must have appropriate file and directory permissions for that user ID.
- You must also set up Kerberos authentication, as described in [Enabling Kerberos Authentication for Impala](#) on page 116, so that users can only connect from trusted hosts. With Kerberos enabled, if someone connects a new

host to the network and creates user IDs that match your privileged IDs, they will be blocked from connecting to Impala at all from that host.

Installation Considerations for Impala Security

Impala 1.1 comes set up with all the software and settings needed to enable security when you run the `impalad` daemon with the new security-related options (`-server_name` and `-authorization_policy_file`). You do not need to change any environment variables or install any additional JAR files. In a cluster managed by Cloudera Manager, you do not need to change any settings in Cloudera Manager.

Securing the Hive Metastore Database

It is important to secure the Hive metastore, so that users cannot access the names or other information about databases and tables through the Hive client or by querying the metastore database. Do this by turning on Hive metastore security, using the instructions in the [CDH 5 Security Guide](#) for securing different Hive components:

- Secure the Hive Metastore.
- In addition, allow access to the metastore only from the HiveServer2 server, and then disable local access to the HiveServer2 server.

Securing the Impala Web User Interface

The instructions in this section presume you are familiar with the [.htpasswd mechanism](#) commonly used to password-protect pages on web servers.

Password-protect the Impala web UI that listens on port 25000 by default. Set up a `.htpasswd` file in the `$IMPALA_HOME` directory, or start both the `impalad` and `statedored` daemons with the `--webserver_password_file` option to specify a different location (including the filename).

This file should only be readable by the Impala process and machine administrators, because it contains (hashed) versions of passwords. The username / password pairs are not derived from Unix usernames, Kerberos users, or any other system. The `domain` field in the password file must match the domain supplied to Impala by the new command-line option `--webserver_authentication_domain`. The default is `mydomain.com`.

Impala also supports using HTTPS for secure web traffic. To do so, set `--webserver_certificate_file` to refer to a valid `.pem` TLS/SSL certificate file. Impala will automatically start using HTTPS once the TLS/SSL certificate has been read and validated. A `.pem` file is basically a private key, followed by a signed TLS/SSL certificate; make sure to concatenate both parts when constructing the `.pem` file.

If Impala cannot find or parse the `.pem` file, it prints an error message and quits.



Note:

If the private key is encrypted using a passphrase, Impala will ask for that passphrase on startup, which is not useful for a large cluster. In that case, remove the passphrase and make the `.pem` file readable only by Impala and administrators.

When you turn on TLS/SSL for the Impala web UI, the associated URLs change from `http://` prefixes to `https://`. Adjust any bookmarks or application code that refers to those URLs.

Configuring Secure Access for Impala Web Servers

Cloudera Manager supports two methods of authentication for secure access to the Impala Catalog Server, Daemon, and StateStoreweb servers: password-based authentication and TLS/SSL certificate authentication.

Authentication for the three types of daemons can be configured independently.

Configuring Password Authentication

1. Navigate to **Clusters > Impala Service > Configuration**.
2. Search for "password" using the Search box in the **Configuration** tab. This should display the password-related properties (Username and Password properties) for the Impala Daemon, StateStore, and Catalog Server. If there are multiple role groups configured for Impala Daemon instances, the search should display all of them.
3. Enter a username and password into these fields.
4. Click **Save Changes**, and restart the Impala service.

Now when you access the Web UI for the Impala Daemon, StateStore, or Catalog Server, you are asked to log in before access is granted.

Configuring TLS/SSL Certificate Authentication

1. Create or obtain an TLS/SSL certificate.
2. Place the certificate, in `.pem` format, on the hosts where the Impala Catalog Server and StateStore are running, and on each host where an Impala Daemon is running. It can be placed in any location (path) you choose. If all the Impala Daemons are members of the same role group, then the `.pem` file must have the same path on every host.
3. Navigate to **Clusters > Impala Service > Configuration**.
4. Search for "certificate" using the Search box in the **Configuration** tab. This should display the certificate file location properties for the Impala Catalog Server, Impala Daemon, and StateStore. If there are multiple role groups configured for Impala Daemon instances, the search should display all of them.
5. In the property fields, enter the full path name to the certificate file.
6. Click **Save Changes**, and restart the Impala service.



Important: If Cloudera Manager cannot find the `.pem` file on the host for a specific role instance, that role will fail to start.

When you access the Web UI for the Impala Catalog Server, Impala Daemon, and StateStore, `https` will be used.

Configuring TLS/SSL for Impala

Impala supports TLS/SSL network encryption, between Impala and client programs, and between the Impala-related daemons running on different nodes in the cluster. This feature is important when you also use other features such as Kerberos authentication or Sentry authorization, where credentials are being transmitted back and forth.



Important:

- You can use either Cloudera Manager or the following command-line instructions to complete this configuration.
- This information applies specifically to CDH 5.9.x. If you use an earlier version of CDH, see the documentation for that version located at [Cloudera Documentation](#).

Using Cloudera Manager

To configure Impala to listen for Beeswax and HiveServer2 requests on TLS/SSL-secured ports:

1. Open the Cloudera Manager Admin Console and go to the **Impala** service.
2. Click the **Configuration** tab.
3. Select **Scope > Impala (Service-Wide)**.
4. Select **Category > Security**.
5. Edit the following properties:

Table 1: Impala SSL Properties

Property	Description
Enable TLS/SSL for Impala Client Services	Encrypt communication between clients (like ODBC, JDBC, and the Impala shell) and the Impala daemon using Transport Layer Security (TLS) (formerly known as Secure Socket Layer (SSL)).
SSL/TLS Certificate for Clients	Local path to the X509 certificate that identifies the Impala daemon to clients during TLS/SSL connections. This file must be in PEM format.
SSL/TLS Private Key for Clients	Local path to the private key that matches the certificate specified in the Certificate for Clients. This file must be in PEM format.
SSL/TLS Private Key Password for Clients	A shell command for Impala to run on startup to retrieve the password for a password-protected private key file. The output of the command is truncated to a maximum of 1024 bytes, and any trailing whitespace (such as spaces or newline characters) is trimmed. If the command exits with an error, Impala does not start. If the password is incorrect, clients cannot connect to the server regardless of whether the public key is correct.
SSL/TLS CA Certificate	Must be specified for TLS/SSL encryption to be enabled for communication between internal Impala components.
SSL/TLS Certificate for Impala component Webserver	There are three of these configuration settings, one each for “Impala Daemon”, “Catalog Server”, and “Statestore”. Each of these Impala components has its own internal web server that powers the associated web UI with diagnostic information. The configuration setting represents the local path to the X509 certificate that identifies the web server to clients during TLS/SSL connections. This file must be in PEM format.

6. Click **Save Changes** to commit the changes.
7. Restart the Impala service.

For information on configuring TLS/SSL communication with the `impala-shell` interpreter, see [Configuring TLS/SSL Communication for the Impala Shell](#) on page 105.

Using the Command Line

To enable SSL for when client applications connect to Impala, add both of the following flags to the `impalad` startup options:

- `--ssl_server_certificate`: the full path to the server certificate, on the local filesystem.
- `--ssl_private_key`: the full path to the server private key, on the local filesystem.

In CDH 5.5 / Impala 2.3 and higher, Impala can also use SSL for its own internal communication between the `impalad`, `statestored`, and `catalogd` daemons. To enable this additional SSL encryption, set the `--ssl_server_certificate` and `--ssl_private_key` flags in the startup options for `impalad`, `catalogd`, and `statestored`, and also add the `--ssl_client_ca_certificate` flag for all three of those daemons.



Warning: Prior to CDH 5.5.2 / Impala 2.3.2, you could enable Kerberos authentication between Impala internal components, or SSL encryption between Impala internal components, but not both at the same time. This restriction has now been lifted. See [IMPALA-2598](#) to see the maintenance releases for different levels of CDH where the fix has been published.

If either of these flags are set, both must be set. In that case, Impala starts listening for Beeswax and HiveServer2 requests on SSL-secured ports only. (The port numbers stay the same; see [Ports Used by Impala](#) on page 639 for details.)

Since Impala uses passphrase-less certificates in PEM format, you can reuse a host's existing Java keystore by converting it to the PEM format. For instructions, see http://www.cloudera.com/documentation/enterprise/latest/topics/cm_sg_openssl_jks.html.

Configuring TLS/SSL Communication for the Impala Shell

Typically, a client program has corresponding configuration properties in Cloudera Manager to verify that it is connecting to the right server. For example, with SSL enabled for Impala, you use the following options when starting the `impala-shell` interpreter:

- `--ssl`: enables TLS/SSL for `impala-shell`.
- `--ca_cert`: the local pathname pointing to the third-party CA certificate, or to a copy of the server certificate for self-signed server certificates.

If `--ca_cert` is not set, `impala-shell` enables TLS/SSL, but does not validate the server certificate. This is useful for connecting to a known-good Impala that is only running over TLS/SSL, when a copy of the certificate is not available (such as when debugging customer installations).

For `impala-shell` to successfully connect to an Impala cluster that has the minimum allowed TLS/SSL version set to 1.2 (`--ssl_minimum_version=tlsv1.2`), the Python version on the cluster that `impala-shell` runs on must be 2.7.9 or higher (or a vendor-provided Python version with the required support. Some vendors patched Python 2.7.5 versions on Red Hat Enterprise Linux 7 and derivatives).

Using TLS/SSL with Business Intelligence Tools

You can use Kerberos authentication, TLS/SSL encryption, or both to secure connections from JDBC and ODBC applications to Impala. See [Configuring Impala to Work with JDBC](#) on page 36 and [Configuring Impala to Work with ODBC](#) on page 33 for details.

Prior to CDH 5.7 / Impala 2.5, the Hive JDBC driver did not support connections that use both Kerberos authentication and SSL encryption. If your cluster is running an older release that has this restriction, to use both of these security features with Impala through a JDBC application, use the [Cloudera JDBC Connector](#) as the JDBC driver.

Enabling Sentry Authorization for Impala

Authorization determines which users are allowed to access which resources, and what operations they are allowed to perform. In Impala 1.1 and higher, you use the Sentry open source project for authorization. Sentry adds a fine-grained authorization framework for Hadoop. By default (when authorization is not enabled), Impala does all read and write operations with the privileges of the `impala` user, which is suitable for a development/test environment but not for a secure production environment. When authorization is enabled, Impala uses the OS user ID of the user who runs `impala-shell` or other client program, and associates various privileges with each user.



Note: Sentry is typically used in conjunction with Kerberos authentication, which defines which hosts are allowed to connect to each server. Using the combination of Sentry and Kerberos prevents malicious users from being able to connect by creating a named account on an untrusted machine. See [Enabling Kerberos Authentication for Impala](#) on page 116 for details about Kerberos authentication.

The Sentry Privilege Model

Privileges can be granted on different objects in the schema. Any privilege that can be granted is associated with a level in the object hierarchy. If a privilege is granted on a container object in the hierarchy, the child object automatically inherits it. This is the same privilege model as Hive and other database systems such as MySQL.

The object hierarchy for Impala covers Server, URI, Database, Table, and Column. (The Table privileges apply to views as well; anywhere you specify a table name, you can specify a view name instead.) Column-level authorization is available in CDH 5.5 / Impala 2.3 and higher, as described in https://www.cloudera.com/documentation/enterprise/latest/topics/sg_hive_sql.html. Previously, you constructed views to query specific columns and assigned privileges based on the views rather than the base tables.

A restricted set of privileges determines what you can do with each object:

SELECT privilege

Lets you read data from a table or view, for example with the `SELECT` statement, the `INSERT . . . SELECT` syntax, or `CREATE TABLE . . . LIKE`. Also required to issue the `DESCRIBE` statement or the `EXPLAIN` statement for a query against a particular table. Only objects for which a user has this privilege are shown in the output for `SHOW DATABASES` and `SHOW TABLES` statements. The `REFRESH` statement and `INVALIDATE METADATA` statements only access metadata for tables for which the user has this privilege.

INSERT privilege

Lets you write data to a table. Applies to the `INSERT` and `LOAD DATA` statements.

ALL privilege

Lets you create or modify the object. Required to run DDL statements such as `CREATE TABLE`, `ALTER TABLE`, or `DROP TABLE` for a table, `CREATE DATABASE` or `DROP DATABASE` for a database, or `CREATE VIEW`, `ALTER VIEW`, or `DROP VIEW` for a view. Also required for the URI of the “location” parameter for the `CREATE EXTERNAL TABLE` and `LOAD DATA` statements.

Privileges can be specified for a table or view before that object actually exists. If you do not have sufficient privilege to perform an operation, the error message does not disclose if the object exists or not.

Originally, privileges were encoded in a policy file, stored in HDFS. This mode of operation is still an option, but the emphasis of privilege management is moving towards being SQL-based. Although currently Impala does not have `GRANT` or `REVOKE` statements, Impala can make use of privileges assigned through `GRANT` and `REVOKE` statements done through Hive. The mode of operation with `GRANT` and `REVOKE` statements instead of the policy file requires that a special Sentry service be enabled; this service stores, retrieves, and manipulates privilege information stored inside the metastore database.

Starting the `impalad` Daemon with Sentry Authorization Enabled

To run the `impalad` daemon with authorization enabled, you add one or more options to the `IMPALA_SERVER_ARGS` declaration in the `/etc/default/impala` configuration file:

- The `-server_name` option turns on Sentry authorization for Impala. The authorization rules refer to a symbolic server name, and you specify the name to use as the argument to the `-server_name` option.
- If you specify just `-server_name`, Impala uses the Sentry service for authorization, relying on the results of `GRANT` and `REVOKE` statements issued through Hive. (This mode of operation is available in Impala 1.4.0 and higher.) Prior to Impala 1.4.0, or if you want to continue storing privilege rules in the policy file, also specify the `-authorization_policy_file` option as in the following item.
- Specifying the `-authorization_policy_file` option in addition to `-server_name` makes Impala read privilege information from a policy file, rather than from the metastore database. The argument to the `-authorization_policy_file` option specifies the HDFS path to the policy file that defines the privileges on different schema objects.

For example, you might adapt your `/etc/default/impala` configuration to contain lines like the following. To use the Sentry service rather than the policy file:

```
IMPALA_SERVER_ARGS=" \
-server_name=server1 \
...
```

Or to use the policy file, as in releases prior to Impala 1.4:

```
IMPALA_SERVER_ARGS=" \
-authorization_policy_file=/user/hive/warehouse/auth-policy.ini \
-server_name=server1 \
...
```

The preceding examples set up a symbolic name of `server1` to refer to the current instance of Impala. This symbolic name is used in the following ways:

- In an environment managed by Cloudera Manager, the server name is specified through **Impala (Service-Wide) > Category > Advanced > Sentry Service** and **Hive > Service-Wide > Advanced > Sentry Service**. The values must be the same for both, so that Impala and Hive can share the privilege rules. Restart the Impala and Hive services after setting or changing this value.
- In an environment not managed by Cloudera Manager, you specify this value for the `sentry.hive.server` property in the `sentry-site.xml` configuration file for Hive, as well as in the `-server_name` option for `impalad`.
If the `impalad` daemon is not already running, start it as described in [Starting Impala](#) on page 44. If it is already running, restart it with the command `sudo /etc/init.d/impala-server restart`. Run the appropriate commands on all the nodes where `impalad` normally runs.
- If you use the mode of operation using the policy file, the rules in the `[roles]` section of the policy file refer to this same `server1` name. For example, the following rule sets up a role `report_generator` that lets users with that role query any table in a database named `reporting_db` on a node where the `impalad` daemon was started up with the `-server_name=server1` option:

```
[roles]
report_generator = server=server1->db=reporting_db->table=*->action=SELECT
```

When `impalad` is started with one or both of the `-server_name=server1` and `-authorization_policy_file` options, Impala authorization is enabled. If Impala detects any errors or inconsistencies in the authorization settings or the policy file, the daemon refuses to start.

Using Impala with the Sentry Service (CDH 5.1 or higher only)

When you use the Sentry service rather than the policy file, you set up privileges through `GRANT` and `REVOKE` statement in either Impala or Hive, then both components use those same privileges automatically. (Impala added the `GRANT` and `REVOKE` statements in Impala 2.0.0 / CDH 5.2.0.)

Hive already had `GRANT` and `REVOKE` statements prior to CDH 5.1, but those statements were not production-ready. CDH 5.1 is the first release where those statements use the Sentry framework and are considered GA level. If you used the Hive `GRANT` and `REVOKE` statements prior to CDH 5.1, you must set up these privileges with the CDH 5.1 versions of `GRANT` and `REVOKE` to take advantage of Sentry authorization.

For information about using the updated Hive `GRANT` and `REVOKE` statements, see [Sentry service](#) topic in the *CDH 5 Security Guide*.

Using Impala with the Sentry Policy File

The policy file is a file that you put in a designated location in HDFS, and is read during the startup of the `impalad` daemon when you specify both the `-server_name` and `-authorization_policy_file` startup options. It controls which objects (databases, tables, and HDFS directory paths) can be accessed by the user who connects to `impalad`, and what operations that user can perform on the objects.



Note:

In CDH 5 and higher, Cloudera recommends managing privileges through SQL statements, as described in [Using Impala with the Sentry Service \(CDH 5.1 or higher only\)](#) on page 107. If you are still using policy files, plan to migrate to the new approach some time in the future.

The location of the policy file is listed in the `auth-site.xml` configuration file. To minimize overhead, the security information from this file is cached by each `impalad` daemon and refreshed automatically, with a default interval of 5 minutes. After making a substantial change to security policies, restart all Impala daemons to pick up the changes immediately.

Policy File Location and Format

The policy file uses the familiar `.ini` format, divided into the major sections `[groups]` and `[roles]`. There is also an optional `[databases]` section, which allows you to specify a specific policy file for a particular database, as explained in [Using Multiple Policy Files for Different Databases](#) on page 111. Another optional section, `[users]`, allows you to override the OS-level mapping of users to groups; that is an advanced technique primarily for testing and debugging, and is beyond the scope of this document.

In the `[groups]` section, you define various categories of users and select which roles are associated with each category. The group and usernames correspond to Linux groups and users on the server where the `impalad` daemon runs.

The group and usernames in the `[groups]` section correspond to Linux groups and users on the server where the `impalad` daemon runs. When you access Impala through the `impalad` interpreter, for purposes of authorization, the user is the logged-in Linux user and the groups are the Linux groups that user is a member of. When you access Impala through the ODBC or JDBC interfaces, the user and password specified through the connection string are used as login credentials for the Linux server, and authorization is based on that username and the associated Linux group membership.

In the `[roles]` section, you a set of roles. For each role, you specify precisely the set of privileges is available. That is, which objects users with that role can access, and what operations they can perform on those objects. This is the lowest-level category of security information; the other sections in the policy file map the privileges to higher-level divisions of groups and users. In the `[groups]` section, you specify which roles are associated with which groups. The group and usernames correspond to Linux groups and users on the server where the `impalad` daemon runs. The privileges are specified using patterns like:

```
server=server_name->db=database_name->table=table_name->action=SELECT
server=server_name->db=database_name->table=table_name->action=CREATE
server=server_name->db=database_name->table=table_name->action=ALL
```

For the `server_name` value, substitute the same symbolic name you specify with the `impalad -server_name` option. You can use `*` wildcard characters at each level of the privilege specification to allow access to all such objects. For example:

```
server=impala-host.example.com->db=default->table=t1->action=SELECT
server=impala-host.example.com->db=*->table=*->action=CREATE
server=impala-host.example.com->db=*->table=audit_log->action=SELECT
server=impala-host.example.com->db=default->table=t1->action=*
```

When authorization is enabled, Impala uses the policy file as a *whitelist*, representing every privilege available to any user on any object. That is, only operations specified for the appropriate combination of object, role, group, and user are allowed; all other operations are not allowed. If a group or role is defined multiple times in the policy file, the last definition takes precedence.

To understand the notion of whitelisting, set up a minimal policy file that does not provide any privileges for any object. When you connect to an Impala node where this policy file is in effect, you get no results for `SHOW DATABASES`, and an error when you issue any `SHOW TABLES`, `USE database_name`, `DESCRIBE table_name`, `SELECT`, and or other statements that expect to access databases or tables, even if the corresponding databases and tables exist.

The contents of the policy file are cached, to avoid a performance penalty for each query. The policy file is re-checked by each `impalad` node every 5 minutes. When you make a non-time-sensitive change such as adding new privileges or new users, you can let the change take effect automatically a few minutes later. If you remove or reduce privileges, and want the change to take effect immediately, restart the `impalad` daemon on all nodes, again specifying the `-server_name` and `-authorization_policy_file` options so that the rules from the updated policy file are applied.

Examples of Policy File Rules for Security Scenarios

The following examples show rules that might go in the policy file to deal with various authorization-related scenarios. For illustration purposes, this section shows several very small policy files with only a few rules each. In your environment, typically you would define many roles to cover all the scenarios involving your own databases, tables, and applications, and a smaller number of groups, whose members are given the privileges from one or more roles.

A User with No Privileges

If a user has no privileges at all, that user cannot access any schema objects in the system. The error messages do not disclose the names or existence of objects that the user is not authorized to read.

This is the experience you want a user to have if they somehow log into a system where they are not an authorized Impala user. In a real deployment with a filled-in policy file, a user might have no privileges because they are not a member of any of the relevant groups mentioned in the policy file.

Examples of Privileges for Administrative Users

When an administrative user has broad access to tables or databases, the associated rules in the `[roles]` section typically use wildcards and/or inheritance. For example, in the following sample policy file, `db=*` refers to all databases and `db=*->table=*` refers to all tables in all databases.

Omitting the rightmost portion of a rule means that the privileges apply to all the objects that could be specified there. For example, in the following sample policy file, the `all_databases` role has all privileges for all tables in all databases, while the `one_database` role has all privileges for all tables in one specific database. The `all_databases` role does not grant privileges on URIs, so a group with that role could not issue a `CREATE TABLE` statement with a `LOCATION` clause. The `entire_server` role has all privileges on both databases and URIs within the server.

```
[groups]
supergroup = all_databases

[roles]
read_all_tables = server=server1->db=*->table=*->action=SELECT
all_tables = server=server1->db=*->table=*
all_databases = server=server1->db=*
one_database = server=server1->db=test_db
entire_server = server=server1
```

A User with Privileges for Specific Databases and Tables

If a user has privileges for specific tables in specific databases, the user can access those things but nothing else. They can see the tables and their parent databases in the output of `SHOW TABLES` and `SHOW DATABASES`, use the appropriate databases, and perform the relevant actions (`SELECT` and/or `INSERT`) based on the table privileges. To actually create a table requires the `ALL` privilege at the database level, so you might define separate roles for the user that sets up a schema and other users or applications that perform day-to-day operations on the tables.

The following sample policy file shows some of the syntax that is appropriate as the policy file grows, such as the `#` comment syntax, `\` continuation syntax, and comma separation for roles assigned to groups or privileges assigned to roles.

```
[groups]
cloudera = training_sysadmin, instructor
visitor = student

[roles]
training_sysadmin = server=server1->db=training, \
server=server1->db=instructor_private, \
server=server1->db=lesson_development
instructor = server=server1->db=training->table=*->action=*, \
server=server1->db=instructor_private->table=*->action=*, \
server=server1->db=lesson_development->table=lesson*
# This particular course is all about queries, so the students can SELECT but not INSERT
or CREATE/DROP.
student = server=server1->db=training->table=lesson_*->action=SELECT
```

Privileges for Working with External Data Files

When data is being inserted through the `LOAD DATA` statement, or is referenced from an HDFS location outside the normal Impala database directories, the user also needs appropriate permissions on the URIs corresponding to those HDFS locations.

In this sample policy file:

- The `external_table` role lets us insert into and query the Impala table, `external_table.sample`.
- The `staging_dir` role lets us specify the HDFS path `/user/cloudera/external_data` with the `LOAD DATA` statement. Remember, when Impala queries or loads data files, it operates on all the files in that directory, not just a single file, so any Impala `LOCATION` parameters refer to a directory rather than an individual file.
- We included the IP address and port of the Hadoop name node in the HDFS URI of the `staging_dir` rule. We found those details in `/etc/hadoop/conf/core-site.xml`, under the `fs.default.name` element. That is what we use in any roles that specify URIs (that is, the locations of directories in HDFS).
- We start this example after the table `external_table.sample` is already created. In the policy file for the example, we have already taken away the `external_table_admin` role from the `cloudera` group, and replaced it with the lesser-privileged `external_table` role.
- We assign privileges to a subdirectory underneath `/user/cloudera` in HDFS, because such privileges also apply to any subdirectories underneath. If we had assigned privileges to the parent directory `/user/cloudera`, it would be too likely to mess up other files by specifying a wrong location by mistake.
- The `cloudera` under the `[groups]` section refers to the `cloudera` group. (In the demo VM used for this example, there is a `cloudera` user that is a member of a `cloudera` group.)

Policy file:

```
[groups]
cloudera = external_table, staging_dir

[roles]
external_table_admin = server=server1->db=external_table
external_table = server=server1->db=external_table->table=sample->action=*
staging_dir =
server=server1->uri=hdfs://127.0.0.1:8020/user/cloudera/external_data->action=*
```

impala-shell session:

```
[localhost:21000] > use external_table;
Query: use external_table
[localhost:21000] > show tables;
Query: show tables
Query finished, fetching results ...
+-----+
| name   |
+-----+
| sample |
+-----+
Returned 1 row(s) in 0.02s

[localhost:21000] > select * from sample;
Query: select * from sample
Query finished, fetching results ...
+-----+
| x      |
+-----+
| 1      |
| 5      |
| 150    |
+-----+
Returned 3 row(s) in 1.04s

[localhost:21000] > load data inpath '/user/cloudera/external_data' into table sample;
Query: load data inpath '/user/cloudera/external_data' into table sample
Query finished, fetching results ...
+-----+
| summary                                     |
+-----+
| Loaded 1 file(s). Total files in destination location: 2 |
+-----+
Returned 1 row(s) in 0.26s
[localhost:21000] > select * from sample;
Query: select * from sample
Query finished, fetching results ...
+-----+
```

```

+----+
| x   |
+----+
| 2   |
| 4   |
| 6   |
| 8   |
| 64738 |
| 49152 |
| 1   |
| 5   |
| 150 |
+----+

```

Returned 9 row(s) in 0.22s

```

[localhost:21000] > load data inpath '/user/cloudera/unauthorized_data' into table
sample;
Query: load data inpath '/user/cloudera/unauthorized_data' into table sample
ERROR: AuthorizationException: User 'cloudera' does not have privileges to access:
hdfs://127.0.0.1:8020/user/cloudera/unauthorized_data

```

Separating Administrator Responsibility from Read and Write Privileges

Remember that to create a database requires full privilege on that database, while day-to-day operations on tables within that database can be performed with lower levels of privilege on specific table. Thus, you might set up separate roles for each database or application: an administrative one that could create or drop the database, and a user-level one that can access only the relevant tables.

For example, this policy file divides responsibilities between users in 3 different groups:

- Members of the `supergroup` group have the `training_sysadmin` role and so can set up a database named `training`.
- Members of the `cloudera` group have the `instructor` role and so can create, insert into, and query any tables in the `training` database, but cannot create or drop the database itself.
- Members of the `visitor` group have the `student` role and so can query those tables in the `training` database.

```

[groups]
supergroup = training_sysadmin
cloudera = instructor
visitor = student

[roles]
training_sysadmin = server=server1->db=training
instructor = server=server1->db=training->table=*->action=*
student = server=server1->db=training->table=*->action=SELECT

```

Using Multiple Policy Files for Different Databases

For an Impala cluster with many databases being accessed by many users and applications, it might be cumbersome to update the security policy file for each privilege change or each new database, table, or view. You can allow security to be managed separately for individual databases, by setting up a separate policy file for each database:

- Add the optional `[databases]` section to the main policy file.
- Add entries in the `[databases]` section for each database that has its own policy file.
- For each listed database, specify the HDFS path of the appropriate policy file.

For example:

```

[databases]
# Defines the location of the per-DB policy files for the 'customers' and 'sales'
databases.
customers = hdfs://ha-nn-uri/etc/access/customers.ini
sales = hdfs://ha-nn-uri/etc/access/sales.ini

```

To enable URIs in per-DB policy files, add the following string in the Cloudera Manager field **Impala Service Environment Advanced Configuration Snippet (Safety Valve)**:

```
JAVA_TOOL_OPTIONS="-Dsentry.allow.uri.db.policyfile=true"
```



Important: Enabling URIs in per-DB policy files introduces a security risk by allowing the owner of the db-level policy file to grant himself/herself load privileges to anything the `impala` user has read permissions for in HDFS (including data in other databases controlled by different db-level policy files).

Setting Up Schema Objects for a Secure Impala Deployment

Remember that in your role definitions, you specify privileges at the level of individual databases and tables, or all databases or all tables within a database. To simplify the structure of these rules, plan ahead of time how to name your schema objects so that data with different authorization requirements is divided into separate databases.

If you are adding security on top of an existing Impala deployment, remember that you can rename tables or even move them between databases using the `ALTER TABLE` statement. In Impala, creating new databases is a relatively inexpensive operation, basically just creating a new directory in HDFS.

You can also plan the security scheme and set up the policy file before the actual schema objects named in the policy file exist. Because the authorization capability is based on whitelisting, a user can only create a new database or table if the required privilege is already in the policy file: either by listing the exact name of the object being created, or a * wildcard to match all the applicable objects within the appropriate container.

Privilege Model and Object Hierarchy

Privileges can be granted on different objects in the schema. Any privilege that can be granted is associated with a level in the object hierarchy. If a privilege is granted on a container object in the hierarchy, the child object automatically inherits it. This is the same privilege model as Hive and other database systems such as MySQL.

The kinds of objects in the schema hierarchy are:

```
Server
URI
Database
  Table
```

The server name is specified by the `-server_name` option when `impalad` starts. Specify the same name for all `impalad` nodes in the cluster.

URIs represent the HDFS paths you specify as part of statements such as `CREATE EXTERNAL TABLE` and `LOAD DATA`. Typically, you specify what look like UNIX paths, but these locations can also be prefixed with `hdfs://` to make clear that they are really URIs. To set privileges for a URI, specify the name of a directory, and the privilege applies to all the files in that directory and any directories underneath it.

In CDH 5.5 / Impala 2.3 and higher, you can specify privileges for individual columns, as described in https://www.cloudera.com/documentation/enterprise/latest/topics/sg_hive_sql.html. Formerly, to specify read privileges at this level, you created a view that queried specific columns and/or partitions from a base table, and gave `SELECT` privilege on the view but not the underlying table.

URIs must start with either `hdfs://` or `file://`. If a URI starts with anything else, it will cause an exception and the policy file will be invalid. When defining URIs for HDFS, you must also specify the NameNode. For example:

```
data_read = server=server1->uri=file:///path/to/dir, \
server=server1->uri=hdfs://namenode:port/path/to/dir
```


**Warning:**

Because the NameNode host and port must be specified, Cloudera strongly recommends you use High Availability (HA). This ensures that the URI will remain constant even if the NameNode changes.

```
data_read = server=server1->uri=file:///path/to/dir,\
server=server1->uri=hdfs://ha-nn-uri/path/to/dir
```

Table 2: Valid privilege types and objects they apply to

Privilege	Object
INSERT	DB, TABLE
SELECT	DB, TABLE, VIEW, COLUMN
ALL	SERVER, TABLE, DB, URI

**Note:**

Although this document refers to the ALL privilege, currently if you use the policy file mode, you do not use the actual keyword ALL in the policy file. When you code role entries in the policy file:

- To specify the ALL privilege for a server, use a role like `server=server_name`.
- To specify the ALL privilege for a database, use a role like `server=server_name->db=database_name`.
- To specify the ALL privilege for a table, use a role like `server=server_name->db=database_name->table=table_name->action=*`.

Operation	Scope	Privileges Required	URI
CREATE DATABASE	SERVER	ALL	
DROP DATABASE	DATABASE	ALL	
CREATE TABLE	DATABASE	ALL	
DROP TABLE	TABLE	ALL	
CREATE VIEW -This operation is allowed if you have column-level SELECT access to the columns being used.	DATABASE; SELECT on TABLE;	ALL	
ALTER VIEW -This operation is allowed if you have column-level SELECT access to the columns being used.	VIEW/TABLE	ALL	
DROP VIEW	VIEW/TABLE	ALL	
ALTER TABLE .. ADD COLUMNS	TABLE	ALL	
ALTER TABLE .. REPLACE COLUMNS	TABLE	ALL	
ALTER TABLE .. CHANGE column	TABLE	ALL	
ALTER TABLE .. RENAME	TABLE	ALL	

Operation	Scope	Privileges Required	URI
ALTER TABLE .. SET TBLPROPERTIES	TABLE	ALL	
ALTER TABLE .. SET FILEFORMAT	TABLE	ALL	
ALTER TABLE .. SET LOCATION	TABLE	ALL	URI
ALTER TABLE .. ADD PARTITION	TABLE	ALL	
ALTER TABLE .. ADD PARTITION location	TABLE	ALL	URI
ALTER TABLE .. DROP PARTITION	TABLE	ALL	
ALTER TABLE .. PARTITION SET FILEFORMAT	TABLE	ALL	
SHOW CREATE TABLE	TABLE	SELECT/INSERT	
SHOW PARTITIONS	TABLE	SELECT/INSERT	
SHOW TABLES -Output includes all the tables for which the user has table-level privileges and all the tables for which the user has some column-level privileges.	TABLE	SELECT/INSERT	
SHOW GRANT ROLE -Output includes an additional field for any column-level privileges.	TABLE	SELECT/INSERT	
DESCRIBE TABLE -Output shows <i>all</i> columns if the user has table level-privileges or <code>SELECT</code> privilege on at least one table column	TABLE	SELECT/INSERT	
LOAD DATA	TABLE	INSERT	URI
SELECT -You can grant the <code>SELECT</code> privilege on a view to give users access to specific columns of a table they do not otherwise have access to. -See Column-level Authorization for details on allowed column-level operations.	VIEW/TABLE; COLUMN	SELECT	
INSERT OVERWRITE TABLE	TABLE	INSERT	
CREATE TABLE .. AS SELECT -This operation is allowed if you have column-level <code>SELECT</code> access to the columns being used.	DATABASE; SELECT on TABLE	ALL	

Operation	Scope	Privileges Required	URI
USE <dbName>	Any		
CREATE FUNCTION	SERVER	ALL	
ALTER TABLE .. SET SERDEPROPERTIES	TABLE	ALL	
ALTER TABLE .. PARTITION SET SERDEPROPERTIES	TABLE	ALL	
EXPLAIN SELECT	TABLE; COLUMN	SELECT	
EXPLAIN INSERT	TABLE; COLUMN	INSERT	
INVALIDATE METADATA	SERVER	ALL	
INVALIDATE METADATA <table name>	TABLE	SELECT/INSERT	
REFRESH <table name> or REFRESH <table name> PARTITION (<partition_spec>)	TABLE	SELECT/INSERT	
DROP FUNCTION	SERVER	ALL	
COMPUTE STATS	TABLE	ALL	

Debugging Failed Sentry Authorization Requests

Sentry logs all facts that lead up to authorization decisions at the debug level. If you do not understand why Sentry is denying access, the best way to debug is to temporarily turn on debug logging:

- In Cloudera Manager, add `log4j.logger.org.apache.sentry=DEBUG` to the logging settings for your service through the corresponding **Logging Safety Valve** field for the Impala, Hive Server 2, or Solr Server services.
- On systems not managed by Cloudera Manager, add `log4j.logger.org.apache.sentry=DEBUG` to the `log4j.properties` file on each host in the cluster, in the appropriate configuration directory for each service.

Specifically, look for exceptions and messages such as:

```
FilePermission server..., RequestPermission server..., result [true|false]
```

which indicate each evaluation Sentry makes. The `FilePermission` is from the policy file, while `RequestPermission` is the privilege required for the query. A `RequestPermission` will iterate over all appropriate `FilePermission` settings until a match is found. If no matching privilege is found, Sentry returns `false` indicating "Access Denied".

Managing Sentry for Impala through Cloudera Manager

To enable the Sentry service for Impala and Hive, set **Hive/Impala > Service-Wide > Sentry Service** parameter to the Sentry service. Then restart Impala and Hive. Simply adding Sentry service as a dependency and restarting enables Impala and Hive to use the Sentry service.

To set the server name to use when granting server level privileges, set the **Hive > Service-Wide > Advanced > Server Name for Sentry Authorization** parameter. When using Sentry with the Hive Metastore, you can specify the list of users that are allowed to bypass Sentry Authorization in Hive Metastore using **Hive > Service-Wide > Security > Bypass Sentry Authorization Users**. These are usually service users that already ensure all activity has been authorized.



Note: The **Hive/Impala > Service-Wide > Policy File Based Sentry** tab contains parameters only relevant to configuring Sentry using policy files. In particular, make sure that **Enable Sentry Authorization using Policy Files** parameter is unchecked when using the Sentry service. Cloudera Manager throws a validation error if you attempt to configure the Sentry service and policy file at the same time.

The DEFAULT Database in a Secure Deployment

Because of the extra emphasis on granular access controls in a secure deployment, you should move any important or sensitive information out of the `DEFAULT` database into a named database whose privileges are specified in the policy file. Sometimes you might need to give privileges on the `DEFAULT` database for administrative reasons; for example, as a place you can reliably specify with a `USE` statement when preparing to drop a database.

Impala Authentication

Authentication is the mechanism to ensure that only specified hosts and users can connect to Impala. It also verifies that when clients connect to Impala, they are connected to a legitimate server. This feature prevents spoofing such as **impersonation** (setting up a phony client system with the same account and group names as a legitimate user) and **man-in-the-middle attacks** (intercepting application requests before they reach Impala and eavesdropping on sensitive information in the requests or the results).

Impala supports authentication using either Kerberos or LDAP.



Note: Regardless of the authentication mechanism used, Impala always creates HDFS directories and data files owned by the same user (typically `impala`). To implement user-level access to different databases, tables, columns, partitions, and so on, use the Sentry authorization feature, as explained in [Enabling Sentry Authorization for Impala](#) on page 105.

Once you are finished setting up authentication, move on to authorization, which involves specifying what databases, tables, HDFS directories, and so on can be accessed by particular users when they connect through Impala. See [Enabling Sentry Authorization for Impala](#) on page 105 for details.

Enabling Kerberos Authentication for Impala

Impala supports Kerberos authentication. For more information on enabling Kerberos authentication, see the topic on Configuring Hadoop Security in the [CDH 5 Security Guide](#).

When using Impala in a managed environment, Cloudera Manager automatically completes Kerberos configuration. In an unmanaged environment, create a Kerberos principal for each host running `impalad` or `statedored`. Cloudera recommends using a consistent format, such as `impala/_HOST@Your-Realm`, but you can use any three-part Kerberos server principal.

In Impala 2.0 and later, `user ()` returns the full Kerberos principal string, such as `user@example.com`, in a Kerberized environment.



Note: Regardless of the authentication mechanism used, Impala always creates HDFS directories and data files owned by the same user (typically `impala`). To implement user-level access to different databases, tables, columns, partitions, and so on, use the Sentry authorization feature, as explained in [Enabling Sentry Authorization for Impala](#) on page 105.

An alternative form of authentication you can use is LDAP, described in [Enabling LDAP Authentication for Impala](#) on page 119.

Requirements for Using Impala with Kerberos

On version 5 of Red Hat Enterprise Linux and comparable distributions, some additional setup is needed for the `impala-shell` interpreter to connect to a Kerberos-enabled Impala cluster:

```
sudo yum install python-devel openssl-devel python-pip
sudo pip-python install ssl
```



Important:

- If you plan to use Impala in your cluster, you must configure your KDC to allow tickets to be renewed, and you must configure `krb5.conf` to request renewable tickets. Typically, you can do this by adding the `max_renewable_life` setting to your realm in `kdc.conf`, and by adding the `renew_lifetime` parameter to the `libdefaults` section of `krb5.conf`.

For more information about renewable tickets, see the [Kerberos documentation](#).

- The Impala Web UI does not support Kerberos authentication.
- You cannot use the Impala resource management feature on a cluster that has Kerberos authentication enabled.

Start all `impalad` and `statedored` daemons with the `--principal` and `--keytab-file` flags set to the principal and full path name of the `keytab` file containing the credentials for the principal.

Impala supports the Cloudera ODBC driver and the Kerberos interface provided. To use Kerberos through the ODBC driver, the host type must be set depending on the level of the ODBC driver:

- `SecImpala` for the ODBC 1.0 driver.
- `SecBeeswax` for the ODBC 1.2 driver.
- Blank for the ODBC 2.0 driver or higher, when connecting to a secure cluster.
- `HS2NoSasl` for the ODBC 2.0 driver or higher, when connecting to a non-secure cluster.

To enable Kerberos in the Impala shell, start the `impala-shell` command using the `-k` flag.

To enable Impala to work with Kerberos security on your Hadoop cluster, make sure you perform the installation and configuration steps in [Authentication in the CDH 5 Security Guide](#).

Configuring Impala to Support Kerberos Security

Enabling Kerberos authentication for Impala involves steps that can be summarized as follows:

- Creating service principals for Impala and the HTTP service. Principal names take the form: `serviceName/fully.qualified.domain.name@KERBEROS.REALM`
- Creating, merging, and distributing key tab files for these principals.
- Editing `/etc/default/impala` (in cluster not managed by Cloudera Manager), or editing the **Security** settings in the Cloudera Manager interface, to accommodate Kerberos authentication.

Enabling Kerberos for Impala

1. Create an Impala service principal, specifying the name of the OS user that the Impala daemons run under, the fully qualified domain name of each node running `impalad`, and the realm name. For example:

```
$ kadmin
kadmin: addprinc -requires_preauth -randkey
impala/impala_host.example.com@TEST.EXAMPLE.COM
```

2. Create an HTTP service principal. For example:

```
kadmin: addprinc -randkey HTTP/impala_host.example.com@TEST.EXAMPLE.COM
```



Note: The HTTP component of the service principal must be uppercase as shown in the preceding example.

3. Create keytab files with both principals. For example:

```
kadmin: xst -k impala.keytab impala/impala_host.example.com
kadmin: xst -k http.keytab HTTP/impala_host.example.com
kadmin: quit
```

4. Use `ktutil` to read the contents of the two keytab files and then write those contents to a new file. For example:

```
$ ktutil
ktutil: rkt impala.keytab
ktutil: rkt http.keytab
ktutil: wkt impala-http.keytab
ktutil: quit
```

5. (Optional) Test that credentials in the merged keytab file are valid, and that the “renew until” date is in the future. For example:

```
$ klist -e -k -t impala-http.keytab
```

6. Copy the `impala-http.keytab` file to the Impala configuration directory. Change the permissions to be only read for the file owner and change the file owner to the `impala` user. By default, the Impala user and group are both named `impala`. For example:

```
$ cp impala-http.keytab /etc/impala/conf
$ cd /etc/impala/conf
$ chmod 400 impala-http.keytab
$ chown impala:impala impala-http.keytab
```

7. Add Kerberos options to the Impala defaults file, `/etc/default/impala`. Add the options for both the `impalad` and `statedored` daemons, using the `IMPALA_SERVER_ARGS` and `IMPALA_STATE_STORE_ARGS` variables. For example, you might add:

```
-kerberos_reinit_interval=60
-principal=impala_1/impala_host.example.com@TEST.EXAMPLE.COM
-keytab_file=/var/run/cloudera-scm-agent/process/3212-impala-IMPALAD/impala.keytab
```

For more information on changing the Impala defaults specified in `/etc/default/impala`, see [Modifying Impala Startup Options](#).



Note: Restart `impalad` and `statedored` for these configuration changes to take effect.

Enabling Kerberos for Impala with a Proxy Server

A common configuration for Impala with High Availability is to use a proxy server to submit requests to the actual `impalad` daemons on different hosts in the cluster. This configuration avoids connection problems in case of machine failure, because the proxy server can route new requests through one of the remaining hosts in the cluster. This configuration also helps with load balancing, because the additional overhead of being the “coordinator node” for each query is spread across multiple hosts.

Although you can set up a proxy server with or without Kerberos authentication, typically users set up a secure Kerberized configuration. For information about setting up a proxy server for Impala, including Kerberos-specific steps, see [Using Impala through a Proxy for High Availability](#) on page 93.

Enabling Impala Delegation for Kerberos Users

See [Configuring Impala Delegation for Hue and BI Tools](#) on page 122 for details about the delegation feature that lets certain users submit queries using the credentials of other users.

Using TLS/SSL with Business Intelligence Tools

You can use Kerberos authentication, TLS/SSL encryption, or both to secure connections from JDBC and ODBC applications to Impala. See [Configuring Impala to Work with JDBC](#) on page 36 and [Configuring Impala to Work with ODBC](#) on page 33 for details.

Prior to CDH 5.7 / Impala 2.5, the Hive JDBC driver did not support connections that use both Kerberos authentication and SSL encryption. If your cluster is running an older release that has this restriction, to use both of these security features with Impala through a JDBC application, use the [Cloudera JDBC Connector](#) as the JDBC driver.

Enabling Access to Internal Impala APIs for Kerberos Users

For applications that need direct access to Impala APIs, without going through the HiveServer2 or Beeswax interfaces, you can specify a list of Kerberos users who are allowed to call those APIs. By default, the `impala` and `hdfs` users are the only ones authorized for this kind of access. Any users not explicitly authorized through the `internal_principals_whitelist` configuration setting are blocked from accessing the APIs. This setting applies to all the Impala-related daemons, although currently it is primarily used for HDFS to control the behavior of the catalog server.

Mapping Kerberos Principals to Short Names for Impala

In CDH 5.8 / Impala 2.6 and higher, Impala recognizes the `auth_to_local` setting, specified through the HDFS configuration setting `hadoop.security.auth_to_local` or the Cloudera Manager setting **Additional Rules to Map Kerberos Principals to Short Names**. This feature is disabled by default, to avoid an unexpected change in security-related behavior. To enable it:

- For clusters not managed by Cloudera Manager, specify `--load_auth_to_local_rules=true` in the `impalad` and `catalogd` configuration settings.
- For clusters managed by Cloudera Manager, select the **Use HDFS Rules to Map Kerberos Principals to Short Names** checkbox to enable the service-wide `load_auth_to_local_rules` configuration setting. Then restart the Impala service.

See [Using Auth-to-Local Rules to Isolate Cluster Users](#) for general information about this feature.

Enabling LDAP Authentication for Impala

Authentication is the process of allowing only specified named users to access the server (in this case, the Impala server). This feature is crucial for any production deployment, to prevent misuse, tampering, or excessive load on the server. Impala uses LDAP for authentication, verifying the credentials of each user who connects through `impala-shell`, Hue, a Business Intelligence tool, JDBC or ODBC application, and so on.



Note: Regardless of the authentication mechanism used, Impala always creates HDFS directories and data files owned by the same user (typically `impala`). To implement user-level access to different databases, tables, columns, partitions, and so on, use the Sentry authorization feature, as explained in [Enabling Sentry Authorization for Impala](#) on page 105.

An alternative form of authentication you can use is Kerberos, described in [Enabling Kerberos Authentication for Impala](#) on page 116.

Requirements for Using Impala with LDAP

Authentication against LDAP servers is available in Impala 1.2.2 and higher. Impala 1.4.0 adds support for secure LDAP authentication through SSL and TLS.

The Impala LDAP support lets you use Impala with systems such as Active Directory that use LDAP behind the scenes.

Kerberos Authentication for Connections Between Impala Components

Only client->Impala connections can be authenticated by LDAP.

You must use the Kerberos authentication mechanism for connections between internal Impala components, such as between the `impalad`, `statedored`, and `catalogd` daemons. See [Enabling Kerberos Authentication for Impala](#) on page 116 on how to set up Kerberos for Impala.

Server-Side LDAP Setup

These requirements apply on the server side when configuring and starting Impala:

To enable LDAP authentication, set the following startup options for `impalad`:

- `--enable_ldap_auth` enables LDAP-based authentication between the client and Impala.
- `--ldap_uri` sets the URI of the LDAP server to use. Typically, the URI is prefixed with `ldap://`. In Impala 1.4.0 and higher, you can specify secure SSL-based LDAP transport by using the prefix `ldaps://`. The URI can optionally specify the port, for example: `ldap://ldap_server.cloudera.com:389` or `ldaps://ldap_server.cloudera.com:636`. (389 and 636 are the default ports for non-SSL and SSL LDAP connections, respectively.)
- For `ldaps://` connections secured by SSL, `--ldap_ca_certificate="/path/to/certificate/pem"` specifies the location of the certificate in standard `.PEM` format. Store this certificate on the local filesystem, in a location that only the `impala` user and other trusted users can read.

Support for Custom Bind Strings

When Impala connects to LDAP it issues a bind call to the LDAP server to authenticate as the connected user. Impala clients, including the Impala shell, provide the short name of the user to Impala. This is necessary so that Impala can use Sentry for role-based access, which uses short names.

However, LDAP servers often require more complex, structured usernames for authentication. Impala supports three ways of transforming the short name (for example, 'henry') to a more complicated string. If necessary, specify one of the following configuration options when starting the `impalad` daemon on each DataNode:

- `--ldap_domain`: Replaces the username with a string `username@ldap_domain`.
- `--ldap_baseDN`: Replaces the username with a "distinguished name" (DN) of the form: `uid=userid,ldap_baseDN`. (This is equivalent to a Hive option).
- `--ldap_bind_pattern`: This is the most general option, and replaces the username with the string `ldap_bind_pattern` where all instances of the string `#UID` are replaced with `userid`. For example, an `ldap_bind_pattern` of `"user=#UID,OU=foo,CN=bar"` with a username of `henry` will construct a bind name of `"user=henry,OU=foo,CN=bar"`.

For clusters not managed by Cloudera Manager, specify the option on the `impalad` command line. For clusters managed by Cloudera Manager 5.4.0 and higher, search for the configuration field names `ldap_domain`, `ldap_basedn`, or `ldap_bind_pattern`, fill in and save the appropriate field values, and restart the Impala service. Prior to Cloudera Manager 5.4.0, these values were filled in using the **Impala Daemon Command Line Argument Advanced Configuration Snippet (Safety Valve)** field.

These options are mutually exclusive; Impala does not start if more than one of these options is specified.

Secure LDAP Connections

To avoid sending credentials over the wire in cleartext, you must configure a secure connection between both the client and Impala, and between Impala and the LDAP server. The secure connection could use SSL or TLS.

Secure LDAP connections through SSL:

For SSL-enabled LDAP connections, specify a prefix of `ldaps://` instead of `ldap://`. Also, the default port for SSL-enabled LDAP connections is 636 instead of 389.

Secure LDAP connections through TLS:

[TLS](#), the successor to the SSL protocol, is supported by most modern LDAP servers. Unlike SSL connections, TLS connections can be made on the same server port as non-TLS connections. To secure all connections using TLS, specify the following flags as startup options to the `impalad` daemon:

- `--ldap_tls` tells Impala to start a TLS connection to the LDAP server, and to fail authentication if it cannot be done.
- `--ldap_ca_certificate="/path/to/certificate/pem"` specifies the location of the certificate in standard `.PEM` format. Store this certificate on the local filesystem, in a location that only the `impala` user and other trusted users can read.

LDAP Authentication for `impala-shell` Interpreter

To connect to Impala using LDAP authentication, you specify command-line options to the `impala-shell` command interpreter and enter the password when prompted:

- `-l` enables LDAP authentication.
- `-u` sets the user. Per Active Directory, the user is the short username, not the full LDAP distinguished name. If your LDAP settings include a search base, use the `--ldap_bind_pattern` on the `impalad` daemon to translate the short user name from `impala-shell` automatically to the fully qualified name.
- `impala-shell` automatically prompts for the password.

For the full list of available `impala-shell` options, see [impala-shell Configuration Options](#) on page 511.

LDAP authentication for JDBC applications: See [Configuring Impala to Work with JDBC](#) on page 36 for the format to use with the JDBC connection string for servers using LDAP authentication.

Enabling LDAP for Impala in Hue

Enabling LDAP for Impala in Hue Using Cloudera Manager

1. Go to the Hue service.
2. Click the Configuration tab.
3. Select **Scope > Hue Server**.
4. Select **Category > Advanced**.
5. Add the following properties to the **Hue Server Advanced Configuration Snippet (Safety Valve) for `hue_safety_valve_server.ini`** property.

```
[impala]
auth_username=<LDAP username of Hue user to be authenticated>
auth_password=<LDAP password of Hue user to be authenticated>
```

6. Click **Save Changes**.

Enabling LDAP for Impala in Hue Using the Command Line

LDAP authentication for the Impala app in Hue can be enabled by setting the following properties under the `[impala]` section in `hue.ini`.

<code>auth_username</code>	LDAP username of Hue user to be authenticated.
<code>auth_password</code>	LDAP password of Hue user to be authenticated.

These login details are only used by Impala to authenticate to LDAP. The Impala service trusts Hue to have already validated the user being impersonated, rather than simply passing on the credentials.

Enabling Impala Delegation for LDAP Users

See [Configuring Impala Delegation for Hue and BI Tools](#) on page 122 for details about the delegation feature that lets certain users submit queries using the credentials of other users.

LDAP Restrictions for Impala

The LDAP support is preliminary. It currently has only been tested against Active Directory.

Using Multiple Authentication Methods with Impala

Impala 2.0 and later automatically handles both Kerberos and LDAP authentication. Each `impalad` daemon can accept both Kerberos and LDAP requests through the same port. No special actions need to be taken if some users authenticate through Kerberos and some through LDAP.

Prior to Impala 2.0, you had to configure each `impalad` to listen on a specific port depending on the kind of authentication, then configure your network load balancer to forward each kind of request to a DataNode that was set up with the appropriate authentication type. Once the initial request was made using either Kerberos or LDAP authentication, Impala automatically handled the process of coordinating the work across multiple nodes and transmitting intermediate results back to the coordinator node.

Configuring Impala Delegation for Hue and BI Tools

When users submit Impala queries through a separate application, such as Hue or a business intelligence tool, typically all requests are treated as coming from the same user. In Impala 1.2 and higher, Impala supports applications to pass along credentials for the users that connect to them, known as “delegation”, and to issue Impala queries with the privileges for those users. Currently, the delegation feature is available only for Impala queries submitted through application interfaces such as Hue and BI tools; for example, Impala cannot issue queries using the privileges of the HDFS user.

The delegation feature is enabled by a startup option for `impalad`: `--authorized_proxy_user_config`. When you specify this option, users whose names you specify (such as `hue`) can delegate the execution of a query to another user. The query runs with the privileges of the delegated user, not the original user such as `hue`. The name of the delegated user is passed using the HiveServer2 configuration property `impala.doas.user`.

You can specify a list of users that the application user can delegate to, or `*` to allow a superuser to delegate to any other user. For example:

```
impalad --authorized_proxy_user_config 'hue=user1,user2;admin=*' ...
```



Note: Make sure to use single quotes or escape characters to ensure that any `*` characters do not undergo wildcard expansion when specified in command-line arguments.

See [Modifying Impala Startup Options](#) on page 45 for details about adding or changing `impalad` startup options. See [this Cloudera blog post](#) for background information about the delegation capability in HiveServer2.

To set up authentication for the delegated users:

- On the server side, configure either user/password authentication through LDAP, or Kerberos authentication, for all the delegated users. See [Enabling LDAP Authentication for Impala](#) on page 119 or [Enabling Kerberos Authentication for Impala](#) on page 116 for details.
- On the client side, follow the instructions in the “Using User Name and Password” section in the [ODBC driver installation guide](#). Then search for “delegation” in that same installation guide to learn about the **Delegation UID** field and `DelegationUID` configuration keyword to enable the delegation feature for ODBC-based BI tools.

Enabling Delegation in Cloudera Manager

To enable delegation in Cloudera Manager:

1. Navigate to **Clusters > Impala > Configuration > Policy File-Based Sentry**.
2. In the **Proxy User Configuration** field, type the a semicolon-separated list of key=value pairs of authorized proxy users to the user(s) they can impersonate. The list of delegated users are delimited with a comma, e.g. **hue=user1, user2**.
3. Click **Save Changes** and then restart Impala service.

Auditing Impala Operations

To monitor how Impala data is being used within your organization, ensure that your Impala authorization and authentication policies are effective, and detect attempts at intrusion or unauthorized access to Impala data, you can use the auditing feature in Impala 1.2.1 and higher:

- Enable auditing by including the option `-audit_event_log_dir=directory_path` in your `impalad` startup options for a cluster not managed by Cloudera Manager, or [configuring Impala Daemon logging in Cloudera Manager](#). The log directory must be a local directory on the server, not an HDFS directory.
- Decide how many queries will be represented in each log files. By default, Impala starts a new log file every 5000 queries. To specify a different number, include the option `-max_audit_event_log_file_size=number_of_queries` in the `impalad` startup options.
- Configure Cloudera Navigator to collect and consolidate the audit logs from all the hosts in the cluster.
- Use Cloudera Navigator or Cloudera Manager to filter, visualize, and produce reports based on the audit data. (The Impala auditing feature works with Cloudera Manager 4.7 to 5.1 and Cloudera Navigator 2.1 and higher.) Check the audit data to ensure that all activity is authorized and detect attempts at unauthorized access.

Durability and Performance Considerations for Impala Auditing

The auditing feature only imposes performance overhead while auditing is enabled.

Because any Impala host can process a query, enable auditing on all hosts where the `impalad` daemon runs. Each host stores its own log files, in a directory in the local filesystem. The log data is periodically flushed to disk (through an `fsync()` system call) to avoid loss of audit data in case of a crash.

The runtime overhead of auditing applies to whichever host serves as the coordinator for the query, that is, the host you connect to when you issue the query. This might be the same host for all queries, or different applications or users might connect to and issue queries through different hosts.

To avoid excessive I/O overhead on busy coordinator hosts, Impala syncs the audit log data (using the `fsync()` system call) periodically rather than after every query. Currently, the `fsync()` calls are issued at a fixed interval, every 5 seconds.

By default, Impala avoids losing any audit log data in the case of an error during a logging operation (such as a disk full error), by immediately shutting down `impalad` on the host where the auditing problem occurred. You can override this setting by specifying the option `-abort_on_failed_audit_event=false` in the `impalad` startup options.

Format of the Audit Log Files

The audit log files represent the query information in JSON format, one query per line. Typically, rather than looking at the log files themselves, you use the Cloudera Navigator product to consolidate the log data from all Impala hosts and filter and visualize the results in useful ways. (If you do examine the raw log data, you might run the files through a JSON pretty-printer first.)

All the information about schema objects accessed by the query is encoded in a single nested record on the same line. For example, the audit log for an `INSERT ... SELECT` statement records that a select operation occurs on the source table and an insert operation occurs on the destination table. The audit log for a query against a view records the base table accessed by the view, or multiple base tables in the case of a view that includes a join query. Every Impala operation that corresponds to a SQL statement is recorded in the audit logs, whether the operation succeeds or fails. Impala records more information for a successful operation than for a failed one, because an unauthorized query is stopped immediately, before all the query planning is completed.

The information logged for each query includes:

- Client session state:
 - Session ID
 - User name
 - Network address of the client connection

- SQL statement details:
 - Query ID
 - Statement Type - DML, DDL, and so on
 - SQL statement text
 - Execution start time, in local time
 - Execution Status - Details on any errors that were encountered
 - Target Catalog Objects:
 - Object Type - Table, View, or Database
 - Fully qualified object name
 - Privilege - How the object is being used (`SELECT`, `INSERT`, `CREATE`, and so on)

Which Operations Are Audited

The kinds of SQL queries represented in the audit log are:

- Queries that are prevented due to lack of authorization.
- Queries that Impala can analyze and parse to determine that they are authorized. The audit data is recorded immediately after Impala finishes its analysis, before the query is actually executed.

The audit log does not contain entries for queries that could not be parsed and analyzed. For example, a query that fails due to a syntax error is not recorded in the audit log. The audit log also does not contain queries that fail due to a reference to a table that does not exist, if you would be authorized to access the table if it did exist.

Certain statements in the `impala-shell` interpreter, such as `CONNECT`, `SUMMARY`, `PROFILE`, `SET`, and `QUIT`, do not correspond to actual SQL queries, and these statements are not reflected in the audit log.

Reviewing the Audit Logs

You typically do not review the audit logs in raw form. The Cloudera Manager Agent periodically transfers the log information into a back-end database where it can be examined in consolidated form. See the [Cloudera Navigator documentation](#) for details .

Viewing Lineage Information for Impala Data

Lineage is a feature in the Cloudera Navigator data management component that helps you track where data originated, and how data propagates through the system through SQL statements such as `SELECT`, `INSERT`, and `CREATE TABLE AS SELECT`. Impala is covered by the Cloudera Navigator lineage features in CDH 5.4.0 and higher.

This type of tracking is important in high-security configurations, especially in highly regulated industries such as healthcare, pharmaceuticals, financial services and intelligence. For such kinds of sensitive data, it is important to know all the places in the system that contain that data or other data derived from it; to verify who has accessed that data; and to be able to doublecheck that the data used to make a decision was processed correctly and not tampered with.

You interact with this feature through **lineage diagrams** showing relationships between tables and columns. For instructions about interpreting lineage diagrams, see http://www.cloudera.com/documentation/enterprise/latest/topics/cn_iu_lineage.html.

Column Lineage

Column lineage tracks information in fine detail, at the level of particular columns rather than entire tables.

For example, if you have a table with information derived from web logs, you might copy that data into other tables as part of the ETL process. The ETL operations might involve transformations through expressions and function calls, and rearranging the columns into more or fewer tables (**normalizing** or **denormalizing** the data). Then for reporting, you might issue queries against multiple tables and views. In this example, column lineage helps you determine that data that entered the system as `RAW_LOGS.FIELD1` was then turned into `WEBSITE_REPORTS.IP_ADDRESS` through

an `INSERT . . . SELECT` statement. Or, conversely, you could start with a reporting query against a view, and trace the origin of the data in a field such as `TOP_10_VISITORS.USER_ID` back to the underlying table and even further back to the point where the data was first loaded into Impala.

When you have tables where you need to track or control access to sensitive information at the column level, see [Enabling Sentry Authorization for Impala](#) on page 105 for how to implement column-level security. You set up authorization using the Sentry framework, create views that refer to specific sets of columns, and then assign authorization privileges to those views rather than the underlying tables.

Lineage Data for Impala

The lineage feature is enabled by default. When lineage logging is enabled, the serialized column lineage graph is computed for each query and stored in a specialized log file in JSON format.

Impala records queries in the lineage log if they complete successfully, or fail due to authorization errors. For write operations such as `INSERT` and `CREATE TABLE AS SELECT`, the statement is recorded in the lineage log only if it successfully completes. Therefore, the lineage feature tracks data that was accessed by successful queries, or that was attempted to be accessed by unsuccessful queries that were blocked due to authorization failure. These kinds of queries represent data that really was accessed, or where the attempted access could represent malicious activity.

Impala does not record in the lineage log queries that fail due to syntax errors or that fail or are cancelled before they reach the stage of requesting rows from the result set.

To enable or disable this feature on a system not managed by Cloudera Manager, set or remove the `-lineage_event_log_dir` configuration option for the `impalad` daemon. For information about turning the lineage feature on and off through Cloudera Manager, see http://www.cloudera.com/documentation/enterprise/latest/topics/datamgmt_impala_lineage_log.html.

Impala SQL Language Reference

Impala uses SQL as its query language. To protect user investment in skills development and query design, Impala provides a high degree of compatibility with the Hive Query Language (HiveQL):

- Because Impala uses the same metadata store as Hive to record information about table structure and properties, Impala can access tables defined through the native Impala `CREATE TABLE` command, or tables created using the Hive data definition language (DDL).
- Impala supports data manipulation (DML) statements similar to the DML component of HiveQL.
- Impala provides many [built-in functions](#) with the same names and parameter types as their HiveQL equivalents.

Impala supports most of the same [statements and clauses](#) as HiveQL, including, but not limited to `JOIN`, `AGGREGATE`, `DISTINCT`, `UNION ALL`, `ORDER BY`, `LIMIT` and (uncorrelated) subquery in the `FROM` clause. Impala also supports `INSERT INTO` and `INSERT OVERWRITE`.

Impala supports data types with the same names and semantics as the equivalent Hive data types: `STRING`, `TINYINT`, `SMALLINT`, `INT`, `BIGINT`, `FLOAT`, `DOUBLE`, `BOOLEAN`, `STRING`, `TIMESTAMP`.

For full details about Impala SQL syntax and semantics, see [Impala SQL Statements](#) on page 228.

Most HiveQL `SELECT` and `INSERT` statements run unmodified with Impala. For information about Hive syntax not available in Impala, see [SQL Differences Between Impala and Hive](#) on page 502.

For a list of the built-in functions available in Impala queries, see [Impala Built-In Functions](#) on page 373.

Comments

Impala supports the familiar styles of SQL comments:

- All text from a `--` sequence to the end of the line is considered a comment and ignored. This type of comment can occur on a single line by itself, or after all or part of a statement.
- All text from a `/*` sequence to the next `*/` sequence is considered a comment and ignored. This type of comment can stretch over multiple lines. This type of comment can occur on one or more lines by itself, in the middle of a statement, or before or after a statement.

For example:

```
-- This line is a comment about a table.
create table ...;

/*
This is a multi-line comment about a query.
*/
select ...;

select * from t /* This is an embedded comment about a query. */ where ...;

select * from t -- This is a trailing comment within a multi-line command.
where ...;
```

Data Types

Impala supports a set of data types that you can use for table columns, expression values, and function arguments and return values.



Note: Currently, Impala supports only scalar types, not composite or nested types. Accessing a table containing any columns with unsupported types causes an error.

For the notation to write literals of each of these data types, see [Literals](#) on page 195.

See [SQL Differences Between Impala and Hive](#) on page 502 for differences between Impala and Hive data types.

ARRAY Complex Type (CDH 5.5 or higher only)

A complex data type that can represent an arbitrary number of ordered elements. The elements can be scalars or another complex type (ARRAY, STRUCT, or MAP).

Syntax:

```
column_name ARRAY < type >
type ::= primitive_type | complex_type
```

Usage notes:

Because complex types are often used in combination, for example an ARRAY of STRUCT elements, if you are unfamiliar with the Impala complex types, start with [Complex Types \(CDH 5.5 or higher only\)](#) on page 167 for background information and usage examples.

The elements of the array have no names. You refer to the value of the array item using the ITEM pseudocolumn, or its position in the array with the POS pseudocolumn. See [ITEM and POS Pseudocolumns](#) on page 181 for information about these pseudocolumns.

Each row can have a different number of elements (including none) in the array for that row.

When an array contains items of scalar types, you can use aggregation functions on the array elements without using join notation. For example, you can find the COUNT(), AVG(), SUM(), and so on of numeric array elements, or the MAX() and MIN() of any scalar array elements by referring to *table_name.array_column* in the FROM clause of the query. When you need to cross-reference values from the array with scalar values from the same row, such as by including a GROUP BY clause to produce a separate aggregated result for each row, then the join clause is required.

A common usage pattern with complex types is to have an array as the top-level type for the column: an array of structs, an array of maps, or an array of arrays. For example, you can model a denormalized table by creating a column that is an ARRAY of STRUCT elements; each item in the array represents a row from a table that would normally be used in a join query. This kind of data structure lets you essentially denormalize tables by associating multiple rows from one table with the matching row in another table.

You typically do not create more than one top-level ARRAY column, because if there is some relationship between the elements of multiple arrays, it is convenient to model the data as an array of another complex type element (either STRUCT or MAP).

You can pass a multi-part qualified name to DESCRIBE to specify an ARRAY, STRUCT, or MAP column and visualize its structure as if it were a table. For example, if table T1 contains an ARRAY column A1, you could issue the statement DESCRIBE t1.a1. If table T1 contained a STRUCT column S1, and a field F1 within the STRUCT was a MAP, you could issue the statement DESCRIBE t1.s1.f1. An ARRAY is shown as a two-column table, with ITEM and POS columns. A STRUCT is shown as a table with each field representing a column in the table. A MAP is shown as a two-column table, with KEY and VALUE columns.

Added in: CDH 5.5.0 (Impala 2.3.0)

Restrictions:

- Columns with this data type can only be used in tables or partitions with the Parquet file format.
- Columns with this data type cannot be used as partition key columns in a partitioned table.
- The COMPUTE STATS statement does not produce any statistics for columns of this data type.
- The maximum length of the column definition for any complex type, including declarations for any nested types, is 4000 characters.
- See [Limitations and Restrictions for Complex Types](#) on page 171 for a full list of limitations and associated guidelines about complex type columns.

Examples:



Note: Many of the complex type examples refer to tables such as `CUSTOMER` and `REGION` adapted from the tables used in the TPC-H benchmark. See [Sample Schema and Data for Experimenting with Impala Complex Types](#) on page 188 for the table definitions.

The following example shows how to construct a table with various kinds of `ARRAY` columns, both at the top level and nested within other complex types. Whenever the `ARRAY` consists of a scalar value, such as in the `PETS` column or the `CHILDREN` field, you can see that future expansion is limited. For example, you could not easily evolve the schema to record the kind of pet or the child's birthday alongside the name. Therefore, it is more common to use an `ARRAY` whose elements are of `STRUCT` type, to associate multiple fields with each array element.



Note: Practice the `CREATE TABLE` and query notation for complex type columns using empty tables, until you can visualize a complex data structure and construct corresponding SQL statements reliably.

```
CREATE TABLE array_demo
(
  id BIGINT,
  name STRING,
  -- An ARRAY of scalar type as a top-level column.
  pets ARRAY <STRING>,
  -- An ARRAY with elements of complex type (STRUCT).
  places_lived ARRAY < STRUCT <
    place: STRING,
    start_year: INT
  >>,
  -- An ARRAY as a field (CHILDREN) within a STRUCT.
  -- (The STRUCT is inside another ARRAY, because it is rare
  -- for a STRUCT to be a top-level column.)
  marriages ARRAY < STRUCT <
    spouse: STRING,
    children: ARRAY <STRING>
  >>,
  -- An ARRAY as the value part of a MAP.
  -- The first MAP field (the key) would be a value such as
  -- 'Parent' or 'Grandparent', and the corresponding array would
  -- represent 2 parents, 4 grandparents, and so on.
  ancestors MAP < STRING, ARRAY <STRING> >
)
STORED AS PARQUET;
```

The following example shows how to examine the structure of a table containing one or more `ARRAY` columns by using the `DESCRIBE` statement. You can visualize each `ARRAY` as its own two-column table, with columns `ITEM` and `POS`.

```
DESCRIBE array_demo;
+-----+-----+
| name      | type                                     |
+-----+-----+
| id        | bigint                                  |
| name      | string                                  |
| pets      | array<string>                           |
| marriages | array<struct<                             |
|           |   spouse:string,                       |
|           |   children:array<string>                |
|           | >>                                       |
| places_lived | array<struct<                             |
|           |   place:string,                         |
|           |   start_year:int                       |
|           | >>                                       |
| ancestors | map<string,array<string>>                |
+-----+-----+
```



```
DESCRIBE array_demo.pets;
+-----+-----+
| name | type |
+-----+-----+
| item | string |
| pos  | bigint |
+-----+-----+

DESCRIBE array_demo.marriages;
+-----+-----+
| name | type |
+-----+-----+
| item | struct<
|      | spouse:string,
|      | children:array<string>
|      | >
| pos  | bigint |
+-----+-----+

DESCRIBE array_demo.places_lived;
+-----+-----+
| name | type |
+-----+-----+
| item | struct<
|      | place:string,
|      | start_year:int
|      | >
| pos  | bigint |
+-----+-----+

DESCRIBE array_demo.ancestors;
+-----+-----+
| name | type |
+-----+-----+
| key  | string |
| value | array<string> |
+-----+-----+
```

The following example shows queries involving ARRAY columns containing elements of scalar or complex types. You “unpack” each ARRAY column by referring to it in a join query, as if it were a separate table with ITEM and POS columns. If the array element is a scalar type, you refer to its value using the ITEM pseudocolumn. If the array element is a STRUCT, you refer to the STRUCT fields using dot notation and the field names. If the array element is another ARRAY or a MAP, you use another level of join to unpack the nested collection elements.

```
-- Array of scalar values.
-- Each array element represents a single string, plus we know its position in the array.
SELECT id, name, pets.pos, pets.item FROM array_demo, array_demo.pets;

-- Array of structs.
-- Now each array element has named fields, possibly of different types.
-- You can consider an ARRAY of STRUCT to represent a table inside another table.
SELECT id, name, places_lived.pos, places_lived.item.place, places_lived.item.start_year
FROM array_demo, array_demo.places_lived;

-- The .ITEM name is optional for array elements that are structs.
-- The following query is equivalent to the previous one, with .ITEM
-- removed from the column references.
SELECT id, name, places_lived.pos, places_lived.place, places_lived.start_year
FROM array_demo, array_demo.places_lived;

-- To filter specific items from the array, do comparisons against the .POS or .ITEM
-- pseudocolumns, or names of struct fields, in the WHERE clause.
SELECT id, name, pets.item FROM array_demo, array_demo.pets
WHERE pets.pos in (0, 1, 3);

SELECT id, name, pets.item FROM array_demo, array_demo.pets
WHERE pets.item LIKE 'Mr. %';

SELECT id, name, places_lived.pos, places_lived.place, places_lived.start_year
FROM array_demo, array_demo.places_lived
```

```
WHERE places_lived.place like '%California%';
```

Related information:

[Complex Types \(CDH 5.5 or higher only\)](#) on page 167, [STRUCT Complex Type \(CDH 5.5 or higher only\)](#) on page 153, [MAP Complex Type \(CDH 5.5 or higher only\)](#) on page 146

BIGINT Data Type

An 8-byte integer data type used in `CREATE TABLE` and `ALTER TABLE` statements.

Syntax:

In the column definition of a `CREATE TABLE` statement:

```
column_name BIGINT
```

Range: -9223372036854775808 .. 9223372036854775807. There is no `UNSIGNED` subtype.

Conversions: Impala automatically converts to a floating-point type (`FLOAT` or `DOUBLE`) automatically. Use `CAST()` to convert to `TINYINT`, `SMALLINT`, `INT`, `STRING`, or `TIMESTAMP`. Casting an integer or floating-point value `N` to `TIMESTAMP` produces a value that is `N` seconds past the start of the epoch date (January 1, 1970). By default, the result value represents a date and time in the UTC time zone. If the setting `--use_local_tz_for_unix_timestamp_conversions=true` is in effect, the resulting `TIMESTAMP` represents a date and time in the local time zone.

Examples:

```
CREATE TABLE t1 (x BIGINT);
SELECT CAST(1000 AS BIGINT);
```

Usage notes:

`BIGINT` is a convenient type to use for column declarations because you can use any kind of integer values in `INSERT` statements and they are promoted to `BIGINT` where necessary. However, `BIGINT` also requires the most bytes of any integer type on disk and in memory, meaning your queries are not as efficient and scalable as possible if you overuse this type. Therefore, prefer to use the smallest integer type with sufficient range to hold all input values, and `CAST()` when necessary to the appropriate type.

For a convenient and automated way to check the bounds of the `BIGINT` type, call the functions `MIN_BIGINT()` and `MAX_BIGINT()`.

If an integer value is too large to be represented as a `BIGINT`, use a `DECIMAL` instead with sufficient digits of precision.

NULL considerations: Casting any non-numeric value to this type produces a `NULL` value.

Partitioning: Prefer to use this type for a partition key column. Impala can process the numeric type more efficiently than a `STRING` representation of the value.

HBase considerations: This data type is fully compatible with HBase tables.

Text table considerations: Values of this type are potentially larger in text tables than in tables using Parquet or other binary formats.

Internal details: Represented in memory as an 8-byte value.

Added in: Available in all versions of Impala.

Column statistics considerations: Because this type has a fixed size, the maximum and average size fields are always filled in for column statistics, even before you run the `COMPUTE STATS` statement.

Sqoop considerations:

If you use Sqoop to convert RDBMS data to Parquet, be careful with interpreting any resulting values from `DATE`, `DATETIME`, or `TIMESTAMP` columns. The underlying values are represented as the Parquet `INT64` type, which is represented as `BIGINT` in the Impala table. The Parquet values represent the time in milliseconds, while Impala interprets `BIGINT` as the time in seconds. Therefore, if you have a `BIGINT` column in a Parquet table that was imported this way from Sqoop, divide the values by 1000 when interpreting as the `TIMESTAMP` type.

Related information:

[Numeric Literals](#) on page 195, [TINYINT Data Type](#) on page 164, [SMALLINT Data Type](#) on page 150, [INT Data Type](#) on page 145, [BIGINT Data Type](#) on page 130, [DECIMAL Data Type \(CDH 5.1 or higher only\)](#) on page 135, [Impala Mathematical Functions](#) on page 374

BOOLEAN Data Type

A data type used in `CREATE TABLE` and `ALTER TABLE` statements, representing a single true/false choice.

Syntax:

In the column definition of a `CREATE TABLE` statement:

```
column_name BOOLEAN
```

Range: `TRUE` or `FALSE`. Do not use quotation marks around the `TRUE` and `FALSE` literal values. You can write the literal values in uppercase, lowercase, or mixed case. The values queried from a table are always returned in lowercase, `true` or `false`.

Conversions: Impala does not automatically convert any other type to `BOOLEAN`. All conversions must use an explicit call to the `CAST()` function.

You can use `CAST()` to convert any integer or floating-point type to `BOOLEAN`: a value of 0 represents `false`, and any non-zero value is converted to `true`.

```
SELECT CAST(42 AS BOOLEAN) AS nonzero_int, CAST(99.44 AS BOOLEAN) AS nonzero_decimal,
       CAST(000 AS BOOLEAN) AS zero_int, CAST(0.0 AS BOOLEAN) AS zero_decimal;
+-----+-----+-----+-----+
| nonzero_int | nonzero_decimal | zero_int | zero_decimal |
+-----+-----+-----+-----+
| true       | true            | false   | false        |
+-----+-----+-----+-----+
```

When you cast the opposite way, from `BOOLEAN` to a numeric type, the result becomes either 1 or 0:

```
SELECT CAST(true AS INT) AS true_int, CAST(true AS DOUBLE) AS true_double,
       CAST(false AS INT) AS false_int, CAST(false AS DOUBLE) AS false_double;
+-----+-----+-----+-----+
| true_int | true_double | false_int | false_double |
+-----+-----+-----+-----+
| 1       | 1          | 0        | 0            |
+-----+-----+-----+-----+
```

You can cast `DECIMAL` values to `BOOLEAN`, with the same treatment of zero and non-zero values as the other numeric types. You cannot cast a `BOOLEAN` to a `DECIMAL`.

You cannot cast a `STRING` value to `BOOLEAN`, although you can cast a `BOOLEAN` value to `STRING`, returning `'1'` for true values and `'0'` for false values.

Although you can cast a `TIMESTAMP` to a `BOOLEAN` or a `BOOLEAN` to a `TIMESTAMP`, the results are unlikely to be useful. Any non-zero `TIMESTAMP` (that is, any value other than `1970-01-01 00:00:00`) becomes `TRUE` when converted to `BOOLEAN`, while `1970-01-01 00:00:00` becomes `FALSE`. A value of `FALSE` becomes `1970-01-01 00:00:00` when converted to `BOOLEAN`, and `TRUE` becomes one second past this epoch date, that is, `1970-01-01 00:00:01`.

NULL considerations: An expression of this type produces a `NULL` value if any argument of the expression is `NULL`.

Partitioning:

Do not use a `BOOLEAN` column as a partition key. Although you can create such a table, subsequent operations produce errors:

```
[localhost:21000] > create table truth_table (assertion string) partitioned by (truth
boolean);
[localhost:21000] > insert into truth_table values ('Pigs can fly',false);
ERROR: AnalysisException: INSERT into table with BOOLEAN partition column (truth) is
not supported: partitioning.truth_table
```

Examples:

```
SELECT 1 < 2;
SELECT 2 = 5;
SELECT 100 < NULL, 100 > NULL;
CREATE TABLE assertions (claim STRING, really BOOLEAN);
INSERT INTO assertions VALUES
  ("1 is less than 2", 1 < 2),
  ("2 is the same as 5", 2 = 5),
  ("Grass is green", true),
  ("The moon is made of green cheese", false);
SELECT claim FROM assertions WHERE really = TRUE;
```

HBase considerations: This data type is fully compatible with HBase tables.

Parquet considerations: This type is fully compatible with Parquet tables.

Text table considerations: Values of this type are potentially larger in text tables than in tables using Parquet or other binary formats.

Column statistics considerations: Because this type has a fixed size, the maximum and average size fields are always filled in for column statistics, even before you run the `COMPUTE STATS` statement.

Related information: [Boolean Literals](#) on page 197, [SQL Operators](#) on page 199, [Impala Conditional Functions](#) on page 427

CHAR Data Type (CDH 5.2 or higher only)

A fixed-length character type, padded with trailing spaces if necessary to achieve the specified length. If values are longer than the specified length, Impala truncates any trailing characters.

Syntax:

In the column definition of a `CREATE TABLE` statement:

```
column_name CHAR(length)
```

The maximum length you can specify is 255.

Semantics of trailing spaces:

- When you store a `CHAR` value shorter than the specified length in a table, queries return the value padded with trailing spaces if necessary; the resulting value has the same length as specified in the column definition.
- If you store a `CHAR` value containing trailing spaces in a table, those trailing spaces are not stored in the data file. When the value is retrieved by a query, the result could have a different number of trailing spaces. That is, the value includes however many spaces are needed to pad it to the specified length of the column.
- If you compare two `CHAR` values that differ only in the number of trailing spaces, those values are considered identical.

Partitioning: This type can be used for partition key columns. Because of the efficiency advantage of numeric values over character-based values, if the partition key is a string representation of a number, prefer to use an integer type with sufficient range (`INT`, `BIGINT`, and so on) where practical.

HBase considerations: This data type cannot be used with HBase tables.

Parquet considerations:

- This type can be read from and written to Parquet files.
- There is no requirement for a particular level of Parquet.
- Parquet files generated by Impala and containing this type can be freely interchanged with other components such as Hive and MapReduce.
- Any trailing spaces, whether implicitly or explicitly specified, are not written to the Parquet data files.
- Parquet data files might contain values that are longer than allowed by the `CHAR(n)` length limit. Impala ignores any extra trailing characters when it processes those values during a query.

Text table considerations:

Text data files might contain values that are longer than allowed for a particular `CHAR(n)` column. Any extra trailing characters are ignored when Impala processes those values during a query. Text data files can also contain values that are shorter than the defined length limit, and Impala pads them with trailing spaces up to the specified length. Any text data files produced by Impala `INSERT` statements do not include any trailing blanks for `CHAR` columns.

Avro considerations:

The Avro specification allows string values up to $2^{**}64$ bytes in length. Impala queries for Avro tables use 32-bit integers to hold string lengths. In CDH 5.7 / Impala 2.5 and higher, Impala truncates `CHAR` and `VARCHAR` values in Avro tables to $(2^{**}31)-1$ bytes. If a query encounters a `STRING` value longer than $(2^{**}31)-1$ bytes in an Avro table, the query fails. In earlier releases, encountering such long values in an Avro table could cause a crash.

Compatibility:

This type is available using Impala 2.0 or higher under CDH 4, or with Impala on CDH 5.2 or higher. There are no compatibility issues with other components when exchanging data files or running Impala on CDH 4.

Some other database systems make the length specification optional. For Impala, the length is required.

Internal details: Represented in memory as a byte array with the same size as the length specification. Values that are shorter than the specified length are padded on the right with trailing spaces.

Added in: CDH 5.2.0 (Impala 2.0.0)

Column statistics considerations: Because this type has a fixed size, the maximum and average size fields are always filled in for column statistics, even before you run the `COMPUTE STATS` statement.

UDF considerations: This type cannot be used for the argument or return type of a user-defined function (UDF) or user-defined aggregate function (UDA).

Examples:

These examples show how trailing spaces are not considered significant when comparing or processing `CHAR` values. `CAST()` truncates any longer string to fit within the defined length. If a `CHAR` value is shorter than the specified length, it is padded on the right with spaces until it matches the specified length. Therefore, `LENGTH()` represents the length including any trailing spaces, and `CONCAT()` also treats the column value as if it has trailing spaces.

```
select cast('x' as char(4)) = cast('x   ' as char(4)) as "unpadded equal to padded";
+-----+
| unpadded equal to padded |
+-----+
| true                       |
+-----+

create table char_length(c char(3));
insert into char_length values (cast('1' as char(3))), (cast('12' as char(3))),
(cast('123' as char(3))), (cast('123456' as char(3)));
select concat("[",c,"]") as c, length(c) from char_length;
+-----+-----+
| c      | length(c) |
+-----+-----+
| [1  ]  | 3         |
| [12 ]  | 3         |
| [123]  | 3         |
| [123]  | 3         |
+-----+-----+
```

This example shows a case where data values are known to have a specific length, where CHAR is a logical data type to use.

```
create table addresses
(id bigint,
 street_name string,
 state_abbreviation char(2),
 country_abbreviation char(2));
```

The following example shows how values written by Impala do not physically include the trailing spaces. It creates a table using text format, with CHAR values much shorter than the declared length, and then prints the resulting data file to show that the delimited values are not separated by spaces. The same behavior applies to binary-format Parquet data files.

```
create table char_in_text (a char(20), b char(30), c char(40))
row format delimited fields terminated by ',';

insert into char_in_text values (cast('foo' as char(20)), cast('bar' as char(30)),
cast('baz' as char(40)), (cast('hello' as char(20)), cast('goodbye' as char(30)),
cast('aloha' as char(40)));

-- Running this Linux command inside impala-shell using the ! shortcut.
!hdfs dfs -cat
'hdfs://127.0.0.1:8020/user/hive/warehouse/impala_doc_testing.db/char_in_text/*..*';
foo,bar,baz
hello,goodbye,aloha
```

The following example further illustrates the treatment of spaces. It replaces the contents of the previous table with some values including leading spaces, trailing spaces, or both. Any leading spaces are preserved within the data file, but trailing spaces are discarded. Then when the values are retrieved by a query, the leading spaces are retrieved verbatim while any necessary trailing spaces are supplied by Impala.

```
insert overwrite char_in_text values (cast('trailing ' as char(20)), cast(' leading
and trailing ' as char(30)), cast(' leading' as char(40)));
!hdfs dfs -cat
'hdfs://127.0.0.1:8020/user/hive/warehouse/impala_doc_testing.db/char_in_text/*..*';
trailing, leading and trailing, leading

select concat([' ',a,']) as a, concat([' ',b,']) as b, concat([' ',c,']) as c from
char_in_text;
```

a	b	c
[trailing]	[leading and trailing]	[leading

Restrictions:

Because the blank-padding behavior requires allocating the maximum length for each value in memory, for scalability reasons avoid declaring CHAR columns that are much longer than typical values in that column.

All data in CHAR and VARCHAR columns must be in a character encoding that is compatible with UTF-8. If you have binary data from another database system (that is, a BLOB type), use a STRING column to hold it.

When an expression compares a CHAR with a STRING or VARCHAR, the CHAR value is implicitly converted to STRING first, with trailing spaces preserved.

```
select cast("foo " as char(5)) = 'foo' as "char equal to string";
```

char equal to string
false

This behavior differs from other popular database systems. To get the expected result of `TRUE`, cast the expressions on both sides to `CHAR` values of the appropriate length:

```
select cast("foo " as char(5)) = cast('foo' as char(3)) as "char equal to string";
+-----+
| char equal to string |
+-----+
| true                 |
+-----+
```

This behavior is subject to change in future releases.

Related information:

[STRING Data Type](#) on page 151, [VARCHAR Data Type \(CDH 5.2 or higher only\)](#) on page 165, [String Literals](#) on page 196, [Impala String Functions](#) on page 430

DECIMAL Data Type (CDH 5.1 or higher only)

A numeric data type with fixed scale and precision, used in `CREATE TABLE` and `ALTER TABLE` statements. Suitable for financial and other arithmetic calculations where the imprecise representation and rounding behavior of `FLOAT` and `DOUBLE` make those types impractical.

Syntax:

In the column definition of a `CREATE TABLE` statement:

```
column_name DECIMAL[(precision[,scale])]
```

`DECIMAL` with no precision or scale values is equivalent to `DECIMAL(9,0)`.

Precision and Scale:

precision represents the total number of digits that can be represented by the column, regardless of the location of the decimal point. This value must be between 1 and 38. For example, representing integer values up to 9999, and floating-point values up to 99.99, both require a precision of 4. You can also represent corresponding negative values, without any change in the precision. For example, the range -9999 to 9999 still only requires a precision of 4.

scale represents the number of fractional digits. This value must be less than or equal to *precision*. A scale of 0 produces integral values, with no fractional part. If precision and scale are equal, all the digits come after the decimal point, making all the values between 0 and 0.999... or 0 and -0.999...

When *precision* and *scale* are omitted, a `DECIMAL` value is treated as `DECIMAL(9,0)`, that is, an integer value ranging from -999,999,999 to 999,999,999. This is the largest `DECIMAL` value that can still be represented in 4 bytes. If precision is specified but scale is omitted, Impala uses a value of zero for the scale.

Both *precision* and *scale* must be specified as integer literals, not any other kind of constant expressions.

To check the precision or scale for arbitrary values, you can call the [precision\(\)](#) and [scale\(\)](#) built-in functions. For example, you might use these values to figure out how many characters are required for various fields in a report, or to understand the rounding characteristics of a formula as applied to a particular `DECIMAL` column.

Range:

The maximum precision value is 38. Thus, the largest integral value is represented by `DECIMAL(38,0)` (999... with 9 repeated 38 times). The most precise fractional value (between 0 and 1, or 0 and -1) is represented by `DECIMAL(38,38)`, with 38 digits to the right of the decimal point. The value closest to 0 would be .0000...1 (37 zeros and the final 1). The value closest to 1 would be .999... (9 repeated 38 times).

For a given precision and scale, the range of `DECIMAL` values is the same in the positive and negative directions. For example, `DECIMAL(4,2)` can represent from -99.99 to 99.99. This is different from other integral numeric types where the positive and negative bounds differ slightly.

When you use `DECIMAL` values in arithmetic expressions, the precision and scale of the result value are determined as follows:

- For addition and subtraction, the precision and scale are based on the maximum possible result, that is, if all the digits of the input values were 9s and the absolute values were added together.
- For multiplication, the precision is the sum of the precisions of the input values. The scale is the sum of the scales of the input values.
- For division, Impala sets the precision and scale to values large enough to represent the whole and fractional parts of the result.
- For UNION, the scale is the larger of the scales of the input values, and the precision is increased if necessary to accommodate any additional fractional digits. If the same input value has the largest precision and the largest scale, the result value has the same precision and scale. If one value has a larger precision but smaller scale, the scale of the result value is increased. For example, `DECIMAL(20, 2) UNION DECIMAL(8, 6)` produces a result of type `DECIMAL(24, 6)`. The extra 4 fractional digits of scale (6-2) are accommodated by extending the precision by the same amount (20+4).
- To doublecheck, you can always call the `PRECISION()` and `SCALE()` functions on the results of an arithmetic expression to see the relevant values, or use a `CREATE TABLE AS SELECT` statement to define a column based on the return type of the expression.

Compatibility:

- Using the `DECIMAL` type is only supported under CDH 5.1.0 and higher.
- Use the `DECIMAL` data type in Impala for applications where you used the `NUMBER` data type in Oracle. The Impala `DECIMAL` type does not support the Oracle idioms of `*` for scale or negative values for precision.

Conversions and casting:

Casting an integer or floating-point value `N` to `TIMESTAMP` produces a value that is `N` seconds past the start of the epoch date (January 1, 1970). By default, the result value represents a date and time in the UTC time zone. If the setting `--use_local_tz_for_unix_timestamp_conversions=true` is in effect, the resulting `TIMESTAMP` represents a date and time in the local time zone.

Impala automatically converts between `DECIMAL` and other numeric types where possible. A `DECIMAL` with zero scale is converted to or from the smallest appropriate integral type. A `DECIMAL` with a fractional part is automatically converted to or from the smallest appropriate floating-point type. If the destination type does not have sufficient precision or scale to hold all possible values of the source type, Impala raises an error and does not convert the value.

For example, these statements show how expressions of `DECIMAL` and other types are reconciled to the same type in the context of `UNION` queries and `INSERT` statements:

```
[localhost:21000] > select cast(1 as int) as x union select cast(1.5 as decimal(9,4))
as x;
+-----+
| x      |
+-----+
| 1.5000 |
| 1.0000 |
+-----+
[localhost:21000] > create table int_vs_decimal as select cast(1 as int) as x union
select cast(1.5 as decimal(9,4)) as x;
+-----+
| summary          |
+-----+
| Inserted 2 row(s) |
+-----+
[localhost:21000] > desc int_vs_decimal;
+-----+-----+-----+
| name | type          | comment |
+-----+-----+-----+
| x    | decimal(14,4) |         |
+-----+-----+-----+
```


- The result of the `SUM()` aggregate function on `DECIMAL` values is promoted to a precision of 38, with the same precision as the underlying column. Thus, the result can represent the largest possible value at that particular precision.
- `STRING` columns, literals, or expressions can be converted to `DECIMAL` as long as the overall number of digits and digits to the right of the decimal point fit within the specified precision and scale for the declared `DECIMAL` type. By default, a `DECIMAL` value with no specified scale or precision can hold a maximum of 9 digits of an integer value. If there are more digits in the string value than are allowed by the `DECIMAL` scale and precision, the result is `NULL`.

The following examples demonstrate how `STRING` values with integer and fractional parts are represented when converted to `DECIMAL`. If the scale is 0, the number is treated as an integer value with a maximum of *precision* digits. If the precision is greater than 0, the scale must be increased to account for the digits both to the left and right of the decimal point. As the precision increases, output values are printed with additional trailing zeros after the decimal point if needed. Any trailing zeros after the decimal point in the `STRING` value must fit within the number of digits specified by the precision.

```
[localhost:21000] > select cast('100' as decimal); -- Small integer value fits within
9 digits of scale.
+-----+
| cast('100' as decimal(9,0)) |
+-----+
| 100                          |
+-----+
[localhost:21000] > select cast('100' as decimal(3,0)); -- Small integer value fits
within 3 digits of scale.
+-----+
| cast('100' as decimal(3,0)) |
+-----+
| 100                          |
+-----+
[localhost:21000] > select cast('100' as decimal(2,0)); -- 2 digits of scale is not
enough!
+-----+
| cast('100' as decimal(2,0)) |
+-----+
| NULL                          |
+-----+
[localhost:21000] > select cast('100' as decimal(3,1)); -- (3,1) = 2 digits left of the
decimal point, 1 to the right. Not enough.
+-----+
| cast('100' as decimal(3,1)) |
+-----+
| NULL                          |
+-----+
[localhost:21000] > select cast('100' as decimal(4,1)); -- 4 digits total, 1 to the
right of the decimal point.
+-----+
| cast('100' as decimal(4,1)) |
+-----+
| 100.0                          |
+-----+
[localhost:21000] > select cast('98.6' as decimal(3,1)); -- (3,1) can hold a 3 digit
number with 1 fractional digit.
+-----+
| cast('98.6' as decimal(3,1)) |
+-----+
| 98.6                          |
+-----+
[localhost:21000] > select cast('98.6' as decimal(15,1)); -- Larger scale allows bigger
numbers but still only 1 fractional digit.
+-----+
| cast('98.6' as decimal(15,1)) |
+-----+
| 98.6                          |
+-----+
[localhost:21000] > select cast('98.6' as decimal(15,5)); -- Larger precision allows
more fractional digits, outputs trailing zeros.
+-----+
| cast('98.6' as decimal(15,5)) |
```

```

+-----+
| 98.60000 |
+-----+
[localhost:21000] > select cast('98.60000' as decimal(15,1)); -- Trailing zeros in the
string must fit within 'scale' digits (1 in this case).
+-----+
| cast('98.60000' as decimal(15,1)) |
+-----+
| NULL |
+-----+

```

- Most built-in arithmetic functions such as `SIN()` and `COS()` continue to accept only `DOUBLE` values because they are so commonly used in scientific context for calculations of IEEE 754-compliant values. The built-in functions that accept and return `DECIMAL` are:

- `ABS()`
- `CEIL()`
- `COALESCE()`
- `FLOOR()`
- `FNV_HASH()`
- `GREATEST()`
- `IF()`
- `ISNULL()`
- `LEAST()`
- `NEGATIVE()`
- `NULLIF()`
- `POSITIVE()`
- `PRECISION()`
- `ROUND()`
- `SCALE()`
- `TRUNCATE()`
- `ZEROIFNULL()`

See [Impala Built-In Functions](#) on page 373 for details.

- `BIGINT`, `INT`, `SMALLINT`, and `TINYINT` values can all be cast to `DECIMAL`. The number of digits to the left of the decimal point in the `DECIMAL` type must be sufficient to hold the largest value of the corresponding integer type. Note that integer literals are treated as the smallest appropriate integer type, meaning there is sometimes a range of values that require one more digit of `DECIMAL` scale than you might expect. For integer values, the precision of the `DECIMAL` type can be zero; if the precision is greater than zero, remember to increase the scale value by an equivalent amount to hold the required number of digits to the left of the decimal point.

The following examples show how different integer types are converted to `DECIMAL`.

```

[localhost:21000] > select cast(1 as decimal(1,0));
+-----+
| cast(1 as decimal(1,0)) |
+-----+
| 1 |
+-----+
[localhost:21000] > select cast(9 as decimal(1,0));
+-----+
| cast(9 as decimal(1,0)) |
+-----+
| 9 |
+-----+
[localhost:21000] > select cast(10 as decimal(1,0));
+-----+
| cast(10 as decimal(1,0)) |
+-----+
| 10 |
+-----+

```

```

+-----+
[localhost:21000] > select cast(10 as decimal(1,1));
+-----+
| cast(10 as decimal(1,1)) |
+-----+
| 10.0                      |
+-----+
[localhost:21000] > select cast(100 as decimal(1,1));
+-----+
| cast(100 as decimal(1,1)) |
+-----+
| 100.0                     |
+-----+
[localhost:21000] > select cast(1000 as decimal(1,1));
+-----+
| cast(1000 as decimal(1,1)) |
+-----+
| 1000.0                    |
+-----+

```

- When a DECIMAL value is converted to any of the integer types, any fractional part is truncated (that is, rounded towards zero):

```

[localhost:21000] > create table num_dec_days (x decimal(4,1));
[localhost:21000] > insert into num_dec_days values (1), (2), (cast(4.5 as decimal(4,1)));
[localhost:21000] > insert into num_dec_days values (cast(0.1 as decimal(4,1))), (cast(.9
as decimal(4,1))), (cast(9.1 as decimal(4,1))), (cast(9.9 as decimal(4,1)));
[localhost:21000] > select cast(x as int) from num_dec_days;
+-----+
| cast(x as int) |
+-----+
| 1              |
| 2              |
| 4              |
| 0              |
| 0              |
| 9              |
| 9              |
+-----+

```

- You cannot directly cast TIMESTAMP or BOOLEAN values to or from DECIMAL values. You can turn a DECIMAL value into a time-related representation using a two-step process, by converting it to an integer value and then using that result in a call to a date and time function such as from_unixtime().

```

[localhost:21000] > select from_unixtime(cast(cast(1000.0 as decimal) as bigint));
+-----+
| from_unixtime(cast(cast(1000.0 as decimal(9,0)) as bigint)) |
+-----+
| 1970-01-01 00:16:40                                         |
+-----+
[localhost:21000] > select now() + interval cast(x as int) days from num_dec_days; --
x is a DECIMAL column.

[localhost:21000] > create table num_dec_days (x decimal(4,1));
[localhost:21000] > insert into num_dec_days values (1), (2), (cast(4.5 as decimal(4,1)));
[localhost:21000] > select now() + interval cast(x as int) days from num_dec_days; --
The 4.5 value is truncated to 4 and becomes '4 days'.
+-----+
| now() + interval cast(x as int) days |
+-----+
| 2014-05-13 23:11:55.163284000        |
| 2014-05-14 23:11:55.163284000        |
| 2014-05-16 23:11:55.163284000        |
+-----+

```

- Because values in `INSERT` statements are checked rigorously for type compatibility, be prepared to use `CAST()` function calls around literals, column references, or other expressions that you are inserting into a `DECIMAL` column.

NULL considerations: Casting any non-numeric value to this type produces a `NULL` value.

DECIMAL differences from integer and floating-point types:

With the `DECIMAL` type, you are concerned with the number of overall digits of a number rather than powers of 2 (as in `TINYINT`, `SMALLINT`, and so on). Therefore, the limits with integral values of `DECIMAL` types fall around 99, 999, 9999, and so on rather than 32767, 65535, $2^{32}-1$, and so on. For fractional values, you do not need to account for imprecise representation of the fractional part according to the IEEE-954 standard (as in `FLOAT` and `DOUBLE`). Therefore, when you insert a fractional value into a `DECIMAL` column, you can compare, sum, query, `GROUP BY`, and so on that column and get back the original values rather than some “close but not identical” value.

`FLOAT` and `DOUBLE` can cause problems or unexpected behavior due to inability to precisely represent certain fractional values, for example dollar and cents values for currency. You might find output values slightly different than you inserted, equality tests that do not match precisely, or unexpected values for `GROUP BY` columns. `DECIMAL` can help reduce unexpected behavior and rounding errors, at the expense of some performance overhead for assignments and comparisons.

Literals and expressions:

- When you use an integer literal such as 1 or 999 in a SQL statement, depending on the context, Impala will treat it as either the smallest appropriate `DECIMAL` type, or the smallest integer type (`TINYINT`, `SMALLINT`, `INT`, or `BIGINT`). To minimize memory usage, Impala prefers to treat the literal as the smallest appropriate integer type.
- When you use a floating-point literal such as 1.1 or 999.44 in a SQL statement, depending on the context, Impala will treat it as either the smallest appropriate `DECIMAL` type, or the smallest floating-point type (`FLOAT` or `DOUBLE`). To avoid loss of accuracy, Impala prefers to treat the literal as a `DECIMAL`.

Storage considerations:

- Only the precision determines the storage size for `DECIMAL` values; the scale setting has no effect on the storage size.
- Text, RCFile, and SequenceFile tables all use ASCII-based formats. In these text-based file formats, leading zeros are not stored, but trailing zeros are stored. In these tables, each `DECIMAL` value takes up as many bytes as there are digits in the value, plus an extra byte if the decimal point is present and an extra byte for negative values. Once the values are loaded into memory, they are represented in 4, 8, or 16 bytes as described in the following list items. The on-disk representation varies depending on the file format of the table.
- Parquet and Avro tables use binary formats. In these tables, Impala stores each value in as few bytes as possible depending on the precision specified for the `DECIMAL` column.
 - In memory, `DECIMAL` values with precision of 9 or less are stored in 4 bytes.
 - In memory, `DECIMAL` values with precision of 10 through 18 are stored in 8 bytes.
 - In memory, `DECIMAL` values with precision greater than 18 are stored in 16 bytes.

File format considerations:

- The `DECIMAL` data type can be stored in any of the file formats supported by Impala, as described in [How Impala Works with Hadoop File Formats](#) on page 575. Impala only writes to tables that use the Parquet and text formats, so those formats are the focus for file format compatibility.
- Impala can query Avro, RCFile, or SequenceFile tables containing `DECIMAL` columns, created by other Hadoop components, on CDH 5 only.
- You can use `DECIMAL` columns in Impala tables that are mapped to HBase tables. Impala can query and insert into such tables.
- Text, RCFile, and SequenceFile tables all use ASCII-based formats. In these tables, each `DECIMAL` value takes up as many bytes as there are digits in the value, plus an extra byte if the decimal point is present. The binary format of Parquet or Avro files offers more compact storage for `DECIMAL` columns.

- Parquet and Avro tables use binary formats, In these tables, Impala stores each value in 4, 8, or 16 bytes depending on the precision specified for the `DECIMAL` column.

UDF considerations: When writing a C++ UDF, use the `DecimalVal` data type defined in `/usr/include/impala_udf/udf.h`.

Partitioning:

You can use a `DECIMAL` column as a partition key. Doing so provides a better match between the partition key values and the HDFS directory names than using a `DOUBLE` or `FLOAT` partitioning column:

Schema evolution considerations:

- For text-based formats (text, RCFile, and SequenceFile tables), you can issue an `ALTER TABLE ... REPLACE COLUMNS` statement to change the precision and scale of an existing `DECIMAL` column. As long as the values in the column fit within the new precision and scale, they are returned correctly by a query. Any values that do not fit within the new precision and scale are returned as `NULL`, and Impala reports the conversion error. Leading zeros do not count against the precision value, but trailing zeros after the decimal point do.

```
[localhost:21000] > create table text_decimals (x string);
[localhost:21000] > insert into text_decimals values ("1"), ("2"), ("99.99"), ("1.234"),
("000001"), ("1.000000000");
[localhost:21000] > select * from text_decimals;
+-----+
| x      |
+-----+
| 1      |
| 2      |
| 99.99  |
| 1.234  |
| 000001 |
| 1.000000000 |
+-----+
[localhost:21000] > alter table text_decimals replace columns (x decimal(4,2));
[localhost:21000] > select * from text_decimals;
+-----+
| x      |
+-----+
| 1.00   |
| 2.00   |
| 99.99  |
| NULL   |
| 1.00   |
| NULL   |
+-----+
ERRORS:
Backend 0:Error converting column: 0 TO DECIMAL(4, 2) (Data is: 1.234)
file:
hdfs://127.0.0.1:8020/user/hive/warehouse/decimal_testing.db/text_decimals/634d4bd3aa0
e8420-b4b13bab7f1be787_56794587_data.0
record: 1.234
Error converting column: 0 TO DECIMAL(4, 2) (Data is: 1.000000000)
file:
hdfs://127.0.0.1:8020/user/hive/warehouse/decimal_testing.db/text_decimals/cd40dc68e20
c565a-cc4bd86c724c96ba_311873428_data.0
record: 1.000000000
```

- For binary formats (Parquet and Avro tables), although an `ALTER TABLE ... REPLACE COLUMNS` statement that changes the precision or scale of a `DECIMAL` column succeeds, any subsequent attempt to query the changed column results in a fatal error. (The other columns can still be queried successfully.) This is because the metadata about the columns is stored in the data files themselves, and `ALTER TABLE` does not actually make any updates to the data files. If the metadata in the data files disagrees with the metadata in the metastore database, Impala cancels the query.

Examples:

```
CREATE TABLE t1 (x DECIMAL, y DECIMAL(5,2), z DECIMAL(25,0));
INSERT INTO t1 VALUES (5, 99.44, 123456), (300, 6.7, 999999999);
SELECT x+y, ROUND(y,1), z/98.6 FROM t1;
SELECT CAST(1000.5 AS DECIMAL);
```

Restrictions:

Currently, the `COMPUTE STATS` statement under CDH 4 does not store any statistics for `DECIMAL` columns. When Impala runs under CDH 5, which has better support for `DECIMAL` in the metastore database, `COMPUTE STATS` does collect statistics for `DECIMAL` columns and Impala uses the statistics to optimize query performance.

HBase considerations: This data type is fully compatible with HBase tables.

Parquet considerations: This type is fully compatible with Parquet tables.

Text table considerations: Values of this type are potentially larger in text tables than in tables using Parquet or other binary formats.

Column statistics considerations: Because this type has a fixed size, the maximum and average size fields are always filled in for column statistics, even before you run the `COMPUTE STATS` statement.

Related information:

[Numeric Literals](#) on page 195, [TINYINT Data Type](#) on page 164, [SMALLINT Data Type](#) on page 150, [INT Data Type](#) on page 145, [BIGINT Data Type](#) on page 130, [DECIMAL Data Type \(CDH 5.1 or higher only\)](#) on page 135, [Impala Mathematical Functions](#) on page 374 (especially `PRECISION()` and `SCALE()`)

DOUBLE Data Type

A double precision floating-point data type used in `CREATE TABLE` and `ALTER TABLE` statements.

Syntax:

In the column definition of a `CREATE TABLE` statement:

```
column_name DOUBLE
```

Range: 4.94065645841246544e-324d .. 1.79769313486231570e+308, positive or negative

Precision: 15 to 17 significant digits, depending on usage. The number of significant digits does not depend on the position of the decimal point.

Representation: The values are stored in 8 bytes, using [IEEE 754 Double Precision Binary Floating Point](#) format.

Conversions: Impala does not automatically convert `DOUBLE` to any other type. You can use `CAST()` to convert `DOUBLE` values to `FLOAT`, `TINYINT`, `SMALLINT`, `INT`, `BIGINT`, `STRING`, `TIMESTAMP`, or `BOOLEAN`. You can use exponential notation in `DOUBLE` literals or when casting from `STRING`, for example `1.0e6` to represent one million. Casting an integer or floating-point value `N` to `TIMESTAMP` produces a value that is `N` seconds past the start of the epoch date (January 1, 1970). By default, the result value represents a date and time in the UTC time zone. If the setting `--use_local_tz_for_unix_timestamp_conversions=true` is in effect, the resulting `TIMESTAMP` represents a date and time in the local time zone.

Usage notes:

The data type `REAL` is an alias for `DOUBLE`.

Examples:

```
CREATE TABLE t1 (x DOUBLE);
SELECT CAST(1000.5 AS DOUBLE);
```

Partitioning: Because fractional values of this type are not always represented precisely, when this type is used for a partition key column, the underlying HDFS directories might not be named exactly as you expect. Prefer to partition on a `DECIMAL` column instead.

HBase considerations: This data type is fully compatible with HBase tables.

Parquet considerations: This type is fully compatible with Parquet tables.

Text table considerations: Values of this type are potentially larger in text tables than in tables using Parquet or other binary formats.

Internal details: Represented in memory as an 8-byte value.

Column statistics considerations: Because this type has a fixed size, the maximum and average size fields are always filled in for column statistics, even before you run the `COMPUTE STATS` statement.

Restrictions:

Due to the way arithmetic on `FLOAT` and `DOUBLE` columns uses high-performance hardware instructions, and distributed queries can perform these operations in different order for each query, results can vary slightly for aggregate function calls such as `SUM()` and `AVG()` for `FLOAT` and `DOUBLE` columns, particularly on large data sets where millions or billions of values are summed or averaged. For perfect consistency and repeatability, use the `DECIMAL` data type for such operations instead of `FLOAT` or `DOUBLE`.

The inability to exactly represent certain floating-point values means that `DECIMAL` is sometimes a better choice than `DOUBLE` or `FLOAT` when precision is critical, particularly when transferring data from other database systems that use different representations or file formats.

Related information:

[Numeric Literals](#) on page 195, [Impala Mathematical Functions](#) on page 374, [FLOAT Data Type](#) on page 144

FLOAT Data Type

A single precision floating-point data type used in `CREATE TABLE` and `ALTER TABLE` statements.

Syntax:

In the column definition of a `CREATE TABLE` statement:

```
column_name FLOAT
```

Range: 1.40129846432481707e-45 .. 3.40282346638528860e+38, positive or negative

Precision: 6 to 9 significant digits, depending on usage. The number of significant digits does not depend on the position of the decimal point.

Representation: The values are stored in 4 bytes, using [IEEE 754 Single Precision Binary Floating Point](#) format.

Conversions: Impala automatically converts `FLOAT` to more precise `DOUBLE` values, but not the other way around. You can use `CAST()` to convert `FLOAT` values to `TINYINT`, `SMALLINT`, `INT`, `BIGINT`, `STRING`, `TIMESTAMP`, or `BOOLEAN`. You can use exponential notation in `FLOAT` literals or when casting from `STRING`, for example `1.0e6` to represent one million. Casting an integer or floating-point value `N` to `TIMESTAMP` produces a value that is `N` seconds past the start of the epoch date (January 1, 1970). By default, the result value represents a date and time in the UTC time zone. If the setting `--use_local_tz_for_unix_timestamp_conversions=true` is in effect, the resulting `TIMESTAMP` represents a date and time in the local time zone.

Examples:

```
CREATE TABLE t1 (x FLOAT);
SELECT CAST(1000.5 AS FLOAT);
```

Partitioning: Because fractional values of this type are not always represented precisely, when this type is used for a partition key column, the underlying HDFS directories might not be named exactly as you expect. Prefer to partition on a `DECIMAL` column instead.

HBase considerations: This data type is fully compatible with HBase tables.

Parquet considerations: This type is fully compatible with Parquet tables.

Text table considerations: Values of this type are potentially larger in text tables than in tables using Parquet or other binary formats.

Internal details: Represented in memory as a 4-byte value.

Column statistics considerations: Because this type has a fixed size, the maximum and average size fields are always filled in for column statistics, even before you run the `COMPUTE STATS` statement.

Restrictions:

Due to the way arithmetic on `FLOAT` and `DOUBLE` columns uses high-performance hardware instructions, and distributed queries can perform these operations in different order for each query, results can vary slightly for aggregate function calls such as `SUM()` and `AVG()` for `FLOAT` and `DOUBLE` columns, particularly on large data sets where millions or billions of values are summed or averaged. For perfect consistency and repeatability, use the `DECIMAL` data type for such operations instead of `FLOAT` or `DOUBLE`.

The inability to exactly represent certain floating-point values means that `DECIMAL` is sometimes a better choice than `DOUBLE` or `FLOAT` when precision is critical, particularly when transferring data from other database systems that use different representations or file formats.

Related information:

[Numeric Literals](#) on page 195, [Impala Mathematical Functions](#) on page 374, [DOUBLE Data Type](#) on page 143

INT Data Type

A 4-byte integer data type used in `CREATE TABLE` and `ALTER TABLE` statements.

Syntax:

In the column definition of a `CREATE TABLE` statement:

```
column_name INT
```

Range: -2147483648 .. 2147483647. There is no `UNSIGNED` subtype.

Conversions: Impala automatically converts to a larger integer type (`BIGINT`) or a floating-point type (`FLOAT` or `DOUBLE`) automatically. Use `CAST()` to convert to `TINYINT`, `SMALLINT`, `STRING`, or `TIMESTAMP`. Casting an integer or floating-point value `N` to `TIMESTAMP` produces a value that is `N` seconds past the start of the epoch date (January 1, 1970). By default, the result value represents a date and time in the UTC time zone. If the setting `--use_local_tz_for_unix_timestamp_conversions=true` is in effect, the resulting `TIMESTAMP` represents a date and time in the local time zone.

Usage notes:

The data type `INTEGER` is an alias for `INT`.

For a convenient and automated way to check the bounds of the `INT` type, call the functions `MIN_INT()` and `MAX_INT()`.

If an integer value is too large to be represented as a `INT`, use a `BIGINT` instead.

NULL considerations: Casting any non-numeric value to this type produces a `NULL` value.

Examples:

```
CREATE TABLE t1 (x INT);
SELECT CAST(1000 AS INT);
```

Partitioning: Prefer to use this type for a partition key column. Impala can process the numeric type more efficiently than a `STRING` representation of the value.

HBase considerations: This data type is fully compatible with HBase tables.

Parquet considerations:

Text table considerations: Values of this type are potentially larger in text tables than in tables using Parquet or other binary formats.

Internal details: Represented in memory as a 4-byte value.

Added in: Available in all versions of Impala.

Column statistics considerations: Because this type has a fixed size, the maximum and average size fields are always filled in for column statistics, even before you run the `COMPUTE STATS` statement.

Related information:

[Numeric Literals](#) on page 195, [TINYINT Data Type](#) on page 164, [SMALLINT Data Type](#) on page 150, [INT Data Type](#) on page 145, [BIGINT Data Type](#) on page 130, [DECIMAL Data Type \(CDH 5.1 or higher only\)](#) on page 135, [Impala Mathematical Functions](#) on page 374

MAP Complex Type (CDH 5.5 or higher only)

A complex data type representing an arbitrary set of key-value pairs. The key part is a scalar type, while the value part can be a scalar or another complex type (`ARRAY`, `STRUCT`, or `MAP`).

Syntax:

```
column_name MAP < primitive_type, type >
type ::= primitive_type | complex_type
```

Usage notes:

Because complex types are often used in combination, for example an `ARRAY` of `STRUCT` elements, if you are unfamiliar with the Impala complex types, start with [Complex Types \(CDH 5.5 or higher only\)](#) on page 167 for background information and usage examples.

The `MAP` complex data type represents a set of key-value pairs. Each element of the map is indexed by a primitive type such as `BIGINT` or `STRING`, letting you define sequences that are not continuous or categories with arbitrary names. You might find it convenient for modelling data produced in other languages, such as a Python dictionary or Java `HashMap`, where a single scalar value serves as the lookup key.

In a big data context, the keys in a map column might represent a numeric sequence of events during a manufacturing process, or `TIMESTAMP` values corresponding to sensor observations. The map itself is inherently unordered, so you choose whether to make the key values significant (such as a recorded `TIMESTAMP`) or synthetic (such as a random global universal ID).



Note: Behind the scenes, the `MAP` type is implemented in a similar way as the `ARRAY` type. Impala does not enforce any uniqueness constraint on the `KEY` values, and the `KEY` values are processed by looping through the elements of the `MAP` rather than by a constant-time lookup. Therefore, this type is primarily for ease of understanding when importing data and algorithms from non-SQL contexts, rather than optimizing the performance of key lookups.

You can pass a multi-part qualified name to `DESCRIBE` to specify an `ARRAY`, `STRUCT`, or `MAP` column and visualize its structure as if it were a table. For example, if table `T1` contains an `ARRAY` column `A1`, you could issue the statement `DESCRIBE t1.a1`. If table `T1` contained a `STRUCT` column `S1`, and a field `F1` within the `STRUCT` was a `MAP`, you could issue the statement `DESCRIBE t1.s1.f1`. An `ARRAY` is shown as a two-column table, with `ITEM` and `POS` columns. A `STRUCT` is shown as a table with each field representing a column in the table. A `MAP` is shown as a two-column table, with `KEY` and `VALUE` columns.

Added in: CDH 5.5.0 (Impala 2.3.0)

Restrictions:

- Columns with this data type can only be used in tables or partitions with the Parquet file format.

- Columns with this data type cannot be used as partition key columns in a partitioned table.
- The `COMPUTE STATS` statement does not produce any statistics for columns of this data type.
- The maximum length of the column definition for any complex type, including declarations for any nested types, is 4000 characters.
- See [Limitations and Restrictions for Complex Types](#) on page 171 for a full list of limitations and associated guidelines about complex type columns.

Examples:

Note: Many of the complex type examples refer to tables such as `CUSTOMER` and `REGION` adapted from the tables used in the TPC-H benchmark. See [Sample Schema and Data for Experimenting with Impala Complex Types](#) on page 188 for the table definitions.

The following example shows a table with various kinds of `MAP` columns, both at the top level and nested within other complex types. Each row represents information about a specific country, with complex type fields of various levels of nesting to represent different information associated with the country: factual measurements such as area and population, notable people in different categories, geographic features such as cities, points of interest within each city, and mountains with associated facts. Practice the `CREATE TABLE` and query notation for complex type columns using empty tables, until you can visualize a complex data structure and construct corresponding SQL statements reliably.

```
create TABLE map_demo
(
  country_id BIGINT,
  -- Numeric facts about each country, looked up by name.
  -- For example, 'Area':1000, 'Population':999999.
  -- Using a MAP instead of a STRUCT because there could be
  -- a different set of facts for each country.
  metrics MAP <STRING, BIGINT>,
  -- MAP whose value part is an ARRAY.
  -- For example, the key 'Famous Politicians' could represent an array of 10 elements,
  -- while the key 'Famous Actors' could represent an array of 20 elements.
  notables MAP <STRING, ARRAY <STRING>>,
  -- MAP that is a field within a STRUCT.
  -- (The STRUCT is inside another ARRAY, because it is rare
  -- for a STRUCT to be a top-level column.)
  -- For example, city #1 might have points of interest with key 'Zoo',
  -- representing an array of 3 different zoos.
  -- City #2 might have completely different kinds of points of interest.
  -- Because the set of field names is potentially large, and most entries could be blank,
  -- a MAP makes more sense than a STRUCT to represent such a sparse data structure.
  cities ARRAY < STRUCT <
    name: STRING,
    points_of_interest: MAP <STRING, ARRAY <STRING>>
  >>,
  -- MAP that is an element within an ARRAY. The MAP is inside a STRUCT field to associate
  -- the mountain name with all the facts about the mountain.
  -- The "key" of the map (the first STRING field) represents the name of some fact whose
  -- value
  -- can be expressed as an integer, such as 'Height', 'Year First Climbed', and so on.
  mountains ARRAY < STRUCT < name: STRING, facts: MAP <STRING, INT > > >
)
STORED AS PARQUET;
```

```
DESCRIBE map_demo;
```

```
+-----+-----+
| name      | type                                     |
+-----+-----+
```

country_id	bigint
metrics	map<string, bigint>
notables	map<string, array<string>>
cities	array<struct< name:string, points_of_interest:map<string, array<string>> >>
mountains	array<struct< name:string, facts:map<string, int> >>

```
DESCRIBE map_demo.metrics;
```

name	type
key	string
value	bigint

```
DESCRIBE map_demo.notables;
```

name	type
key	string
value	array<string>

```
DESCRIBE map_demo.notables.value;
```

name	type
item	string
pos	bigint

```
DESCRIBE map_demo.cities;
```

name	type
item	struct< name:string, points_of_interest:map<string, array<string>> >
pos	bigint

```
DESCRIBE map_demo.cities.item.points_of_interest;
```

name	type
key	string
value	array<string>

```
DESCRIBE map_demo.cities.item.points_of_interest.value;
```

name	type
item	string
pos	bigint

```
DESCRIBE map_demo.mountains;
```

name	type
item	struct< name:string, facts:map<string, int> >
pos	bigint

```

+-----+-----+
DESCRIBE map_demo.mountains.item.facts;
+-----+-----+
| name | type |
+-----+-----+
| key  | string |
| value | int |
+-----+-----+

```

The following example shows a table that uses a variety of data types for the MAP “key” field. Typically, you use BIGINT or STRING to use numeric or character-based keys without worrying about exceeding any size or length constraints.

```

CREATE TABLE map_demo_obscura
(
  id BIGINT,
  m1 MAP <INT, INT>,
  m2 MAP <SMALLINT, INT>,
  m3 MAP <TINYINT, INT>,
  m4 MAP <TIMESTAMP, INT>,
  m5 MAP <BOOLEAN, INT>,
  m6 MAP <CHAR(5), INT>,
  m7 MAP <VARCHAR(25), INT>,
  m8 MAP <FLOAT, INT>,
  m9 MAP <DOUBLE, INT>,
  m10 MAP <DECIMAL(12,2), INT>
)
STORED AS PARQUET;

```

```

CREATE TABLE celebrities (name STRING, birth_year MAP < STRING, SMALLINT >) STORED AS
PARQUET;
-- A typical row might represent values with 2 different birth years, such as:
-- ("Joe Movie Star", { "real": 1972, "claimed": 1977 })

CREATE TABLE countries (name STRING, famous_leaders MAP < INT, STRING >) STORED AS
PARQUET;
-- A typical row might represent values with different leaders, with key values
-- corresponding to their numeric sequence, such as:
-- ("United States", { 1: "George Washington", 3: "Thomas Jefferson", 16: "Abraham
Lincoln" })

CREATE TABLE airlines (name STRING, special_meals MAP < STRING, MAP < STRING, STRING >
>) STORED AS PARQUET;
-- A typical row might represent values with multiple kinds of meals, each with several
-- components:
-- ("Elegant Airlines",
--  {
--    "vegetarian": { "breakfast": "pancakes", "snack": "cookies", "dinner": "rice
pilaf" },
--    "gluten free": { "breakfast": "oatmeal", "snack": "fruit", "dinner": "chicken"
--  }
-- )

```

Related information:

[Complex Types \(CDH 5.5 or higher only\)](#) on page 167, [ARRAY Complex Type \(CDH 5.5 or higher only\)](#) on page 127, [STRUCT Complex Type \(CDH 5.5 or higher only\)](#) on page 153

REAL Data Type

An alias for the DOUBLE data type. See [DOUBLE Data Type](#) on page 143 for details.

Examples:

These examples show how you can use the type names `REAL` and `DOUBLE` interchangeably, and behind the scenes Impala treats them always as `DOUBLE`.

```
[localhost:21000] > create table r1 (x real);
[localhost:21000] > describe r1;
+-----+-----+-----+
| name | type   | comment |
+-----+-----+-----+
| x    | double |          |
+-----+-----+-----+
[localhost:21000] > insert into r1 values (1.5), (cast (2.2 as double));
[localhost:21000] > select cast (1e6 as real);
+-----+-----+
| cast(1000000.0 as double) |
+-----+-----+
| 1000000                   |
+-----+-----+
```

SMALLINT Data Type

A 2-byte integer data type used in `CREATE TABLE` and `ALTER TABLE` statements.

Syntax:

In the column definition of a `CREATE TABLE` statement:

```
column_name SMALLINT
```

Range: -32768 .. 32767. There is no `UNSIGNED` subtype.

Conversions: Impala automatically converts to a larger integer type (`INT` or `BIGINT`) or a floating-point type (`FLOAT` or `DOUBLE`) automatically. Use `CAST()` to convert to `TINYINT`, `STRING`, or `TIMESTAMP`. Casting an integer or floating-point value `N` to `TIMESTAMP` produces a value that is `N` seconds past the start of the epoch date (January 1, 1970). By default, the result value represents a date and time in the UTC time zone. If the setting `--use_local_tz_for_unix_timestamp_conversions=true` is in effect, the resulting `TIMESTAMP` represents a date and time in the local time zone.

Usage notes:

For a convenient and automated way to check the bounds of the `SMALLINT` type, call the functions `MIN_SMALLINT()` and `MAX_SMALLINT()`.

If an integer value is too large to be represented as a `SMALLINT`, use an `INT` instead.

NULL considerations: Casting any non-numeric value to this type produces a `NULL` value.

Examples:

```
CREATE TABLE t1 (x SMALLINT);
SELECT CAST(1000 AS SMALLINT);
```

Parquet considerations:

Physically, Parquet files represent `TINYINT` and `SMALLINT` values as 32-bit integers. Although Impala rejects attempts to insert out-of-range values into such columns, if you create a new table with the `CREATE TABLE ... LIKE PARQUET` syntax, any `TINYINT` or `SMALLINT` columns in the original table turn into `INT` columns in the new table.

Partitioning: Prefer to use this type for a partition key column. Impala can process the numeric type more efficiently than a `STRING` representation of the value.

HBase considerations: This data type is fully compatible with HBase tables.

Text table considerations: Values of this type are potentially larger in text tables than in tables using Parquet or other binary formats.

Internal details: Represented in memory as a 2-byte value.

Added in: Available in all versions of Impala.

Column statistics considerations: Because this type has a fixed size, the maximum and average size fields are always filled in for column statistics, even before you run the `COMPUTE STATS` statement.

Related information:

[Numeric Literals](#) on page 195, [TINYINT Data Type](#) on page 164, [SMALLINT Data Type](#) on page 150, [INT Data Type](#) on page 145, [BIGINT Data Type](#) on page 130, [DECIMAL Data Type \(CDH 5.1 or higher only\)](#) on page 135, [Impala Mathematical Functions](#) on page 374

STRING Data Type

A data type used in `CREATE TABLE` and `ALTER TABLE` statements.

Syntax:

In the column definition of a `CREATE TABLE` and `ALTER TABLE` statements:

```
column_name STRING
```

Length:

If you need to manipulate string values with precise or maximum lengths, in Impala 2.0 and higher you can declare columns as `VARCHAR(max_length)` or `CHAR(length)`, but for best performance use `STRING` where practical.

Take the following considerations for `STRING` lengths:

- The hard limit on the size of a `STRING` and the total size of a row is 2 GB.
 - If a query tries to process or create a string larger than this limit, it will return an error to the user.
- The limit is 1 GB on `STRING` when writing to Parquet files.
- Queries operating on strings with 32 KB or less will work reliably and will not hit significant performance or memory problems (unless you have very complex queries, very many columns, etc.)
- Performance and memory consumption may degrade with strings larger than 32 KB.
- The row size, i.e. the total size of all string and other columns, is subject to lower limits at various points in query execution that support spill-to-disk. A few examples for lower row size limits are:
 - Rows coming from the right side of any hash join
 - Rows coming from either side of a hash join that spills to disk
 - Rows being sorted by the `SORT` operator without a limit
 - Rows in a grouping aggregation

In and lower, the default limit of the row size in the above cases is 8 MB.

In and higher, the max row size is configurable on a per-query basis with the `MAX_ROW_SIZE` query option. Rows up to `MAX_ROW_SIZE` (which defaults to 512 KB) can always be processed in the above cases. Rows larger than `MAX_ROW_SIZE` are processed on a best-effort basis. See `MAX_ROW_SIZE` for more details.

Character sets:

For full support in all Impala subsystems, restrict string values to the ASCII character set. Although some UTF-8 character data can be stored in Impala and retrieved through queries, UTF-8 strings containing non-ASCII characters are not guaranteed to work properly in combination with many SQL aspects, including but not limited to:

- String manipulation functions.
- Comparison operators.
- The `ORDER BY` clause.
- Values in partition key columns.

For any national language aspects such as collation order or interpreting extended ASCII variants such as ISO-8859-1 or ISO-8859-2 encodings, Impala does not include such metadata with the table definition. If you need to sort, manipulate, or display data depending on those national language characteristics of string data, use logic on the application side.

Conversions:

- Impala does not automatically convert `STRING` to any numeric type. Impala does automatically convert `STRING` to `TIMESTAMP` if the value matches one of the accepted `TIMESTAMP` formats; see [TIMESTAMP Data Type](#) on page 158 for details.
- You can use `CAST()` to convert `STRING` values to `TINYINT`, `SMALLINT`, `INT`, `BIGINT`, `FLOAT`, `DOUBLE`, or `TIMESTAMP`.
- You cannot directly cast a `STRING` value to `BOOLEAN`. You can use a `CASE` expression to evaluate string values such as `'T'`, `'true'`, and so on and return Boolean `true` and `false` values as appropriate.
- You can cast a `BOOLEAN` value to `STRING`, returning `'1'` for `true` values and `'0'` for `false` values.

Partitioning:

Although it might be convenient to use `STRING` columns for partition keys, even when those columns contain numbers, for performance and scalability it is much better to use numeric columns as partition keys whenever practical. Although the underlying HDFS directory name might be the same in either case, the in-memory storage for the partition key columns is more compact, and computations are faster, if partition key columns such as `YEAR`, `MONTH`, `DAY` and so on are declared as `INT`, `SMALLINT`, and so on.

Zero-length strings: For purposes of clauses such as `DISTINCT` and `GROUP BY`, Impala considers zero-length strings (`" "`), `NULL`, and space to all be different values.

Text table considerations: Values of this type are potentially larger in text tables than in tables using Parquet or other binary formats.

Avro considerations:

The Avro specification allows string values up to 2^{64} bytes in length. Impala queries for Avro tables use 32-bit integers to hold string lengths. In CDH 5.7 / Impala 2.5 and higher, Impala truncates `CHAR` and `VARCHAR` values in Avro tables to $(2^{31})-1$ bytes. If a query encounters a `STRING` value longer than $(2^{31})-1$ bytes in an Avro table, the query fails. In earlier releases, encountering such long values in an Avro table could cause a crash.

Column statistics considerations: Because the values of this type have variable size, none of the column statistics fields are filled in until you run the `COMPUTE STATS` statement.

Examples:

The following examples demonstrate double-quoted and single-quoted string literals, and required escaping for quotation marks within string literals:

```
SELECT 'I am a single-quoted string';
SELECT "I am a double-quoted string";
SELECT 'I\'m a single-quoted string with an apostrophe';
SELECT "I\'m a double-quoted string with an apostrophe";
SELECT 'I am a "short" single-quoted string containing quotes';
SELECT "I am a \"short\" double-quoted string containing quotes";
```

The following examples demonstrate calls to string manipulation functions to concatenate strings, convert numbers to strings, or pull out substrings:

```
SELECT CONCAT("Once upon a time, there were ", CAST(3 AS STRING), ' little pigs.');
```

```
SELECT SUBSTR("hello world",7,5);
```


The following examples show how to perform operations on `STRING` columns within a table:

```
CREATE TABLE t1 (s1 STRING, s2 STRING);
INSERT INTO t1 VALUES ("hello", 'world'), (CAST(7 AS STRING), "wonders");
SELECT s1, s2, length(s1) FROM t1 WHERE s2 LIKE 'w%';
```

Related information:

[String Literals](#) on page 196, [CHAR Data Type \(CDH 5.2 or higher only\)](#) on page 132, [VARCHAR Data Type \(CDH 5.2 or higher only\)](#) on page 165, [Impala String Functions](#) on page 430, [Impala Date and Time Functions](#) on page 398

STRUCT Complex Type (CDH 5.5 or higher only)

A complex data type, representing multiple fields of a single item. Frequently used as the element type of an `ARRAY` or the `VALUE` part of a `MAP`.

Syntax:

```
column_name STRUCT < name : type [COMMENT 'comment_string'], ... >
type ::= primitive_type | complex_type
```

The names and number of fields within the `STRUCT` are fixed. Each field can be a different type. A field within a `STRUCT` can also be another `STRUCT`, or an `ARRAY` or a `MAP`, allowing you to create nested data structures with a maximum nesting depth of 100.

A `STRUCT` can be the top-level type for a column, or can itself be an item within an `ARRAY` or the value part of the key-value pair in a `MAP`.

When a `STRUCT` is used as an `ARRAY` element or a `MAP` value, you use a join clause to bring the `ARRAY` or `MAP` elements into the result set, and then refer to `array_name.ITEM.field` or `map_name.VALUE.field`. In the case of a `STRUCT` directly inside an `ARRAY` or `MAP`, you can omit the `.ITEM` and `.VALUE` pseudocolumns and refer directly to `array_name.field` or `map_name.field`.

Usage notes:

Because complex types are often used in combination, for example an `ARRAY` of `STRUCT` elements, if you are unfamiliar with the Impala complex types, start with [Complex Types \(CDH 5.5 or higher only\)](#) on page 167 for background information and usage examples.

A `STRUCT` is similar conceptually to a table row: it contains a fixed number of named fields, each with a predefined type. To combine two related tables, while using complex types to minimize repetition, the typical way to represent that data is as an `ARRAY` of `STRUCT` elements.

Because a `STRUCT` has a fixed number of named fields, it typically does not make sense to have a `STRUCT` as the type of a table column. In such a case, you could just make each field of the `STRUCT` into a separate column of the table. The `STRUCT` type is most useful as an item of an `ARRAY` or the value part of the key-value pair in a `MAP`. A nested type column with a `STRUCT` at the lowest level lets you associate a variable number of row-like objects with each row of the table.

The `STRUCT` type is straightforward to reference within a query. You do not need to include the `STRUCT` column in a join clause or give it a table alias, as is required for the `ARRAY` and `MAP` types. You refer to the individual fields using dot notation, such as `struct_column_name.field_name`, without any pseudocolumn such as `ITEM` or `VALUE`.

You can pass a multi-part qualified name to `DESCRIBE` to specify an `ARRAY`, `STRUCT`, or `MAP` column and visualize its structure as if it were a table. For example, if table `T1` contains an `ARRAY` column `A1`, you could issue the statement `DESCRIBE t1.a1`. If table `T1` contained a `STRUCT` column `S1`, and a field `F1` within the `STRUCT` was a `MAP`, you could issue the statement `DESCRIBE t1.s1.f1`. An `ARRAY` is shown as a two-column table, with `ITEM` and `POS` columns. A `STRUCT` is shown as a table with each field representing a column in the table. A `MAP` is shown as a two-column table, with `KEY` and `VALUE` columns.

Internal details:

Within the Parquet data file, the values for each `STRUCT` field are stored adjacent to each other, so that they can be encoded and compressed using all the Parquet techniques for storing sets of similar or repeated values. The adjacency applies even when the `STRUCT` values are part of an `ARRAY` or `MAP`. During a query, Impala avoids unnecessary I/O by reading only the portions of the Parquet data file containing the requested `STRUCT` fields.

Added in: CDH 5.5.0 (Impala 2.3.0)

Restrictions:

- Columns with this data type can only be used in tables or partitions with the Parquet file format.
- Columns with this data type cannot be used as partition key columns in a partitioned table.
- The `COMPUTE STATS` statement does not produce any statistics for columns of this data type.
- The maximum length of the column definition for any complex type, including declarations for any nested types, is 4000 characters.
- See [Limitations and Restrictions for Complex Types](#) on page 171 for a full list of limitations and associated guidelines about complex type columns.

Examples:



Note: Many of the complex type examples refer to tables such as `CUSTOMER` and `REGION` adapted from the tables used in the TPC-H benchmark. See [Sample Schema and Data for Experimenting with Impala Complex Types](#) on page 188 for the table definitions.

The following example shows a table with various kinds of `STRUCT` columns, both at the top level and nested within other complex types. Practice the `CREATE TABLE` and query notation for complex type columns using empty tables, until you can visualize a complex data structure and construct corresponding SQL statements reliably.

```
CREATE TABLE struct_demo
(
  id BIGINT,
  name STRING,
  -- A STRUCT as a top-level column. Demonstrates how the table ID column
  -- and the ID field within the STRUCT can coexist without a name conflict.
  employee_info STRUCT < employer: STRING, id: BIGINT, address: STRING >,
  -- A STRUCT as the element type of an ARRAY.
  places_lived ARRAY < STRUCT <street: STRING, city: STRING, country: STRING >>,
  -- A STRUCT as the value portion of the key-value pairs in a MAP.
  memorable_moments MAP < STRING, STRUCT < year: INT, place: STRING, details: STRING
  >>,
  -- A STRUCT where one of the fields is another STRUCT.
  current_address STRUCT < street_address: STRUCT <street_number: INT, street_name:
  STRING, street_type: STRING>, country: STRING, postal_code: STRING >
)
STORED AS PARQUET;
```

The following example shows how to examine the structure of a table containing one or more `STRUCT` columns by using the `DESCRIBE` statement. You can visualize each `STRUCT` as its own table, with columns named the same as each field of the `STRUCT`. If the `STRUCT` is nested inside another complex type, such as `ARRAY`, you can extend the qualified name passed to `DESCRIBE` until the output shows just the `STRUCT` fields.

```
DESCRIBE struct_demo;
+-----+-----+
| name          | type          |
+-----+-----+
| id            | bigint       |
| name         | string       |
```

employee_info	struct< employer:string, id:bigint, address:string >
places_lived	array<struct< street:string, city:string, country:string >>
memorable_moments	map<string,struct< year:int, place:string, details:string >>
current_address	struct< street_address:struct< street_number:int, street_name:string, street_type:string >, country:string, postal_code:string >

The top-level column `EMPLOYEE_INFO` is a `STRUCT`. Describing `table_name.struct_name` displays the fields of the `STRUCT` as if they were columns of a table:

```
DESCRIBE struct_demo.employee_info;
```

name	type
employer	string
id	bigint
address	string

Because `PLACES_LIVED` is a `STRUCT` inside an `ARRAY`, the initial `DESCRIBE` shows the structure of the `ARRAY`:

```
DESCRIBE struct_demo.places_lived;
```

name	type
item	struct< street:string, city:string, country:string >
pos	bigint

Ask for the details of the `ITEM` field of the `ARRAY` to see just the layout of the `STRUCT`:

```
DESCRIBE struct_demo.places_lived.item;
```

name	type
street	string
city	string
country	string

Likewise, MEMORABLE_MOMENTS has a STRUCT inside a MAP, which requires an extra level of qualified name to see just the STRUCT part:

```
DESCRIBE struct_demo.memorable_moments;
+-----+-----+
| name | type |
+-----+-----+
| key  | string |
| value| struct< |
|      |   year:int, |
|      |   place:string, |
|      |   details:string |
|      | > |
+-----+-----+
```

For a MAP, ask to see the VALUE field to see the corresponding STRUCT fields in a table-like structure:

```
DESCRIBE struct_demo.memorable_moments.value;
+-----+-----+
| name | type |
+-----+-----+
| year | int |
| place | string |
| details | string |
+-----+-----+
```

For a STRUCT inside a STRUCT, we can see the fields of the outer STRUCT:

```
DESCRIBE struct_demo.current_address;
+-----+-----+
| name | type |
+-----+-----+
| street_address | struct< |
|                 |   street_number:int, |
|                 |   street_name:string, |
|                 |   street_type:string |
|                 | > |
| country | string |
| postal_code | string |
+-----+-----+
```

Then we can use a further qualified name to see just the fields of the inner STRUCT:

```
DESCRIBE struct_demo.current_address.street_address;
+-----+-----+
| name | type |
+-----+-----+
| street_number | int |
| street_name | string |
| street_type | string |
+-----+-----+
```

The following example shows how to examine the structure of a table containing one or more STRUCT columns by using the DESCRIBE statement. You can visualize each STRUCT as its own table, with columns named the same as each field of the STRUCT. If the STRUCT is nested inside another complex type, such as ARRAY, you can extend the qualified name passed to DESCRIBE until the output shows just the STRUCT fields.

```
DESCRIBE struct_demo;
+-----+-----+-----+
| name | type | comment |
+-----+-----+-----+
| id | bigint | |
| name | string | |
| employee_info | struct< | |
+-----+-----+-----+
```

	<pre> employer:string, id:bigint, address:string > </pre>	
places_lived	<pre> array<struct< street:string, city:string, country:string >> </pre>	
memorable_moments	<pre> map<string,struct< year:int, place:string, details:string >> </pre>	
current_address	<pre> struct< street_address:struct< street_number:int, street_name:string, street_type:string >, country:string, postal_code:string > </pre>	

```
SELECT id, employee_info.id FROM struct_demo;
```

```
SELECT id, employee_info.id AS employee_id FROM struct_demo;
```

```
SELECT id, employee_info.id AS employee_id, employee_info.employer
FROM struct_demo;
```

```
SELECT id, name, street, city, country
FROM struct_demo, struct_demo.places_lived;
```

```
SELECT id, name, places_lived.pos, places_lived.street, places_lived.city,
places_lived.country
FROM struct_demo, struct_demo.places_lived;
```

```
SELECT id, name, pl.pos, pl.street, pl.city, pl.country
FROM struct_demo, struct_demo.places_lived AS pl;
```

```
SELECT id, name, places_lived.pos, places_lived.street, places_lived.city,
places_lived.country
FROM struct_demo, struct_demo.places_lived;
```

```
SELECT id, name, pos, street, city, country
FROM struct_demo, struct_demo.places_lived;
```

```
SELECT id, name, memorable_moments.key,
memorable_moments.value.year,
memorable_moments.value.place,
memorable_moments.value.details
FROM struct_demo, struct_demo.memorable_moments
WHERE memorable_moments.key IN ('Birthday', 'Anniversary', 'Graduation');
```

```
SELECT id, name, mm.key, mm.value.year, mm.value.place, mm.value.details
FROM struct_demo, struct_demo.memorable_moments AS mm
WHERE mm.key IN ('Birthday', 'Anniversary', 'Graduation');
```

```
SELECT id, name, memorable_moments.key, memorable_moments.value.year,
memorable_moments.value.place, memorable_moments.value.details
FROM struct_demo, struct_demo.memorable_moments
WHERE key IN ('Birthday', 'Anniversary', 'Graduation');
```

```
SELECT id, name, key, value.year, value.place, value.details
FROM struct_demo, struct_demo.memorable_moments
WHERE key IN ('Birthday', 'Anniversary', 'Graduation');
```

```
SELECT id, name, key, year, place, details
FROM struct_demo, struct_demo.memorable_moments
WHERE key IN ('Birthday', 'Anniversary', 'Graduation');
```

```
SELECT id, name,
       current_address.street_address.street_number,
       current_address.street_address.street_name,
       current_address.street_address.street_type,
       current_address.country,
       current_address.postal_code
FROM struct_demo;
```

For example, this table uses a struct that encodes several data values for each phone number associated with a person. Each person can have a variable-length array of associated phone numbers, and queries can refer to the category field to locate specific home, work, mobile, and so on kinds of phone numbers.

```
CREATE TABLE contact_info_many_structs
(
  id BIGINT, name STRING,
  phone_numbers ARRAY < STRUCT <category:STRING, country_code:STRING, area_code:SMALLINT,
  full_number:STRING, mobile:BOOLEAN, carrier:STRING > >
) STORED AS PARQUET;
```

Because structs are naturally suited to composite values where the fields have different data types, you might use them to decompose things such as addresses:

```
CREATE TABLE contact_info_detailed_address
(
  id BIGINT, name STRING,
  address STRUCT < house_number:INT, street:STRING, street_type:STRING, apartment:STRING,
  city:STRING, region:STRING, country:STRING >
);
```

In a big data context, splitting out data fields such as the number part of the address and the street name could let you do analysis on each field independently. For example, which streets have the largest number range of addresses, what are the statistical properties of the street names, which areas have a higher proportion of “Roads”, “Courts” or “Boulevards”, and so on.

Related information:

[Complex Types \(CDH 5.5 or higher only\)](#) on page 167, [ARRAY Complex Type \(CDH 5.5 or higher only\)](#) on page 127, [MAP Complex Type \(CDH 5.5 or higher only\)](#) on page 146

TIMESTAMP Data Type

A data type used in `CREATE TABLE` and `ALTER TABLE` statements, representing a point in time.

Syntax:

In the column definition of a `CREATE TABLE` statement:

```
column_name TIMESTAMP
```

Range: Allowed date values range from 1400-01-01 to 9999-12-31; this range is different from the Hive `TIMESTAMP` type. Internally, the resolution of the time portion of a `TIMESTAMP` value is in nanoseconds.

INTERVAL expressions:

You can perform date arithmetic by adding or subtracting a specified number of time units, using the `INTERVAL` keyword and the `+` and `-` operators or `date_add()` and `date_sub()` functions. You can specify units as `YEAR[S]`, `MONTH[S]`, `WEEK[S]`, `DAY[S]`, `HOURL[S]`, `MINUTE[S]`, `SECOND[S]`, `MILLISECOND[S]`, `MICROSECOND[S]`, and `NANOSECOND[S]`. You can only specify one time unit in each interval expression, for example `INTERVAL 3 DAYS` or `INTERVAL 25 HOURS`, but you can produce any granularity by adding together successive `INTERVAL` values, such as `timestamp_value + INTERVAL 3 WEEKS - INTERVAL 1 DAY + INTERVAL 10 MICROSECONDS`.

For example:

```
select now() + interval 1 day;
select date_sub(now(), interval 5 minutes);
insert into auction_details
  select auction_id, auction_start_time, auction_start_time + interval 2 days + interval
  12 hours
  from new_auctions;
```

Time zones:

By default, Impala does not store timestamps using the local timezone, to avoid undesired results from unexpected time zone issues. Timestamps are stored and interpreted relative to UTC, both when written to or read from data files, or when converted to or from Unix time values through functions such as `from_unixtime()` or `unix_timestamp()`. To convert such a `TIMESTAMP` value to one that represents the date and time in a specific time zone, convert the original value with the `from_utc_timestamp()` function.

Because Impala does not assume that `TIMESTAMP` values are in any particular time zone, you must be conscious of the time zone aspects of data that you query, insert, or convert.

For consistency with Unix system calls, the `TIMESTAMP` returned by the `now()` function represents the local time in the system time zone, rather than in UTC. To store values relative to the current time in a portable way, convert any `now()` return values using the `to_utc_timestamp()` function first. For example, the following example shows that the current time in California (where this Impala cluster is located) is shortly after 2 PM. If that value was written to a data file, and shipped off to a distant server to be analyzed alongside other data from far-flung locations, the dates and times would not match up precisely because of time zone differences. Therefore, the `to_utc_timestamp()` function converts it using a common reference point, the UTC time zone (descended from the old Greenwich Mean Time standard). The `'PDT'` argument indicates that the original value is from the Pacific time zone with Daylight Saving Time in effect. When servers in all geographic locations run the same transformation on any local date and time values (with the appropriate time zone argument), the stored data uses a consistent representation. Impala queries can use functions such as `EXTRACT()`, `MIN()`, `AVG()`, and so on to do time-series analysis on those timestamps.

```
[localhost:21000] > select now();
+-----+
| now() |
+-----+
| 2015-04-09 14:07:46.580465000 |
+-----+
[localhost:21000] > select to_utc_timestamp(now(), 'PDT');
+-----+
| to_utc_timestamp(now(), 'pdt') |
+-----+
| 2015-04-09 21:08:07.664547000 |
+-----+
```

The converse function, `from_utc_timestamp()`, lets you take stored `TIMESTAMP` data or calculated results and convert back to local date and time for processing on the application side. The following example shows how you might represent some future date (such as the ending date and time of an auction) in UTC, and then convert back to local time when convenient for reporting or other processing. The final query in the example tests whether this arbitrary UTC date and time has passed yet, by converting it back to the local time zone and comparing it against the current date and time.

```
[localhost:21000] > select to_utc_timestamp(now() + interval 2 weeks, 'PDT');
+-----+
| to_utc_timestamp(now() + interval 2 weeks, 'pdt') |
+-----+
| 2015-04-23 21:08:34.152923000 |
+-----+
[localhost:21000] > select from_utc_timestamp('2015-04-23 21:08:34.152923000', 'PDT');
+-----+
| from_utc_timestamp('2015-04-23 21:08:34.152923000', 'pdt') |
+-----+
| 2015-04-23 14:08:34.152923000 |
+-----+
[localhost:21000] > select from_utc_timestamp('2015-04-23 21:08:34.152923000', 'PDT') <
```

```

now();
+-----+
| from_utc_timestamp('2015-04-23 21:08:34.152923000', 'pdt') < now() |
+-----+
| false |
+-----+

```

If you have data files written by Hive, those `TIMESTAMP` values represent the local timezone of the host where the data was written, potentially leading to inconsistent results when processed by Impala. To avoid compatibility problems or having to code workarounds, you can specify one or both of these `impalad` startup flags:

```
--use_local_tz_for_unix_timestamp_conversions=true
```

```
-convert_legacy_hive_parquet_utc_timestamps=true. Although
```

`-convert_legacy_hive_parquet_utc_timestamps` is turned off by default to avoid performance overhead, Cloudera recommends turning it on when processing `TIMESTAMP` columns in Parquet files written by Hive, to avoid unexpected behavior.

The `--use_local_tz_for_unix_timestamp_conversions` setting affects conversions from `TIMESTAMP` to `BIGINT`, or from `BIGINT` to `TIMESTAMP`. By default, Impala treats all `TIMESTAMP` values as UTC, to simplify analysis of time-series data from different geographic regions. When you enable the

`--use_local_tz_for_unix_timestamp_conversions` setting, these operations treat the input values as if they are in the local time zone of the host doing the processing. See [Impala Date and Time Functions](#) on page 398 for the list of functions affected by the `--use_local_tz_for_unix_timestamp_conversions` setting.

The following sequence of examples shows how the interpretation of `TIMESTAMP` values in Parquet tables is affected by the setting of the `-convert_legacy_hive_parquet_utc_timestamps` setting.

Regardless of the `-convert_legacy_hive_parquet_utc_timestamps` setting, `TIMESTAMP` columns in text tables can be written and read interchangeably by Impala and Hive:

Impala DDL and queries for text table:

```

[localhost:21000] > create table t1 (x timestamp);
[localhost:21000] > insert into t1 values (now()), (now() + interval 1 day);
[localhost:21000] > select x from t1;
+-----+
| x |
+-----+
| 2015-04-07 15:43:02.892403000 |
| 2015-04-08 15:43:02.892403000 |
+-----+
[localhost:21000] > select to_utc_timestamp(x, 'PDT') from t1;
+-----+
| to_utc_timestamp(x, 'pdt') |
+-----+
| 2015-04-07 22:43:02.892403000 |
| 2015-04-08 22:43:02.892403000 |
+-----+

```

Hive query for text table:

```

hive> select * from t1;
OK
2015-04-07 15:43:02.892403
2015-04-08 15:43:02.892403
Time taken: 1.245 seconds, Fetched: 2 row(s)

```

When the table uses Parquet format, Impala expects any time zone adjustment to be applied prior to writing, while `TIMESTAMP` values written by Hive are adjusted to be in the UTC time zone. When Hive queries Parquet data files that it wrote, it adjusts the `TIMESTAMP` values back to the local time zone, while Impala does no conversion. Hive does no time zone conversion when it queries Impala-written Parquet files.

Impala DDL and queries for Parquet table:

```

[localhost:21000] > create table p1 stored as parquet as select x from t1;
+-----+
| summary |
+-----+

```



```

+-----+
| Inserted 2 row(s) |
+-----+
[localhost:21000] > select x from pl;
+-----+
| x |
+-----+
| 2015-04-07 15:43:02.892403000 |
| 2015-04-08 15:43:02.892403000 |
+-----+

```

Hive DDL and queries for Parquet table:

```

hive> create table h1 (x timestamp) stored as parquet;
OK
hive> insert into h1 select * from pl;
...
OK
Time taken: 35.573 seconds
hive> select x from pl;
OK
2015-04-07 15:43:02.892403
2015-04-08 15:43:02.892403
Time taken: 0.324 seconds, Fetched: 2 row(s)
hive> select x from h1;
OK
2015-04-07 15:43:02.892403
2015-04-08 15:43:02.892403
Time taken: 0.197 seconds, Fetched: 2 row(s)

```

The discrepancy arises when Impala queries the Hive-created Parquet table. The underlying values in the `TIMESTAMP` column are different from the ones written by Impala, even though they were copied from one table to another by an `INSERT ... SELECT` statement in Hive. Hive did an implicit conversion from the local time zone to UTC as it wrote the values to Parquet.

Impala query for `TIMESTAMP` values from Impala-written and Hive-written data:

```

[localhost:21000] > select * from pl;
+-----+
| x |
+-----+
| 2015-04-07 15:43:02.892403000 |
| 2015-04-08 15:43:02.892403000 |
+-----+
Fetched 2 row(s) in 0.29s
[localhost:21000] > select * from h1;
+-----+
| x |
+-----+
| 2015-04-07 22:43:02.892403000 |
| 2015-04-08 22:43:02.892403000 |
+-----+
Fetched 2 row(s) in 0.41s

```

Underlying integer values for Impala-written and Hive-written data:

```

[localhost:21000] > select cast(x as bigint) from pl;
+-----+
| cast(x as bigint) |
+-----+
| 1428421382 |
| 1428507782 |
+-----+
Fetched 2 row(s) in 0.38s
[localhost:21000] > select cast(x as bigint) from h1;
+-----+
| cast(x as bigint) |
+-----+
| 1428446582 |
| 1428532982 |
+-----+

```

```
+-----+
Fetched 2 row(s) in 0.20s
```

When the `-convert_legacy_hive_parquet_utc_timestamps` setting is enabled, Impala recognizes the Parquet data files written by Hive, and applies the same UTC-to-local-timezone conversion logic during the query as Hive uses, making the contents of the Impala-written P1 table and the Hive-written H1 table appear identical, whether represented as `TIMESTAMP` values or the underlying `BIGINT` integers:

```
[localhost:21000] > select x from p1;
+-----+
| x |
+-----+
| 2015-04-07 15:43:02.892403000 |
| 2015-04-08 15:43:02.892403000 |
+-----+
Fetched 2 row(s) in 0.37s
[localhost:21000] > select x from h1;
+-----+
| x |
+-----+
| 2015-04-07 15:43:02.892403000 |
| 2015-04-08 15:43:02.892403000 |
+-----+
Fetched 2 row(s) in 0.19s
[localhost:21000] > select cast(x as bigint) from p1;
+-----+
| cast(x as bigint) |
+-----+
| 1428446582 |
| 1428532982 |
+-----+
Fetched 2 row(s) in 0.29s
[localhost:21000] > select cast(x as bigint) from h1;
+-----+
| cast(x as bigint) |
+-----+
| 1428446582 |
| 1428532982 |
+-----+
Fetched 2 row(s) in 0.22s
```

Conversions:

Impala automatically converts `STRING` literals of the correct format into `TIMESTAMP` values. Timestamp values are accepted in the format `"YYYY-MM-dd HH:mm:ss.SSSSSS"`, and can consist of just the date, or just the time, with or without the fractional second portion. For example, you can specify `TIMESTAMP` values such as `'1966-07-30'`, `'08:30:00'`, or `'1985-09-25 17:45:30.005'`. Casting an integer or floating-point value `N` to `TIMESTAMP` produces a value that is `N` seconds past the start of the epoch date (January 1, 1970). By default, the result value represents a date and time in the UTC time zone. If the setting `--use_local_tz_for_unix_timestamp_conversions=true` is in effect, the resulting `TIMESTAMP` represents a date and time in the local time zone.

In Impala 1.3 and higher, the `FROM_UNIXTIME()` and `UNIX_TIMESTAMP()` functions allow a wider range of format strings, with more flexibility in element order, repetition of letter placeholders, and separator characters. In CDH 5.5 / Impala 2.3 and higher, the `UNIX_TIMESTAMP()` function also allows a numeric timezone offset to be specified as part of the input string. See [Impala Date and Time Functions](#) on page 398 for details.

In Impala 2.2.0 and higher, built-in functions that accept or return integers representing `TIMESTAMP` values use the `BIGINT` type for parameters and return values, rather than `INT`. This change lets the date and time functions avoid an overflow error that would otherwise occur on January 19th, 2038 (known as the [“Year 2038 problem”](#) or [“Y2K38 problem”](#)). This change affects the `from_unixtime()` and `unix_timestamp()` functions. You might need to change application code that interacts with these functions, change the types of columns that store the return values, or add `CAST()` calls to SQL statements that call these functions.

Partitioning:

Although you cannot use a `TIMESTAMP` column as a partition key, you can extract the individual years, months, days, hours, and so on and partition based on those columns. Because the partition key column values are represented in HDFS directory names, rather than as fields in the data files themselves, you can also keep the original `TIMESTAMP` values if desired, without duplicating data or wasting storage space. See [Partition Key Columns](#) on page 573 for more details on partitioning with date and time values.

```
[localhost:21000] > create table timeline (event string) partitioned by (happened
timestamp);
ERROR: AnalysisException: Type 'TIMESTAMP' is not supported as partition-column type in
column: happened
```

Examples:

```
select cast('1966-07-30' as timestamp);
select cast('1985-09-25 17:45:30.005' as timestamp);
select cast('08:30:00' as timestamp);
select hour('1970-01-01 15:30:00');           -- Succeeds, returns 15.
select hour('1970-01-01 15:30');           -- Returns NULL because seconds field
required.
select hour('1970-01-01 27:30:00');       -- Returns NULL because hour value out of
range.
select dayofweek('2004-06-13');           -- Returns 1, representing Sunday.
select dayname('2004-06-13');             -- Returns 'Sunday'.
select date_add('2004-06-13', 365);       -- Returns 2005-06-13 with zeros for hh:mm:ss
fields.
select day('2004-06-13');                 -- Returns 13.
select datediff('1989-12-31', '1984-09-01'); -- How many days between these 2 dates?
select now();                             -- Returns current date and time in local
timezone.

create table dates_and_times (t timestamp);
insert into dates_and_times values
  ('1966-07-30'), ('1985-09-25 17:45:30.005'), ('08:30:00'), (now());
```

NULL considerations: Casting any unrecognized `STRING` value to this type produces a `NULL` value.

Partitioning: Because this type potentially has so many distinct values, it is often not a sensible choice for a partition key column. For example, events 1 millisecond apart would be stored in different partitions. Consider using the `TRUNC()` function to condense the number of distinct values, and partition on a new column with the truncated values.

HBase considerations: This data type is fully compatible with HBase tables.

Parquet considerations: This type is fully compatible with Parquet tables.

Text table considerations: Values of this type are potentially larger in text tables than in tables using Parquet or other binary formats.

Internal details: Represented in memory as a 16-byte value.

Added in: Available in all versions of Impala.

Column statistics considerations: Because this type has a fixed size, the maximum and average size fields are always filled in for column statistics, even before you run the `COMPUTE STATS` statement.

Sqoop considerations:

If you use Sqoop to convert RDBMS data to Parquet, be careful with interpreting any resulting values from `DATE`, `DATETIME`, or `TIMESTAMP` columns. The underlying values are represented as the Parquet `INT64` type, which is represented as `BIGINT` in the Impala table. The Parquet values represent the time in milliseconds, while Impala interprets `BIGINT` as the time in seconds. Therefore, if you have a `BIGINT` column in a Parquet table that was imported this way from Sqoop, divide the values by 1000 when interpreting as the `TIMESTAMP` type.

Restrictions:

If you cast a `STRING` with an unrecognized format to a `TIMESTAMP`, the result is `NULL` rather than an error. Make sure to test your data pipeline to be sure any textual date and time values are in a format that Impala `TIMESTAMP` can recognize.

Currently, Avro tables cannot contain `TIMESTAMP` columns. If you need to store date and time values in Avro tables, as a workaround you can use a `STRING` representation of the values, convert the values to `BIGINT` with the `UNIX_TIMESTAMP()` function, or create separate numeric columns for individual date and time fields using the `EXTRACT()` function.

Related information:

- [Timestamp Literals](#) on page 197.
- To convert to or from different date formats, or perform date arithmetic, use the date and time functions described in [Impala Date and Time Functions](#) on page 398. In particular, the `from_unixtime()` function requires a case-sensitive format string such as `"YYYY-MM-dd HH:mm:ss.SSSS"`, matching one of the allowed variations of a `TIMESTAMP` value (date plus time, only date, only time, optional fractional seconds).
- See [SQL Differences Between Impala and Hive](#) on page 502 for details about differences in `TIMESTAMP` handling between Impala and Hive.

TINYINT Data Type

A 1-byte integer data type used in `CREATE TABLE` and `ALTER TABLE` statements.

Syntax:

In the column definition of a `CREATE TABLE` statement:

```
column_name TINYINT
```

Range: -128 .. 127. There is no `UNSIGNED` subtype.

Conversions: Impala automatically converts to a larger integer type (`SMALLINT`, `INT`, or `BIGINT`) or a floating-point type (`FLOAT` or `DOUBLE`) automatically. Use `CAST()` to convert to `STRING` or `TIMESTAMP`. Casting an integer or floating-point value `N` to `TIMESTAMP` produces a value that is `N` seconds past the start of the epoch date (January 1, 1970). By default, the result value represents a date and time in the UTC time zone. If the setting `--use_local_tz_for_unix_timestamp_conversions=true` is in effect, the resulting `TIMESTAMP` represents a date and time in the local time zone.

Impala does not return column overflows as `NULL`, so that customers can distinguish between `NULL` data and overflow conditions similar to how they do so with traditional database systems. Impala returns the largest or smallest value in the range for the type. For example, valid values for a `tinyint` range from -128 to 127. In Impala, a `tinyint` with a value of -200 returns -128 rather than `NULL`. A `tinyint` with a value of 200 returns 127.

Usage notes:

For a convenient and automated way to check the bounds of the `TINYINT` type, call the functions `MIN_TINYINT()` and `MAX_TINYINT()`.

If an integer value is too large to be represented as a `TINYINT`, use a `SMALLINT` instead.

NULL considerations: Casting any non-numeric value to this type produces a `NULL` value.

Examples:

```
CREATE TABLE t1 (x TINYINT);
SELECT CAST(100 AS TINYINT);
```

Parquet considerations:

Physically, Parquet files represent `TINYINT` and `SMALLINT` values as 32-bit integers. Although Impala rejects attempts to insert out-of-range values into such columns, if you create a new table with the `CREATE TABLE ... LIKE PARQUET` syntax, any `TINYINT` or `SMALLINT` columns in the original table turn into `INT` columns in the new table.

HBase considerations: This data type is fully compatible with HBase tables.

Text table considerations: Values of this type are potentially larger in text tables than in tables using Parquet or other binary formats.

Internal details: Represented in memory as a 1-byte value.

Added in: Available in all versions of Impala.

Column statistics considerations: Because this type has a fixed size, the maximum and average size fields are always filled in for column statistics, even before you run the `COMPUTE STATS` statement.

Related information:

[Numeric Literals](#) on page 195, [TINYINT Data Type](#) on page 164, [SMALLINT Data Type](#) on page 150, [INT Data Type](#) on page 145, [BIGINT Data Type](#) on page 130, [DECIMAL Data Type \(CDH 5.1 or higher only\)](#) on page 135, [Impala Mathematical Functions](#) on page 374

VARCHAR Data Type (CDH 5.2 or higher only)

A variable-length character type, truncated during processing if necessary to fit within the specified length.

Syntax:

In the column definition of a `CREATE TABLE` statement:

```
column_name VARCHAR(max_length)
```

The maximum length you can specify is 65,535.

Partitioning: This type can be used for partition key columns. Because of the efficiency advantage of numeric values over character-based values, if the partition key is a string representation of a number, prefer to use an integer type with sufficient range (`INT`, `BIGINT`, and so on) where practical.

HBase considerations: This data type cannot be used with HBase tables.

Parquet considerations:

- This type can be read from and written to Parquet files.
- There is no requirement for a particular level of Parquet.
- Parquet files generated by Impala and containing this type can be freely interchanged with other components such as Hive and MapReduce.
- Parquet data files can contain values that are longer than allowed by the `VARCHAR(n)` length limit. Impala ignores any extra trailing characters when it processes those values during a query.

Text table considerations:

Text data files can contain values that are longer than allowed by the `VARCHAR(n)` length limit. Any extra trailing characters are ignored when Impala processes those values during a query.

Avro considerations:

The Avro specification allows string values up to 2^{64} bytes in length. Impala queries for Avro tables use 32-bit integers to hold string lengths. In CDH 5.7 / Impala 2.5 and higher, Impala truncates `CHAR` and `VARCHAR` values in Avro tables to $(2^{31})-1$ bytes. If a query encounters a `STRING` value longer than $(2^{31})-1$ bytes in an Avro table, the query fails. In earlier releases, encountering such long values in an Avro table could cause a crash.

Schema evolution considerations:

You can use `ALTER TABLE ... CHANGE` to switch column data types to and from `VARCHAR`. You can convert from `STRING` to `VARCHAR(n)`, or from `VARCHAR(n)` to `STRING`, or from `CHAR(n)` to `VARCHAR(n)`, or from `VARCHAR(n)` to `CHAR(n)`. When switching back and forth between `VARCHAR` and `CHAR`, you can also change the length value. This schema evolution works the same for tables using any file format. If a table contains values longer than the maximum length defined for a `VARCHAR` column, Impala does not return an error. Any extra trailing characters are ignored when Impala processes those values during a query.

Compatibility:

This type is available on CDH 5.2 or higher.

Internal details: Represented in memory as a byte array with the minimum size needed to represent each value.

Added in: CDH 5.2.0 (Impala 2.0.0)

Column statistics considerations: Because the values of this type have variable size, none of the column statistics fields are filled in until you run the `COMPUTE STATS` statement.

Restrictions:

All data in `CHAR` and `VARCHAR` columns must be in a character encoding that is compatible with UTF-8. If you have binary data from another database system (that is, a `BLOB` type), use a `STRING` column to hold it.

Examples:

The following examples show how long and short `VARCHAR` values are treated. Values longer than the maximum specified length are truncated by `CAST()`, or when queried from existing data files. Values shorter than the maximum specified length are represented as the actual length of the value, with no extra padding as seen with `CHAR` values.

```
create table varchar_1 (s varchar(1));
create table varchar_4 (s varchar(4));
create table varchar_20 (s varchar(20));

insert into varchar_1 values (cast('a' as varchar(1)), (cast('b' as varchar(1))),
(cast('hello' as varchar(1)), (cast('world' as varchar(1)));
insert into varchar_4 values (cast('a' as varchar(4)), (cast('b' as varchar(4))),
(cast('hello' as varchar(4)), (cast('world' as varchar(4)));
insert into varchar_20 values (cast('a' as varchar(20)), (cast('b' as varchar(20))),
(cast('hello' as varchar(20)), (cast('world' as varchar(20)));

select * from varchar_1;
+----+
| s |
+----+
| a |
| b |
| h |
| w |
+----+
select * from varchar_4;
+-----+
| s |
+-----+
| a |
| b |
| hell |
| worl |
+-----+
[localhost:21000] > select * from varchar_20;
+-----+
| s |
+-----+
| a |
| b |
| hello |
| world |
+-----+
select concat(['',s,']) as s from varchar_20;
+-----+
| s |
+-----+
| [a] |
| [b] |
| [hello] |
| [world] |
+-----+
```

The following example shows how identical `VARCHAR` values compare as equal, even if the columns are defined with different maximum lengths. Both tables contain 'a' and 'b' values. The longer 'hello' and 'world' values from the `VARCHAR_20` table were truncated when inserted into the `VARCHAR_1` table.

```
select s from varchar_1 join varchar_20 using (s);
+-----+
```

```

| s |
+---+
| a |
| b |
+---+

```

The following examples show how `VARCHAR` values are freely interchangeable with `STRING` values in contexts such as comparison operators and built-in functions:

```

select length(cast('foo' as varchar(100))) as length;
+-----+
| length |
+-----+
| 3      |
+-----+
select cast('xyz' as varchar(5)) > cast('abc' as varchar(10)) as greater;
+-----+
| greater |
+-----+
| true    |
+-----+

```

UDF considerations: This type cannot be used for the argument or return type of a user-defined function (UDF) or user-defined aggregate function (UDA).

Related information:

[STRING Data Type](#) on page 151, [CHAR Data Type \(CDH 5.2 or higher only\)](#) on page 132, [String Literals](#) on page 196, [Impala String Functions](#) on page 430

Complex Types (CDH 5.5 or higher only)

Complex types (also referred to as **nested types**) let you represent multiple data values within a single row/column position. They differ from the familiar column types such as `BIGINT` and `STRING`, known as **scalar types** or **primitive types**, which represent a single data value within a given row/column position. Impala supports the complex types `ARRAY`, `MAP`, and `STRUCT` in CDH 5.5 / Impala 2.3 and higher. The Hive `UNION` type is not currently supported.

Once you understand the basics of complex types, refer to the individual type topics when you need to refresh your memory about syntax and examples:

- [ARRAY Complex Type \(CDH 5.5 or higher only\)](#) on page 127
- [STRUCT Complex Type \(CDH 5.5 or higher only\)](#) on page 153
- [MAP Complex Type \(CDH 5.5 or higher only\)](#) on page 146

Benefits of Impala Complex Types

The reasons for using Impala complex types include the following:

- You already have data produced by Hive or other non-Impala component that uses the complex type column names. You might need to convert the underlying data to Parquet to use it with Impala.
- Your data model originates with a non-SQL programming language or a NoSQL data management system. For example, if you are representing Python data expressed as nested lists, dictionaries, and tuples, those data structures correspond closely to Impala `ARRAY`, `MAP`, and `STRUCT` types.
- Your analytic queries involving multiple tables could benefit from greater locality during join processing. By packing more related data items within each HDFS data block, complex types let join queries avoid the network overhead of the traditional Hadoop shuffle or broadcast join techniques.

The Impala complex type support produces result sets with all scalar values, and the scalar components of complex types can be used with all SQL clauses, such as `GROUP BY`, `ORDER BY`, all kinds of joins, subqueries, and inline views. The ability to process complex type data entirely in SQL reduces the need to write application-specific code in Java or other programming languages to deconstruct the underlying data structures.

Overview of Impala Complex Types

The `ARRAY` and `MAP` types are closely related: they represent collections with arbitrary numbers of elements, where each element is the same type. In contrast, `STRUCT` groups together a fixed number of items into a single element. The parts of a `STRUCT` element (the *fields*) can be of different types, and each field has a name.

The elements of an `ARRAY` or `MAP`, or the fields of a `STRUCT`, can also be other complex types. You can construct elaborate data structures with up to 100 levels of nesting. For example, you can make an `ARRAY` whose elements are `STRUCTS`. Within each `STRUCT`, you can have some fields that are `ARRAY`, `MAP`, or another kind of `STRUCT`. The Impala documentation uses the terms complex and nested types interchangeably; for simplicity, it primarily uses the term complex types, to encompass all the properties of these types.

When visualizing your data model in familiar SQL terms, you can think of each `ARRAY` or `MAP` as a miniature table, and each `STRUCT` as a row within such a table. By default, the table represented by an `ARRAY` has two columns, `POS` to represent ordering of elements, and `ITEM` representing the value of each element. Likewise, by default, the table represented by a `MAP` encodes key-value pairs, and therefore has two columns, `KEY` and `VALUE`.

The `ITEM` and `VALUE` names are only required for the very simplest kinds of `ARRAY` and `MAP` columns, ones that hold only scalar values. When the elements within the `ARRAY` or `MAP` are of type `STRUCT` rather than a scalar type, then the result set contains columns with names corresponding to the `STRUCT` fields rather than `ITEM` or `VALUE`.

You write most queries that process complex type columns using familiar join syntax, even though the data for both sides of the join resides in a single table. The join notation brings together the scalar values from a row with the values from the complex type columns for that same row. The final result set contains all scalar values, allowing you to do all the familiar filtering, aggregation, ordering, and so on for the complex data entirely in SQL or using business intelligence tools that issue SQL queries.

Behind the scenes, Impala ensures that the processing for each row is done efficiently on a single host, without the network traffic involved in broadcast or shuffle joins. The most common type of join query for tables with complex type columns is `INNER JOIN`, which returns results only in those cases where the complex type contains some elements. Therefore, most query examples in this section use either the `INNER JOIN` clause or the equivalent comma notation.



Note:

Although Impala can query complex types that are present in Parquet files, Impala currently cannot create new Parquet files containing complex types. Therefore, the discussion and examples presume that you are working with existing Parquet data produced through Hive, Spark, or some other source. See [Constructing Parquet Files with Complex Columns Using Hive](#) on page 190 for examples of constructing Parquet data files with complex type columns.

For learning purposes, you can create empty tables with complex type columns and practice query syntax, even if you do not have sample data with the required structure.

Design Considerations for Complex Types

When planning to use Impala complex types, and designing the Impala schema, first learn how this kind of schema differs from traditional table layouts from the relational database and data warehousing fields. Because you might have already encountered complex types in a Hadoop context while using Hive for ETL, also learn how to write high-performance analytic queries for complex type data using Impala SQL syntax.

How Complex Types Differ from Traditional Data Warehouse Schemas

Complex types let you associate arbitrary data structures with a particular row. If you are familiar with schema design for relational database management systems or data warehouses, a schema with complex types has the following differences:

- Logically, related values can now be grouped tightly together in the same table.

In traditional data warehousing, related values were typically arranged in one of two ways:

- Split across multiple normalized tables. Foreign key columns specified which rows from each table were associated with each other. This arrangement avoided duplicate data and therefore the data was compact,

but join queries could be expensive because the related data had to be retrieved from separate locations. (In the case of distributed Hadoop queries, the joined tables might even be transmitted between different hosts in a cluster.)

- Flattened into a single denormalized table. Although this layout eliminated some potential performance issues by removing the need for join queries, the table typically became larger because values were repeated. The extra data volume could cause performance issues in other parts of the workflow, such as longer ETL cycles or more expensive full-table scans during queries.

Complex types represent a middle ground that addresses these performance and volume concerns. By physically locating related data within the same data files, complex types increase locality and reduce the expense of join queries. By associating an arbitrary amount of data with a single row, complex types avoid the need to repeat lengthy values such as strings. Because Impala knows which complex type values are associated with each row, you can save storage by avoiding artificial foreign key values that are only used for joins. The flexibility of the `STRUCT`, `ARRAY`, and `MAP` types lets you model familiar constructs such as fact and dimension tables from a data warehouse, and wide tables representing sparse matrixes.

Physical Storage for Complex Types

Physically, the scalar and complex columns in each row are located adjacent to each other in the same Parquet data file, ensuring that they are processed on the same host rather than being broadcast across the network when cross-referenced within a query. This co-location simplifies the process of copying, converting, and backing all the columns up at once. Because of the column-oriented layout of Parquet files, you can still query only the scalar columns of a table without imposing the I/O penalty of reading the (possibly large) values of the composite columns.

Within each Parquet data file, the constituent parts of complex type columns are stored in column-oriented format:

- Each field of a `STRUCT` type is stored like a column, with all the scalar values adjacent to each other and encoded, compressed, and so on using the Parquet space-saving techniques.
- For an `ARRAY` containing scalar values, all those values (represented by the `ITEM` pseudocolumn) are stored adjacent to each other.
- For a `MAP`, the values of the `KEY` pseudocolumn are stored adjacent to each other. If the `VALUE` pseudocolumn is a scalar type, its values are also stored adjacent to each other.
- If an `ARRAY` element, `STRUCT` field, or `MAP VALUE` part is another complex type, the column-oriented storage applies to the next level down (or the next level after that, and so on for deeply nested types) where the final elements, fields, or values are of scalar types.

The numbers represented by the `POS` pseudocolumn of an `ARRAY` are not physically stored in the data files. They are synthesized at query time based on the order of the `ARRAY` elements associated with each row.

File Format Support for Impala Complex Types

Currently, Impala queries support complex type data only in the Parquet file format. See [Using the Parquet File Format with Impala Tables](#) on page 584 for details about the performance benefits and physical layout of this file format.

Because Impala does not parse the data structures containing nested types for unsupported formats such as text, Avro, SequenceFile, or RCFile, you cannot use data files in these formats with Impala, even if the query does not refer to the nested type columns. Also, if a table using an unsupported format originally contained nested type columns, and then those columns were dropped from the table using `ALTER TABLE ... DROP COLUMN`, any existing data files in the table still contain the nested type data and Impala queries on that table will generate errors.

The one exception to the preceding rule is `COUNT(*)` queries on RCFile tables that include complex types. Such queries are allowed in and higher.

You can perform DDL operations for tables involving complex types in most file formats other than Parquet. You cannot create tables in Impala with complex types using text files.

You can have a partitioned table with complex type columns that uses a non-Parquet format, and use `ALTER TABLE` to change the file format to Parquet for individual partitions. When you put Parquet data files into those partitions, Impala can execute queries against that data as long as the query does not involve any of the non-Parquet partitions.

If you use the `parquet-tools` command to examine the structure of a Parquet data file that includes complex types, you see that both `ARRAY` and `MAP` are represented as a `Bag` in Parquet terminology, with all fields marked `Optional` because Impala allows any column to be nullable.

Impala supports either 2-level and 3-level encoding within each Parquet data file. When constructing Parquet data files outside Impala, use either encoding style but do not mix 2-level and 3-level encoding within the same data file.

Choosing Between Complex Types and Normalized Tables

Choosing between multiple normalized fact and dimension tables, or a single table containing complex types, is an important design decision.

- If you are coming from a traditional database or data warehousing background, you might be familiar with how to split up data between tables. Your business intelligence tools might already be optimized for dealing with this kind of multi-table scenario through join queries.
- If you are pulling data from Impala into an application written in a programming language that has data structures analogous to the complex types, such as Python or Java, complex types in Impala could simplify data interchange and improve understandability and reliability of your program logic.
- You might already be faced with existing infrastructure or receive high volumes of data that assume one layout or the other. For example, complex types are popular with web-oriented applications, for example to keep information about an online user all in one place for convenient lookup and analysis, or to deal with sparse or constantly evolving data fields.
- If some parts of the data change over time while related data remains constant, using multiple normalized tables lets you replace certain parts of the data without reloading the entire data set. Conversely, if you receive related data all bundled together, such as in JSON files, using complex types can save the overhead of splitting the related items across multiple tables.
- From a performance perspective:
 - In Parquet tables, Impala can skip columns that are not referenced in a query, avoiding the I/O penalty of reading the embedded data. When complex types are nested within a column, the data is physically divided at a very granular level; for example, a query referring to data nested multiple levels deep in a complex type column does not have to read all the data from that column, only the data for the relevant parts of the column type hierarchy.
 - Complex types avoid the possibility of expensive join queries when data from fact and dimension tables is processed in parallel across multiple hosts. All the information for a row containing complex types is typically to be in the same data block, and therefore does not need to be transmitted across the network when joining fields that are all part of the same row.
 - The tradeoff with complex types is that fewer rows fit in each data block. Whether it is better to have more data blocks with fewer rows, or fewer data blocks with many rows, depends on the distribution of your data and the characteristics of your query workload. If the complex columns are rarely referenced, using them might lower efficiency. If you are seeing low parallelism due to a small volume of data (relatively few data blocks) in each table partition, increasing the row size by including complex columns might produce more data blocks and thus spread the work more evenly across the cluster. See [Scalability Considerations for Impala](#) on page 561 for more on this advanced topic.

Differences Between Impala and Hive Complex Types

Impala can query Parquet tables containing `ARRAY`, `STRUCT`, and `MAP` columns produced by Hive. There are some differences to be aware of between the Impala SQL and HiveQL syntax for complex types, primarily for queries.

Impala supports a subset of the syntax that Hive supports for specifying `ARRAY`, `STRUCT`, and `MAP` types in the `CREATE TABLE` statements.

Because Impala `STRUCT` columns include user-specified field names, you use the `NAMED_STRUCT()` constructor in Hive rather than the `STRUCT()` constructor when you populate an Impala `STRUCT` column using a Hive `INSERT` statement.

The Hive `UNION` type is not currently supported in Impala.

While Impala usually aims for a high degree of compatibility with HiveQL query syntax, Impala syntax differs from Hive for queries involving complex types. The differences are intended to provide extra flexibility for queries involving these kinds of tables.

- Impala uses dot notation for referring to element names or elements within complex types, and join notation for cross-referencing scalar columns with the elements of complex types within the same row, rather than the `LATERAL VIEW` clause and `EXPLODE()` function of HiveQL.
- Using join notation lets you use all the kinds of join queries with complex type columns. For example, you can use a `LEFT OUTER JOIN`, `LEFT ANTI JOIN`, or `LEFT SEMI JOIN` query to evaluate different scenarios where the complex columns do or do not contain any elements.
- You can include references to collection types inside subqueries and inline views. For example, you can construct a `FROM` clause where one of the “tables” is a subquery against a complex type column, or use a subquery against a complex type column as the argument to an `IN` or `EXISTS` clause.
- The Impala pseudocolumn `POS` lets you retrieve the position of elements in an array along with the elements themselves, equivalent to the `POSEXPLODE()` function of HiveQL. You do not use index notation to retrieve a single array element in a query; the join query loops through the array elements and you use `WHERE` clauses to specify which elements to return.
- Join clauses involving complex type columns do not require an `ON` or `USING` clause. Impala implicitly applies the join key so that the correct array entries or map elements are associated with the correct row from the table.
- Impala does not currently support the `UNION` complex type.

Limitations and Restrictions for Complex Types

Complex type columns can only be used in tables or partitions with the Parquet file format.

Complex type columns cannot be used as partition key columns in a partitioned table.

When you use complex types with the `ORDER BY`, `GROUP BY`, `HAVING`, or `WHERE` clauses, you cannot refer to the column name by itself. Instead, you refer to the names of the scalar values within the complex type, such as the `ITEM`, `POS`, `KEY`, or `VALUE` pseudocolumns, or the field names from a `STRUCT`.

The maximum depth of nesting for complex types is 100 levels.

The maximum length of the column definition for any complex type, including declarations for any nested types, is 4000 characters.

For ideal performance and scalability, use small or medium-sized collections, where all the complex columns contain at most a few hundred megabytes per row. Remember, all the columns of a row are stored in the same HDFS data block, whose size in Parquet files typically ranges from 256 MB to 1 GB.

Including complex type columns in a table introduces some overhead that might make queries that do not reference those columns somewhat slower than Impala queries against tables without any complex type columns. Expect at most a 2x slowdown compared to tables that do not have any complex type columns.

Currently, the `COMPUTE STATS` statement does not collect any statistics for columns containing complex types. Impala uses heuristics to construct execution plans involving complex type columns.

Currently, Impala built-in functions and user-defined functions cannot accept complex types as parameters or produce them as function return values. (When the complex type values are materialized in an Impala result set, the result set contains the scalar components of the values, such as the `POS` or `ITEM` for an `ARRAY`, the `KEY` or `VALUE` for a `MAP`, or the fields of a `STRUCT`; these scalar data items *can* be used with built-in functions and UDFs as usual.)

Impala currently cannot write new data files containing complex type columns. Therefore, although the `SELECT` statement works for queries involving complex type columns, you cannot use a statement form that writes data to complex type columns, such as `CREATE TABLE AS SELECT` or `INSERT ... SELECT`. To create data files containing

complex type data, use the Hive `INSERT` statement, or another ETL mechanism such as MapReduce jobs, Spark jobs, Pig, and so on.

Currently, Impala can query complex type columns only from Parquet tables or Parquet partitions within partitioned tables. Although you can use complex types in tables with Avro, text, and other file formats as part of your ETL pipeline, for example as intermediate tables populated through Hive, doing analytics through Impala requires that the data eventually ends up in a Parquet table. The requirement for Parquet data files means that you can use complex types with Impala tables hosted on other kinds of file storage systems such as Isilon and Amazon S3, but you cannot use Impala to query complex types from HBase tables. See [File Format Support for Impala Complex Types](#) on page 169 for more details.

Using Complex Types in SQL

When using complex types through SQL in Impala, you learn the notation for `< >` delimiters for the complex type columns in `CREATE TABLE` statements, and how to construct join queries to “unpack” the scalar values nested inside the complex data structures. You might need to condense a traditional RDBMS or data warehouse schema into a smaller number of Parquet tables, and use Hive, Spark, Pig, or other mechanism outside Impala to populate the tables with data.

Complex Type Syntax for DDL Statements

The definition of *data_type*, as seen in the `CREATE TABLE` and `ALTER TABLE` statements, now includes complex types in addition to primitive types:

```
primitive_type
| array_type
| map_type
| struct_type
```

Unions are not currently supported.

`Array`, `struct`, and `map` column type declarations are specified in the `CREATE TABLE` statement. You can also add or change the type of complex columns through the `ALTER TABLE` statement.

Currently, Impala queries allow complex types only in tables that use the Parquet format. If an Impala query encounters complex types in a table or partition using another file format, the query returns a runtime error.

You can use `ALTER TABLE ... SET FILEFORMAT PARQUET` to change the file format of an existing table containing complex types to Parquet, after which Impala can query it. Make sure to load Parquet files into the table after changing the file format, because the `ALTER TABLE ... SET FILEFORMAT` statement does not convert existing data to the new file format.

Partitioned tables can contain complex type columns. All the partition key columns must be scalar types.

Because use cases for Impala complex types require that you already have Parquet data files produced outside of Impala, you can use the Impala `CREATE TABLE LIKE PARQUET` syntax to produce a table with columns that match the structure of an existing Parquet file, including complex type columns for nested data structures. Remember to include the `STORED AS PARQUET` clause in this case, because even with `CREATE TABLE LIKE PARQUET`, the default file format of the resulting table is still text.

You cannot use the `CREATE TABLE AS SELECT` syntax to create a table with nested type columns because the complex columns are omitted from the result set of an Impala `SELECT *` or `SELECT col_name` query, and because Impala currently does not support writing Parquet files with complex type columns,

**Note:**

Once you have a table set up with complex type columns, use the `DESCRIBE` and `SHOW CREATE TABLE` statements to see the correct notation with `<` and `>` delimiters and comma and colon separators within the complex type definitions. If you do not have existing data with the same layout as the table, you can query the empty table to practice with the notation for the `SELECT` statement. In the `SELECT` list, you use dot notation and pseudocolumns such as `ITEM`, `KEY`, and `VALUE` for referring to items within the complex type columns. In the `FROM` clause, you use join notation to construct table aliases for any referenced `ARRAY` and `MAP` columns.

For example, when defining a table that holds contact information, you might represent phone numbers differently depending on the expected layout and relationships of the data, and how well you can predict those properties in advance.

Here are different ways that you might represent phone numbers in a traditional relational schema, with equivalent representations using complex types.

The traditional, simplest way to represent phone numbers in a relational table is to store all contact info in a single table, with all columns having scalar types, and each potential phone number represented as a separate column. In this example, each person can only have these 3 types of phone numbers. If the person does not have a particular kind of phone number, the corresponding column is `NULL` for that row.

```
CREATE TABLE contacts_fixed_phones
(
  id BIGINT
  , name STRING
  , address STRING
  , home_phone STRING
  , work_phone STRING
  , mobile_phone STRING
) STORED AS PARQUET;
```

Figure 1: Traditional Relational Representation of Phone Numbers: Single Table

Using a complex type column to represent the phone numbers adds some extra flexibility. Now there could be an unlimited number of phone numbers. Because the array elements have an order but not symbolic names, you could decide in advance that `phone_number[0]` is the home number, `[1]` is the work number, `[2]` is the mobile number, and so on. (In subsequent examples, you will see how to create a more flexible naming scheme using other complex type variations, such as a `MAP` or an `ARRAY` where each element is a `STRUCT`.)

```
CREATE TABLE contacts_array_of_phones
(
  id BIGINT
  , name STRING
  , address STRING
  , phone_number ARRAY < STRING >
) STORED AS PARQUET;
```

Figure 2: An Array of Phone Numbers

Another way to represent an arbitrary set of phone numbers is with a `MAP` column. With a `MAP`, each element is associated with a key value that you specify, which could be a numeric, string, or other scalar type. This example uses a `STRING` key to give each phone number a name, such as `'home'` or `'mobile'`. A query could filter the data based on the key values, or display the key values in reports.

```
CREATE TABLE contacts_unlimited_phones
(
  id BIGINT, name STRING, address STRING, phone_number MAP < STRING,STRING >
```

```
) STORED AS PARQUET;
```

Figure 3: A Map of Phone Numbers

If you are an experienced database designer, you already know how to work around the limitations of the single-table schema from [Figure 1: Traditional Relational Representation of Phone Numbers: Single Table](#) on page 173. By normalizing the schema, with the phone numbers in their own table, you can associate an arbitrary set of phone numbers with each person, and associate additional details with each phone number, such as whether it is a home, work, or mobile phone.

The flexibility of this approach comes with some drawbacks. Reconstructing all the data for a particular person requires a join query, which might require performance tuning on Hadoop because the data from each table might be transmitted from a different host. Data management tasks such as backups and refreshing the data require dealing with multiple tables instead of a single table.

This example illustrates a traditional database schema to store contact info normalized across 2 tables. The fact table establishes the identity and basic information about person. A dimension table stores information only about phone numbers, using an ID value to associate each phone number with a person ID from the fact table. Each person can have 0, 1, or many phones; the categories are not restricted to a few predefined ones; and the phone table can contain as many columns as desired, to represent all sorts of details about each phone number.

```
CREATE TABLE fact_contacts (id BIGINT, name STRING, address STRING) STORED AS PARQUET;
CREATE TABLE dim_phones
(
  contact_id BIGINT
  , category STRING
  , international_code STRING
  , area_code STRING
  , exchange STRING
  , extension STRING
  , mobile BOOLEAN
  , carrier STRING
  , current BOOLEAN
  , service_start_date TIMESTAMP
  , service_end_date TIMESTAMP
)
STORED AS PARQUET;
```

Figure 4: Traditional Relational Representation of Phone Numbers: Normalized Tables

To represent a schema equivalent to the one from [Figure 4: Traditional Relational Representation of Phone Numbers: Normalized Tables](#) on page 174 using complex types, this example uses an `ARRAY` where each array element is a `STRUCT`. As with the earlier complex type examples, each person can have an arbitrary set of associated phone numbers. Making each array element into a `STRUCT` lets us associate multiple data items with each phone number, and give a separate name and type to each data item. The `STRUCT` fields of the `ARRAY` elements reproduce the columns of the dimension table from the previous example.

You can do all the same kinds of queries with the complex type schema as with the normalized schema from the previous example. The advantages of the complex type design are in the areas of convenience and performance. Now your backup and ETL processes only deal with a single table. When a query uses a join to cross-reference the information about a person with their associated phone numbers, all the relevant data for each row resides in the same HDFS data block, meaning each row can be processed on a single host without requiring network transmission.

```
CREATE TABLE contacts_detailed_phones
(
  id BIGINT, name STRING, address STRING
  , phone ARRAY < STRUCT <
    category: STRING
    , international_code: STRING
    , area_code: STRING
    , exchange: STRING
```

```

    , extension: STRING
    , mobile: BOOLEAN
    , carrier: STRING
    , current: BOOLEAN
    , service_start_date: TIMESTAMP
    , service_end_date: TIMESTAMP
  >>
) STORED AS PARQUET;

```

Figure 5: Phone Numbers Represented as an Array of Structs

SQL Statements that Support Complex Types

The Impala SQL statements that support complex types are currently [CREATE TABLE](#), [ALTER TABLE](#), [DESCRIBE](#), [LOAD DATA](#), and [SELECT](#). That is, currently Impala can create or alter tables containing complex type columns, examine the structure of a table containing complex type columns, import existing data files containing complex type columns into a table, and query Parquet tables containing complex types.

Impala currently cannot write new data files containing complex type columns. Therefore, although the `SELECT` statement works for queries involving complex type columns, you cannot use a statement form that writes data to complex type columns, such as `CREATE TABLE AS SELECT` or `INSERT ... SELECT`. To create data files containing complex type data, use the Hive `INSERT` statement, or another ETL mechanism such as MapReduce jobs, Spark jobs, Pig, and so on.

DDL Statements and Complex Types

Column specifications for complex or nested types use `<` and `>` delimiters:

```

-- What goes inside the < > for an ARRAY is a single type, either a scalar or another
-- complex type (ARRAY, STRUCT, or MAP).
CREATE TABLE array_t
(
  id BIGINT,
  a1 ARRAY <STRING>,
  a2 ARRAY <BIGINT>,
  a3 ARRAY <TIMESTAMP>,
  a4 ARRAY <STRUCT <f1: STRING, f2: INT, f3: BOOLEAN>>
)
STORED AS PARQUET;

-- What goes inside the < > for a MAP is two comma-separated types specifying the types
-- of the key-value pair:
-- a scalar type representing the key, and a scalar or complex type representing the
-- value.
CREATE TABLE map_t
(
  id BIGINT,
  m1 MAP <STRING, STRING>,
  m2 MAP <STRING, BIGINT>,
  m3 MAP <BIGINT, STRING>,
  m4 MAP <BIGINT, BIGINT>,
  m5 MAP <STRING, ARRAY <STRING>>
)
STORED AS PARQUET;

-- What goes inside the < > for a STRUCT is a comma-separated list of fields, each field
-- defined as
-- name:type. The type can be a scalar or a complex type. The field names for each STRUCT
-- do not clash
-- with the names of table columns or fields in other STRUCTs. A STRUCT is most often
-- used inside
-- an ARRAY or a MAP rather than as a top-level column.
CREATE TABLE struct_t
(
  id BIGINT,
  s1 STRUCT <f1: STRING, f2: BIGINT>,
  s2 ARRAY <STRUCT <f1: INT, f2: TIMESTAMP>>,
  s3 MAP <BIGINT, STRUCT <name: STRING, birthday: TIMESTAMP>>
)

```

```
STORED AS PARQUET;
```

Queries and Complex Types

The result set of an Impala query always contains all scalar types; the elements and fields within any complex type queries must be “unpacked” using join queries. A query cannot directly retrieve the entire value for a complex type column. Impala returns an error in this case. Queries using `SELECT *` are allowed for tables with complex types, but the columns with complex types are skipped.

The following example shows how referring directly to a complex type column returns an error, while `SELECT *` on the same table succeeds, but only retrieves the scalar columns.



Note: Many of the complex type examples refer to tables such as `CUSTOMER` and `REGION` adapted from the tables used in the TPC-H benchmark. See [Sample Schema and Data for Experimenting with Impala Complex Types](#) on page 188 for the table definitions.

```
SELECT c_orders FROM customer LIMIT 1;
ERROR: AnalysisException: Expr 'c_orders' in select list returns a complex type
'ARRAY<STRUCT<o_orderkey:BIGINT,o_orderstatus:STRING, ...
l_receiptdate:STRING,l_shipinstruct:STRING,l_shipmode:STRING,l_comment:STRING>>>>'.
Only scalar types are allowed in the select list.

-- Original column has several scalar and one complex column.
DESCRIBE customer;
+-----+-----+
| name          | type          |
+-----+-----+
| c_custkey     | bigint       |
| c_name        | string       |
| ...           |              |
| c_orders      | array<struct<
|               |   o_orderkey:bigint,
|               |   o_orderstatus:string,
|               |   o_totalprice:decimal(12,2),
| ...           |              |
|               | >>          |
+-----+-----+

-- When we SELECT * from that table, only the scalar columns come back in the result
set.
CREATE TABLE select_star_customer STORED AS PARQUET AS SELECT * FROM customer;
+-----+-----+
| summary      |              |
+-----+-----+
| Inserted 150000 row(s) |
+-----+-----+

-- The c_orders column, being of complex type, was not included in the SELECT * result
set.
DESC select_star_customer;
+-----+-----+
| name          | type          |
+-----+-----+
| c_custkey     | bigint       |
| c_name        | string       |
| c_address     | string       |
| c_nationkey   | smallint    |
| c_phone       | string       |
| c_acctbal     | decimal(12,2) |
| c_mktsegment  | string       |
| c_comment     | string       |
+-----+-----+
```


References to fields within `STRUCT` columns use dot notation. If the field name is unambiguous, you can omit qualifiers such as table name, column name, or even the `ITEM` or `VALUE` pseudocolumn names for `STRUCT` elements inside an `ARRAY` or a `MAP`.

```
SELECT id, address.city FROM customers WHERE address.zip = 94305;
```

References to elements within `ARRAY` columns use the `ITEM` pseudocolumn:

```
select r_name, r_nations.item.n_name from region, region.r_nations limit 7;
```

r_name	item.n_name
EUROPE	UNITED KINGDOM
EUROPE	RUSSIA
EUROPE	ROMANIA
EUROPE	GERMANY
EUROPE	FRANCE
ASIA	VIETNAM
ASIA	CHINA

References to fields within `MAP` columns use the `KEY` and `VALUE` pseudocolumns. In this example, once the query establishes the alias `MAP_FIELD` for a `MAP` column with a `STRING` key and an `INT` value, the query can refer to `MAP_FIELD.KEY` and `MAP_FIELD.VALUE`, which have zero, one, or many instances for each row from the containing table.

```
DESCRIBE table_0;
```

name	type
field_0	string
field_1	map<string,int>
...	

```
SELECT field_0, map_field.key, map_field.value
FROM table_0, table_0.field_1 AS map_field
WHERE length(field_0) = 1
LIMIT 10;
```

field_0	key	value
b	gshsgkvd	NULL
b	twrtcxj6	18
b	2vp5	39
b	fh0s	13
v	2	41
v	8b58mz	20
v	hw	16
v	65l388pyt	29
v	03k68g9lz	30
v	r2hlg5b	NULL

When complex types are nested inside each other, you use a combination of joins, pseudocolumn names, and dot notation to refer to specific fields at the appropriate level. This is the most frequent form of query syntax for complex columns, because the typical use case involves two levels of complex types, such as an `ARRAY` of `STRUCT` elements.

```
SELECT id, phone_numbers.area_code FROM contact_info_many_structs INNER JOIN
contact_info_many_structs.phone_numbers phone_numbers LIMIT 3;
```

You can express relationships between `ARRAY` and `MAP` columns at different levels as joins. You include comparison operators between fields at the top level and within the nested type columns so that Impala can do the appropriate join operation.



Note: Many of the complex type examples refer to tables such as `CUSTOMER` and `REGION` adapted from the tables used in the TPC-H benchmark. See [Sample Schema and Data for Experimenting with Impala Complex Types](#) on page 188 for the table definitions.

For example, the following queries work equivalently. They each return customer and order data for customers that have at least one order.

```
SELECT c.c_name, o.o_orderkey FROM customer c, c.c_orders o LIMIT 5;
```

c_name	o_orderkey
Customer#000072578	558821
Customer#000072578	2079810
Customer#000072578	5768068
Customer#000072578	1805604
Customer#000072578	3436389

```
SELECT c.c_name, o.o_orderkey FROM customer c INNER JOIN c.c_orders o LIMIT 5;
```

c_name	o_orderkey
Customer#000072578	558821
Customer#000072578	2079810
Customer#000072578	5768068
Customer#000072578	1805604
Customer#000072578	3436389

The following query using an outer join returns customers that have orders, plus customers with no orders (no entries in the `C_ORDERS` array):

```
SELECT c.c_custkey, o.o_orderkey
FROM customer c LEFT OUTER JOIN c.c_orders o
LIMIT 5;
```

c_custkey	o_orderkey
60210	NULL
147873	NULL
72578	558821
72578	2079810
72578	5768068

The following query returns *only* customers that have no orders. (With `LEFT ANTI JOIN` or `LEFT SEMI JOIN`, the query can only refer to columns from the left-hand table, because by definition there is no matching information in the right-hand table.)

```
SELECT c.c_custkey, c.c_name
FROM customer c LEFT ANTI JOIN c.c_orders o
LIMIT 5;
```

c_custkey	c_name
60210	Customer#000060210
147873	Customer#000147873
141576	Customer#000141576
85365	Customer#000085365
70998	Customer#000070998

You can also perform correlated subqueries to examine the properties of complex type columns for each row in the result set.

Count the number of orders per customer. Note the correlated reference to the table alias `c`. The `COUNT(*)` operation applies to all the elements of the `C_ORDERS` array for the corresponding row, avoiding the need for a `GROUP BY` clause.

```
select c_name, howmany FROM customer c, (SELECT COUNT(*) howmany FROM c.c_orders) v
limit 5;
```

c_name	howmany
Customer#000030065	15
Customer#000065455	18
Customer#000113644	21
Customer#000111078	0
Customer#000024621	0

Count the number of orders per customer, ignoring any customers that have not placed any orders:

```
SELECT c_name, howmany_orders
FROM
  customer c,
  (SELECT COUNT(*) howmany_orders FROM c.c_orders) subq1
WHERE howmany_orders > 0
LIMIT 5;
```

c_name	howmany_orders
Customer#000072578	7
Customer#000046378	26
Customer#000069815	11
Customer#000079058	12
Customer#000092239	26

Count the number of line items in each order. The reference to `C.C_ORDERS` in the `FROM` clause is needed because the `O_ORDERKEY` field is a member of the elements in the `C_ORDERS` array. The subquery labelled `SUBQ1` is correlated: it is re-evaluated for the `C_ORDERS.O_LINEITEMS` array from each row of the `CUSTOMERS` table.

```
SELECT c_name, o_orderkey, howmany_line_items
FROM
  customer c,
  c.c_orders t2,
  (SELECT COUNT(*) howmany_line_items FROM c.c_orders.o_lineitems) subq1
WHERE howmany_line_items > 0
LIMIT 5;
```

c_name	o_orderkey	howmany_line_items
Customer#000020890	1884930	95
Customer#000020890	4570754	95
Customer#000020890	3771072	95
Customer#000020890	2555489	95
Customer#000020890	919171	95

Get the number of orders, the average order price, and the maximum items in any order per customer. For this example, the subqueries labelled `SUBQ1` and `SUBQ2` are correlated: they are re-evaluated for each row from the original `CUSTOMER` table, and only apply to the complex columns associated with that row.

```
SELECT c_name, howmany, average_price, most_items
FROM
  customer c,
  (SELECT COUNT(*) howmany, AVG(o_totalprice) average_price FROM c.c_orders) subq1,
  (SELECT MAX(l_quantity) most_items FROM c.c_orders.o_lineitems ) subq2
LIMIT 5;
```

c_name	howmany	average_price	most_items
Customer#000030065	15	128908.34	50.00

Customer#000088191	0	NULL	NULL
Customer#000101555	10	164250.31	50.00
Customer#000022092	0	NULL	NULL
Customer#000036277	27	166040.06	50.00

For example, these queries show how to access information about the ARRAY elements within the CUSTOMER table from the “nested TPC-H” schema, starting with the initial ARRAY elements and progressing to examine the STRUCT fields of the ARRAY, and then the elements nested within another ARRAY of STRUCT:

```
-- How many orders does each customer have?
-- The type of the ARRAY column doesn't matter, this is just counting the elements.
SELECT c_custkey, count(*)
  FROM customer, customer.c_orders
 GROUP BY c_custkey
LIMIT 5;
```

c_custkey	count(*)
61081	21
115987	15
69685	19
109124	15
50491	12

```
-- How many line items are part of each customer order?
-- Now we examine a field from a STRUCT nested inside the ARRAY.
SELECT c_custkey, c_orders.o_orderkey, count(*)
  FROM customer, customer.c_orders c_orders, c_orders.o_lineitems
 GROUP BY c_custkey, c_orders.o_orderkey
LIMIT 5;
```

c_custkey	o_orderkey	count(*)
63367	4985959	7
53989	1972230	2
143513	5750498	5
17849	4857989	1
89881	1046437	1

```
-- What are the line items in each customer order?
-- One of the STRUCT fields inside the ARRAY is another
-- ARRAY containing STRUCT elements. The join finds
-- all the related items from both levels of ARRAY.
SELECT c_custkey, o_orderkey, l_partkey
  FROM customer, customer.c_orders, c_orders.o_lineitems
LIMIT 5;
```

c_custkey	o_orderkey	l_partkey
113644	2738497	175846
113644	2738497	27309
113644	2738497	175873
113644	2738497	88559
113644	2738497	8032

Pseudocolumns for ARRAY and MAP Types

Each element in an ARRAY type has a position, indexed starting from zero, and a value. Each element in a MAP type represents a key-value pair. Impala provides pseudocolumns that let you retrieve this metadata as part of a query, or filter query results by including such things in a WHERE clause. You refer to the pseudocolumns as part of qualified column names in queries:

- ITEM: The value of an array element. If the ARRAY contains STRUCT elements, you can refer to either `array_name.ITEM.field_name` or use the shorthand `array_name.field_name`.
- POS: The position of an element within an array.

- **KEY:** The value forming the first part of a key-value pair in a map. It is not necessarily unique.
- **VALUE:** The data item forming the second part of a key-value pair in a map. If the **VALUE** part of the **MAP** element is a **STRUCT**, you can refer to either `map_name.VALUE.field_name` or use the shorthand `map_name.field_name`.

ITEM and POS Pseudocolumns

When an **ARRAY** column contains **STRUCT** elements, you can refer to a field within the **STRUCT** using a qualified name of the form `array_column.field_name`. If the **ARRAY** contains scalar values, Impala recognizes the special name `array_column.ITEM` to represent the value of each scalar array element. For example, if a column contained an **ARRAY** where each element was a **STRING**, you would use `array_name.ITEM` to refer to each scalar value in the **SELECT** list, or the **WHERE** or other clauses.

This example shows a table with two **ARRAY** columns whose elements are of the scalar type **STRING**. When referring to the values of the array elements in the **SELECT** list, **WHERE** clause, or **ORDER BY** clause, you use the **ITEM** pseudocolumn because within the array, the individual elements have no defined names.

```
create TABLE persons_of_interest
(
  person_id BIGINT,
  aliases ARRAY <STRING>,
  associates ARRAY <STRING>,
  real_name STRING
)
STORED AS PARQUET;

-- Get all the aliases of each person.
SELECT real_name, aliases.ITEM
  FROM persons_of_interest, persons_of_interest.aliases
 ORDER BY real_name, aliases.item;

-- Search for particular associates of each person.
SELECT real_name, associates.ITEM
  FROM persons_of_interest, persons_of_interest.associates
 WHERE associates.item LIKE '% MacGuffin';
```

Because an array is inherently an ordered data structure, Impala recognizes the special name `array_column.POS` to represent the numeric position of each element within the array. The **POS** pseudocolumn lets you filter or reorder the result set based on the sequence of array elements.

The following example uses a table from a flattened version of the TPC-H schema. The **REGION** table only has a few rows, such as one row for Europe and one for Asia. The row for each region represents all the countries in that region as an **ARRAY** of **STRUCT** elements:

```
[localhost:21000] > desc region;
+-----+-----+
| name      | type                                     |
+-----+-----+
| r_regionkey | smallint                                |
| r_name      | string                                  |
| r_comment   | string                                  |
| r_nations   | array<struct<n_nationkey:smallint,n_name:string,n_comment:string>> |
+-----+-----+
```

To find the countries within a specific region, you use a join query. To find out the order of elements in the array, you also refer to the **POS** pseudocolumn in the select list:

```
[localhost:21000] > SELECT r1.r_name, r2.n_name, r2.POS
  > FROM region r1 INNER JOIN r1.r_nations r2
  > WHERE r1.r_name = 'ASIA';
+-----+-----+-----+
| r_name | n_name  | pos |
+-----+-----+-----+
| ASIA   | VIETNAM | 0   |
| ASIA   | CHINA   | 1   |
| ASIA   | JAPAN   | 2   |
+-----+-----+-----+
```

ASIA	INDONESIA	3
ASIA	INDIA	4

Once you know the positions of the elements, you can use that information in subsequent queries, for example to change the ordering of results from the complex type column or to filter certain elements from the array:

```
[localhost:21000] > SELECT r1.r_name, r2.n_name, r2.POS
> FROM region r1 INNER JOIN r1.r_nations r2
> WHERE r1.r_name = 'ASIA'
> ORDER BY r2.POS DESC;
+-----+-----+-----+
| r_name | n_name | pos |
+-----+-----+-----+
| ASIA   | INDIA  | 4   |
| ASIA   | INDONESIA | 3   |
| ASIA   | JAPAN  | 2   |
| ASIA   | CHINA  | 1   |
| ASIA   | VIETNAM | 0   |
+-----+-----+-----+
[localhost:21000] > SELECT r1.r_name, r2.n_name, r2.POS
> FROM region r1 INNER JOIN r1.r_nations r2
> WHERE r1.r_name = 'ASIA' AND r2.POS BETWEEN 1 and 3;
+-----+-----+-----+
| r_name | n_name | pos |
+-----+-----+-----+
| ASIA   | CHINA  | 1   |
| ASIA   | JAPAN  | 2   |
| ASIA   | INDONESIA | 3   |
+-----+-----+-----+
```


KEY and VALUE Pseudocolumns

The MAP data type is suitable for representing sparse or wide data structures, where each row might only have entries for a small subset of named fields. Because the element names (the map keys) vary depending on the row, a query must be able to refer to both the key and the value parts of each key-value pair. The KEY and VALUE pseudocolumns let you refer to the parts of the key-value pair independently within the query, as `map_column.KEY` and `map_column.VALUE`.

The KEY must always be a scalar type, such as STRING, BIGINT, or TIMESTAMP. It can be NULL. Values of the KEY field are not necessarily unique within the same MAP. You apply any required DISTINCT, GROUP BY, and other clauses in the query, and loop through the result set to process all the values matching any specified keys.

The VALUE can be either a scalar type or another complex type. If the VALUE is a STRUCT, you can construct a qualified name `map_column.VALUE.struct_field` to refer to the individual fields inside the value part. If the VALUE is an ARRAY or another MAP, you must include another join condition that establishes a table alias for `map_column.VALUE`, and then construct another qualified name using that alias, for example `table_alias.ITEM` or `table_alias.KEY` and `table_alias.VALUE`

The following example shows different ways to access a MAP column using the KEY and VALUE pseudocolumns. The DETAILS column has a STRING first part with short, standardized values such as 'Recurring', 'Lucid', or 'Anxiety'. This is the "key" that is used to look up particular kinds of elements from the MAP. The second part, also a STRING, is a longer free-form explanation. Impala gives you the standard pseudocolumn names KEY and VALUE for the two parts, and you apply your own conventions and interpretations to the underlying values.



Note: If you find that the single-item nature of the VALUE makes it difficult to model your data accurately, the solution is typically to add some nesting to the complex type. For example, to have several sets of key-value pairs, make the column an ARRAY whose elements are MAP. To make a set of key-value pairs that holds more elaborate information, make a MAP column whose VALUE part contains an ARRAY or a STRUCT.

```
CREATE TABLE dream_journal
(
```

```

    dream_id BIGINT,
    details MAP <STRING,STRING>
)
STORED AS PARQUET;

-- What are all the types of dreams that are recorded?
SELECT DISTINCT details.KEY FROM dream_journal, dream_journal.details;

-- How many lucid dreams were recorded?
-- Because there is no GROUP BY, we count the 'Lucid' keys across all rows.
SELECT COUNT(details.KEY)
    FROM dream_journal, dream_journal.details
    WHERE details.KEY = 'Lucid';

-- Print a report of a subset of dreams, filtering based on both the lookup key
-- and the detailed value.
SELECT dream_id, details.KEY AS "Dream Type", details.VALUE AS "Dream Summary"
    FROM dream_journal, dream_journal.details
    WHERE
        details.KEY IN ('Happy', 'Pleasant', 'Joyous')
        AND details.VALUE LIKE '%childhood%';

```

The following example shows a more elaborate version of the previous table, where the VALUE part of the MAP entry is a STRUCT rather than a scalar type. Now instead of referring to the VALUE pseudocolumn directly, you use dot notation to refer to the STRUCT fields inside it.

```

CREATE TABLE better_dream_journal
(
    dream_id BIGINT,
    details MAP <STRING,STRUCT <summary: STRING, when_happened: TIMESTAMP, duration:
DECIMAL(5,2), woke_up: BOOLEAN> >
)
STORED AS PARQUET;

-- Do more elaborate reporting and filtering by examining multiple attributes within
the same dream.
SELECT dream_id, details.KEY AS "Dream Type", details.VALUE.summary AS "Dream Summary",
    details.VALUE.duration AS "Duration"
    FROM better_dream_journal, better_dream_journal.details
    WHERE
        details.KEY IN ('Anxiety', 'Nightmare')
        AND details.VALUE.duration > 60
        AND details.VALUE.woke_up = TRUE;

-- Remember that if the ITEM or VALUE contains a STRUCT, you can reference
-- the STRUCT fields directly without the .ITEM or .VALUE qualifier.
SELECT dream_id, details.KEY AS "Dream Type", details.summary AS "Dream Summary",
    details.duration AS "Duration"
    FROM better_dream_journal, better_dream_journal.details
    WHERE
        details.KEY IN ('Anxiety', 'Nightmare')
        AND details.duration > 60
        AND details.woke_up = TRUE;

```

Loading Data Containing Complex Types

Because the Impala INSERT statement does not currently support creating new data with complex type columns, or copying existing complex type values from one table to another, you primarily use Impala to query Parquet tables with complex types where the data was inserted through Hive, or create tables with complex types where you already have existing Parquet data files.

If you have created a Hive table with the Parquet file format and containing complex types, use the same table for Impala queries with no changes. If you have such a Hive table in some other format, use a Hive CREATE TABLE AS SELECT ... STORED AS PARQUET or INSERT ... SELECT statement to produce an equivalent Parquet table that Impala can query.

If you have existing Parquet data files containing complex types, located outside of any Impala or Hive table, such as data files created by Spark jobs, you can use an Impala `CREATE TABLE ... STORED AS PARQUET` statement, followed by an Impala `LOAD DATA` statement to move the data files into the table. As an alternative, you can use an Impala `CREATE EXTERNAL TABLE` statement to create a table pointing to the HDFS directory that already contains the data files.

Perhaps the simplest way to get started with complex type data is to take a denormalized table containing duplicated values, and use an `INSERT ... SELECT` statement to copy the data into a Parquet table and condense the repeated values into complex types. With the Hive `INSERT` statement, you use the `COLLECT_LIST()`, `NAMED_STRUCT()`, and `MAP()` constructor functions within a `GROUP BY` query to produce the complex type values. `COLLECT_LIST()` turns a sequence of values into an `ARRAY`. `NAMED_STRUCT()` uses the first, third, and so on arguments as the field names for a `STRUCT`, to match the field names from the `CREATE TABLE` statement.



Note: Because Hive currently cannot construct individual rows using complex types through the `INSERT ... VALUES` syntax, you prepare the data in flat form in a separate table, then copy it to the table with complex columns using `INSERT ... SELECT` and the complex type constructors. See [Constructing Parquet Files with Complex Columns Using Hive](#) on page 190 for examples.

Using Complex Types as Nested Types

The `ARRAY`, `STRUCT`, and `MAP` types can be the top-level types for “nested type” columns. That is, each of these types can contain other complex or scalar types, with multiple levels of nesting to a maximum depth of 100. For example, you can have an array of structures, a map containing other maps, a structure containing an array of other structures, and so on. At the lowest level, there are always scalar types making up the fields of a `STRUCT`, elements of an `ARRAY`, and keys and values of a `MAP`.

Schemas involving complex types typically use some level of nesting for the complex type columns.

For example, to model a relationship like a dimension table and a fact table, you typically use an `ARRAY` where each array element is a `STRUCT`. The `STRUCT` fields represent what would traditionally be columns in a separate joined table. It makes little sense to use a `STRUCT` as the top-level type for a column, because you could just make the fields of the `STRUCT` into regular table columns.

Perhaps the only use case for a top-level `STRUCT` would be to allow `STRUCT` fields with the same name as columns to coexist in the same table. The following example shows how a table could have a column named `ID`, and two separate `STRUCT` fields also named `ID`. Because the `STRUCT` fields are always referenced using qualified names, the identical `ID` names do not cause a conflict.

```
CREATE TABLE struct_namespaces
(
  id BIGINT
  , s1 STRUCT < id: BIGINT, field1: STRING >
  , s2 STRUCT < id: BIGINT, when_happened: TIMESTAMP >
)
STORED AS PARQUET;

select id, s1.id, s2.id from struct_namespaces;
```

It is common to make the value portion of each key-value pair in a `MAP` a `STRUCT`, `ARRAY` of `STRUCT`, or other complex type variation. That way, each key in the `MAP` can be associated with a flexible and extensible data structure. The key values are not predefined ahead of time (other than by specifying their data type). Therefore, the `MAP` can accommodate a rapidly evolving schema, or sparse data structures where each row contains only a few data values drawn from a large set of possible choices.

Although you can use an `ARRAY` of scalar values as the top-level column in a table, such a simple array is typically of limited use for analytic queries. The only property of the array elements, aside from the element value, is the ordering sequence available through the `POS` pseudocolumn. To record any additional item about each array element, such as a `TIMESTAMP` or a symbolic name, you use an `ARRAY` of `STRUCT` rather than of scalar values.

If you are considering having multiple `ARRAY` or `MAP` columns, with related items under the same position in each `ARRAY` or the same key in each `MAP`, prefer to use a `STRUCT` to group all the related items into a single `ARRAY` or `MAP`.

Doing so avoids the additional storage overhead and potential duplication of key values from having an extra complex type column. Also, because each `ARRAY` or `MAP` that you reference in the query `SELECT` list requires an additional join clause, minimizing the number of complex type columns also makes the query easier to read and maintain, relying more on dot notation to refer to the relevant fields rather than a sequence of join clauses.

For example, here is a table with several complex type columns all at the top level and containing only scalar types. To retrieve every data item for the row requires a separate join for each `ARRAY` or `MAP` column. The fields of the `STRUCT` can be referenced using dot notation, but there is no real advantage to using the `STRUCT` at the top level rather than just making separate columns `FIELD1` and `FIELD2`.

```
CREATE TABLE complex_types_top_level
(
  id BIGINT,
  a1 ARRAY<INT>,
  a2 ARRAY<STRING>,
  s STRUCT<field1: INT, field2: STRING>,
  -- Numeric lookup key for a string value.
  m1 MAP<INT,STRING>,
  -- String lookup key for a numeric value.
  m2 MAP<STRING,INT>
)
STORED AS PARQUET;
```

```
describe complex_types_top_level;
```

name	type
id	bigint
a1	array<int>
a2	array<string>
s	struct< field1:int, field2:string >
m1	map<int,string>
m2	map<string,int>

```
select
  id,
  a1.item,
  a2.item,
  s.field1,
  s.field2,
  m1.key,
  m1.value,
  m2.key,
  m2.value
from
  complex_types_top_level,
  complex_types_top_level.a1,
  complex_types_top_level.a2,
  complex_types_top_level.m1,
  complex_types_top_level.m2;
```

For example, here is a table with columns containing an `ARRAY` of `STRUCT`, a `MAP` where each key value is a `STRUCT`, and a `MAP` where each key value is an `ARRAY` of `STRUCT`.

```
CREATE TABLE nesting_demo
(
  user_id BIGINT,
  family_members ARRAY < STRUCT < name: STRING, email: STRING, date_joined: TIMESTAMP
  >>,
  foo map < STRING, STRUCT < f1: INT, f2: INT, f3: TIMESTAMP, f4: BOOLEAN >>,
  gameplay MAP < STRING , ARRAY < STRUCT <
    name: STRING, highest: BIGINT, lives_used: INT, total_spent: DECIMAL(16,2)
  >>>
)
)
```

```
STORED AS PARQUET;
```

The `DESCRIBE` statement rearranges the `<` and `>` separators and the field names within each `STRUCT` for easy readability:

```
DESCRIBE nesting_demo;
```

name	type
user_id	bigint
family_members	array<struct< name:string, email:string, date_joined:timestamp >>
foo	map<string,struct< f1:int, f2:int, f3:timestamp, f4:boolean >>
gameplay	map<string,array<struct< name:string, highest:bigint, lives_used:int, total_spent:decimal(16,2) >>>

To query the complex type columns, you use join notation to refer to the lowest-level scalar values. If the value is an `ARRAY` element, the fully qualified name includes the `ITEM` pseudocolumn. If the value is inside a `MAP`, the fully qualified name includes the `KEY` or `VALUE` pseudocolumn. Each reference to a different `ARRAY` or `MAP` (even if nested inside another complex type) requires an additional join clause.

```
SELECT
-- The lone scalar field doesn't require any dot notation or join clauses.
  user_id
-- Retrieve the fields of a STRUCT inside an ARRAY.
-- The FAMILY_MEMBERS name refers to the FAMILY_MEMBERS table alias defined later in
the FROM clause.
  , family_members.item.name
  , family_members.item.email
  , family_members.item.date_joined
-- Retrieve the KEY and VALUE fields of a MAP, with the value being a STRUCT consisting
of more fields.
-- The FOO name refers to the FOO table alias defined later in the FROM clause.
  , foo.key
  , foo.value.f1
  , foo.value.f2
  , foo.value.f3
  , foo.value.f4
-- Retrieve the KEY fields of a MAP, and expand the VALUE part into ARRAY items consisting
of STRUCT fields.
-- The GAMEPLAY name refers to the GAMEPLAY table alias defined later in the FROM clause
(referring to the MAP item).
-- The GAME_N name refers to the GAME_N table alias defined later in the FROM clause
(referring to the ARRAY
inside the MAP item's VALUE part.)
  , gameplay.key
  , game_n.name
  , game_n.highest
  , game_n.lives_used
  , game_n.total_spent
FROM
  nesting_demo
  , nesting_demo.family_members AS family_members
  , nesting_demo.foo AS foo
  , nesting_demo.gameplay AS gameplay
```

```
, nesting_demo.gameplay.value AS game_n;
```

Once you understand the notation to refer to a particular data item in the `SELECT` list, you can use the same qualified name to refer to that data item in other parts of the query, such as the `WHERE` clause, `ORDER BY` or `GROUP BY` clauses, or calls to built-in functions. For example, you might frequently retrieve the `VALUE` part of each `MAP` item in the `SELECT` list, while choosing the specific `MAP` items by running comparisons against the `KEY` part in the `WHERE` clause.

Accessing Complex Type Data in Flattened Form Using Views

The layout of complex and nested types is largely a physical consideration. The complex type columns reside in the same data files rather than in separate normalized tables, for your convenience in managing related data sets and performance in querying related data sets. You can use views to treat tables with complex types as if they were flattened. By putting the join logic and references to the complex type columns in the view definition, you can query the same tables using existing queries intended for tables containing only scalar columns. This technique also lets you use tables with complex types with BI tools that are not aware of the data types and query notation for accessing complex type columns.

For example, the variation of the TPC-H schema containing complex types has a table `REGION`. This table has 5 rows, corresponding to 5 regions such as `NORTH AMERICA` and `AFRICA`. Each row has an `ARRAY` column, where each array item is a `STRUCT` containing details about a country in that region.

```
DESCRIBE region;
+-----+-----+
| name      | type      |
+-----+-----+
| r_regionkey | smallint  |
| r_name     | string    |
| r_comment  | string    |
| r_nations  | array<struct<
|            |   n_nationkey:smallint,
|            |   n_name:string,
|            |   n_comment:string
|            | >>
+-----+-----+
```

The same data could be represented in traditional denormalized form, as a single table where the information about each region is repeated over and over, alongside the information about each country. The nested complex types let us avoid the repetition, while still keeping the data in a single table rather than normalizing across multiple tables.

To use this table with a JDBC or ODBC application that expected scalar columns, we could create a view that represented the result set as a set of scalar columns (three columns from the original table, plus three more from the `STRUCT` fields of the array elements). In the following examples, any column with an `R_*` prefix is taken unchanged from the original table, while any column with an `N_*` prefix is extracted from the `STRUCT` inside the `ARRAY`.

```
CREATE VIEW region_view AS
SELECT
  r_regionkey,
  r_name,
  r_comment,
  array_field.item.n_nationkey AS n_nationkey,
  array_field.item.n_name AS n_name,
  array_field.n_comment AS n_comment
FROM
  region, region.r_nations AS array_field;
```

Then we point the application queries at the view rather than the original table. From the perspective of the view, there are 25 rows in the result set, one for each nation in each region, and queries can refer freely to fields related to the region or the nation.

```
-- Retrieve info such as the nation name from the original R_NATIONS array elements.
select n_name from region_view where r_name in ('EUROPE', 'ASIA');
+-----+
```

n_name
UNITED KINGDOM
RUSSIA
ROMANIA
GERMANY
FRANCE
VIETNAM
CHINA
JAPAN
INDONESIA
INDIA

```
-- UNITED STATES in AMERICA and UNITED KINGDOM in EUROPE.
SELECT DISTINCT r_name FROM region_view WHERE n_name LIKE 'UNITED%';
```

r_name
AMERICA
EUROPE

```
-- For conciseness, we only list some view columns in the SELECT list.
-- SELECT * would bring back all the data, unlike SELECT *
-- queries on the original table with complex type columns.
```

```
SELECT r_regionkey, r_name, n_nationkey, n_name FROM region_view LIMIT 7;
```

r_regionkey	r_name	n_nationkey	n_name
3	EUROPE	23	UNITED KINGDOM
3	EUROPE	22	RUSSIA
3	EUROPE	19	ROMANIA
3	EUROPE	7	GERMANY
3	EUROPE	6	FRANCE
2	ASIA	21	VIETNAM
2	ASIA	18	CHINA

Tutorials and Examples for Complex Types

The following examples illustrate the query syntax for some common use cases involving complex type columns.

Sample Schema and Data for Experimenting with Impala Complex Types

The tables used for earlier examples of complex type syntax are trivial ones with no actual data. The more substantial examples of the complex type feature use these tables, adapted from the schema used for TPC-H testing:

```
SHOW TABLES;
```

name
customer
part
region
supplier

```
DESCRIBE customer;
```

name	type
c_custkey	bigint
c_name	string
c_address	string
c_nationkey	smallint
c_phone	string
c_acctbal	decimal(12,2)
c_mktsegment	string
c_comment	string
c_orders	array<struct< o_orderkey:bigint,

```

o_orderstatus:string,
o_totalprice:decimal(12,2),
o_orderdate:string,
o_orderpriority:string,
o_clerk:string,
o_shippriority:int,
o_comment:string,
o_lineitems:array<struct<
  l_partkey:bigint,
  l_suppkey:bigint,
  l_linenum: int,
  l_quantity:decimal(12,2),
  l_extendedprice:decimal(12,2),
  l_discount:decimal(12,2),
  l_tax:decimal(12,2),
  l_returnflag:string,
  l_linestatus:string,
  l_shipdate:string,
  l_commitdate:string,
  l_receiptdate:string,
  l_shipinstruct:string,
  l_shipmode:string,
  l_comment:string
>>
>>

```

```
DESCRIBE part;
```

name	type
p_partkey	bigint
p_name	string
p_mfgr	string
p_brand	string
p_type	string
p_size	int
p_container	string
p_retailprice	decimal(12,2)
p_comment	string

```
DESCRIBE region;
```

name	type
r_regionkey	smallint
r_name	string
r_comment	string
r_nations	array<struct<n_nationkey:smallint,n_name:string,n_comment:string>>

```
DESCRIBE supplier;
```

name	type
s_suppkey	bigint
s_name	string
s_address	string
s_nationkey	smallint
s_phone	string
s_acctbal	decimal(12,2)
s_comment	string
s_partsupps	array<struct<ps_partkey:bigint,ps_availqty:int,ps_supplycost:decimal(12,2),ps_comment:string>>

The volume of data used in the following examples is:

```

SELECT count(*) FROM customer;
+-----+
| count(*) |
+-----+
| 150000   |
+-----+

SELECT count(*) FROM part;
+-----+
| count(*) |
+-----+
| 200000   |
+-----+

SELECT count(*) FROM region;
+-----+
| count(*) |
+-----+
| 5        |
+-----+

SELECT count(*) FROM supplier;
+-----+
| count(*) |
+-----+
| 10000    |
+-----+

```

Constructing Parquet Files with Complex Columns Using Hive

The following examples demonstrate the Hive syntax to transform flat data (tables with all scalar columns) into Parquet tables where Impala can query the complex type columns. Each example shows the full sequence of steps, including switching back and forth between Impala and Hive. Although the source table can use any file format, the destination table must use the Parquet file format.

Create table with `ARRAY` in Impala, load data in Hive, query in Impala:

This example shows the cycle of creating the tables and querying the complex data in Impala, and using Hive (either the `hive` shell or `beeline`) for the data loading step. The data starts in flattened, denormalized form in a text table. Hive writes the corresponding Parquet data, including an `ARRAY` column. Then Impala can run analytic queries on the Parquet table, using join notation to unpack the `ARRAY` column.

```

/* Initial DDL and loading of flat, denormalized data happens in impala-shell */CREATE
TABLE flat_array (country STRING, city STRING);INSERT INTO flat_array VALUES
  ('Canada', 'Toronto'), ('Canada', 'Vancouver'), ('Canada', "St. John's")
  , ('Canada', 'Saint John'), ('Canada', 'Montreal'), ('Canada', 'Halifax')
  , ('Canada', 'Winnipeg'), ('Canada', 'Calgary'), ('Canada', 'Saskatoon')
  , ('Canada', 'Ottawa'), ('Canada', 'Yellowknife'), ('France', 'Paris')
  , ('France', 'Nice'), ('France', 'Marseilles'), ('France', 'Cannes')
  , ('Greece', 'Athens'), ('Greece', 'Piraeus'), ('Greece', 'Hania')
  , ('Greece', 'Heraklion'), ('Greece', 'Rethymnon'), ('Greece', 'Fira');

CREATE TABLE complex_array (country STRING, city ARRAY <STRING>) STORED AS PARQUET;

```

```

/* Conversion to Parquet and complex and/or nested columns happens in Hive */

INSERT INTO complex_array SELECT country, collect_list(city) FROM flat_array GROUP BY
country;
Query ID = dev_20151108160808_84477ff2-82bd-4ba4-9a77-554fa7b8c0cb
Total jobs = 1
Launching Job 1 out of 1

```

...

```

/* Back to impala-shell again for analytic queries */

REFRESH complex_array;
SELECT country, city.item FROM complex_array, complex_array.city
+-----+-----+
| country | item |
+-----+-----+
| Canada | Toronto |
| Canada | Vancouver |
| Canada | St. John's |
| Canada | Saint John |
| Canada | Montreal |
| Canada | Halifax |
| Canada | Winnipeg |
| Canada | Calgary |
| Canada | Saskatoon |
| Canada | Ottawa |
| Canada | Yellowknife |
| France | Paris |
| France | Nice |
| France | Marseilles |
| France | Cannes |
| Greece | Athens |
| Greece | Piraeus |
| Greece | Hania |
| Greece | Heraklion |
| Greece | Rethymnon |
| Greece | Fira |
+-----+-----+

```

Create table with STRUCT and ARRAY in Impala, load data in Hive, query in Impala:

This example shows the cycle of creating the tables and querying the complex data in Impala, and using Hive (either the hive shell or beeline) for the data loading step. The data starts in flattened, denormalized form in a text table. Hive writes the corresponding Parquet data, including a STRUCT column with an ARRAY field. Then Impala can run analytic queries on the Parquet table, using join notation to unpack the ARRAY field from the STRUCT column.

```

/* Initial DDL and loading of flat, denormalized data happens in impala-shell */

CREATE TABLE flat_struct_array (continent STRING, country STRING, city STRING);
INSERT INTO flat_struct_array VALUES
  ('North America', 'Canada', 'Toronto') , ('North America', 'Canada', 'Vancouver')
  , ('North America', 'Canada', "St. John's") , ('North America', 'Canada', 'Saint
John')
  , ('North America', 'Canada', 'Montreal') , ('North America', 'Canada', 'Halifax')
  , ('North America', 'Canada', 'Winnipeg') , ('North America', 'Canada', 'Calgary')
  , ('North America', 'Canada', 'Saskatoon') , ('North America', 'Canada', 'Ottawa')
  , ('North America', 'Canada', 'Yellowknife') , ('Europe', 'France', 'Paris')
  , ('Europe', 'France', 'Nice') , ('Europe', 'France', 'Marseilles')
  , ('Europe', 'France', 'Cannes') , ('Europe', 'Greece', 'Athens')
  , ('Europe', 'Greece', 'Piraeus') , ('Europe', 'Greece', 'Hania')
  , ('Europe', 'Greece', 'Heraklion') , ('Europe', 'Greece', 'Rethymnon')
  , ('Europe', 'Greece', 'Fira');

CREATE TABLE complex_struct_array (continent STRING, country STRUCT <name: STRING, city:
ARRAY <STRING> >) STORED AS PARQUET;

```

```

/* Conversion to Parquet and complex and/or nested columns happens in Hive */

INSERT INTO complex_struct_array SELECT continent, named_struct('name', country, 'city',
collect_list(city)) FROM flat_array_array GROUP BY continent, country;
Query ID = dev_20151108163535_11a4fa53-0003-4638-97e6-ef13cdb8e09e
Total jobs = 1
Launching Job 1 out of 1

```

...

```
/* Back to impala-shell again for analytic queries */
```

```
REFRESH complex_struct_array;
SELECT t1.continent, t1.country.name, t2.item
FROM complex_struct_array t1, t1.country.city t2
```

continent	country.name	item
Europe	France	Paris
Europe	France	Nice
Europe	France	Marseilles
Europe	France	Cannes
Europe	Greece	Athens
Europe	Greece	Piraeus
Europe	Greece	Hania
Europe	Greece	Heraklion
Europe	Greece	Rethymnon
Europe	Greece	Fira
North America	Canada	Toronto
North America	Canada	Vancouver
North America	Canada	St. John's
North America	Canada	Saint John
North America	Canada	Montreal
North America	Canada	Halifax
North America	Canada	Winnipeg
North America	Canada	Calgary
North America	Canada	Saskatoon
North America	Canada	Ottawa
North America	Canada	Yellowknife

Flattening Normalized Tables into a Single Table with Complex Types

One common use for complex types is to embed the contents of one table into another. The traditional technique of denormalizing results in a huge number of rows with some column values repeated over and over. With complex types, you can keep the same number of rows as in the original normalized table, and put all the associated data from the other table in a single new column.

In this flattening scenario, you might frequently use a column that is an `ARRAY` consisting of `STRUCT` elements, where each field within the `STRUCT` corresponds to a column name from the table that you are combining.

The following example shows a traditional normalized layout using two tables, and then an equivalent layout using complex types in a single table.

```
/* Traditional relational design */
```

```
-- This table just stores numbers, allowing us to look up details about the employee
-- and details about their vacation time using a three-table join query.
```

```
CREATE table employee_vacations
```

```
(
  employee_id BIGINT,
  vacation_id BIGINT
)
```

```
STORED AS PARQUET;
```

```
-- Each kind of information to track gets its own "fact table".
```

```
CREATE table vacation_details
```

```
(
  vacation_id BIGINT,
  vacation_start TIMESTAMP,
  duration INT
)
```

```
STORED AS PARQUET;
```

```
-- Any time we print a human-readable report, we join with this table to
-- display info about employee #1234.
```



```

CREATE TABLE employee_contact
(
  employee_id BIGINT,
  name STRING,
  address STRING,
  phone STRING,
  email STRING,
  address_type STRING /* 'home', 'work', 'remote', etc. */
)
STORED AS PARQUET;

/* Equivalent flattened schema using complex types */

-- For analytic queries using complex types, we can bundle the dimension table
-- and multiple fact tables into a single table.
CREATE TABLE employee_vacations_nested_types
(
  -- We might still use the employee_id for other join queries.
  -- The table needs at least one scalar column to serve as an identifier
  -- for the complex type columns.
  employee_id BIGINT,

  -- Columns of the VACATION_DETAILS table are folded into a STRUCT.
  -- We drop the VACATION_ID column because Impala doesn't need
  -- synthetic IDs to join a complex type column.
  -- Each row from the VACATION_DETAILS table becomes an array element.
  vacation ARRAY < STRUCT <
    vacation_start: TIMESTAMP,
    duration: INT
  >>,

  -- The ADDRESS_TYPE column, with a small number of predefined values that are distinct
  -- for each employee, makes the EMPLOYEE_CONTACT table a good candidate to turn into a
  MAP,
  -- with each row represented as a STRUCT. The string value from ADDRESS_TYPE becomes
  the
  -- "key" (the anonymous first field) of the MAP.
  contact MAP < STRING, STRUCT <
    address: STRING,
    phone: STRING,
    email: STRING
  >>
)
STORED AS PARQUET;

```

Interchanging Complex Type Tables and Data Files with Hive and Other Components

You can produce Parquet data files through several Hadoop components and APIs, as explained in http://www.cloudera.com/documentation/enterprise/latest/topics/cdh_ig_parquet.html.

If you have a Hive-created Parquet table that includes ARRAY, STRUCT, or MAP columns, Impala can query that same table in Impala 2.3 / CDH 5.5 and higher, subject to the usual restriction that all other columns are of data types supported by Impala, and also that the file type of the table must be Parquet.

If you have a Parquet data file produced outside of Impala, Impala can automatically deduce the appropriate table structure using the syntax `CREATE TABLE ... LIKE PARQUET 'hdfs_path_of_parquet_file'`. In Impala 2.3 / CDH 5.5 and higher, this feature works for Parquet files that include ARRAY, STRUCT, or MAP types.

```

/* In impala-shell, find the HDFS data directory of the original table.
DESCRIBE FORMATTED tpch_nested_parquet.customer;
...
| Location: | hdfs://localhost:20500/test-warehouse/tpch_nested_parquet.db/customer
| NULL |
...

# In the Unix shell, find the path of any Parquet data file in that HDFS directory.
$ hdfs dfs -ls hdfs://localhost:20500/test-warehouse/tpch_nested_parquet.db/customer
Found 4 items
-rwxr-xr-x  3 dev supergroup  171298918 2015-09-22 23:30
hdfs://localhost:20500/blah/tpch_nested_parquet.db/customer/000000_0

```

...

```
/* Back in impala-shell, use the HDFS path in a CREATE TABLE LIKE PARQUET statement. */
CREATE TABLE customer_ctlp
  LIKE PARQUET 'hdfs://localhost:20500/blah/tpch_nested_parquet.db/customer/000000_0'
  STORED AS PARQUET;
```

```
/* Confirm that old and new tables have the same column layout, including complex types.
*/
DESCRIBE tpch_nested_parquet.customer
```

name	type	comment
c_custkey	bigint	
c_name	string	
c_address	string	
c_nationkey	smallint	
c_phone	string	
c_acctbal	decimal(12,2)	
c_mktsegment	string	
c_comment	string	
c_orders	array<struct< o_orderkey:bigint, o_orderstatus:string, o_totalprice:decimal(12,2), o_orderdate:string, o_orderpriority:string, o_clerk:string, o_shippriority:int, o_comment:string, o_lineitems:array<struct< l_partkey:bigint, l_suppkey:bigint, l_linenumber:int, l_quantity:decimal(12,2), l_extendedprice:decimal(12,2), l_discount:decimal(12,2), l_tax:decimal(12,2), l_returnflag:string, l_linestatus:string, l_shipdate:string, l_commitdate:string, l_receiptdate:string, l_shipinstruct:string, l_shipmode:string, l_comment:string >> >>	

```
describe customer_ctlp;
```

name	type	comment
c_custkey	bigint	Inferred from Parquet file.
c_name	string	Inferred from Parquet file.
c_address	string	Inferred from Parquet file.
c_nationkey	int	Inferred from Parquet file.
c_phone	string	Inferred from Parquet file.
c_acctbal	decimal(12,2)	Inferred from Parquet file.
c_mktsegment	string	Inferred from Parquet file.
c_comment	string	Inferred from Parquet file.
c_orders	array<struct< o_orderkey:bigint, o_orderstatus:string, o_totalprice:decimal(12,2), o_orderdate:string, o_orderpriority:string, o_clerk:string, o_shippriority:int, o_comment:string, o_lineitems:array<struct< l_partkey:bigint,	Inferred from Parquet file.

```

l_suppkey:bigint,
l_linenum: int,
l_quantity:decimal(12,2),
l_extendedprice:decimal(12,2),
l_discount:decimal(12,2),
l_tax:decimal(12,2),
l_returnflag:string,
l_linestatus:string,
l_shipdate:string,
l_commitdate:string,
l_receiptdate:string,
l_shipinstruct:string,
l_shipmode:string,
l_comment:string
>>
>>

```

Literals

Each of the Impala data types has corresponding notation for literal values of that type. You specify literal values in SQL statements, such as in the `SELECT` list or `WHERE` clause of a query, or as an argument to a function call. See [Data Types](#) on page 126 for a complete list of types, ranges, and conversion rules.

Numeric Literals

To write literals for the integer types (`TINYINT`, `SMALLINT`, `INT`, and `BIGINT`), use a sequence of digits with optional leading zeros.

To write literals for the floating-point types (`DECIMAL`, `FLOAT`, and `DOUBLE`), use a sequence of digits with an optional decimal point (`.` character). To preserve accuracy during arithmetic expressions, Impala interprets floating-point literals as the `DECIMAL` type with the smallest appropriate precision and scale, until required by the context to convert the result to `FLOAT` or `DOUBLE`.

Integer values are promoted to floating-point when necessary, based on the context.

You can also use exponential notation by including an `e` character. For example, `1e6` is 1 times 10 to the power of 6 (1 million). A number in exponential notation is always interpreted as floating-point.

When Impala encounters a numeric literal, it considers the type to be the “smallest” that can accurately represent the value. The type is promoted to larger or more accurate types if necessary, based on subsequent parts of an expression.

For example, you can see by the types Impala defines for the following table columns how it interprets the corresponding numeric literals:

```

[localhost:21000] > create table ten as select 10 as x;
+-----+
| summary |
+-----+
| Inserted 1 row(s) |
+-----+
[localhost:21000] > desc ten;
+-----+-----+-----+
| name | type | comment |
+-----+-----+-----+
| x | tinyint | |
+-----+-----+-----+

[localhost:21000] > create table four_k as select 4096 as x;
+-----+
| summary |
+-----+
| Inserted 1 row(s) |
+-----+
[localhost:21000] > desc four_k;

```

```

+-----+-----+-----+
| name | type      | comment |
+-----+-----+-----+
| x    | smallint  |         |
+-----+-----+-----+

[localhost:21000] > create table one_point_five as select 1.5 as x;
+-----+-----+
| summary |
+-----+
| Inserted 1 row(s) |
+-----+
[localhost:21000] > desc one_point_five;
+-----+-----+-----+
| name | type          | comment |
+-----+-----+-----+
| x    | decimal(2,1) |         |
+-----+-----+-----+

[localhost:21000] > create table one_point_three_three_three as select 1.333 as x;
+-----+-----+
| summary |
+-----+
| Inserted 1 row(s) |
+-----+
[localhost:21000] > desc one_point_three_three_three;
+-----+-----+-----+
| name | type          | comment |
+-----+-----+-----+
| x    | decimal(4,3) |         |
+-----+-----+-----+

```

String Literals

String literals are quoted using either single or double quotation marks. You can use either kind of quotes for string literals, even both kinds for different literals within the same statement.

Quoted literals are considered to be of type `STRING`. To use quoted literals in contexts requiring a `CHAR` or `VARCHAR` value, `CAST()` the literal to a `CHAR` or `VARCHAR` of the appropriate length.

Escaping special characters:

To encode special characters within a string literal, precede them with the backslash (`\`) escape character:

- `\t` represents a tab.
- `\n` represents a newline or linefeed. This might cause extra line breaks in `impala-shell` output.
- `\r` represents a carriage return. This might cause unusual formatting (making it appear that some content is overwritten) in `impala-shell` output.
- `\b` represents a backspace. This might cause unusual formatting (making it appear that some content is overwritten) in `impala-shell` output.
- `\0` represents an ASCII `nul` character (not the same as a SQL `NULL`). This might not be visible in `impala-shell` output.
- `\Z` represents a DOS end-of-file character. This might not be visible in `impala-shell` output.
- `\%` and `_` can be used to escape wildcard characters within the string passed to the `LIKE` operator.
- `\` followed by 3 octal digits represents the ASCII code of a single character; for example, `\101` is ASCII 65, the character `A`.
- Use two consecutive backslashes (`\\`) to prevent the backslash from being interpreted as an escape character.
- Use the backslash to escape single or double quotation mark characters within a string literal, if the literal is enclosed by the same type of quotation mark.
- If the character following the `\` does not represent the start of a recognized escape sequence, the character is passed through unchanged.

Quotes within quotes:

To include a single quotation character within a string value, enclose the literal with either single or double quotation marks, and optionally escape the single quote as a `\'` sequence. Earlier releases required escaping a single quote inside double quotes. Continue using escape sequences in this case if you also need to run your SQL code on older versions of Impala.

To include a double quotation character within a string value, enclose the literal with single quotation marks, no escaping is necessary in this case. Or, enclose the literal with double quotation marks and escape the double quote as a `\"` sequence.

```
[localhost:21000] > select "What\'s happening?" as single_within_double,
>         'I\'m not sure.' as single_within_single,
>         "Homer wrote \"The Iliad\"." as double_within_double,
>         'Homer also wrote "The Odyssey".' as double_within_single;
+-----+-----+-----+-----+
| single_within_double | single_within_single | double_within_double | double_within_single |
+-----+-----+-----+-----+
| What's happening?   | I'm not sure.        | Homer wrote "The Iliad". | Homer also wrote "The Odyssey". |
+-----+-----+-----+-----+
```

Field terminator character in CREATE TABLE:



Note: The `CREATE TABLE` clauses `FIELDS TERMINATED BY`, `ESCAPED BY`, and `LINES TERMINATED BY` have special rules for the string literal used for their argument, because they all require a single character. You can use a regular character surrounded by single or double quotation marks, an octal sequence such as `'\054'` (representing a comma), or an integer in the range `'-127'..'128'` (with quotation marks but no backslash), which is interpreted as a single-byte ASCII character. Negative values are subtracted from 256; for example, `FIELDS TERMINATED BY '-2'` sets the field delimiter to ASCII code 254, the “Icelandic Thorn” character used as a delimiter by some data formats.

impala-shell considerations:

When dealing with output that includes non-ASCII or non-printable characters such as linefeeds and backspaces, use the `impala-shell` options to save to a file, turn off pretty printing, or both rather than relying on how the output appears visually. See [impala-shell Configuration Options](#) on page 511 for a list of `impala-shell` options.

Boolean Literals

For `BOOLEAN` values, the literals are `TRUE` and `FALSE`, with no quotation marks and case-insensitive.

Examples:

```
select true;
select * from t1 where assertion = false;
select case bool_col when true then 'yes' when false 'no' else 'null' end from t1;
```

Timestamp Literals

Impala automatically converts `STRING` literals of the correct format into `TIMESTAMP` values. Timestamp values are accepted in the format `"YYYY-MM-dd HH:mm:ss.SSSSS"`, and can consist of just the date, or just the time, with or without the fractional second portion. For example, you can specify `TIMESTAMP` values such as `'1966-07-30'`, `'08:30:00'`, or `'1985-09-25 17:45:30.005'`. Casting an integer or floating-point value `N` to `TIMESTAMP` produces a value that is `N` seconds past the start of the epoch date (January 1, 1970). By default, the result value represents a date and time in the UTC time zone. If the setting `--use_local_tz_for_unix_timestamp_conversions=true` is in effect, the resulting `TIMESTAMP` represents a date and time in the local time zone.

You can also use `INTERVAL` expressions to add or subtract from timestamp literal values, such as `CAST('1966-07-30' AS TIMESTAMP) + INTERVAL 5 YEARS + INTERVAL 3 DAYS`. See [TIMESTAMP Data Type](#) on page 158 for details.

Depending on your data pipeline, you might receive date and time data as text, in notation that does not exactly match the format for Impala `TIMESTAMP` literals. See [Impala Date and Time Functions](#) on page 398 for functions that can convert between a variety of string literals (including different field order, separators, and timezone notation) and equivalent `TIMESTAMP` or numeric values.

NULL

The notion of `NULL` values is familiar from all kinds of database systems, but each SQL dialect can have its own behavior and restrictions on `NULL` values. For Big Data processing, the precise semantics of `NULL` values are significant: any misunderstanding could lead to inaccurate results or misformatted data, that could be time-consuming to correct for large data sets.

- `NULL` is a different value than an empty string. The empty string is represented by a string literal with nothing inside, `"` or `'`.
- In a delimited text file, the `NULL` value is represented by the special token `\N`.
- When Impala inserts data into a partitioned table, and the value of one of the partitioning columns is `NULL` or the empty string, the data is placed in a special partition that holds only these two kinds of values. When these values are returned in a query, the result is `NULL` whether the value was originally `NULL` or an empty string. This behavior is compatible with the way Hive treats `NULL` values in partitioned tables. Hive does not allow empty strings as partition keys, and it returns a string value such as `__HIVE_DEFAULT_PARTITION__` instead of `NULL` when such values are returned from a query. For example:

```
create table t1 (i int) partitioned by (x int, y string);
-- Select an INT column from another table, with all rows going into a special HDFS
subdirectory
-- named __HIVE_DEFAULT_PARTITION__. Depending on whether one or both of the partitioning
keys
-- are null, this special directory name occurs at different levels of the physical data
directory
-- for the table.
insert into t1 partition(x=NULL, y=NULL) select c1 from some_other_table;
insert into t1 partition(x, y=NULL) select c1, c2 from some_other_table;
insert into t1 partition(x=NULL, y) select c1, c3 from some_other_table;
```

- There is no `NOT NULL` clause when defining a column to prevent `NULL` values in that column.
- There is no `DEFAULT` clause to specify a non-`NULL` default value.
- If an `INSERT` operation mentions some columns but not others, the unmentioned columns contain `NULL` for all inserted rows.
- In Impala 1.2.1 and higher, all `NULL` values come at the end of the result set for `ORDER BY ... ASC` queries, and at the beginning of the result set for `ORDER BY ... DESC` queries. In effect, `NULL` is considered greater than all other values for sorting purposes. The original Impala behavior always put `NULL` values at the end, even for `ORDER BY ... DESC` queries. The new behavior in Impala 1.2.1 makes Impala more compatible with other popular database systems. In Impala 1.2.1 and higher, you can override or specify the sorting behavior for `NULL` by adding the clause `NULLS FIRST` or `NULLS LAST` at the end of the `ORDER BY` clause.



Note: Because the `NULLS FIRST` and `NULLS LAST` keywords are not currently available in Hive queries, any views you create using those keywords will not be available through Hive.

- In all other contexts besides sorting with `ORDER BY`, comparing a `NULL` to anything else returns `NULL`, making the comparison meaningless. For example, `10 > NULL` produces `NULL`, `10 < NULL` also produces `NULL`, `BETWEEN 1 AND NULL` produces `NULL`, and so on.

Several built-in functions serve as shorthand for evaluating expressions and returning `NULL`, `0`, or some other substitution value depending on the expression result: `ifnull()`, `isnull()`, `nvl()`, `nullif()`, `nullifzero()`, and `zeroifnull()`. See [Impala Conditional Functions](#) on page 427 for details.

SQL Operators

SQL operators are a class of comparison functions that are widely used within the `WHERE` clauses of `SELECT` statements.

Arithmetic Operators

The arithmetic operators use expressions with a left-hand argument, the operator, and then (in most cases) a right-hand argument.

Syntax:

```
left_hand_arg binary_operator right_hand_arg
unary_operator single_arg
```

- `+` and `-`: Can be used either as unary or binary operators.
 - With unary notation, such as `+5`, `-2.5`, or `-col_name`, they multiply their single numeric argument by `+1` or `-1`. Therefore, unary `+` returns its argument unchanged, while unary `-` flips the sign of its argument. Although you can double up these operators in expressions such as `++5` (always positive) or `--2` or `+-2` (both always negative), you cannot double the unary minus operator because `--` is interpreted as the start of a comment. (You can use a double unary minus operator if you separate the `-` characters, for example with a space or parentheses.)
 - With binary notation, such as `2+2`, `5-2.5`, or `col1 + col2`, they add or subtract respectively the right-hand argument to (or from) the left-hand argument. Both arguments must be of numeric types.

- `*` and `/`: Multiplication and division respectively. Both arguments must be of numeric types.

When multiplying, the shorter argument is promoted if necessary (such as `SMALLINT` to `INT` or `BIGINT`, or `FLOAT` to `DOUBLE`), and then the result is promoted again to the next larger type. Thus, multiplying a `TINYINT` and an `INT` produces a `BIGINT` result. Multiplying a `FLOAT` and a `FLOAT` produces a `DOUBLE` result. Multiplying a `FLOAT` and a `DOUBLE` or a `DOUBLE` and a `DOUBLE` produces a `DECIMAL(38,17)`, because `DECIMAL` values can represent much larger and more precise values than `DOUBLE`.

When dividing, Impala always treats the arguments and result as `DOUBLE` values to avoid losing precision. If you need to insert the results of a division operation into a `FLOAT` column, use the `CAST()` function to convert the result to the correct type.

- `DIV`: Integer division. Arguments are not promoted to a floating-point type, and any fractional result is discarded. For example, `13 DIV 7` returns 1, `14 DIV 7` returns 2, and `15 DIV 7` returns 2. This operator is the same as the `QUOTIENT()` function.
- `%`: Modulo operator. Returns the remainder of the left-hand argument divided by the right-hand argument. Both arguments must be of one of the integer types.
- `&`, `|`, `~`, and `^`: Bitwise operators that return the logical AND, logical OR, NOT, or logical XOR (exclusive OR) of their argument values. Both arguments must be of one of the integer types. If the arguments are of different type, the argument with the smaller type is implicitly extended to match the argument with the longer type.

You can chain a sequence of arithmetic expressions, optionally grouping them with parentheses.

The arithmetic operators generally do not have equivalent calling conventions using functional notation. For example, prior to Impala 2.2.0 / CDH 5.4.0, there is no `MOD()` function equivalent to the `%` modulo operator. Conversely, there are some arithmetic functions that do not have a corresponding operator. For example, for exponentiation you use the `POW()` function, but there is no `**` exponentiation operator. See [Impala Mathematical Functions](#) on page 374 for the arithmetic functions you can use.

Complex type considerations:

To access a column with a complex type (`ARRAY`, `STRUCT`, or `MAP`) in an aggregation function, you unpack the individual elements using join notation in the query, and then apply the function to the final scalar item, field, key, or value at

the bottom of any nested type hierarchy in the column. See [Complex Types \(CDH 5.5 or higher only\)](#) on page 167 for details about using complex types in Impala.

The following example demonstrates calls to several aggregation functions using values from a column containing nested complex types (an ARRAY of STRUCT items). The array is unpacked inside the query using join notation. The array elements are referenced using the ITEM pseudocolumn, and the structure fields inside the array elements are referenced using dot notation. Numeric values such as SUM() and AVG() are computed using the numeric R_NATIONKEY field, and the general-purpose MAX() and MIN() values are computed from the string N_NAME field.

```
describe region;
```

name	type	comment
r_regionkey	smallint	
r_name	string	
r_comment	string	
r_nations	array<struct< n_nationkey:smallint, n_name:string, n_comment:string >>	

```
select r_name, r_nations.item.n_nationkey
  from region, region.r_nations as r_nations
 order by r_name, r_nations.item.n_nationkey;
```

r_name	item.n_nationkey
AFRICA	0
AFRICA	5
AFRICA	14
AFRICA	15
AFRICA	16
AMERICA	1
AMERICA	2
AMERICA	3
AMERICA	17
AMERICA	24
ASIA	8
ASIA	9
ASIA	12
ASIA	18
ASIA	21
EUROPE	6
EUROPE	7
EUROPE	19
EUROPE	22
EUROPE	23
MIDDLE EAST	4
MIDDLE EAST	10
MIDDLE EAST	11
MIDDLE EAST	13
MIDDLE EAST	20

```
select
  r_name,
  count(r_nations.item.n_nationkey) as count,
  sum(r_nations.item.n_nationkey) as sum,
  avg(r_nations.item.n_nationkey) as avg,
  min(r_nations.item.n_name) as minimum,
  max(r_nations.item.n_name) as maximum,
  ndv(r_nations.item.n_nationkey) as distinct_vals
from
  region, region.r_nations as r_nations
group by r_name
order by r_name;
```

r_name	count	sum	avg	minimum	maximum	distinct_vals
AFRICA	5	50	10	ALGERIA	MOZAMBIQUE	5

AMERICA	5	47	9.4	ARGENTINA	UNITED STATES	5
ASIA	5	68	13.6	CHINA	VIETNAM	5
EUROPE	5	77	15.4	FRANCE	UNITED KINGDOM	5
MIDDLE EAST	5	58	11.6	EGYPT	SAUDI ARABIA	5

You cannot refer to a column with a complex data type (ARRAY, STRUCT, or MAP) directly in an operator. You can apply operators only to scalar values that make up a complex type (the fields of a STRUCT, the items of an ARRAY, or the key or value portion of a MAP) as part of a join query that refers to the scalar value using the appropriate dot notation or ITEM, KEY, or VALUE pseudocolumn names.

The following example shows how to do an arithmetic operation using a numeric field of a STRUCT type that is an item within an ARRAY column. Once the scalar numeric value `R_NATIONKEY` is extracted, it can be used in an arithmetic expression, such as multiplying by 10:

```
-- The SMALLINT is a field within an array of structs.
describe region;
```

name	type	comment
r_regionkey	smallint	
r_name	string	
r_comment	string	
r_nations	array<struct< n_nationkey:smallint, n_name:string, n_comment:string >>	

```
-- When we refer to the scalar value using dot notation,
-- we can use arithmetic and comparison operators on it
-- like any other number.
select r_name, nation.item.n_name, nation.item.n_nationkey * 10
from region, region.r_nations as nation
where nation.item.n_nationkey < 5;
```

r_name	item.n_name	nation.item.n_nationkey * 10
AMERICA	CANADA	30
AMERICA	BRAZIL	20
AMERICA	ARGENTINA	10
MIDDLE EAST	EGYPT	40
AFRICA	ALGERIA	0

BETWEEN Operator

In a WHERE clause, compares an expression to both a lower and upper bound. The comparison is successful if the expression is greater than or equal to the lower bound, and less than or equal to the upper bound. If the bound values are switched, so the lower bound is greater than the upper bound, does not match any values.

Syntax:

```
expression BETWEEN lower_bound AND upper_bound
```

Data types: Typically used with numeric data types. Works with any data type, although not very practical for BOOLEAN values. (BETWEEN false AND true will match all BOOLEAN values.) Use CAST() if necessary to ensure the lower and upper bound values are compatible types. Call string or date/time functions if necessary to extract or transform the relevant portion to compare, especially if the value can be transformed into a number.

Usage notes:

Be careful when using short string operands. A longer string that starts with the upper bound value will not be included, because it is considered greater than the upper bound. For example, BETWEEN 'A' and 'M' would not match the

string value 'Midway'. Use functions such as `upper()`, `lower()`, `substr()`, `trim()`, and so on if necessary to ensure the comparison works as expected.

Complex type considerations:

You cannot refer to a column with a complex data type (ARRAY, STRUCT, or MAP) directly in an operator. You can apply operators only to scalar values that make up a complex type (the fields of a STRUCT, the items of an ARRAY, or the key or value portion of a MAP) as part of a join query that refers to the scalar value using the appropriate dot notation or ITEM, KEY, or VALUE pseudocolumn names.

Examples:

```
-- Retrieve data for January through June, inclusive.
select c1 from t1 where month between 1 and 6;

-- Retrieve data for names beginning with 'A' through 'M' inclusive.
-- Only test the first letter to ensure all the values starting with 'M' are matched.
-- Do a case-insensitive comparison to match names with various capitalization
conventions.
select last_name from customers where upper(substr(last_name,1,1)) between 'A' and 'M';

-- Retrieve data for only the first week of each month.
select count(distinct visitor_id) from web_traffic where dayofmonth(when_viewed) between
1 and 7;
```

The following example shows how to do a BETWEEN comparison using a numeric field of a STRUCT type that is an item within an ARRAY column. Once the scalar numeric value R_NATIONKEY is extracted, it can be used in a comparison operator:

```
-- The SMALLINT is a field within an array of structs.
describe region;
```

name	type	comment
r_regionkey	smallint	
r_name	string	
r_comment	string	
r_nations	array<struct< n_nationkey:smallint, n_name:string, n_comment:string >>	

```
-- When we refer to the scalar value using dot notation,
-- we can use arithmetic and comparison operators on it
-- like any other number.
select r_name, nation.item.n_name, nation.item.n_nationkey
from region, region.r_nations as nation
where nation.item.n_nationkey between 3 and 5
```

r_name	item.n_name	item.n_nationkey
AMERICA	CANADA	3
MIDDLE EAST	EGYPT	4
AFRICA	ETHIOPIA	5

Comparison Operators

Impala supports the familiar comparison operators for checking equality and sort order for the column data types:

Syntax:

```
left_hand_expression comparison_operator right_hand_expression
```

- =, !=, <>: apply to all scalar types.

- <, <=, >, >=: apply to all scalar types; for BOOLEAN, TRUE is considered greater than FALSE.

Alternatives:

The `IN` and `BETWEEN` operators provide shorthand notation for expressing combinations of equality, less than, and greater than comparisons with a single operator.

Because comparing any value to `NULL` produces `NULL` rather than `TRUE` or `FALSE`, use the `IS NULL` and `IS NOT NULL` operators to check if a value is `NULL` or not.

Complex type considerations:

You cannot refer to a column with a complex data type (`ARRAY`, `STRUCT`, or `MAP`) directly in an operator. You can apply operators only to scalar values that make up a complex type (the fields of a `STRUCT`, the items of an `ARRAY`, or the key or value portion of a `MAP`) as part of a join query that refers to the scalar value using the appropriate dot notation or `ITEM`, `KEY`, or `VALUE` pseudocolumn names.

The following example shows how to do an arithmetic operation using a numeric field of a `STRUCT` type that is an item within an `ARRAY` column. Once the scalar numeric value `R_NATIONKEY` is extracted, it can be used with a comparison operator such as `<`:

```
-- The SMALLINT is a field within an array of structs.
describe region;
+-----+-----+-----+
| name          | type                               | comment |
+-----+-----+-----+
| r_regionkey   | smallint                           |         |
| r_name        | string                             |         |
| r_comment     | string                             |         |
| r_nations     | array<struct<                      |         |
|               |   n_nationkey:smallint,            |         |
|               |   n_name:string,                  |         |
|               |   n_comment:string                |         |
|               | >>                                |         |
+-----+-----+-----+

-- When we refer to the scalar value using dot notation,
-- we can use arithmetic and comparison operators on it
-- like any other number.
select r_name, nation.item.n_name, nation.item.n_nationkey
from region, region.r_nations as nation
where nation.item.n_nationkey < 5
+-----+-----+-----+
| r_name        | item.n_name | item.n_nationkey |
+-----+-----+-----+
| AMERICA      | CANADA      | 3                 |
| AMERICA      | BRAZIL      | 2                 |
| AMERICA      | ARGENTINA   | 1                 |
| MIDDLE EAST  | EGYPT       | 4                 |
| AFRICA       | ALGERIA     | 0                 |
+-----+-----+-----+
```

EXISTS Operator

The `EXISTS` operator tests whether a subquery returns any results. You typically use it to find values from one table that have corresponding values in another table.

The converse, `NOT EXISTS`, helps to find all the values from one table that do not have any corresponding values in another table.

Syntax:

```
EXISTS (subquery)
NOT EXISTS (subquery)
```

Usage notes:

The subquery can refer to a different table than the outer query block, or the same table. For example, you might use `EXISTS` or `NOT EXISTS` to check the existence of parent/child relationships between two columns of the same table.

You can also use operators and function calls within the subquery to test for other kinds of relationships other than strict equality. For example, you might use a call to `COUNT()` in the subquery to check whether the number of matching values is higher or lower than some limit. You might call a UDF in the subquery to check whether values in one table matches a hashed representation of those same values in a different table.

NULL considerations:

If the subquery returns any value at all (even `NULL`), `EXISTS` returns `TRUE` and `NOT EXISTS` returns `false`.

The following example shows how even when the subquery returns only `NULL` values, `EXISTS` still returns `TRUE` and thus matches all the rows from the table in the outer query block.

```
[localhost:21000] > create table all_nulls (x int);
[localhost:21000] > insert into all_nulls values (null), (null), (null);
[localhost:21000] > select y from t2 where exists (select x from all_nulls);
+----+
| y |
+----+
| 2 |
| 4 |
| 6 |
+----+
```

However, if the table in the subquery is empty and so the subquery returns an empty result set, `EXISTS` returns `FALSE`:

```
[localhost:21000] > create table empty (x int);
[localhost:21000] > select y from t2 where exists (select x from empty);
[localhost:21000] >
```

Added in: CDH 5.2.0 (Impala 2.0.0)

Restrictions:

Correlated subqueries used in `EXISTS` and `IN` operators cannot include a `LIMIT` clause.

Prior to CDH 5.8 / Impala 2.6, the `NOT EXISTS` operator required a correlated subquery. In CDH 5.8 / Impala 2.6 and higher, `NOT EXISTS` works with uncorrelated queries also.

Complex type considerations:

You cannot refer to a column with a complex data type (`ARRAY`, `STRUCT`, or `MAP`) directly in an operator. You can apply operators only to scalar values that make up a complex type (the fields of a `STRUCT`, the items of an `ARRAY`, or the key or value portion of a `MAP`) as part of a join query that refers to the scalar value using the appropriate dot notation or `ITEM`, `KEY`, or `VALUE` pseudocolumn names.

Examples:

The following examples refer to these simple tables containing small sets of integers or strings:

```
[localhost:21000] > create table t1 (x int);
[localhost:21000] > insert into t1 values (1), (2), (3), (4), (5), (6);

[localhost:21000] > create table t2 (y int);
[localhost:21000] > insert into t2 values (2), (4), (6);

[localhost:21000] > create table t3 (z int);
[localhost:21000] > insert into t3 values (1), (3), (5);

[localhost:21000] > create table month_names (m string);
[localhost:21000] > insert into month_names values
> ('January'), ('February'), ('March'),
> ('April'), ('May'), ('June'), ('July'),
> ('August'), ('September'), ('October'),
> ('November'), ('December');
```

The following example shows a correlated subquery that finds all the values in one table that exist in another table. For each value x from $T1$, the query checks if the y column of $T2$ contains an identical value, and the `EXISTS` operator returns `TRUE` or `FALSE` as appropriate in each case.

```
localhost:21000] > select x from t1 where exists (select y from t2 where t1.x = y);
+----+
| x   |
+----+
| 2   |
| 4   |
| 6   |
+----+
```

An uncorrelated query is less interesting in this case. Because the subquery always returns `TRUE`, all rows from $T1$ are returned. If the table contents were changed so that the subquery did not match any rows, none of the rows from $T1$ would be returned.

```
[localhost:21000] > select x from t1 where exists (select y from t2 where y > 5);
+----+
| x   |
+----+
| 1   |
| 2   |
| 3   |
| 4   |
| 5   |
| 6   |
+----+
```

The following example shows how an uncorrelated subquery can test for the existence of some condition within a table. By using `LIMIT 1` or an aggregate function, the query returns a single result or no result based on whether the subquery matches any rows. Here, we know that $T1$ and $T2$ contain some even numbers, but $T3$ does not.

```
[localhost:21000] > select "contains an even number" from t1 where exists (select x from
t1 where x % 2 = 0) limit 1;
+-----+
| 'contains an even number' |
+-----+
| contains an even number  |
+-----+
[localhost:21000] > select "contains an even number" as assertion from t1 where exists
(select x from t1 where x % 2 = 0) limit 1;
+-----+
| assertion                 |
+-----+
| contains an even number  |
+-----+
[localhost:21000] > select "contains an even number" as assertion from t2 where exists
(select x from t2 where y % 2 = 0) limit 1;
ERROR: AnalysisException: couldn't resolve column reference: 'x'
[localhost:21000] > select "contains an even number" as assertion from t2 where exists
(select y from t2 where y % 2 = 0) limit 1;
+-----+
| assertion                 |
+-----+
| contains an even number  |
+-----+
[localhost:21000] > select "contains an even number" as assertion from t3 where exists
(select z from t3 where z % 2 = 0) limit 1;
[localhost:21000] >
```

The following example finds numbers in one table that are 1 greater than numbers from another table. The `EXISTS` notation is simpler than an equivalent `CROSS JOIN` between the tables. (The example then also illustrates how the same test could be performed using an `IN` operator.)

```
[localhost:21000] > select x from t1 where exists (select y from t2 where x = y + 1);
+----+
```

```

| x |
+---+
| 3 |
| 5 |
+---+
[localhost:21000] > select x from t1 where x in (select y + 1 from t2);
| x |
+---+
| 3 |
| 5 |
+---+

```

The following example finds values from one table that do not exist in another table.

```

[localhost:21000] > select x from t1 where not exists (select y from t2 where x = y);
+---+
| x |
+---+
| 1 |
| 3 |
| 5 |
+---+

```

The following example uses the `NOT EXISTS` operator to find all the leaf nodes in tree-structured data. This simplified “tree of life” has multiple levels (class, order, family, and so on), with each item pointing upward through a `PARENT` pointer. The example runs an outer query and a subquery on the same table, returning only those items whose `ID` value is *not* referenced by the `PARENT` of any other item.

```

[localhost:21000] > create table tree (id int, parent int, name string);
[localhost:21000] > insert overwrite tree values
> (0, null, "animals"),
> (1, 0, "placentals"),
> (2, 0, "marsupials"),
> (3, 1, "bats"),
> (4, 1, "cats"),
> (5, 2, "kangaroos"),
> (6, 4, "lions"),
> (7, 4, "tigers"),
> (8, 5, "red kangaroo"),
> (9, 2, "wallabies");
[localhost:21000] > select name as "leaf node" from tree one
> where not exists (select parent from tree two where one.id =
two.parent);
+-----+
| leaf node |
+-----+
| bats      |
| lions     |
| tigers    |
| red kangaroo |
| wallabies |
+-----+

```

Related information:

[Subqueries in Impala SELECT Statements](#) on page 322

ILIKE Operator

A case-insensitive comparison operator for `STRING` data, with basic wildcard capability using `_` to match a single character and `%` to match multiple characters. The argument expression must match the entire string value. Typically, it is more efficient to put any `%` wildcard match at the end of the string.

This operator, available in CDH 5.7 / Impala 2.5 and higher, is the equivalent of the `LIKE` operator, but with case-insensitive comparisons.

Syntax:

```
string_expression ILIKE wildcard_expression
string_expression NOT ILIKE wildcard_expression
```

Complex type considerations:

You cannot refer to a column with a complex data type (`ARRAY`, `STRUCT`, or `MAP`) directly in an operator. You can apply operators only to scalar values that make up a complex type (the fields of a `STRUCT`, the items of an `ARRAY`, or the key or value portion of a `MAP`) as part of a join query that refers to the scalar value using the appropriate dot notation or `ITEM`, `KEY`, or `VALUE` pseudocolumn names.

Examples:

In the following examples, strings that are the same except for differences in uppercase and lowercase match successfully with `ILIKE`, but do not match with `LIKE`:

```
select 'fooBar' ilike 'FOOBAR';
+-----+
| 'fooBar' ilike 'FOOBAR' |
+-----+
| true                      |
+-----+

select 'fooBar' like 'FOOBAR';
+-----+
| 'fooBar' like 'FOOBAR'  |
+-----+
| false                   |
+-----+

select 'FOOBAR' ilike 'f%';
+-----+
| 'fooBar' ilike 'f%'    |
+-----+
| true                   |
+-----+

select 'FOOBAR' like 'f%';
+-----+
| 'fooBar' like 'f%'    |
+-----+
| false                  |
+-----+

select 'ABCXYZ' not ilike 'ab_xyz';
+-----+
| not 'abcxyz' ilike 'ab_xyz' |
+-----+
| false                       |
+-----+

select 'ABCXYZ' not like 'ab_xyz';
+-----+
| not 'abcxyz' like 'ab_xyz'  |
+-----+
| true                        |
+-----+
```

Related information:

For case-sensitive comparisons, see [LIKE Operator](#) on page 213. For a more general kind of search operator using regular expressions, see [REGEXP Operator](#) on page 216 or its case-insensitive counterpart [IREGEXP Operator](#) on page 210.

IN Operator

The `IN` operator compares an argument value to a set of values, and returns `TRUE` if the argument matches any value in the set. The `NOT IN` operator reverses the comparison, and checks if the argument value is not part of a set of values.

Syntax:

```

expression IN (expression [, expression])
expression IN (subquery)

expression NOT IN (expression [, expression])
expression NOT IN (subquery)

```

The left-hand expression and the set of comparison values must be of compatible types.

The left-hand expression must consist only of a single value, not a tuple. Although the left-hand expression is typically a column name, it could also be some other value. For example, the `WHERE` clauses `WHERE id IN (5)` and `WHERE 5 IN (id)` produce the same results.

The set of values to check against can be specified as constants, function calls, column names, or other expressions in the query text. The maximum number of expressions in the `IN` list is 9999. (The maximum number of elements of a single expression is 10,000 items, and the `IN` operator itself counts as one.)

In Impala 2.0 and higher, the set of values can also be generated by a subquery. `IN` can evaluate an unlimited number of results using a subquery.

Usage notes:

Any expression using the `IN` operator could be rewritten as a series of equality tests connected with `OR`, but the `IN` syntax is often clearer, more concise, and easier for Impala to optimize. For example, with partitioned tables, queries frequently use `IN` clauses to filter data by comparing the partition key columns to specific values.

NULL considerations:

If there really is a matching non-null value, `IN` returns `TRUE`:

```

[localhost:21000] > select 1 in (1,null,2,3);
+-----+
| 1 in (1, null, 2, 3) |
+-----+
| true                 |
+-----+
[localhost:21000] > select 1 not in (1,null,2,3);
+-----+
| 1 not in (1, null, 2, 3) |
+-----+
| false                  |
+-----+

```

If the searched value is not found in the comparison values, and the comparison values include `NULL`, the result is `NULL`:

```

[localhost:21000] > select 5 in (1,null,2,3);
+-----+
| 5 in (1, null, 2, 3) |
+-----+
| NULL                 |
+-----+
[localhost:21000] > select 5 not in (1,null,2,3);
+-----+
| 5 not in (1, null, 2, 3) |
+-----+
| NULL                  |
+-----+
[localhost:21000] > select 1 in (null);
+-----+
| 1 in (null) |
+-----+
| NULL        |
+-----+
[localhost:21000] > select 1 not in (null);
+-----+
| 1 not in (null) |
+-----+

```



```
| NULL |
+-----+
```

If the left-hand argument is `NULL`, `IN` always returns `NULL`. This rule applies even if the comparison values include `NULL`.

```
[localhost:21000] > select null in (1,2,3);
+-----+
| null in (1, 2, 3) |
+-----+
| NULL |
+-----+
[localhost:21000] > select null not in (1,2,3);
+-----+
| null not in (1, 2, 3) |
+-----+
| NULL |
+-----+
[localhost:21000] > select null in (null);
+-----+
| null in (null) |
+-----+
| NULL |
+-----+
[localhost:21000] > select null not in (null);
+-----+
| null not in (null) |
+-----+
| NULL |
+-----+
```

Added in: Available in earlier Impala releases, but new capabilities were added in CDH 5.2.0 / Impala 2.0.0

Complex type considerations:

You cannot refer to a column with a complex data type (`ARRAY`, `STRUCT`, or `MAP`) directly in an operator. You can apply operators only to scalar values that make up a complex type (the fields of a `STRUCT`, the items of an `ARRAY`, or the key or value portion of a `MAP`) as part of a join query that refers to the scalar value using the appropriate dot notation or `ITEM`, `KEY`, or `VALUE` pseudocolumn names.

The following example shows how to do an arithmetic operation using a numeric field of a `STRUCT` type that is an item within an `ARRAY` column. Once the scalar numeric value `R_NATIONKEY` is extracted, it can be used in an arithmetic expression, such as multiplying by 10:

```
-- The SMALLINT is a field within an array of structs.
describe region;
+-----+-----+-----+
| name          | type                                     | comment |
+-----+-----+-----+
| r_regionkey   | smallint                                |          |
| r_name        | string                                  |          |
| r_comment     | string                                  |          |
| r_nations     | array<struct<                            |          |
|               |   n_nationkey:smallint,                 |          |
|               |   n_name:string,                       |          |
|               |   n_comment:string                     |          |
|               | >>                                     |          |
+-----+-----+-----+

-- When we refer to the scalar value using dot notation,
-- we can use arithmetic and comparison operators on it
-- like any other number.
select r_name, nation.item.n_name, nation.item.n_nationkey
from region, region.r_nations as nation
where nation.item.n_nationkey in (1,3,5)
+-----+-----+-----+
| r_name | item.n_name | item.n_nationkey |
+-----+-----+-----+
```

AMERICA	CANADA	3
AMERICA	ARGENTINA	1
AFRICA	ETHIOPIA	5

Restrictions:

Correlated subqueries used in `EXISTS` and `IN` operators cannot include a `LIMIT` clause.

Examples:

```
-- Using IN is concise and self-documenting.
SELECT * FROM t1 WHERE c1 IN (1,2,10);
-- Equivalent to series of = comparisons ORed together.
SELECT * FROM t1 WHERE c1 = 1 OR c1 = 2 OR c1 = 10;

SELECT c1 AS "starts with vowel" FROM t2 WHERE upper(substr(c1,1,1)) IN
('A','E','I','O','U');

SELECT COUNT(DISTINCT(visitor_id)) FROM web_traffic WHERE month IN
('January','June','July');
```

Related information:

[Subqueries in Impala SELECT Statements](#) on page 322

IREGEXP Operator

Tests whether a value matches a regular expression, using case-insensitive string comparisons. Uses the POSIX regular expression syntax where `^` and `$` match the beginning and end of the string, `.` represents any single character, `*` represents a sequence of zero or more items, `+` represents a sequence of one or more items, `?` produces a non-greedy match, and so on.

This operator, available in CDH 5.7 / Impala 2.5 and higher, is the equivalent of the `REGEXP` operator, but with case-insensitive comparisons.

Syntax:

```
string_expression IREGEXP regular_expression
```

Usage notes:

The `|` symbol is the alternation operator, typically used within `()` to match different sequences. The `()` groups do not allow backreferences. To retrieve the part of a value matched within a `()` section, use the [`regexp_extract\(\)`](#) built-in function. (Currently, there is not any case-insensitive equivalent for the `regexp_extract()` function.)

In Impala 1.3.1 and higher, the `REGEXP` and `RLIKE` operators now match a regular expression string that occurs anywhere inside the target string, the same as if the regular expression was enclosed on each side by `.*`. See [REGEXP Operator](#) on page 216 for examples. Previously, these operators only succeeded when the regular expression matched the entire target string. This change improves compatibility with the regular expression support for popular database systems. There is no change to the behavior of the `regexp_extract()` and `regexp_replace()` built-in functions.

In Impala 2.0 and later, the Impala regular expression syntax conforms to the POSIX Extended Regular Expression syntax used by the Google RE2 library. For details, see [the RE2 documentation](#). It has most idioms familiar from regular expressions in Perl, Python, and so on, including `.*` for non-greedy matches.

In Impala 2.0 and later, a change in the underlying regular expression library could cause changes in the way regular expressions are interpreted by this function. Test any queries that use regular expressions and adjust the expression patterns if necessary. See [Incompatible Changes Introduced in Impala 2.0.0 / CDH 5.2.0](#) on page 690 for details.

Complex type considerations:

You cannot refer to a column with a complex data type (`ARRAY`, `STRUCT`, or `MAP`) directly in an operator. You can apply operators only to scalar values that make up a complex type (the fields of a `STRUCT`, the items of an `ARRAY`, or the key

or value portion of a MAP) as part of a join query that refers to the scalar value using the appropriate dot notation or ITEM, KEY, or VALUE pseudocolumn names.

Examples:

The following examples demonstrate the syntax for the IREGEXP operator.

```
select 'abcABCaabbcc' iregexp '^[a-c]+$';
+-----+
| 'abcabcaabbcc' iregexp '[a-c]+' |
+-----+
| true                               |
+-----+
```

Related information:

[REGEXP Operator](#) on page 216

IS DISTINCT FROM Operator

The IS DISTINCT FROM operator, and its converse the IS NOT DISTINCT FROM operator, test whether or not values are identical. IS NOT DISTINCT FROM is similar to the = operator, and IS DISTINCT FROM is similar to the != operator, except that NULL values are treated as identical. Therefore, IS NOT DISTINCT FROM returns true rather than NULL, and IS DISTINCT FROM returns false rather than NULL, when comparing two NULL values. If one of the values being compared is NULL and the other is not, IS DISTINCT FROM returns true and IS NOT DISTINCT FROM returns false, again instead of returning NULL in both cases.

Syntax:

```
expression1 IS DISTINCT FROM expression2
expression1 IS NOT DISTINCT FROM expression2
expression1 <=> expression2
```

The operator <=> is an alias for IS NOT DISTINCT FROM. It is typically used as a NULL-safe equality operator in join queries. That is, A <=> B is true if A equals B or if both A and B are NULL.

Usage notes:

This operator provides concise notation for comparing two values and always producing a true or false result, without treating NULL as a special case. Otherwise, to unambiguously distinguish between two values requires a compound expression involving IS [NOT] NULL tests of both operands in addition to the = or != operator.

The <=> operator, used like an equality operator in a join query, is more efficient than the equivalent clause: A = B OR (A IS NULL AND B IS NULL). The <=> operator can use a hash join, while the OR expression cannot.

Examples:

The following examples show how IS DISTINCT FROM gives output similar to the != operator, and IS NOT DISTINCT FROM gives output similar to the = operator. The exception is when the expression involves a NULL value on one side or both sides, where != and = return NULL but the IS [NOT] DISTINCT FROM operators still return true or false.

```
select 1 is distinct from 0, 1 != 0;
+-----+-----+
| 1 is distinct from 0 | 1 != 0 |
+-----+-----+
| true                 | true   |
+-----+-----+

select 1 is distinct from 1, 1 != 1;
+-----+-----+
| 1 is distinct from 1 | 1 != 1 |
+-----+-----+
| false                | false  |
+-----+-----+
```

```

select 1 is distinct from null, 1 != null;
+-----+-----+
| 1 is distinct from null | 1 != null |
+-----+-----+
| true                    | NULL     |
+-----+-----+

select null is distinct from null, null != null;
+-----+-----+
| null is distinct from null | null != null |
+-----+-----+
| false                      | NULL       |
+-----+-----+

select 1 is not distinct from 0, 1 = 0;
+-----+-----+
| 1 is not distinct from 0 | 1 = 0 |
+-----+-----+
| false                    | false |
+-----+-----+

select 1 is not distinct from 1, 1 = 1;
+-----+-----+
| 1 is not distinct from 1 | 1 = 1 |
+-----+-----+
| true                     | true  |
+-----+-----+

select 1 is not distinct from null, 1 = null;
+-----+-----+
| 1 is not distinct from null | 1 = null |
+-----+-----+
| false                       | NULL    |
+-----+-----+

select null is not distinct from null, null = null;
+-----+-----+
| null is not distinct from null | null = null |
+-----+-----+
| true                           | NULL      |
+-----+-----+

```

The following example shows how `IS DISTINCT FROM` considers `CHAR` values to be the same (not distinct from each other) if they only differ in the number of trailing spaces. Therefore, sometimes the result of an `IS [NOT] DISTINCT FROM` operator differs depending on whether the values are `STRING/VARCHAR` or `CHAR`.

```

select
  'x' is distinct from 'x ' as string_with_trailing_spaces,
  cast('x' as char(5)) is distinct from cast('x ' as char(5)) as
  char_with_trailing_spaces;
+-----+-----+
| string_with_trailing_spaces | char_with_trailing_spaces |
+-----+-----+
| true                       | false                     |
+-----+-----+

```

IS NULL Operator

The `IS NULL` operator, and its converse the `IS NOT NULL` operator, test whether a specified value is [NULL](#). Because using `NULL` with any of the other comparison operators such as `=` or `!=` also returns `NULL` rather than `TRUE` or `FALSE`, you use a special-purpose comparison operator to check for this special condition.

Syntax:

```

expression IS NULL
expression IS NOT NULL

```

Usage notes:

In many cases, `NULL` values indicate some incorrect or incomplete processing during data ingestion or conversion. You might check whether any values in a column are `NULL`, and if so take some followup action to fill them in.

With sparse data, often represented in “wide” tables, it is common for most values to be `NULL` with only an occasional non-`NULL` value. In those cases, you can use the `IS NOT NULL` operator to identify the rows containing any data at all for a particular column, regardless of the actual value.

With a well-designed database schema, effective use of `NULL` values and `IS NULL` and `IS NOT NULL` operators can save having to design custom logic around special values such as 0, -1, 'N/A', empty string, and so on. `NULL` lets you distinguish between a value that is known to be 0, false, or empty, and a truly unknown value.

Complex type considerations:

This operator is not applicable to complex type columns (`STRUCT`, `ARRAY`, or `MAP`). Using a complex type column with `IS NULL` or `IS NOT NULL` causes a query error.

Examples:

```
-- If this value is non-zero, something is wrong.
select count(*) from employees where employee_id is null;

-- With data from disparate sources, some fields might be blank.
-- Not necessarily an error condition.
select count(*) from census where household_income is null;

-- Sometimes we expect fields to be null, and followup action
-- is needed when they are not.
select count(*) from web_traffic where weird_http_code is not null;
```

LIKE Operator

A comparison operator for `STRING` data, with basic wildcard capability using the underscore (`_`) to match a single character and the percent sign (`%`) to match multiple characters. The argument expression must match the entire string value. Typically, it is more efficient to put any `%` wildcard match at the end of the string.

Syntax:

```
string_expression LIKE wildcard_expression
string_expression NOT LIKE wildcard_expression
```

Complex type considerations:

You cannot refer to a column with a complex data type (`ARRAY`, `STRUCT`, or `MAP`) directly in an operator. You can apply operators only to scalar values that make up a complex type (the fields of a `STRUCT`, the items of an `ARRAY`, or the key or value portion of a `MAP`) as part of a join query that refers to the scalar value using the appropriate dot notation or `ITEM`, `KEY`, or `VALUE` pseudocolumn names.

Examples:

```
select distinct c_last_name from customer where c_last_name like 'Mc%' or c_last_name
like 'Mac%';
select count(c_last_name) from customer where c_last_name like 'M%';
select c_email_address from customer where c_email_address like '%.edu';

-- We can find 4-letter names beginning with 'M' by calling functions...
select distinct c_last_name from customer where length(c_last_name) = 4 and
substr(c_last_name,1,1) = 'M';
-- ...or in a more readable way by matching M followed by exactly 3 characters.
select distinct c_last_name from customer where c_last_name like 'M____';
```

For case-insensitive comparisons, see [ILIKE Operator](#) on page 206. For a more general kind of search operator using regular expressions, see [REGEXP Operator](#) on page 216 or its case-insensitive counterpart [IREGEXP Operator](#) on page 210.

Logical Operators

Logical operators return a `BOOLEAN` value, based on a binary or unary logical operation between arguments that are also Booleans. Typically, the argument expressions use [comparison operators](#).

Syntax:

```
boolean_expression binary_logical_operator boolean_expression
unary_logical_operator boolean_expression
```

The Impala logical operators are:

- **AND:** A binary operator that returns `true` if its left-hand and right-hand arguments both evaluate to `true`, `NULL` if either argument is `NULL`, and `false` otherwise.
- **OR:** A binary operator that returns `true` if either of its left-hand and right-hand arguments evaluate to `true`, `NULL` if one argument is `NULL` and the other is either `NULL` or `false`, and `false` otherwise.
- **NOT:** A unary operator that flips the state of a Boolean expression from `true` to `false`, or `false` to `true`. If the argument expression is `NULL`, the result remains `NULL`. (When `NOT` is used this way as a unary logical operator, it works differently than the `IS NOT NULL` comparison operator, which returns `true` when applied to a `NULL`.)

Complex type considerations:

You cannot refer to a column with a complex data type (`ARRAY`, `STRUCT`, or `MAP`) directly in an operator. You can apply operators only to scalar values that make up a complex type (the fields of a `STRUCT`, the items of an `ARRAY`, or the key or value portion of a `MAP`) as part of a join query that refers to the scalar value using the appropriate dot notation or `ITEM`, `KEY`, or `VALUE` pseudocolumn names.

The following example shows how to do an arithmetic operation using a numeric field of a `STRUCT` type that is an item within an `ARRAY` column. Once the scalar numeric value `R_NATIONKEY` is extracted, it can be used in an arithmetic expression, such as multiplying by 10:

```
-- The SMALLINT is a field within an array of structs.
describe region;
+-----+-----+-----+
| name          | type                               | comment |
+-----+-----+-----+
| r_regionkey   | smallint                           |         |
| r_name        | string                              |         |
| r_comment     | string                              |         |
| r_nations     | array<struct<                       |         |
|               |   n_nationkey:smallint,             |         |
|               |   n_name:string,                   |         |
|               |   n_comment:string                 |         |
|               | >>                                 |         |
+-----+-----+-----+

-- When we refer to the scalar value using dot notation,
-- we can use arithmetic and comparison operators on it
-- like any other number.
select r_name, nation.item.n_name, nation.item.n_nationkey
from region, region.r_nations as nation
where
  nation.item.n_nationkey between 3 and 5
  or nation.item.n_nationkey < 15;
+-----+-----+-----+
| r_name        | item.n_name      | item.n_nationkey |
+-----+-----+-----+
| EUROPE        | UNITED KINGDOM  | 23                |
| EUROPE        | RUSSIA          | 22                |
| EUROPE        | ROMANIA         | 19                |
| ASIA          | VIETNAM         | 21                |
| ASIA          | CHINA           | 18                |
| AMERICA       | UNITED STATES   | 24                |
| AMERICA       | PERU            | 17                |
| AMERICA       | CANADA          | 3                 |
| MIDDLE EAST   | SAUDI ARABIA    | 20                |
| MIDDLE EAST   | EGYPT           | 4                 |
+-----+-----+-----+
```

AFRICA	MOZAMBIQUE	16
AFRICA	ETHIOPIA	5

Examples:

These examples demonstrate the AND operator:

```
[localhost:21000] > select true and true;
+-----+
| true and true |
+-----+
| true          |
+-----+
[localhost:21000] > select true and false;
+-----+
| true and false |
+-----+
| false          |
+-----+
[localhost:21000] > select false and false;
+-----+
| false and false |
+-----+
| false           |
+-----+
[localhost:21000] > select true and null;
+-----+
| true and null  |
+-----+
| NULL          |
+-----+
[localhost:21000] > select (10 > 2) and (6 != 9);
+-----+
| (10 > 2) and (6 != 9) |
+-----+
| true                  |
+-----+
```

These examples demonstrate the OR operator:

```
[localhost:21000] > select true or true;
+-----+
| true or true |
+-----+
| true        |
+-----+
[localhost:21000] > select true or false;
+-----+
| true or false |
+-----+
| true         |
+-----+
[localhost:21000] > select false or false;
+-----+
| false or false |
+-----+
| false         |
+-----+
[localhost:21000] > select true or null;
+-----+
| true or null  |
+-----+
| true         |
+-----+
[localhost:21000] > select null or true;
+-----+
| null or true |
+-----+
| true        |
+-----+
```

```
[localhost:21000] > select false or null;
+-----+
| false or null |
+-----+
| NULL          |
+-----+
[localhost:21000] > select (1 = 1) or ('hello' = 'world');
+-----+
| (1 = 1) or ('hello' = 'world') |
+-----+
| true                             |
+-----+
[localhost:21000] > select (2 + 2 != 4) or (-1 > 0);
+-----+
| (2 + 2 != 4) or (-1 > 0) |
+-----+
| false                       |
+-----+
```

These examples demonstrate the NOT operator:

```
[localhost:21000] > select not true;
+-----+
| not true |
+-----+
| false    |
+-----+
[localhost:21000] > select not false;
+-----+
| not false |
+-----+
| true      |
+-----+
[localhost:21000] > select not null;
+-----+
| not null |
+-----+
| NULL     |
+-----+
[localhost:21000] > select not (1=1);
+-----+
| not (1 = 1) |
+-----+
| false       |
+-----+
```

REGEXP Operator

Tests whether a value matches a regular expression. Uses the POSIX regular expression syntax where `^` and `$` match the beginning and end of the string, `.` represents any single character, `*` represents a sequence of zero or more items, `+` represents a sequence of one or more items, `?` produces a non-greedy match, and so on.

Syntax:

```
string_expression REGEXP regular_expression
```

Usage notes:

The `RLIKE` operator is a synonym for `REGEXP`.

The `|` symbol is the alternation operator, typically used within `()` to match different sequences. The `()` groups do not allow backreferences. To retrieve the part of a value matched within a `()` section, use the [regexp_extract\(\)](#) built-in function.

In Impala 1.3.1 and higher, the `REGEXP` and `RLIKE` operators now match a regular expression string that occurs anywhere inside the target string, the same as if the regular expression was enclosed on each side by `.` `*`. See [REGEXP Operator](#) on page 216 for examples. Previously, these operators only succeeded when the regular expression matched

the entire target string. This change improves compatibility with the regular expression support for popular database systems. There is no change to the behavior of the `regexp_extract()` and `regexp_replace()` built-in functions.

In Impala 2.0 and later, the Impala regular expression syntax conforms to the POSIX Extended Regular Expression syntax used by the Google RE2 library. For details, see [the RE2 documentation](#). It has most idioms familiar from regular expressions in Perl, Python, and so on, including `. *?` for non-greedy matches.

In Impala 2.0 and later, a change in the underlying regular expression library could cause changes in the way regular expressions are interpreted by this function. Test any queries that use regular expressions and adjust the expression patterns if necessary. See [Incompatible Changes Introduced in Impala 2.0.0 / CDH 5.2.0](#) on page 690 for details.

Complex type considerations:

You cannot refer to a column with a complex data type (ARRAY, STRUCT, or MAP) directly in an operator. You can apply operators only to scalar values that make up a complex type (the fields of a STRUCT, the items of an ARRAY, or the key or value portion of a MAP) as part of a join query that refers to the scalar value using the appropriate dot notation or ITEM, KEY, or VALUE pseudocolumn names.

Examples:

The following examples demonstrate the identical syntax for the REGEXP and RLIKE operators.

```
-- Find all customers whose first name starts with 'J', followed by 0 or more of any
character.
select c_first_name, c_last_name from customer where c_first_name regexp '^J.*';
select c_first_name, c_last_name from customer where c_first_name rlike '^J.*';

-- Find 'Macdonald', where the first 'a' is optional and the 'D' can be upper- or
lowercase.
-- The ^...$ are required, to match the start and end of the value.
select c_first_name, c_last_name from customer where c_last_name regexp '^Ma?c[Dd]onald$';
select c_first_name, c_last_name from customer where c_last_name rlike '^Ma?c[Dd]onald$';

-- Match multiple character sequences, either 'Mac' or 'Mc'.
select c_first_name, c_last_name from customer where c_last_name regexp
'^ (Mac|Mc)donald$';
select c_first_name, c_last_name from customer where c_last_name rlike '^ (Mac|Mc)donald$';

-- Find names starting with 'S', then one or more vowels, then 'r', then any other
characters.
-- Matches 'Searcy', 'Sorenson', 'Sauer'.
select c_first_name, c_last_name from customer where c_last_name regexp '^S[aeiou]+r.*$';
select c_first_name, c_last_name from customer where c_last_name rlike '^S[aeiou]+r.*$';

-- Find names that end with 2 or more vowels: letters from the set a,e,i,o,u.
select c_first_name, c_last_name from customer where c_last_name regexp '.*[aeiou]{2,}$';
select c_first_name, c_last_name from customer where c_last_name rlike '.*[aeiou]{2,}$';

-- You can use letter ranges in the [] blocks, for example to find names starting with
A, B, or C.
select c_first_name, c_last_name from customer where c_last_name regexp '^[A-C].*';
select c_first_name, c_last_name from customer where c_last_name rlike '^[A-C].*';

-- If you are not sure about case, leading/trailing spaces, and so on, you can process
the
-- column using string functions first.
select c_first_name, c_last_name from customer where lower(trim(c_last_name)) regexp
'^de.*';
select c_first_name, c_last_name from customer where lower(trim(c_last_name)) rlike
'^de.*';
```

Related information:

For regular expression matching with case-insensitive comparisons, see [IREGEXP Operator](#) on page 210.

RLIKE Operator

Synonym for the REGEXP operator. See [REGEXP Operator](#) on page 216 for details.

Examples:

The following examples demonstrate the identical syntax for the REGEXP and RLIKE operators.

```
-- Find all customers whose first name starts with 'J', followed by 0 or more of any
character.
select c_first_name, c_last_name from customer where c_first_name regexp '^J.*';
select c_first_name, c_last_name from customer where c_first_name rlike '^J.*';

-- Find 'Macdonald', where the first 'a' is optional and the 'D' can be upper- or
lowercase.
-- The ^...$ are required, to match the start and end of the value.
select c_first_name, c_last_name from customer where c_last_name regexp '^Ma?c[Dd]onald$';
select c_first_name, c_last_name from customer where c_last_name rlike '^Ma?c[Dd]onald$';

-- Match multiple character sequences, either 'Mac' or 'Mc'.
select c_first_name, c_last_name from customer where c_last_name regexp
'^(Mac|Mc)donald$';
select c_first_name, c_last_name from customer where c_last_name rlike '^(\Mac|Mc)donald$';

-- Find names starting with 'S', then one or more vowels, then 'r', then any other
characters.
-- Matches 'Searcy', 'Sorenson', 'Sauer'.
select c_first_name, c_last_name from customer where c_last_name regexp '^S[aeiou]+r.*$';
select c_first_name, c_last_name from customer where c_last_name rlike '^S[aeiou]+r.*$';

-- Find names that end with 2 or more vowels: letters from the set a,e,i,o,u.
select c_first_name, c_last_name from customer where c_last_name regexp '.*[aeiou]{2,}$';
select c_first_name, c_last_name from customer where c_last_name rlike '.*[aeiou]{2,}$';

-- You can use letter ranges in the [] blocks, for example to find names starting with
A, B, or C.
select c_first_name, c_last_name from customer where c_last_name regexp '^[A-C].*';
select c_first_name, c_last_name from customer where c_last_name rlike '^[A-C].*';

-- If you are not sure about case, leading/trailing spaces, and so on, you can process
the
-- column using string functions first.
select c_first_name, c_last_name from customer where lower(trim(c_last_name)) regexp
'^de.*';
select c_first_name, c_last_name from customer where lower(trim(c_last_name)) rlike
'^de.*';
```

Impala Schema Objects and Object Names

With Impala, you work with schema objects that are familiar to database users: primarily databases, tables, views, and functions. The SQL syntax to work with these objects is explained in [Impala SQL Statements](#) on page 228. This section explains the conceptual knowledge you need to work with these objects and the various ways to specify their names.

Within a table, partitions can also be considered a kind of object. Partitioning is an important subject for Impala, with its own documentation section covering use cases and performance considerations. See [Partitioning for Impala Tables](#) on page 568 for details.

Impala does not have a counterpart of the “tablespace” notion from some database systems. By default, all the data files for a database, table, or partition are located within nested folders within the HDFS file system. You can also specify a particular HDFS location for a given Impala table or partition. The raw data for these objects is represented as a collection of data files, providing the flexibility to load data by simply moving files into the expected HDFS location.

Information about the schema objects is held in the [metastore](#) database. This database is shared between Impala and Hive, allowing each to create, drop, and query each other's databases, tables, and so on. When Impala makes a change to schema objects through a CREATE, ALTER, DROP, INSERT, or LOAD DATA statement, it broadcasts those changes to all nodes in the cluster through the [catalog service](#). When you make such changes through Hive or directly through manipulating HDFS files, you use the [REFRESH](#) or [INVALIDATE METADATA](#) statements on the Impala side to recognize the newly loaded data, new tables, and so on.

Overview of Impala Aliases

When you write the names of tables, columns, or column expressions in a query, you can assign an alias at the same time. Then you can specify the alias rather than the original name when making other references to the table or column in the same statement. You typically specify aliases that are shorter, easier to remember, or both than the original names. The aliases are printed in the query header, making them useful for self-documenting output.

To set up an alias, add the `AS alias` clause immediately after any table, column, or expression name in the `SELECT` list or `FROM` list of a query. The `AS` keyword is optional; you can also specify the alias immediately after the original name.

```
-- Make the column headers of the result set easier to understand.
SELECT c1 AS name, c2 AS address, c3 AS phone FROM table_with_terse_columns;
SELECT SUM(ss_xyz_dollars_net) AS total_sales FROM table_with_cryptic_columns;
-- The alias can be a quoted string for extra readability.
SELECT c1 AS "Employee ID", c2 AS "Date of hire" FROM t1;
-- The AS keyword is optional.
SELECT c1 "Employee ID", c2 "Date of hire" FROM t1;

-- The table aliases assigned in the FROM clause can be used both earlier
-- in the query (the SELECT list) and later (the WHERE clause).
SELECT one.name, two.address, three.phone
  FROM census one, building_directory two, phonebook three
 WHERE one.id = two.id and two.id = three.id;

-- The aliases c1 and c2 let the query handle columns with the same names from 2 joined
-- tables.
-- The aliases t1 and t2 let the query abbreviate references to long or cryptically
-- named tables.
SELECT t1.column_n AS c1, t2.column_n AS c2 FROM long_name_table AS t1,
very_long_name_table2 AS t2
  WHERE c1 = c2;
SELECT t1.column_n c1, t2.column_n c2 FROM table1 t1, table2 t2
  WHERE c1 = c2;
```

To use an alias name that matches one of the Impala reserved keywords (listed in [Impala Reserved Words](#) on page 641), surround the identifier with either single or double quotation marks, or `` characters (backticks).

Aliases follow the same rules as identifiers when it comes to case insensitivity. Aliases can be longer than identifiers (up to the maximum length of a Java string) and can include additional characters such as spaces and dashes when they are quoted using backtick characters.

Complex type considerations:

Queries involving the complex types (`ARRAY`, `STRUCT`, and `MAP`), typically make extensive use of table aliases. These queries involve join clauses where the complex type column is treated as a joined table. To construct two-part or three-part qualified names for the complex column elements in the `FROM` list, sometimes it is syntactically required to construct a table alias for the complex column where it is referenced in the join clause. See [Complex Types \(CDH 5.5 or higher only\)](#) on page 167 for details and examples.

Alternatives:

Another way to define different names for the same tables or columns is to create views. See [Overview of Impala Views](#) on page 224 for details.

Overview of Impala Databases

In Impala, a database is a logical container for a group of tables. Each database defines a separate namespace. Within a database, you can refer to the tables inside it using their unqualified names. Different databases can contain tables with identical names.

Creating a database is a lightweight operation. There are minimal database-specific properties to configure, only `LOCATION` and `COMMENT`. There is no `ALTER DATABASE` statement.

Typically, you create a separate database for each project or application, to avoid naming conflicts between tables and to make clear which tables are related to each other. The `USE` statement lets you switch between databases. Unqualified

references to tables, views, and functions refer to objects within the current database. You can also refer to objects in other databases by using qualified names of the form `dbname.object_name`.

Each database is physically represented by a directory in HDFS. When you do not specify a `LOCATION` attribute, the directory is located in the Impala data directory with the associated tables managed by Impala. When you do specify a `LOCATION` attribute, any read and write operations for tables in that database are relative to the specified HDFS directory.

There is a special database, named `default`, where you begin when you connect to Impala. Tables created in `default` are physically located one level higher in HDFS than all the user-created databases.

Impala includes another predefined database, `_impala_builtins`, that serves as the location for the [built-in functions](#). To see the built-in functions, use a statement like the following:

```
show functions in _impala_builtins;
show functions in _impala_builtins like '*substring*';
```

Related statements:

[CREATE DATABASE Statement](#) on page 246, [DROP DATABASE Statement](#) on page 273, [USE Statement](#) on page 372, [SHOW DATABASES](#) on page 361

Overview of Impala Functions

Functions let you apply arithmetic, string, or other computations and transformations to Impala data. You typically use them in `SELECT` lists and `WHERE` clauses to filter and format query results so that the result set is exactly what you want, with no further processing needed on the application side.

Scalar functions return a single result for each input row. See [Impala Built-In Functions](#) on page 373.

```
[localhost:21000] > select name, population from country where continent = 'North America'
order by population desc limit 4;
[localhost:21000] > select upper(name), population from country where continent = 'North
America' order by population desc limit 4;
```

upper(name)	population
USA	320000000
MEXICO	122000000
CANADA	25000000
GUATEMALA	16000000

Aggregate functions combine the results from multiple rows: either a single result for the entire table, or a separate result for each group of rows. Aggregate functions are frequently used in combination with `GROUP BY` and `HAVING` clauses in the `SELECT` statement. See [Impala Aggregate Functions](#) on page 443.

```
[localhost:21000] > select continent, sum(population) as howmany from country group by
continent order by howmany desc;
```

continent	howmany
Asia	4298723000
Africa	1110635000
Europe	742452000
North America	565265000
South America	406740000
Oceania	38304000

User-defined functions (UDFs) let you code your own logic. They can be either scalar or aggregate functions. UDFs let you implement important business or scientific logic using high-performance code for Impala to automatically parallelize.

You can also use UDFs to implement convenience functions to simplify reporting or porting SQL from other database systems. See [Impala User-Defined Functions \(UDFs\)](#) on page 487.

```
[localhost:21000] > select rot13('Hello world!') as 'Weak obfuscation';
+-----+
| weak obfuscation |
+-----+
| Uryyb jbeyq!    |
+-----+
[localhost:21000] > select likelihood_of_new_subatomic_particle(sensor1, sensor2, sensor3)
as probability
> from experimental_results group by experiment;
```

Each function is associated with a specific database. For example, if you issue a `USE somedb` statement followed by `CREATE FUNCTION somefunc`, the new function is created in the `somedb` database, and you could refer to it through the fully qualified name `somedb.somefunc`. You could then issue another `USE` statement and create a function with the same name in a different database.

Impala built-in functions are associated with a special database named `_impala_builtins`, which lets you refer to them from any database without qualifying the name.

```
[localhost:21000] > show databases;
+-----+
| name |
+-----+
| _impala_builtins |
| analytic_functions |
| avro_testing |
| data_file_size |
| ... |
[localhost:21000] > show functions in _impala_builtins like '*subs*';
+-----+
| return type | signature |
+-----+
| STRING | substr(STRING, BIGINT) |
| STRING | substr(STRING, BIGINT, BIGINT) |
| STRING | substring(STRING, BIGINT) |
| STRING | substring(STRING, BIGINT, BIGINT) |
+-----+
```

Related statements: [CREATE FUNCTION Statement](#) on page 248, [DROP FUNCTION Statement](#) on page 275

Overview of Impala Identifiers

Identifiers are the names of databases, tables, or columns that you specify in a SQL statement. The rules for identifiers govern what names you can give to things you create, the notation for referring to names containing unusual characters, and other aspects such as case sensitivity.

- The minimum length of an identifier is 1 character.
- The maximum length of an identifier is currently 128 characters, enforced by the metastore database.
- An identifier must start with an alphabetic character. The remainder can contain any combination of alphanumeric characters and underscores. Quoting the identifier with backticks has no effect on the allowed characters in the name.
- An identifier can contain only ASCII characters.
- To use an identifier name that matches one of the Impala reserved keywords (listed in [Impala Reserved Words](#) on page 641), surround the identifier with `` characters (backticks). Quote the reserved word even if it is part of a fully qualified name. The following example shows how a reserved word can be used as a column name if it is

quoted with backticks in the `CREATE TABLE` statement, and how the column name must also be quoted with backticks in a query:

```
[localhost:21000] > create table reserved (`data` string);

[localhost:21000] > select data from reserved;
ERROR: AnalysisException: Syntax error in line 1:
select data from reserved
      ^
Encountered: DATA
Expected: ALL, CASE, CAST, DISTINCT, EXISTS, FALSE, IF, INTERVAL, NOT, NULL,
STRAIGHT_JOIN, TRUE, IDENTIFIER
CAUSED BY: Exception: Syntax error

[localhost:21000] > select reserved.data from reserved;
ERROR: AnalysisException: Syntax error in line 1:
select reserved.data from reserved
      ^
Encountered: DATA
Expected: IDENTIFIER
CAUSED BY: Exception: Syntax error

[localhost:21000] > select reserved.`data` from reserved;

[localhost:21000] >
```



Important: Because the list of reserved words grows over time as new SQL syntax is added, consider adopting coding conventions (especially for any automated scripts or in packaged applications) to always quote all identifiers with backticks. Quoting all identifiers protects your SQL from compatibility issues if new reserved words are added in later releases.

- Impala identifiers are always case-insensitive. That is, tables named `t1` and `T1` always refer to the same table, regardless of quote characters. Internally, Impala always folds all specified table and column names to lowercase. This is why the column headers in query output are always displayed in lowercase.

See [Overview of Impala Aliases](#) on page 219 for how to define shorter or easier-to-remember aliases if the original names are long or cryptic identifiers. Aliases follow the same rules as identifiers when it comes to case insensitivity. Aliases can be longer than identifiers (up to the maximum length of a Java string) and can include additional characters such as spaces and dashes when they are quoted using backtick characters.

Another way to define different names for the same tables or columns is to create views. See [Overview of Impala Views](#) on page 224 for details.

Overview of Impala Tables

Tables are the primary containers for data in Impala. They have the familiar row and column layout similar to other database systems, plus some features such as partitioning often associated with higher-end data warehouse systems.

Logically, each table has a structure based on the definition of its columns, partitions, and other properties.

Physically, each table that uses HDFS storage is associated with a directory in HDFS. The table data consists of all the data files underneath that directory:

- [Internal tables](#) are managed by Impala, and use directories inside the designated Impala work area.
- [External tables](#) use arbitrary HDFS directories, where the data files are typically shared between different Hadoop components.
- Large-scale data is usually handled by partitioned tables, where the data files are divided among different HDFS subdirectories.

Impala tables can also represent data that is stored in HBase, or in the Amazon S3 filesystem (CDH 5.4.0 or higher), or on Isilon storage devices (CDH 5.4.3 or higher). See [Using Impala to Query HBase Tables](#) on page 608, [Using Impala with the Amazon S3 Filesystem](#) on page 617, and [Using Impala with Isilon Storage](#) on page 625 for details about those special kinds of tables.

Impala queries ignore files with extensions commonly used for temporary work files by Hadoop tools. Any files with extensions `.tmp` or `.copying` are not considered part of the Impala table. The suffix matching is case-insensitive, so for example Impala ignores both `.copying` and `.COPYING` suffixes.

Related statements: [CREATE TABLE Statement](#) on page 254, [DROP TABLE Statement](#) on page 280, [ALTER TABLE Statement](#) on page 230, [INSERT Statement](#) on page 286, [LOAD DATA Statement](#) on page 297, [SELECT Statement](#) on page 304

Internal Tables

The default kind of table produced by the `CREATE TABLE` statement is known as an internal table. (Its counterpart is the external table, produced by the `CREATE EXTERNAL TABLE` syntax.)

- Impala creates a directory in HDFS to hold the data files.
- You can create data in internal tables by issuing `INSERT` or `LOAD DATA` statements.
- If you add or replace data using HDFS operations, issue the `REFRESH` command in `impala-shell` so that Impala recognizes the changes in data files, block locations, and so on.
- When you issue a `DROP TABLE` statement, Impala physically removes all the data files from the directory.
- To see whether a table is internal or external, and its associated HDFS location, issue the statement `DESCRIBE FORMATTED table_name`. The `Table Type` field displays `MANAGED_TABLE` for internal tables and `EXTERNAL_TABLE` for external tables. The `Location` field displays the path of the table directory as an HDFS URI.
- When you issue an `ALTER TABLE` statement to rename an internal table, all data files are moved into the new HDFS directory for the table. The files are moved even if they were formerly in a directory outside the Impala data directory, for example in an internal table with a `LOCATION` attribute pointing to an outside HDFS directory.

Examples:

You can switch a table from internal to external, or from external to internal, by using the `ALTER TABLE` statement:

```
-- Switch a table from internal to external.
ALTER TABLE table_name SET TBLPROPERTIES('EXTERNAL'='TRUE');

-- Switch a table from external to internal.
ALTER TABLE table_name SET TBLPROPERTIES('EXTERNAL'='FALSE');
```

Related information:

[External Tables](#) on page 223, [CREATE TABLE Statement](#) on page 254, [DROP TABLE Statement](#) on page 280, [ALTER TABLE Statement](#) on page 230, [DESCRIBE Statement](#) on page 264

External Tables

The syntax `CREATE EXTERNAL TABLE` sets up an Impala table that points at existing data files, potentially in HDFS locations outside the normal Impala data directories.. This operation saves the expense of importing the data into a new table when you already have the data files in a known location in HDFS, in the desired file format.

- You can use Impala to query the data in this table.
- You can create data in external tables by issuing `INSERT` or `LOAD DATA` statements.
- If you add or replace data using HDFS operations, issue the `REFRESH` command in `impala-shell` so that Impala recognizes the changes in data files, block locations, and so on.
- When you issue a `DROP TABLE` statement in Impala, that removes the connection that Impala has with the associated data files, but does not physically remove the underlying data. You can continue to use the data files with other Hadoop components and HDFS operations.
- To see whether a table is internal or external, and its associated HDFS location, issue the statement `DESCRIBE FORMATTED table_name`. The `Table Type` field displays `MANAGED_TABLE` for internal tables and

`EXTERNAL_TABLE` for external tables. The `Location` field displays the path of the table directory as an HDFS URI.

- When you issue an `ALTER TABLE` statement to rename an external table, all data files are left in their original locations.
- You can point multiple external tables at the same HDFS directory by using the same `LOCATION` attribute for each one. The tables could have different column definitions, as long as the number and types of columns are compatible with the schema evolution considerations for the underlying file type. For example, for text data files, one table might define a certain column as a `STRING` while another defines the same column as a `BIGINT`.

Examples:

You can switch a table from internal to external, or from external to internal, by using the `ALTER TABLE` statement:

```
-- Switch a table from internal to external.
ALTER TABLE table_name SET TBLPROPERTIES('EXTERNAL'='TRUE');

-- Switch a table from external to internal.
ALTER TABLE table_name SET TBLPROPERTIES('EXTERNAL'='FALSE');
```

Related information:

[Internal Tables](#) on page 223, [CREATE TABLE Statement](#) on page 254, [DROP TABLE Statement](#) on page 280, [ALTER TABLE Statement](#) on page 230, [DESCRIBE Statement](#) on page 264

File Formats

Each table has an associated file format, which determines how Impala interprets the associated data files. See [How Impala Works with Hadoop File Formats](#) on page 575 for details.

You set the file format during the `CREATE TABLE` statement, or change it later using the `ALTER TABLE` statement. Partitioned tables can have a different file format for individual partitions, allowing you to change the file format used in your ETL process for new data without going back and reconvertting all the existing data in the same table.

Any `INSERT` statements produce new data files with the current file format of the table. For existing data files, changing the file format of the table does not automatically do any data conversion. You must use `TRUNCATE TABLE` or `INSERT OVERWRITE` to remove any previous data files that use the old file format. Then you use the `LOAD DATA` statement, `INSERT ... SELECT`, or other mechanism to put data files of the correct format into the table.

The default file format, text, is the most flexible and easy to produce when you are just getting started with Impala. The Parquet file format offers the highest query performance and uses compression to reduce storage requirements; therefore, Cloudera recommends using Parquet for Impala tables with substantial amounts of data. Also, the complex types (`ARRAY`, `STRUCT`, and `MAP`) available in CDH 5.5 / Impala 2.3 and higher are currently only supported with the Parquet file type. Based on your existing ETL workflow, you might use other file formats such as Avro, possibly doing a final conversion step to Parquet to take advantage of its performance for analytic queries.

Overview of Impala Views

Views are lightweight logical constructs that act as aliases for queries. You can specify a view name in a query (a `SELECT` statement or the `SELECT` portion of an `INSERT` statement) where you would usually specify a table name.

A view lets you:

- Issue complicated queries with compact and simple syntax:

```
-- Take a complicated reporting query, plug it into a CREATE VIEW statement...
create view v1 as select c1, c2, avg(c3) from t1 group by c3 order by c1 desc limit 10;
-- ... and now you can produce the report with 1 line of code.
select * from v1;
```


- Reduce maintenance, by avoiding the duplication of complicated queries across multiple applications in multiple languages:

```
create view v2 as select t1.c1, t1.c2, t2.c3 from t1 join t2 on (t1.id = t2.id);
-- This simple query is safer to embed in reporting applications than the longer query
  above.
-- The view definition can remain stable even if the structure of the underlying tables
  changes.
select c1, c2, c3 from v2;
```

- Build a new, more refined query on top of the original query by adding new clauses, select-list expressions, function calls, and so on:

```
create view average_price_by_category as select category, avg(price) as avg_price from
  products group by category;
create view expensive_categories as select category, avg_price from
  average_price_by_category order by avg_price desc limit 10000;
create view top_10_expensive_categories as select category, avg_price from
  expensive_categories limit 10;
```

This technique lets you build up several more or less granular variations of the same query, and switch between them when appropriate.

- Set up aliases with intuitive names for tables, columns, result sets from joins, and so on:

```
-- The original tables might have cryptic names inherited from a legacy system.
create view action_items as select rrptsk as assignee, treq as due_date, dmisc as notes
  from vxy_t1_br;
-- You can leave original names for compatibility, build new applications using more
  intuitive ones.
select assignee, due_date, notes from action_items;
```

- Swap tables with others that use different file formats, partitioning schemes, and so on without any downtime for data copying or conversion:

```
create table slow (x int, s string) stored as textfile;
create view report as select s from slow where x between 20 and 30;
-- Query is kind of slow due to inefficient table definition, but it works.
select * from report;

create table fast (s string) partitioned by (x int) stored as parquet;
-- ...Copy data from SLOW to FAST. Queries against REPORT view continue to work...

-- After changing the view definition, queries will be faster due to partitioning,
-- binary format, and compression in the new table.
alter view report as select s from fast where x between 20 and 30;
select * from report;
```

- Avoid coding lengthy subqueries and repeating the same subquery text in many other queries.
- Set up fine-grained security where a user can query some columns from a table but not other columns. Because CDH 5.5 / Impala 2.3 and higher support column-level authorization, this technique is no longer required. If you formerly implemented column-level security through views, see https://www.cloudera.com/documentation/enterprise/latest/topics/sg_hive_sql.html for details about the column-level authorization feature.

The SQL statements that configure views are [CREATE VIEW Statement](#) on page 263, [ALTER VIEW Statement](#) on page 240, and [DROP VIEW Statement](#) on page 282. You can specify view names when querying data ([SELECT Statement](#) on page 304) and copying data from one table to another ([INSERT Statement](#) on page 286). The [WITH](#) clause creates an inline view, that only exists for the duration of a single query.

```
[localhost:21000] > create view trivial as select * from customer;
[localhost:21000] > create view some_columns as select c_first_name, c_last_name, c_login
  from customer;
[localhost:21000] > select * from some_columns limit 5;
Query finished, fetching results ...
```

c_first_name	c_last_name	c_login
Javier	Lewis	
Amy	Moses	
Latisha	Hamilton	
Michael	White	
Robert	Moran	

```
[localhost:21000] > create view ordered_results as select * from some_columns order by c_last_name desc, c_first_name desc limit 1000;
```

```
[localhost:21000] > select * from ordered_results limit 5;
```

```
Query: select * from ordered_results limit 5
```

```
Query finished, fetching results ...
```

c_first_name	c_last_name	c_login
Thomas	Zuniga	
Sarah	Zuniga	
Norma	Zuniga	
Lloyd	Zuniga	
Lisa	Zuniga	

```
Returned 5 row(s) in 0.48s
```

The previous example uses descending order for ORDERED_RESULTS because in the sample TPCD-H data, there are some rows with empty strings for both C_FIRST_NAME and C_LAST_NAME, making the lowest-ordered names unuseful in a sample query.

```
create view visitors_by_day as select day, count(distinct visitors) as howmany from web_traffic group by day;
create view top_10_days as select day, howmany from visitors_by_day order by howmany limit 10;
select * from top_10_days;
```

Usage notes:

To see the definition of a view, issue a DESCRIBE FORMATTED statement, which shows the query from the original CREATE VIEW statement:

```
[localhost:21000] > create view v1 as select * from t1;
```

```
[localhost:21000] > describe formatted v1;
```

```
Query finished, fetching results ...
```

name	type	comment
# col_name	data_type	comment
x	NULL	NULL
y	int	None
s	int	None
	string	None
	NULL	NULL
# Detailed Table Information	NULL	NULL
Database:	views	NULL
Owner:	cloudera	NULL
CreateTime:	Mon Jul 08 15:56:27 EDT 2013	NULL
LastAccessTime:	UNKNOWN	NULL
Protect Mode:	None	NULL
Retention:	0	NULL
Table Type:	VIRTUAL_VIEW	NULL
Table Parameters:	NULL	NULL
	transient_lastDdlTime	1373313387
	NULL	NULL
# Storage Information	NULL	NULL
SerDe Library:	null	NULL
InputFormat:	null	NULL
OutputFormat:	null	NULL
Compressed:	No	NULL
Num Buckets:	0	NULL
Bucket Columns:	[]	NULL

Sort Columns:	[]	NULL
# View Information	NULL	NULL
View Original Text:	SELECT * FROM t1	NULL
View Expanded Text:	SELECT * FROM t1	NULL

Prior to Impala 1.4.0, it was not possible to use the `CREATE TABLE LIKE view_name` syntax. In Impala 1.4.0 and higher, you can create a table with the same column definitions as a view using the `CREATE TABLE LIKE` technique. Although `CREATE TABLE LIKE` normally inherits the file format of the original table, a view has no underlying file format, so `CREATE TABLE LIKE view_name` produces a text table by default. To specify a different file format, include a `STORED AS file_format` clause at the end of the `CREATE TABLE LIKE` statement.

Complex type considerations:

For tables containing complex type columns (`ARRAY`, `STRUCT`, or `MAP`), you typically use join queries to refer to the complex values. You can use views to hide the join notation, making such tables seem like traditional denormalized tables, and making those tables queryable by business intelligence tools that do not have built-in support for those complex types. See [Accessing Complex Type Data in Flattened Form Using Views](#) on page 187 for details.

The `STRAIGHT_JOIN` hint affects the join order of table references in the query block containing the hint. It does not affect the join order of nested queries, such as views, inline views, or `WHERE`-clause subqueries. To use this hint for performance tuning of complex queries, apply the hint to all query blocks that need a fixed join order.

Restrictions:

- You cannot insert into an Impala view. (In some database systems, this operation is allowed and inserts rows into the base table.) You can use a view name on the right-hand side of an `INSERT` statement, in the `SELECT` part.
- If a view applies to a partitioned table, any partition pruning considers the clauses on both the original query and any additional `WHERE` predicates in the query that refers to the view. Prior to Impala 1.4, only the `WHERE` clauses on the original query from the `CREATE VIEW` statement were used for partition pruning.
- An `ORDER BY` clause without an additional `LIMIT` clause is ignored in any view definition. If you need to sort the entire result set from a view, use an `ORDER BY` clause in the `SELECT` statement that queries the view. You can still make a simple “top 10” report by combining the `ORDER BY` and `LIMIT` clauses in the same view definition:

```
[localhost:21000] > create table unsorted (x bigint);
[localhost:21000] > insert into unsorted values (1), (9), (3), (7), (5), (8), (4), (6),
(2);
[localhost:21000] > create view sorted_view as select x from unsorted order by x;
[localhost:21000] > select x from sorted_view; -- ORDER BY clause in view has no effect.
+----+
| x |
+----+
| 1 |
| 9 |
| 3 |
| 7 |
| 5 |
| 8 |
| 4 |
| 6 |
| 2 |
+----+
[localhost:21000] > select x from sorted_view order by x; -- View query requires ORDER
BY at outermost level.
+----+
| x |
+----+
| 1 |
| 2 |
| 3 |
| 4 |
| 5 |
| 6 |
| 7 |
```

```

      | 8 |
      | 9 |
+----+
[localhost:21000] > create view top_3_view as select x from unsorted order by x limit
3;
[localhost:21000] > select x from top_3_view; -- ORDER BY and LIMIT together in view
definition are preserved.
+----+
      | x |
+----+
      | 1 |
      | 2 |
      | 3 |
+----+

```

Related statements: [CREATE VIEW Statement](#) on page 263, [ALTER VIEW Statement](#) on page 240, [DROP VIEW Statement](#) on page 282

Impala SQL Statements

The Impala SQL dialect supports a range of standard elements, plus some extensions for Big Data use cases related to data loading and data warehousing.



Note:

In the `impala-shell` interpreter, a semicolon at the end of each statement is required. Since the semicolon is not actually part of the SQL syntax, we do not include it in the syntax definition of each statement, but we do show it in examples intended to be run in `impala-shell`.

DDL Statements

DDL refers to “Data Definition Language”, a subset of SQL statements that change the structure of the database schema in some way, typically by creating, deleting, or modifying schema objects such as databases, tables, and views. Most Impala DDL statements start with the keywords `CREATE`, `DROP`, or `ALTER`.

The Impala DDL statements are:

- [ALTER TABLE Statement](#) on page 230
- [ALTER VIEW Statement](#) on page 240
- [COMPUTE STATS Statement](#) on page 241
- [CREATE DATABASE Statement](#) on page 246
- [CREATE FUNCTION Statement](#) on page 248
- [CREATE ROLE Statement \(CDH 5.2 or higher only\)](#) on page 253
- [CREATE TABLE Statement](#) on page 254
- [CREATE VIEW Statement](#) on page 263
- [DROP DATABASE Statement](#) on page 273
- [DROP FUNCTION Statement](#) on page 275
- [DROP ROLE Statement \(CDH 5.2 or higher only\)](#) on page 277
- [DROP TABLE Statement](#) on page 280
- [DROP VIEW Statement](#) on page 282
- [GRANT Statement \(CDH 5.2 or higher only\)](#) on page 285
- [REVOKE Statement \(CDH 5.2 or higher only\)](#) on page 304

After Impala executes a DDL command, information about available tables, columns, views, partitions, and so on is automatically synchronized between all the Impala nodes in a cluster. (Prior to Impala 1.2, you had to issue a `REFRESH` or `INVALIDATE METADATA` statement manually on the other nodes to make them aware of the changes.)

If the timing of metadata updates is significant, for example if you use round-robin scheduling where each query could be issued through a different Impala node, you can enable the [SYNC_DDL](#) query option to make the DDL statement wait until all nodes have been notified about the metadata changes.

See [Using Impala with the Amazon S3 Filesystem](#) on page 617 for details about how Impala DDL statements interact with tables and partitions stored in the Amazon S3 filesystem.

Although the `INSERT` statement is officially classified as a DML (data manipulation language) statement, it also involves metadata changes that must be broadcast to all Impala nodes, and so is also affected by the `SYNC_DDL` query option.

Because the `SYNC_DDL` query option makes each DDL operation take longer than normal, you might only enable it before the last DDL operation in a sequence. For example, if you are running a script that issues multiple of DDL operations to set up an entire new schema, add several new partitions, and so on, you might minimize the performance overhead by enabling the query option only before the last `CREATE`, `DROP`, `ALTER`, or `INSERT` statement. The script only finishes when all the relevant metadata changes are recognized by all the Impala nodes, so you could connect to any node and issue queries through it.

The classification of DDL, DML, and other statements is not necessarily the same between Impala and Hive. Impala organizes these statements in a way intended to be familiar to people familiar with relational databases or data warehouse products. Statements that modify the metastore database, such as `COMPUTE STATS`, are classified as DDL. Statements that only query the metastore database, such as `SHOW` or `DESCRIBE`, are put into a separate category of utility statements.



Note: The query types shown in the Impala debug web user interface might not match exactly the categories listed here. For example, currently the `USE` statement is shown as DDL in the debug web UI. The query types shown in the debug web UI are subject to change, for improved consistency.

Related information:

The other major classifications of SQL statements are data manipulation language (see [DML Statements](#) on page 229) and queries (see [SELECT Statement](#) on page 304).

DML Statements

DML refers to “Data Manipulation Language”, a subset of SQL statements that modify the data stored in tables. Because Impala focuses on query performance and leverages the append-only nature of HDFS storage, currently Impala only supports a small set of DML statements:

- [INSERT Statement](#) on page 286
- [LOAD DATA Statement](#) on page 297

`INSERT` in Impala is primarily optimized for inserting large volumes of data in a single statement, to make effective use of the multi-megabyte HDFS blocks. This is the way in Impala to create new data files. If you intend to insert one or a few rows at a time, such as using the `INSERT . . . VALUES` syntax, that technique is much more efficient for Impala tables stored in HBase. See [Using Impala to Query HBase Tables](#) on page 608 for details.

`LOAD DATA` moves existing data files into the directory for an Impala table, making them immediately available for Impala queries. This is one way in Impala to work with data files produced by other Hadoop components. (`CREATE EXTERNAL TABLE` is the other alternative; with external tables, you can query existing data files, while the files remain in their original location.)

To simulate the effects of an `UPDATE` or `DELETE` statement in other database systems, typically you use `INSERT` or `CREATE TABLE AS SELECT` to copy data from one table to another, filtering out or changing the appropriate rows during the copy operation.

Although Impala currently does not have an `UPDATE` statement, you can achieve a similar result by using Impala tables stored in HBase. When you insert a row into an HBase table, and the table already contains a row with the same value for the key column, the older row is hidden, effectively the same as a single-row `UPDATE`.

Impala can perform DML operations for tables or partitions stored in the Amazon S3 filesystem with CDH 5.8 / Impala 2.6 and higher. See [Using Impala with the Amazon S3 Filesystem](#) on page 617 for details.

Related information:

The other major classifications of SQL statements are data definition language (see [DDL Statements](#) on page 228) and queries (see [SELECT Statement](#) on page 304).

ALTER TABLE Statement

The `ALTER TABLE` statement changes the structure or properties of an existing Impala table.

In Impala, this is primarily a logical operation that updates the table metadata in the metastore database that Impala shares with Hive. Most `ALTER TABLE` operations do not actually rewrite, move, and so on the actual data files. (The `RENAME TO` clause is the one exception; it can cause HDFS files to be moved to different paths.) When you do an `ALTER TABLE` operation, you typically need to perform corresponding physical filesystem operations, such as rewriting the data files to include extra fields, or converting them to a different file format.

Syntax:

```
ALTER TABLE [old_db_name.]old_table_name RENAME TO [new_db_name.]new_table_name

ALTER TABLE name ADD COLUMNS (col_spec[, col_spec ...])
ALTER TABLE name DROP [COLUMN] column_name
ALTER TABLE name CHANGE column_name col_spec
ALTER TABLE name REPLACE COLUMNS (col_spec[, col_spec ...])

ALTER TABLE name ADD [IF NOT EXISTS] PARTITION (partition_spec)
    [location_spec]
    [cache_spec]
ALTER TABLE name ADD [IF NOT EXISTS] RANGE PARTITION kudu_partition_spec

ALTER TABLE name DROP [IF EXISTS] PARTITION (partition_spec)
    [PURGE]
ALTER TABLE name DROP [IF EXISTS] RANGE PARTITION kudu_partition_spec

ALTER TABLE name RECOVER PARTITIONS

ALTER TABLE name [PARTITION (partition_spec)]
    SET { FILEFORMAT file_format
        | LOCATION 'hdfs_path_of_directory'
        | TBLPROPERTIES (table_properties)
        | SERDEPROPERTIES (serde_properties) }

ALTER TABLE name colname
    ('statsKey'='val, ...')

statsKey ::= numDVs | numNulls | avgSize | maxSize

ALTER TABLE name [PARTITION (partition_spec)] SET { CACHED IN 'pool_name' [WITH
REPLICATION = integer] | UNCACHED }

new_name ::= [new_database.]new_table_name

col_spec ::= col_name type_name COMMENT 'column-comment' [kudu_attributes]

kudu_attributes ::= { [NOT] NULL | ENCODING codec | COMPRESSION algorithm |
    DEFAULT constant | BLOCK_SIZE number }

partition_spec ::= partition_col=constant_value

table_properties ::= 'name'='value'[, 'name'='value' ...]

serde_properties ::= 'name'='value'[, 'name'='value' ...]

file_format ::= { PARQUET | TEXTFILE | RCFILE | SEQUENCEFILE | AVRO }
```

Statement type: DDL

Complex type considerations:

In CDH 5.5 / Impala 2.3 and higher, the `ALTER TABLE` statement can change the metadata for tables containing complex types (ARRAY, STRUCT, and MAP). For example, you can use an `ADD COLUMNS`, `DROP COLUMN`, or `CHANGE`

clause to modify the table layout for complex type columns. Although Impala queries only work for complex type columns in Parquet tables, the complex type support in the `ALTER TABLE` statement applies to all file formats. For example, you can use Impala to update metadata for a staging table in a non-Parquet file format where the data is populated by Hive. Or you can use `ALTER TABLE SET FILEFORMAT` to change the format of an existing table to Parquet so that Impala can query it. Remember that changing the file format for a table does not convert the data files within the table; you must prepare any Parquet data files containing complex types outside Impala, and bring them into the table using `LOAD DATA` or updating the table's `LOCATION` property. See [Complex Types \(CDH 5.5 or higher only\)](#) on page 167 for details about using complex types.

Usage notes:

Whenever you specify partitions in an `ALTER TABLE` statement, through the `PARTITION (partition_spec)` clause, you must include all the partitioning columns in the specification.

Most of the `ALTER TABLE` operations work the same for internal tables (managed by Impala) as for external tables (with data files located in arbitrary locations). The exception is renaming a table; for an external table, the underlying data directory is not renamed or moved.

Amazon S3 considerations:

You can specify an `s3a://` prefix on the `LOCATION` attribute of a table or partition to make Impala query data from the Amazon S3 filesystem. In CDH 5.8 / Impala 2.6 and higher, Impala automatically handles creating or removing the associated folders when you issue `ALTER TABLE` statements with the `ADD PARTITION` or `DROP PARTITION` clauses.

In CDH 5.8 / Impala 2.6 and higher, Impala DDL statements such as `CREATE DATABASE`, `CREATE TABLE`, `DROP DATABASE CASCADE`, `DROP TABLE`, and `ALTER TABLE [ADD|DROP] PARTITION` can create or remove folders as needed in the Amazon S3 system. Prior to CDH 5.8 / Impala 2.6, you had to create folders yourself and point Impala database, tables, or partitions at them, and manually remove folders when no longer needed. See [Using Impala with the Amazon S3 Filesystem](#) on page 617 for details about reading and writing S3 data with Impala.

HDFS caching (CACHED IN clause):

If you specify the `CACHED IN` clause, any existing or future data files in the table directory or the partition subdirectories are designated to be loaded into memory with the HDFS caching mechanism. See [Using HDFS Caching with Impala \(CDH 5.1 or higher only\)](#) on page 550 for details about using the HDFS caching feature.

In Impala 2.2 / CDH 5.4 and higher, the optional `WITH REPLICATION` clause for `CREATE TABLE` and `ALTER TABLE` lets you specify a **replication factor**, the number of hosts on which to cache the same data blocks. When Impala processes a cached data block, where the cache replication factor is greater than 1, Impala randomly selects a host that has a cached copy of that data block. This optimization avoids excessive CPU usage on a single host when the same cached data block is processed multiple times. Cloudera recommends specifying a value greater than or equal to the HDFS block replication factor.

If you connect to different Impala nodes within an `impala-shell` session for load-balancing purposes, you can enable the `SYNC_DDL` query option to make each DDL statement wait before returning, until the new or changed metadata has been received by all the Impala nodes. See [SYNC_DDL Query Option](#) on page 356 for details.

The following sections show examples of the use cases for various `ALTER TABLE` clauses.

To rename a table (RENAME TO clause):

The `RENAME TO` clause lets you change the name of an existing table, and optionally which database it is located in.

For internal tables, this operation physically renames the directory within HDFS that contains the data files; the original directory name no longer exists. By qualifying the table names with database names, you can use this technique to move an internal table (and its associated data directory) from one database to another. For example:

```
create database d1;
create database d2;
create database d3;
use d1;
create table mobile (x int);
use d2;
-- Move table from another database to the current one.
```

```
alter table d1.mobile rename to mobile;
use d1;
-- Move table from one database to another.
alter table d2.mobile rename to d3.mobile;
```

For external tables,

To change the physical location where Impala looks for data files associated with a table or partition:

```
ALTER TABLE table_name [PARTITION (partition_spec)] SET LOCATION 'hdfs_path_of_directory';
```

The path you specify is the full HDFS path where the data files reside, or will be created. Impala does not create any additional subdirectory named after the table. Impala does not move any data files to this new location or change any data files that might already exist in that directory.

To set the location for a single partition, include the `PARTITION` clause. Specify all the same partitioning columns for the table, with a constant value for each, to precisely identify the single partition affected by the statement:

```
create table p1 (s string) partitioned by (month int, day int);
-- Each ADD PARTITION clause creates a subdirectory in HDFS.
alter table p1 add partition (month=1, day=1);
alter table p1 add partition (month=1, day=2);
alter table p1 add partition (month=2, day=1);
alter table p1 add partition (month=2, day=2);
-- Redirect queries, INSERT, and LOAD DATA for one partition
-- to a specific different directory.
alter table p1 partition (month=1, day=1) set location '/usr/external_data/new_years_day';
```



Note: If you are creating a partition for the first time and specifying its location, for maximum efficiency, use a single `ALTER TABLE` statement including both the `ADD PARTITION` and `LOCATION` clauses, rather than separate statements with `ADD PARTITION` and `SET LOCATION` clauses.

To automatically detect new partition directories added through Hive or HDFS operations:

In CDH 5.5 / Impala 2.3 and higher, the `RECOVER PARTITIONS` clause scans a partitioned table to detect if any new partition directories were added outside of Impala, such as by Hive `ALTER TABLE` statements or by `hdfs dfs` or `hadoop fs` commands. The `RECOVER PARTITIONS` clause automatically recognizes any data files present in these new directories, the same as the `REFRESH` statement does.

For example, here is a sequence of examples showing how you might create a partitioned table in Impala, create new partitions through Hive, copy data files into the new partitions with the `hdfs` command, and have Impala recognize the new partitions and new data:

In Impala, create the table, and a single partition for demonstration purposes:

```
create database recover_partitions;
use recover_partitions;
create table t1 (s string) partitioned by (yy int, mm int);
insert into t1 partition (yy = 2016, mm = 1) values ('Partition exists');
show files in t1;
+-----+-----+-----+
| Path | | Size | Partition |
+-----+-----+-----+
| /user/hive/warehouse/recover_partitions.db/t1/yy=2016/mm=1/data.txt | 17B | |
yy=2016/mm=1 |
+-----+-----+-----+
quit;
```


In Hive, create some new partitions. In a real use case, you might create the partitions and populate them with data as the final stages of an ETL pipeline.

```
hive> use recover_partitions;
OK
hive> alter table t1 add partition (yy = 2016, mm = 2);
OK
hive> alter table t1 add partition (yy = 2016, mm = 3);
OK
hive> quit;
```

For demonstration purposes, manually copy data (a single row) into these new partitions, using manual HDFS operations:

```
$ hdfs dfs -ls /user/hive/warehouse/recover_partitions.db/t1/yy=2016/
Found 3 items
drwxr-xr-x - impala   hive 0 2016-05-09 16:06
/user/hive/warehouse/recover_partitions.db/t1/yy=2016/mm=1
drwxr-xr-x - jrussell hive 0 2016-05-09 16:14
/user/hive/warehouse/recover_partitions.db/t1/yy=2016/mm=2
drwxr-xr-x - jrussell hive 0 2016-05-09 16:13
/user/hive/warehouse/recover_partitions.db/t1/yy=2016/mm=3

$ hdfs dfs -cp /user/hive/warehouse/recover_partitions.db/t1/yy=2016/mm=1/data.txt \
/user/hive/warehouse/recover_partitions.db/t1/yy=2016/mm=2/data.txt
$ hdfs dfs -cp /user/hive/warehouse/recover_partitions.db/t1/yy=2016/mm=1/data.txt \
/user/hive/warehouse/recover_partitions.db/t1/yy=2016/mm=3/data.txt
```

```
hive> select * from t1;
OK
Partition exists 2016 1
Partition exists 2016 2
Partition exists 2016 3
hive> quit;
```

In Impala, initially the partitions and data are not visible. Running `ALTER TABLE` with the `RECOVER PARTITIONS` clause scans the table data directory to find any new partition directories, and the data files inside them:

```
select * from t1;
+-----+-----+-----+
| s      | yy    | mm    |
+-----+-----+-----+
| Partition exists | 2016 | 1     |
+-----+-----+-----+

alter table t1 recover partitions;
select * from t1;
+-----+-----+-----+
| s      | yy    | mm    |
+-----+-----+-----+
| Partition exists | 2016 | 1     |
| Partition exists | 2016 | 3     |
| Partition exists | 2016 | 2     |
+-----+-----+-----+
```

To change the key-value pairs of the TBLPROPERTIES and SERDEPROPERTIES fields:

```
ALTER TABLE table_name SET TBLPROPERTIES ('key1'='value1', 'key2'='value2'[, ...]);
ALTER TABLE table_name SET SERDEPROPERTIES ('key1'='value1', 'key2'='value2'[, ...]);
```

The TBLPROPERTIES clause is primarily a way to associate arbitrary user-specified data items with a particular table.

The SERDEPROPERTIES clause sets up metadata defining how tables are read or written, needed in some cases by Hive but not used extensively by Impala. You would use this clause primarily to change the delimiter in an existing text table or partition, by setting the 'serialization.format' and 'field.delim' property values to the new delimiter character:

```
-- This table begins life as pipe-separated text format.
create table change_to_csv (s1 string, s2 string) row format delimited fields terminated
  by '|';
-- Then we change it to a CSV table.
alter table change_to_csv set SERDEPROPERTIES ('serialization.format'=',',
  'field.delim'=',');
insert overwrite change_to_csv values ('stop','go'), ('yes','no');
!hdfs dfs -cat 'hdfs://hostname:8020/data_directory/dbname.db/change_to_csv/data_file';
stop,go
yes,no
```

Use the DESCRIBE FORMATTED statement to see the current values of these properties for an existing table. See [CREATE TABLE Statement](#) on page 254 for more details about these clauses. See [Setting the NUMROWS Value Manually through ALTER TABLE](#) on page 540 for an example of using table properties to fine-tune the performance-related table statistics.

To manually set or update table or column statistics:

Although for most tables the COMPUTE STATS or COMPUTE INCREMENTAL STATS statement is all you need to keep table and column statistics up to date for a table, sometimes for a very large table or one that is updated frequently, the length of time to recompute all the statistics might make it impractical to run those statements as often as needed. As a workaround, you can use the ALTER TABLE statement to set table statistics at the level of the entire table or a single partition, or column statistics at the level of the entire table.

You can set the numrows value for table statistics by changing the TBLPROPERTIES setting for a table or partition. For example:

```
create table analysis_data stored as parquet as select * from raw_data;
Inserted 1000000000 rows in 181.98s
compute stats analysis_data;
insert into analysis_data select * from smaller_table_we_forgot_before;
Inserted 1000000 rows in 15.32s
-- Now there are 1001000000 rows. We can update this single data point in the stats.
alter table analysis_data set tblproperties('numRows'='1001000000',
  'STATS_GENERATED_VIA_STATS_TASK'='true');
```

```
-- If the table originally contained 1 million rows, and we add another partition with
  30 thousand rows,
-- change the numRows property for the partition and the overall table.
alter table partitioned_data partition(year=2009, month=4) set tblproperties
  ('numRows'='30000', 'STATS_GENERATED_VIA_STATS_TASK'='true');
alter table partitioned_data set tblproperties ('numRows'='1030000',
  'STATS_GENERATED_VIA_STATS_TASK'='true');
```

See [Setting the NUMROWS Value Manually through ALTER TABLE](#) on page 540 for details.

In CDH 5.8 / Impala 2.6 and higher, you can use the SET COLUMN STATS clause to set a specific stats value for a particular column.

You specify a case-insensitive symbolic name for the kind of statistics: `numDVs`, `numNulls`, `avgSize`, `maxSize`. The key names and values are both quoted. This operation applies to an entire table, not a specific partition. For example:

```
create table t1 (x int, s string);
insert into t1 values (1, 'one'), (2, 'two'), (2, 'deux');
show column stats t1;
```

Column	Type	#Distinct Values	#Nulls	Max Size	Avg Size
x	INT	-1	-1	4	4
s	STRING	-1	-1	-1	-1

```
alter table t1 set column stats x ('numDVs'='2','numNulls'='0');
alter table t1 set column stats s ('numdvs'='3','maxsize'='4');
show column stats t1;
```

Column	Type	#Distinct Values	#Nulls	Max Size	Avg Size
x	INT	2	0	4	4
s	STRING	3	-1	4	-1

To reorganize columns for a table:

```
ALTER TABLE table_name ADD COLUMNS (column_defs);
ALTER TABLE table_name REPLACE COLUMNS (column_defs);
ALTER TABLE table_name CHANGE column_name new_name new_type;
ALTER TABLE table_name DROP column_name;
```

The *column_spec* is the same as in the `CREATE TABLE` statement: the column name, then its data type, then an optional comment. You can add multiple columns at a time. The parentheses are required whether you add a single column or multiple columns. When you replace columns, all the original column definitions are discarded. You might use this technique if you receive a new set of data files with different data types or columns in a different order. (The data files are retained, so if the new columns are incompatible with the old ones, use `INSERT OVERWRITE` or `LOAD DATA OVERWRITE` to replace all the data before issuing any further queries.)

For example, here is how you might add columns to an existing table. The first `ALTER TABLE` adds two new columns, and the second `ALTER TABLE` adds one new column. A single Impala query reads both the old and new data files, containing different numbers of columns. For any columns not present in a particular data file, all the column values are considered to be `NULL`.

```
create table t1 (x int);
insert into t1 values (1), (2);

alter table t1 add columns (s string, t timestamp);
insert into t1 values (3, 'three', now());

alter table t1 add columns (b boolean);
insert into t1 values (4, 'four', now(), true);
```

```
select * from t1 order by x;
```

x	s	t	b
1	NULL	NULL	NULL
2	NULL	NULL	NULL
3	three	2016-05-11 11:19:45.054457000	NULL
4	four	2016-05-11 11:20:20.260733000	true

You might use the `CHANGE` clause to rename a single column, or to treat an existing column as a different type than before, such as to switch between treating a column as `STRING` and `TIMESTAMP`, or between `INT` and `BIGINT`. You can only drop a single column at a time; to drop multiple columns, issue multiple `ALTER TABLE` statements, or define the new set of columns with a single `ALTER TABLE ... REPLACE COLUMNS` statement.

The following examples show some safe operations to drop or change columns. Dropping the final column in a table lets Impala ignore the data causing any disruption to existing data files. Changing the type of a column works if existing data values can be safely converted to the new type. The type conversion rules depend on the file format of the underlying table. For example, in a text table, the same value can be interpreted as a `STRING` or a numeric value, while in a binary format such as Parquet, the rules are stricter and type conversions only work between certain sizes of integers.

```
create table optional_columns (x int, y int, z int, a1 int, a2 int);
insert into optional_columns values (1,2,3,0,0), (2,3,4,100,100);
```

```
-- When the last column in the table is dropped, Impala ignores the
-- values that are no longer needed. (Dropping A1 but leaving A2
-- would cause problems, as we will see in a subsequent example.)
alter table optional_columns drop column a2;
alter table optional_columns drop column a1;
```

```
select * from optional_columns;
```

x	y	z
1	2	3
2	3	4

```
create table int_to_string (s string, x int);
insert into int_to_string values ('one', 1), ('two', 2);
```

```
-- What was an INT column will now be interpreted as STRING.
-- This technique works for text tables but not other file formats.
-- The second X represents the new name of the column, which we keep the same.
alter table int_to_string change x x string;
```

```
-- Once the type is changed, we can insert non-integer values into the X column
-- and treat that column as a string, for example by uppercasing or concatenating.
insert into int_to_string values ('three', 'trois');
select s, upper(x) from int_to_string;
```

s	upper(x)
one	1
two	2
three	TROIS

Remember that Impala does not actually do any conversion for the underlying data files as a result of `ALTER TABLE` statements. If you use `ALTER TABLE` to create a table layout that does not agree with the contents of the underlying files, you must replace the files yourself, such as using `LOAD DATA` to load a new set of data files, or `INSERT OVERWRITE` to copy from another table and replace the original data.

The following example shows what happens if you delete the middle column from a Parquet table containing three columns. The underlying data files still contain three columns of data. Because the columns are interpreted based on their positions in the data file instead of the specific column names, a `SELECT *` query now reads the first and second columns from the data file, potentially leading to unexpected results or conversion errors. For this reason, if you expect to someday drop a column, declare it as the last column in the table, where its data can be ignored by queries after the column is dropped. Or, re-run your ETL process and create new data files if you drop or change the type of a column in a way that causes problems with existing data files.

```
-- Parquet table showing how dropping a column can produce unexpected results.
create table p1 (s1 string, s2 string, s3 string) stored as parquet;
```

```
insert into p1 values ('one', 'un', 'uno'), ('two', 'deux', 'dos'),
 ('three', 'trois', 'tres');
select * from p1;
```

```
+-----+-----+-----+
```

s1	s2	s3
one	un	uno
two	deux	dos
three	trois	tres

```
alter table p1 drop column s2;
-- The S3 column contains unexpected results.
-- Because S2 and S3 have compatible types, the query reads
-- values from the dropped S2, because the existing data files
-- still contain those values as the second column.
select * from p1;
```

s1	s3
one	un
two	deux
three	trois

```
-- Parquet table showing how dropping a column can produce conversion errors.
create table p2 (s1 string, x int, s3 string) stored as parquet;
```

```
insert into p2 values ('one', 1, 'uno'), ('two', 2, 'dos'), ('three', 3, 'tres');
select * from p2;
```

s1	x	s3
one	1	uno
two	2	dos
three	3	tres

```
alter table p2 drop column x;
select * from p2;
```

WARNINGS:

```
File 'hdfs_filename' has an incompatible Parquet schema for column 'add_columns.p2.s3'.
Column type: STRING, Parquet schema:
optional int32 x [i:1 d:1 r:0]
```

```
File 'hdfs_filename' has an incompatible Parquet schema for column 'add_columns.p2.s3'.
Column type: STRING, Parquet schema:
optional int32 x [i:1 d:1 r:0]
```

In CDH 5.8 / Impala 2.6 and higher, if an Avro table is created without column definitions in the `CREATE TABLE` statement, and columns are later added through `ALTER TABLE`, the resulting table is now queryable. Missing values from the newly added columns now default to `NULL`.

To change the file format that Impala expects data to be in, for a table or partition:

Use an `ALTER TABLE ... SET FILEFORMAT` clause. You can include an optional `PARTITION (col1=val1, col2=val2, ...)` clause so that the file format is changed for a specific partition rather than the entire table.

Because this operation only changes the table metadata, you must do any conversion of existing data using regular Hadoop techniques outside of Impala. Any new data created by the Impala `INSERT` statement will be in the new format. You cannot specify the delimiter for Text files; the data files must be comma-delimited.

To set the file format for a single partition, include the `PARTITION` clause. Specify all the same partitioning columns for the table, with a constant value for each, to precisely identify the single partition affected by the statement:

```
create table p1 (s string) partitioned by (month int, day int);
-- Each ADD PARTITION clause creates a subdirectory in HDFS.
alter table p1 add partition (month=1, day=1);
alter table p1 add partition (month=1, day=2);
alter table p1 add partition (month=2, day=1);
alter table p1 add partition (month=2, day=2);
-- Queries and INSERT statements will read and write files
```

```
-- in this format for this specific partition.
alter table p1 partition (month=2, day=2) set fileformat parquet;
```

To add or drop partitions for a table, the table must already be partitioned (that is, created with a `PARTITIONED BY` clause). The partition is a physical directory in HDFS, with a name that encodes a particular column value (the **partition key**). The Impala `INSERT` statement already creates the partition if necessary, so the `ALTER TABLE ... ADD PARTITION` is primarily useful for importing data by moving or copying existing data files into the HDFS directory corresponding to a partition. (You can use the `LOAD DATA` statement to move files into the partition directory, or `ALTER TABLE ... PARTITION (...) SET LOCATION` to point a partition at a directory that already contains data files.

The `DROP PARTITION` clause is used to remove the HDFS directory and associated data files for a particular set of partition key values; for example, if you always analyze the last 3 months worth of data, at the beginning of each month you might drop the oldest partition that is no longer needed. Removing partitions reduces the amount of metadata associated with the table and the complexity of calculating the optimal query plan, which can simplify and speed up queries on partitioned tables, particularly join queries. Here is an example showing the `ADD PARTITION` and `DROP PARTITION` clauses.

To avoid errors while adding or dropping partitions whose existence is not certain, add the optional `IF [NOT] EXISTS` clause between the `ADD` or `DROP` keyword and the `PARTITION` keyword. That is, the entire clause becomes `ADD IF NOT EXISTS PARTITION` or `DROP IF EXISTS PARTITION`. The following example shows how partitions can be created automatically through `INSERT` statements, or manually through `ALTER TABLE` statements. The `IF [NOT] EXISTS` clauses let the `ALTER TABLE` statements succeed even if a new requested partition already exists, or a partition to be dropped does not exist.

Inserting 2 year values creates 2 partitions:

```
create table partition_t (s string) partitioned by (y int);
insert into partition_t (s,y) values ('two thousand',2000), ('nineteen ninety',1990);
show partitions partition_t;
```

y	#Rows	#Files	Size	Bytes Cached	Cache Replication	Format	Incremental stats
1990	-1	1	16B	NOT CACHED	NOT CACHED	TEXT	false
2000	-1	1	13B	NOT CACHED	NOT CACHED	TEXT	false
Total	-1	2	29B	0B			

Without the `IF NOT EXISTS` clause, an attempt to add a new partition might fail:

```
alter table partition_t add partition (y=2000);
ERROR: AnalysisException: Partition spec already exists: (y=2000).
```

The `IF NOT EXISTS` clause makes the statement succeed whether or not there was already a partition with the specified key value:

```
alter table partition_t add if not exists partition (y=2000);
alter table partition_t add if not exists partition (y=2010);
show partitions partition_t;
```

y	#Rows	#Files	Size	Bytes Cached	Cache Replication	Format	Incremental stats
1990	-1	1	16B	NOT CACHED	NOT CACHED	TEXT	false
2000	-1	1	13B	NOT CACHED	NOT CACHED	TEXT	false
2010	-1	0	0B	NOT CACHED	NOT CACHED	TEXT	false
Total	-1	2	29B	0B			

Likewise, the `IF EXISTS` clause lets `DROP PARTITION` succeed whether or not the partition is already in the table:

```
alter table partition_t drop if exists partition (y=2000);
alter table partition_t drop if exists partition (y=1950);
show partitions partition_t;
```

y	#Rows	#Files	Size	Bytes Cached	Cache Replication	Format	Incremental stats
1990	-1	1	16B	NOT CACHED	NOT CACHED	TEXT	false
2010	-1	0	0B	NOT CACHED	NOT CACHED	TEXT	false
Total	-1	1	16B	0B			

The optional `PURGE` keyword, available in CDH 5.5 / Impala 2.3 and higher, is used with the `DROP PARTITION` clause to remove associated HDFS data files immediately rather than going through the HDFS trashcan mechanism. Use this keyword when dropping a partition if it is crucial to remove the data as quickly as possible to free up space, or if there is a problem with the trashcan, such as the trash cannot be configured or being in a different HDFS encryption zone than the data files.

```
-- Create an empty table and define the partitioning scheme.
create table part_t (x int) partitioned by (month int);
-- Create an empty partition into which you could copy data files from some other source.
alter table part_t add partition (month=1);
-- After changing the underlying data, issue a REFRESH statement to make the data visible
in Impala.
refresh part_t;
-- Later, do the same for the next month.
alter table part_t add partition (month=2);

-- Now you no longer need the older data.
alter table part_t drop partition (month=1);
-- If the table was partitioned by month and year, you would issue a statement like:
-- alter table part_t drop partition (year=2003,month=1);
-- which would require 12 ALTER TABLE statements to remove a year's worth of data.

-- If the data files for subsequent months were in a different file format,
-- you could set a different file format for the new partition as you create it.
alter table part_t add partition (month=3) set fileformat=parquet;
```

The value specified for a partition key can be an arbitrary constant expression, without any references to columns. For example:

```
alter table time_data add partition (month=concat('Decem','ber'));
alter table sales_data add partition (zipcode = cast(9021 * 10 as string));
```



Note:

An alternative way to reorganize a table and its associated data files is to use `CREATE TABLE` to create a variation of the original table, then use `INSERT` to copy the transformed or reordered data to the new table. The advantage of `ALTER TABLE` is that it avoids making a duplicate copy of the data files, allowing you to reorganize huge volumes of data in a space-efficient way using familiar Hadoop techniques.

To switch a table between internal and external:

You can switch a table from internal to external, or from external to internal, by using the `ALTER TABLE` statement:

```
-- Switch a table from internal to external.
ALTER TABLE table_name SET TBLPROPERTIES('EXTERNAL'='TRUE');

-- Switch a table from external to internal.
ALTER TABLE table_name SET TBLPROPERTIES('EXTERNAL'='FALSE');
```

Cancellation: Cannot be cancelled.

HDFS permissions:

Most `ALTER TABLE` clauses do not actually read or write any HDFS files, and so do not depend on specific HDFS permissions. For example, the `SET FILEFORMAT` clause does not actually check the file format existing data files or convert them to the new format, and the `SET LOCATION` clause does not require any special permissions on the new location. (Any permission-related failures would come later, when you actually query or insert into the table.)

In general, `ALTER TABLE` clauses that do touch HDFS files and directories require the same HDFS permissions as corresponding `CREATE`, `INSERT`, or `SELECT` statements. The permissions allow the user ID that the `impalad` daemon runs under, typically the `impala` user, to read or write files or directories, or (in the case of the `execute` bit) descend into a directory. The `RENAME TO` clause requires read, write, and execute permission in the source and destination database directories and in the table data directory, and read and write permission for the data files within the table. The `ADD PARTITION` and `DROP PARTITION` clauses require write and execute permissions for the associated partition directory.

Related information:

[Overview of Impala Tables](#) on page 222, [CREATE TABLE Statement](#) on page 254, [DROP TABLE Statement](#) on page 280, [Partitioning for Impala Tables](#) on page 568, [Internal Tables](#) on page 223, [External Tables](#) on page 223

ALTER VIEW Statement

Changes the characteristics of a view. The syntax has two forms:

- The `AS` clause associates the view with a different query.
- The `RENAME TO` clause changes the name of the view, moves the view to a different database, or both.

Because a view is purely a logical construct (an alias for a query) with no physical data behind it, `ALTER VIEW` only involves changes to metadata in the metastore database, not any data files in HDFS.

Syntax:

```
ALTER VIEW [database_name.]view_name AS select_statement
ALTER VIEW [database_name.]view_name RENAME TO [database_name.]view_name
```

Statement type: DDL

If you connect to different Impala nodes within an `impala-shell` session for load-balancing purposes, you can enable the `SYNC_DDL` query option to make each DDL statement wait before returning, until the new or changed metadata has been received by all the Impala nodes. See [SYNC_DDL Query Option](#) on page 356 for details.

Security considerations:

If these statements in your environment contain sensitive literal values such as credit card numbers or tax identifiers, Impala can redact this sensitive information when displaying the statements in log files and other administrative contexts. See http://www.cloudera.com/content/cloudera/en/documentation/core/latest/topics/sg_redaction.html for details.

Cancellation: Cannot be cancelled.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Examples:

```
create table t1 (x int, y int, s string);
create table t2 like t1;
create view v1 as select * from t1;
alter view v1 as select * from t2;
alter view v1 as select x, upper(s) s from t2;
```


To see the definition of a view, issue a `DESCRIBE FORMATTED` statement, which shows the query from the original `CREATE VIEW` statement:

```
[localhost:21000] > create view v1 as select * from t1;
[localhost:21000] > describe formatted v1;
Query finished, fetching results ...
```

name	type	comment
# col_name	data_type	comment
x	NULL	NULL
y	int	None
s	int	None
	string	None
	NULL	NULL
# Detailed Table Information	NULL	NULL
Database:	views	NULL
Owner:	cloudera	NULL
CreateTime:	Mon Jul 08 15:56:27 EDT 2013	NULL
LastAccessTime:	UNKNOWN	NULL
Protect Mode:	None	NULL
Retention:	0	NULL
Table Type:	VIRTUAL_VIEW	NULL
Table Parameters:	NULL	NULL
	transient_lastDdlTime	1373313387
	NULL	NULL
# Storage Information	NULL	NULL
SerDe Library:	null	NULL
InputFormat:	null	NULL
OutputFormat:	null	NULL
Compressed:	No	NULL
Num Buckets:	0	NULL
Bucket Columns:	[]	NULL
Sort Columns:	[]	NULL
	NULL	NULL
# View Information	NULL	NULL
View Original Text:	SELECT * FROM t1	NULL
View Expanded Text:	SELECT * FROM t1	NULL

Related information:

[Overview of Impala Views](#) on page 224, [CREATE VIEW Statement](#) on page 263, [DROP VIEW Statement](#) on page 282

COMPUTE STATS Statement

Gathers information about volume and distribution of data in a table and all associated columns and partitions. The information is stored in the metastore database, and used by Impala to help optimize queries. For example, if Impala can determine that a table is large or small, or has many or few distinct values it can organize parallelize the work appropriately for a join query or insert operation. For details about the kinds of information gathered by this statement, see [Table and Column Statistics](#) on page 533.

Syntax:

```
COMPUTE STATS [db_name.]table_name
COMPUTE INCREMENTAL STATS [db_name.]table_name [PARTITION (partition_spec)]

partition_spec ::= partition_col=constant_value
```

The `PARTITION` clause is only allowed in combination with the `INCREMENTAL` clause. It is optional for `COMPUTE INCREMENTAL STATS`, and required for `DROP INCREMENTAL STATS`. Whenever you specify partitions through the `PARTITION (partition_spec)` clause in a `COMPUTE INCREMENTAL STATS` or `DROP INCREMENTAL STATS` statement, you must include all the partitioning columns in the specification, and specify constant values for all the partition key columns.

Usage notes:

Originally, Impala relied on users to run the Hive `ANALYZE TABLE` statement, but that method of gathering statistics proved unreliable and difficult to use. The Impala `COMPUTE STATS` statement is built from the ground up to improve the reliability and user-friendliness of this operation. `COMPUTE STATS` does not require any setup steps or special configuration. You only run a single Impala `COMPUTE STATS` statement to gather both table and column statistics, rather than separate Hive `ANALYZE TABLE` statements for each kind of statistics.

The `COMPUTE INCREMENTAL STATS` variation is a shortcut for partitioned tables that works on a subset of partitions rather than the entire table. The incremental nature makes it suitable for large tables with many partitions, where a full `COMPUTE STATS` operation takes too long to be practical each time a partition is added or dropped. See [Overview of Incremental Statistics](#) on page 537 for full usage details.

`COMPUTE INCREMENTAL STATS` only applies to partitioned tables. If you use the `INCREMENTAL` clause for an unpartitioned table, Impala automatically uses the original `COMPUTE STATS` statement. Such tables display `false` under the `Incremental stats` column of the `SHOW TABLE STATS` output.



Note: Because many of the most performance-critical and resource-intensive operations rely on table and column statistics to construct accurate and efficient plans, `COMPUTE STATS` is an important step at the end of your ETL process. Run `COMPUTE STATS` on all tables as your first step during performance tuning for slow queries, or troubleshooting for out-of-memory conditions:

- Accurate statistics help Impala construct an efficient query plan for join queries, improving performance and reducing memory usage.
- Accurate statistics help Impala distribute the work effectively for insert operations into Parquet tables, improving performance and reducing memory usage.
- Accurate statistics help Impala estimate the memory required for each query, which is important when you use resource management features, such as admission control and the YARN resource management framework. The statistics help Impala to achieve high concurrency, full utilization of available memory, and avoid contention with workloads from other Hadoop components.

Complex type considerations:

Currently, the statistics created by the `COMPUTE STATS` statement do not include information about complex type columns. The column stats metrics for complex columns are always shown as `-1`. For queries involving complex type columns, Impala uses heuristics to estimate the data distribution within such columns.

HBase considerations:

`COMPUTE STATS` works for HBase tables also. The statistics gathered for HBase tables are somewhat different than for HDFS-backed tables, but that metadata is still used for optimization when HBase tables are involved in join queries.

Amazon S3 considerations:

`COMPUTE STATS` also works for tables where data resides in the Amazon Simple Storage Service (S3). See [Using Impala with the Amazon S3 Filesystem](#) on page 617 for details.

Performance considerations:

The statistics collected by `COMPUTE STATS` are used to optimize join queries `INSERT` operations into Parquet tables, and other resource-intensive kinds of SQL statements. See [Table and Column Statistics](#) on page 533 for details.

For large tables, the `COMPUTE STATS` statement itself might take a long time and you might need to tune its performance. The `COMPUTE STATS` statement does not work with the `EXPLAIN` statement, or the `SUMMARY` command in `impala-shell`. You can use the `PROFILE` statement in `impala-shell` to examine timing information for the statement as a whole. If a basic `COMPUTE STATS` statement takes a long time for a partitioned table, consider switching to the `COMPUTE INCREMENTAL STATS` syntax so that only newly added partitions are analyzed each time.

Examples:

This example shows two tables, `T1` and `T2`, with a small number distinct values linked by a parent-child relationship between `T1.ID` and `T2.PARENT`. `T1` is tiny, while `T2` has approximately 100K rows. Initially, the statistics includes physical measurements such as the number of files, the total size, and size measurements for fixed-length columns

such as with the `INT` type. Unknown values are represented by `-1`. After running `COMPUTE STATS` for each table, much more information is available through the `SHOW STATS` statements. If you were running a join query involving both of these tables, you would need statistics for both tables to get the most effective optimization for the query.

```
[localhost:21000] > show table stats t1;
Query: show table stats t1
+-----+-----+-----+-----+
| #Rows | #Files | Size | Format |
+-----+-----+-----+-----+
| -1    | 1      | 33B  | TEXT  |
+-----+-----+-----+-----+
Returned 1 row(s) in 0.02s
[localhost:21000] > show table stats t2;
Query: show table stats t2
+-----+-----+-----+-----+
| #Rows | #Files | Size      | Format |
+-----+-----+-----+-----+
| -1    | 28     | 960.00KB | TEXT  |
+-----+-----+-----+-----+
Returned 1 row(s) in 0.01s
[localhost:21000] > show column stats t1;
Query: show column stats t1
+-----+-----+-----+-----+-----+-----+
| Column | Type   | #Distinct Values | #Nulls | Max Size | Avg Size |
+-----+-----+-----+-----+-----+-----+
| id     | INT    | -1                | -1     | 4        | 4        |
| s      | STRING | -1                | -1     | -1       | -1       |
+-----+-----+-----+-----+-----+-----+
Returned 2 row(s) in 1.71s
[localhost:21000] > show column stats t2;
Query: show column stats t2
+-----+-----+-----+-----+-----+-----+
| Column | Type   | #Distinct Values | #Nulls | Max Size | Avg Size |
+-----+-----+-----+-----+-----+-----+
| parent | INT    | -1                | -1     | 4        | 4        |
| s      | STRING | -1                | -1     | -1       | -1       |
+-----+-----+-----+-----+-----+-----+
Returned 2 row(s) in 0.01s
[localhost:21000] > compute stats t1;
Query: compute stats t1
+-----+-----+
| summary |
+-----+-----+
| Updated 1 partition(s) and 2 column(s). |
+-----+-----+
Returned 1 row(s) in 5.30s
[localhost:21000] > show table stats t1;
Query: show table stats t1
+-----+-----+-----+-----+
| #Rows | #Files | Size | Format |
+-----+-----+-----+-----+
| 3     | 1      | 33B  | TEXT  |
+-----+-----+-----+-----+
Returned 1 row(s) in 0.01s
[localhost:21000] > show column stats t1;
Query: show column stats t1
+-----+-----+-----+-----+-----+-----+
| Column | Type   | #Distinct Values | #Nulls | Max Size | Avg Size |
+-----+-----+-----+-----+-----+-----+
| id     | INT    | 3                | -1     | 4        | 4        |
| s      | STRING | 3                | -1     | -1       | -1       |
+-----+-----+-----+-----+-----+-----+
Returned 2 row(s) in 0.02s
[localhost:21000] > compute stats t2;
Query: compute stats t2
+-----+-----+
| summary |
+-----+-----+
| Updated 1 partition(s) and 2 column(s). |
+-----+-----+
Returned 1 row(s) in 5.70s
[localhost:21000] > show table stats t2;
Query: show table stats t2
```

```

+-----+-----+-----+-----+
| #Rows | #Files | Size      | Format |
+-----+-----+-----+-----+
| 98304 | 1       | 960.00KB | TEXT  |
+-----+-----+-----+-----+
Returned 1 row(s) in 0.03s
[localhost:21000] > show column stats t2;
Query: show column stats t2
+-----+-----+-----+-----+-----+-----+
| Column | Type      | #Distinct Values | #Nulls | Max Size | Avg Size |
+-----+-----+-----+-----+-----+-----+
| parent | INT       | 3                 | -1     | 4        | 4        |
| s      | STRING    | 6                 | -1     | 14       | 9.3      |
+-----+-----+-----+-----+-----+-----+
Returned 2 row(s) in 0.01s

```

The following example shows how to use the `INCREMENTAL` clause, available in Impala 2.1.0 and higher. The `COMPUTE INCREMENTAL STATS` syntax lets you collect statistics for newly added or changed partitions, without rescanning the entire table.

```

-- Initially the table has no incremental stats, as indicated
-- by -1 under #Rows and false under Incremental stats.
show table stats item_partitioned;
+-----+-----+-----+-----+-----+-----+
| i_category | #Rows | #Files | Size      | Bytes Cached | Format | Incremental stats |
+-----+-----+-----+-----+-----+-----+
| Books      | -1    | 1      | 223.74KB | NOT CACHED   | PARQUET | false             |
| Children   | -1    | 1      | 230.05KB | NOT CACHED   | PARQUET | false             |
| Electronics| -1    | 1      | 232.67KB | NOT CACHED   | PARQUET | false             |
| Home       | -1    | 1      | 232.56KB | NOT CACHED   | PARQUET | false             |
| Jewelry    | -1    | 1      | 223.72KB | NOT CACHED   | PARQUET | false             |
| Men        | -1    | 1      | 231.25KB | NOT CACHED   | PARQUET | false             |
| Music      | -1    | 1      | 237.90KB | NOT CACHED   | PARQUET | false             |
| Shoes      | -1    | 1      | 234.90KB | NOT CACHED   | PARQUET | false             |
| Sports     | -1    | 1      | 227.97KB | NOT CACHED   | PARQUET | false             |
| Women      | -1    | 1      | 226.27KB | NOT CACHED   | PARQUET | false             |
| Total      | -1    | 10     | 2.25MB   | 0B           |         | false             |
+-----+-----+-----+-----+-----+-----+

-- After the first COMPUTE INCREMENTAL STATS,
-- all partitions have stats.
compute incremental stats item_partitioned;
+-----+-----+-----+
| summary |
+-----+
| Updated 10 partition(s) and 21 column(s). |
+-----+

show table stats item_partitioned;
+-----+-----+-----+-----+-----+-----+
| i_category | #Rows | #Files | Size      | Bytes Cached | Format | Incremental stats |
+-----+-----+-----+-----+-----+-----+
| Books      | 1733  | 1      | 223.74KB | NOT CACHED   | PARQUET | true              |
| Children   | 1786  | 1      | 230.05KB | NOT CACHED   | PARQUET | true              |
| Electronics| 1812  | 1      | 232.67KB | NOT CACHED   | PARQUET | true              |
| Home       | 1807  | 1      | 232.56KB | NOT CACHED   | PARQUET | true              |
| Jewelry    | 1740  | 1      | 223.72KB | NOT CACHED   | PARQUET | true              |
| Men        | 1811  | 1      | 231.25KB | NOT CACHED   | PARQUET | true              |
| Music      | 1860  | 1      | 237.90KB | NOT CACHED   | PARQUET | true              |
| Shoes      | 1835  | 1      | 234.90KB | NOT CACHED   | PARQUET | true              |
| Sports     | 1783  | 1      | 227.97KB | NOT CACHED   | PARQUET | true              |
| Women      | 1790  | 1      | 226.27KB | NOT CACHED   | PARQUET | true              |
| Total      | 17957 | 10     | 2.25MB   | 0B           |         | true              |
+-----+-----+-----+-----+-----+-----+

-- Add a new partition...
alter table item_partitioned add partition (i_category='Camping');
-- Add or replace files in HDFS outside of Impala,
-- rendering the stats for a partition obsolete.
!import_data_into_sports_partition.sh
refresh item_partitioned;
drop incremental stats item_partitioned partition (i_category='Sports');
-- Now some partitions have incremental stats

```

```
-- and some do not.
show table stats item_partitioned;
```

i_category	#Rows	#Files	Size	Bytes Cached	Format	Incremental stats
Books	1733	1	223.74KB	NOT CACHED	PARQUET	true
Camping	-1	1	408.02KB	NOT CACHED	PARQUET	false
Children	1786	1	230.05KB	NOT CACHED	PARQUET	true
Electronics	1812	1	232.67KB	NOT CACHED	PARQUET	true
Home	1807	1	232.56KB	NOT CACHED	PARQUET	true
Jewelry	1740	1	223.72KB	NOT CACHED	PARQUET	true
Men	1811	1	231.25KB	NOT CACHED	PARQUET	true
Music	1860	1	237.90KB	NOT CACHED	PARQUET	true
Shoes	1835	1	234.90KB	NOT CACHED	PARQUET	true
Sports	-1	1	227.97KB	NOT CACHED	PARQUET	false
Women	1790	1	226.27KB	NOT CACHED	PARQUET	true
Total	17957	11	2.65MB	0B		

```
-- After another COMPUTE INCREMENTAL STATS,
-- all partitions have incremental stats, and only the 2
-- partitions without incremental stats were scanned.
compute incremental stats item_partitioned;
```

```
| summary |
| Updated 2 partition(s) and 21 column(s). |
```

```
show table stats item_partitioned;
```

i_category	#Rows	#Files	Size	Bytes Cached	Format	Incremental stats
Books	1733	1	223.74KB	NOT CACHED	PARQUET	true
Camping	5328	1	408.02KB	NOT CACHED	PARQUET	true
Children	1786	1	230.05KB	NOT CACHED	PARQUET	true
Electronics	1812	1	232.67KB	NOT CACHED	PARQUET	true
Home	1807	1	232.56KB	NOT CACHED	PARQUET	true
Jewelry	1740	1	223.72KB	NOT CACHED	PARQUET	true
Men	1811	1	231.25KB	NOT CACHED	PARQUET	true
Music	1860	1	237.90KB	NOT CACHED	PARQUET	true
Shoes	1835	1	234.90KB	NOT CACHED	PARQUET	true
Sports	1783	1	227.97KB	NOT CACHED	PARQUET	true
Women	1790	1	226.27KB	NOT CACHED	PARQUET	true
Total	17957	11	2.65MB	0B		

File format considerations:

The `COMPUTE STATS` statement works with tables created with any of the file formats supported by Impala. See [How Impala Works with Hadoop File Formats](#) on page 575 for details about working with the different file formats. The following considerations apply to `COMPUTE STATS` depending on the file format of the table.

The `COMPUTE STATS` statement works with text tables with no restrictions. These tables can be created through either Impala or Hive.

The `COMPUTE STATS` statement works with Parquet tables. These tables can be created through either Impala or Hive.

The `COMPUTE STATS` statement works with Avro tables without restriction in CDH 5.4 / Impala 2.2 and higher. In earlier releases, `COMPUTE STATS` worked only for Avro tables created through Hive, and required the `CREATE TABLE` statement to use SQL-style column names and types rather than an Avro-style schema specification.

The `COMPUTE STATS` statement works with RCFile tables with no restrictions. These tables can be created through either Impala or Hive.

The `COMPUTE STATS` statement works with SequenceFile tables with no restrictions. These tables can be created through either Impala or Hive.

The `COMPUTE STATS` statement works with partitioned tables, whether all the partitions use the same file format, or some partitions are defined through `ALTER TABLE` to use different file formats.

Statement type: DDL

Cancellation: Certain multi-stage statements (`CREATE TABLE AS SELECT` and `COMPUTE STATS`) can be cancelled during some stages, when running `INSERT` or `SELECT` operations internally. To cancel this statement, use Ctrl-C from the `impala-shell` interpreter, the **Cancel** button from the **Watch** page in Hue, **Actions > Cancel** from the **Queries** list in Cloudera Manager, or **Cancel** from the list of in-flight queries (for a particular node) on the **Queries** tab in the Impala web UI (port 25000).

Restrictions:

Currently, the `COMPUTE STATS` statement under CDH 4 does not store any statistics for `DECIMAL` columns. When Impala runs under CDH 5, which has better support for `DECIMAL` in the metastore database, `COMPUTE STATS` does collect statistics for `DECIMAL` columns and Impala uses the statistics to optimize query performance.



Note: Prior to Impala 1.4.0, `COMPUTE STATS` counted the number of `NULL` values in each column and recorded that figure in the metastore database. Because Impala does not currently use the `NULL` count during query planning, Impala 1.4.0 and higher speeds up the `COMPUTE STATS` statement by skipping this `NULL` counting.

Internal details:

Behind the scenes, the `COMPUTE STATS` statement executes two statements: one to count the rows of each partition in the table (or the entire table if unpartitioned) through the `COUNT(*)` function, and another to count the approximate number of distinct values in each column through the `NDV()` function. You might see these queries in your monitoring and diagnostic displays. The same factors that affect the performance, scalability, and execution of other queries (such as parallel execution, memory usage, admission control, and timeouts) also apply to the queries run by the `COMPUTE STATS` statement.

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have read permission for all affected files in the source directory: all files in the case of an unpartitioned table or a partitioned table in the case of `COMPUTE STATS`; or all the files in partitions without incremental stats in the case of `COMPUTE INCREMENTAL STATS`. It must also have read and execute permissions for all relevant directories holding the data files. (Essentially, `COMPUTE STATS` requires the same permissions as the underlying `SELECT` queries it runs against the table.)

Related information:

[DROP STATS Statement](#) on page 277, [SHOW TABLE STATS Statement](#) on page 365, [SHOW COLUMN STATS Statement](#) on page 366, [Table and Column Statistics](#) on page 533

CREATE DATABASE Statement

Creates a new database.

In Impala, a database is both:

- A logical construct for grouping together related tables, views, and functions within their own namespace. You might use a separate database for each application, set of related tables, or round of experimentation.
- A physical construct represented by a directory tree in HDFS. Tables (internal tables), partitions, and data files are all located under this directory. You can perform HDFS-level operations such as backing it up and measuring space usage, or remove it with a `DROP DATABASE` statement.

Syntax:

```
CREATE (DATABASE|SCHEMA) [IF NOT EXISTS] database_name[COMMENT 'database_comment']
[LOCATION hdfs_path];
```

Statement type: DDL

Usage notes:

A database is physically represented as a directory in HDFS, with a filename extension `.db`, under the main Impala data directory. If the associated HDFS directory does not exist, it is created for you. All databases and their associated directories are top-level objects, with no physical or logical nesting.

After creating a database, to make it the current database within an `impala-shell` session, use the `USE` statement. You can refer to tables in the current database without prepending any qualifier to their names.

When you first connect to Impala through `impala-shell`, the database you start in (before issuing any `CREATE DATABASE` or `USE` statements) is named `default`.

Impala includes another predefined database, `_impala_builtins`, that serves as the location for the [built-in functions](#). To see the built-in functions, use a statement like the following:

```
show functions in _impala_builtins;
show functions in _impala_builtins like '*substring*';
```

After creating a database, your `impala-shell` session or another `impala-shell` connected to the same node can immediately access that database. To access the database through the Impala daemon on a different node, issue the `INVALIDATE METADATA` statement first while connected to that other node.

Setting the `LOCATION` attribute for a new database is a way to work with sets of files in an HDFS directory structure outside the default Impala data directory, as opposed to setting the `LOCATION` attribute for each individual table.

If you connect to different Impala nodes within an `impala-shell` session for load-balancing purposes, you can enable the `SYNC_DDL` query option to make each DDL statement wait before returning, until the new or changed metadata has been received by all the Impala nodes. See [SYNC_DDL Query Option](#) on page 356 for details.

Hive considerations:

When you create a database in Impala, the database can also be used by Hive. When you create a database in Hive, issue an `INVALIDATE METADATA` statement in Impala to make Impala permanently aware of the new database.

The `SHOW DATABASES` statement lists all databases, or the databases whose name matches a wildcard pattern. In CDH 5.7 / Impala 2.5 and higher, the `SHOW DATABASES` output includes a second column that displays the associated comment, if any, for each database.

Amazon S3 considerations:

To specify that any tables created within a database reside on the Amazon S3 system, you can include an `s3a://` prefix on the `LOCATION` attribute. In CDH 5.8 / Impala 2.6 and higher, Impala automatically creates any required folders as the databases, tables, and partitions are created, and removes them when they are dropped.

In CDH 5.8 / Impala 2.6 and higher, Impala DDL statements such as `CREATE DATABASE`, `CREATE TABLE`, `DROP DATABASE CASCADE`, `DROP TABLE`, and `ALTER TABLE [ADD|DROP] PARTITION` can create or remove folders as needed in the Amazon S3 system. Prior to CDH 5.8 / Impala 2.6, you had to create folders yourself and point Impala database, tables, or partitions at them, and manually remove folders when no longer needed. See [Using Impala with the Amazon S3 Filesystem](#) on page 617 for details about reading and writing S3 data with Impala.

Cancellation: Cannot be cancelled.

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have write permission for the parent HDFS directory under which the database is located.

Examples:

```
create database first_db;
use first_db;
create table t1 (x int);

create database second_db;
use second_db;
-- Each database has its own namespace for tables.
-- You can reuse the same table names in each database.
create table t1 (s string);
```

```

create database temp;

-- You can either USE a database after creating it,
-- or qualify all references to the table name with the name of the database.
-- Here, tables T2 and T3 are both created in the TEMP database.

create table temp.t2 (x int, y int);
use database temp;
create table t3 (s string);

-- You cannot drop a database while it is selected by the USE statement.
drop database temp;
ERROR: AnalysisException: Cannot drop current default database: temp

-- The always-available database 'default' is a convenient one to USE
-- before dropping a database you created.
use default;

-- Before dropping a database, first drop all the tables inside it,
-- or in CDH 5.5 and higher use the CASCADE clause.
drop database temp;
ERROR: ImpalaRuntimeException: Error making 'dropDatabase' RPC to Hive Metastore:
CAUSED BY: InvalidOperationException: Database temp is not empty
show tables in temp;
+-----+
| name |
+-----+
| t3   |
+-----+

-- CDH 5.5 and higher:
drop database temp cascade;

-- CDH 5.4 and lower:
drop table temp.t3;
drop database temp;

```

Related information:

[Overview of Impala Databases](#) on page 219, [DROP DATABASE Statement](#) on page 273, [USE Statement](#) on page 372, [SHOW DATABASES](#) on page 361, [Overview of Impala Tables](#) on page 222

CREATE FUNCTION Statement

Creates a user-defined function (UDF), which you can use to implement custom logic during `SELECT` or `INSERT` operations.

Syntax:

The syntax is different depending on whether you create a scalar UDF, which is called once for each row and implemented by a single function, or a user-defined aggregate function (UDA), which is implemented by multiple functions that compute intermediate results across sets of rows.

In CDH 5.7 / Impala 2.5 and higher, the syntax is also different for creating or dropping scalar Java-based UDFs. The statements for Java UDFs use a new syntax, without any argument types or return type specified. Java-based UDFs created using the new syntax persist across restarts of the Impala catalog server, and can be shared transparently between Impala and Hive.

To create a persistent scalar C++ UDF with `CREATE FUNCTION`:

```

CREATE FUNCTION [IF NOT EXISTS] [db_name.]function_name([arg_type[, arg_type...])
  RETURNS return_type
  LOCATION 'hdfs_path_to_dot_so'
  SYMBOL='symbol_name'

```


To create a persistent Java UDF with `CREATE FUNCTION`:

```
CREATE FUNCTION [IF NOT EXISTS] [db_name.]function_name
  LOCATION 'hdfs_path_to_jar'
  SYMBOL='class_name'
```

To create a persistent UDA, which must be written in C++, issue a `CREATE AGGREGATE FUNCTION` statement:

```
CREATE [AGGREGATE] FUNCTION [IF NOT EXISTS] [db_name.]function_name([arg_type[,
arg_type...])
  RETURNS return_type
  [INTERMEDIATE type_spec]
  LOCATION 'hdfs_path'
  [INIT_FN='function']
  UPDATE_FN='function'
  MERGE_FN='function'
  [PREPARE_FN='function']
  [CLOSEFN='function']
  [SERIALIZE_FN='function']
  [FINALIZE_FN='function']
```

Statement type: DDL

Varargs notation:



Note:

Variable-length argument lists are supported for C++ UDFs, but currently not for Java UDFs.

If the underlying implementation of your function accepts a variable number of arguments:

- The variable arguments must go last in the argument list.
- The variable arguments must all be of the same type.
- You must include at least one instance of the variable arguments in every function call invoked from SQL.
- You designate the variable portion of the argument list in the `CREATE FUNCTION` statement by including `...` immediately after the type name of the first variable argument. For example, to create a function that accepts an `INT` argument, followed by a `BOOLEAN`, followed by one or more `STRING` arguments, your `CREATE FUNCTION` statement would look like:

```
CREATE FUNCTION func_name (INT, BOOLEAN, STRING ...)
  RETURNS type LOCATION 'path' SYMBOL='entry_point';
```

See [Variable-Length Argument Lists](#) on page 493 for how to code a C++ UDF to accept variable-length argument lists.

Scalar and aggregate functions:

The simplest kind of user-defined function returns a single scalar value each time it is called, typically once for each row in the result set. This general kind of function is what is usually meant by UDF. User-defined aggregate functions (UDAs) are a specialized kind of UDF that produce a single value based on the contents of multiple rows. You usually use UDAs in combination with a `GROUP BY` clause to condense a large result set into a smaller one, or even a single row summarizing column values across an entire table.

You create UDAs by using the `CREATE AGGREGATE FUNCTION` syntax. The clauses `INIT_FN`, `UPDATE_FN`, `MERGE_FN`, `SERIALIZE_FN`, `FINALIZE_FN`, and `INTERMEDIATE` only apply when you create a UDA rather than a scalar UDF.

The `*_FN` clauses specify functions to call at different phases of function processing.

- **Initialize:** The function you specify with the `INIT_FN` clause does any initial setup, such as initializing member variables in internal data structures. This function is often a stub for simple UDAs. You can omit this clause and a default (no-op) function will be used.
- **Update:** The function you specify with the `UPDATE_FN` clause is called once for each row in the original result set, that is, before any `GROUP BY` clause is applied. A separate instance of the function is called for each different

value returned by the `GROUP BY` clause. The final argument passed to this function is a pointer, to which you write an updated value based on its original value and the value of the first argument.

- **Merge:** The function you specify with the `MERGE_FN` clause is called an arbitrary number of times, to combine intermediate values produced by different nodes or different threads as Impala reads and processes data files in parallel. The final argument passed to this function is a pointer, to which you write an updated value based on its original value and the value of the first argument.
- **Serialize:** The function you specify with the `SERIALIZE_FN` clause frees memory allocated to intermediate results. It is required if any memory was allocated by the `Allocate` function in the `Init`, `Update`, or `Merge` functions, or if the intermediate type contains any pointers. See [the UDA code samples](#) for details.
- **Finalize:** The function you specify with the `FINALIZE_FN` clause does any required teardown for resources acquired by your UDF, such as freeing memory, closing file handles if you explicitly opened any files, and so on. This function is often a stub for simple UDAs. You can omit this clause and a default (no-op) function will be used. It is required in UDAs where the final return type is different than the intermediate type. or if any memory was allocated by the `Allocate` function in the `Init`, `Update`, or `Merge` functions. See [the UDA code samples](#) for details.

If you use a consistent naming convention for each of the underlying functions, Impala can automatically determine the names based on the first such clause, so the others are optional.

For end-to-end examples of UDAs, see [Impala User-Defined Functions \(UDFs\)](#) on page 487.

Complex type considerations:

Currently, Impala UDFs cannot accept arguments or return values of the Impala complex types (`STRUCT`, `ARRAY`, or `MAP`).

Usage notes:

- You can write Impala UDFs in either C++ or Java. C++ UDFs are new to Impala, and are the recommended format for high performance utilizing native code. Java-based UDFs are compatible between Impala and Hive, and are most suited to reusing existing Hive UDFs. (Impala can run Java-based Hive UDFs but not Hive UDAs.)
- CDH 5.7 / Impala 2.5 introduces UDF improvements to persistence for both C++ and Java UDFs, and better compatibility between Impala and Hive for Java UDFs. See [Impala User-Defined Functions \(UDFs\)](#) on page 487 for details.
- The body of the UDF is represented by a `.so` or `.jar` file, which you store in HDFS and the `CREATE FUNCTION` statement distributes to each Impala node.
- Impala calls the underlying code during SQL statement evaluation, as many times as needed to process all the rows from the result set. All UDFs are assumed to be deterministic, that is, to always return the same result when passed the same argument values. Impala might or might not skip some invocations of a UDF if the result value is already known from a previous call. Therefore, do not rely on the UDF being called a specific number of times, and do not return different result values based on some external factor such as the current time, a random number function, or an external data source that could be updated while an Impala query is in progress.
- The names of the function arguments in the UDF are not significant, only their number, positions, and data types.
- You can overload the same function name by creating multiple versions of the function, each with a different argument signature. For security reasons, you cannot make a UDF with the same name as any built-in function.
- In the UDF code, you represent the function return result as a `struct`. This `struct` contains 2 fields. The first field is a `boolean` representing whether the value is `NULL` or not. (When this field is `true`, the return value is interpreted as `NULL`.) The second field is the same type as the specified function return type, and holds the return value when the function returns something other than `NULL`.
- In the UDF code, you represent the function arguments as an initial pointer to a UDF context structure, followed by references to zero or more `structs`, corresponding to each of the arguments. Each `struct` has the same 2 fields as with the return value, a `boolean` field representing whether the argument is `NULL`, and a field of the appropriate type holding any non-`NULL` argument value.
- For sample code and build instructions for UDFs, see [the sample UDFs in the Impala github repo](#).
- Because the file representing the body of the UDF is stored in HDFS, it is automatically available to all the Impala nodes. You do not need to manually copy any UDF-related files between servers.

- Because Impala currently does not have any `ALTER FUNCTION` statement, if you need to rename a function, move it to a different database, or change its signature or other properties, issue a `DROP FUNCTION` statement for the original function followed by a `CREATE FUNCTION` with the desired properties.
- Because each UDF is associated with a particular database, either issue a `USE` statement before doing any `CREATE FUNCTION` statements, or specify the name of the function as `db_name.function_name`.

If you connect to different Impala nodes within an `impala-shell` session for load-balancing purposes, you can enable the `SYNC_DDL` query option to make each DDL statement wait before returning, until the new or changed metadata has been received by all the Impala nodes. See [SYNC_DDL Query Option](#) on page 356 for details.

Compatibility:

Impala can run UDFs that were created through Hive, as long as they refer to Impala-compatible data types (not composite or nested column types). Hive can run Java-based UDFs that were created through Impala, but not Impala UDFs written in C++.

The Hive `current_user()` function cannot be called from a Java UDF through Impala.

Persistence:

In CDH 5.7 / Impala 2.5 and higher, Impala UDFs and UDAs written in C++ are persisted in the metastore database. Java UDFs are also persisted, if they were created with the new `CREATE FUNCTION` syntax for Java UDFs, where the Java function argument and return types are omitted. Java-based UDFs created with the old `CREATE FUNCTION` syntax do not persist across restarts because they are held in the memory of the `catalogd` daemon. Until you re-create such Java UDFs using the new `CREATE FUNCTION` syntax, you must reload those Java-based UDFs by running the original `CREATE FUNCTION` statements again each time you restart the `catalogd` daemon. Prior to CDH 5.7 / Impala 2.5, the requirement to reload functions after a restart applied to both C++ and Java functions.

Cancellation: Cannot be cancelled.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Examples:

For additional examples of all kinds of user-defined functions, see [Impala User-Defined Functions \(UDFs\)](#) on page 487.

The following example shows how to take a Java jar file and make all the functions inside one of its classes into UDFs under a single (overloaded) function name in Impala. Each `CREATE FUNCTION` or `DROP FUNCTION` statement applies to all the overloaded Java functions with the same name. This example uses the signatureless syntax for `CREATE FUNCTION` and `DROP FUNCTION`, which is available in CDH 5.7 / Impala 2.5 and higher.

At the start, the jar file is in the local filesystem. Then it is copied into HDFS, so that it is available for Impala to reference through the `CREATE FUNCTION` statement and queries that refer to the Impala function name.

```
$ jar -tvf udf-examples-cdh570.jar
 0 Mon Feb 22 04:06:50 PST 2016 META-INF/
122 Mon Feb 22 04:06:48 PST 2016 META-INF/MANIFEST.MF
 0 Mon Feb 22 04:06:46 PST 2016 com/
 0 Mon Feb 22 04:06:46 PST 2016 com/cloudera/
 0 Mon Feb 22 04:06:46 PST 2016 com/cloudera/impala/
2460 Mon Feb 22 04:06:46 PST 2016 com/cloudera/impala/IncompatibleUdfTest.class
 541 Mon Feb 22 04:06:46 PST 2016 com/cloudera/impala/TestUdfException.class
3438 Mon Feb 22 04:06:46 PST 2016 com/cloudera/impala/JavaUdfTest.class
5872 Mon Feb 22 04:06:46 PST 2016 com/cloudera/impala/TestUdf.class
...
$ hdfs dfs -put udf-examples-cdh570.jar /user/impala/udfs
$ hdfs dfs -ls /user/impala/udfs
Found 2 items
-rw-r--r--  3 jrussell supergroup      853 2015-10-09 14:05
/user/impala/udfs/hello_world.jar
-rw-r--r--  3 jrussell supergroup    7366 2016-06-08 14:25
/user/impala/udfs/udf-examples-cdh570.jar
```

In `impala-shell`, the `CREATE FUNCTION` refers to the HDFS path of the jar file and the fully qualified class name inside the jar. Each of the functions inside the class becomes an Impala function, each one overloaded under the specified Impala function name.

```
[localhost:21000] > create function testudf location
'/user/impala/udfs/udf-examples-cdh570.jar' symbol='com.cloudera.impala.TestUdf';
[localhost:21000] > show functions;
```

return type	signature	binary type	is persistent
BIGINT	testudf(BIGINT)	JAVA	true
BOOLEAN	testudf(BOOLEAN)	JAVA	true
BOOLEAN	testudf(BOOLEAN, BOOLEAN)	JAVA	true
BOOLEAN	testudf(BOOLEAN, BOOLEAN, BOOLEAN)	JAVA	true
DOUBLE	testudf(DOUBLE)	JAVA	true
DOUBLE	testudf(DOUBLE, DOUBLE)	JAVA	true
DOUBLE	testudf(DOUBLE, DOUBLE, DOUBLE)	JAVA	true
FLOAT	testudf(FLOAT)	JAVA	true
FLOAT	testudf(FLOAT, FLOAT)	JAVA	true
FLOAT	testudf(FLOAT, FLOAT, FLOAT)	JAVA	true
INT	testudf(INT)	JAVA	true
DOUBLE	testudf(INT, DOUBLE)	JAVA	true
INT	testudf(INT, INT)	JAVA	true
INT	testudf(INT, INT, INT)	JAVA	true
SMALLINT	testudf(SMALLINT)	JAVA	true
SMALLINT	testudf(SMALLINT, SMALLINT)	JAVA	true
SMALLINT	testudf(SMALLINT, SMALLINT, SMALLINT)	JAVA	true
STRING	testudf(STRING)	JAVA	true
STRING	testudf(STRING, STRING)	JAVA	true
STRING	testudf(STRING, STRING, STRING)	JAVA	true
TINYINT	testudf(TINYINT)	JAVA	true

These are all simple functions that return their single arguments, or sum, concatenate, and so on their multiple arguments. Impala determines which overloaded function to use based on the number and types of the arguments.

```
insert into bigint_x values (1), (2), (4), (3);
select testudf(x) from bigint_x;
```

udfs.testudf(x)
1
2
4
3

```
insert into int_x values (1), (2), (4), (3);
select testudf(x, x+1, x*x) from int_x;
```

udfs.testudf(x, x + 1, x * x)
4
9
25
16

```
select testudf(x) from string_x;
```

udfs.testudf(x)
one
two
four
three

```
select testudf(x,x) from string_x;
```

```
| udfs.testudf(x, x) |
+-----+
| oneone
| twotwo
| fourfour
| threethree
+-----+
```

The previous example used the same Impala function name as the name of the class. This example shows how the Impala function name is independent of the underlying Java class or function names. A second `CREATE FUNCTION` statement results in a set of overloaded functions all named `my_func`, to go along with the overloaded functions all named `testudf`.

```
create function my_func location '/user/impala/udfs/udf-examples-cdh570.jar'
  symbol='com.cloudera.impala.TestUdf';
```

```
show functions;
```

return type	signature	binary type	is persistent
BIGINT	my_func(BIGINT)	JAVA	true
BOOLEAN	my_func(BOOLEAN)	JAVA	true
BOOLEAN	my_func(BOOLEAN, BOOLEAN)	JAVA	true
...			
BIGINT	testudf(BIGINT)	JAVA	true
BOOLEAN	testudf(BOOLEAN)	JAVA	true
BOOLEAN	testudf(BOOLEAN, BOOLEAN)	JAVA	true
...			

The corresponding `DROP FUNCTION` statement with no signature drops all the overloaded functions with that name.

```
drop function my_func;
show functions;
```

return type	signature	binary type	is persistent
BIGINT	testudf(BIGINT)	JAVA	true
BOOLEAN	testudf(BOOLEAN)	JAVA	true
BOOLEAN	testudf(BOOLEAN, BOOLEAN)	JAVA	true
...			

The signatureless `CREATE FUNCTION` syntax for Java UDFs ensures that the functions shown in this example remain available after the Impala service (specifically, the Catalog Server) are restarted.

Related information:

[Impala User-Defined Functions \(UDFs\)](#) on page 487 for more background information, usage instructions, and examples for Impala UDFs; [DROP FUNCTION Statement](#) on page 275

CREATE ROLE Statement (CDH 5.2 or higher only)

The `CREATE ROLE` statement creates a role to which privileges can be granted. Privileges can be granted to roles, which can then be assigned to users. A user that has been assigned a role will only be able to exercise the privileges of that role. Only users that have administrative privileges can create/drop roles. By default, the `hive`, `impala` and `hue` users have administrative privileges in Sentry.

Syntax:

```
CREATE ROLE role_name
```

Required privileges:

Only administrative users (those with `ALL` privileges on the server, defined in the Sentry policy file) can use this statement.

Compatibility:

Impala makes use of any roles and privileges specified by the `GRANT` and `REVOKE` statements in Hive, and Hive makes use of any roles and privileges specified by the `GRANT` and `REVOKE` statements in Impala. The Impala `GRANT` and `REVOKE` statements for privileges do not require the `ROLE` keyword to be repeated before each role name, unlike the equivalent Hive statements.

Cancellation: Cannot be cancelled.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Related information:

[Enabling Sentry Authorization for Impala](#) on page 105, [GRANT Statement \(CDH 5.2 or higher only\)](#) on page 285, [REVOKE Statement \(CDH 5.2 or higher only\)](#) on page 304, [DROP ROLE Statement \(CDH 5.2 or higher only\)](#) on page 277, [SHOW Statement](#) on page 356

CREATE TABLE Statement

Creates a new table and specifies its characteristics. While creating a table, you optionally specify aspects such as:

- Whether the table is internal or external.
- The columns and associated data types.
- The columns used for physically partitioning the data.
- The file format for data files.
- The HDFS directory where the data files are located.

Syntax:

The general syntax for creating a table and specifying its columns is as follows:

Explicit column definitions:

```
CREATE [EXTERNAL] TABLE [IF NOT EXISTS] [db_name.]table_name
  (col_name data_type [COMMENT 'col_comment'], ...)
  [PARTITIONED BY (col_name data_type [COMMENT 'col_comment'], ...)]
  [COMMENT 'table_comment']
  [WITH SERDEPROPERTIES ('key1'='value1', 'key2'='value2', ...)]
  [
    [ROW FORMAT row_format] [STORED AS file_format]
  ]
  [LOCATION 'hdfs_path']
  [TBLPROPERTIES ('key1'='value1', 'key2'='value2', ...)]
  [CACHED IN 'pool_name' [WITH REPLICATION = integer] | UNCACHED]
```

Column definitions inferred from data file:

```
CREATE [EXTERNAL] TABLE [IF NOT EXISTS] [db_name.]table_name
  LIKE PARQUET 'hdfs_path_of_parquet_file'
  [COMMENT 'table_comment']
  [PARTITIONED BY (col_name data_type [COMMENT 'col_comment'], ...)]
  [WITH SERDEPROPERTIES ('key1'='value1', 'key2'='value2', ...)]
  [
    [ROW FORMAT row_format] [STORED AS file_format]
  ]
  [LOCATION 'hdfs_path']
  [TBLPROPERTIES ('key1'='value1', 'key2'='value2', ...)]
  [CACHED IN 'pool_name' [WITH REPLICATION = integer] | UNCACHED]
data_type:
  primitive_type
  | array_type
  | map_type
  | struct_type
```

CREATE TABLE AS SELECT:

```
CREATE [EXTERNAL] TABLE [IF NOT EXISTS] db_name.table_name
  [PARTITIONED BY (col_name[, ...])]
  [COMMENT 'table_comment']
  [WITH SERDEPROPERTIES ('key1'='value1', 'key2'='value2', ...)]
  [
    [ROW FORMAT row_format] [STORED AS ctas_file_format]
  ]
  [LOCATION 'hdfs_path']
  [TBLPROPERTIES ('key1'='value1', 'key2'='value2', ...)]
  [CACHED IN 'pool_name' [WITH REPLICATION = integer] | UNCACHED]
AS
  select_statement
```

primitive_type:

```
TINYINT
| SMALLINT
| INT
| BIGINT
| BOOLEAN
| FLOAT
| DOUBLE
| DECIMAL
| STRING
| CHAR
| VARCHAR
| TIMESTAMP
```

complex_type:

```
struct_type
| array_type
| map_type
```

```
struct_type: STRUCT < name : primitive_or_complex_type [COMMENT 'comment_string'], ...
>
```

```
array_type: ARRAY < primitive_or_complex_type >
```

```
map_type: MAP < primitive_type, primitive_or_complex_type >
```

row_format:

```
DELIMITED [FIELDS TERMINATED BY 'char' [ESCAPED BY 'char']]
[LINES TERMINATED BY 'char']
```

file_format:

```
PARQUET
| TEXTFILE
| AVRO
| SEQUENCEFILE
| RCFILE
```

ctas_file_format:

```
PARQUET
| TEXTFILE
```

Statement type: DDL**Column definitions:**

Depending on the form of the `CREATE TABLE` statement, the column definitions are required or not allowed.

With the `CREATE TABLE AS SELECT` and `CREATE TABLE LIKE` syntax, you do not specify the columns at all; the column names and types are derived from the source table, query, or data file.

With the basic `CREATE TABLE` syntax, you must list one or more columns, its name, type, and optionally a comment, in addition to any columns used as partitioning keys. There is one exception where the column list is not required: when creating an Avro table with the `STORED AS AVRO` clause, you can omit the list of columns and specify the same metadata as part of the `TBLPROPERTIES` clause.

Complex type considerations:

The Impala complex types (`STRUCT`, `ARRAY`, or `MAP`) are available in CDH 5.5 / Impala 2.3 and higher. Because you can nest these types (for example, to make an array of maps or a struct with an array field), these types are also sometimes referred to as nested types. See [Complex Types \(CDH 5.5 or higher only\)](#) on page 167 for usage details.

Impala can create tables containing complex type columns, with any supported file format. Because currently Impala can only query complex type columns in Parquet tables, creating tables with complex type columns and other file formats such as text is of limited use. For example, you might create a text table including some columns with complex types with Impala, and use Hive as part of your to ingest the nested type data and copy it to an identical Parquet table. Or you might create a partitioned table containing complex type columns using one file format, and use `ALTER TABLE` to change the file format of individual partitions to Parquet; Impala can then query only the Parquet-format partitions in that table.

Partitioned tables can contain complex type columns. All the partition key columns must be scalar types.

Internal and external tables (`EXTERNAL` and `LOCATION` clauses):

By default, Impala creates an “internal” table, where Impala manages the underlying data files for the table, and physically deletes the data files when you drop the table. If you specify the `EXTERNAL` clause, Impala treats the table as an “external” table, where the data files are typically produced outside Impala and queried from their original locations in HDFS, and Impala leaves the data files in place when you drop the table. For details about internal and external tables, see [Overview of Impala Tables](#) on page 222.

Typically, for an external table you include a `LOCATION` clause to specify the path to the HDFS directory where Impala reads and writes files for the table. For example, if your data pipeline produces Parquet files in the HDFS directory `/user/etl/destination`, you might create an external table as follows:

```
CREATE EXTERNAL TABLE external_parquet (c1 INT, c2 STRING, c3 TIMESTAMP)
  STORED AS PARQUET LOCATION '/user/etl/destination';
```

Although the `EXTERNAL` and `LOCATION` clauses are often specified together, `LOCATION` is optional for external tables, and you can also specify `LOCATION` for internal tables. The difference is all about whether Impala “takes control” of the underlying data files and moves them when you rename the table, or deletes them when you drop the table. For more about internal and external tables and how they interact with the `LOCATION` attribute, see [Overview of Impala Tables](#) on page 222.

Partitioned tables (`PARTITIONED BY` clause):

The `PARTITIONED BY` clause divides the data files based on the values from one or more specified columns. Impala queries can use the partition metadata to minimize the amount of data that is read from disk or transmitted across the network, particularly during join queries. For details about partitioning, see [Partitioning for Impala Tables](#) on page 568.

Prior to CDH 5.7 / Impala 2.5, you could use a partitioned table as the source and copy data from it, but could not specify any partitioning clauses for the new table. In CDH 5.7 / Impala 2.5 and higher, you can now use the `PARTITIONED BY` clause with a `CREATE TABLE AS SELECT` statement. See the examples under the following discussion of the `CREATE TABLE AS SELECT` syntax variation.

Specifying file format (`STORED AS` and `ROW FORMAT` clauses):

The `STORED AS` clause identifies the format of the underlying data files. Currently, Impala can query more types of file formats than it can create or insert into. Use Hive to perform any create or data load operations that are not currently available in Impala. For example, Impala can create an Avro, SequenceFile, or RCFile table but cannot insert data into it. There are also Impala-specific procedures for using compression with each kind of file format. For details about working with data files of various formats, see [How Impala Works with Hadoop File Formats](#) on page 575.



Note: In Impala 1.4.0 and higher, Impala can create Avro tables, which formerly required doing the `CREATE TABLE` statement in Hive. See [Using the Avro File Format with Impala Tables](#) on page 597 for details and examples.

By default (when no `STORED AS` clause is specified), data files in Impala tables are created as text files with Ctrl-A (hex 01) characters as the delimiter. Specify the `ROW FORMAT DELIMITED` clause to produce or ingest data files that use

a different delimiter character such as tab or |, or a different line end character such as carriage return or newline. When specifying delimiter and line end characters with the `FIELDS TERMINATED BY` and `LINES TERMINATED BY` clauses, use `'\t'` for tab, `'\n'` for newline or linefeed, `'\r'` for carriage return, and `\0` for ASCII nul (hex 00). For more examples of text tables, see [Using Text Data Files with Impala Tables](#) on page 576.

The `ESCAPED BY` clause applies both to text files that you create through an `INSERT` statement to an Impala `TEXTFILE` table, and to existing data files that you put into an Impala table directory. (You can ingest existing data files either by creating the table with `CREATE EXTERNAL TABLE ... LOCATION`, the `LOAD DATA` statement, or through an HDFS operation such as `hdfs dfs -put file hdfs_path`.) Choose an escape character that is not used anywhere else in the file, and put it in front of each instance of the delimiter character that occurs within a field value. Surrounding field values with quotation marks does not help Impala to parse fields with embedded delimiter characters; the quotation marks are considered to be part of the column value. If you want to use `\` as the escape character, specify the clause in `impala-shell` as `ESCAPED BY '\\'`.



Note: The `CREATE TABLE` clauses `FIELDS TERMINATED BY`, `ESCAPED BY`, and `LINES TERMINATED BY` have special rules for the string literal used for their argument, because they all require a single character. You can use a regular character surrounded by single or double quotation marks, an octal sequence such as `'\054'` (representing a comma), or an integer in the range `'-127'..'128'` (with quotation marks but no backslash), which is interpreted as a single-byte ASCII character. Negative values are subtracted from 256; for example, `FIELDS TERMINATED BY '-2'` sets the field delimiter to ASCII code 254, the “Icelandic Thorn” character used as a delimiter by some data formats.

Cloning tables (LIKE clause):

To create an empty table with the same columns, comments, and other attributes as another table, use the following variation. The `CREATE TABLE ... LIKE` form allows a restricted set of clauses, currently only the `LOCATION`, `COMMENT`, and `STORED AS` clauses.

```
CREATE [EXTERNAL] TABLE [IF NOT EXISTS] [db_name.]table_name
LIKE { [db_name.]table_name | PARQUET 'hdfs_path_of_parquet_file' }
[COMMENT 'table_comment']
[STORED AS file_format]
[LOCATION 'hdfs_path']
```



Note: To clone the structure of a table and transfer data into it in a single operation, use the `CREATE TABLE AS SELECT` syntax described in the next subsection.

When you clone the structure of an existing table using the `CREATE TABLE ... LIKE` syntax, the new table keeps the same file format as the original one, so you only need to specify the `STORED AS` clause if you want to use a different file format, or when specifying a view as the original table. (Creating a table “like” a view produces a text table by default.)

Although normally Impala cannot create an HBase table directly, Impala can clone the structure of an existing HBase table with the `CREATE TABLE ... LIKE` syntax, preserving the file format and metadata from the original table.

There are some exceptions to the ability to use `CREATE TABLE ... LIKE` with an Avro table. For example, you cannot use this technique for an Avro table that is specified with an Avro schema but no columns. When in doubt, check if a `CREATE TABLE ... LIKE` operation works in Hive; if not, it typically will not work in Impala either.

If the original table is partitioned, the new table inherits the same partition key columns. Because the new table is initially empty, it does not inherit the actual partitions that exist in the original one. To create partitions in the new table, insert data or issue `ALTER TABLE ... ADD PARTITION` statements.

Prior to Impala 1.4.0, it was not possible to use the `CREATE TABLE LIKE view_name` syntax. In Impala 1.4.0 and higher, you can create a table with the same column definitions as a view using the `CREATE TABLE LIKE` technique. Although `CREATE TABLE LIKE` normally inherits the file format of the original table, a view has no underlying file

format, so `CREATE TABLE LIKE view_name` produces a text table by default. To specify a different file format, include a `STORED AS file_format` clause at the end of the `CREATE TABLE LIKE` statement.

Because `CREATE TABLE ... LIKE` only manipulates table metadata, not the physical data of the table, issue `INSERT INTO TABLE` statements afterward to copy any data from the original table into the new one, optionally converting the data to a new file format. (For some file formats, Impala can do a `CREATE TABLE ... LIKE` to create the table, but Impala cannot insert data in that file format; in these cases, you must load the data in Hive. See [How Impala Works with Hadoop File Formats](#) on page 575 for details.)

CREATE TABLE AS SELECT:

The `CREATE TABLE AS SELECT` syntax is a shorthand notation to create a table based on column definitions from another table, and copy data from the source table to the destination table without issuing any separate `INSERT` statement. This idiom is so popular that it has its own acronym, “CTAS”.

The following examples show how to copy data from a source table `T1` to a variety of destinations tables, applying various transformations to the table properties, table layout, or the data itself as part of the operation:

```
-- Sample table to be the source of CTAS operations.
CREATE TABLE t1 (x INT, y STRING);
INSERT INTO t1 VALUES (1, 'one'), (2, 'two'), (3, 'three');
```

```
-- Clone all the columns and data from one table to another.
CREATE TABLE clone_of_t1 AS SELECT * FROM t1;
```

```
-----+
| summary |
+-----+
| Inserted 3 row(s) |
+-----+
```

```
-- Clone the columns and data, and convert the data to a different file format.
CREATE TABLE parquet_version_of_t1 STORED AS PARQUET AS SELECT * FROM t1;
```

```
-----+
| summary |
+-----+
| Inserted 3 row(s) |
+-----+
```

```
-- Copy only some rows to the new table.
CREATE TABLE subset_of_t1 AS SELECT * FROM t1 WHERE x >= 2;
```

```
-----+
| summary |
+-----+
| Inserted 2 row(s) |
+-----+
```

```
-- Same idea as CREATE TABLE LIKE: clone table layout but do not copy any data.
CREATE TABLE empty_clone_of_t1 AS SELECT * FROM t1 WHERE 1=0;
```

```
-----+
| summary |
+-----+
| Inserted 0 row(s) |
+-----+
```

```
-- Reorder and rename columns and transform the data.
CREATE TABLE t5 AS SELECT upper(y) AS s, x+1 AS a, 'Entirely new column' AS n FROM t1;
```

```
-----+
| summary |
+-----+
| Inserted 3 row(s) |
+-----+
SELECT * FROM t5;
```

```
-----+-----+-----+
| s | a | n |
+-----+-----+-----+
| ONE | 2 | Entirely new column |
| TWO | 3 | Entirely new column |
| THREE | 4 | Entirely new column |
+-----+-----+-----+
```

See [SELECT Statement](#) on page 304 for details about query syntax for the `SELECT` portion of a `CREATE TABLE AS SELECT` statement.

The newly created table inherits the column names that you select from the original table, which you can override by specifying column aliases in the query. Any column or table comments from the original table are not carried over to the new table.



Note: When using the `STORED AS` clause with a `CREATE TABLE AS SELECT` statement, the destination table must be a file format that Impala can write to: currently, text or Parquet. You cannot specify an Avro, SequenceFile, or RCFile table as the destination table for a CTAS operation.

Prior to CDH 5.7 / Impala 2.5, you could use a partitioned table as the source and copy data from it, but could not specify any partitioning clauses for the new table. In CDH 5.7 / Impala 2.5 and higher, you can now use the `PARTITIONED BY` clause with a `CREATE TABLE AS SELECT` statement. The following example demonstrates how you can copy data from an unpartitioned table in a `CREATE TABLE AS SELECT` operation, creating a new partitioned table in the process. The main syntax consideration is the column order in the `PARTITIONED BY` clause and the select list: the partition key columns must be listed last in the select list, in the same order as in the `PARTITIONED BY` clause. Therefore, in this case, the column order in the destination table is different from the source table. You also only specify the column names in the `PARTITIONED BY` clause, not the data types or column comments.

```
create table partitions_no (year smallint, month tinyint, s string);
insert into partitions_no values (2016, 1, 'January 2016'),
  (2016, 2, 'February 2016'), (2016, 3, 'March 2016');

-- Prove that the source table is not partitioned.
show partitions partitions_no;
ERROR: AnalysisException: Table is not partitioned: ctas_partition_by.partitions_no

-- Create new table with partitions based on column values from source table.
create table partitions_yes partitioned by (year, month)
as select s, year, month from partitions_no;
+-----+-----+
| summary |
+-----+-----+
| Inserted 3 row(s) |
+-----+-----+

-- Prove that the destination table is partitioned.
show partitions partitions_yes;
+-----+-----+-----+-----+-----+...
| year | month | #Rows | #Files | Size | ...
+-----+-----+-----+-----+-----+...
| 2016 | 1 | -1 | 1 | 13B | ...
| 2016 | 2 | -1 | 1 | 14B | ...
| 2016 | 3 | -1 | 1 | 11B | ...
| Total | | -1 | 3 | 38B | ...
+-----+-----+-----+-----+-----+...
```

The most convenient layout for partitioned tables is with all the partition key columns at the end. The `CTAS PARTITIONED BY` syntax requires that column order in the select list, resulting in that same column order in the destination table.

```
describe partitions_no;
+-----+-----+-----+
| name | type | comment |
+-----+-----+-----+
| year | smallint |
| month | tinyint |
| s | string |
+-----+-----+-----+

-- The CTAS operation forced us to put the partition key columns last.
-- Having those columns last works better with idioms such as SELECT *
-- for partitioned tables.
describe partitions_yes;
```

name	type	comment
s	string	
year	smallint	
month	tinyint	

Attempting to use a select list with the partition key columns not at the end results in an error due to a column name mismatch:

```
-- We expect this CTAS to fail because non-key column S
-- comes after key columns YEAR and MONTH in the select list.
create table partitions_maybe partitioned by (year, month)
as select year, month, s from partitions_no;
ERROR: AnalysisException: Partition column name mismatch: year != month
```

For example, the following statements show how you can clone all the data in a table, or a subset of the columns and/or rows, or reorder columns, rename them, or construct them out of expressions:

As part of a CTAS operation, you can convert the data to any file format that Impala can write (currently, `TEXTFILE` and `PARQUET`). You cannot specify the lower-level properties of a text table, such as the delimiter.

Sorting considerations: Although you can specify an `ORDER BY` clause in an `INSERT ... SELECT` statement, any `ORDER BY` clause is ignored and the results are not necessarily sorted. An `INSERT ... SELECT` operation potentially creates many different data files, prepared on different data nodes, and therefore the notion of the data being stored in sorted order is impractical.

CREATE TABLE LIKE PARQUET:

The variation `CREATE TABLE ... LIKE PARQUET 'hdfs_path_of_parquet_file'` lets you skip the column definitions of the `CREATE TABLE` statement. The column names and data types are automatically configured based on the organization of the specified Parquet data file, which must already reside in HDFS. You can use a data file located outside the Impala database directories, or a file from an existing Impala Parquet table; either way, Impala only uses the column definitions from the file and does not use the HDFS location for the `LOCATION` attribute of the new table. (Although you can also specify the enclosing directory with the `LOCATION` attribute, to both use the same schema as the data file and point the Impala table at the associated directory for querying.)

The following considerations apply when you use the `CREATE TABLE LIKE PARQUET` technique:

- Any column comments from the original table are not preserved in the new table. Each column in the new table has a comment stating the low-level Parquet field type used to deduce the appropriate SQL column type.
- If you use a data file from a partitioned Impala table, any partition key columns from the original table are left out of the new table, because they are represented in HDFS directory names rather than stored in the data file. To preserve the partition information, repeat the same `PARTITION` clause as in the original `CREATE TABLE` statement.
- The file format of the new table defaults to text, as with other kinds of `CREATE TABLE` statements. To make the new table also use Parquet format, include the clause `STORED AS PARQUET` in the `CREATE TABLE LIKE PARQUET` statement.
- If the Parquet data file comes from an existing Impala table, currently, any `TINYINT` or `SMALLINT` columns are turned into `INT` columns in the new table. Internally, Parquet stores such values as 32-bit integers.
- When the destination table uses the Parquet file format, the `CREATE TABLE AS SELECT` and `INSERT ... SELECT` statements always create at least one data file, even if the `SELECT` part of the statement does not match any rows. You can use such an empty Parquet data file as a template for subsequent `CREATE TABLE LIKE PARQUET` statements.

For more details about creating Parquet tables, and examples of the `CREATE TABLE LIKE PARQUET` syntax, see [Using the Parquet File Format with Impala Tables](#) on page 584.

Visibility and Metadata (TBLPROPERTIES and WITH SERDEPROPERTIES clauses):

You can associate arbitrary items of metadata with a table by specifying the `TBLPROPERTIES` clause. This clause takes a comma-separated list of key-value pairs and stores those items in the metastore database. You can also change the table properties later with an `ALTER TABLE` statement. You can observe the table properties for different delimiter and escape characters using the `DESCRIBE FORMATTED` command, and change those settings for an existing table with `ALTER TABLE ... SET TBLPROPERTIES`.

You can also associate SerDes properties with the table by specifying key-value pairs through the `WITH SERDEPROPERTIES` clause. This metadata is not used by Impala, which has its own built-in serializer and deserializer for the file formats it supports. Particular property values might be needed for Hive compatibility with certain variations of file formats, particularly Avro.

Some DDL operations that interact with other Hadoop components require specifying particular values in the `SERDEPROPERTIES` or `TBLPROPERTIES` fields, such as creating an Avro table or an HBase table. (You typically create HBase tables in Hive, because they require additional clauses not currently available in Impala.)

To see the column definitions and column comments for an existing table, for example before issuing a `CREATE TABLE ... LIKE` or a `CREATE TABLE ... AS SELECT` statement, issue the statement `DESCRIBE table_name`. To see even more detail, such as the location of data files and the values for clauses such as `ROW FORMAT` and `STORED AS`, issue the statement `DESCRIBE FORMATTED table_name`. `DESCRIBE FORMATTED` is also needed to see any overall table comment (as opposed to individual column comments).

After creating a table, your `impala-shell` session or another `impala-shell` connected to the same node can immediately query that table. There might be a brief interval (one statestore heartbeat) before the table can be queried through a different Impala node. To make the `CREATE TABLE` statement return only when the table is recognized by all Impala nodes in the cluster, enable the `SYNC_DDL` query option.

HDFS caching (CACHED IN clause):

If you specify the `CACHED IN` clause, any existing or future data files in the table directory or the partition subdirectories are designated to be loaded into memory with the HDFS caching mechanism. See [Using HDFS Caching with Impala \(CDH 5.1 or higher only\)](#) on page 550 for details about using the HDFS caching feature.

In Impala 2.2 / CDH 5.4 and higher, the optional `WITH REPLICATION` clause for `CREATE TABLE` and `ALTER TABLE` lets you specify a **replication factor**, the number of hosts on which to cache the same data blocks. When Impala processes a cached data block, where the cache replication factor is greater than 1, Impala randomly selects a host that has a cached copy of that data block. This optimization avoids excessive CPU usage on a single host when the same cached data block is processed multiple times. Cloudera recommends specifying a value greater than or equal to the HDFS block replication factor.

Column order:

If you intend to use the table to hold data files produced by some external source, specify the columns in the same order as they appear in the data files.

If you intend to insert or copy data into the table through Impala, or if you have control over the way externally produced data files are arranged, use your judgment to specify columns in the most convenient order:

- If certain columns are often `NULL`, specify those columns last. You might produce data files that omit these trailing columns entirely. Impala automatically fills in the `NULL` values if so.
- If an unpartitioned table will be used as the source for an `INSERT ... SELECT` operation into a partitioned table, specify last in the unpartitioned table any columns that correspond to partition key columns in the partitioned table, and in the same order as the partition key columns are declared in the partitioned table. This technique lets you use `INSERT ... SELECT *` when copying data to the partitioned table, rather than specifying each column name individually.
- If you specify columns in an order that you later discover is suboptimal, you can sometimes work around the problem without recreating the table. You can create a view that selects columns from the original table in a permuted order, then do a `SELECT *` from the view. When inserting data into a table, you can specify a permuted order for the inserted columns to match the order in the destination table.

Hive considerations:

Impala queries can make use of metadata about the table and columns, such as the number of rows in a table or the number of different values in a column. Prior to Impala 1.2.2, to create this metadata, you issued the `ANALYZE TABLE` statement in Hive to gather this information, after creating the table and loading representative data into it. In Impala 1.2.2 and higher, the `COMPUTE STATS` statement produces these statistics within Impala, without needing to use Hive at all.

HBase considerations:



Note:

The Impala `CREATE TABLE` statement cannot create an HBase table, because it currently does not support the `STORED BY` clause needed for HBase tables. Create such tables in Hive, then query them through Impala. For information on using Impala with HBase tables, see [Using Impala to Query HBase Tables](#) on page 608.

Amazon S3 considerations:

To create a table where the data resides in the Amazon Simple Storage Service (S3), specify a `s3a://` prefix `LOCATION` attribute pointing to the data files in S3.

In CDH 5.8 / Impala 2.6 and higher, you can use this special `LOCATION` syntax as part of a `CREATE TABLE AS SELECT` statement.

In CDH 5.8 / Impala 2.6 and higher, Impala DDL statements such as `CREATE DATABASE`, `CREATE TABLE`, `DROP DATABASE CASCADE`, `DROP TABLE`, and `ALTER TABLE [ADD|DROP] PARTITION` can create or remove folders as needed in the Amazon S3 system. Prior to CDH 5.8 / Impala 2.6, you had to create folders yourself and point Impala database, tables, or partitions at them, and manually remove folders when no longer needed. See [Using Impala with the Amazon S3 Filesystem](#) on page 617 for details about reading and writing S3 data with Impala.

Sorting considerations: Although you can specify an `ORDER BY` clause in an `INSERT ... SELECT` statement, any `ORDER BY` clause is ignored and the results are not necessarily sorted. An `INSERT ... SELECT` operation potentially creates many different data files, prepared on different data nodes, and therefore the notion of the data being stored in sorted order is impractical.

HDFS considerations:

The `CREATE TABLE` statement for an internal table creates a directory in HDFS. The `CREATE EXTERNAL TABLE` statement associates the table with an existing HDFS directory, and does not create any new directory in HDFS. To locate the HDFS data directory for a table, issue a `DESCRIBE FORMATTED table` statement. To examine the contents of that HDFS directory, use an OS command such as `hdfs dfs -ls hdfs://path`, either from the OS command line or through the `shell` or `!` commands in `impala-shell`.

The `CREATE TABLE AS SELECT` syntax creates data files under the table data directory to hold any data copied by the `INSERT` portion of the statement. (Even if no data is copied, Impala might create one or more empty data files.)

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have both execute and write permission for the database directory where the table is being created.

Security considerations:

If these statements in your environment contain sensitive literal values such as credit card numbers or tax identifiers, Impala can redact this sensitive information when displaying the statements in log files and other administrative contexts. See http://www.cloudera.com/content/cloudera/en/documentation/core/latest/topics/sg_redaction.html for details.

Cancellation: Certain multi-stage statements (`CREATE TABLE AS SELECT` and `COMPUTE STATS`) can be cancelled during some stages, when running `INSERT` or `SELECT` operations internally. To cancel this statement, use Ctrl-C from the `impala-shell` interpreter, the **Cancel** button from the **Watch** page in Hue, **Actions > Cancel** from the **Queries** list in Cloudera Manager, or **Cancel** from the list of in-flight queries (for a particular node) on the **Queries** tab in the Impala web UI (port 25000).

Related information:

[Overview of Impala Tables](#) on page 222, [ALTER TABLE Statement](#) on page 230, [DROP TABLE Statement](#) on page 280, [Partitioning for Impala Tables](#) on page 568, [Internal Tables](#) on page 223, [External Tables](#) on page 223, [COMPUTE STATS Statement](#) on page 241, [SYNC DDL Query Option](#) on page 356, [SHOW TABLES Statement](#) on page 362, [SHOW CREATE TABLE Statement](#) on page 363, [DESCRIBE Statement](#) on page 264

CREATE VIEW Statement

The `CREATE VIEW` statement lets you create a shorthand abbreviation for a more complicated query. The base query can involve joins, expressions, reordered columns, column aliases, and other SQL features that can make a query hard to understand or maintain.

Because a view is purely a logical construct (an alias for a query) with no physical data behind it, `ALTER VIEW` only involves changes to metadata in the metastore database, not any data files in HDFS.

Syntax:

```
CREATE VIEW [IF NOT EXISTS] view_name
  [(column_name [COMMENT 'column_comment'][, ...])]
  [COMMENT 'view_comment']
  AS select_statement
```

Statement type: DDL**Usage notes:**

The `CREATE VIEW` statement can be useful in scenarios such as the following:

- To turn even the most lengthy and complicated SQL query into a one-liner. You can issue simple queries against the view from applications, scripts, or interactive queries in `impala-shell`. For example:

```
select * from view_name;
select * from view_name order by c1 desc limit 10;
```

The more complicated and hard-to-read the original query, the more benefit there is to simplifying the query using a view.

- To hide the underlying table and column names, to minimize maintenance problems if those names change. In that case, you re-create the view using the new names, and all queries that use the view rather than the underlying tables keep running with no changes.
- To experiment with optimization techniques and make the optimized queries available to all applications. For example, if you find a combination of `WHERE` conditions, join order, join hints, and so on that works the best for a class of queries, you can establish a view that incorporates the best-performing techniques. Applications can then make relatively simple queries against the view, without repeating the complicated and optimized logic over and over. If you later find a better way to optimize the original query, when you re-create the view, all the applications immediately take advantage of the optimized base query.
- To simplify a whole class of related queries, especially complicated queries involving joins between multiple tables, complicated expressions in the column list, and other SQL syntax that makes the query difficult to understand and debug. For example, you might create a view that joins several tables, filters using several `WHERE` conditions, and selects several columns from the result set. Applications might issue queries against this view that only vary in their `LIMIT`, `ORDER BY`, and similar simple clauses.

For queries that require repeating complicated clauses over and over again, for example in the `select` list, `ORDER BY`, and `GROUP BY` clauses, you can use the `WITH` clause as an alternative to creating a view.

You can optionally specify the table-level and the column-level comments as in the `CREATE TABLE` statement.

Complex type considerations:

For tables containing complex type columns (`ARRAY`, `STRUCT`, or `MAP`), you typically use join queries to refer to the complex values. You can use views to hide the join notation, making such tables seem like traditional denormalized

tables, and making those tables queryable by business intelligence tools that do not have built-in support for those complex types. See [Accessing Complex Type Data in Flattened Form Using Views](#) on page 187 for details.

Because you cannot directly issue `SELECT col_name` against a column of complex type, you cannot use a view or a `WITH` clause to “rename” a column by selecting it with a column alias.

If you connect to different Impala nodes within an `impala-shell` session for load-balancing purposes, you can enable the `SYNC_DDL` query option to make each DDL statement wait before returning, until the new or changed metadata has been received by all the Impala nodes. See [SYNC_DDL Query Option](#) on page 356 for details.

Security considerations:

If these statements in your environment contain sensitive literal values such as credit card numbers or tax identifiers, Impala can redact this sensitive information when displaying the statements in log files and other administrative contexts. See http://www.cloudera.com/content/cloudera/en/documentation/core/latest/topics/sg_redaction.html for details.

Cancellation: Cannot be cancelled.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Examples:

```
-- Create a view that is exactly the same as the underlying table.
CREATE VIEW v1 AS SELECT * FROM t1;

-- Create a view that includes only certain columns from the underlying table.
CREATE VIEW v2 AS SELECT c1, c3, c7 FROM t1;

-- Create a view that filters the values from the underlying table.
CREATE VIEW v3 AS SELECT DISTINCT c1, c3, c7 FROM t1 WHERE c1 IS NOT NULL AND c5 > 0;

-- Create a view that reorders and renames columns from the underlying table.
CREATE VIEW v4 AS SELECT c4 AS last_name, c6 AS address, c2 AS birth_date FROM t1;

-- Create a view that runs functions to convert or transform certain columns.
CREATE VIEW v5 AS SELECT c1, CAST(c3 AS STRING) c3, CONCAT(c4,c5) c5, TRIM(c6) c6,
"Constant" c8 FROM t1;

-- Create a view that hides the complexity of a view query.
CREATE VIEW v6 AS SELECT t1.c1, t2.c2 FROM t1 JOIN t2 ON t1.id = t2.id;

-- Create a view with a column comment and a table comment.
CREATE VIEW v7 (c1 COMMENT 'Comment for c1', c2) COMMENT 'Comment for v7' AS SELECT
t1.c1, t1.c2 FROM t1;
```

Related information:

[Overview of Impala Views](#) on page 224, [ALTER VIEW Statement](#) on page 240, [DROP VIEW Statement](#) on page 282

DESCRIBE Statement

The `DESCRIBE` statement displays metadata about a table, such as the column names and their data types. In CDH 5.5 / Impala 2.3 and higher, you can specify the name of a complex type column, which takes the form of a dotted path. The path might include multiple components in the case of a nested type definition. In CDH 5.7 / Impala 2.5 and higher, the `DESCRIBE DATABASE` form can display information about a database.

Syntax:

```
DESCRIBE [DATABASE] [FORMATTED|EXTENDED] object_name

object_name ::=
  [db_name.]table_name[.complex_col_name ...]
  | db_name
```

You can use the abbreviation `DESC` for the `DESCRIBE` statement.

The `DESCRIBE FORMATTED` variation displays additional information, in a format familiar to users of Apache Hive. The extra information includes low-level details such as whether the table is internal or external, when it was created, the file format, the location of the data in HDFS, whether the object is a table or a view, and (for views) the text of the query from the view definition.



Note: The `Compressed` field is not a reliable indicator of whether the table contains compressed data. It typically always shows `No`, because the compression settings only apply during the session that loads data and are not stored persistently with the table metadata.

Describing databases:

By default, the `DESCRIBE` output for a database includes the location and the comment, which can be set by the `LOCATION` and `COMMENT` clauses on the `CREATE DATABASE` statement.

The additional information displayed by the `FORMATTED` or `EXTENDED` keyword includes the HDFS user ID that is considered the owner of the database, and any optional database properties. The properties could be specified by the `WITH DBPROPERTIES` clause if the database is created using a Hive `CREATE DATABASE` statement. Impala currently does not set or do any special processing based on those properties.

The following examples show the variations in syntax and output for describing databases. This feature is available in CDH 5.7 / Impala 2.5 and higher.

```
describe database default;
+-----+-----+-----+
| name | location | comment |
+-----+-----+-----+
| default | /user/hive/warehouse | Default Hive database |
+-----+-----+-----+

describe database formatted default;
+-----+-----+-----+
| name | location | comment |
+-----+-----+-----+
| default | /user/hive/warehouse | Default Hive database |
| Owner: | public | ROLE |
+-----+-----+-----+

describe database extended default;
+-----+-----+-----+
| name | location | comment |
+-----+-----+-----+
| default | /user/hive/warehouse | Default Hive database |
| Owner: | public | ROLE |
+-----+-----+-----+
```

Describing tables:

If the `DATABASE` keyword is omitted, the default for the `DESCRIBE` statement is to refer to a table.

```
-- By default, the table is assumed to be in the current database.
describe my_table;
+-----+-----+-----+
| name | type | comment |
+-----+-----+-----+
| x | int | |
| s | string | |
+-----+-----+-----+

-- Use a fully qualified table name to specify a table in any database.
describe my_database.my_table;
+-----+-----+-----+
| name | type | comment |
+-----+-----+-----+
```

```

| x      | int  |      |
| s      | string |    |
+-----+-----+-----+

-- The formatted or extended output includes additional useful information.
-- The LOCATION field is especially useful to know for DDL statements and HDFS commands
-- during ETL jobs. (The LOCATION includes a full hdfs:// URL, omitted here for
readability.)
describe formatted my_table;
+-----+-----+-----+
| name          |      | type          |      | comment
+-----+-----+-----+
| # col_name    |      | data_type     |      | comment
|              |      | NULL          |      | NULL
| x            |      | int           |      | NULL
| s            |      | string        |      | NULL
|              |      | NULL          |      | NULL
| # Detailed Table Information | NULL | NULL          |      | NULL
| Database:    |      | my_database   |      | NULL
| Owner:       |      | jRussell     |      | NULL
| CreateTime:  |      | Fri Mar 18 15:58:00 PDT 2016 |      | NULL
| LastAccessTime: |      | UNKNOWN      |      | NULL
| Protect Mode: |      | None         |      | NULL
| Retention:   |      | 0            |      | NULL
| Location:    |      | /user/hive/warehouse/my_database.db/my_table |      | NULL
| Table Type:  |      | MANAGED_TABLE |      | NULL
| Table Parameters: |      | NULL         |      | NULL
|              |      | transient_lastDdlTime |      | 1458341880
|              |      | NULL          |      | NULL
| # Storage Information | NULL | NULL          |      | NULL
| SerDe Library: |      | org. ....LazySimpleSerDe |      | NULL
| InputFormat:  |      | org.apache.hadoop.mapred.TextInputFormat |      | NULL
| OutputFormat: |      | org. ....HiveIgnoreKeyTextOutputFormat |      | NULL
| Compressed:   |      | No           |      | NULL
| Num Buckets:  |      | 0            |      | NULL
| Bucket Columns: |      | []           |      | NULL
| Sort Columns: |      | []           |      | NULL
+-----+-----+-----+

```

Complex type considerations:

Because the column definitions for complex types can become long, particularly when such types are nested, the DESCRIBE statement uses special formatting for complex type columns to make the output readable.

For the ARRAY, STRUCT, and MAP types available in CDH 5.5 / Impala 2.3 and higher, the DESCRIBE output is formatted to avoid excessively long lines for multiple fields within a STRUCT, or a nested sequence of complex types.

You can pass a multi-part qualified name to `DESCRIBE` to specify an `ARRAY`, `STRUCT`, or `MAP` column and visualize its structure as if it were a table. For example, if table `T1` contains an `ARRAY` column `A1`, you could issue the statement `DESCRIBE t1.a1`. If table `T1` contained a `STRUCT` column `S1`, and a field `F1` within the `STRUCT` was a `MAP`, you could issue the statement `DESCRIBE t1.s1.f1`. An `ARRAY` is shown as a two-column table, with `ITEM` and `POS` columns. A `STRUCT` is shown as a table with each field representing a column in the table. A `MAP` is shown as a two-column table, with `KEY` and `VALUE` columns.

For example, here is the `DESCRIBE` output for a table containing a single top-level column of each complex type:

```
create table t1 (x int, a array<int>, s struct<f1: string, f2: bigint>, m map<string,int>)
  stored as parquet;

describe t1;
```

name	type	comment
x	int	
a	array<int>	
s	struct< f1:string, f2:bigint >	
m	map<string,int>	

Here are examples showing how to “drill down” into the layouts of complex types, including using multi-part names to examine the definitions of nested types. The `< >` delimiters identify the columns with complex types; these are the columns where you can descend another level to see the parts that make up the complex type. This technique helps you to understand the multi-part names you use as table references in queries involving complex types, and the corresponding column names you refer to in the `SELECT` list. These tables are from the “nested TPC-H” schema, shown in detail in [Sample Schema and Data for Experimenting with Impala Complex Types](#) on page 188.

The `REGION` table contains an `ARRAY` of `STRUCT` elements:

- The first `DESCRIBE` specifies the table name, to display the definition of each top-level column.
- The second `DESCRIBE` specifies the name of a complex column, `REGION.R_NATIONS`, showing that when you include the name of an `ARRAY` column in a `FROM` clause, that table reference acts like a two-column table with columns `ITEM` and `POS`.
- The final `DESCRIBE` specifies the fully qualified name of the `ITEM` field, to display the layout of its underlying `STRUCT` type in table format, with the fields mapped to column names.

```
-- #1: The overall layout of the entire table.
describe region;
```

name	type	comment
r_regionkey	smallint	
r_name	string	
r_comment	string	
r_nations	array<struct< n_nationkey:smallint, n_name:string, n_comment:string >>	

```
-- #2: The ARRAY column within the table.
describe region.r_nations;
```

name	type	comment
item	struct< n_nationkey:smallint, >	

	n_name:string, n_comment:string	
pos	> bigint	

```
-- #3: The STRUCT that makes up each ARRAY element.
-- The fields of the STRUCT act like columns of a table.
describe region.r_nations.item;
```

name	type	comment
n_nationkey	smallint	
n_name	string	
n_comment	string	

The CUSTOMER table contains an ARRAY of STRUCT elements, where one field in the STRUCT is another ARRAY of STRUCT elements:

- Again, the initial DESCRIBE specifies only the table name.
- The second DESCRIBE specifies the qualified name of the complex column, CUSTOMER.C_ORDERS, showing how an ARRAY is represented as a two-column table with columns ITEM and POS.
- The third DESCRIBE specifies the qualified name of the ITEM of the ARRAY column, to see the structure of the nested ARRAY. Again, it has two parts, ITEM and POS. Because the ARRAY contains a STRUCT, the layout of the STRUCT is shown.
- The fourth and fifth DESCRIBE statements drill down into a STRUCT field that is itself a complex type, an ARRAY of STRUCT. The ITEM portion of the qualified name is only required when the ARRAY elements are anonymous. The fields of the STRUCT give names to any other complex types nested inside the STRUCT. Therefore, the DESCRIBE parameters CUSTOMER.C_ORDERS.ITEM.O_LINEITEMS and CUSTOMER.C_ORDERS.O_LINEITEMS are equivalent. (For brevity, Cloudera recommends leaving out the ITEM portion of a qualified name when it is not required.)
- The final DESCRIBE shows the layout of the deeply nested STRUCT type. Because there are no more complex types nested inside this STRUCT, this is as far as you can drill down into the layout for this table.

```
-- #1: The overall layout of the entire table.
describe customer;
```

name	type
c_custkey	bigint
.. more scalar	columns ..
c_orders	array<struct< o_orderkey:bigint, o_orderstatus:string, o_totalprice:decimal(12,2), o_orderdate:string, o_orderpriority:string, o_clerk:string, o_shippriority:int, o_comment:string, o_lineitems:array<struct< l_partkey:bigint, l_suppkey:bigint, l_linenummer:int, l_quantity:decimal(12,2), l_extendedprice:decimal(12,2), l_discount:decimal(12,2), l_tax:decimal(12,2), l_returnflag:string, l_linestatus:string, l_shipdate:string, l_commitdate:string,

```

        l_receiptdate:string,
        l_shipinstruct:string,
        l_shipmode:string,
        l_comment:string
    >>
>>

```

```

-- #2: The ARRAY column within the table.
describe customer.c_orders;

```

```

+-----+-----+
| name | type |
+-----+-----+
| item | struct< |
|      |   o_orderkey:bigint, |
|      |   o_orderstatus:string, |
|... more struct fields ... |
|      |   o_lineitems:array<struct< |
|      |     l_partkey:bigint, |
|... more nested struct fields ... |
|      |     l_suppkey:bigint, |
|      |     l_comment:string |
|      |   >> |
| pos  |   > |
|      | bigint |
+-----+-----+

```

```

-- #3: The STRUCT that makes up each ARRAY element.
-- The fields of the STRUCT act like columns of a table.
describe customer.c_orders.item;

```

```

+-----+-----+
| name | type |
+-----+-----+
| o_orderkey | bigint |
| o_orderstatus | string |
| o_totalprice | decimal(12,2) |
| o_orderdate | string |
| o_orderpriority | string |
| o_clerk | string |
| o_shippriority | int |
| o_comment | string |
| o_lineitems | array<struct< |
|              |   l_partkey:bigint, |
|              |   l_suppkey:bigint, |
|... more struct fields ... |
|              |   l_comment:string |
|              |   >> |
+-----+-----+

```

```

-- #4: The ARRAY nested inside the STRUCT elements of the first ARRAY.
describe customer.c_orders.item.o_lineitems;

```

```

+-----+-----+
| name | type |
+-----+-----+
| item | struct< |
|      |   l_partkey:bigint, |
|      |   l_suppkey:bigint, |
|... more struct fields ... |
|      |   l_comment:string |
|      |   > |
| pos  |   bigint |
+-----+-----+

```

```

-- #5: Shorter form of the previous DESCRIBE. Omits the .ITEM portion of the name
-- because O_LINEITEMS and other field names provide a way to refer to things
-- inside the ARRAY element.
describe customer.c_orders.o_lineitems;

```

```

+-----+-----+
| name | type |
+-----+-----+
| item | struct< |
|      |   l_partkey:bigint, |
|      |   l_suppkey:bigint, |
+-----+-----+

```

```

... more struct fields ...
|      |      | l_comment:string |
|      |      | >               |
| pos  |      | bigint          |
+-----+-----+-----+

-- #6: The STRUCT representing ARRAY elements nested inside
-- another ARRAY of STRUCTs. The lack of any complex types
-- in this output means this is as far as DESCRIBE can
-- descend into the table layout.
describe customer.c_orders.o_lineitems.item;
+-----+-----+-----+
| name          | type          |
+-----+-----+-----+
| l_partkey     | bigint       |
| l_suppkey     | bigint       |
... more scalar columns ...
| l_comment     | string       |
+-----+-----+-----+

```


Usage notes:

After the `impalad` daemons are restarted, the first query against a table can take longer than subsequent queries, because the metadata for the table is loaded before the query is processed. This one-time delay for each table can cause misleading results in benchmark tests or cause unnecessary concern. To “warm up” the Impala metadata cache, you can issue a `DESCRIBE` statement in advance for each table you intend to access later.

When you are dealing with data files stored in HDFS, sometimes it is important to know details such as the path of the data files for an Impala table, and the hostname for the namenode. You can get this information from the `DESCRIBE FORMATTED` output. You specify HDFS URIs or path specifications with statements such as `LOAD DATA` and the `LOCATION` clause of `CREATE TABLE` or `ALTER TABLE`. You might also use HDFS URIs or paths with Linux commands such as `hadoop` and `hdfs` to copy, rename, and so on, data files in HDFS.

If you connect to different Impala nodes within an `impala-shell` session for load-balancing purposes, you can enable the `SYNC_DDL` query option to make each DDL statement wait before returning, until the new or changed metadata has been received by all the Impala nodes. See [SYNC_DDL Query Option](#) on page 356 for details.

Each table can also have associated table statistics and column statistics. To see these categories of information, use the `SHOW TABLE STATS table_name` and `SHOW COLUMN STATS table_name` statements. See [SHOW Statement](#) on page 356 for details.

 **Important:** After adding or replacing data in a table used in performance-critical queries, issue a `COMPUTE STATS` statement to make sure all statistics are up-to-date. Consider updating statistics for a table after any `INSERT`, `LOAD DATA`, or `CREATE TABLE AS SELECT` statement in Impala, or after loading data through Hive and doing a `REFRESH table_name` in Impala. This technique is especially important for tables that are very large, used in join queries, or both.

Examples:

The following example shows the results of both a standard `DESCRIBE` and `DESCRIBE FORMATTED` for different kinds of schema objects:

- `DESCRIBE` for a table or a view returns the name, type, and comment for each of the columns. For a view, if the column value is computed by an expression, the column name is automatically generated as `_c0`, `_c1`, and so on depending on the ordinal number of the column.
- A table created with no special format or storage clauses is designated as a `MANAGED_TABLE` (an “internal table” in Impala terminology). Its data files are stored in an HDFS directory under the default Hive data directory. By default, it uses Text data format.
- A view is designated as `VIRTUAL_VIEW` in `DESCRIBE FORMATTED` output. Some of its properties are `NULL` or blank because they are inherited from the base table. The text of the query that defines the view is part of the `DESCRIBE FORMATTED` output.

- A table with additional clauses in the CREATE TABLE statement has differences in DESCRIBE FORMATTED output. The output for T2 includes the EXTERNAL_TABLE keyword because of the CREATE EXTERNAL TABLE syntax, and different InputFormat and OutputFormat fields to reflect the Parquet file format.

```
[localhost:21000] > create table t1 (x int, y int, s string);
Query: create table t1 (x int, y int, s string)
[localhost:21000] > describe t1;
Query: describe t1
Query finished, fetching results ...
```

name	type	comment
x	int	
y	int	
s	string	

```
Returned 3 row(s) in 0.13s
[localhost:21000] > describe formatted t1;
Query: describe formatted t1
Query finished, fetching results ...
```

name	type	comment
# col_name	data_type	comment
x	int	None
y	int	None
s	string	None
# Detailed Table Information	NULL	NULL
Database:	describe_formatted	NULL
Owner:	cloudera	NULL
CreateTime:	Mon Jul 22 17:03:16 EDT 2013	NULL
LastAccessTime:	UNKNOWN	NULL
Protect Mode:	None	NULL
Retention:	0	NULL
Location:	hdfs://127.0.0.1:8020/user/hive/warehouse/	
	describe_formatted.db/t1	NULL
Table Type:	MANAGED_TABLE	NULL
Table Parameters:	NULL	NULL
	transient_lastDdlTime	1374526996
	NULL	NULL
# Storage Information	NULL	NULL
SerDe Library:	org.apache.hadoop.hive.serde2.lazy.	
	LazySimpleSerDe	NULL
InputFormat:	org.apache.hadoop.mapred.TextInputFormat	NULL
OutputFormat:	org.apache.hadoop.hive ql.io.	
	HiveIgnoreKeyTextOutputFormat	NULL

Compressed:	No	NULL
Num Buckets:	0	NULL
Bucket Columns:	[]	NULL
Sort Columns:	[]	NULL

Returned 26 row(s) in 0.03s

[localhost:21000] > create view v1 as select x, upper(s) from t1;

Query: create view v1 as select x, upper(s) from t1

[localhost:21000] > describe v1;

Query: describe v1

Query finished, fetching results ...

name	type	comment
x	int	
_c1	string	

Returned 2 row(s) in 0.10s

[localhost:21000] > describe formatted v1;

Query: describe formatted v1

Query finished, fetching results ...

name	type	comment
# col_name	data_type	comment
x	NULL	NULL
_c1	int	None
	string	None
	NULL	NULL
# Detailed Table Information	NULL	NULL
Database:	describe_formatted	NULL
Owner:	cloudera	NULL
CreateTime:	Mon Jul 22 16:56:38 EDT 2013	NULL
LastAccessTime:	UNKNOWN	NULL
Protect Mode:	None	NULL
Retention:	0	NULL
Table Type:	VIRTUAL_VIEW	NULL
Table Parameters:	NULL	NULL
	transient_lastDdlTime	1374526598
	NULL	NULL
# Storage Information	NULL	NULL
SerDe Library:	null	NULL
InputFormat:	null	NULL
OutputFormat:	null	NULL
Compressed:	No	NULL
Num Buckets:	0	NULL
Bucket Columns:	[]	NULL
Sort Columns:	[]	NULL
	NULL	NULL
# View Information	NULL	NULL
View Original Text:	SELECT x, upper(s) FROM t1	NULL
View Expanded Text:	SELECT x, upper(s) FROM t1	NULL

Returned 28 row(s) in 0.03s

[localhost:21000] > create external table t2 (x int, y int, s string) stored as parquet location '/user/cloudera/sample_data';

[localhost:21000] > describe formatted t2;

Query: describe formatted t2

Query finished, fetching results ...

name	type
comment	
# col_name	data_type
comment	
NULL	NULL
x	int


```

None          |
| Y           | int
None          |
| s           | string
None          |
|            | NULL
NULL          |
| # Detailed Table Information | NULL
NULL          |
| Database:   | describe_formatted
NULL          |
| Owner:      | cloudera
NULL          |
| CreateTime: | Mon Jul 22 17:01:47 EDT 2013
NULL          |
| LastAccessTime: | UNKNOWN
NULL          |
| Protect Mode: | None
NULL          |
| Retention:   | 0
NULL          |
| Location:    | hdfs://127.0.0.1:8020/user/cloudera/sample_data
NULL          |
| Table Type:  | EXTERNAL_TABLE
NULL          |
| Table Parameters: | NULL
NULL          |
|            | EXTERNAL
TRUE          |
|            | transient_lastDdlTime
1374526907   |
|            | NULL
NULL          |
| # Storage Information | NULL
NULL          |
| SerDe Library: | org.apache.hadoop.hive.serde2.lazy.LazySimpleSerDe
NULL          |
| InputFormat:  | com.cloudera.impala.hive.serde.ParquetInputFormat
NULL          |
| OutputFormat: | com.cloudera.impala.hive.serde.ParquetOutputFormat
NULL          |
| Compressed:   | No
NULL          |
| Num Buckets:  | 0
NULL          |
| Bucket Columns: | []
NULL          |
| Sort Columns: | []
NULL          |
+-----+-----+
Returned 27 row(s) in 0.17s

```

Cancellation: Cannot be cancelled.

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have read and execute permissions for all directories that are part of the table. (A table could span multiple different HDFS directories if it is partitioned. The directories could be widely scattered because a partition can reside in an arbitrary HDFS directory based on its `LOCATION` attribute.)

Related information:

[Overview of Impala Tables](#) on page 222, [CREATE TABLE Statement](#) on page 254, [SHOW TABLES Statement](#) on page 362, [SHOW CREATE TABLE Statement](#) on page 363

DROP DATABASE Statement

Removes a database from the system. The physical operations involve removing the metadata for the database from the metastore, and deleting the corresponding `*.db` directory from HDFS.

Syntax:

```
DROP (DATABASE | SCHEMA) [IF EXISTS] database_name [RESTRICT | CASCADE];
```

Statement type: DDL**Usage notes:**

By default, the database must be empty before it can be dropped, to avoid losing any data.

In CDH 5.5 / Impala 2.3 and higher, you can include the `CASCADE` clause to make Impala drop all tables and other objects in the database before dropping the database itself. The `RESTRICT` clause enforces the original requirement that the database be empty before being dropped. Because the `RESTRICT` behavior is still the default, this clause is optional.

The automatic dropping resulting from the `CASCADE` clause follows the same rules as the corresponding `DROP TABLE`, `DROP VIEW`, and `DROP FUNCTION` statements. In particular, the HDFS directories and data files for any external tables are left behind when the tables are removed.

When you do not use the `CASCADE` clause, drop or move all the objects inside the database manually before dropping the database itself:

- Use the `SHOW TABLES` statement to locate all tables and views in the database, and issue `DROP TABLE` and `DROP VIEW` statements to remove them all.
- Use the `SHOW FUNCTIONS` and `SHOW AGGREGATE FUNCTIONS` statements to locate all user-defined functions in the database, and issue `DROP FUNCTION` and `DROP AGGREGATE FUNCTION` statements to remove them all.
- To keep tables or views contained by a database while removing the database itself, use `ALTER TABLE` and `ALTER VIEW` to move the relevant objects to a different database before dropping the original database.

You cannot drop the current database, that is, the database your session connected to either through the `USE` statement or the `-d` option of `impala-shell`. Issue a `USE` statement to switch to a different database first. Because the `default` database is always available, issuing `USE default` is a convenient way to leave the current database before dropping it.

Hive considerations:

When you drop a database in Impala, the database can no longer be used by Hive.

Examples:

See [CREATE DATABASE Statement](#) on page 246 for examples covering `CREATE DATABASE`, `USE`, and `DROP DATABASE`.

Amazon S3 considerations:

In CDH 5.8 / Impala 2.6 and higher, Impala DDL statements such as `CREATE DATABASE`, `CREATE TABLE`, `DROP DATABASE CASCADE`, `DROP TABLE`, and `ALTER TABLE [ADD|DROP] PARTITION` can create or remove folders as needed in the Amazon S3 system. Prior to CDH 5.8 / Impala 2.6, you had to create folders yourself and point Impala database, tables, or partitions at them, and manually remove folders when no longer needed. See [Using Impala with the Amazon S3 Filesystem](#) on page 617 for details about reading and writing S3 data with Impala.

Cancellation: Cannot be cancelled.

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have write permission for the directory associated with the database.

Examples:

```
create database first_db;
use first_db;
create table t1 (x int);

create database second_db;
```

```

use second_db;
-- Each database has its own namespace for tables.
-- You can reuse the same table names in each database.
create table t1 (s string);

create database temp;

-- You can either USE a database after creating it,
-- or qualify all references to the table name with the name of the database.
-- Here, tables T2 and T3 are both created in the TEMP database.

create table temp.t2 (x int, y int);
use database temp;
create table t3 (s string);

-- You cannot drop a database while it is selected by the USE statement.
drop database temp;
ERROR: AnalysisException: Cannot drop current default database: temp

-- The always-available database 'default' is a convenient one to USE
-- before dropping a database you created.
use default;

-- Before dropping a database, first drop all the tables inside it,
-- or in CDH 5.5 and higher use the CASCADE clause.
drop database temp;
ERROR: ImpalaRuntimeException: Error making 'dropDatabase' RPC to Hive Metastore:
CAUSED BY: InvalidOperationException: Database temp is not empty
show tables in temp;
+-----+
| name  |
+-----+
| t3    |
+-----+

-- CDH 5.5 and higher:
drop database temp cascade;

-- CDH 5.4 and lower:
drop table temp.t3;
drop database temp;

```

Related information:

[Overview of Impala Databases](#) on page 219, [CREATE DATABASE Statement](#) on page 246, [USE Statement](#) on page 372, [SHOW DATABASES](#) on page 361, [DROP TABLE Statement](#) on page 280

DROP FUNCTION Statement

Removes a user-defined function (UDF), so that it is not available for execution during Impala `SELECT` or `INSERT` operations.

Syntax:

To drop C++ UDFs and UDAs:

```
DROP [AGGREGATE] FUNCTION [IF EXISTS] [db_name.]function_name(type[, type...])
```

**Note:**

The preceding syntax, which includes the function signature, also applies to Java UDFs that were created using the corresponding `CREATE FUNCTION` syntax that includes the argument and return types. After upgrading to CDH 5.7 / Impala 2.5 or higher, consider re-creating all Java UDFs with the `CREATE FUNCTION` syntax that does not include the function signature. Java UDFs created this way are now persisted in the metastore database and do not need to be re-created after an Impala restart.

To drop Java UDFs (created using the `CREATE FUNCTION` syntax with no function signature):

```
DROP FUNCTION [IF EXISTS] [db_name.]function_name
```

Statement type: DDL

Usage notes:

Because the same function name could be overloaded with different argument signatures, you specify the argument types to identify the exact function to drop.

Restrictions:

In CDH 5.7 / Impala 2.5 and higher, Impala UDFs and UDAs written in C++ are persisted in the metastore database. Java UDFs are also persisted, if they were created with the new `CREATE FUNCTION` syntax for Java UDFs, where the Java function argument and return types are omitted. Java-based UDFs created with the old `CREATE FUNCTION` syntax do not persist across restarts because they are held in the memory of the `catalogd` daemon. Until you re-create such Java UDFs using the new `CREATE FUNCTION` syntax, you must reload those Java-based UDFs by running the original `CREATE FUNCTION` statements again each time you restart the `catalogd` daemon. Prior to CDH 5.7 / Impala 2.5, the requirement to reload functions after a restart applied to both C++ and Java functions.

Cancellation: Cannot be cancelled.

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, does not need any particular HDFS permissions to perform this statement. All read and write operations are on the metastore database, not HDFS files and directories.

Examples:

The following example shows how to drop Java functions created with the signatureless `CREATE FUNCTION` syntax in CDH 5.7 / Impala 2.5 and higher. Issuing `DROP FUNCTION function_name` removes all the overloaded functions under that name. (See [CREATE FUNCTION Statement](#) on page 248 for a longer example showing how to set up such functions in the first place.)

```
create function my_func location '/user/impala/udfs/udf-examples-cdh570.jar'
  symbol='com.cloudera.impala.TestUdf';

show functions;
```

return type	signature	binary type	is persistent
BIGINT	my_func(BIGINT)	JAVA	true
BOOLEAN	my_func(BOOLEAN)	JAVA	true
BOOLEAN	my_func(BOOLEAN, BOOLEAN)	JAVA	true
...			
BIGINT	testudf(BIGINT)	JAVA	true
BOOLEAN	testudf(BOOLEAN)	JAVA	true
BOOLEAN	testudf(BOOLEAN, BOOLEAN)	JAVA	true
...			

```
drop function my_func;
show functions;
```

return type	signature	binary type	is persistent
BIGINT	testudf(BIGINT)	JAVA	true
BOOLEAN	testudf(BOOLEAN)	JAVA	true
BOOLEAN	testudf(BOOLEAN, BOOLEAN)	JAVA	true
...			

Related information:

[Impala User-Defined Functions \(UDFs\)](#) on page 487, [CREATE FUNCTION Statement](#) on page 248

DROP ROLE Statement (CDH 5.2 or higher only)

The `DROP ROLE` statement removes a role from the metastore database. Once dropped, the role is revoked for all users to whom it was previously assigned, and all privileges granted to that role are revoked. Queries that are already executing are not affected. Impala verifies the role information approximately every 60 seconds, so the effects of `DROP ROLE` might not take effect for new Impala queries for a brief period.

Syntax:

```
DROP ROLE role_name
```

Required privileges:

Only administrative users (initially, a predefined set of users specified in the Sentry service configuration file) can use this statement.

Compatibility:

Impala makes use of any roles and privileges specified by the `GRANT` and `REVOKE` statements in Hive, and Hive makes use of any roles and privileges specified by the `GRANT` and `REVOKE` statements in Impala. The Impala `GRANT` and `REVOKE` statements for privileges do not require the `ROLE` keyword to be repeated before each role name, unlike the equivalent Hive statements.

Related information:

[Enabling Sentry Authorization for Impala](#) on page 105, [GRANT Statement \(CDH 5.2 or higher only\)](#) on page 285 [REVOKE Statement \(CDH 5.2 or higher only\)](#) on page 304, [CREATE ROLE Statement \(CDH 5.2 or higher only\)](#) on page 253, [SHOW Statement](#) on page 356

Cancellation: Cannot be cancelled.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

DROP STATS Statement

Removes the specified statistics from a table or partition. The statistics were originally created by the `COMPUTE STATS` or `COMPUTE INCREMENTAL STATS` statement.

Syntax:

```
DROP STATS [database_name.]table_name
DROP INCREMENTAL STATS [database_name.]table_name PARTITION (partition_spec)

partition_spec ::= partition_col=constant_value
```

The `PARTITION` clause is only allowed in combination with the `INCREMENTAL` clause. It is optional for `COMPUTE INCREMENTAL STATS`, and required for `DROP INCREMENTAL STATS`. Whenever you specify partitions through the `PARTITION (partition_spec)` clause in a `COMPUTE INCREMENTAL STATS` or `DROP INCREMENTAL STATS` statement, you must include all the partitioning columns in the specification, and specify constant values for all the partition key columns.

`DROP STATS` removes all statistics from the table, whether created by `COMPUTE STATS` or `COMPUTE INCREMENTAL STATS`.

`DROP INCREMENTAL STATS` only affects incremental statistics for a single partition, specified through the `PARTITION` clause. The incremental stats are marked as outdated, so that they are recomputed by the next `COMPUTE INCREMENTAL STATS` statement.

Usage notes:

You typically use this statement when the statistics for a table or a partition have become stale due to data files being added to or removed from the associated HDFS data directories, whether by manual HDFS operations or `INSERT`, `INSERT OVERWRITE`, or `LOAD DATA` statements, or adding or dropping partitions.

When a table or partition has no associated statistics, Impala treats it as essentially zero-sized when constructing the execution plan for a query. In particular, the statistics influence the order in which tables are joined in a join query. To ensure proper query planning and good query performance and scalability, make sure to run `COMPUTE STATS` or `COMPUTE INCREMENTAL STATS` on the table or partition after removing any stale statistics.

Dropping the statistics is not required for an unpartitioned table or a partitioned table covered by the original type of statistics. A subsequent `COMPUTE STATS` statement replaces any existing statistics with new ones, for all partitions, regardless of whether the old ones were outdated. Therefore, this statement was rarely used before the introduction of incremental statistics.

Dropping the statistics is required for a partitioned table containing incremental statistics, to make a subsequent `COMPUTE INCREMENTAL STATS` statement rescan an existing partition. See [Table and Column Statistics](#) on page 533 for information about incremental statistics, a new feature available in Impala 2.1.0 and higher.

Statement type: DDL

Cancellation: Cannot be cancelled.

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, does not need any particular HDFS permissions to perform this statement. All read and write operations are on the metastore database, not HDFS files and directories.

Examples:

The following example shows a partitioned table that has associated statistics produced by the `COMPUTE INCREMENTAL STATS` statement, and how the situation evolves as statistics are dropped from specific partitions, then the entire table.

Initially, all table and column statistics are filled in.

```
show table stats item_partitioned;
```

i_category	#Rows	#Files	Size	Bytes Cached	Format	Incremental stats
Books	1733	1	223.74KB	NOT CACHED	PARQUET	true
Children	1786	1	230.05KB	NOT CACHED	PARQUET	true
Electronics	1812	1	232.67KB	NOT CACHED	PARQUET	true
Home	1807	1	232.56KB	NOT CACHED	PARQUET	true
Jewelry	1740	1	223.72KB	NOT CACHED	PARQUET	true
Men	1811	1	231.25KB	NOT CACHED	PARQUET	true
Music	1860	1	237.90KB	NOT CACHED	PARQUET	true
Shoes	1835	1	234.90KB	NOT CACHED	PARQUET	true
Sports	1783	1	227.97KB	NOT CACHED	PARQUET	true
Women	1790	1	226.27KB	NOT CACHED	PARQUET	true
Total	17957	10	2.25MB	0B		

```
show column stats item_partitioned;
```

Column	Type	#Distinct Values	#Nulls	Max Size	Avg Size
i_item_sk	INT	19443	-1	4	4
i_item_id	STRING	9025	-1	16	16
i_rec_start_date	TIMESTAMP	4	-1	16	16
i_rec_end_date	TIMESTAMP	3	-1	16	16
i_item_desc	STRING	13330	-1	200	100.302803039
i_current_price	FLOAT	2807	-1	4	4
i_wholesale_cost	FLOAT	2105	-1	4	4
i_brand_id	INT	965	-1	4	4
i_brand	STRING	725	-1	22	16.1776008605
i_class_id	INT	16	-1	4	4
i_class	STRING	101	-1	15	7.76749992370
i_category_id	INT	10	-1	4	4
i_manufact_id	INT	1857	-1	4	4
i_manufact	STRING	1028	-1	15	11.3295001983
i_size	STRING	8	-1	11	4.33459997177
i_formulation	STRING	12884	-1	20	19.9799995422
i_color	STRING	92	-1	10	5.38089990615

i_units	STRING	22	-1	7	4.18690013885
i_container	STRING	2	-1	7	6.99259996414
i_manager_id	INT	105	-1	4	4
i_product_name	STRING	19094	-1	25	18.0233001708
i_category	STRING	10	0	-1	-1

To remove statistics for particular partitions, use the `DROP INCREMENTAL STATS` statement. After removing statistics for two partitions, the table-level statistics reflect that change in the `#Rows` and `Incremental stats` fields. The counts, maximums, and averages of the column-level statistics are unaffected.



Note: (It is possible that the row count might be preserved in future after a `DROP INCREMENTAL STATS` statement. Check the resolution of the issue [IMPALA-1615](#).)

```
drop incremental stats item_partitioned partition (i_category='Sports');
drop incremental stats item_partitioned partition (i_category='Electronics');
```

```
show table stats item_partitioned
```

i_category	#Rows	#Files	Size	Bytes Cached	Format	Incremental stats
Books	1733	1	223.74KB	NOT CACHED	PARQUET	true
Children	1786	1	230.05KB	NOT CACHED	PARQUET	true
Electronics	-1	1	232.67KB	NOT CACHED	PARQUET	false
Home	1807	1	232.56KB	NOT CACHED	PARQUET	true
Jewelry	1740	1	223.72KB	NOT CACHED	PARQUET	true
Men	1811	1	231.25KB	NOT CACHED	PARQUET	true
Music	1860	1	237.90KB	NOT CACHED	PARQUET	true
Shoes	1835	1	234.90KB	NOT CACHED	PARQUET	true
Sports	-1	1	227.97KB	NOT CACHED	PARQUET	false
Women	1790	1	226.27KB	NOT CACHED	PARQUET	true
Total	17957	10	2.25MB	0B		

```
show column stats item_partitioned
```

Column	Type	#Distinct Values	#Nulls	Max Size	Avg Size
i_item_sk	INT	19443	-1	4	4
i_item_id	STRING	9025	-1	16	16
i_rec_start_date	TIMESTAMP	4	-1	16	16
i_rec_end_date	TIMESTAMP	3	-1	16	16
i_item_desc	STRING	13330	-1	200	100.302803039
i_current_price	FLOAT	2807	-1	4	4
i_wholesale_cost	FLOAT	2105	-1	4	4
i_brand_id	INT	965	-1	4	4
i_brand	STRING	725	-1	22	16.1776008605
i_class_id	INT	16	-1	4	4
i_class	STRING	101	-1	15	7.76749992370
i_category_id	INT	10	-1	4	4
i_manufact_id	INT	1857	-1	4	4
i_manufact	STRING	1028	-1	15	11.3295001983
i_size	STRING	8	-1	11	4.33459997177
i_formulation	STRING	12884	-1	20	19.9799995422
i_color	STRING	92	-1	10	5.38089990615
i_units	STRING	22	-1	7	4.18690013885
i_container	STRING	2	-1	7	6.99259996414
i_manager_id	INT	105	-1	4	4
i_product_name	STRING	19094	-1	25	18.0233001708
i_category	STRING	10	0	-1	-1

To remove all statistics from the table, whether produced by `COMPUTE STATS` or `COMPUTE INCREMENTAL STATS`, use the `DROP STATS` statement without the `INCREMENTAL` clause). Now, both table-level and column-level statistics are reset.

```
drop stats item_partitioned;
```

```
show table stats item_partitioned
```

i_category	#Rows	#Files	Size	Bytes Cached	Format	Incremental stats
Books	-1	1	223.74KB	NOT CACHED	PARQUET	false
Children	-1	1	230.05KB	NOT CACHED	PARQUET	false
Electronics	-1	1	232.67KB	NOT CACHED	PARQUET	false
Home	-1	1	232.56KB	NOT CACHED	PARQUET	false
Jewelry	-1	1	223.72KB	NOT CACHED	PARQUET	false
Men	-1	1	231.25KB	NOT CACHED	PARQUET	false
Music	-1	1	237.90KB	NOT CACHED	PARQUET	false
Shoes	-1	1	234.90KB	NOT CACHED	PARQUET	false
Sports	-1	1	227.97KB	NOT CACHED	PARQUET	false
Women	-1	1	226.27KB	NOT CACHED	PARQUET	false
Total	-1	10	2.25MB	0B		

```
show column stats item_partitioned
```

Column	Type	#Distinct Values	#Nulls	Max Size	Avg Size
i_item_sk	INT	-1	-1	4	4
i_item_id	STRING	-1	-1	-1	-1
i_rec_start_date	TIMESTAMP	-1	-1	16	16
i_rec_end_date	TIMESTAMP	-1	-1	16	16
i_item_desc	STRING	-1	-1	-1	-1
i_current_price	FLOAT	-1	-1	4	4
i_wholesale_cost	FLOAT	-1	-1	4	4
i_brand_id	INT	-1	-1	4	4
i_brand	STRING	-1	-1	-1	-1
i_class_id	INT	-1	-1	4	4
i_class	STRING	-1	-1	-1	-1
i_category_id	INT	-1	-1	4	4
i_manufact_id	INT	-1	-1	4	4
i_manufact	STRING	-1	-1	-1	-1
i_size	STRING	-1	-1	-1	-1
i_formulation	STRING	-1	-1	-1	-1
i_color	STRING	-1	-1	-1	-1
i_units	STRING	-1	-1	-1	-1
i_container	STRING	-1	-1	-1	-1
i_manager_id	INT	-1	-1	4	4
i_product_name	STRING	-1	-1	-1	-1
i_category	STRING	10	0	-1	-1

Related information:

[COMPUTE STATS Statement](#) on page 241, [SHOW TABLE STATS Statement](#) on page 365, [SHOW COLUMN STATS Statement](#) on page 366, [Table and Column Statistics](#) on page 533

DROP TABLE Statement

Removes an Impala table. Also removes the underlying HDFS data files for internal tables, although not for external tables.

Syntax:

```
DROP TABLE [IF EXISTS] [db_name.]table_name [PURGE]
```

IF EXISTS clause:

The optional `IF EXISTS` clause makes the statement succeed whether or not the table exists. If the table does exist, it is dropped; if it does not exist, the statement has no effect. This capability is useful in standardized setup scripts that remove existing schema objects and create new ones. By using some combination of `IF EXISTS` for the `DROP` statements and `IF NOT EXISTS` clauses for the `CREATE` statements, the script can run successfully the first time you run it (when the objects do not exist yet) and subsequent times (when some or all of the objects do already exist).

PURGE clause:

The optional `PURGE` keyword, available in CDH 5.5 / Impala 2.3 and higher, causes Impala to remove the associated HDFS data files immediately, rather than going through the HDFS trashcan mechanism. Use this keyword when dropping a table if it is crucial to remove the data as quickly as possible to free up space, or if there is a problem with the trashcan, such as the trash cannot be configured or being in a different HDFS encryption zone than the data files.

Statement type: DDL

Usage notes:

By default, Impala removes the associated HDFS directory and data files for the table. If you issue a `DROP TABLE` and the data files are not deleted, it might be for the following reasons:

- If the table was created with the [EXTERNAL](#) clause, Impala leaves all files and directories untouched. Use external tables when the data is under the control of other Hadoop components, and Impala is only used to query the data files from their original locations.
- Impala might leave the data files behind unintentionally, if there is no HDFS location available to hold the HDFS trashcan for the `impala` user. See [User Account Requirements](#) on page 26 for the procedure to set up the required HDFS home directory.

Make sure that you are in the correct database before dropping a table, either by issuing a `USE` statement first or by using a fully qualified name `db_name.table_name`.

If you intend to issue a `DROP DATABASE` statement, first issue `DROP TABLE` statements to remove all the tables in that database.

Examples:

```
create database temporary;
use temporary;
create table unimportant (x int);
create table trivial (s string);
-- Drop a table in the current database.
drop table unimportant;
-- Switch to a different database.
use default;
-- To drop a table in a different database...
drop table trivial;
ERROR: AnalysisException: Table does not exist: default.trivial
-- ...use a fully qualified name.
drop table temporary.trivial;
```

For other tips about managing and reclaiming Impala disk space, see [Managing Disk Space for Impala Data](#) on page 98.

Amazon S3 considerations:

The `DROP TABLE` statement can remove data files from S3 if the associated S3 table is an internal table. In CDH 5.8 / Impala 2.6 and higher, as part of improved support for writing to S3, Impala also removes the associated folder when dropping an internal table that resides on S3. See [Using Impala with the Amazon S3 Filesystem](#) on page 617 for details about working with S3 tables.

For best compatibility with the S3 write support in CDH 5.8 / Impala 2.6 and higher:

- Use native Hadoop techniques to create data files in S3 for querying through Impala.
- Use the `PURGE` clause of `DROP TABLE` when dropping internal (managed) tables.

By default, when you drop an internal (managed) table, the data files are moved to the HDFS trashcan. This operation is expensive for tables that reside on the Amazon S3 filesystem. Therefore, for S3 tables, prefer to use `DROP TABLE table_name PURGE` rather than the default `DROP TABLE` statement. The `PURGE` clause makes Impala delete the data files immediately, skipping the HDFS trashcan. For the `PURGE` clause to work effectively, you must originally create the data files on S3 using one of the tools from the Hadoop ecosystem, such as `hadoop fs -cp`, or `INSERT` in Impala or Hive.

In CDH 5.8 / Impala 2.6 and higher, Impala DDL statements such as `CREATE DATABASE`, `CREATE TABLE`, `DROP DATABASE CASCADE`, `DROP TABLE`, and `ALTER TABLE [ADD|DROP] PARTITION` can create or remove folders as

needed in the Amazon S3 system. Prior to CDH 5.8 / Impala 2.6, you had to create folders yourself and point Impala database, tables, or partitions at them, and manually remove folders when no longer needed. See [Using Impala with the Amazon S3 Filesystem](#) on page 617 for details about reading and writing S3 data with Impala.

Cancellation: Cannot be cancelled.

HDFS permissions:

For an internal table, the user ID that the `impalad` daemon runs under, typically the `impala` user, must have write permission for all the files and directories that make up the table.

For an external table, dropping the table only involves changes to metadata in the metastore database. Because Impala does not remove any HDFS files or directories when external tables are dropped, no particular permissions are needed for the associated HDFS files or directories.

Related information:

[Overview of Impala Tables](#) on page 222, [ALTER TABLE Statement](#) on page 230, [CREATE TABLE Statement](#) on page 254, [Partitioning for Impala Tables](#) on page 568, [Internal Tables](#) on page 223, [External Tables](#) on page 223

DROP VIEW Statement

Removes the specified view, which was originally created by the `CREATE VIEW` statement. Because a view is purely a logical construct (an alias for a query) with no physical data behind it, `DROP VIEW` only involves changes to metadata in the metastore database, not any data files in HDFS.

Syntax:

```
DROP VIEW [IF EXISTS] [db_name.]view_name
```

Statement type: DDL

Cancellation: Cannot be cancelled.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Examples:

The following example creates a series of views and then drops them. These examples illustrate how views are associated with a particular database, and both the view definitions and the view names for `CREATE VIEW` and `DROP VIEW` can refer to a view in the current database or a fully qualified view name.

```
-- Create and drop a view in the current database.
CREATE VIEW few_rows_from_t1 AS SELECT * FROM t1 LIMIT 10;
DROP VIEW few_rows_from_t1;

-- Create and drop a view referencing a table in a different database.
CREATE VIEW table_from_other_db AS SELECT x FROM db1.foo WHERE x IS NOT NULL;
DROP VIEW table_from_other_db;

USE db1;
-- Create a view in a different database.
CREATE VIEW db2.v1 AS SELECT * FROM db2.foo;
-- Switch into the other database and drop the view.
USE db2;
DROP VIEW v1;

USE db1;
-- Create a view in a different database.
CREATE VIEW db2.v1 AS SELECT * FROM db2.foo;
-- Drop a view in the other database.
DROP VIEW db2.v1;
```

Related information:

[Overview of Impala Views](#) on page 224, [CREATE VIEW Statement](#) on page 263, [ALTER VIEW Statement](#) on page 240

EXPLAIN Statement

Returns the execution plan for a statement, showing the low-level mechanisms that Impala will use to read the data, divide the work among nodes in the cluster, and transmit intermediate and final results across the network. Use `explain` followed by a complete `SELECT` query. For example:

Syntax:

```
EXPLAIN { select_query | ctas_stmt | insert_stmt }
```

The *select_query* is a `SELECT` statement, optionally prefixed by a `WITH` clause. See [SELECT Statement](#) on page 304 for details.

The *insert_stmt* is an `INSERT` statement that inserts into or overwrites an existing table. It can use either the `INSERT ... SELECT` or `INSERT ... VALUES` syntax. See [INSERT Statement](#) on page 286 for details.

The *ctas_stmt* is a `CREATE TABLE` statement using the `AS SELECT` clause, typically abbreviated as a “CTAS” operation. See [CREATE TABLE Statement](#) on page 254 for details.

Usage notes:

You can interpret the output to judge whether the query is performing efficiently, and adjust the query and/or the schema if not. For example, you might change the tests in the `WHERE` clause, add hints to make join operations more efficient, introduce subqueries, change the order of tables in a join, add or change partitioning for a table, collect column statistics and/or table statistics in Hive, or any other performance tuning steps.

The `EXPLAIN` output reminds you if table or column statistics are missing from any table involved in the query. These statistics are important for optimizing queries involving large tables or multi-table joins. See [COMPUTE STATS Statement](#) on page 241 for how to gather statistics, and [Table and Column Statistics](#) on page 533 for how to use this information for query tuning.

Read the `EXPLAIN` plan from bottom to top:

- The last part of the plan shows the low-level details such as the expected amount of data that will be read, where you can judge the effectiveness of your partitioning strategy and estimate how long it will take to scan a table based on total data size and the size of the cluster.
- As you work your way up, next you see the operations that will be parallelized and performed on each Impala node.
- At the higher levels, you see how data flows when intermediate result sets are combined and transmitted from one node to another.
- See [EXPLAIN_LEVEL Query Option](#) on page 336 for details about the `EXPLAIN_LEVEL` query option, which lets you customize how much detail to show in the `EXPLAIN` plan depending on whether you are doing high-level or low-level tuning, dealing with logical or physical aspects of the query.

If you come from a traditional database background and are not familiar with data warehousing, keep in mind that Impala is optimized for full table scans across very large tables. The structure and distribution of this data is typically not suitable for the kind of indexing and single-row lookups that are common in OLTP environments. Seeing a query scan entirely through a large table is common, not necessarily an indication of an inefficient query. Of course, if you can reduce the volume of scanned data by orders of magnitude, for example by using a query that affects only certain partitions within a partitioned table, then you might be able to optimize a query so that it executes in seconds rather than minutes.

For more information and examples to help you interpret `EXPLAIN` output, see [Using the EXPLAIN Plan for Performance Tuning](#) on page 557.

Extended EXPLAIN output:

For performance tuning of complex queries, and capacity planning (such as using the admission control and resource management features), you can enable more detailed and informative output for the `EXPLAIN` statement. In the `impala-shell` interpreter, issue the command `SET EXPLAIN_LEVEL=level`, where *level* is an integer from 0 to 3 or corresponding mnemonic values `minimal`, `standard`, `extended`, or `verbose`.

When extended EXPLAIN output is enabled, EXPLAIN statements print information about estimated memory requirements, minimum number of virtual cores, and so on.

See [EXPLAIN_LEVEL Query Option](#) on page 336 for details and examples.

Examples:

This example shows how the standard EXPLAIN output moves from the lowest (physical) level to the higher (logical) levels. The query begins by scanning a certain amount of data; each node performs an aggregation operation (evaluating COUNT(*)) on some subset of data that is local to that node; the intermediate results are transmitted back to the coordinator node (labelled here as the EXCHANGE node); lastly, the intermediate results are summed to display the final result.

```
[impalad-host:21000] > explain select count(*) from customer_address;
+-----+
| Explain String |
+-----+
| Estimated Per-Host Requirements: Memory=42.00MB VCores=1 |
| 03:AGGREGATE [MERGE FINALIZE] |
|   output: sum(count(*)) |
| 02:EXCHANGE [PARTITION=UNPARTITIONED] |
| 01:AGGREGATE |
|   output: count(*) |
| 00:SCAN HDFS [default.customer_address] |
|   partitions=1/1 size=5.25MB |
+-----+
```

These examples show how the extended EXPLAIN output becomes more accurate and informative as statistics are gathered by the COMPUTE STATS statement. Initially, much of the information about data size and distribution is marked “unavailable”. Impala can determine the raw data size, but not the number of rows or number of distinct values for each column without additional analysis. The COMPUTE STATS statement performs this analysis, so a subsequent EXPLAIN statement has additional information to use in deciding how to optimize the distributed query.

```
[localhost:21000] > set explain_level=extended;
EXPLAIN_LEVEL set to extended
[localhost:21000] > explain select x from t1;
[localhost:21000] > explain select x from t1;
+-----+
| Explain String |
+-----+
| Estimated Per-Host Requirements: Memory=32.00MB VCores=1 |
| 01:EXCHANGE [PARTITION=UNPARTITIONED] |
|   hosts=1 per-host-mem=unavailable |
|   tuple-ids=0 row-size=4B cardinality=unavailable |
| 00:SCAN HDFS [default.t2, PARTITION=RANDOM] |
|   partitions=1/1 size=36B |
|   table stats: unavailable |
|   column stats: unavailable |
|   hosts=1 per-host-mem=32.00MB |
|   tuple-ids=0 row-size=4B cardinality=unavailable |
+-----+
```

```
[localhost:21000] > compute stats t1;
+-----+
| summary |
+-----+
| Updated 1 partition(s) and 1 column(s). |
+-----+
[localhost:21000] > explain select x from t1;
+-----+
| Explain String |
+-----+
```

```

Estimated Per-Host Requirements: Memory=64.00MB VCores=1
01:EXCHANGE [PARTITION=UNPARTITIONED]
  hosts=1 per-host-mem=unavailable
  tuple-ids=0 row-size=4B cardinality=0
00:SCAN HDFS [default.t1, PARTITION=RANDOM]
  partitions=1/1 size=36B
  table stats: 0 rows total
  column stats: all
  hosts=1 per-host-mem=64.00MB
  tuple-ids=0 row-size=4B cardinality=0

```

Security considerations:

If these statements in your environment contain sensitive literal values such as credit card numbers or tax identifiers, Impala can redact this sensitive information when displaying the statements in log files and other administrative contexts. See http://www.cloudera.com/content/cloudera/en/documentation/core/latest/topics/sg_redaction.html for details.

Cancellation: Cannot be cancelled.

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have read and execute permissions for all applicable directories in all source tables for the query that is being explained. (A `SELECT` operation could read files from multiple different HDFS directories if the source table is partitioned.)

Related information:

[SELECT Statement](#) on page 304, [INSERT Statement](#) on page 286, [CREATE TABLE Statement](#) on page 254, [Understanding Impala Query Performance - EXPLAIN Plans and Query Profiles](#) on page 556

GRANT Statement (CDH 5.2 or higher only)

The `GRANT` statement grants roles or privileges on specified objects to groups. Only Sentry administrative users can grant roles to a group.

Syntax:

```

GRANT ROLE role_name TO GROUP group_name

GRANT privilege ON object_type object_name
  TO [ROLE] roleName
  [WITH GRANT OPTION]

privilege ::= SELECT | SELECT(column_name) | INSERT | ALL
object_type ::= TABLE | DATABASE | SERVER | URI

```

Typically, the object name is an identifier. For URIs, it is a string literal.

Required privileges:

Only administrative users (initially, a predefined set of users specified in the Sentry service configuration file) can use this statement.

The `WITH GRANT OPTION` clause allows members of the specified role to issue `GRANT` and `REVOKE` statements for those same privileges. Hence, if a role has the `ALL` privilege on a database and the `WITH GRANT OPTION` set, users granted that role can execute `GRANT/REVOKE` statements only for that database or child tables of the database. This means a user could revoke the privileges of the user that provided them the `GRANT OPTION`.

Impala does not currently support revoking only the `WITH GRANT OPTION` from a privilege previously granted to a role. To remove the `WITH GRANT OPTION`, revoke the privilege and grant it again without the `WITH GRANT OPTION` flag.

The ability to grant or revoke `SELECT` privilege on specific columns is available in CDH 5.5 / Impala 2.3 and higher. See https://www.cloudera.com/documentation/enterprise/latest/topics/sg_hive_sql.html for details.

Compatibility:

- The Impala `GRANT` and `REVOKE` statements are available in CDH 5.2 and later.
- In CDH 5.1 and later, Impala can make use of any roles and privileges specified by the `GRANT` and `REVOKE` statements in Hive, when your system is configured to use the Sentry service instead of the file-based policy mechanism.
- The Impala `GRANT` and `REVOKE` statements for privileges do not require the `ROLE` keyword to be repeated before each role name, unlike the equivalent Hive statements.
- Currently, each Impala `GRANT` or `REVOKE` statement can only grant or revoke a single privilege to or from a single role.

Cancellation: Cannot be cancelled.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Related information:

[Enabling Sentry Authorization for Impala](#) on page 105, [REVOKE Statement \(CDH 5.2 or higher only\)](#) on page 304, [CREATE ROLE Statement \(CDH 5.2 or higher only\)](#) on page 253, [DROP ROLE Statement \(CDH 5.2 or higher only\)](#) on page 277, [SHOW Statement](#) on page 356

INSERT Statement

Impala supports inserting into tables and partitions that you create with the Impala `CREATE TABLE` statement, or pre-defined tables and partitions created through Hive.

Syntax:

```
[with_clause]
INSERT { INTO | OVERWRITE } [TABLE] table_name
  [(column_list)]
  [ PARTITION (partition_clause)]
  {
    [hint_clause] select_statement
  | VALUES (value [, value ...]) [, (value [, value ...]) ...]
  }

partition_clause ::= col_name [= constant] [, col_name [= constant] ...]

hint_clause ::= [SHUFFLE] | [NOSHUFFLE]    (Note: the square brackets are part of the
syntax.)
```

Appending or replacing (INTO and OVERWRITE clauses):

The `INSERT INTO` syntax appends data to a table. The existing data files are left as-is, and the inserted data is put into one or more new data files.

The `INSERT OVERWRITE` syntax replaces the data in a table. Currently, the overwritten data files are deleted immediately; they do not go through the HDFS trash mechanism.

Complex type considerations:

The `INSERT` statement currently does not support writing data files containing complex types (`ARRAY`, `STRUCT`, and `MAP`). To prepare Parquet data for such tables, you generate the data files outside Impala and then use `LOAD DATA` or `CREATE EXTERNAL TABLE` to associate those data files with the table. Currently, such tables must use the Parquet file format. See [Complex Types \(CDH 5.5 or higher only\)](#) on page 167 for details about working with complex types.

Ignoring duplicate partition keys for Kudu tables (IGNORE clause)

Normally, an `INSERT` operation into a Kudu table fails if it would result in duplicate partition key columns for any rows. Specify `INSERT IGNORE rest_of_statement` to make the `INSERT` continue in this case. The rows that would have duplicate partition key columns are not inserted.

Usage notes:

Impala currently supports:

- Copy data from another table using `SELECT` query. In Impala 1.2.1 and higher, you can combine `CREATE TABLE` and `INSERT` operations into a single step with the `CREATE TABLE AS SELECT` syntax, which bypasses the actual `INSERT` keyword.
- An optional [WITH clause](#) before the `INSERT` keyword, to define a subquery referenced in the `SELECT` portion.
- Create one or more new rows using constant expressions through `VALUES` clause. (The `VALUES` clause was added in Impala 1.0.1.)
- By default, the first column of each newly inserted row goes into the first column of the table, the second column into the second column, and so on.

You can also specify the columns to be inserted, an arbitrarily ordered subset of the columns in the destination table, by specifying a column list immediately after the name of the destination table. This feature lets you adjust the inserted columns to match the layout of a `SELECT` statement, rather than the other way around. (This feature was added in Impala 1.1.)

The number of columns mentioned in the column list (known as the “column permutation”) must match the number of columns in the `SELECT` list or the `VALUES` tuples. The order of columns in the column permutation can be different than in the underlying table, and the columns of each input row are reordered to match. If the number of columns in the column permutation is less than in the destination table, all unmentioned columns are set to `NULL`.

- For a partitioned table, the optional `PARTITION` clause identifies which partition or partitions the new values go into. If a partition key column is given a constant value such as `PARTITION (year=2012)` or `PARTITION (year=2012, month=2)`, all the inserted rows use those same values for those partition key columns and you omit any corresponding columns in the source table from the `SELECT` list. This form is known as “static partitioning”.

If a partition key column is mentioned but not assigned a value, such as in `PARTITION (year, region)` (both columns unassigned) or `PARTITION(year, region='CA')` (year column unassigned), the unassigned columns are filled in with the final columns of the `SELECT` list. In this case, the number of columns in the `SELECT` list must equal the number of columns in the column permutation plus the number of partition key columns not assigned a constant value. This form is known as “dynamic partitioning”.

See [Static and Dynamic Partitioning Clauses](#) on page 569 for examples and performance characteristics of static and dynamic partitioned inserts.

- An optional hint clause immediately before the `SELECT` keyword, to fine-tune the behavior when doing an `INSERT . . . SELECT` operation into partitioned Parquet tables. The hint keywords are `[SHUFFLE]` and `[NOSHUFFLE]`, including the square brackets. Inserting into partitioned Parquet tables can be a resource-intensive operation because it potentially involves many files being written to HDFS simultaneously, and separate large memory buffers being allocated to buffer the data for each partition. For usage details, see [Loading Data into Parquet Tables](#) on page 585.

**Note:**

- Insert commands that partition or add files result in changes to Hive metadata. Because Impala uses Hive metadata, such changes may necessitate a metadata refresh. For more information, see the [REFRESH](#) function.
- Currently, Impala can only insert data into tables that use the text and Parquet formats. For other file formats, insert the data using Hive and use Impala to query it.
- As an alternative to the `INSERT` statement, if you have existing data files elsewhere in HDFS, the `LOAD DATA` statement can move those files into a table. This statement works with tables of any file format.

Statement type: DML (but still affected by [SYNC_DDL](#) query option)

Usage notes:

When you insert the results of an expression, particularly of a built-in function call, into a small numeric column such as `INT`, `SMALLINT`, `TINYINT`, or `FLOAT`, you might need to use a `CAST()` expression to coerce values into the appropriate type. Impala does not automatically convert from a larger type to a smaller one. For example, to insert cosine values into a `FLOAT` column, write `CAST(COS(angle) AS FLOAT)` in the `INSERT` statement to make the conversion explicit.

File format considerations:

Because Impala can read certain file formats that it cannot write, the `INSERT` statement does not work for all kinds of Impala tables. See [How Impala Works with Hadoop File Formats](#) on page 575 for details about what file formats are supported by the `INSERT` statement.

Any `INSERT` statement for a Parquet table requires enough free space in the HDFS filesystem to write one block. Because Parquet data files use a block size of 1 GB by default, an `INSERT` might fail (even for a very small amount of data) if your HDFS is running low on space.

If you connect to different Impala nodes within an `impala-shell` session for load-balancing purposes, you can enable the `SYNC_DDL` query option to make each DDL statement wait before returning, until the new or changed metadata has been received by all the Impala nodes. See [SYNC_DDL Query Option](#) on page 356 for details.



Important: After adding or replacing data in a table used in performance-critical queries, issue a `COMPUTE STATS` statement to make sure all statistics are up-to-date. Consider updating statistics for a table after any `INSERT`, `LOAD DATA`, or `CREATE TABLE AS SELECT` statement in Impala, or after loading data through Hive and doing a `REFRESH table_name` in Impala. This technique is especially important for tables that are very large, used in join queries, or both.

Examples:

The following example sets up new tables with the same definition as the `TAB1` table from the [Tutorial](#) section, using different file formats, and demonstrates inserting data into the tables created with the `STORED AS TEXTFILE` and `STORED AS PARQUET` clauses:

```
CREATE DATABASE IF NOT EXISTS file_formats;
USE file_formats;

DROP TABLE IF EXISTS text_table;
CREATE TABLE text_table
( id INT, col_1 BOOLEAN, col_2 DOUBLE, col_3 TIMESTAMP )
STORED AS TEXTFILE;

DROP TABLE IF EXISTS parquet_table;
CREATE TABLE parquet_table
( id INT, col_1 BOOLEAN, col_2 DOUBLE, col_3 TIMESTAMP )
STORED AS PARQUET;
```

With the `INSERT INTO TABLE` syntax, each new set of inserted rows is appended to any existing data in the table. This is how you would record small amounts of data that arrive continuously, or ingest new batches of data alongside the existing data. For example, after running 2 `INSERT INTO TABLE` statements with 5 rows each, the table contains 10 rows total:

```
[localhost:21000] > insert into table text_table select * from default.tab1;
Inserted 5 rows in 0.41s

[localhost:21000] > insert into table text_table select * from default.tab1;
Inserted 5 rows in 0.46s

[localhost:21000] > select count(*) from text_table;
+-----+
| count(*) |
+-----+
| 10       |
+-----+
Returned 1 row(s) in 0.26s
```


With the `INSERT OVERWRITE TABLE` syntax, each new set of inserted rows replaces any existing data in the table. This is how you load data to query in a data warehousing scenario where you analyze just the data for a particular day, quarter, and so on, discarding the previous data each time. You might keep the entire set of data in one raw table, and transfer and transform certain rows into a more compact and efficient form to perform intensive analysis on that subset.

For example, here we insert 5 rows into a table using the `INSERT INTO` clause, then replace the data by inserting 3 rows with the `INSERT OVERWRITE` clause. Afterward, the table only contains the 3 rows from the final `INSERT` statement.

```
[localhost:21000] > insert into table parquet_table select * from default.tab1;
Inserted 5 rows in 0.35s

[localhost:21000] > insert overwrite table parquet_table select * from default.tab1
limit 3;
Inserted 3 rows in 0.43s
[localhost:21000] > select count(*) from parquet_table;
+-----+
| count(*) |
+-----+
| 3         |
+-----+
Returned 1 row(s) in 0.43s
```

The [VALUES](#) clause lets you insert one or more rows by specifying constant values for all the columns. The number, types, and order of the expressions must match the table definition.



Note: The `INSERT ... VALUES` technique is not suitable for loading large quantities of data into HDFS-based tables, because the insert operations cannot be parallelized, and each one produces a separate data file. Use it for setting up small dimension tables or tiny amounts of data for experimenting with SQL syntax, or with HBase tables. Do not use it for large ETL jobs or benchmark tests for load operations. Do not run scripts with thousands of `INSERT ... VALUES` statements that insert a single row each time. If you do run `INSERT ... VALUES` operations to load data into a staging table as one stage in an ETL pipeline, include multiple row values if possible within each `VALUES` clause, and use a separate database to make cleanup easier if the operation does produce many tiny files.

The following example shows how to insert one row or multiple rows, with expressions of different types, using literal values, expressions, and function return values:

```
create table val_test_1 (c1 int, c2 float, c3 string, c4 boolean, c5 timestamp);
insert into val_test_1 values (100, 99.9/10, 'abc', true, now());
create table val_test_2 (id int, token string);
insert overwrite val_test_2 values (1, 'a'), (2, 'b'), (-1, 'xyzy');
```

These examples show the type of “not implemented” error that you see when attempting to insert data into a table with a file format that Impala currently does not write to:

```
DROP TABLE IF EXISTS sequence_table;
CREATE TABLE sequence_table
( id INT, col_1 BOOLEAN, col_2 DOUBLE, col_3 TIMESTAMP )
STORED AS SEQUENCEFILE;

DROP TABLE IF EXISTS rc_table;
CREATE TABLE rc_table
( id INT, col_1 BOOLEAN, col_2 DOUBLE, col_3 TIMESTAMP )
STORED AS RCFILE;

[localhost:21000] > insert into table rc_table select * from default.tab1;
Remote error
Backend 0:RC_FILE not implemented.

[localhost:21000] > insert into table sequence_table select * from default.tab1;
Remote error
Backend 0:SEQUENCE_FILE not implemented.
```

Inserting data into partitioned tables requires slightly different syntax that divides the partitioning columns from the others:

```
create table t1 (i int) partitioned by (x int, y string);
-- Select an INT column from another table.
-- All inserted rows will have the same x and y values, as specified in the INSERT
statement.
-- This technique of specifying all the partition key values is known as static
partitioning.
insert into t1 partition(x=10, y='a') select c1 from some_other_table;
-- Select two INT columns from another table.
-- All inserted rows will have the same y value, as specified in the INSERT statement.
-- Values from c2 go into t1.x.
-- Any partitioning columns whose value is not specified are filled in
-- from the columns specified last in the SELECT list.
-- This technique of omitting some partition key values is known as dynamic partitioning.
insert into t1 partition(x, y='b') select c1, c2 from some_other_table;
-- Select an INT and a STRING column from another table.
-- All inserted rows will have the same x value, as specified in the INSERT statement.
-- Values from c3 go into t1.y.
insert into t1 partition(x=20, y) select c1, c3 from some_other_table;
```

The following examples show how you can copy the data in all the columns from one table to another, copy the data from only some columns, or specify the columns in the select list in a different order than they actually appear in the table:

```
-- Start with 2 identical tables.
create table t1 (c1 int, c2 int);
create table t2 like t1;

-- If there is no () part after the destination table name,
-- all columns must be specified, either as * or by name.
insert into t2 select * from t1;
insert into t2 select c1, c2 from t1;

-- With the () notation following the destination table name,
-- you can omit columns (all values for that column are NULL
-- in the destination table), and/or reorder the values
-- selected from the source table. This is the "column permutation" feature.
insert into t2 (c1) select c1 from t1;
insert into t2 (c2, c1) select c1, c2 from t1;

-- The column names can be entirely different in the source and destination tables.
-- You can copy any columns, not just the corresponding ones, from the source table.
-- But the number and type of selected columns must match the columns mentioned in the
() part.
alter table t2 replace columns (x int, y int);
insert into t2 (y) select c1 from t1;

-- For partitioned tables, all the partitioning columns must be mentioned in the ()
column list
-- or a PARTITION clause; these columns cannot be defaulted to NULL.
create table pt1 (x int, y int) partitioned by (z int);
-- The values from c1 are copied into the column x in the new table,
-- all in the same partition based on a constant value for z.
-- The values of y in the new table are all NULL.
insert into pt1 (x) partition (z=5) select c1 from t1;
-- Again we omit the values for column y so they are all NULL.
-- The inserted x values can go into different partitions, based on
-- the different values inserted into the partitioning column z.
insert into pt1 (x,z) select x, z from t2;
```

`SELECT *` for a partitioned table requires that all partition key columns in the source table be declared as the last columns in the `CREATE TABLE` statement. You still include a `PARTITION BY` clause listing all the partition key columns. These partition columns are automatically mapped to the last columns from the `SELECT *` list.

```
create table source (x int, y int, year int, month int, day int);
create table destination (x int, y int) partitioned by (year int, month int, day int);
...load some data into the unpartitioned source table...
-- Insert a single partition of data.
```

```
-- The SELECT * means you cannot specify partition (year=2014, month, day).
insert overwrite destination partition (year, month, day) select * from source where
year=2014;
-- Insert the data for all year/month/day combinations.
insert overwrite destination partition (year, month, day) select * from source;

-- If one of the partition columns is omitted from the source table,
-- then you can specify a specific value for that column in the PARTITION clause.
-- Here the source table holds only data from 2014, and so does not include a year
column.
create table source_2014 (x int, y int, month, day);
...load some data into the unpartitioned source_2014 table...
insert overwrite destination partition (year=2014, month, day) select * from source_2014;
```

Sorting considerations: Although you can specify an `ORDER BY` clause in an `INSERT ... SELECT` statement, any `ORDER BY` clause is ignored and the results are not necessarily sorted. An `INSERT ... SELECT` operation potentially creates many different data files, prepared on different data nodes, and therefore the notion of the data being stored in sorted order is impractical.

Concurrency considerations: Each `INSERT` operation creates new data files with unique names, so you can run multiple `INSERT INTO` statements simultaneously without filename conflicts. While data is being inserted into an Impala table, the data is staged temporarily in a subdirectory inside the data directory; during this period, you cannot issue queries against that table in Hive. If an `INSERT` operation fails, the temporary data file and the subdirectory could be left behind in the data directory. If so, remove the relevant subdirectory and any data files it contains manually, by issuing an `hdfs dfs -rm -r` command, specifying the full path of the work subdirectory, whose name ends in `_dir`.

VALUES Clause

The `VALUES` clause is a general-purpose way to specify the columns of one or more rows, typically within an [INSERT](#) statement.



Note: The `INSERT ... VALUES` technique is not suitable for loading large quantities of data into HDFS-based tables, because the insert operations cannot be parallelized, and each one produces a separate data file. Use it for setting up small dimension tables or tiny amounts of data for experimenting with SQL syntax, or with HBase tables. Do not use it for large ETL jobs or benchmark tests for load operations. Do not run scripts with thousands of `INSERT ... VALUES` statements that insert a single row each time. If you do run `INSERT ... VALUES` operations to load data into a staging table as one stage in an ETL pipeline, include multiple row values if possible within each `VALUES` clause, and use a separate database to make cleanup easier if the operation does produce many tiny files.

The following examples illustrate:

- How to insert a single row using a `VALUES` clause.
- How to insert multiple rows using a `VALUES` clause.
- How the row or rows from a `VALUES` clause can be appended to a table through `INSERT INTO`, or replace the contents of the table through `INSERT OVERWRITE`.
- How the entries in a `VALUES` clause can be literals, function results, or any other kind of expression. See [Literals](#) on page 195 for the notation to use for literal values, especially [String Literals](#) on page 196 for quoting and escaping conventions for strings. See [SQL Operators](#) on page 199 and [Impala Built-In Functions](#) on page 373 for other things you can include in expressions with the `VALUES` clause.

```
[localhost:21000] > describe val_example;
Query: describe val_example
Query finished, fetching results ...
+-----+-----+-----+
| name  | type  | comment |
+-----+-----+-----+
| id    | int   |          |
| col_1 | boolean |         |
| col_2 | double |         |
+-----+-----+-----+
```

```
[localhost:21000] > insert into val_example values (1,true,100.0);
Inserted 1 rows in 0.30s
[localhost:21000] > select * from val_example;
+-----+-----+-----+
| id | col_1 | col_2 |
+-----+-----+-----+
| 1  | true  | 100   |
+-----+-----+-----+

[localhost:21000] > insert overwrite val_example values (10,false,pow(2,5)),
(50,true,10/3);
Inserted 2 rows in 0.16s
[localhost:21000] > select * from val_example;
+-----+-----+-----+
| id | col_1 | col_2 |
+-----+-----+-----+
| 10 | false | 32    |
| 50 | true  | 3.333333333333333 |
+-----+-----+-----+
```

When used in an `INSERT` statement, the Impala `VALUES` clause can specify some or all of the columns in the destination table, and the columns can be specified in a different order than they actually appear in the table. To specify a different set or order of columns than in the table, use the syntax:

```
INSERT INTO destination
  (col_x, col_y, col_z)
VALUES
  (val_x, val_y, val_z);
```

Any columns in the table that are not listed in the `INSERT` statement are set to `NULL`.

To use a `VALUES` clause like a table in other statements, wrap it in parentheses and use `AS` clauses to specify aliases for the entire object and any columns you need to refer to:

```
[localhost:21000] > select * from (values(4,5,6),(7,8,9)) as t;
+-----+-----+-----+
| 4 | 5 | 6 |
+-----+-----+-----+
| 4 | 5 | 6 |
| 7 | 8 | 9 |
+-----+-----+-----+

[localhost:21000] > select * from (values(1 as c1, true as c2, 'abc' as
c3),(100,false,'xyz')) as t;
+-----+-----+-----+
| c1 | c2 | c3 |
+-----+-----+-----+
| 1  | true | abc |
| 100 | false | xyz |
+-----+-----+-----+
```

For example, you might use a tiny table constructed like this from constant literals or function return values as part of a longer statement involving joins or `UNION ALL`.

HDFS considerations:

Impala physically writes all inserted files under the ownership of its default user, typically `impala`. Therefore, this user must have HDFS write permission in the corresponding table directory.

The permission requirement is independent of the authorization performed by the Sentry framework. (If the connected user is not authorized to insert into a table, Sentry blocks that operation immediately, regardless of the privileges available to the `impala` user.) Files created by Impala are not owned by and do not inherit permissions from the connected user.

The number of data files produced by an `INSERT` statement depends on the size of the cluster, the number of data blocks that are processed, the partition key columns in a partitioned table, and the mechanism Impala uses for dividing the work in parallel. Do not assume that an `INSERT` statement will produce some particular number of output files. In case of performance issues with data written by Impala, check that the output files do not suffer from issues such

as many tiny files or many tiny partitions. (In the Hadoop context, even files or partitions of a few tens of megabytes are considered “tiny”.)

The `INSERT` statement has always left behind a hidden work directory inside the data directory of the table. Formerly, this hidden work directory was named `.impala_insert_staging`. In Impala 2.0.1 and later, this directory name is changed to `_impala_insert_staging`. (While HDFS tools are expected to treat names beginning either with underscore and dot as hidden, in practice names beginning with an underscore are more widely supported.) If you have any scripts, cleanup jobs, and so on that rely on the name of this work directory, adjust them to use the new name.

HBase considerations:

You can use the `INSERT` statement with HBase tables as follows:

- You can insert a single row or a small set of rows into an HBase table with the `INSERT ... VALUES` syntax. This is a good use case for HBase tables with Impala, because HBase tables are not subject to the same kind of fragmentation from many small insert operations as HDFS tables are.
- You can insert any number of rows at once into an HBase table using the `INSERT ... SELECT` syntax.
- If more than one inserted row has the same value for the HBase key column, only the last inserted row with that value is visible to Impala queries. You can take advantage of this fact with `INSERT ... VALUES` statements to effectively update rows one at a time, by inserting new rows with the same key values as existing rows. Be aware that after an `INSERT ... SELECT` operation copying from an HDFS table, the HBase table might contain fewer rows than were inserted, if the key column in the source table contained duplicate values.
- You cannot `INSERT OVERWRITE` into an HBase table. New rows are always appended.
- When you create an Impala or Hive table that maps to an HBase table, the column order you specify with the `INSERT` statement might be different than the order you declare with the `CREATE TABLE` statement. Behind the scenes, HBase arranges the columns based on how they are divided into column families. This might cause a mismatch during insert operations, especially if you use the syntax `INSERT INTO hbase_table SELECT * FROM hdfs_table`. Before inserting data, verify the column order by issuing a `DESCRIBE` statement for the table, and adjust the order of the select list in the `INSERT` statement.

See [Using Impala to Query HBase Tables](#) on page 608 for more details about using Impala with HBase.

Amazon S3 considerations:

In CDH 5.8 / Impala 2.6 and higher, the Impala DML statements (`INSERT`, `LOAD DATA`, and `CREATE TABLE AS SELECT`) can write data into a table or partition that resides in the Amazon Simple Storage Service (S3). The syntax of the DML statements is the same as for any other tables, because the S3 location for tables and partitions is specified by an `s3a://` prefix in the `LOCATION` attribute of `CREATE TABLE` or `ALTER TABLE` statements. If you bring data into S3 using the normal S3 transfer mechanisms instead of Impala DML statements, issue a `REFRESH` statement for the table before using Impala to query the S3 data.

Because of differences between S3 and traditional filesystems, DML operations for S3 tables can take longer than for tables on HDFS. For example, both the `LOAD DATA` statement and the final stage of the `INSERT` and `CREATE TABLE AS SELECT` statements involve moving files from one directory to another. (In the case of `INSERT` and `CREATE TABLE AS SELECT`, the files are moved from a temporary staging directory to the final destination directory.) Because S3 does not support a “rename” operation for existing objects, in these cases Impala actually copies the data files from one location to another and then removes the original files. In CDH 5.8 / Impala 2.6, the `S3_SKIP_INSERT_STAGING` query option provides a way to speed up `INSERT` statements for S3 tables and partitions, with the tradeoff that a problem during statement execution could leave data in an inconsistent state. It does not apply to `INSERT OVERWRITE` or `LOAD DATA` statements. See [S3_SKIP_INSERT_STAGING Query Option \(CDH 5.8 or higher only\)](#) on page 354 for details.

See [Using Impala with the Amazon S3 Filesystem](#) on page 617 for details about reading and writing S3 data with Impala.

Security considerations:

If these statements in your environment contain sensitive literal values such as credit card numbers or tax identifiers, Impala can redact this sensitive information when displaying the statements in log files and other administrative

contexts. See http://www.cloudera.com/content/cloudera/en/documentation/core/latest/topics/sg_redaction.html for details.

Cancellation: Can be cancelled. To cancel this statement, use Ctrl-C from the `impala-shell` interpreter, the **Cancel** button from the **Watch** page in Hue, **Actions > Cancel** from the **Queries** list in Cloudera Manager, or **Cancel** from the list of in-flight queries (for a particular node) on the **Queries** tab in the Impala web UI (port 25000).

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have read permission for the files in the source directory of an `INSERT ... SELECT` operation, and write permission for all affected directories in the destination table. (An `INSERT` operation could write files to multiple different HDFS directories if the destination table is partitioned.) This user must also have write permission to create a temporary work directory in the top-level HDFS directory of the destination table. An `INSERT OVERWRITE` operation does not require write permission on the original data files in the table, only on the table directories themselves.

Restrictions:

For `INSERT` operations into `CHAR` or `VARCHAR` columns, you must cast all `STRING` literals or expressions returning `STRING` to to a `CHAR` or `VARCHAR` type with the appropriate length.

Related startup options:

By default, if an `INSERT` statement creates any new subdirectories underneath a partitioned table, those subdirectories are assigned default HDFS permissions for the `impala` user. To make each subdirectory have the same permissions as its parent directory in HDFS, specify the `--insert_inherit_permissions` startup option for the `impalad` daemon.

INVALIDATE METADATA Statement

Marks the metadata for one or all tables as stale. Required after a table is created through the Hive shell, before the table is available for Impala queries. The next time the current Impala node performs a query against a table whose metadata is invalidated, Impala reloads the associated metadata before the query proceeds. This is a relatively expensive operation compared to the incremental metadata update done by the `REFRESH` statement, so in the common scenario of adding new data files to an existing table, prefer `REFRESH` rather than `INVALIDATE METADATA`. If you are not familiar with the way Impala uses metadata and how it shares the same metastore database as Hive, see [Overview of Impala Metadata and the Metastore](#) on page 23 for background information.

Syntax:

```
INVALIDATE METADATA [[db_name.]table_name]
```

By default, the cached metadata for all tables is flushed. If you specify a table name, only the metadata for that one table is flushed. Even for a single table, `INVALIDATE METADATA` is more expensive than `REFRESH`, so prefer `REFRESH` in the common case where you add new data files for an existing table.

Internal details:

To accurately respond to queries, Impala must have current metadata about those databases and tables that clients query directly. Therefore, if some other entity modifies information used by Impala in the metastore that Impala and Hive share, the information cached by Impala must be updated. However, this does not mean that all metadata updates require an Impala update.

**Note:**

In Impala 1.2.4 and higher, you can specify a table name with `INVALIDATE METADATA` after the table is created in Hive, allowing you to make individual tables visible to Impala without doing a full reload of the catalog metadata. Impala 1.2.4 also includes other changes to make the metadata broadcast mechanism faster and more responsive, especially during Impala startup. See [New Features in Impala 1.2.4](#) on page 678 for details.

In Impala 1.2 and higher, a dedicated daemon (`catalogd`) broadcasts DDL changes made through Impala to all Impala nodes. Formerly, after you created a database or table while connected to one Impala node, you needed to issue an `INVALIDATE METADATA` statement on another Impala node before accessing the new database or table from the other node. Now, newly created or altered objects are picked up automatically by all Impala nodes. You must still use the `INVALIDATE METADATA` technique after creating or altering objects through Hive. See [The Impala Catalog Service](#) on page 20 for more information on the catalog service.

The `INVALIDATE METADATA` statement is new in Impala 1.1 and higher, and takes over some of the use cases of the Impala 1.0 `REFRESH` statement. Because `REFRESH` now requires a table name parameter, to flush the metadata for all tables at once, use the `INVALIDATE METADATA` statement.

Because `REFRESH table_name` only works for tables that the current Impala node is already aware of, when you create a new table in the Hive shell, enter `INVALIDATE METADATA new_table` before you can see the new table in `impala-shell`. Once the table is known by Impala, you can issue `REFRESH table_name` after you add data files for that table.

`INVALIDATE METADATA` and `REFRESH` are counterparts: `INVALIDATE METADATA` waits to reload the metadata when needed for a subsequent query, but reloads all the metadata for the table, which can be an expensive operation, especially for large tables with many partitions. `REFRESH` reloads the metadata immediately, but only loads the block location data for newly added data files, making it a less expensive operation overall. If data was altered in some more extensive way, such as being reorganized by the HDFS balancer, use `INVALIDATE METADATA` to avoid a performance penalty from reduced local reads. If you used Impala version 1.0, the `INVALIDATE METADATA` statement works just like the Impala 1.0 `REFRESH` statement did, while the Impala 1.1 `REFRESH` is optimized for the common use case of adding new data files to an existing table, thus the table name argument is now required.

Usage notes:

A metadata update for an `impalad` instance **is** required if:

- A metadata change occurs.
- **and** the change is made from another `impalad` instance in your cluster, or through Hive.
- **and** the change is made to a metastore database to which clients such as the Impala shell or ODBC directly connect.

A metadata update for an Impala node is **not** required when you issue queries from the same Impala node where you ran `ALTER TABLE`, `INSERT`, or other table-modifying statement.

Database and table metadata is typically modified by:

- Hive - via `ALTER`, `CREATE`, `DROP` or `INSERT` operations.
- `Impalad` - via `CREATE TABLE`, `ALTER TABLE`, and `INSERT` operations.

`INVALIDATE METADATA` causes the metadata for that table to be marked as stale, and reloaded the next time the table is referenced. For a huge table, that process could take a noticeable amount of time; thus you might prefer to use `REFRESH` where practical, to avoid an unpredictable delay later, for example if the next reference to the table is during a benchmark test.

Examples:

The following example shows how you might use the `INVALIDATE METADATA` statement after creating new tables (such as SequenceFile or HBase tables) through the Hive shell. Before the `INVALIDATE METADATA` statement was issued, Impala would give a “table not found” error if you tried to refer to those table names. The `DESCRIBE` statements

cause the latest metadata to be immediately loaded for the tables, avoiding a delay the next time those tables are queried.

```
[impalad-host:21000] > invalidate metadata;
[impalad-host:21000] > describe t1;
...
[impalad-host:21000] > describe t2;
...
```

For more examples of using `REFRESH` and `INVALIDATE METADATA` with a combination of Impala and Hive operations, see [Switching Back and Forth Between Impala and Hive](#) on page 62.

If you need to ensure that the metadata is up-to-date when you start an `impala-shell` session, run `impala-shell` with the `-r` or `--refresh_after_connect` command-line option. Because this operation adds a delay to the next query against each table, potentially expensive for large tables with many partitions, try to avoid using this option for day-to-day operations in a production environment.

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have execute permissions for all the relevant directories holding table data. (A table could have data spread across multiple directories, or in unexpected paths, if it uses partitioning or specifies a `LOCATION` attribute for individual partitions or the entire table.) Issues with permissions might not cause an immediate error for this statement, but subsequent statements such as `SELECT` or `SHOW TABLE STATS` could fail.

HDFS considerations:

By default, the `INVALIDATE METADATA` command checks HDFS permissions of the underlying data files and directories, caching this information so that a statement can be cancelled immediately if for example the `impala` user does not have permission to write to the data directory for the table. (This checking does not apply if you have set the `catalogd` configuration option `--load_catalog_in_background=false`.) Impala reports any lack of write permissions as an `INFO` message in the log file, in case that represents an oversight. If you change HDFS permissions to make data readable or writable by the Impala user, issue another `INVALIDATE METADATA` to make Impala aware of the change.

Usage notes:

This example illustrates creating a new database and new table in Hive, then doing an `INVALIDATE METADATA` statement in Impala using the fully qualified table name, after which both the new table and the new database are visible to Impala. The ability to specify `INVALIDATE METADATA table_name` for a table created in Hive is a new capability in Impala 1.2.4. In earlier releases, that statement would have returned an error indicating an unknown table, requiring you to do `INVALIDATE METADATA` with no table name, a more expensive operation that reloaded metadata for all tables and databases.

```
$ hive
hive> create database new_db_from_hive;
OK
Time taken: 4.118 seconds
hive> create table new_db_from_hive.new_table_from_hive (x int);
OK
Time taken: 0.618 seconds
hive> quit;
$ impala-shell
[localhost:21000] > show databases like 'new*';
[localhost:21000] > refresh new_db_from_hive.new_table_from_hive;
ERROR: AnalysisException: Database does not exist: new_db_from_hive
[localhost:21000] > invalidate metadata new_db_from_hive.new_table_from_hive;
[localhost:21000] > show databases like 'new*';
+-----+
| name          |
+-----+
| new_db_from_hive |
+-----+
[localhost:21000] > show tables in new_db_from_hive;
+-----+
| name          |
+-----+
```



```
| new_table_from_hive |
+-----+
```

Amazon S3 considerations:

The `REFRESH` and `INVALIDATE METADATA` statements also cache metadata for tables where the data resides in the Amazon Simple Storage Service (S3). In particular, issue a `REFRESH` for a table after adding or removing files in the associated S3 data directory. See [Using Impala with the Amazon S3 Filesystem](#) on page 617 for details about working with S3 tables.

Cancellation: Cannot be cancelled.

Related information:

[Overview of Impala Metadata and the Metastore](#) on page 23, [REFRESH Statement](#) on page 300

LOAD DATA Statement

The `LOAD DATA` statement streamlines the ETL process for an internal Impala table by moving a data file or all the data files in a directory from an HDFS location into the Impala data directory for that table.

Syntax:

```
LOAD DATA INPATH 'hdfs_file_or_directory_path' [OVERWRITE] INTO TABLE tablename
  [PARTITION (partcol1=val1, partcol2=val2 ...)]
```

When the `LOAD DATA` statement operates on a partitioned table, it always operates on one partition at a time. Specify the `PARTITION` clauses and list all the partition key columns, with a constant value specified for each.

Statement type: DML (but still affected by [SYNC_DDL](#) query option)

Usage notes:

- The loaded data files are moved, not copied, into the Impala data directory.
- You can specify the HDFS path of a single file to be moved, or the HDFS path of a directory to move all the files inside that directory. You cannot specify any sort of wildcard to take only some of the files from a directory. When loading a directory full of data files, keep all the data files at the top level, with no nested directories underneath.
- Currently, the Impala `LOAD DATA` statement only imports files from HDFS, not from the local filesystem. It does not support the `LOCAL` keyword of the Hive `LOAD DATA` statement. You must specify a path, not an `hdfs://` URI.
- In the interest of speed, only limited error checking is done. If the loaded files have the wrong file format, different columns than the destination table, or other kind of mismatch, Impala does not raise any error for the `LOAD DATA` statement. Querying the table afterward could produce a runtime error or unexpected results. Currently, the only checking the `LOAD DATA` statement does is to avoid mixing together uncompressed and LZO-compressed text files in the same table.
- When you specify an HDFS directory name as the `LOAD DATA` argument, any hidden files in that directory (files whose names start with a `.`) are not moved to the Impala data directory.
- The operation fails if the source directory contains any non-hidden directories. Prior to CDH 5.7 / Impala 2.5, if the source directory contained any subdirectory, even a hidden one such as `_impala_insert_staging`, the `LOAD DATA` statement would fail. In CDH 5.7 / Impala 2.5 and higher, `LOAD DATA` ignores hidden subdirectories in the source directory, and only fails if any of the subdirectories are non-hidden.
- The loaded data files retain their original names in the new location, unless a name conflicts with an existing data file, in which case the name of the new file is modified slightly to be unique. (The name-mangling is a slight difference from the Hive `LOAD DATA` statement, which replaces identically named files.)
- By providing an easy way to transport files from known locations in HDFS into the Impala data directory structure, the `LOAD DATA` statement lets you avoid memorizing the locations and layout of HDFS directory tree containing the Impala databases and tables. (For a quick way to check the location of the data files for an Impala table, issue the statement `DESCRIBE FORMATTED table_name`.)
- The `PARTITION` clause is especially convenient for ingesting new data for a partitioned table. As you receive new data for a time period, geographic region, or other division that corresponds to one or more partitioning columns,

you can load that data straight into the appropriate Impala data directory, which might be nested several levels down if the table is partitioned by multiple columns. When the table is partitioned, you must specify constant values for all the partitioning columns.

Complex type considerations:

Because Impala currently cannot create Parquet data files containing complex types (ARRAY, STRUCT, and MAP), the LOAD DATA statement is especially important when working with tables containing complex type columns. You create the Parquet data files outside Impala, then use either LOAD DATA, an external table, or HDFS-level file operations followed by REFRESH to associate the data files with the corresponding table. See [Complex Types \(CDH 5.5 or higher only\)](#) on page 167 for details about using complex types.

If you connect to different Impala nodes within an `impala-shell` session for load-balancing purposes, you can enable the SYNC_DDL query option to make each DDL statement wait before returning, until the new or changed metadata has been received by all the Impala nodes. See [SYNC_DDL Query Option](#) on page 356 for details.



Important: After adding or replacing data in a table used in performance-critical queries, issue a COMPUTE STATS statement to make sure all statistics are up-to-date. Consider updating statistics for a table after any INSERT, LOAD DATA, or CREATE TABLE AS SELECT statement in Impala, or after loading data through Hive and doing a REFRESH *table_name* in Impala. This technique is especially important for tables that are very large, used in join queries, or both.

Examples:

First, we use a trivial Python script to write different numbers of strings (one per line) into files stored in the `cloudera` HDFS user account. (Substitute the path for your own HDFS user account when doing `hdfs dfs` operations like these.)

```
$ random_strings.py 1000 | hdfs dfs -put - /user/cloudera/thousand_strings.txt
$ random_strings.py 100 | hdfs dfs -put - /user/cloudera/hundred_strings.txt
$ random_strings.py 10 | hdfs dfs -put - /user/cloudera/ten_strings.txt
```

Next, we create a table and load an initial set of data into it. Remember, unless you specify a STORED AS clause, Impala tables default to TEXTFILE format with Ctrl-A (hex 01) as the field delimiter. This example uses a single-column table, so the delimiter is not significant. For large-scale ETL jobs, you would typically use binary format data files such as Parquet or Avro, and load them into Impala tables that use the corresponding file format.

```
[localhost:21000] > create table t1 (s string);
[localhost:21000] > load data inpath '/user/cloudera/thousand_strings.txt' into table
t1;
Query finished, fetching results ...
+-----+
| summary |
+-----+
| Loaded 1 file(s). Total files in destination location: 1 |
+-----+
Returned 1 row(s) in 0.61s
[kilo2-202-961.cs1cloud.internal:21000] > select count(*) from t1;
Query finished, fetching results ...
+-----+
| _c0 |
+-----+
| 1000 |
+-----+
Returned 1 row(s) in 0.67s
[localhost:21000] > load data inpath '/user/cloudera/thousand_strings.txt' into table
t1;
ERROR: AnalysisException: INPATH location '/user/cloudera/thousand_strings.txt' does
not exist.
```

As indicated by the message at the end of the previous example, the data file was moved from its original location. The following example illustrates how the data file was moved into the Impala data directory for the destination table, keeping its original filename:

```
$ hdfs dfs -ls /user/hive/warehouse/load_data_testing.db/t1
Found 1 items
-rw-r--r-- 1 cloudera cloudera      13926 2013-06-26 15:40
/user/hive/warehouse/load_data_testing.db/t1/thousand_strings.txt
```

The following example demonstrates the difference between the `INTO TABLE` and `OVERWRITE TABLE` clauses. The table already contains 1000 rows. After issuing the `LOAD DATA` statement with the `INTO TABLE` clause, the table contains 100 more rows, for a total of 1100. After issuing the `LOAD DATA` statement with the `OVERWRITE INTO TABLE` clause, the former contents are gone, and now the table only contains the 10 rows from the just-loaded data file.

```
[localhost:21000] > load data inpath '/user/cloudera/hundred_strings.txt' into table
t1;
Query finished, fetching results ...
+-----+
| summary |
+-----+
| Loaded 1 file(s). Total files in destination location: 2 |
+-----+
Returned 1 row(s) in 0.24s
[localhost:21000] > select count(*) from t1;
Query finished, fetching results ...
+-----+
| _c0 |
+-----+
| 1100 |
+-----+
Returned 1 row(s) in 0.55s
[localhost:21000] > load data inpath '/user/cloudera/ten_strings.txt' overwrite into
table t1;
Query finished, fetching results ...
+-----+
| summary |
+-----+
| Loaded 1 file(s). Total files in destination location: 1 |
+-----+
Returned 1 row(s) in 0.26s
[localhost:21000] > select count(*) from t1;
Query finished, fetching results ...
+-----+
| _c0 |
+-----+
| 10 |
+-----+
Returned 1 row(s) in 0.62s
```

Amazon S3 considerations:

In CDH 5.8 / Impala 2.6 and higher, the Impala DML statements (`INSERT`, `LOAD DATA`, and `CREATE TABLE AS SELECT`) can write data into a table or partition that resides in the Amazon Simple Storage Service (S3). The syntax of the DML statements is the same as for any other tables, because the S3 location for tables and partitions is specified by an `s3a://` prefix in the `LOCATION` attribute of `CREATE TABLE` or `ALTER TABLE` statements. If you bring data into S3 using the normal S3 transfer mechanisms instead of Impala DML statements, issue a `REFRESH` statement for the table before using Impala to query the S3 data.

Because of differences between S3 and traditional filesystems, DML operations for S3 tables can take longer than for tables on HDFS. For example, both the `LOAD DATA` statement and the final stage of the `INSERT` and `CREATE TABLE AS SELECT` statements involve moving files from one directory to another. (In the case of `INSERT` and `CREATE TABLE AS SELECT`, the files are moved from a temporary staging directory to the final destination directory.) Because S3 does not support a “rename” operation for existing objects, in these cases Impala actually copies the data files from one location to another and then removes the original files. In CDH 5.8 / Impala 2.6, the `S3_SKIP_INSERT_STAGING` query option provides a way to speed up `INSERT` statements for S3 tables and partitions, with the tradeoff that a

problem during statement execution could leave data in an inconsistent state. It does not apply to `INSERT OVERWRITE` or `LOAD DATA` statements. See [S3_SKIP_INSERT_STAGING Query Option \(CDH 5.8 or higher only\)](#) on page 354 for details.

See [Using Impala with the Amazon S3 Filesystem](#) on page 617 for details about reading and writing S3 data with Impala.

Cancellation: Cannot be cancelled.

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have read and write permissions for the files in the source directory, and write permission for the destination directory.

HBase considerations:

The `LOAD DATA` statement cannot be used with HBase tables.

Related information:

The `LOAD DATA` statement is an alternative to the `INSERT` statement. Use `LOAD DATA` when you have the data files in HDFS but outside of any Impala table.

The `LOAD DATA` statement is also an alternative to the `CREATE EXTERNAL TABLE` statement. Use `LOAD DATA` when it is appropriate to move the data files under Impala control rather than querying them from their original location. See [External Tables](#) on page 223 for information about working with external tables.

REFRESH Statement

To accurately respond to queries, the Impala node that acts as the coordinator (the node to which you are connected through `impala-shell`, JDBC, or ODBC) must have current metadata about those databases and tables that are referenced in Impala queries. If you are not familiar with the way Impala uses metadata and how it shares the same metastore database as Hive, see [Overview of Impala Metadata and the Metastore](#) on page 23 for background information.

Syntax:

```
REFRESH [db_name.]table_name [PARTITION (key_col1=val1 [, key_col2=val2...])]
```

Usage notes:

Use the `REFRESH` statement to load the latest metastore metadata and block location data for a particular table in these scenarios:

- After loading new data files into the HDFS data directory for the table. (Once you have set up an ETL pipeline to bring data into Impala on a regular basis, this is typically the most frequent reason why metadata needs to be refreshed.)
- After issuing `ALTER TABLE`, `INSERT`, `LOAD DATA`, or other table-modifying SQL statement in Hive.



Note:

In CDH 5.5 / Impala 2.3 and higher, the syntax `ALTER TABLE table_name RECOVER PARTITIONS` is a faster alternative to `REFRESH` when the only change to the table data is the addition of new partition directories through Hive or manual HDFS operations. See [ALTER TABLE Statement](#) on page 230 for details.

You only need to issue the `REFRESH` statement on the node to which you connect to issue queries. The coordinator node divides the work among all the Impala nodes in a cluster, and sends read requests for the correct HDFS blocks without relying on the metadata on the other nodes.

`REFRESH` reloads the metadata for the table from the metastore database, and does an incremental reload of the low-level block location data to account for any new data files added to the HDFS data directory for the table. It is a low-overhead, single-table operation, specifically tuned for the common scenario where new data files are added to HDFS.

Only the metadata for the specified table is flushed. The table must already exist and be known to Impala, either because the `CREATE TABLE` statement was run in Impala rather than Hive, or because a previous `INVALIDATE METADATA` statement caused Impala to reload its entire metadata catalog.



Note:

The catalog service broadcasts any changed metadata as a result of Impala `ALTER TABLE`, `INSERT` and `LOAD DATA` statements to all Impala nodes. Thus, the `REFRESH` statement is only required if you load data through Hive or by manipulating data files in HDFS directly. See [The Impala Catalog Service](#) on page 20 for more information on the catalog service.

Another way to avoid inconsistency across nodes is to enable the `SYNC_DDL` query option before performing a DDL statement or an `INSERT` or `LOAD DATA`.

The table name is a required parameter. To flush the metadata for all tables, use the [INVALIDATE METADATA](#) command.

Because `REFRESH table_name` only works for tables that the current Impala node is already aware of, when you create a new table in the Hive shell, enter `INVALIDATE METADATA new_table` before you can see the new table in `impala-shell`. Once the table is known by Impala, you can issue `REFRESH table_name` after you add data files for that table.

`INVALIDATE METADATA` and `REFRESH` are counterparts: `INVALIDATE METADATA` waits to reload the metadata when needed for a subsequent query, but reloads all the metadata for the table, which can be an expensive operation, especially for large tables with many partitions. `REFRESH` reloads the metadata immediately, but only loads the block location data for newly added data files, making it a less expensive operation overall. If data was altered in some more extensive way, such as being reorganized by the HDFS balancer, use `INVALIDATE METADATA` to avoid a performance penalty from reduced local reads. If you used Impala version 1.0, the `INVALIDATE METADATA` statement works just like the Impala 1.0 `REFRESH` statement did, while the Impala 1.1 `REFRESH` is optimized for the common use case of adding new data files to an existing table, thus the table name argument is now required.

A metadata update for an `impalad` instance **is** required if:

- A metadata change occurs.
- **and** the change is made through Hive.
- **and** the change is made to a metastore database to which clients such as the Impala shell or ODBC directly connect.

A metadata update for an Impala node is **not** required after you run `ALTER TABLE`, `INSERT`, or other table-modifying statement in Impala rather than Hive. Impala handles the metadata synchronization automatically through the catalog service.

Database and table metadata is typically modified by:

- Hive - through `ALTER`, `CREATE`, `DROP` or `INSERT` operations.
- Impalad - through `CREATE TABLE`, `ALTER TABLE`, and `INSERT` operations. Such changes are propagated to all Impala nodes by the Impala catalog service.

`REFRESH` causes the metadata for that table to be immediately reloaded. For a huge table, that process could take a noticeable amount of time; but doing the refresh up front avoids an unpredictable delay later, for example if the next reference to the table is during a benchmark test.

Refreshing a single partition:

In CDH 5.9 / Impala 2.7 and higher, the `REFRESH` statement can apply to a single partition at a time, rather than the whole table. Include the optional `PARTITION (partition_spec)` clause and specify values for each of the partition key columns.

The following examples show how to make Impala aware of data added to a single partition, after data is loaded into a partition's data directory using some mechanism outside Impala, such as Hive or Spark. The partition can be one that Impala created and is already aware of, or a new partition created through Hive.

```

impala> create table p (x int) partitioned by (y int);
impala> insert into p (x,y) values (1,2), (2,2), (2,1);
impala> show partitions p;
+-----+-----+-----+-----+...
| y      | #Rows | #Files | Size  | ...
+-----+-----+-----+-----+...
| 1      | -1    | 1      | 2B    | ...
| 2      | -1    | 1      | 4B    | ...
| Total  | -1    | 2      | 6B    | ...
+-----+-----+-----+-----+...

-- ... Data is inserted into one of the partitions by some external mechanism ...
beeline> insert into p partition (y = 1) values(1000);

impala> refresh p partition (y=1);
impala> select x from p where y=1;
+-----+
| x      |
+-----+
| 2      | <- Original data created by Impala
| 1000   | <- Additional data inserted through Beeline
+-----+

```

The same applies for tables with more than one partition key column. The PARTITION clause of the REFRESH statement must include all the partition key columns.

```

impala> create table p2 (x int) partitioned by (y int, z int);
impala> insert into p2 (x,y,z) values (0,0,0), (1,2,3), (2,2,3);
impala> show partitions p2;
+-----+-----+-----+-----+-----+...
| y      | z      | #Rows | #Files | Size  | ...
+-----+-----+-----+-----+-----+...
| 0      | 0      | -1    | 1      | 2B    | ...
| 2      | 3      | -1    | 1      | 4B    | ...
| Total  | -1     | -1    | 2      | 6B    | ...
+-----+-----+-----+-----+-----+...

-- ... Data is inserted into one of the partitions by some external mechanism ...
beeline> insert into p2 partition (y = 2, z = 3) values(1000);

impala> refresh p2 partition (y=2, z=3);
impala> select x from p where y=2 and z = 3;
+-----+
| x      |
+-----+
| 1      | <- Original data created by Impala
| 2      | <- Original data created by Impala
| 1000   | <- Additional data inserted through Beeline
+-----+

```

The following examples show how specifying a nonexistent partition does not cause any error, and the order of the partition key columns does not have to match the column order in the table. The partition spec must include all the partition key columns; specifying an incomplete set of columns does cause an error.

```

-- Partition doesn't exist.
refresh p2 partition (y=0, z=3);
refresh p2 partition (y=0, z=-1)
-- Key columns specified in a different order than the table definition.
refresh p2 partition (z=1, y=0)
-- Incomplete partition spec causes an error.
refresh p2 partition (y=0)

```

```
ERROR: AnalysisException: Items in partition spec must exactly match the partition
columns in the table definition: default.p2 (1 vs 2)
```

If you connect to different Impala nodes within an `impala-shell` session for load-balancing purposes, you can enable the `SYNC_DDL` query option to make each DDL statement wait before returning, until the new or changed metadata has been received by all the Impala nodes. See [SYNC_DDL Query Option](#) on page 356 for details.

Examples:

The following example shows how you might use the `REFRESH` statement after manually adding new HDFS data files to the Impala data directory for a table:

```
[impalad-host:21000] > refresh t1;
[impalad-host:21000] > refresh t2;
[impalad-host:21000] > select * from t1;
...
[impalad-host:21000] > select * from t2;
...
```

For more examples of using `REFRESH` and `INVALIDATE METADATA` with a combination of Impala and Hive operations, see [Switching Back and Forth Between Impala and Hive](#) on page 62.

Related impala-shell options:

The `impala-shell` option `-r` issues an `INVALIDATE METADATA` statement when starting up the shell, effectively performing a `REFRESH` of all tables. Due to the expense of reloading the metadata for all tables, the `impala-shell -r` option is not recommended for day-to-day use in a production environment. (This option was mainly intended as a workaround for synchronization issues in very old Impala versions.)

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have execute permissions for all the relevant directories holding table data. (A table could have data spread across multiple directories, or in unexpected paths, if it uses partitioning or specifies a `LOCATION` attribute for individual partitions or the entire table.) Issues with permissions might not cause an immediate error for this statement, but subsequent statements such as `SELECT` or `SHOW TABLE STATS` could fail.

All HDFS and Sentry permissions and privileges are the same whether you refresh the entire table or a single partition.

HDFS considerations:

The `REFRESH` command checks HDFS permissions of the underlying data files and directories, caching this information so that a statement can be cancelled immediately if for example the `impala` user does not have permission to write to the data directory for the table. Impala reports any lack of write permissions as an `INFO` message in the log file, in case that represents an oversight. If you change HDFS permissions to make data readable or writable by the Impala user, issue another `REFRESH` to make Impala aware of the change.



Important: After adding or replacing data in a table used in performance-critical queries, issue a `COMPUTE STATS` statement to make sure all statistics are up-to-date. Consider updating statistics for a table after any `INSERT`, `LOAD DATA`, or `CREATE TABLE AS SELECT` statement in Impala, or after loading data through Hive and doing a `REFRESH table_name` in Impala. This technique is especially important for tables that are very large, used in join queries, or both.

Amazon S3 considerations:

The `REFRESH` and `INVALIDATE METADATA` statements also cache metadata for tables where the data resides in the Amazon Simple Storage Service (S3). In particular, issue a `REFRESH` for a table after adding or removing files in the associated S3 data directory. See [Using Impala with the Amazon S3 Filesystem](#) on page 617 for details about working with S3 tables.

Cancellation: Cannot be cancelled.

Related information:

[Overview of Impala Metadata and the Metastore](#) on page 23, [INVALIDATE METADATA Statement](#) on page 294

REVOKE Statement (CDH 5.2 or higher only)

The `REVOKE` statement revokes roles or privileges on a specified object from groups. Only Sentry administrative users can revoke the role from a group. The revocation has a cascading effect. For example, revoking the `ALL` privilege on a database also revokes the same privilege for all the tables in that database.

Syntax:

```
REVOKE ROLE role_name FROM GROUP group_name

REVOKE privilege ON object_type object_name
FROM [ROLE] role_name

privilege ::= SELECT | SELECT(column_name) | INSERT | ALL
object_type ::= TABLE | DATABASE | SERVER | URI
```

Typically, the object name is an identifier. For URIs, it is a string literal.

The ability to grant or revoke `SELECT` privilege on specific columns is available in CDH 5.5 / Impala 2.3 and higher. See https://www.cloudera.com/documentation/enterprise/latest/topics/sg_hive_sql.html for details.

Required privileges:

Only administrative users (those with `ALL` privileges on the server, defined in the Sentry policy file) can use this statement.

Compatibility:

- The Impala `GRANT` and `REVOKE` statements are available in CDH 5.2 and higher.
- In CDH 5.1 and higher, Impala makes use of any roles and privileges specified by the `GRANT` and `REVOKE` statements in Hive, when your system is configured to use the Sentry service instead of the file-based policy mechanism.
- The Impala `GRANT` and `REVOKE` statements do not require the `ROLE` keyword to be repeated before each role name, unlike the equivalent Hive statements.
- Currently, each Impala `GRANT` or `REVOKE` statement can only grant or revoke a single privilege to or from a single role.

Cancellation: Cannot be cancelled.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Related information:

[Enabling Sentry Authorization for Impala](#) on page 105, [GRANT Statement \(CDH 5.2 or higher only\)](#) on page 285 [CREATE ROLE Statement \(CDH 5.2 or higher only\)](#) on page 253, [DROP ROLE Statement \(CDH 5.2 or higher only\)](#) on page 277, [SHOW Statement](#) on page 356

SELECT Statement

The `SELECT` statement performs queries, retrieving data from one or more tables and producing result sets consisting of rows and columns.

The Impala [INSERT](#) statement also typically ends with a `SELECT` statement, to define data to copy from one table to another.

Syntax:

```
[WITH name AS (select_expression) [, ...] ]
SELECT
  [ALL | DISTINCT]
  [STRAIGHT_JOIN]
```



```

    expression [, expression ...]
FROM table_reference [, table_reference ...]
[[FULL | [LEFT | RIGHT] INNER | [LEFT | RIGHT] OUTER | [LEFT | RIGHT] SEMI | [LEFT |
RIGHT] ANTI | CROSS]
JOIN table_reference
  [ON join_equality_clauses | USING (col1[, col2 ...]] ...
WHERE conditions
GROUP BY { column | expression [, ...] }
HAVING conditions
ORDER BY { column | expression [ASC | DESC] [NULLS FIRST | NULLS LAST] [, ...] }
LIMIT expression [OFFSET expression]
[UNION [ALL] select_statement] ...]

```

Impala SELECT queries support:

- SQL scalar data types: [BOOLEAN](#), [TINYINT](#), [SMALLINT](#), [INT](#), [BIGINT](#), [DECIMAL](#), [FLOAT](#), [DOUBLE](#), [TIMESTAMP](#), [STRING](#), [VARCHAR](#), [CHAR](#).
- The complex data types `ARRAY`, `STRUCT`, and `MAP`, are available in CDH 5.5 / Impala 2.3 and higher. Queries involving these types typically involve special qualified names using dot notation for referring to the complex column fields, and join clauses for bringing the complex columns into the result set. See [Complex Types \(CDH 5.5 or higher only\)](#) on page 167 for details.
- An optional [WITH clause](#) before the `SELECT` keyword, to define a subquery whose name or column names can be referenced from later in the main query. This clause lets you abstract repeated clauses, such as aggregation functions, that are referenced multiple times in the same query.
- By default, one `DISTINCT` clause per query. See [DISTINCT Operator](#) on page 325 for details. See [APPX_COUNT_DISTINCT Query Option \(CDH 5.2 or higher only\)](#) on page 332 for a query option to allow multiple `COUNT(DISTINCT)` impressions in the same query.
- Subqueries in a `FROM` clause. In CDH 5.2 / Impala 2.0 and higher, subqueries can also go in the `WHERE` clause, for example with the `IN()`, `EXISTS`, and `NOT EXISTS` operators.
- `WHERE`, `GROUP BY`, `HAVING` clauses.
- [ORDER BY](#). Prior to Impala 1.4.0, Impala required that queries using an `ORDER BY` clause also include a [LIMIT](#) clause. In Impala 1.4.0 and higher, this restriction is lifted; sort operations that would exceed the Impala memory limit automatically use a temporary disk work area to perform the sort.
- Impala supports a wide variety of `JOIN` clauses. Left, right, semi, full, and outer joins are supported in all Impala versions. The `CROSS JOIN` operator is available in Impala 1.2.2 and higher. During performance tuning, you can override the reordering of join clauses that Impala does internally by including the keyword `STRAIGHT_JOIN` immediately after the `SELECT` and any `DISTINCT` or `ALL` keywords.

See [Joins in Impala SELECT Statements](#) on page 306 for details and examples of join queries.

- `UNION ALL`.
- `LIMIT`.
- External tables.
- Relational operators such as greater than, less than, or equal to.
- Arithmetic operators such as addition or subtraction.
- Logical/Boolean operators `AND`, `OR`, and `NOT`. Impala does not support the corresponding symbols `&&`, `||`, and `!`.
- Common SQL built-in functions such as `COUNT`, `SUM`, `CAST`, `LIKE`, `IN`, `BETWEEN`, and `COALESCE`. Impala specifically supports built-ins described in [Impala Built-In Functions](#) on page 373.

Impala queries ignore files with extensions commonly used for temporary work files by Hadoop tools. Any files with extensions `.tmp` or `.copying` are not considered part of the Impala table. The suffix matching is case-insensitive, so for example Impala ignores both `.copying` and `.COPYING` suffixes.

Security considerations:

If these statements in your environment contain sensitive literal values such as credit card numbers or tax identifiers, Impala can redact this sensitive information when displaying the statements in log files and other administrative contexts. See http://www.cloudera.com/content/cloudera/en/documentation/core/latest/topics/sg_redaction.html for details.

Amazon S3 considerations:

In CDH 5.8 / Impala 2.6 and higher, Impala queries are optimized for files stored in Amazon S3. For Impala tables that use the file formats Parquet, RCFile, SequenceFile, Avro, and uncompressed text, the setting `fs.s3a.block.size` in the `core-site.xml` configuration file determines how Impala divides the I/O work of reading the data files. This configuration setting is specified in bytes. By default, this value is 33554432 (32 MB), meaning that Impala parallelizes S3 read operations on the files as if they were made up of 32 MB blocks. For example, if your S3 queries primarily access Parquet files written by MapReduce or Hive, increase `fs.s3a.block.size` to 134217728 (128 MB) to match the row group size of those files. If most S3 queries involve Parquet files written by Impala, increase `fs.s3a.block.size` to 268435456 (256 MB) to match the row group size produced by Impala.

Cancellation: Can be cancelled. To cancel this statement, use Ctrl-C from the `impala-shell` interpreter, the **Cancel** button from the **Watch** page in Hue, **Actions > Cancel** from the **Queries** list in Cloudera Manager, or **Cancel** from the list of in-flight queries (for a particular node) on the **Queries** tab in the Impala web UI (port 25000).

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have read permissions for the files in all applicable directories in all source tables, and read and execute permissions for the relevant data directories. (A `SELECT` operation could read files from multiple different HDFS directories if the source table is partitioned.) If a query attempts to read a data file and is unable to because of an HDFS permission error, the query halts and does not return any further results.

Related information:

The `SELECT` syntax is so extensive that it forms its own category of statements: queries. The other major classifications of SQL statements are data definition language (see [DDL Statements](#) on page 228) and data manipulation language (see [DML Statements](#) on page 229).

Because the focus of Impala is on fast queries with interactive response times over huge data sets, query performance and scalability are important considerations. See [Tuning Impala for Performance](#) on page 523 and [Scalability Considerations for Impala](#) on page 561 for details.

Joins in Impala SELECT Statements

A join query is a `SELECT` statement that combines data from two or more tables, and returns a result set containing items from some or all of those tables. It is a way to cross-reference and correlate related data that is organized into multiple tables, typically using identifiers that are repeated in each of the joined tables.

Syntax:

Impala supports a wide variety of `JOIN` clauses. Left, right, semi, full, and outer joins are supported in all Impala versions. The `CROSS JOIN` operator is available in Impala 1.2.2 and higher. During performance tuning, you can override the reordering of join clauses that Impala does internally by including the keyword `STRAIGHT_JOIN` immediately after the `SELECT` and any `DISTINCT` or `ALL` keywords.

```
SELECT select_list FROM
  table_or_subquery1 [INNER] JOIN table_or_subquery2 |
  table_or_subquery1 {LEFT [OUTER] | RIGHT [OUTER] | FULL [OUTER]} JOIN table_or_subquery2
|
  table_or_subquery1 {LEFT | RIGHT} SEMI JOIN table_or_subquery2 |
  table_or_subquery1 {LEFT | RIGHT} ANTI JOIN table_or_subquery2 |
  [ ON col1 = col2 [AND col3 = col4 ...] |
  USING (col1 [, col2 ...]) ]
  [other_join_clause ...]
[ WHERE where_clauses ]

SELECT select_list FROM
  table_or_subquery1, table_or_subquery2 [, table_or_subquery3 ...]
[other_join_clause ...]
WHERE
  col1 = col2 [AND col3 = col4 ...]

SELECT select_list FROM
  table_or_subquery1 CROSS JOIN table_or_subquery2
```

```
[ other_join_clause ... ]
[ WHERE where_clauses ]
```

SQL-92 and SQL-89 Joins:

Queries with the explicit JOIN keywords are known as SQL-92 style joins, referring to the level of the SQL standard where they were introduced. The corresponding ON or USING clauses clearly show which columns are used as the join keys in each case:

```
SELECT t1.c1, t2.c2 FROM t1 JOIN t2
  ON t1.id = t2.id and t1.type_flag = t2.type_flag
 WHERE t1.c1 > 100;

SELECT t1.c1, t2.c2 FROM t1 JOIN t2
  USING (id, type_flag)
 WHERE t1.c1 > 100;
```

The ON clause is a general way to compare columns across the two tables, even if the column names are different. The USING clause is a shorthand notation for specifying the join columns, when the column names are the same in both tables. You can code equivalent WHERE clauses that compare the columns, instead of ON or USING clauses, but that practice is not recommended because mixing the join comparisons with other filtering clauses is typically less readable and harder to maintain.

Queries with a comma-separated list of tables and subqueries are known as SQL-89 style joins. In these queries, the equality comparisons between columns of the joined tables go in the WHERE clause alongside other kinds of comparisons. This syntax is easy to learn, but it is also easy to accidentally remove a WHERE clause needed for the join to work correctly.

```
SELECT t1.c1, t2.c2 FROM t1, t2
  WHERE
    t1.id = t2.id AND t1.type_flag = t2.type_flag
  AND t1.c1 > 100;
```

Self-joins:

Impala can do self-joins, for example to join on two different columns in the same table to represent parent-child relationships or other tree-structured data. There is no explicit syntax for this; just use the same table name for both the left-hand and right-hand table, and assign different table aliases to use when referring to the fully qualified column names:

```
-- Combine fields from both parent and child rows.
SELECT lhs.id, rhs.parent, lhs.c1, rhs.c2 FROM tree_data lhs, tree_data rhs WHERE lhs.id
 = rhs.parent;
```

Inner and outer joins:

An inner join is the most common and familiar type: rows in the result set contain the requested columns from the appropriate tables, for all combinations of rows where the join columns of the tables have identical values. If a column with the same name occurs in both tables, use a fully qualified name or a column alias to refer to the column in the select list or other clauses. Impala performs inner joins by default for both SQL-89 and SQL-92 join syntax:

```
-- The following 3 forms are all equivalent.
SELECT t1.id, c1, c2 FROM t1, t2 WHERE t1.id = t2.id;
SELECT t1.id, c1, c2 FROM t1 JOIN t2 ON t1.id = t2.id;
SELECT t1.id, c1, c2 FROM t1 INNER JOIN t2 ON t1.id = t2.id;
```

An outer join retrieves all rows from the left-hand table, or the right-hand table, or both; wherever there is no matching data in the table on the other side of the join, the corresponding columns in the result set are set to `NULL`. To perform an outer join, include the `OUTER` keyword in the join operator, along with either `LEFT`, `RIGHT`, or `FULL`:

```
SELECT * FROM t1 LEFT OUTER JOIN t2 ON t1.id = t2.id;
SELECT * FROM t1 RIGHT OUTER JOIN t2 ON t1.id = t2.id;
SELECT * FROM t1 FULL OUTER JOIN t2 ON t1.id = t2.id;
```

For outer joins, Impala requires SQL-92 syntax; that is, the `JOIN` keyword instead of comma-separated table names. Impala does not support vendor extensions such as `(+)` or `*=` notation for doing outer joins with SQL-89 query syntax.

Equijoins and Non-Equijoins:

By default, Impala requires an equality comparison between the left-hand and right-hand tables, either through `ON`, `USING`, or `WHERE` clauses. These types of queries are classified broadly as equijoins. Inner, outer, full, and semi joins can all be equijoins based on the presence of equality tests between columns in the left-hand and right-hand tables.

In Impala 1.2.2 and higher, non-equijoin queries are also possible, with comparisons such as `!=` or `<` between the join columns. These kinds of queries require care to avoid producing huge result sets that could exceed resource limits. Once you have planned a non-equijoin query that produces a result set of acceptable size, you can code the query using the `CROSS JOIN` operator, and add the extra comparisons in the `WHERE` clause:

```
SELECT * FROM t1 CROSS JOIN t2 WHERE t1.total > t2.maximum_price;
```

In CDH 5.5 / Impala 2.3 and higher, additional non-equijoin queries are possible due to the addition of nested loop joins. These queries typically involve `SEMI JOIN`, `ANTI JOIN`, or `FULL OUTER JOIN` clauses. Impala sometimes also uses nested loop joins internally when evaluating `OUTER JOIN` queries involving complex type columns. Query phases involving nested loop joins do not use the spill-to-disk mechanism if they exceed the memory limit. Impala decides internally when to use each join mechanism; you cannot specify any query hint to choose between the nested loop join or the original hash join algorithm.

```
SELECT * FROM t1 LEFT OUTER JOIN t2 ON t1.int_col < t2.int_col;
```

Semi-joins:

Semi-joins are a relatively rarely used variation. With the left semi-join, only data from the left-hand table is returned, for rows where there is matching data in the right-hand table, based on comparisons between join columns in `ON` or `WHERE` clauses. Only one instance of each row from the left-hand table is returned, regardless of how many matching rows exist in the right-hand table. A right semi-join (available in Impala 2.0 and higher) reverses the comparison and returns data from the right-hand table.

```
SELECT t1.c1, t1.c2, t1.c2 FROM t1 LEFT SEMI JOIN t2 ON t1.id = t2.id;
```

Natural joins (not supported):

Impala does not support the `NATURAL JOIN` operator, again to avoid inconsistent or huge result sets. Natural joins do away with the `ON` and `USING` clauses, and instead automatically join on all columns with the same names in the left-hand and right-hand tables. This kind of query is not recommended for rapidly evolving data structures such as are typically used in Hadoop. Thus, Impala does not support the `NATURAL JOIN` syntax, which can produce different query results as columns are added to or removed from tables.

If you do have any queries that use `NATURAL JOIN`, make sure to rewrite them with explicit `USING` clauses, because Impala could interpret the `NATURAL` keyword as a table alias:

```
-- 'NATURAL' is interpreted as an alias for 't1' and Impala attempts an inner join,
-- resulting in an error because inner joins require explicit comparisons between columns.
SELECT t1.c1, t2.c2 FROM t1 NATURAL JOIN t2;
ERROR: NotImplementedException: Join with 't2' requires at least one conjunctive equality predicate.
    To perform a Cartesian product between two tables, use a CROSS JOIN.

-- If you expect the tables to have identically named columns with matching values,
```

```
-- list the corresponding column names in a USING clause.
SELECT t1.c1, t2.c2 FROM t1 JOIN t2 USING (id, type_flag, name, address);
```

Anti-joins (Impala 2.0 / CDH 5.2 and higher only):

Impala supports the `LEFT ANTI JOIN` and `RIGHT ANTI JOIN` clauses in Impala 2.0 and higher on CDH 4, or CDH 5.2 and higher on CDH 5. The `LEFT` or `RIGHT` keyword is required for this kind of join. For `LEFT ANTI JOIN`, this clause returns those values from the left-hand table that have no matching value in the right-hand table. `RIGHT ANTI JOIN` reverses the comparison and returns values from the right-hand table. You can express this negative relationship either through the `ANTI JOIN` clause or through a `NOT EXISTS` operator with a subquery.

Complex type considerations:

When referring to a column with a complex type (`STRUCT`, `ARRAY`, or `MAP`) in a query, you use join notation to “unpack” the scalar fields of the struct, the elements of the array, or the key-value pairs of the map. (The join notation is not required for aggregation operations, such as `COUNT()` or `SUM()` for array elements.) Because Impala recognizes which complex type elements are associated with which row of the result set, you use the same syntax as for a cross or cartesian join, without an explicit join condition. See [Complex Types \(CDH 5.5 or higher only\)](#) on page 167 for details about Impala support for complex types.

Usage notes:

You typically use join queries in situations like these:

- When related data arrives from different sources, with each data set physically residing in a separate table. For example, you might have address data from business records that you cross-check against phone listings or census data.



Note: Impala can join tables of different file formats, including Impala-managed tables and HBase tables. For example, you might keep small dimension tables in HBase, for convenience of single-row lookups and updates, and for the larger fact tables use Parquet or other binary file format optimized for scan operations. Then, you can issue a join query to cross-reference the fact tables with the dimension tables.

- When data is normalized, a technique for reducing data duplication by dividing it across multiple tables. This kind of organization is often found in data that comes from traditional relational database systems. For example, instead of repeating some long string such as a customer name in multiple tables, each table might contain a numeric customer ID. Queries that need to display the customer name could “join” the table that specifies which customer ID corresponds to which name.
- When certain columns are rarely needed for queries, so they are moved into separate tables to reduce overhead for common queries. For example, a `biography` field might be rarely needed in queries on employee data. Putting that field in a separate table reduces the amount of I/O for common queries on employee addresses or phone numbers. Queries that do need the `biography` column can retrieve it by performing a join with that separate table.
- In CDH 5.5 / Impala 2.3 or higher, when referring to complex type columns in queries. See [Complex Types \(CDH 5.5 or higher only\)](#) on page 167 for details.

When comparing columns with the same names in `ON` or `WHERE` clauses, use the fully qualified names such as `db_name.table_name`, or assign table aliases, column aliases, or both to make the code more compact and understandable:

```
select t1.c1 as first_id, t2.c2 as second_id from
  t1 join t2 on first_id = second_id;

select fact.custno, dimension.custno from
  customer_data as fact join customer_address as dimension
  using (custno)
```



Note:

Performance for join queries is a crucial aspect for Impala, because complex join queries are resource-intensive operations. An efficient join query produces much less network traffic and CPU overhead than an inefficient one. For best results:

- Make sure that both [table and column statistics](#) are available for all the tables involved in a join query, and especially for the columns referenced in any join conditions. Impala uses the statistics to automatically deduce an efficient join order. Use `SHOW TABLE STATS table_name` and `SHOW COLUMN STATS table_name` to check if statistics are already present. Issue the `COMPUTE STATS table_name` for a nonpartitioned table, or (in Impala 2.1.0 and higher) `COMPUTE INCREMENTAL STATS table_name` for a partitioned table, to collect the initial statistics at both the table and column levels, and to keep the statistics up to date after any substantial `INSERT` or `LOAD DATA` operations.
- If table or column statistics are not available, join the largest table first. You can check the existence of statistics with the `SHOW TABLE STATS table_name` and `SHOW COLUMN STATS table_name` statements.
- If table or column statistics are not available, join subsequent tables according to which table has the most selective filter, based on overall size and `WHERE` clauses. Joining the table with the most selective filter results in the fewest number of rows being returned.

For more information and examples of performance for join queries, see [Performance Considerations for Join Queries](#) on page 526.

To control the result set from a join query, include the names of corresponding column names in both tables in an `ON` or `USING` clause, or by coding equality comparisons for those columns in the `WHERE` clause.

```
[localhost:21000] > select c_last_name, ca_city from customer join customer_address
where c_customer_sk = ca_address_sk;
+-----+-----+
| c_last_name | ca_city |
+-----+-----+
| Lewis      | Fairfield |
| Moses      | Fairview |
| Hamilton    | Pleasant Valley |
| White      | Oak Ridge |
| Moran      | Glendale |
| ..         | ..         |
| Richards   | Lakewood |
| Day        | Lebanon  |
| Painter    | Oak Hill |
| Bentley    | Greenfield |
| Jones      | Stringtown |
+-----+-----+
Returned 50000 row(s) in 9.82s
```

One potential downside of joins is the possibility of excess resource usage in poorly constructed queries. Impala imposes restrictions on join queries to guard against such issues. To minimize the chance of runaway queries on large data sets, Impala requires every join query to contain at least one equality predicate between the columns of the various tables. For example, if T1 contains 1000 rows and T2 contains 1,000,000 rows, a query `SELECT columns FROM t1 JOIN t2` could return up to 1 billion rows (1000 * 1,000,000); Impala requires that the query include a clause such as `ON t1.c1 = t2.c2` or `WHERE t1.c1 = t2.c2`.

Because even with equality clauses, the result set can still be large, as we saw in the previous example, you might use a `LIMIT` clause to return a subset of the results:

```
[localhost:21000] > select c_last_name, ca_city from customer, customer_address where
c_customer_sk = ca_address_sk limit 10;
+-----+-----+
| c_last_name | ca_city |
+-----+-----+
| Lewis      | Fairfield |
+-----+-----+
```

```

| Moses      | Fairview      |
| Hamilton   | Pleasant Valley |
| White      | Oak Ridge     |
| Moran      | Glendale      |
| Sharp      | Lakeview      |
| Wiles      | Farmington    |
| Shipman    | Union         |
| Gilbert    | New Hope      |
| Brunson    | Martinsville  |
+-----+-----+
Returned 10 row(s) in 0.63s

```

Or you might use additional comparison operators or aggregation functions to condense a large result set into a smaller set of values:

```

[localhost:21000] > -- Find the names of customers who live in one particular town.
[localhost:21000] > select distinct c_last_name from customer, customer_address
  c_customer_sk = ca_address_sk
  and ca_city = "Green Acres";
+-----+-----+
| c_last_name |
+-----+-----+
| Hensley     |
| Pearson     |
| Mayer       |
| Montgomery  |
| Ricks       |
| ..         |
| Barrett    |
| Price       |
| Hill        |
| Hansen      |
| Meeks       |
+-----+-----+
Returned 332 row(s) in 0.97s

[localhost:21000] > -- See how many different customers in this town have names starting
with "A".
[localhost:21000] > select count(distinct c_last_name) from customer, customer_address
  where
  c_customer_sk = ca_address_sk
  and ca_city = "Green Acres"
  and substr(c_last_name,1,1) = "A";
+-----+-----+
| count(distinct c_last_name) |
+-----+-----+
| 12                          |
+-----+-----+
Returned 1 row(s) in 1.00s

```

Because a join query can involve reading large amounts of data from disk, sending large amounts of data across the network, and loading large amounts of data into memory to do the comparisons and filtering, you might do benchmarking, performance analysis, and query tuning to find the most efficient join queries for your data set, hardware capacity, network configuration, and cluster workload.

The two categories of joins in Impala are known as **partitioned joins** and **broadcast joins**. If inaccurate table or column statistics, or some quirk of the data distribution, causes Impala to choose the wrong mechanism for a particular join, consider using query hints as a temporary workaround. For details, see [Query Hints in Impala SELECT Statements](#) on page 326.

Handling NULLs in Join Columns:

By default, join key columns do not match if either one contains a `NULL` value. To treat such columns as equal if both contain `NULL`, you can use an expression such as `A = B OR (A IS NULL AND B IS NULL)`. In CDH 5.7 / Impala 2.5 and higher, the `<=>` operator (shorthand for `IS NOT DISTINCT FROM`) performs the same comparison in a concise and efficient form. The `<=>` operator is more efficient in for comparing join keys in a `NULL`-safe manner, because the operator can use a hash join while the `OR` expression cannot.

Examples:

The following examples refer to these simple tables containing small sets of integers:

```
[localhost:21000] > create table t1 (x int);
[localhost:21000] > insert into t1 values (1), (2), (3), (4), (5), (6);

[localhost:21000] > create table t2 (y int);
[localhost:21000] > insert into t2 values (2), (4), (6);

[localhost:21000] > create table t3 (z int);
[localhost:21000] > insert into t3 values (1), (3), (5);
```

The following example demonstrates an anti-join, returning the values from T1 that do not exist in T2 (in this case, the odd numbers 1, 3, and 5):

```
[localhost:21000] > select x from t1 left anti join t2 on (t1.x = t2.y);
+----+
| x  |
+----+
| 1  |
| 3  |
| 5  |
+----+
```

Related information:

See these tutorials for examples of different kinds of joins:

- [Cross Joins and Cartesian Products with the CROSS JOIN Operator](#) on page 63

ORDER BY Clause

The `ORDER BY` clause of a `SELECT` statement sorts the result set based on the values from one or more columns.

First, data is sorted locally by each `impalad` daemon, then streamed to the coordinator daemon, which merges the sorted result sets. For distributed queries, this is a relatively expensive operation and can require more memory capacity than a query without `ORDER BY`. Even if the query takes approximately the same time to finish with or without the `ORDER BY` clause, subjectively it can appear slower because no results are available until all processing is finished, rather than results coming back gradually as rows matching the `WHERE` clause are found. Therefore, if you only need the first N results from the sorted result set, also include the `LIMIT` clause, which reduces network overhead and the memory requirement on the coordinator node.



Note:

In Impala 1.4.0 and higher, the `LIMIT` clause is now optional (rather than required) for queries that use the `ORDER BY` clause. Impala automatically uses a temporary disk work area to perform the sort if the sort operation would otherwise exceed the Impala memory limit for a particular `DataNode`.

Syntax:

The full syntax for the `ORDER BY` clause is:

```
ORDER BY col_ref [, col_ref ...] [ASC | DESC] [NULLS FIRST | NULLS LAST]
col_ref ::= column_name | integer_literal
```

Although the most common usage is `ORDER BY column_name`, you can also specify `ORDER BY 1` to sort by the first column of the result set, `ORDER BY 2` to sort by the second column, and so on. The number must be a numeric literal, not some other kind of constant expression. (If the argument is some other expression, even a `STRING` value, the query succeeds but the order of results is undefined.)

`ORDER BY column_number` can only be used when the query explicitly lists the columns in the `SELECT` list, not with `SELECT *` queries.

Ascending and descending sorts:

The default sort order (the same as using the `ASC` keyword) puts the smallest values at the start of the result set, and the largest values at the end. Specifying the `DESC` keyword reverses that order.

Sort order for NULL values:

See [NULL](#) on page 198 for details about how `NULL` values are positioned in the sorted result set, and how to use the `NULLS FIRST` and `NULLS LAST` clauses. (The sort position for `NULL` values in `ORDER BY ... DESC` queries is changed in Impala 1.2.1 and higher to be more standards-compliant, and the `NULLS FIRST` and `NULLS LAST` keywords are new in Impala 1.2.1.)

Prior to Impala 1.4.0, Impala required any query including an `ORDER BY` clause to also use a `LIMIT` clause. In Impala 1.4.0 and higher, the `LIMIT` clause is optional for `ORDER BY` queries. In cases where sorting a huge result set requires enough memory to exceed the Impala memory limit for a particular node, Impala automatically uses a temporary disk work area to perform the sort operation.

Complex type considerations:

In CDH 5.5 / Impala 2.3 and higher, the complex data types `STRUCT`, `ARRAY`, and `MAP` are available. These columns cannot be referenced directly in the `ORDER BY` clause. When you query a complex type column, you use join notation to “unpack” the elements of the complex type, and within the join query you can include an `ORDER BY` clause to control the order in the result set of the scalar elements from the complex type. See [Complex Types \(CDH 5.5 or higher only\)](#) on page 167 for details about Impala support for complex types.

The following query shows how a complex type column cannot be directly used in an `ORDER BY` clause:

```
CREATE TABLE games (id BIGINT, score ARRAY <BIGINT>) STORED AS PARQUET;
...use LOAD DATA to load externally created Parquet files into the table...
SELECT id FROM games ORDER BY score DESC;
ERROR: AnalysisException: ORDER BY expression 'score' with complex type 'ARRAY<BIGINT>'
is not supported.
```

Examples:

The following query retrieves the user ID and score, only for scores greater than one million, with the highest scores for each user listed first. Because the individual array elements are now represented as separate rows in the result set, they can be used in the `ORDER BY` clause, referenced using the `ITEM` pseudocolumn that represents each array element.

```
SELECT id, item FROM games, games.score
WHERE item > 1000000
ORDER BY id, item desc;
```

The following queries use similar `ORDER BY` techniques with variations of the `GAMES` table, where the complex type is an `ARRAY` containing `STRUCT` or `MAP` elements to represent additional details about each game that was played. For an array of structures, the fields of the structure are referenced as `ITEM.field_name`. For an array of maps, the keys and values within each array element are referenced as `ITEM.KEY` and `ITEM.VALUE`.

```
CREATE TABLE games2 (id BIGINT, play array < struct <game_name: string, score: BIGINT,
high_score: boolean> >) STORED AS PARQUET
...use LOAD DATA to load externally created Parquet files into the table...
SELECT id, item.game_name, item.score FROM games2, games2.play
WHERE item.score > 1000000
ORDER BY id, item.score DESC;

CREATE TABLE games3 (id BIGINT, play ARRAY < MAP <STRING, BIGINT> >) STORED AS PARQUET;
...use LOAD DATA to load externally created Parquet files into the table...
SELECT id, info.key AS k, info.value AS v from games3, games3.play AS plays,
games3.play.item AS info
WHERE info.KEY = 'score' AND info.VALUE > 1000000
ORDER BY id, info.value desc;
```

Usage notes:

Although the `LIMIT` clause is now optional on `ORDER BY` queries, if your query only needs some number of rows that you can predict in advance, use the `LIMIT` clause to reduce unnecessary processing. For example, if the query has a

clause `LIMIT 10`, each data node sorts its portion of the relevant result set and only returns 10 rows to the coordinator node. The coordinator node picks the 10 highest or lowest row values out of this small intermediate result set.

If an `ORDER BY` clause is applied to an early phase of query processing, such as a subquery or a view definition, Impala ignores the `ORDER BY` clause. To get ordered results from a subquery or view, apply an `ORDER BY` clause to the outermost or final `SELECT` level.

`ORDER BY` is often used in combination with `LIMIT` to perform “top-N” queries:

```
SELECT user_id AS "Top 10 Visitors", SUM(page_views) FROM web_stats
GROUP BY page_views, user_id
ORDER BY SUM(page_views) DESC LIMIT 10;
```

`ORDER BY` is sometimes used in combination with `OFFSET` and `LIMIT` to paginate query results, although it is relatively inefficient to issue multiple queries like this against the large tables typically used with Impala:

```
SELECT page_title AS "Page 1 of search results", page_url FROM search_content
WHERE LOWER(page_title) LIKE '%game%'
ORDER BY page_title LIMIT 10 OFFSET 0;
SELECT page_title AS "Page 2 of search results", page_url FROM search_content
WHERE LOWER(page_title) LIKE '%game%'
ORDER BY page_title LIMIT 10 OFFSET 10;
SELECT page_title AS "Page 3 of search results", page_url FROM search_content
WHERE LOWER(page_title) LIKE '%game%'
ORDER BY page_title LIMIT 10 OFFSET 20;
```

Internal details:

Impala sorts the intermediate results of an `ORDER BY` clause in memory whenever practical. In a cluster of N DataNodes, each node sorts roughly $1/N$ th of the result set, the exact proportion varying depending on how the data matching the query is distributed in HDFS.

If the size of the sorted intermediate result set on any DataNode would cause the query to exceed the Impala memory limit, Impala sorts as much as practical in memory, then writes partially sorted data to disk. (This technique is known in industry terminology as “external sorting” and “spilling to disk”.) As each 8 MB batch of data is written to disk, Impala frees the corresponding memory to sort a new 8 MB batch of data. When all the data has been processed, a final merge sort operation is performed to correctly order the in-memory and on-disk results as the result set is transmitted back to the coordinator node. When external sorting becomes necessary, Impala requires approximately 60 MB of RAM at a minimum for the buffers needed to read, write, and sort the intermediate results. If more RAM is available on the DataNode, Impala will use the additional RAM to minimize the amount of disk I/O for sorting.

This external sort technique is used as appropriate on each DataNode (possibly including the coordinator node) to sort the portion of the result set that is processed on that node. When the sorted intermediate results are sent back to the coordinator node to produce the final result set, the coordinator node uses a merge sort technique to produce a final sorted result set without using any extra resources on the coordinator node.

Configuration for disk usage:

By default, intermediate files used during large sort, join, aggregation, or analytic function operations are stored in the directory `/tmp/impala-scratch`. These files are removed when the operation finishes. (Multiple concurrent queries can perform operations that use the “spill to disk” technique, without any name conflicts for these temporary files.) You can specify a different location by starting the `impalad` daemon with the `--scratch_dirs="path_to_directory"` configuration option or the equivalent configuration option in the Cloudera Manager user interface. You can specify a single directory, or a comma-separated list of directories. The scratch directories must be on the local filesystem, not in HDFS. You might specify different directory paths for different hosts, depending on the capacity and speed of the available storage devices. In CDH 5.5 / Impala 2.3 or higher, Impala successfully starts (with a warning written to the log) if it cannot create or read and write files in one of the scratch directories. If there is less than 1 GB free on the filesystem where that directory resides, Impala still runs, but writes a warning message to its log. If Impala encounters an error reading or writing files in a scratch directory during a query, Impala logs the error and the query fails.

Sorting considerations: Although you can specify an `ORDER BY` clause in an `INSERT ... SELECT` statement, any `ORDER BY` clause is ignored and the results are not necessarily sorted. An `INSERT ... SELECT` operation potentially

creates many different data files, prepared on different data nodes, and therefore the notion of the data being stored in sorted order is impractical.

An `ORDER BY` clause without an additional `LIMIT` clause is ignored in any view definition. If you need to sort the entire result set from a view, use an `ORDER BY` clause in the `SELECT` statement that queries the view. You can still make a simple “top 10” report by combining the `ORDER BY` and `LIMIT` clauses in the same view definition:

```
[localhost:21000] > create table unsorted (x bigint);
[localhost:21000] > insert into unsorted values (1), (9), (3), (7), (5), (8), (4), (6),
(2);
[localhost:21000] > create view sorted_view as select x from unsorted order by x;
[localhost:21000] > select x from sorted_view; -- ORDER BY clause in view has no effect.
+----+
| x |
+----+
| 1 |
| 9 |
| 3 |
| 7 |
| 5 |
| 8 |
| 4 |
| 6 |
| 2 |
+----+
[localhost:21000] > select x from sorted_view order by x; -- View query requires ORDER
BY at outermost level.
+----+
| x |
+----+
| 1 |
| 2 |
| 3 |
| 4 |
| 5 |
| 6 |
| 7 |
| 8 |
| 9 |
+----+
[localhost:21000] > create view top_3_view as select x from unsorted order by x limit
3;
[localhost:21000] > select x from top_3_view; -- ORDER BY and LIMIT together in view
definition are preserved.
+----+
| x |
+----+
| 1 |
| 2 |
| 3 |
+----+
```

With the lifting of the requirement to include a `LIMIT` clause in every `ORDER BY` query (in Impala 1.4 and higher):

- Now the use of scratch disk space raises the possibility of an “out of disk space” error on a particular DataNode, as opposed to the previous possibility of an “out of memory” error. Make sure to keep at least 1 GB free on the filesystem used for temporary sorting work.
- The query options [DEFAULT_ORDER_BY_LIMIT](#) and [ABORT_ON_DEFAULT_LIMIT_EXCEEDED](#), which formerly controlled the behavior of `ORDER BY` queries with no limit specified, are now ignored.

In Impala 1.2.1 and higher, all `NULL` values come at the end of the result set for `ORDER BY ... ASC` queries, and at the beginning of the result set for `ORDER BY ... DESC` queries. In effect, `NULL` is considered greater than all other values for sorting purposes. The original Impala behavior always put `NULL` values at the end, even for `ORDER BY ... DESC` queries. The new behavior in Impala 1.2.1 makes Impala more compatible with other popular database systems.

In Impala 1.2.1 and higher, you can override or specify the sorting behavior for `NULL` by adding the clause `NULLS FIRST` or `NULLS LAST` at the end of the `ORDER BY` clause.

```
[localhost:21000] > create table numbers (x int);
[localhost:21000] > insert into numbers values (1), (null), (2), (null), (3);
[localhost:21000] > select x from numbers order by x nulls first;
+-----+
| x     |
+-----+
| NULL  |
| NULL  |
| 1     |
| 2     |
| 3     |
+-----+
[localhost:21000] > select x from numbers order by x desc nulls first;
+-----+
| x     |
+-----+
| NULL  |
| NULL  |
| 3     |
| 2     |
| 1     |
+-----+
[localhost:21000] > select x from numbers order by x nulls last;
+-----+
| x     |
+-----+
| 1     |
| 2     |
| 3     |
| NULL  |
| NULL  |
+-----+
[localhost:21000] > select x from numbers order by x desc nulls last;
+-----+
| x     |
+-----+
| 3     |
| 2     |
| 1     |
| NULL  |
| NULL  |
+-----+
```

Related information:

See [SELECT Statement](#) on page 304 for further examples of queries with the `ORDER BY` clause.

Analytic functions use the `ORDER BY` clause in a different context to define the sequence in which rows are analyzed. See [Impala Analytic Functions](#) on page 470 for details.

GROUP BY Clause

Specify the `GROUP BY` clause in queries that use aggregation functions, such as [COUNT\(\)](#), [SUM\(\)](#), [AVG\(\)](#), [MIN\(\)](#), and [MAX\(\)](#). Specify in the [GROUP BY](#) clause the names of all the columns that do not participate in the aggregation operation.

Complex type considerations:

In CDH 5.5 / Impala 2.3 and higher, the complex data types `STRUCT`, `ARRAY`, and `MAP` are available. These columns cannot be referenced directly in the `ORDER BY` clause. When you query a complex type column, you use join notation to “unpack” the elements of the complex type, and within the join query you can include an `ORDER BY` clause to control the order in the result set of the scalar elements from the complex type. See [Complex Types \(CDH 5.5 or higher only\)](#) on page 167 for details about Impala support for complex types.

Zero-length strings: For purposes of clauses such as `DISTINCT` and `GROUP BY`, Impala considers zero-length strings (`" "`), `NULL`, and space to all be different values.

Examples:

For example, the following query finds the 5 items that sold the highest total quantity (using the `SUM()` function, and also counts the number of sales transactions for those items (using the `COUNT()` function). Because the column representing the item IDs is not used in any aggregation functions, we specify that column in the `GROUP BY` clause.

```
select
  ss_item_sk as Item,
  count(ss_item_sk) as Times_Purchased,
  sum(ss_quantity) as Total_Quantity_Purchased
from store_sales
group by ss_item_sk
order by sum(ss_quantity) desc
limit 5;
```

item	times_purchased	total_quantity_purchased
9325	372	19072
4279	357	18501
7507	371	18475
5953	369	18451
16753	375	18446

The `HAVING` clause lets you filter the results of aggregate functions, because you cannot refer to those expressions in the `WHERE` clause. For example, to find the 5 lowest-selling items that were included in at least 100 sales transactions, we could use this query:

```
select
  ss_item_sk as Item,
  count(ss_item_sk) as Times_Purchased,
  sum(ss_quantity) as Total_Quantity_Purchased
from store_sales
group by ss_item_sk
having times_purchased >= 100
order by sum(ss_quantity)
limit 5;
```

item	times_purchased	total_quantity_purchased
13943	105	4087
2992	101	4176
4773	107	4204
14350	103	4260
11956	102	4275

When performing calculations involving scientific or financial data, remember that columns with type `FLOAT` or `DOUBLE` are stored as true floating-point numbers, which cannot precisely represent every possible fractional value. Thus, if you include a `FLOAT` or `DOUBLE` column in a `GROUP BY` clause, the results might not precisely match literal values in your query or from an original Text data file. Use rounding operations, the `BETWEEN` operator, or another arithmetic technique to match floating-point values that are “near” literal values you expect. For example, this query on the `ss_wholesale_cost` column returns cost values that are close but not identical to the original figures that were entered as decimal fractions.

```
select ss_wholesale_cost, avg(ss_quantity * ss_sales_price) as avg_revenue_per_sale
from sales
group by ss_wholesale_cost
order by avg_revenue_per_sale desc
limit 5;
```

ss_wholesale_cost	avg_revenue_per_sale
96.94000244140625	4454.351539300434
95.93000030517578	4423.119941283189
98.37999725341797	4332.516490316291
97.97000122070312	4330.480601655014
98.52999877929688	4291.316953108634

Notice how wholesale cost values originally entered as decimal fractions such as 96.94 and 98.38 are slightly larger or smaller in the result set, due to precision limitations in the hardware floating-point types. The imprecise representation of `FLOAT` and `DOUBLE` values is why financial data processing systems often store currency using data types that are less space-efficient but avoid these types of rounding errors.

Related information:

[SELECT Statement](#) on page 304, [Impala Aggregate Functions](#) on page 443

HAVING Clause

Performs a filter operation on a `SELECT` query, by examining the results of aggregation functions rather than testing each individual table row. Therefore, it is always used in conjunction with a function such as [COUNT\(\)](#), [SUM\(\)](#), [AVG\(\)](#), [MIN\(\)](#), or [MAX\(\)](#), and typically with the [GROUP BY](#) clause also.

Restrictions:

The filter expression in the `HAVING` clause cannot include a scalar subquery.

Related information:

[SELECT Statement](#) on page 304, [GROUP BY Clause](#) on page 316, [Impala Aggregate Functions](#) on page 443

LIMIT Clause

The `LIMIT` clause in a `SELECT` query sets a maximum number of rows for the result set. Pre-selecting the maximum size of the result set helps Impala to optimize memory usage while processing a distributed query.

Syntax:

```
LIMIT constant_integer_expression
```

The argument to the `LIMIT` clause must evaluate to a constant value. It can be a numeric literal, or another kind of numeric expression involving operators, casts, and function return values. You cannot refer to a column or use a subquery.

Usage notes:

This clause is useful in contexts such as:

- To return exactly N items from a top-N query, such as the 10 highest-rated items in a shopping category or the 50 hostnames that refer the most traffic to a web site.
- To demonstrate some sample values from a table or a particular query. (To display some arbitrary items, use a query with no `ORDER BY` clause. An `ORDER BY` clause causes additional memory and/or disk usage during the query.)
- To keep queries from returning huge result sets by accident if a table is larger than expected, or a `WHERE` clause matches more rows than expected.

Originally, the value for the `LIMIT` clause had to be a numeric literal. In Impala 1.2.1 and higher, it can be a numeric expression.

Prior to Impala 1.4.0, Impala required any query including an [ORDER BY](#) clause to also use a [LIMIT](#) clause. In Impala 1.4.0 and higher, the `LIMIT` clause is optional for `ORDER BY` queries. In cases where sorting a huge result set requires enough memory to exceed the Impala memory limit for a particular node, Impala automatically uses a temporary disk work area to perform the sort operation.

See [ORDER BY Clause](#) on page 312 for details.

In Impala 1.2.1 and higher, you can combine a `LIMIT` clause with an `OFFSET` clause to produce a small result set that is different from a top-N query, for example, to return items 11 through 20. This technique can be used to simulate “paged” results. Because Impala queries typically involve substantial amounts of I/O, use this technique only for compatibility in cases where you cannot rewrite the application logic. For best performance and scalability, wherever practical, query as many items as you expect to need, cache them on the application side, and display small groups of results to users using application logic.

Restrictions:

Correlated subqueries used in `EXISTS` and `IN` operators cannot include a `LIMIT` clause.

Examples:

The following example shows how the `LIMIT` clause caps the size of the result set, with the limit being applied after any other clauses such as `WHERE`.

```
[localhost:21000] > create database limits;
[localhost:21000] > use limits;
[localhost:21000] > create table numbers (x int);
[localhost:21000] > insert into numbers values (1), (3), (4), (5), (2);
Inserted 5 rows in 1.34s
[localhost:21000] > select x from numbers limit 100;
+----+
| x  |
+----+
| 1  |
| 3  |
| 4  |
| 5  |
| 2  |
+----+
Returned 5 row(s) in 0.26s
[localhost:21000] > select x from numbers limit 3;
+----+
| x  |
+----+
| 1  |
| 3  |
| 4  |
+----+
Returned 3 row(s) in 0.27s
[localhost:21000] > select x from numbers where x > 2 limit 2;
+----+
| x  |
+----+
| 3  |
| 4  |
+----+
Returned 2 row(s) in 0.27s
```

For top-N and bottom-N queries, you use the `ORDER BY` and `LIMIT` clauses together:

```
[localhost:21000] > select x as "Top 3" from numbers order by x desc limit 3;
+-----+
| top 3 |
+-----+
| 5     |
| 4     |
| 3     |
+-----+
[localhost:21000] > select x as "Bottom 3" from numbers order by x limit 3;
+-----+
| bottom 3 |
+-----+
| 1        |
| 2        |
| 3        |
+-----+
```

You can use constant values besides integer literals as the `LIMIT` argument:

```
-- Other expressions that yield constant integer values work too.
SELECT x FROM t1 LIMIT 1e6;           -- Limit is one million.
SELECT x FROM t1 LIMIT length('hello world'); -- Limit is 11.
SELECT x FROM t1 LIMIT 2+2;          -- Limit is 4.
SELECT x FROM t1 LIMIT cast(trunc(9.9) AS INT); -- Limit is 9.
```

OFFSET Clause

The `OFFSET` clause in a `SELECT` query causes the result set to start some number of rows after the logical first item. The result set is numbered starting from zero, so `OFFSET 0` produces the same result as leaving out the `OFFSET` clause. Always use this clause in combination with `ORDER BY` (so that it is clear which item should be first, second, and so on) and `LIMIT` (so that the result set covers a bounded range, such as items 0-9, 100-199, and so on).

In Impala 1.2.1 and higher, you can combine a `LIMIT` clause with an `OFFSET` clause to produce a small result set that is different from a top-N query, for example, to return items 11 through 20. This technique can be used to simulate “paged” results. Because Impala queries typically involve substantial amounts of I/O, use this technique only for compatibility in cases where you cannot rewrite the application logic. For best performance and scalability, wherever practical, query as many items as you expect to need, cache them on the application side, and display small groups of results to users using application logic.

Examples:

The following example shows how you could run a “paging” query originally written for a traditional database application. Because typical Impala queries process megabytes or gigabytes of data and read large data files from disk each time, it is inefficient to run a separate query to retrieve each small group of items. Use this technique only for compatibility while porting older applications, then rewrite the application code to use a single query with a large result set, and display pages of results from the cached result set.

```
[localhost:21000] > create table numbers (x int);
[localhost:21000] > insert into numbers select x from very_long_sequence;
Inserted 1000000 rows in 1.34s
[localhost:21000] > select x from numbers order by x limit 5 offset 0;
+-----+
| x     |
+-----+
| 1     |
| 2     |
| 3     |
| 4     |
| 5     |
+-----+
[localhost:21000] > select x from numbers order by x limit 5 offset 5;
+-----+
| x     |
+-----+
| 6     |
| 7     |
| 8     |
| 9     |
| 10    |
+-----+
```

UNION Clause

The `UNION` clause lets you combine the result sets of multiple queries. By default, the result sets are combined as if the `DISTINCT` operator was applied.

Syntax:

```
query_1 UNION [DISTINCT | ALL] query_2
```

Usage notes:

The `UNION` keyword by itself is the same as `UNION DISTINCT`. Because eliminating duplicates can be a memory-intensive process for a large result set, prefer `UNION ALL` where practical. (That is, when you know the different queries in the union will not produce any duplicates, or where the duplicate values are acceptable.)

When an `ORDER BY` clause applies to a `UNION ALL` or `UNION` query, in Impala 1.4 and higher, the `LIMIT` clause is no longer required. To make the `ORDER BY` and `LIMIT` clauses apply to the entire result set, turn the `UNION` query into a subquery, `SELECT` from the subquery, and put the `ORDER BY` clause at the end, outside the subquery.

Examples:

First, set up some sample data, including duplicate 1 values:

```
[localhost:21000] > create table few_ints (x int);
[localhost:21000] > insert into few_ints values (1), (1), (2), (3);
[localhost:21000] > set default_order_by_limit=1000;
```

This example shows how `UNION ALL` returns all rows from both queries, without any additional filtering to eliminate duplicates. For the large result sets common with Impala queries, this is the most memory-efficient technique.

```
[localhost:21000] > select x from few_ints order by x;
+----+
| x |
+----+
| 1 |
| 1 |
| 2 |
| 3 |
+----+
Returned 4 row(s) in 0.41s
[localhost:21000] > select x from few_ints union all select x from few_ints;
+----+
| x |
+----+
| 1 |
| 1 |
| 2 |
| 3 |
| 1 |
| 1 |
| 2 |
| 3 |
+----+
Returned 8 row(s) in 0.42s
[localhost:21000] > select * from (select x from few_ints union all select x from
few_ints) as t1 order by x;
+----+
| x |
+----+
| 1 |
| 1 |
| 1 |
| 1 |
| 2 |
| 2 |
| 3 |
| 3 |
+----+
Returned 8 row(s) in 0.53s
[localhost:21000] > select x from few_ints union all select 10;
+----+
| x |
+----+
| 10 |
| 1 |
| 1 |
| 2 |
| 3 |
+----+
Returned 5 row(s) in 0.38s
```

This example shows how the `UNION` clause without the `ALL` keyword condenses the result set to eliminate all duplicate values, making the query take more time and potentially more memory. The extra processing typically makes this technique not recommended for queries that return result sets with millions or billions of values.

```
[localhost:21000] > select x from few_ints union select x+1 from few_ints;
+----+
| x |
+----+
| 3 |
| 4 |
```

```

| 1 |
| 2 |
+----+
Returned 4 row(s) in 0.51s
[localhost:21000] > select x from few_ints union select 10;
+----+
| x |
+----+
| 2 |
| 10 |
| 1 |
| 3 |
+----+
Returned 4 row(s) in 0.49s
[localhost:21000] > select * from (select x from few_ints union select x from few_ints)
as t1 order by x;
+----+
| x |
+----+
| 1 |
| 2 |
| 3 |
+----+
Returned 3 row(s) in 0.53s

```

Subqueries in Impala SELECT Statements

A **subquery** is a query that is nested within another query. Subqueries let queries on one table dynamically adapt based on the contents of another table. This technique provides great flexibility and expressive power for SQL queries.

A subquery can return a result set for use in the `FROM` or `WITH` clauses, or with operators such as `IN` or `EXISTS`.

A **scalar subquery** produces a result set with a single row containing a single column, typically produced by an aggregation function such as `MAX()` or `SUM()`. This single result value can be substituted in scalar contexts such as arguments to comparison operators. If the result set is empty, the value of the scalar subquery is `NULL`. For example, the following query finds the maximum value of `T2.Y` and then substitutes that value into the `WHERE` clause of the outer block that queries `T1`:

```
SELECT x FROM t1 WHERE x > (SELECT MAX(y) FROM t2);
```

Uncorrelated subqueries do not refer to any tables from the outer block of the query. The same value or set of values produced by the subquery is used when evaluating each row from the outer query block. In this example, the subquery returns an arbitrary number of values from `T2.Y`, and each value of `T1.X` is tested for membership in that same set of values:

```
SELECT x FROM t1 WHERE x IN (SELECT y FROM t2);
```

Correlated subqueries compare one or more values from the outer query block to values referenced in the `WHERE` clause of the subquery. Each row evaluated by the outer `WHERE` clause can be evaluated using a different set of values. These kinds of subqueries are restricted in the kinds of comparisons they can do between columns of the inner and outer tables. (See the following **Restrictions** item.)

For example, the following query finds all the employees with salaries that are higher than average for their department. The subquery potentially computes a different `AVG()` value for each employee.

```
SELECT employee_name, employee_id FROM employees one WHERE
salary > (SELECT avg(salary) FROM employees two WHERE one.dept_id = two.dept_id);
```

Syntax:

Subquery in the `FROM` clause:

```
SELECT select_list FROM table_ref [, table_ref ...]
table_ref ::= table_name | (select_statement)
```

Subqueries in WHERE clause:

```
WHERE value comparison_operator (scalar_select_statement)
WHERE value [NOT] IN (select_statement)
WHERE [NOT] EXISTS (correlated_select_statement)
WHERE NOT EXISTS (correlated_select_statement)
```

comparison_operator is a numeric comparison such as =, <=, !=, and so on, or a string comparison operator such as LIKE or REGEXP.

Although you can use non-equality comparison operators such as < or >=, the subquery must include at least one equality comparison between the columns of the inner and outer query blocks.

All syntax is available for both correlated and uncorrelated queries, except that the NOT EXISTS clause cannot be used with an uncorrelated subquery.

Impala subqueries can be nested arbitrarily deep.

Standards compliance: Introduced in [SQL:1999](#).

Examples:

This example illustrates how subqueries can be used in the FROM clause to organize the table names, column names, and column values by producing intermediate result sets, especially for join queries.

```
SELECT avg(t1.x), max(t2.y) FROM
  (SELECT id, cast(a AS DECIMAL(10,5)) AS x FROM raw_data WHERE a BETWEEN 0 AND 100) AS
  t1
  JOIN
  (SELECT id, length(s) AS y FROM raw_data WHERE s LIKE 'A%') AS t2;
  USING (id);
```

These examples show how a query can test for the existence of values in a separate table using the EXISTS() operator with a subquery.

The following examples show how a value can be compared against a set of values returned by a subquery.

```
SELECT count(x) FROM t1 WHERE EXISTS(SELECT 1 FROM t2 WHERE t1.x = t2.y * 10);
SELECT x FROM t1 WHERE x IN (SELECT y FROM t2 WHERE state = 'CA');
```

The following examples demonstrate scalar subqueries. When a subquery is known to return a single value, you can substitute it where you would normally put a constant value.

```
SELECT x FROM t1 WHERE y = (SELECT max(z) FROM t2);
SELECT x FROM t1 WHERE y > (SELECT count(z) FROM t2);
```

Usage notes:

If the same table is referenced in both the outer and inner query blocks, construct a table alias in the outer query block and use a fully qualified name to distinguish the inner and outer table references:

```
SELECT * FROM t1 one WHERE id IN (SELECT parent FROM t1 two WHERE t1.parent = t2.id);
```

The STRAIGHT_JOIN hint affects the join order of table references in the query block containing the hint. It does not affect the join order of nested queries, such as views, inline views, or WHERE-clause subqueries. To use this hint for performance tuning of complex queries, apply the hint to all query blocks that need a fixed join order.

Internal details:

Internally, subqueries involving IN, NOT IN, EXISTS, or NOT EXISTS clauses are rewritten into join queries. Depending on the syntax, the subquery might be rewritten to an outer join, semi join, cross join, or anti join.

A query is processed differently depending on whether the subquery calls any aggregation functions. There are correlated and uncorrelated forms, with and without calls to aggregation functions. Each of these four categories is rewritten differently.

Column statistics considerations:

Because queries that include correlated and uncorrelated subqueries in the `WHERE` clause are written into join queries, to achieve best performance, follow the same guidelines for running the `COMPUTE STATS` statement as you do for tables involved in regular join queries. Run the `COMPUTE STATS` statement for each associated tables after loading or substantially changing the data in that table. See [Table and Column Statistics](#) on page 533 for details.

Added in: Subqueries are substantially enhanced starting in Impala 2.0 for CDH 4, and CDH 5.2.0. Now, they can be used in the `WHERE` clause, in combination with clauses such as `EXISTS` and `IN`, rather than just in the `FROM` clause.

Restrictions:

The initial Impala support for nested subqueries addresses the most common use cases. Some restrictions remain:

- Although you can use subqueries in a query involving `UNION` or `UNION ALL` in Impala 2.1.0 and higher, currently you cannot construct a union of two subqueries (for example, in the argument of an `IN` or `EXISTS` operator).
- Subqueries returning scalar values cannot be used with the operators `ANY` or `ALL`. (Impala does not currently have a `SOME` operator, but if it did, the same restriction would apply.)
- For the `EXISTS` and `NOT EXISTS` clauses, any subquery comparing values from the outer query block to another table must use at least one equality comparison, not exclusively other kinds of comparisons such as less than, greater than, `BETWEEN`, or `!=`.
- Currently, a scalar subquery cannot be used as the first or second argument to the `BETWEEN` operator.
- A subquery cannot be used inside an `OR` conjunction. Expressions inside a subquery, for example in the `WHERE` clause, can use `OR` conjunctions; the restriction only applies to parts of the query “above” the subquery.
- Scalar subqueries are only supported in numeric contexts. You cannot use a scalar subquery as an argument to the `LIKE`, `REGEXP`, or `RLIKE` operators, or compare it to a value of a non-numeric type such as `TIMESTAMP` or `BOOLEAN`.
- You cannot use subqueries with the `CASE` function to generate the comparison value, the values to be compared against, or the return value.
- A subquery is not allowed in the filter condition for the `HAVING` clause. (Strictly speaking, a subquery cannot appear anywhere outside the `WITH`, `FROM`, and `WHERE` clauses.)
- You must use a fully qualified name (`table_name.column_name` or `database_name.table_name.column_name`) when referring to any column from the outer query block within a subquery.

Complex type considerations:

For the complex types (`ARRAY`, `STRUCT`, and `MAP`) available in CDH 5.5 / Impala 2.3 and higher, the join queries that “unpack” complex type columns often use correlated subqueries in the `FROM` clause. For example, if the first table in the join clause is `CUSTOMER`, the second join clause might have a subquery that selects from the column `CUSTOMER.C_ORDERS`, which is an `ARRAY`. The subquery re-evaluates the `ARRAY` elements corresponding to each row from the `CUSTOMER` table. See [Complex Types \(CDH 5.5 or higher only\)](#) on page 167 for details and examples of using subqueries with complex types.

Related information:

[EXISTS Operator](#) on page 203, [IN Operator](#) on page 207

WITH Clause

A clause that can be added before a `SELECT` statement, to define aliases for complicated expressions that are referenced multiple times within the body of the `SELECT`. Similar to `CREATE VIEW`, except that the table and column names

defined in the `WITH` clause do not persist after the query finishes, and do not conflict with names used in actual tables or views. Also known as “subquery factoring”.

You can rewrite a query using subqueries to work the same as with the `WITH` clause. The purposes of the `WITH` clause are:

- Convenience and ease of maintenance from less repetition with the body of the query. Typically used with queries involving `UNION`, joins, or aggregation functions where the similar complicated expressions are referenced multiple times.
- SQL code that is easier to read and understand by abstracting the most complex part of the query into a separate block.
- Improved compatibility with SQL from other database systems that support the same clause (primarily Oracle Database).



Note:

The Impala `WITH` clause does not support recursive queries in the `WITH`, which is supported in some other database systems.

Standards compliance: Introduced in [SQL:1999](#).

Examples:

```
-- Define 2 subqueries that can be referenced from the body of a longer query.
with t1 as (select 1), t2 as (select 2) insert into tab select * from t1 union all select
 * from t2;

-- Define one subquery at the outer level, and another at the inner level as part of
the
-- initial stage of the UNION ALL query.
with t1 as (select 1) (with t2 as (select 2) select * from t2) union all select * from
t1;
```

DISTINCT Operator

The `DISTINCT` operator in a `SELECT` statement filters the result set to remove duplicates:

```
-- Returns the unique values from one column.
-- NULL is included in the set of values if any rows have a NULL in this column.
select distinct c_birth_country from customer;
-- Returns the unique combinations of values from multiple columns.
select distinct c_salutation, c_last_name from customer;
```

You can use `DISTINCT` in combination with an aggregation function, typically `COUNT()`, to find how many different values a column contains:

```
-- Counts the unique values from one column.
-- NULL is not included as a distinct value in the count.
select count(distinct c_birth_country) from customer;
-- Counts the unique combinations of values from multiple columns.
select count(distinct c_salutation, c_last_name) from customer;
```

One construct that Impala SQL does *not* support is using `DISTINCT` in more than one aggregation function in the same query. For example, you could not have a single query with both `COUNT(DISTINCT c_first_name)` and `COUNT(DISTINCT c_last_name)` in the `SELECT` list.

Zero-length strings: For purposes of clauses such as `DISTINCT` and `GROUP BY`, Impala considers zero-length strings (`" "`), `NULL`, and space to all be different values.

**Note:**

By default, Impala only allows a single `COUNT(DISTINCT columns)` expression in each query.

If you do not need precise accuracy, you can produce an estimate of the distinct values for a column by specifying `NDV(column)`; a query can contain multiple instances of `NDV(column)`. To make Impala automatically rewrite `COUNT(DISTINCT)` expressions to `NDV()`, enable the `APPX_COUNT_DISTINCT` query option.

To produce the same result as multiple `COUNT(DISTINCT)` expressions, you can use the following technique for queries involving a single table:

```
select v1.c1 result1, v2.c1 result2 from
  (select count(distinct col1) as c1 from t1) v1
  cross join
  (select count(distinct col2) as c1 from t1) v2;
```

Because `CROSS JOIN` is an expensive operation, prefer to use the `NDV()` technique wherever practical.

**Note:**

In contrast with some database systems that always return `DISTINCT` values in sorted order, Impala does not do any ordering of `DISTINCT` values. Always include an `ORDER BY` clause if you need the values in alphabetical or numeric sorted order.

Query Hints in Impala SELECT Statements

The Impala SQL dialect supports query hints, for fine-tuning the inner workings of queries. Specify hints as a temporary workaround for expensive queries, where missing statistics or other factors cause inefficient performance.

Hints are most often used for the most resource-intensive kinds of Impala queries:

- Join queries involving large tables, where intermediate result sets are transmitted across the network to evaluate the join conditions.
- Inserting into partitioned Parquet tables, where many memory buffers could be allocated on each host to hold intermediate results for each partition.

Syntax:

You can represent the hints as keywords surrounded by `[]` square brackets; include the brackets in the text of the SQL statement.

```
SELECT STRAIGHT_JOIN select_list FROM
  join_left_hand_table
  JOIN [ {BROADCAST|SHUFFLE} ]
  join_right_hand_table
  remainder_of_query;

INSERT insert_clauses
  [ {SHUFFLE|NOSHUFFLE} ]
  SELECT remainder_of_query;

SELECT select_list FROM
  table_ref
  /* +{SCHEDULE_CACHE_LOCAL | SCHEDULE_DISK_LOCAL | SCHEDULE_REMOTE}
  [ ,RANDOM_REPLICA] */
  remainder_of_query;
```

In Impala 2.0 and higher, or CDH 5.2 and higher, you can also specify the hints inside comments that use either the `/* */` or `--` notation. Recently added hints are only available using the `/* */` and `--` notation. For clarity, the `/* */`

and `--` styles are used in the syntax and examples throughout this section. With the `/* */` or `--` notation for hints, specify a `+` symbol immediately before the hint name.

```

SELECT STRAIGHT_JOIN select_list FROM
  join_left_hand_table
  JOIN /* +BROADCAST|SHUFFLE */
  join_right_hand_table
  remainder_of_query;

SELECT select_list FROM
  join_left_hand_table
  JOIN -- +BROADCAST|SHUFFLE
  join_right_hand_table
  remainder_of_query;

INSERT insert_clauses
/* +SHUFFLE|NOSHUFFLE */
SELECT remainder_of_query;

INSERT insert_clauses
-- +SHUFFLE|NOSHUFFLE
SELECT remainder_of_query;

```

Usage notes:

With both forms of hint syntax, include the `STRAIGHT_JOIN` keyword immediately after the `SELECT` and any `DISTINCT` or `ALL` keywords to prevent Impala from reordering the tables in a way that makes the join-related hints ineffective.

The `STRAIGHT_JOIN` hint affects the join order of table references in the query block containing the hint. It does not affect the join order of nested queries, such as views, inline views, or `WHERE`-clause subqueries. To use this hint for performance tuning of complex queries, apply the hint to all query blocks that need a fixed join order.

To reduce the need to use hints, run the `COMPUTE STATS` statement against all tables involved in joins, or used as the source tables for `INSERT ... SELECT` operations where the destination is a partitioned Parquet table. Do this operation after loading data or making substantial changes to the data within each table. Having up-to-date statistics helps Impala choose more efficient query plans without the need for hinting. See [Table and Column Statistics](#) on page 533 for details and examples.

To see which join strategy is used for a particular query, examine the `EXPLAIN` output for that query. See [Using the EXPLAIN Plan for Performance Tuning](#) on page 557 for details and examples.

Hints for join queries:

The `[BROADCAST]` and `[SHUFFLE]` hints control the execution strategy for join queries. Specify one of the following constructs immediately after the `JOIN` keyword in a query:

- `[SHUFFLE]` - Makes that join operation use the “partitioned” technique, which divides up corresponding rows from both tables using a hashing algorithm, sending subsets of the rows to other nodes for processing. (The keyword `SHUFFLE` is used to indicate a “partitioned join”, because that type of join is not related to “partitioned tables”.) Since the alternative “broadcast” join mechanism is the default when table and index statistics are unavailable, you might use this hint for queries where broadcast joins are unsuitable; typically, partitioned joins are more efficient for joins between large tables of similar size.
- `[BROADCAST]` - Makes that join operation use the “broadcast” technique that sends the entire contents of the right-hand table to all nodes involved in processing the join. This is the default mode of operation when table and index statistics are unavailable, so you would typically only need it if stale metadata caused Impala to mistakenly choose a partitioned join operation. Typically, broadcast joins are more efficient in cases where one table is much smaller than the other. (Put the smaller table on the right side of the `JOIN` operator.)

Hints for INSERT ... SELECT queries:

When inserting into partitioned tables, especially using the Parquet file format, you can include a hint in the `INSERT` statement to fine-tune the overall performance of the operation and its resource usage:

- These hints are available in Impala 1.2.2 and higher.

- You would only use these hints if an `INSERT` into a partitioned Parquet table was failing due to capacity limits, or if such an `INSERT` was succeeding but with less-than-optimal performance.
- To use these hints, put the hint keyword `[SHUFFLE]` or `[NOSHUFFLE]` (including the square brackets) after the `PARTITION` clause, immediately before the `SELECT` keyword.
- `[SHUFFLE]` selects an execution plan that minimizes the number of files being written simultaneously to HDFS, and the number of memory buffers holding data for individual partitions. Thus it reduces overall resource usage for the `INSERT` operation, allowing some `INSERT` operations to succeed that otherwise would fail. It does involve some data transfer between the nodes so that the data files for a particular partition are all constructed on the same node.
- `[NOSHUFFLE]` selects an execution plan that might be faster overall, but might also produce a larger number of small data files or exceed capacity limits, causing the `INSERT` operation to fail. Use `[SHUFFLE]` in cases where an `INSERT` statement fails or runs inefficiently due to all nodes attempting to construct data for all partitions.
- Impala automatically uses the `[SHUFFLE]` method if any partition key column in the source table, mentioned in the `INSERT . . . SELECT` query, does not have column statistics. In this case, only the `[NOSHUFFLE]` hint would have any effect.
- If column statistics are available for all partition key columns in the source table mentioned in the `INSERT . . . SELECT` query, Impala chooses whether to use the `[SHUFFLE]` or `[NOSHUFFLE]` technique based on the estimated number of distinct values in those columns and the number of nodes involved in the `INSERT` operation. In this case, you might need the `[SHUFFLE]` or the `[NOSHUFFLE]` hint to override the execution plan selected by Impala.

Hints for scheduling of HDFS blocks:

The hints `/* +SCHEDULE_CACHE_LOCAL */`, `/* +SCHEDULE_DISK_LOCAL */`, and `/* +SCHEDULE_REMOTE */` have the same effect as specifying the `REPLICA_PREFERENCE` query option with the respective option settings of `CACHE_LOCAL`, `DISK_LOCAL`, or `REMOTE`. The hint `/* +RANDOM_REPLICA */` is the same as enabling the `SCHEDULE_RANDOM_REPLICA` query option.

You can use these hints in combination by separating them with commas, for example, `/* +SCHEDULE_CACHE_LOCAL, RANDOM_REPLICA */`. See [REPLICA_PREFERENCE Query Option \(CDH 5.9 or higher only\)](#) on page 351 and [SCHEDULE_RANDOM_REPLICA Query Option \(CDH 5.7 or higher only\)](#) on page 355 for information about how these settings influence the way Impala processes HDFS data blocks.

Specifying the replica preference as a query hint always overrides the query option setting. Specifying either the `SCHEDULE_RANDOM_REPLICA` query option or the corresponding `RANDOM_REPLICA` query hint enables the random tie-breaking behavior when processing data blocks during the query.

Suggestions versus directives:

In early Impala releases, hints were always obeyed and so acted more like directives. Once Impala gained join order optimizations, sometimes join queries were automatically reordered in a way that made a hint irrelevant. Therefore, the hints act more like suggestions in Impala 1.2.2 and higher.

To force Impala to follow the hinted execution mechanism for a join query, include the `STRAIGHT_JOIN` keyword in the `SELECT` statement. See [Overriding Join Reordering with STRAIGHT_JOIN](#) on page 527 for details. When you use this technique, Impala does not reorder the joined tables at all, so you must be careful to arrange the join order to put the largest table (or subquery result set) first, then the smallest, second smallest, third smallest, and so on. This ordering lets Impala do the most I/O-intensive parts of the query using local reads on the DataNodes, and then reduce the size of the intermediate result set as much as possible as each subsequent table or subquery result set is joined.

Restrictions:

Queries that include subqueries in the `WHERE` clause can be rewritten internally as join queries. Currently, you cannot apply hints to the joins produced by these types of queries.

Because hints can prevent queries from taking advantage of new metadata or improvements in query planning, use them only when required to work around performance issues, and be prepared to remove them when they are no longer required, such as after a new Impala release or bug fix.

In particular, the `[BROADCAST]` and `[SHUFFLE]` hints are expected to be needed much less frequently in Impala 1.2.2 and higher, because the join order optimization feature in combination with the `COMPUTE STATS` statement now

automatically choose join order and join mechanism without the need to rewrite the query and add hints. See [Performance Considerations for Join Queries](#) on page 526 for details.

Compatibility:

The hints embedded within `--` comments are compatible with Hive queries. The hints embedded within `/* */` comments or `[]` square brackets are not recognized by or not compatible with Hive. For example, Hive raises an error for Impala hints within `/* */` comments because it does not recognize the Impala hint names.

Considerations for views:

If you use a hint in the query that defines a view, the hint is preserved when you query the view. Impala internally rewrites all hints in views to use the `--` comment notation, so that Hive can query such views without errors due to unrecognized hint names.

Examples:

For example, this query joins a large customer table with a small lookup table of less than 100 rows. The right-hand table can be broadcast efficiently to all nodes involved in the join. Thus, you would use the `[broadcast]` hint to force a broadcast join strategy:

```
select straight_join customer.address, state_lookup.state_name
  from customer join [broadcast] state_lookup
 on customer.state_id = state_lookup.state_id;
```

This query joins two large tables of unpredictable size. You might benchmark the query with both kinds of hints and find that it is more efficient to transmit portions of each table to other nodes for processing. Thus, you would use the `[shuffle]` hint to force a partitioned join strategy:

```
select straight_join weather.wind_velocity, geospatial.altitude
  from weather join [shuffle] geospatial
 on weather.lat = geospatial.lat and weather.long = geospatial.long;
```

For joins involving three or more tables, the hint applies to the tables on either side of that specific `JOIN` keyword. The `STRAIGHT_JOIN` keyword ensures that joins are processed in a predictable order from left to right. For example, this query joins `t1` and `t2` using a partitioned join, then joins that result set to `t3` using a broadcast join:

```
select straight_join t1.name, t2.id, t3.price
  from t1 join [shuffle] t2 join [broadcast] t3
 on t1.id = t2.id and t2.id = t3.id;
```

Related information:

For more background information about join queries, see [Joins in Impala SELECT Statements](#) on page 306. For performance considerations, see [Performance Considerations for Join Queries](#) on page 526.

SET Statement

Specifies values for query options that control the runtime behavior of other statements within the same session.

In CDH 5.7 / Impala 2.5 and higher, `SET` also defines user-specified substitution variables for the `impala-shell` interpreter. This feature uses the `SET` command built into `impala-shell` instead of the SQL `SET` statement. Therefore the substitution mechanism only works with queries processed by `impala-shell`, not with queries submitted through JDBC or ODBC.

Syntax:

```
SET [query_option=option_value]
```

`SET` with no arguments returns a result set consisting of all available query options and their current values.

The query option name and any string argument values are case-insensitive.

Each query option has a specific allowed notation for its arguments. Boolean options can be enabled and disabled by assigning values of either `true` and `false`, or `1` and `0`. Some numeric options accept a final character signifying the unit, such as `2g` for 2 gigabytes or `100m` for 100 megabytes. See [Query Options for the SET Statement](#) on page 331 for the details of each query option.

User-specified substitution variables:

In CDH 5.7 / Impala 2.5 and higher, you can specify your own names and string substitution values within the `impala-shell` interpreter. Once a substitution variable is set up, its value is inserted into any SQL statement in that same `impala-shell` session that contains the notation `${var:varname}`. Using `SET` in an interactive `impala-shell` session overrides any value for that same variable passed in through the `--var=varname=value` command-line option.

For example, to set up some default parameters for report queries, but then override those default within an `impala-shell` session, you might issue commands and statements such as the following:

```
-- Initial setup for this example.
create table staging_table (s string);
insert into staging_table values ('foo'), ('bar'), ('bletch');

create table production_table (s string);
insert into production_table values ('North America'), ('EMEA'), ('Asia');
quit;

-- Start impala-shell with user-specified substitution variables,
-- run a query, then override the variables with SET and run the query again.
$ impala-shell --var=table_name=staging_table --var=cutoff=2
... banner message ...
[localhost:21000] > select s from ${var:table_name} order by s limit ${var:cutoff};
Query: select s from staging_table order by s limit 2
+-----+
| s      |
+-----+
| bar    |
| bletch |
+-----+
Fetched 2 row(s) in 1.06s

[localhost:21000] > set var:table_name=production_table;
Variable TABLE_NAME set to production_table
[localhost:21000] > set var:cutoff=3;
Variable CUTOFF set to 3

[localhost:21000] > select s from ${var:table_name} order by s limit ${var:cutoff};
Query: select s from production_table order by s limit 3
+-----+
| s      |
+-----+
| Asia   |
| EMEA   |
| North America |
+-----+
```

The following example shows how `SET` with no parameters displays all user-specified substitution variables, and how `UNSET` removes the substitution variable entirely:

```
[localhost:21000] > set;
Query options (defaults shown in []):
ABORT_ON_DEFAULT_LIMIT_EXCEEDED: [0]
...
V_CPU_CORES: [0]

Shell Options
LIVE_PROGRESS: False
LIVE_SUMMARY: False

Variables:
```

```

CUTOFF: 3
TABLE_NAME: staging_table

[localhost:21000] > unset var:cutoff;
Unsetting variable CUTOFF
[localhost:21000] > select s from ${var:table_name} order by s limit ${var:cutoff};
Error: Unknown variable CUTOFF

```

See [Running Commands and SQL Statements in impala-shell](#) on page 517 for more examples of using the `--var`, `SET`, and `${var:varname}` substitution technique in `impala-shell`.

Usage notes:

`MEM_LIMIT` is probably the most commonly used query option. You can specify a high value to allow a resource-intensive query to complete. For testing how queries would work on memory-constrained systems, you might specify an artificially low value.

Complex type considerations:

Examples:

The following example sets some numeric and some Boolean query options to control usage of memory, disk space, and timeout periods, then runs a query whose success could depend on the options in effect:

```

set mem_limit=64g;
set DISABLE_UNSAFE_SPILLS=true;
set parquet_file_size=400m;
set RESERVATION_REQUEST_TIMEOUT=900000;
insert overwrite parquet_table select c1, c2, count(c3) from text_table group by c1,
c2, c3;

```

Added in: CDH 5.2.0 (Impala 2.0.0)

`SET` has always been available as an `impala-shell` command. Promoting it to a SQL statement lets you use this feature in client applications through the JDBC and ODBC APIs.

Cancellation: Cannot be cancelled.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Related information:

See [Query Options for the SET Statement](#) on page 331 for the query options you can adjust using this statement.

Query Options for the SET Statement

You can specify the following options using the `SET` statement, and those settings affect all queries issued from that session.

Some query options are useful in day-to-day operations for improving usability, performance, or flexibility.

Other query options control special-purpose aspects of Impala operation and are intended primarily for advanced debugging or troubleshooting.

Options with Boolean parameters can be set to 1 or `true` to enable, or 0 or `false` to turn off.



Note:

In Impala 2.0 and later, you can set query options directly through the JDBC and ODBC interfaces by using the `SET` statement. Formerly, `SET` was only available as a command within the `impala-shell` interpreter.

Related information:

[SET Statement](#) on page 329

ABORT_ON_DEFAULT_LIMIT_EXCEEDED Query Option

Now that the `ORDER BY` clause no longer requires an accompanying `LIMIT` clause in Impala 1.4.0 and higher, this query option is deprecated and has no effect.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false` (shown as 0 in output of `SET` statement)

ABORT_ON_ERROR Query Option

When this option is enabled, Impala cancels a query immediately when any of the nodes encounters an error, rather than continuing and possibly returning incomplete results. This option is disabled by default, to help gather maximum diagnostic information when an error occurs, for example, whether the same problem occurred on all nodes or only a single node. Currently, the errors that Impala can skip over involve data corruption, such as a column that contains a string value when expected to contain an integer value.

To control how much logging Impala does for non-fatal errors when `ABORT_ON_ERROR` is turned off, use the `MAX_ERRORS` option.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false` (shown as 0 in output of `SET` statement)

Related information:

[MAX_ERRORS Query Option](#) on page 343, [Using Impala Logging](#) on page 627

ALLOW_UNSUPPORTED_FORMATS Query Option

An obsolete query option from early work on support for file formats. Do not use. Might be removed in the future.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false` (shown as 0 in output of `SET` statement)

APPX_COUNT_DISTINCT Query Option (CDH 5.2 or higher only)

Allows multiple `COUNT(DISTINCT)` operations within a single query, by internally rewriting each `COUNT(DISTINCT)` to use the `NDV()` function. The resulting count is approximate rather than precise.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false` (shown as 0 in output of `SET` statement)

Examples:

The following examples show how the `APPX_COUNT_DISTINCT` lets you work around the restriction where a query can only evaluate `COUNT(DISTINCT col_name)` for a single column. By default, you can count the distinct values of one column or another, but not both in a single query:

```
[localhost:21000] > select count(distinct x) from int_t;
+-----+
| count(distinct x) |
+-----+
| 10                |
+-----+
[localhost:21000] > select count(distinct property) from int_t;
+-----+
| count(distinct property) |
+-----+
| 7                        |
+-----+
[localhost:21000] > select count(distinct x), count(distinct property) from int_t;
ERROR: AnalysisException: all DISTINCT aggregate functions need to have the same set of
parameters
as count(DISTINCT x); deviating function: count(DISTINCT property)
```

When you enable the `APPX_COUNT_DISTINCT` query option, now the query with multiple `COUNT(DISTINCT)` works. The reason this behavior requires a query option is that each `COUNT(DISTINCT)` is rewritten internally to use the `NDV()` function instead, which provides an approximate result rather than a precise count.

```
[localhost:21000] > set APPX_COUNT_DISTINCT=true;
[localhost:21000] > select count(distinct x), count(distinct property) from int_t;
+-----+-----+
| count(distinct x) | count(distinct property) |
+-----+-----+
| 10                | 7                          |
+-----+-----+
```

Related information:

[COUNT Function](#) on page 448, [DISTINCT Operator](#) on page 325, [NDV Function](#) on page 461

BATCH_SIZE Query Option

Number of rows evaluated at a time by SQL operators. Unspecified or a size of 0 uses a predefined default size. Using a large number improves responsiveness, especially for scan operations, at the cost of a higher memory footprint.

This option is primarily for Cloudera testing, or for use under the direction of Cloudera Support.

Type: numeric

Default: 0 (meaning the predefined default of 1024)

COMPRESSION_CODEC Query Option (CDH 5.2 or higher only)

When Impala writes Parquet data files using the `INSERT` statement, the underlying compression is controlled by the `COMPRESSION_CODEC` query option.



Note: Prior to Impala 2.0, this option was named `PARQUET_COMPRESSION_CODEC`. In Impala 2.0 and later, the `PARQUET_COMPRESSION_CODEC` name is not recognized. Use the more general name `COMPRESSION_CODEC` for new code.

Syntax:

```
SET COMPRESSION_CODEC=codec_name;
```

The allowed values for this query option are `SNAPPY` (the default), `GZIP`, and `NONE`.



Note: A Parquet file created with `COMPRESSION_CODEC=NONE` is still typically smaller than the original data, due to encoding schemes such as run-length encoding and dictionary encoding that are applied separately from compression.

The option value is not case-sensitive.

If the option is set to an unrecognized value, all kinds of queries will fail due to the invalid option setting, not just queries involving Parquet tables. (The value `BZIP2` is also recognized, but is not compatible with Parquet tables.)

Type: `STRING`

Default: `SNAPPY`

Examples:

```
set compression_codec=gzip;
insert into parquet_table_highly_compressed select * from t1;

set compression_codec=snappy;
insert into parquet_table_compression_plus_fast_queries select * from t1;

set compression_codec=none;
insert into parquet_table_no_compression select * from t1;
```

```
set compression_codec=foo;
select * from t1 limit 5;
ERROR: Invalid compression codec: foo
```

Related information:

For information about how compressing Parquet data files affects query performance, see [Snappy and GZip Compression for Parquet Data Files](#) on page 588.

DEBUG_ACTION Query Option

Introduces artificial problem conditions within queries. For internal Cloudera debugging and troubleshooting.

Type: STRING

Default: empty string

DEFAULT_ORDER_BY_LIMIT Query Option

Now that the `ORDER BY` clause no longer requires an accompanying `LIMIT` clause in Impala 1.4.0 and higher, this query option is deprecated and has no effect.

Prior to Impala 1.4.0, Impala queries that use the `ORDER BY` clause must also include a `LIMIT` clause, to avoid accidentally producing huge result sets that must be sorted. Sorting a huge result set is a memory-intensive operation. In Impala 1.4.0 and higher, Impala uses a temporary disk work area to perform the sort if that operation would otherwise exceed the Impala memory limit on a particular host.

Type: numeric

Default: -1 (no default limit)

DISABLE_CODEGEN Query Option

This is a debug option, intended for diagnosing and working around issues that cause crashes. If a query fails with an “illegal instruction” or other hardware-specific message, try setting `DISABLE_CODEGEN=true` and running the query again. If the query succeeds only when the `DISABLE_CODEGEN` option is turned on, submit the problem to Cloudera support and include that detail in the problem report. Do not otherwise run with this setting turned on, because it results in lower overall performance.

Because the code generation phase adds a small amount of overhead for each query, you might turn on the `DISABLE_CODEGEN` option to achieve maximum throughput when running many short-lived queries against small tables.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false` (shown as 0 in output of `SET` statement)

DISABLE_ROW_RUNTIME_FILTERING Query Option (CDH 5.7 or higher only)

The `DISABLE_ROW_RUNTIME_FILTERING` query option reduces the scope of the runtime filtering feature. Queries still dynamically prune partitions, but do not apply the filtering logic to individual rows within partitions.

Only applies to queries against Parquet tables. For other file formats, Impala only prunes at the level of partitions, not individual rows.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false`

Added in: CDH 5.7.0 (Impala 2.5.0)

Usage notes:

Impala automatically evaluates whether the per-row filters are being effective at reducing the amount of intermediate data. Therefore, this option is typically only needed for the rare case where Impala cannot accurately determine how effective the per-row filtering is for a query.

Because the runtime filtering feature applies mainly to resource-intensive and long-running queries, only adjust this query option when tuning long-running queries involving some combination of large partitioned tables and joins involving large tables.

Because this setting only improves query performance in very specific circumstances, depending on the query characteristics and data distribution, only use it when you determine through benchmarking that it improves performance of specific expensive queries. Consider setting this query option immediately before the expensive query and unsetting it immediately afterward.

Related information:

[Runtime Filtering for Impala Queries](#) on page 545, [RUNTIME_FILTER_MODE Query Option \(CDH 5.7 or higher only\)](#) on page 353

[DISABLE_STREAMING_PREAGGREGATIONS Query Option \(CDH 5.7 or higher only\)](#)

Turns off the “streaming preaggregation” optimization that is available in CDH 5.7 / Impala 2.5 and higher. This optimization reduces unnecessary work performed by queries that perform aggregation operations on columns with few or no duplicate values, for example `DISTINCT id_column` or `GROUP BY unique_column`. If the optimization causes regressions in existing queries that use aggregation functions, you can turn it off as needed by setting this query option.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false` (shown as 0 in output of `SET` statement)



Note: In CDH 5.7.0 / Impala 2.5.0, only the value 1 enables the option, and the value `true` is not recognized. This limitation is tracked by the issue [IMPALA-3334](#), which shows the releases where the problem is fixed.

Usage notes:

Typically, queries that would require enabling this option involve very large numbers of aggregated values, such as a billion or more distinct keys being processed on each worker node.

Added in: CDH 5.7.0 (Impala 2.5.0)

[DISABLE_UNSAFE_SPILLS Query Option \(CDH 5.2 or higher only\)](#)

Enable this option if you prefer to have queries fail when they exceed the Impala memory limit, rather than write temporary data to disk.

Queries that “spill” to disk typically complete successfully, when in earlier Impala releases they would have failed. However, queries with exorbitant memory requirements due to missing statistics or inefficient join clauses could become so slow as a result that you would rather have them cancelled automatically and reduce the memory usage through standard Impala tuning techniques.

This option prevents only “unsafe” spill operations, meaning that one or more tables are missing statistics or the query does not include a hint to set the most efficient mechanism for a join or `INSERT ... SELECT` into a partitioned table. These are the tables most likely to result in suboptimal execution plans that could cause unnecessary spilling. Therefore, leaving this option enabled is a good way to find tables on which to run the `COMPUTE STATS` statement.

See [SQL Operations that Spill to Disk](#) on page 562 for information about the “spill to disk” feature for queries processing large result sets with joins, `ORDER BY`, `GROUP BY`, `DISTINCT`, aggregation functions, or analytic functions.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false` (shown as 0 in output of `SET` statement)

Added in: CDH 5.2.0 (Impala 2.0.0)

[EXEC_SINGLE_NODE_ROWS_THRESHOLD Query Option \(CDH 5.3 or higher only\)](#)

This setting controls the cutoff point (in terms of number of rows scanned) below which Impala treats a query as a “small” query, turning off optimizations such as parallel execution and native code generation. The overhead for these

optimizations is applicable for queries involving substantial amounts of data, but it makes sense to skip them for queries involving tiny amounts of data. Reducing the overhead for small queries allows Impala to complete them more quickly, keeping YARN resources, admission control slots, and so on available for data-intensive queries.

Syntax:

```
SET EXEC_SINGLE_NODE_ROWS_THRESHOLD=number_of_rows
```

Type: numeric

Default: 100

Usage notes: Typically, you increase the default value to make this optimization apply to more queries. If incorrect or corrupted table and column statistics cause Impala to apply this optimization incorrectly to queries that actually involve substantial work, you might see the queries being slower as a result of remote reads. In that case, recompute statistics with the `COMPUTE STATS` or `COMPUTE INCREMENTAL STATS` statement. If there is a problem collecting accurate statistics, you can turn this feature off by setting the value to -1.

Internal details:

This setting applies to query fragments where the amount of data to scan can be accurately determined, either through table and column statistics, or by the presence of a `LIMIT` clause. If Impala cannot accurately estimate the size of the input data, this setting does not apply.

In CDH 5.5 / Impala 2.3 and higher, where Impala supports the complex data types `STRUCT`, `ARRAY`, and `MAP`, if a query refers to any column of those types, the small-query optimization is turned off for that query regardless of the `EXEC_SINGLE_NODE_ROWS_THRESHOLD` setting.

For a query that is determined to be “small”, all work is performed on the coordinator node. This might result in some I/O being performed by remote reads. The savings from not distributing the query work and not generating native code are expected to outweigh any overhead from the remote reads.

Added in: CDH 5.3.0 (Impala 2.1.0)

Examples:

A common use case is to query just a few rows from a table to inspect typical data values. In this example, Impala does not parallelize the query or perform native code generation because the result set is guaranteed to be smaller than the threshold value from this query option:

```
SET EXEC_SINGLE_NODE_ROWS_THRESHOLD=500;
SELECT * FROM enormous_table LIMIT 300;
```

EXPLAIN_LEVEL Query Option

Controls the amount of detail provided in the output of the `EXPLAIN` statement. The basic output can help you identify high-level performance issues such as scanning a higher volume of data or more partitions than you expect. The higher levels of detail show how intermediate results flow between nodes and how different SQL operations such as `ORDER BY`, `GROUP BY`, joins, and `WHERE` clauses are implemented within a distributed query.

Type: `STRING` or `INT`

Default: 1

Arguments:

The allowed range of numeric values for this option is 0 to 3:

- 0 or `MINIMAL`: A barebones list, one line per operation. Primarily useful for checking the join order in very long queries where the regular `EXPLAIN` output is too long to read easily.
- 1 or `STANDARD`: The default level of detail, showing the logical way that work is split up for the distributed query.
- 2 or `EXTENDED`: Includes additional detail about how the query planner uses statistics in its decision-making process, to understand how a query could be tuned by gathering statistics, using query hints, adding or removing predicates, and so on.

- 3 or `VERBOSE`: The maximum level of detail, showing how work is split up within each node into “query fragments” that are connected in a pipeline. This extra detail is primarily useful for low-level performance testing and tuning within Impala itself, rather than for rewriting the SQL code at the user level.



Note: Prior to Impala 1.3, the allowed argument range for `EXPLAIN_LEVEL` was 0 to 1: level 0 had the mnemonic `NORMAL`, and level 1 was `VERBOSE`. In Impala 1.3 and higher, `NORMAL` is not a valid mnemonic value, and `VERBOSE` still applies to the highest level of detail but now corresponds to level 3. You might need to adjust the values if you have any older `impala-shell` script files that set the `EXPLAIN_LEVEL` query option.

Changing the value of this option controls the amount of detail in the output of the `EXPLAIN` statement. The extended information from level 2 or 3 is especially useful during performance tuning, when you need to confirm whether the work for the query is distributed the way you expect, particularly for the most resource-intensive operations such as join queries against large tables, queries against tables with large numbers of partitions, and insert operations for Parquet tables. The extended information also helps to check estimated resource usage when you use the admission control or resource management features explained in [Resource Management for Impala](#) on page 85. See [EXPLAIN Statement](#) on page 283 for the syntax of the `EXPLAIN` statement, and [Using the EXPLAIN Plan for Performance Tuning](#) on page 557 for details about how to use the extended information.

Usage notes:

As always, read the `EXPLAIN` output from bottom to top. The lowest lines represent the initial work of the query (scanning data files), the lines in the middle represent calculations done on each node and how intermediate results are transmitted from one node to another, and the topmost lines represent the final results being sent back to the coordinator node.

The numbers in the left column are generated internally during the initial planning phase and do not represent the actual order of operations, so it is not significant if they appear out of order in the `EXPLAIN` output.

At all `EXPLAIN` levels, the plan contains a warning if any tables in the query are missing statistics. Use the `COMPUTE STATS` statement to gather statistics for each table and suppress this warning. See [Table and Column Statistics](#) on page 533 for details about how the statistics help query performance.

The `PROFILE` command in `impala-shell` always starts with an explain plan showing full detail, the same as with `EXPLAIN_LEVEL=3`. After the explain plan comes the executive summary, the same output as produced by the `SUMMARY` command in `impala-shell`.

Examples:

These examples use a trivial, empty table to illustrate how the essential aspects of query planning are shown in `EXPLAIN` output:

```
[localhost:21000] > create table t1 (x int, s string);
[localhost:21000] > set explain_level=1;
[localhost:21000] > explain select count(*) from t1;
+-----+
| Explain String
+-----+
| Estimated Per-Host Requirements: Memory=10.00MB VCores=1
| WARNING: The following tables are missing relevant table and/or column
| statistics.
| explain_plan.t1
|
| 03:AGGREGATE [MERGE FINALIZE]
|   output: sum(count(*))
|
| 02:EXCHANGE [PARTITION=UNPARTITIONED]
|
| 01:AGGREGATE
|   output: count(*)
|
| 00:SCAN HDFS [explain_plan.t1]
|   partitions=1/1 size=0B
+-----+
```

```
[localhost:21000] > explain select * from t1;
+-----+
| Explain String
+-----+
| Estimated Per-Host Requirements: Memory=-9223372036854775808B VCores=0
| WARNING: The following tables are missing relevant table and/or column
| statistics.
| explain_plan.t1
|
| 01:EXCHANGE [PARTITION=UNPARTITIONED]
| |
| 00:SCAN HDFS [explain_plan.t1]
|   partitions=1/1 size=0B
+-----+
[localhost:21000] > set explain_level=2;
[localhost:21000] > explain select * from t1;
+-----+
| Explain String
+-----+
| Estimated Per-Host Requirements: Memory=-9223372036854775808B VCores=0
| WARNING: The following tables are missing relevant table and/or column
| statistics.
| explain_plan.t1
|
| 01:EXCHANGE [PARTITION=UNPARTITIONED]
| |
|   hosts=0 per-host-mem=unavailable
|   tuple-ids=0 row-size=19B cardinality=unavailable
|
| 00:SCAN HDFS [explain_plan.t1, PARTITION=RANDOM]
|   partitions=1/1 size=0B
|   table stats: unavailable
|   column stats: unavailable
|   hosts=0 per-host-mem=0B
|   tuple-ids=0 row-size=19B cardinality=unavailable
+-----+
[localhost:21000] > set explain_level=3;
[localhost:21000] > explain select * from t1;
+-----+
| Explain String
+-----+
| Estimated Per-Host Requirements: Memory=-9223372036854775808B VCores=0
| WARNING: The following tables are missing relevant table and/or column
| statistics.
| explain_plan.t1
|
| F01:PLAN FRAGMENT [PARTITION=UNPARTITIONED]
|   01:EXCHANGE [PARTITION=UNPARTITIONED]
|     hosts=0 per-host-mem=unavailable
|     tuple-ids=0 row-size=19B cardinality=unavailable
|
| F00:PLAN FRAGMENT [PARTITION=RANDOM]
|   DATASTREAM SINK [FRAGMENT=F01, EXCHANGE=01, PARTITION=UNPARTITIONED]
|   00:SCAN HDFS [explain_plan.t1, PARTITION=RANDOM]
|     partitions=1/1 size=0B
|     table stats: unavailable
|     column stats: unavailable
|     hosts=0 per-host-mem=0B
|     tuple-ids=0 row-size=19B cardinality=unavailable
+-----+
```

As the warning message demonstrates, most of the information needed for Impala to do efficient query planning, and for you to understand the performance characteristics of the query, requires running the `COMPUTE STATS` statement for the table:

```
[localhost:21000] > compute stats t1;
+-----+
| summary
+-----+
| Updated 1 partition(s) and 2 column(s).
+-----+
[localhost:21000] > explain select * from t1;
+-----+
```

```

| Explain String
+-----+
Estimated Per-Host Requirements: Memory=-9223372036854775808B VCores=0
F01:PLAN FRAGMENT [PARTITION=UNPARTITIONED]
  01:EXCHANGE [PARTITION=UNPARTITIONED]
    hosts=0 per-host-mem=unavailable
    tuple-ids=0 row-size=20B cardinality=0

F00:PLAN FRAGMENT [PARTITION=RANDOM]
  DATASTREAM SINK [FRAGMENT=F01, EXCHANGE=01, PARTITION=UNPARTITIONED]
  00:SCAN HDFS [explain_plan.t1, PARTITION=RANDOM]
    partitions=1/1 size=0B
    table stats: 0 rows total
    column stats: all
    hosts=0 per-host-mem=0B
    tuple-ids=0 row-size=20B cardinality=0
+-----+

```

Joins and other complicated, multi-part queries are the ones where you most commonly need to examine the `EXPLAIN` output and customize the amount of detail in the output. This example shows the default `EXPLAIN` output for a three-way join query, then the equivalent output with a `[SHUFFLE]` hint to change the join mechanism between the first two tables from a broadcast join to a shuffle join.

```

[localhost:21000] > set explain_level=1;
[localhost:21000] > explain select one.*, two.*, three.* from t1 one, t1 two, t1 three
where one.x = two.x and two.x = three.x;

```

```

| Explain String
+-----+
Estimated Per-Host Requirements: Memory=4.00GB VCores=3
|
07:EXCHANGE [PARTITION=UNPARTITIONED]
|
04:HASH JOIN [INNER JOIN, BROADCAST]
  hash predicates: two.x = three.x
|
--06:EXCHANGE [BROADCAST]
  |
  02:SCAN HDFS [explain_plan.t1 three]
    partitions=1/1 size=0B
|
03:HASH JOIN [INNER JOIN, BROADCAST]
  hash predicates: one.x = two.x
|
--05:EXCHANGE [BROADCAST]
  |
  01:SCAN HDFS [explain_plan.t1 two]
    partitions=1/1 size=0B
|
00:SCAN HDFS [explain_plan.t1 one]
  partitions=1/1 size=0B
+-----+

```

```

[localhost:21000] > explain select one.*, two.*, three.*
> from t1 one join [shuffle] t1 two join t1 three
> where one.x = two.x and two.x = three.x;

```

```

| Explain String
+-----+
Estimated Per-Host Requirements: Memory=4.00GB VCores=3
|
08:EXCHANGE [PARTITION=UNPARTITIONED]
|
04:HASH JOIN [INNER JOIN, BROADCAST]
  hash predicates: two.x = three.x
|
--07:EXCHANGE [BROADCAST]
  |
  02:SCAN HDFS [explain_plan.t1 three]
    partitions=1/1 size=0B
+-----+

```

```

03:HASH JOIN [INNER JOIN, PARTITIONED]
  hash predicates: one.x = two.x
|--06:EXCHANGE [PARTITION=HASH(two.x)]
  |
  |01:SCAN HDFS [explain_plan.t1 two]
  |  partitions=1/1 size=0B
05:EXCHANGE [PARTITION=HASH(one.x)]
  |
  |00:SCAN HDFS [explain_plan.t1 one]
  |  partitions=1/1 size=0B

```

For a join involving many different tables, the default EXPLAIN output might stretch over several pages, and the only details you care about might be the join order and the mechanism (broadcast or shuffle) for joining each pair of tables. In that case, you might set EXPLAIN_LEVEL to its lowest value of 0, to focus on just the join order and join mechanism for each stage. The following example shows how the rows from the first and second joined tables are hashed and divided among the nodes of the cluster for further filtering; then the entire contents of the third table are broadcast to all nodes for the final stage of join processing.

```

[localhost:21000] > set explain_level=0;
[localhost:21000] > explain select one.*, two.*, three.*
  > from t1 one join [shuffle] t1 two join t1 three
  > where one.x = two.x and two.x = three.x;
-----
| Explain String
-----
Estimated Per-Host Requirements: Memory=4.00GB VCores=3
08:EXCHANGE [PARTITION=UNPARTITIONED]
04:HASH JOIN [INNER JOIN, BROADCAST]
|--07:EXCHANGE [BROADCAST]
  |02:SCAN HDFS [explain_plan.t1 three]
03:HASH JOIN [INNER JOIN, PARTITIONED]
|--06:EXCHANGE [PARTITION=HASH(two.x)]
  |01:SCAN HDFS [explain_plan.t1 two]
05:EXCHANGE [PARTITION=HASH(one.x)]
00:SCAN HDFS [explain_plan.t1 one]
-----

```

HBASE_CACHE_BLOCKS Query Option

Setting this option is equivalent to calling the `setCacheBlocks` method of the class [org.apache.hadoop.hbase.client.Scan](#), in an HBase Java application. Helps to control the memory pressure on the HBase RegionServer, in conjunction with the HBASE_CACHING query option.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false` (shown as 0 in output of SET statement)

Related information:

[Using Impala to Query HBase Tables](#) on page 608, [HBASE_CACHING Query Option](#) on page 340

HBASE_CACHING Query Option

Setting this option is equivalent to calling the `setCaching` method of the class [org.apache.hadoop.hbase.client.Scan](#), in an HBase Java application. Helps to control the memory pressure on the HBase RegionServer, in conjunction with the HBASE_CACHE_BLOCKS query option.

Type: BOOLEAN

Default: 0

Related information:

[Using Impala to Query HBase Tables](#) on page 608, [HBASE_CACHE_BLOCKS Query Option](#) on page 340

LIVE_PROGRESS Query Option (CDH 5.5 or higher only)

For queries submitted through the `impala-shell` command, displays an interactive progress bar showing roughly what percentage of processing has been completed. When the query finishes, the progress bar is erased from the `impala-shell` console output.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false` (shown as 0 in output of `SET` statement)

Command-line equivalent:

You can enable this query option within `impala-shell` by starting the shell with the `--live_progress` command-line option. You can still turn this setting off and on again within the shell through the `SET` command.

Usage notes:

The output from this query option is printed to standard error. The output is only displayed in interactive mode, that is, not when the `-q` or `-f` options are used.

For a more detailed way of tracking the progress of an interactive query through all phases of processing, see [LIVE_SUMMARY Query Option \(CDH 5.5 or higher only\)](#) on page 342.

Restrictions:

Because the percentage complete figure is calculated using the number of issued and completed “scan ranges”, which occur while reading the table data, the progress bar might reach 100% before the query is entirely finished. For example, the query might do work to perform aggregations after all the table data has been read. If many of your queries fall into this category, consider using the `LIVE_SUMMARY` option instead for more granular progress reporting.

The `LIVE_PROGRESS` and `LIVE_SUMMARY` query options currently do not produce any output during `COMPUTE STATS` operations.

Because the `LIVE_PROGRESS` and `LIVE_SUMMARY` query options are available only within the `impala-shell` interpreter:

- You cannot change these query options through the SQL `SET` statement using the JDBC or ODBC interfaces. The `SET` command in `impala-shell` recognizes these names as shell-only options.
- Be careful when using `impala-shell` on a pre-CDH 5.5 system to connect to Impala running on a CDH 5.5 or higher system. The older `impala-shell` does not recognize these query option names. Upgrade `impala-shell` on the systems where you intend to use these query options.
- Likewise, the `impala-shell` command relies on some information only available in Impala 2.3 / CDH 5.5 and higher to prepare live progress reports and query summaries. The `LIVE_PROGRESS` and `LIVE_SUMMARY` query options have no effect when `impala-shell` connects to a cluster running an older version of Impala.

Added in: CDH 5.5.0 (Impala 2.3.0)

Examples:

```
[localhost:21000] > set live_progress=true;
LIVE_PROGRESS set to true
[localhost:21000] > select count(*) from customer;
+-----+
| count(*) |
+-----+
| 150000   |
+-----+
[localhost:21000] > select count(*) from customer t1 cross join customer t2;
[#####] 50%
[#####] 100%
```

To see how the `LIVE_PROGRESS` and `LIVE_SUMMARY` query options work in real time, see [this animated demo](#).

LIVE_SUMMARY Query Option (CDH 5.5 or higher only)

For queries submitted through the `impala-shell` command, displays the same output as the `SUMMARY` command, with the measurements updated in real time as the query progresses. When the query finishes, the final `SUMMARY` output remains visible in the `impala-shell` console output.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false` (shown as 0 in output of `SET` statement)

Command-line equivalent:

You can enable this query option within `impala-shell` by starting the shell with the `--live_summary` command-line option. You can still turn this setting off and on again within the shell through the `SET` command.

Usage notes:

The live summary output can be useful for evaluating long-running queries, to evaluate which phase of execution takes up the most time, or if some hosts take much longer than others for certain operations, dragging overall performance down. By making the information available in real time, this feature lets you decide what action to take even before you cancel a query that is taking much longer than normal.

For example, you might see the HDFS scan phase taking a long time, and therefore revisit performance-related aspects of your schema design such as constructing a partitioned table, switching to the Parquet file format, running the `COMPUTE STATS` statement for the table, and so on. Or you might see a wide variation between the average and maximum times for all hosts to perform some phase of the query, and therefore investigate if one particular host needed more memory or was experiencing a network problem.

The output from this query option is printed to standard error. The output is only displayed in interactive mode, that is, not when the `-q` or `-f` options are used.

For a simple and concise way of tracking the progress of an interactive query, see [LIVE_PROGRESS Query Option \(CDH 5.5 or higher only\)](#) on page 341.

Restrictions:

The `LIVE_PROGRESS` and `LIVE_SUMMARY` query options currently do not produce any output during `COMPUTE STATS` operations.

Because the `LIVE_PROGRESS` and `LIVE_SUMMARY` query options are available only within the `impala-shell` interpreter:

- You cannot change these query options through the SQL `SET` statement using the JDBC or ODBC interfaces. The `SET` command in `impala-shell` recognizes these names as shell-only options.
- Be careful when using `impala-shell` on a pre-CDH 5.5 system to connect to Impala running on a CDH 5.5 or higher system. The older `impala-shell` does not recognize these query option names. Upgrade `impala-shell` on the systems where you intend to use these query options.
- Likewise, the `impala-shell` command relies on some information only available in Impala 2.3 / CDH 5.5 and higher to prepare live progress reports and query summaries. The `LIVE_PROGRESS` and `LIVE_SUMMARY` query options have no effect when `impala-shell` connects to a cluster running an older version of Impala.

Added in: CDH 5.5.0 (Impala 2.3.0)

Examples:

The following example shows a series of `LIVE_SUMMARY` reports that are displayed during the course of a query, showing how the numbers increase to show the progress of different phases of the distributed query. When you do the same in `impala-shell`, only a single report is displayed at any one time, with each update overwriting the previous numbers.

```
[localhost:21000] > set live_summary=true;
LIVE_SUMMARY set to true
[localhost:21000] > select count(*) from customer t1 cross join customer t2;
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+
| Operator | #Hosts | Avg Time | Max Time | #Rows | Est. #Rows | Peak Mem | Est. Peak Mem | Detail |
+-----+-----+-----+-----+-----+-----+-----+-----+-----+-----+

```

06:AGGREGATE	0	0ns	0ns	0	1	0 B	-1 B	FINALIZE
05:EXCHANGE	0	0ns	0ns	0	1	0 B	-1 B	UNPARTITIONED
03:AGGREGATE	0	0ns	0ns	0	1	0 B	10.00 MB	
02:NESTED LOOP JOIN	0	0ns	0ns	0	22.50B	0 B	0 B	CROSS JOIN, BROADCAST
--04:EXCHANGE	0	0ns	0ns	0	150.00K	0 B	0 B	BROADCAST
01:SCAN HDFS	1	503.57ms	503.57ms	150.00K	150.00K	24.09 MB	64.00 MB	tpch.customer t2
00:SCAN HDFS	0	0ns	0ns	0	150.00K	0 B	64.00 MB	tpch.customer t1

Operator	#Hosts	Avg Time	Max Time	#Rows	Est. #Rows	Peak Mem	Est. Peak Mem	Detail
06:AGGREGATE	0	0ns	0ns	0	1	0 B	-1 B	FINALIZE
05:EXCHANGE	0	0ns	0ns	0	1	0 B	-1 B	UNPARTITIONED
03:AGGREGATE	1	0ns	0ns	0	1	20.00 KB	10.00 MB	
02:NESTED LOOP JOIN	1	17.62s	17.62s	81.14M	22.50B	3.23 MB	0 B	CROSS JOIN, BROADCAST
--04:EXCHANGE	1	26.29ms	26.29ms	150.00K	150.00K	0 B	0 B	BROADCAST
01:SCAN HDFS	1	503.57ms	503.57ms	150.00K	150.00K	24.09 MB	64.00 MB	tpch.customer t2
00:SCAN HDFS	1	247.53ms	247.53ms	1.02K	150.00K	24.39 MB	64.00 MB	tpch.customer t1

Operator	#Hosts	Avg Time	Max Time	#Rows	Est. #Rows	Peak Mem	Est. Peak Mem	Detail
06:AGGREGATE	0	0ns	0ns	0	1	0 B	-1 B	FINALIZE
05:EXCHANGE	0	0ns	0ns	0	1	0 B	-1 B	UNPARTITIONED
03:AGGREGATE	1	0ns	0ns	0	1	20.00 KB	10.00 MB	
02:NESTED LOOP JOIN	1	61.85s	61.85s	283.43M	22.50B	3.23 MB	0 B	CROSS JOIN, BROADCAST
--04:EXCHANGE	1	26.29ms	26.29ms	150.00K	150.00K	0 B	0 B	BROADCAST
01:SCAN HDFS	1	503.57ms	503.57ms	150.00K	150.00K	24.09 MB	64.00 MB	tpch.customer t2
00:SCAN HDFS	1	247.59ms	247.59ms	2.05K	150.00K	24.39 MB	64.00 MB	tpch.customer t1

To see how the `LIVE_PROGRESS` and `LIVE_SUMMARY` query options work in real time, see [this animated demo](#).

MAX_ERRORS Query Option

Maximum number of non-fatal errors for any particular query that are recorded in the Impala log file. For example, if a billion-row table had a non-fatal data error in every row, you could diagnose the problem without all billion errors being logged. Unspecified or 0 indicates the built-in default value of 1000.

This option only controls how many errors are reported. To specify whether Impala continues or halts when it encounters such errors, use the `ABORT_ON_ERROR` option.

Type: numeric

Default: 0 (meaning 1000 errors)

Related information:

[ABORT_ON_ERROR Query Option](#) on page 332, [Using Impala Logging](#) on page 627

MAX_IO_BUFFERS Query Option

Deprecated query option. Currently has no effect.

Type: numeric

Default: 0

MAX_SCAN_RANGE_LENGTH Query Option

Maximum length of the scan range. Interacts with the number of HDFS blocks in the table to determine how many CPU cores across the cluster are involved with the processing for a query. (Each core processes one scan range.)

Lowering the value can sometimes increase parallelism if you have unused CPU capacity, but a too-small value can limit query performance because each scan range involves extra overhead.

Only applicable to HDFS tables. Has no effect on Parquet tables. Unspecified or 0 indicates backend default, which is the same as the HDFS block size for each table.

Although the scan range can be arbitrarily long, Impala internally uses an 8 MB read buffer so that it can query tables with huge block sizes without allocating equivalent blocks of memory.

Type: numeric

In CDH 5.9 / Impala 2.7 and higher, the argument value can include unit specifiers, such as 100m or 100mb. In previous versions, Impala interpreted such formatted values as 0, leading to query failures.

Default: 0

MAX_NUM_RUNTIME_FILTERS Query Option (CDH 5.7 or higher only)

The `MAX_NUM_RUNTIME_FILTERS` query option sets an upper limit on the number of runtime filters that can be produced for each query.

Type: integer

Default: 10

Added in: CDH 5.7.0 (Impala 2.5.0)

Usage notes:

Each runtime filter imposes some memory overhead on the query. Depending on the setting of the `RUNTIME_BLOOM_FILTER_SIZE` query option, each filter might consume between 1 and 16 megabytes per plan fragment. There are typically 5 or fewer filters per plan fragment.

Impala evaluates the effectiveness of each filter, and keeps the ones that eliminate the largest number of partitions or rows. Therefore, this setting can protect against potential problems due to excessive memory overhead for filter production, while still allowing a high level of optimization for suitable queries.

Because the runtime filtering feature applies mainly to resource-intensive and long-running queries, only adjust this query option when tuning long-running queries involving some combination of large partitioned tables and joins involving large tables.

Related information:

[Runtime Filtering for Impala Queries](#) on page 545, [RUNTIME_BLOOM_FILTER_SIZE Query Option \(CDH 5.7 or higher only\)](#) on page 351, [RUNTIME_FILTER_MODE Query Option \(CDH 5.7 or higher only\)](#) on page 353

MEM_LIMIT Query Option

The `MEM_LIMIT` query option defines the maximum amount of memory a query can allocate on each node. The total memory that can be used by a query is the `MEM_LIMIT` times the number of nodes.

There are two levels of memory limit for Impala. The `-mem_limit` startup option sets an overall limit for the `impalad` process (which handles multiple queries concurrently). That limit is typically expressed in terms of a percentage of the RAM available on the host, such as `-mem_limit=70%`. The `MEM_LIMIT` query option, which you set through `impala-shell` or the `SET` statement in a JDBC or ODBC application, applies to each individual query. The `MEM_LIMIT` query option is usually expressed as a fixed size such as `10gb`, and must always be less than the `impalad` memory limit.

If query processing exceeds the specified memory limit on any node, either the per-query limit or the `impalad` limit, Impala cancels the query automatically. Memory limits are checked periodically during query processing, so the actual memory in use might briefly exceed the limit without the query being cancelled.

Type: numeric

Units: A numeric argument represents memory size in bytes; you can also use a suffix of `m` or `mb` for megabytes, or more commonly `g` or `gb` for gigabytes. If you specify a value with unrecognized formats, subsequent queries fail with an error.

Default: 0 (unlimited)

Usage notes:

The `MEM_LIMIT` setting is primarily useful in a high-concurrency setting, or on a cluster with a workload shared between Impala and other data processing components. You can prevent any query from accidentally using much more memory than expected, which could negatively impact other Impala queries.

Use the output of the `SUMMARY` command in `impala-shell` to get a report of memory used for each phase of your most heavyweight queries on each node, and then set a `MEM_LIMIT` somewhat higher than that. See [Using the SUMMARY Report for Performance Tuning](#) on page 557 for usage information about the `SUMMARY` command.

Examples:

The following examples show how to set the `MEM_LIMIT` query option using a fixed number of bytes, or suffixes representing gigabytes or megabytes.

```
[localhost:21000] > set mem_limit=3000000000;
MEM_LIMIT set to 3000000000
[localhost:21000] > select 5;
Query: select 5
+----+
| 5 |
+----+

[localhost:21000] > set mem_limit=3g;
MEM_LIMIT set to 3g
[localhost:21000] > select 5;
Query: select 5
+----+
| 5 |
+----+

[localhost:21000] > set mem_limit=3gb;
MEM_LIMIT set to 3gb
[localhost:21000] > select 5;
+----+
| 5 |
+----+

[localhost:21000] > set mem_limit=3m;
MEM_LIMIT set to 3m
[localhost:21000] > select 5;
+----+
| 5 |
+----+

[localhost:21000] > set mem_limit=3mb;
MEM_LIMIT set to 3mb
[nightly55-2.vpc.cloudera.com:21000] > select 5;
+----+
| 5 |
+----+
```

The following examples show how unrecognized `MEM_LIMIT` values lead to errors for subsequent queries.

```
[localhost:21000] > set mem_limit=3tb;
MEM_LIMIT set to 3tb
[localhost:21000] > select 5;
ERROR: Failed to parse query memory limit from '3tb'.

[localhost:21000] > set mem_limit=xyz;
MEM_LIMIT set to xyz
[localhost:21000] > select 5;
Query: select 5
ERROR: Failed to parse query memory limit from 'xyz'.
```

The following examples shows the automatic query cancellation when the `MEM_LIMIT` value is exceeded on any host involved in the Impala query. First it runs a successful query and checks the largest amount of memory used on any node for any stage of the query. Then it sets an artificially low `MEM_LIMIT` setting so that the same query cannot run.

```
[localhost:21000] > select count(*) from customer;
Query: select count(*) from customer
+-----+
| count(*) |
+-----+
| 150000 |
```

```

+-----+
[localhost:21000] > select count(distinct c_name) from customer;
Query: select count(distinct c_name) from customer
+-----+
| count(distinct c_name) |
+-----+
| 150000                 |
+-----+

[localhost:21000] > summary;
+-----+
| Operator      | #Hosts | Avg Time | Max Time | #Rows | Est. #Rows | Peak Mem | Est. Peak Mem | Detail |
+-----+
| 06:AGGREGATE  | 1      | 230.00ms | 230.00ms | 1     | 1          | 16.00 KB | -1 B          | FINALIZE |
| 05:EXCHANGE   | 1      | 43.44us  | 43.44us  | 1     | 1          | 0 B      | -1 B          | UNPARTITIONED |
| 02:AGGREGATE  | 1      | 227.14ms | 227.14ms | 1     | 1          | 12.00 KB | 10.00 MB     | |
| 04:AGGREGATE  | 1      | 126.27ms | 126.27ms | 150.00K | 150.00K   | 15.17 MB | 10.00 MB     | |
| 03:EXCHANGE   | 1      | 44.07ms  | 44.07ms  | 150.00K | 150.00K   | 0 B      | 0 B          | HASH(c_name) |
| 01:AGGREGATE  | 1      | 361.94ms | 361.94ms | 150.00K | 150.00K   | 23.04 MB | 10.00 MB     | |
| 00:SCAN HDFS  | 1      | 43.64ms  | 43.64ms  | 150.00K | 150.00K   | 24.19 MB | 64.00 MB     | tpch.customer |
+-----+

[localhost:21000] > set mem_limit=15mb;
MEM_LIMIT set to 15mb
[localhost:21000] > select count(distinct c_name) from customer;
Query: select count(distinct c_name) from customer
ERROR:
Memory limit exceeded
Query did not have enough memory to get the minimum required buffers in the block manager.

```

NUM_NODES Query Option

Limit the number of nodes that process a query, typically during debugging.

Type: numeric


Allowed values: Only accepts the values 0 (meaning all nodes) or 1 (meaning all work is done on the coordinator node).

Default: 0

Usage notes:

If you are diagnosing a problem that you suspect is due to a timing issue due to distributed query processing, you can set `NUM_NODES=1` to verify if the problem still occurs when all the work is done on a single node.

You might set the `NUM_NODES` option to 1 briefly, during `INSERT` or `CREATE TABLE AS SELECT` statements. Normally, those statements produce one or more data files per data node. If the write operation involves small amounts of data, a Parquet table, and/or a partitioned table, the default behavior could produce many small files when intuitively you might expect only a single output file. `SET NUM_NODES=1` turns off the “distributed” aspect of the write operation, making it more likely to produce only one or a few data files.

 **Warning:** Because this option results in increased resource utilization on a single host, it could cause problems due to contention with other Impala statements or high resource usage. Symptoms could include queries running slowly, exceeding the memory limit, or appearing to hang. Use it only in a single-user development/test environment; **do not** use it in a production environment or in a cluster with a high-concurrency or high-volume or performance-critical workload.

NUM_SCANNER_THREADS Query Option

Maximum number of scanner threads (on each node) used for each query. By default, Impala uses as many cores as are available (one thread per core). You might lower this value if queries are using excessive resources on a busy cluster. Impala imposes a maximum value automatically, so a high value has no practical effect.

Type: numeric

Default: 0

OPTIMIZE_PARTITION_KEY_SCANS Query Option (CDH 5.7 or higher only)

Enables a fast code path for queries that apply simple aggregate functions to partition key columns: `MIN(key_column)`, `MAX(key_column)`, or `COUNT(DISTINCT key_column)`.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false` (shown as 0 in output of `SET` statement)



Note: In CDH 5.7.0 / Impala 2.5.0, only the value 1 enables the option, and the value `true` is not recognized. This limitation is tracked by the issue [IMPALA-3334](#), which shows the releases where the problem is fixed.

Added in: CDH 5.7.0 (Impala 2.5.0)

Usage notes:

This optimization speeds up common “introspection” operations over partition key columns, for example determining the distinct values of partition keys.

This optimization does not apply to `SELECT` statements that reference columns that are not partition keys. It also only applies when all the partition key columns in the `SELECT` statement are referenced in one of the following contexts:

- Within a `MAX()` or `MIN()` aggregate function or as the argument of any aggregate function with the `DISTINCT` keyword applied.
- Within a `WHERE`, `GROUP BY` or `HAVING` clause.

This optimization is enabled by a query option because it skips some consistency checks and therefore can return slightly different partition values if partitions are in the process of being added, dropped, or loaded outside of Impala. Queries might exhibit different behavior depending on the setting of this option in the following cases:

- If files are removed from a partition using HDFS or other non-Impala operations, there is a period until the next `REFRESH` of the table where regular queries fail at run time because they detect the missing files. With this optimization enabled, queries that evaluate only the partition key column values (not the contents of the partition itself) succeed, and treat the partition as if it still exists.
- If a partition contains any data files, but the data files do not contain any rows, a regular query considers that the partition does not exist. With this optimization enabled, the partition is treated as if it exists.

If the partition includes no files at all, this optimization does not change the query behavior: the partition is considered to not exist whether or not this optimization is enabled.

Examples:

The following example shows initial schema setup and the default behavior of queries that return just the partition key column for a table:

```
-- Make a partitioned table with 3 partitions.
create table t1 (s string) partitioned by (year int);
insert into t1 partition (year=2015) values ('last year');
insert into t1 partition (year=2016) values ('this year');
insert into t1 partition (year=2017) values ('next year');

-- Regardless of the option setting, this query must read the
-- data files to know how many rows to return for each year value.
explain select year from t1;
+-----+
| Explain String |
+-----+
| Estimated Per-Host Requirements: Memory=0B VCores=0 |
| F00:PLAN FRAGMENT [UNPARTITIONED] |
|   00:SCAN HDFS [key_cols.t1] |
|     partitions=3/3 files=4 size=40B |
|     table stats: 3 rows total |
|     column stats: all |
|     hosts=3 per-host-mem=unavailable |
|     tuple-ids=0 row-size=4B cardinality=3 |
+-----+

-- The aggregation operation means the query does not need to read
```

```
-- the data within each partition: the result set contains exactly 1 row
-- per partition, derived from the partition key column value.
-- By default, Impala still includes a 'scan' operation in the query.
explain select distinct year from t1;
```

```
+-----+
| Explain String
+-----+
Estimated Per-Host Requirements: Memory=0B VCores=0

01:AGGREGATE [FINALIZE]
  |
  | group by: year
  |
00:SCAN HDFS [key_cols.t1]
  |
  | partitions=0/0 files=0 size=0B
  |
+-----+
```

The following examples show how the plan is made more efficient when the `OPTIMIZE_PARTITION_KEY_SCANS` option is enabled:

```
set optimize_partition_key_scans=1;
OPTIMIZE_PARTITION_KEY_SCANS set to 1
```

```
-- The aggregation operation is turned into a UNION internally,
-- with constant values known in advance based on the metadata
-- for the partitioned table.
explain select distinct year from t1;
```

```
+-----+
| Explain String
+-----+
Estimated Per-Host Requirements: Memory=0B VCores=0

F00:PLAN FRAGMENT [UNPARTITIONED]
  |
  | 01:AGGREGATE [FINALIZE]
  |   |
  |   | group by: year
  |   | hosts=1 per-host-mem=unavailable
  |   | tuple-ids=1 row-size=4B cardinality=3
  |   |
  |   | 00:UNION
  |   |   |
  |   |   | constant-operands=3
  |   |   | hosts=1 per-host-mem=unavailable
  |   |   | tuple-ids=0 row-size=4B cardinality=3
  |   |
  |
+-----+
```

```
-- The same optimization applies to other aggregation queries
-- that only return values based on partition key columns:
-- MIN, MAX, COUNT(DISTINCT), and so on.
explain select min(year) from t1;
```

```
+-----+
| Explain String
+-----+
Estimated Per-Host Requirements: Memory=0B VCores=0

F00:PLAN FRAGMENT [UNPARTITIONED]
  |
  | 01:AGGREGATE [FINALIZE]
  |   |
  |   | output: min(year)
  |   | hosts=1 per-host-mem=unavailable
  |   | tuple-ids=1 row-size=4B cardinality=1
  |   |
  |   | 00:UNION
  |   |   |
  |   |   | constant-operands=3
  |   |   | hosts=1 per-host-mem=unavailable
  |   |   | tuple-ids=0 row-size=4B cardinality=3
  |   |
  |
+-----+
```

PARQUET_COMPRESSION_CODEC Query Option

Deprecated. Use `COMPRESSION_CODEC` in Impala 2.0 and later. See [COMPRESSION_CODEC Query Option \(CDH 5.2 or higher only\)](#) on page 333 for details.

PARQUET_ANNOTATE_STRINGS_UTF8 Query Option (CDH 5.8 or higher only)

Causes Impala `INSERT` and `CREATE TABLE AS SELECT` statements to write Parquet files that use the UTF-8 annotation for `STRING` columns.

Usage notes:

By default, Impala represents a `STRING` column in Parquet as an unannotated binary field.

Impala always uses the UTF-8 annotation when writing `CHAR` and `VARCHAR` columns to Parquet files. An alternative to using the query option is to cast `STRING` values to `VARCHAR`.

This option is to help make Impala-written data more interoperable with other data processing engines. Impala itself currently does not support all operations on UTF-8 data. Although data processed by Impala is typically represented in ASCII, it is valid to designate the data as UTF-8 when storing on disk, because ASCII is a subset of UTF-8.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false` (shown as 0 in output of `SET` statement)

Added in: CDH 5.8.0 (Impala 2.6.0)

Related information:

[Using the Parquet File Format with Impala Tables](#) on page 584

PARQUET_FALLBACK_SCHEMA_RESOLUTION Query Option (CDH 5.8 or higher only)

The `PARQUET_FALLBACK_SCHEMA_RESOLUTION` query option allows Impala to look up columns within Parquet files by column name, rather than column order, when necessary. The allowed values are:

- `POSITION (0)`
- `NAME (1)`

Usage notes:

By default, Impala looks up columns within a Parquet file based on the order of columns in the table. The name setting for this option enables behavior for Impala queries similar to the Hive setting `parquet.column.index.access=false`. It also allows Impala to query Parquet files created by Hive with the `parquet.column.index.access=false` setting in effect.

Type: integer or string

Added in: CDH 5.8.0 (Impala 2.6.0)

Related information:

[Schema Evolution for Parquet Tables](#) on page 595

PARQUET_FILE_SIZE Query Option

Specifies the maximum size of each Parquet data file produced by Impala `INSERT` statements.

Syntax:

Specify the size in bytes, or with a trailing `m` or `g` character to indicate megabytes or gigabytes. For example:

```
-- 128 megabytes.
set PARQUET_FILE_SIZE=134217728
INSERT OVERWRITE parquet_table SELECT * FROM text_table;

-- 512 megabytes.
set PARQUET_FILE_SIZE=512m;
INSERT OVERWRITE parquet_table SELECT * FROM text_table;

-- 1 gigabyte.
set PARQUET_FILE_SIZE=1g;
INSERT OVERWRITE parquet_table SELECT * FROM text_table;
```

Usage notes:

With tables that are small or finely partitioned, the default Parquet block size (formerly 1 GB, now 256 MB in Impala 2.0 and later) could be much larger than needed for each data file. For `INSERT` operations into such tables, you can increase parallelism by specifying a smaller `PARQUET_FILE_SIZE` value, resulting in more HDFS blocks that can be processed by different nodes.

Type: numeric, with optional unit specifier



Important:

Currently, the maximum value for this setting is 1 gigabyte (1g). Setting a value higher than 1 gigabyte could result in errors during an `INSERT` operation.

Default: 0 (produces files with a target size of 256 MB; files might be larger for very wide tables)

Isilon considerations:

Because the EMC Isilon storage devices use a global value for the block size rather than a configurable value for each file, the `PARQUET_FILE_SIZE` query option has no effect when Impala inserts data into a table or partition residing on Isilon storage. Use the `isi` command to set the default block size globally on the Isilon device. For example, to set the Isilon default block size to 256 MB, the recommended size for Parquet data files for Impala, issue the following command:

```
isi hdfs settings modify --default-block-size=256MB
```

Related information:

For information about the Parquet file format, and how the number and size of data files affects query performance, see [Using the Parquet File Format with Impala Tables](#) on page 584.

PREFETCH_MODE Query Option (CDH 5.8 or higher only)

Determines whether the prefetching optimization is applied during join query processing.

Type: numeric (0, 1) or corresponding mnemonic strings (`NONE`, `HT_BUCKET`).

Default: 1 (equivalent to `HT_BUCKET`)

Added in: CDH 5.8.0 (Impala 2.6.0)

Usage notes:

The default mode is 1, which means that hash table buckets are prefetched during join query processing.

Related information:

[Joins in Impala SELECT Statements](#) on page 306, [Performance Considerations for Join Queries](#) on page 526.

QUERY_TIMEOUT_S Query Option (CDH 5.2 or higher only)

Sets the idle query timeout value for the session, in seconds. Queries that sit idle for longer than the timeout value are automatically cancelled. If the system administrator specified the `--idle_query_timeout` startup option, `QUERY_TIMEOUT_S` must be smaller than or equal to the `--idle_query_timeout` value.



Note:

The timeout clock for queries and sessions only starts ticking when the query or session is idle. For queries, this means the query has results ready but is waiting for a client to fetch the data. A query can run for an arbitrary time without triggering a timeout, because the query is computing results rather than sitting idle waiting for the results to be fetched. The timeout period is intended to prevent unclosed queries from consuming resources and taking up slots in the admission count of running queries, potentially preventing other queries from starting.

For sessions, this means that no query has been submitted for some period of time.

Syntax:

```
SET QUERY_TIMEOUT_S=seconds;
```

Type: numeric**Default:** 0 (no timeout if `--idle_query_timeout` not in effect; otherwise, use `--idle_query_timeout` value)**Added in:** CDH 5.2.0 (Impala 2.0.0)**Related information:**

[Setting Timeout Periods for Daemons, Queries, and Sessions](#) on page 91

REQUEST_POOL Query Option

The pool or queue name that queries should be submitted to. Only applies when you enable the Impala admission control feature. Specifies the name of the pool used by requests from Impala to the resource manager.

Type: STRING**Default:** empty (use the user-to-pool mapping defined by an `impalad` startup option in the Impala configuration file)**Related information:**

[Admission Control and Query Queuing](#) on page 77

REPLICA_PREFERENCE Query Option (CDH 5.9 or higher only)

The `REPLICA_PREFERENCE` query option lets you spread the load more evenly if hotspots and bottlenecks persist, by allowing hosts to do local reads, or even remote reads, to retrieve the data for cached blocks if Impala can determine that it would be too expensive to do all such processing on a particular host.

Type: numeric (0, 2, 4) or corresponding mnemonic strings (`CACHE_LOCAL`, `DISK_LOCAL`, `REMOTE`). The gaps in the numeric sequence are to accommodate other intermediate values that might be added in the future.

Default: 0 (equivalent to `CACHE_LOCAL`)**Added in:** CDH 5.9.0 (Impala 2.7.0)**Related information:**

[Using HDFS Caching with Impala \(CDH 5.1 or higher only\)](#) on page 550, [SCHEDULE_RANDOM_REPLICA Query Option \(CDH 5.7 or higher only\)](#) on page 355

RESERVATION_REQUEST_TIMEOUT Query Option (CDH 5 only)

**Note:**

This query option is no longer supported, because it affects interaction between Impala and Llama. The use of the Llama component for integrated resource management within YARN is no longer supported with CDH 5.5 / Impala 2.3 and higher.

Maximum number of milliseconds Impala will wait for a reservation to be completely granted or denied. Used in conjunction with the Impala resource management feature in Impala 1.2 and higher with CDH 5.

Type: numeric**Default:** 300000 (5 minutes)

RUNTIME_BLOOM_FILTER_SIZE Query Option (CDH 5.7 or higher only)

Size (in bytes) of Bloom filter data structure used by the runtime filtering feature.

**Important:**

In CDH 5.8 / Impala 2.6 and higher, this query option only applies as a fallback, when statistics are not available. By default, Impala estimates the optimal size of the Bloom filter structure regardless of the setting for this option. (This is a change from the original behavior in CDH 5.7 / Impala 2.5.)

In CDH 5.8 / Impala 2.6 and higher, when the value of this query option is used for query planning, it is constrained by the minimum and maximum sizes specified by the `RUNTIME_FILTER_MIN_SIZE` and `RUNTIME_FILTER_MAX_SIZE` query options. The filter size is adjusted upward or downward if necessary to fit within the minimum/maximum range.

Type: integer

Default: 1048576 (1 MB)

Maximum: 16 MB

Added in: CDH 5.7.0 (Impala 2.5.0)

Usage notes:

This setting affects optimizations for large and complex queries, such as dynamic partition pruning for partitioned tables, and join optimization for queries that join large tables. Larger filters are more effective at handling higher cardinality input sets, but consume more memory per filter.

If your query filters on high-cardinality columns (for example, millions of different values) and you do not get the expected speedup from the runtime filtering mechanism, consider doing some benchmarks with a higher value for `RUNTIME_BLOOM_FILTER_SIZE`. The extra memory devoted to the Bloom filter data structures can help make the filtering more accurate.

Because the runtime filtering feature applies mainly to resource-intensive and long-running queries, only adjust this query option when tuning long-running queries involving some combination of large partitioned tables and joins involving large tables.

Because the effectiveness of this setting depends so much on query characteristics and data distribution, you typically only use it for specific queries that need some extra tuning, and the ideal value depends on the query. Consider setting this query option immediately before the expensive query and unsetting it immediately afterward.

Related information:

[Runtime Filtering for Impala Queries](#) on page 545, [RUNTIME_FILTER_MODE Query Option \(CDH 5.7 or higher only\)](#) on page 353, [RUNTIME_FILTER_MIN_SIZE Query Option \(CDH 5.8 or higher only\)](#) on page 353, [RUNTIME_FILTER_MAX_SIZE Query Option \(CDH 5.8 or higher only\)](#) on page 352

`RUNTIME_FILTER_MAX_SIZE` Query Option (CDH 5.8 or higher only)

The `RUNTIME_FILTER_MAX_SIZE` query option adjusts the settings for the runtime filtering feature. This option defines the maximum size for a filter, no matter what the estimates produced by the planner are. This value also overrides any lower number specified for the `RUNTIME_BLOOM_FILTER_SIZE` query option. Filter sizes are rounded up to the nearest power of two.

Type: integer

Default: 0 (meaning use the value from the corresponding `impalad` startup option)

Added in: CDH 5.8.0 (Impala 2.6.0)

Usage notes:

Because the runtime filtering feature applies mainly to resource-intensive and long-running queries, only adjust this query option when tuning long-running queries involving some combination of large partitioned tables and joins involving large tables.

Related information:

[Runtime Filtering for Impala Queries](#) on page 545, [RUNTIME_FILTER_MODE Query Option \(CDH 5.7 or higher only\)](#) on page 353, [RUNTIME_FILTER_MIN_SIZE Query Option \(CDH 5.8 or higher only\)](#) on page 353, [RUNTIME_BLOOM_FILTER_SIZE Query Option \(CDH 5.7 or higher only\)](#) on page 351

RUNTIME_FILTER_MIN_SIZE Query Option (CDH 5.8 or higher only)

The `RUNTIME_FILTER_MIN_SIZE` query option adjusts the settings for the runtime filtering feature. This option defines the minimum size for a filter, no matter what the estimates produced by the planner are. This value also overrides any lower number specified for the `RUNTIME_BLOOM_FILTER_SIZE` query option. Filter sizes are rounded up to the nearest power of two.

Type: integer

Default: 0 (meaning use the value from the corresponding `impalad` startup option)

Added in: CDH 5.8.0 (Impala 2.6.0)

Usage notes:

Because the runtime filtering feature applies mainly to resource-intensive and long-running queries, only adjust this query option when tuning long-running queries involving some combination of large partitioned tables and joins involving large tables.

Related information:

[Runtime Filtering for Impala Queries](#) on page 545, [RUNTIME_FILTER_MODE Query Option \(CDH 5.7 or higher only\)](#) on page 353, [RUNTIME_FILTER_MAX_SIZE Query Option \(CDH 5.8 or higher only\)](#) on page 352, [RUNTIME_BLOOM_FILTER_SIZE Query Option \(CDH 5.7 or higher only\)](#) on page 351

RUNTIME_FILTER_MODE Query Option (CDH 5.7 or higher only)

The `RUNTIME_FILTER_MODE` query option adjusts the settings for the runtime filtering feature. It turns this feature on and off, and controls how extensively the filters are transmitted between hosts.

Type: numeric (0, 1, 2) or corresponding mnemonic strings (`OFF`, `LOCAL`, `GLOBAL`).

Default: 2 (equivalent to `GLOBAL`); formerly was 1 / `LOCAL`, in CDH 5.7 / Impala 2.5

Added in: CDH 5.7.0 (Impala 2.5.0)

Usage notes:

In CDH 5.8 / Impala 2.6 and higher, the default is `GLOBAL`. This setting is recommended for a wide variety of workloads, to provide best performance with “out of the box” settings.

The lowest setting of `LOCAL` does a similar level of optimization (such as partition pruning) as in earlier Impala releases. This setting was the default in CDH 5.7 / Impala 2.5, to allow for a period of post-upgrade testing for existing workloads. This setting is suitable for workloads with non-performance-critical queries, or if the coordinator node is under heavy CPU or memory pressure.

You might change the setting to `OFF` if your workload contains many queries involving partitioned tables or joins that do not experience a performance increase from the runtime filters feature. If the overhead of producing the runtime filters outweighs the performance benefit for queries, you can turn the feature off entirely.

Related information:

[Partitioning for Impala Tables](#) on page 568 for details about runtime filtering. [DISABLE_ROW_RUNTIME_FILTERING Query Option \(CDH 5.7 or higher only\)](#) on page 334, [RUNTIME_BLOOM_FILTER_SIZE Query Option \(CDH 5.7 or higher only\)](#) on page 351, [RUNTIME_FILTER_WAIT_TIME_MS Query Option \(CDH 5.7 or higher only\)](#) on page 353, and [MAX_NUM_RUNTIME_FILTERS Query Option \(CDH 5.7 or higher only\)](#) on page 344 for tuning options for runtime filtering.

RUNTIME_FILTER_WAIT_TIME_MS Query Option (CDH 5.7 or higher only)

The `RUNTIME_FILTER_WAIT_TIME_MS` query option adjusts the settings for the runtime filtering feature. It specifies a time in milliseconds that each scan node waits for runtime filters to be produced by other plan fragments.

Type: integer

Default: 0 (meaning use the value from the corresponding `impalad` startup option)

Added in: CDH 5.7.0 (Impala 2.5.0)

Usage notes:

Because the runtime filtering feature applies mainly to resource-intensive and long-running queries, only adjust this query option when tuning long-running queries involving some combination of large partitioned tables and joins involving large tables.

Related information:

[Runtime Filtering for Impala Queries](#) on page 545, [RUNTIME_FILTER_MODE Query Option \(CDH 5.7 or higher only\)](#) on page 353

[S3_SKIP_INSERT_STAGING Query Option \(CDH 5.8 or higher only\)](#)

Speeds up `INSERT` operations on tables or partitions residing on the Amazon S3 filesystem. The tradeoff is the possibility of inconsistent data left behind if an error occurs partway through the operation.

By default, Impala write operations to S3 tables and partitions involve a two-stage process. Impala writes intermediate files to S3, then (because S3 does not provide a “rename” operation) those intermediate files are copied to their final location, making the process more expensive as on a filesystem that supports renaming or moving files. This query option makes Impala skip the intermediate files, and instead write the new data directly to the final destination.

Usage notes:



Important:

If a host that is participating in the `INSERT` operation fails partway through the query, you might be left with a table or partition that contains some but not all of the expected data files. Therefore, this option is most appropriate for a development or test environment where you have the ability to reconstruct the table if a problem during `INSERT` leaves the data in an inconsistent state.

The timing of file deletion during an `INSERT OVERWRITE` operation makes it impractical to write new files to S3 and delete the old files in a single operation. Therefore, this query option only affects regular `INSERT` statements that add to the existing data in a table, not `INSERT OVERWRITE` statements. Use `TRUNCATE TABLE` if you need to remove all contents from an S3 table before performing a fast `INSERT` with this option enabled.

Performance improvements with this option enabled can be substantial. The speed increase might be more noticeable for non-partitioned tables than for partitioned tables.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `true` (shown as 1 in output of `SET` statement)

Added in: CDH 5.8.0 (Impala 2.6.0)

Related information:

[Using Impala with the Amazon S3 Filesystem](#) on page 617

[SCAN_NODE_CODEGEN_THRESHOLD Query Option \(CDH 5.7 or higher only\)](#)

The `SCAN_NODE_CODEGEN_THRESHOLD` query option adjusts the aggressiveness of the code generation optimization process when performing I/O read operations. It can help to work around performance problems for queries where the table is small and the `WHERE` clause is complicated.

Type: integer

Default: 1800000 (1.8 million)

Added in: CDH 5.7.0 (Impala 2.5.0)

Usage notes:

This query option is intended mainly for the case where a query with a very complicated `WHERE` clause, such as an `IN` operator with thousands of entries, is run against a small table, especially a small table using Parquet format. The code generation phase can become the dominant factor in the query response time, making the query take several seconds even though there is relatively little work to do. In this case, increase the value of this option to a much larger amount, anything up to the maximum for a 32-bit integer.

Because this option only affects the code generation phase for the portion of the query that performs I/O (the *scan nodes* within the query plan), it lets you continue to keep code generation enabled for other queries, and other parts of the same query, that can benefit from it. In contrast, the `IMPALA_DISABLE_CODEGEN` query option turns off code generation entirely.

Because of the way the work for queries is divided internally, this option might not affect code generation for all kinds of queries. If a plan fragment contains a scan node and some other kind of plan node, code generation still occurs regardless of this option setting.

To use this option effectively, you should be familiar with reading query profile output to determine the proportion of time spent in the code generation phase, and whether code generation is enabled or not for specific plan fragments.

`SCHEDULE_RANDOM_REPLICA` Query Option (CDH 5.7 or higher only)

The `SCHEDULE_RANDOM_REPLICA` query option fine-tunes the algorithm for deciding which host processes each HDFS data block. It only applies to tables and partitions that are not enabled for the HDFS caching feature.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false`

Added in: CDH 5.7.0 (Impala 2.5.0)

Usage notes:

In the presence of HDFS cached replicas, Impala randomizes which host processes each cached data block. To ensure that HDFS data blocks are cached on more than one host, use the `WITH REPLICATION` clause along with the `CACHED IN` clause in a `CREATE TABLE` or `ALTER TABLE` statement. Specify a replication value greater than or equal to the HDFS block replication factor.

The `SCHEDULE_RANDOM_REPLICA` query option applies to tables and partitions that *do not* use HDFS caching. By default, Impala estimates how much work each host has done for the query, and selects the host that has the lowest workload. This algorithm is intended to reduce CPU hotspots arising when the same host is selected to process multiple data blocks, but hotspots might still arise for some combinations of queries and data layout. When the `SCHEDULE_RANDOM_REPLICA` option is enabled, Impala further randomizes the scheduling algorithm for non-HDFS cached blocks, which can further reduce the chance of CPU hotspots.

This query option works in conjunction with the work scheduling improvements in CDH 5.7 / Impala 2.5 and higher. The scheduling improvements distribute the processing for cached HDFS data blocks to minimize hotspots: if a data block is cached on more than one host, Impala chooses which host to process each block based on which host has read the fewest bytes during the current query. Enable `SCHEDULE_RANDOM_REPLICA` setting if CPU hotspots still persist because of cases where hosts are “tied” in terms of the amount of work done; by default, Impala picks the first eligible host in this case.

Related information:

[Using HDFS Caching with Impala \(CDH 5.1 or higher only\)](#) on page 550, [Avoiding CPU Hotspots for HDFS Cached Data](#) on page 567, [REPLICA_PREFERENCE Query Option \(CDH 5.9 or higher only\)](#) on page 351

`SUPPORT_START_OVER` Query Option

Leave this setting at its default value. It is a read-only setting, tested by some client applications such as Hue.

If you accidentally change it through `impala-shell`, subsequent queries encounter errors until you undo the change by issuing `UNSET support_start_over`.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false`

SYNC_DDL Query Option

When enabled, causes any DDL operation such as `CREATE TABLE` or `ALTER TABLE` to return only when the changes have been propagated to all other Impala nodes in the cluster by the Impala catalog service. That way, if you issue a subsequent `CONNECT` statement in `impala-shell` to connect to a different node in the cluster, you can be sure that other node will already recognize any added or changed tables. (The catalog service automatically broadcasts the DDL changes to all nodes automatically, but without this option there could be a period of inconsistency if you quickly switched to another node, such as by issuing a subsequent query through a load-balancing proxy.)

Although `INSERT` is classified as a DML statement, when the `SYNC_DDL` option is enabled, `INSERT` statements also delay their completion until all the underlying data and metadata changes are propagated to all Impala nodes. Internally, Impala inserts have similarities with DDL statements in traditional database systems, because they create metadata needed to track HDFS block locations for new files and they potentially add new partitions to partitioned tables.



Note: Because this option can introduce a delay after each write operation, if you are running a sequence of `CREATE DATABASE`, `CREATE TABLE`, `ALTER TABLE`, `INSERT`, and similar statements within a setup script, to minimize the overall delay you can enable the `SYNC_DDL` query option only near the end, before the final DDL statement.

Type: Boolean; recognized values are 1 and 0, or `true` and `false`; any other value interpreted as `false`

Default: `false` (shown as 0 in output of `SET` statement)

Related information:

[DDL Statements](#) on page 228

V_CPU_CORES Query Option (CDH 5 only)



Note: This query option is no longer supported, because it affects interaction between Impala and Llama. The use of the Llama component for integrated resource management within YARN is no longer supported with CDH 5.5 / Impala 2.3 and higher.

The number of per-host virtual CPU cores to request from YARN. If set, the query option overrides the automatic estimate from Impala. Used in conjunction with the Impala resource management feature in Impala 1.2 and higher and CDH 5.

Type: numeric

Default: 0 (use automatic estimates)

SHOW Statement

The `SHOW` statement is a flexible way to get information about different types of Impala objects.

Syntax:

```
SHOW DATABASES [[LIKE] 'pattern']
SHOW SCHEMAS [[LIKE] 'pattern'] - an alias for SHOW DATABASES
SHOW TABLES [IN database_name] [[LIKE] 'pattern']
SHOW [AGGREGATE | ANALYTIC] FUNCTIONS [IN database_name] [[LIKE] 'pattern']
SHOW CREATE TABLE [database_name].table_name
SHOW CREATE VIEW [database_name].view_name
SHOW TABLE STATS [database_name.]table_name
SHOW COLUMN STATS [database_name.]table_name
SHOW PARTITIONS [database_name.]table_name
SHOW FILES IN [database_name.]table_name [PARTITION (key_col=value [, key_col=value])]

SHOW ROLES
SHOW CURRENT ROLES
```

```
SHOW ROLE GRANT GROUP group_name
SHOW GRANT ROLE role_name
```

Issue a `SHOW object_type` statement to see the appropriate objects in the current database, or `SHOW object_type IN database_name` to see objects in a specific database.

The optional *pattern* argument is a quoted string literal, using Unix-style * wildcards and allowing | for alternation. The preceding `LIKE` keyword is also optional. All object names are stored in lowercase, so use all lowercase letters in the pattern string. For example:

```
show databases 'a*';
show databases like 'a*';
show tables in some_db like '*fact*';
use some_db;
show tables '*dim*|*fact*';
```

Cancellation: Cannot be cancelled.

SHOW FILES Statement

The `SHOW FILES` statement displays the files that constitute a specified table, or a partition within a partitioned table. This syntax is available in CDH 5.4 and higher only. The output includes the names of the files, the size of each file, and the applicable partition for a partitioned table. The size includes a suffix of `B` for bytes, `MB` for megabytes, and `GB` for gigabytes.



Note: This statement applies to tables and partitions stored on HDFS, or in the Amazon Simple Storage System (S3). It does not apply to views. It does not apply to tables mapped onto HBase, because HBase does not use the same file-based storage layout.

Usage notes:

You can use this statement to verify the results of your ETL process: that is, that the expected files are present, with the expected sizes. You can examine the file information to detect conditions such as empty files, missing files, or inefficient layouts due to a large number of small files. When you use `INSERT` statements to copy from one table to another, you can see how the file layout changes due to file format conversions, compaction of small input files into large data blocks, and multiple output files from parallel queries and partitioned inserts.

The output from this statement does not include files that Impala considers to be hidden or invisible, such as those whose names start with a dot or an underscore, or that end with the suffixes `.copying` or `.tmp`.

The information for partitioned tables complements the output of the `SHOW PARTITIONS` statement, which summarizes information about each partition. `SHOW PARTITIONS` produces some output for each partition, while `SHOW FILES` does not produce any output for empty partitions because they do not include any data files.

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have read permission for all the table files, read and execute permission for all the directories that make up the table, and execute permission for the database directory and all its parent directories.

Examples:

The following example shows a `SHOW FILES` statement for an unpartitioned table using text format:

```
[localhost:21000] > create table unpart_text (x bigint, s string);
[localhost:21000] > insert into unpart_text (x, s) select id, name
> from oreilly.sample_data limit 20e6;
[localhost:21000] > show files in unpart_text;
+-----+-----+-----+
| path                                     | size      | partition |
+-----+-----+-----+
| hdfs://impala_data_dir/d.db/unpart_text/35665776ef85cfaf_1012432410_data.0. | 448.31MB |           |
+-----+-----+-----+
[localhost:21000] > insert into unpart_text (x, s) select id, name from oreilly.sample_data limit 100e6;
[localhost:21000] > show files in unpart_text;
+-----+-----+-----+
| path                                     | size      | partition |
+-----+-----+-----+
```

```
hdfs://impala_data_dir/d.db/unpart_text/35665776ef85cfaf_1012432410_data.0. | 448.31MB |
hdfs://impala_data_dir/d.db/unpart_text/ac3dba252a8952b8_1663177415_data.0. | 2.19GB |
```

This example illustrates how, after issuing some `INSERT . . . VALUES` statements, the table now contains some tiny files of just a few bytes. Such small files could cause inefficient processing of parallel queries that are expecting multi-megabyte input files. The example shows how you might compact the small files by doing an `INSERT . . . SELECT` into a different table, possibly converting the data to Parquet in the process:

```
[localhost:21000] > insert into unpart_text values (10,'hello'), (20, 'world');
[localhost:21000] > insert into unpart_text values (-1,'foo'), (-1000, 'bar');
[localhost:21000] > show files in unpart_text;
```

path	size
hdfs://impala_data_dir/d.db/unpart_text/4f11b8bdf8b6aa92_238145083_data.0.	18B
hdfs://impala_data_dir/d.db/unpart_text/35665776ef85cfaf_1012432410_data.0.	448.31MB
hdfs://impala_data_dir/d.db/unpart_text/ac3dba252a8952b8_1663177415_data.0.	2.19GB
hdfs://impala_data_dir/d.db/unpart_text/cfb8252452445682_1868457216_data.0.	17B

```
[localhost:21000] > create table unpart_parq stored as parquet as select * from unpart_text;
```

```
[localhost:21000] > show files in unpart_parq;
```

path	size
hdfs://impala_data_dir/d.db/unpart_parq/60798d96ba630184_549959007_data.0.parq	255.36MB
hdfs://impala_data_dir/d.db/unpart_parq/60798d96ba630184_549959007_data.1.parq	178.52MB
hdfs://impala_data_dir/d.db/unpart_parq/60798d96ba630185_549959007_data.0.parq	255.37MB
hdfs://impala_data_dir/d.db/unpart_parq/60798d96ba630185_549959007_data.1.parq	57.71MB
hdfs://impala_data_dir/d.db/unpart_parq/60798d96ba630186_2141167244_data.0.parq	255.40MB
hdfs://impala_data_dir/d.db/unpart_parq/60798d96ba630186_2141167244_data.1.parq	175.52MB
hdfs://impala_data_dir/d.db/unpart_parq/60798d96ba630187_1006832086_data.0.parq	255.40MB
hdfs://impala_data_dir/d.db/unpart_parq/60798d96ba630187_1006832086_data.1.parq	214.61MB

The following example shows a `SHOW FILES` statement for a partitioned text table with data in two different partitions, and two empty partitions. The partitions with no data are not represented in the `SHOW FILES` output.

```
[localhost:21000] > create table part_text (x bigint, y int, s string)
> partitioned by (year bigint, month bigint, day bigint);
[localhost:21000] > insert overwrite part_text (x, y, s) partition (year=2014,month=1,day=1)
> select id, val, name from orelly.normalized_parquet
where id between 1 and 1000000;
[localhost:21000] > insert overwrite part_text (x, y, s) partition (year=2014,month=1,day=2)
> select id, val, name from orelly.normalized_parquet
> where id between 1000001 and 2000000;
[localhost:21000] > alter table part_text add partition (year=2014,month=1,day=3);
[localhost:21000] > alter table part_text add partition (year=2014,month=1,day=4);
[localhost:21000] > show partitions part_text;
```

year	month	day	#Rows	#Files	Size	Bytes Cached	Cache Replication	Format	Incremental stats
2014	1	1	-1	4	25.16MB	NOT CACHED	NOT CACHED	TEXT	false
2014	1	2	-1	4	26.22MB	NOT CACHED	NOT CACHED	TEXT	false
2014	1	3	-1	0	0B	NOT CACHED	NOT CACHED	TEXT	false
2014	1	4	-1	0	0B	NOT CACHED	NOT CACHED	TEXT	false
Total			-1	8	51.38MB	0B			

```
[localhost:21000] > show files in part_text;
```

path	size	partition
hdfs://impala_data_dir/d.db/part_text/year=2014/month=1/day=1/80732d9dc80689f_1418645991_data.0.	5.77MB	year=2014/month=1/day=1
hdfs://impala_data_dir/d.db/part_text/year=2014/month=1/day=1/80732d9dc8068a0_1418645991_data.0.	6.25MB	year=2014/month=1/day=1
hdfs://impala_data_dir/d.db/part_text/year=2014/month=1/day=1/80732d9dc8068a1_147082319_data.0.	7.16MB	year=2014/month=1/day=1
hdfs://impala_data_dir/d.db/part_text/year=2014/month=1/day=1/80732d9dc8068a2_2111411753_data.0.	5.98MB	year=2014/month=1/day=1
hdfs://impala_data_dir/d.db/part_text/year=2014/month=1/day=2/21a828cf494b5bbb_501271652_data.0.	6.42MB	year=2014/month=1/day=2
hdfs://impala_data_dir/d.db/part_text/year=2014/month=1/day=2/21a828cf494b5bbb_501271652_data.0.	6.62MB	year=2014/month=1/day=2
hdfs://impala_data_dir/d.db/part_text/year=2014/month=1/day=2/21a828cf494b5bbd_1393490200_data.0.	6.98MB	year=2014/month=1/day=2
hdfs://impala_data_dir/d.db/part_text/year=2014/month=1/day=2/21a828cf494b5bbe_1393490200_data.0.	6.20MB	year=2014/month=1/day=2

The following example shows a `SHOW FILES` statement for a partitioned Parquet table. The number and sizes of files are different from the equivalent partitioned text table used in the previous example, because `INSERT` operations for Parquet tables are parallelized differently than for text tables. (Also, the amount of data is so small that it can be written to Parquet without involving all the hosts in this 4-node cluster.)

```
[localhost:21000] > create table part_parq (x bigint, y int, s string)
> partitioned by (year bigint, month bigint, day bigint) stored as parquet;
```

```
[localhost:21000] > insert into part_parq partition (year,month,day) select x, y, s, year, month, day from partitioned_text;
[localhost:21000] > show partitions part_parq;
```

year	month	day	#Rows	#Files	Size	Bytes Cached	Cache Replication	Format	Incremental stats
2014	1	1	-1	3	17.89MB	NOT CACHED	NOT CACHED	PARQUET	false
2014	1	2	-1	3	17.89MB	NOT CACHED	NOT CACHED	PARQUET	false
Total			-1	6	35.79MB	0B			

```
[localhost:21000] > show files in part_parq;
```

path	size	partition
hdfs://impala_data_dir/d.db/part_parq/year=2014/month=1/day=1/1134113650_data.0.parq	4.49MB	year=2014/month=1/day=1
hdfs://impala_data_dir/d.db/part_parq/year=2014/month=1/day=1/617567880_data.0.parq	5.14MB	year=2014/month=1/day=1
hdfs://impala_data_dir/d.db/part_parq/year=2014/month=1/day=1/2099499416_data.0.parq	8.27MB	year=2014/month=1/day=1
hdfs://impala_data_dir/d.db/part_parq/year=2014/month=1/day=2/945567189_data.0.parq	8.80MB	year=2014/month=1/day=2
hdfs://impala_data_dir/d.db/part_parq/year=2014/month=1/day=2/2145850112_data.0.parq	4.80MB	year=2014/month=1/day=2
hdfs://impala_data_dir/d.db/part_parq/year=2014/month=1/day=2/665613448_data.0.parq	4.29MB	year=2014/month=1/day=2

The following example shows output from the `SHOW FILES` statement for a table where the data files are stored in Amazon S3:

```
[localhost:21000] > show files in s3_testing.sample_data_s3;
```

path	size
s3a://impala-demo/sample_data/e065453cba1988a6_1733868553_data.0.parq	24.84MB

SHOW ROLES Statement

The `SHOW ROLES` statement displays roles. This syntax is available in CDH 5.2 and later only, when you are using the Sentry authorization framework along with the Sentry service, as described in [Using Impala with the Sentry Service \(CDH 5.1 or higher only\)](#) on page 107. It does not apply when you use the Sentry framework with privileges defined in a policy file.

Security considerations:

When authorization is enabled, the output of the `SHOW` statement is limited to those objects for which you have some privilege. There might be other database, tables, and so on, but their names are concealed. If you believe an object exists but you cannot see it in the `SHOW` output, check with the system administrator if you need to be granted a new privilege for that object. See [Enabling Sentry Authorization for Impala](#) on page 105 for how to set up authorization and add privileges for specific kinds of objects.

Examples:

Depending on the roles set up within your organization by the `CREATE ROLE` statement, the output might look something like this:

```
show roles;
```

role_name
analyst
role1
sales
superuser
test_role

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Related information:

[Enabling Sentry Authorization for Impala](#) on page 105

SHOW CURRENT ROLE

The `SHOW CURRENT ROLE` statement displays roles assigned to the current user. This syntax is available in CDH 5.2 and later only, when you are using the Sentry authorization framework along with the Sentry service, as described in

[Using Impala with the Sentry Service \(CDH 5.1 or higher only\)](#) on page 107. It does not apply when you use the Sentry framework with privileges defined in a policy file.

Security considerations:

When authorization is enabled, the output of the `SHOW` statement is limited to those objects for which you have some privilege. There might be other database, tables, and so on, but their names are concealed. If you believe an object exists but you cannot see it in the `SHOW` output, check with the system administrator if you need to be granted a new privilege for that object. See [Enabling Sentry Authorization for Impala](#) on page 105 for how to set up authorization and add privileges for specific kinds of objects.

Examples:

Depending on the roles set up within your organization by the `CREATE ROLE` statement, the output might look something like this:

```
show current roles;
+-----+
| role_name |
+-----+
| role1     |
| superuser |
+-----+
```

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Related information:

[Enabling Sentry Authorization for Impala](#) on page 105

SHOW ROLE GRANT Statement

The `SHOW ROLE GRANT` statement lists all the roles assigned to the specified group. This statement is only allowed for Sentry administrative users and others users that are part of the specified group. This syntax is available in CDH 5.2 and later only, when you are using the Sentry authorization framework along with the Sentry service, as described in [Using Impala with the Sentry Service \(CDH 5.1 or higher only\)](#) on page 107. It does not apply when you use the Sentry framework with privileges defined in a policy file.

Security considerations:

When authorization is enabled, the output of the `SHOW` statement is limited to those objects for which you have some privilege. There might be other database, tables, and so on, but their names are concealed. If you believe an object exists but you cannot see it in the `SHOW` output, check with the system administrator if you need to be granted a new privilege for that object. See [Enabling Sentry Authorization for Impala](#) on page 105 for how to set up authorization and add privileges for specific kinds of objects.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Related information:

[Enabling Sentry Authorization for Impala](#) on page 105

SHOW GRANT ROLE Statement

The `SHOW GRANT ROLE` statement list all the grants for the given role name. This statement is only allowed for Sentry administrative users and other users that have been granted the specified role. This syntax is available in CDH 5.2 and later only, when you are using the Sentry authorization framework along with the Sentry service, as described in [Using Impala with the Sentry Service \(CDH 5.1 or higher only\)](#) on page 107. It does not apply when you use the Sentry framework with privileges defined in a policy file.

Security considerations:

When authorization is enabled, the output of the `SHOW` statement is limited to those objects for which you have some privilege. There might be other database, tables, and so on, but their names are concealed. If you believe an object

exists but you cannot see it in the `SHOW` output, check with the system administrator if you need to be granted a new privilege for that object. See [Enabling Sentry Authorization for Impala](#) on page 105 for how to set up authorization and add privileges for specific kinds of objects.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Related information:

[Enabling Sentry Authorization for Impala](#) on page 105

SHOW DATABASES

The `SHOW DATABASES` statement is often the first one you issue when connecting to an instance for the first time. You typically issue `SHOW DATABASES` to see the names you can specify in a `USE db_name` statement, then after switching to a database you issue `SHOW TABLES` to see the names you can specify in `SELECT` and `INSERT` statements.

In CDH 5.7 / Impala 2.5 and higher, the output includes a second column showing any associated comment for each database.

The output of `SHOW DATABASES` includes the special `_impala_builtins` database, which lets you view definitions of built-in functions, as described under `SHOW FUNCTIONS`.

Security considerations:

When authorization is enabled, the output of the `SHOW` statement is limited to those objects for which you have some privilege. There might be other database, tables, and so on, but their names are concealed. If you believe an object exists but you cannot see it in the `SHOW` output, check with the system administrator if you need to be granted a new privilege for that object. See [Enabling Sentry Authorization for Impala](#) on page 105 for how to set up authorization and add privileges for specific kinds of objects.

Examples:

This example shows how you might locate a particular table on an unfamiliar system. The `DEFAULT` database is the one you initially connect to; a database with that name is present on every system. You can issue `SHOW TABLES IN db_name` without going into a database, or `SHOW TABLES` once you are inside a particular database.

```
[localhost:21000] > show databases;
+-----+-----+
| name          | comment                                     |
+-----+-----+
| _impala_builtins | System database for Impala builtin functions |
| default        | Default Hive database                       |
| file_formats   |                                             |
+-----+-----+
Returned 3 row(s) in 0.02s
[localhost:21000] > show tables in file_formats;
+-----+-----+
| name          |
+-----+-----+
| parquet_table |
| rcfile_table  |
| sequencefile_table |
| textfile_table |
+-----+-----+
Returned 4 row(s) in 0.01s
[localhost:21000] > use file_formats;
[localhost:21000] > show tables like '*parq*';
+-----+-----+
| name          |
+-----+-----+
| parquet_table |
+-----+-----+
Returned 1 row(s) in 0.01s
```

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Related information:

[Overview of Impala Databases](#) on page 219, [CREATE DATABASE Statement](#) on page 246, [DROP DATABASE Statement](#) on page 273, [USE Statement](#) on page 372, [SHOW TABLES Statement](#) on page 362, [SHOW FUNCTIONS Statement](#) on page 369

SHOW TABLES Statement

Displays the names of tables. By default, lists tables in the current database, or with the `IN` clause, in a specified database. By default, lists all tables, or with the `LIKE` clause, only those whose name match a pattern with `*` wildcards.

Security considerations:

When authorization is enabled, the output of the `SHOW` statement is limited to those objects for which you have some privilege. There might be other database, tables, and so on, but their names are concealed. If you believe an object exists but you cannot see it in the `SHOW` output, check with the system administrator if you need to be granted a new privilege for that object. See [Enabling Sentry Authorization for Impala](#) on page 105 for how to set up authorization and add privileges for specific kinds of objects.

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have read and execute permissions for all directories that are part of the table. (A table could span multiple different HDFS directories if it is partitioned. The directories could be widely scattered because a partition can reside in an arbitrary HDFS directory based on its `LOCATION` attribute.)

Examples:

The following examples demonstrate the `SHOW TABLES` statement. If the database contains no tables, the result set is empty. If the database does contain tables, `SHOW TABLES IN db_name` lists all the table names. `SHOW TABLES` with no qualifiers lists all the table names in the current database.

```
create database empty_db;
show tables in empty_db;
Fetched 0 row(s) in 0.11s

create database full_db;
create table full_db.t1 (x int);
create table full_db.t2 like full_db.t1;

show tables in full_db;
+-----+
| name |
+-----+
| t1   |
| t2   |
+-----+

use full_db;
show tables;
+-----+
| name |
+-----+
| t1   |
| t2   |
+-----+
```

This example demonstrates how `SHOW TABLES LIKE 'wildcard_pattern'` lists table names that match a pattern, or multiple alternative patterns. The ability to do wildcard matches for table names makes it helpful to establish naming conventions for tables to conveniently locate a group of related tables.

```
create table fact_tbl (x int);
create table dim_tbl_1 (s string);
create table dim_tbl_2 (s string);

/* Asterisk is the wildcard character. Only 2 out of the 3 just-created tables are
returned. */
show tables like 'dim*';
+-----+
| name |
+-----+
```

```

| dim_tbl_1 |
| dim_tbl_2 |
+-----+

/* We are already in the FULL_DB database, but just to be sure we can specify the database
   name also. */
show tables in full_db like 'dim*';
+-----+
| name      |
+-----+
| dim_tbl_1 |
| dim_tbl_2 |
+-----+

/* The pipe character separates multiple wildcard patterns. */
show tables like '*dim*|t*';
+-----+
| name      |
+-----+
| dim_tbl_1 |
| dim_tbl_2 |
| t1        |
| t2        |
+-----+

```

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Related information:

[Overview of Impala Tables](#) on page 222, [CREATE TABLE Statement](#) on page 254, [ALTER TABLE Statement](#) on page 230, [DROP TABLE Statement](#) on page 280, [DESCRIBE Statement](#) on page 264, [SHOW CREATE TABLE Statement](#) on page 363, [SHOW TABLE STATS Statement](#) on page 365, [SHOW DATABASES](#) on page 361, [SHOW FUNCTIONS Statement](#) on page 369

SHOW CREATE TABLE Statement

As a schema changes over time, you might run a `CREATE TABLE` statement followed by several `ALTER TABLE` statements. To capture the cumulative effect of all those statements, `SHOW CREATE TABLE` displays a `CREATE TABLE` statement that would reproduce the current structure of a table. You can use this output in scripts that set up or clone a group of tables, rather than trying to reproduce the original sequence of `CREATE TABLE` and `ALTER TABLE` statements. When creating variations on the original table, or cloning the original table on a different system, you might need to edit the `SHOW CREATE TABLE` output to change things such as the database name, `LOCATION` field, and so on that might be different on the destination system.

If you specify a view name in the `SHOW CREATE TABLE`, it returns a `CREATE VIEW` statement with column names and the original SQL statement to reproduce the view. You need the `VIEW_METADATA` privilege on the view and `SELECT` privilege on all underlying views and tables to successfully run the `SHOW CREATE VIEW` statement for a view. The `SHOW CREATE VIEW` is available as an alias for `SHOW CREATE TABLE`.

Security considerations:

When authorization is enabled, the output of the `SHOW` statement is limited to those objects for which you have some privilege. There might be other database, tables, and so on, but their names are concealed. If you believe an object exists but you cannot see it in the `SHOW` output, check with the system administrator if you need to be granted a new privilege for that object. See [Enabling Sentry Authorization for Impala](#) on page 105 for how to set up authorization and add privileges for specific kinds of objects.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Examples:

The following example shows how various clauses from the `CREATE TABLE` statement are represented in the output of `SHOW CREATE TABLE`.

```
create table show_create_table_demo (id int comment "Unique ID", y double, s string)
  partitioned by (year smallint)
  stored as parquet;

show create table show_create_table_demo;
+-----+
| result
+-----+
| CREATE TABLE scratch.show_create_table_demo (
|   id INT COMMENT 'Unique ID',
|   y DOUBLE,
|   s STRING
| )
| PARTITIONED BY (
|   year SMALLINT
| )
| STORED AS PARQUET
| LOCATION 'hdfs://127.0.0.1:8020/user/hive/warehouse/scratch.db/show_create_table_demo'
| TBLPROPERTIES ('transient_lastDdlTime'='1418152582')
+-----+
```

The following example shows how, after a sequence of `ALTER TABLE` statements, the output from `SHOW CREATE TABLE` represents the current state of the table. This output could be used to create a matching table rather than executing the original `CREATE TABLE` and sequence of `ALTER TABLE` statements.

```
alter table show_create_table_demo drop column s;
alter table show_create_table_demo set fileformat textfile;

show create table show_create_table_demo;
+-----+
| result
+-----+
| CREATE TABLE scratch.show_create_table_demo (
|   id INT COMMENT 'Unique ID',
|   y DOUBLE
| )
| PARTITIONED BY (
|   year SMALLINT
| )
| STORED AS TEXTFILE
| LOCATION 'hdfs://127.0.0.1:8020/user/hive/warehouse/demo.db/show_create_table_demo'
| TBLPROPERTIES ('transient_lastDdlTime'='1418152638')
+-----+
```

Related information:

[CREATE TABLE Statement](#) on page 254, [DESCRIBE Statement](#) on page 264, [SHOW TABLES Statement](#) on page 362

SHOW CREATE VIEW Statement

The `SHOW CREATE VIEW`, it returns a `CREATE VIEW` statement with column names and the original SQL statement to reproduce the view. You need the `VIEW_METADATA` privilege on the view and `SELECT` privilege on all underlying views and tables to successfully run the `SHOW CREATE VIEW` statement for a view.

The `SHOW CREATE VIEW` is an alias for `SHOW CREATE TABLE`.

SHOW TABLE STATS Statement

The `SHOW TABLE STATS` and `SHOW COLUMN STATS` variants are important for tuning performance and diagnosing performance issues, especially with the largest tables and the most complex join queries.

Any values that are not available (because the `COMPUTE STATS` statement has not been run yet) are displayed as `-1`.

`SHOW TABLE STATS` provides some general information about the table, such as the number of files, overall size of the data, whether some or all of the data is in the HDFS cache, and the file format, that is useful whether or not you have run the `COMPUTE STATS` statement. A `-1` in the `#Rows` output column indicates that the `COMPUTE STATS` statement has never been run for this table. If the table is partitioned, `SHOW TABLE STATS` provides this information for each partition. (It produces the same output as the `SHOW PARTITIONS` statement in this case.)

The output of `SHOW COLUMN STATS` is primarily only useful after the `COMPUTE STATS` statement has been run on the table. A `-1` in the `#Distinct Values` output column indicates that the `COMPUTE STATS` statement has never been run for this table. Currently, Impala always leaves the `#Nulls` column as `-1`, even after `COMPUTE STATS` has been run.

These `SHOW` statements work on actual tables only, not on views.

Security considerations:

When authorization is enabled, the output of the `SHOW` statement is limited to those objects for which you have some privilege. There might be other database, tables, and so on, but their names are concealed. If you believe an object exists but you cannot see it in the `SHOW` output, check with the system administrator if you need to be granted a new privilege for that object. See [Enabling Sentry Authorization for Impala](#) on page 105 for how to set up authorization and add privileges for specific kinds of objects.

Examples:

The following examples show how the `SHOW TABLE STATS` statement displays physical information about a table and the associated data files:

```
show table stats store_sales;
+-----+-----+-----+-----+-----+-----+
| #Rows | #Files | Size      | Bytes Cached | Format | Incremental stats |
+-----+-----+-----+-----+-----+-----+
| -1    | 1      | 370.45MB | NOT CACHED  | TEXT  | false             |
+-----+-----+-----+-----+-----+-----+

show table stats customer;
+-----+-----+-----+-----+-----+-----+
| #Rows | #Files | Size      | Bytes Cached | Format | Incremental stats |
+-----+-----+-----+-----+-----+-----+
| -1    | 1      | 12.60MB  | NOT CACHED  | TEXT  | false             |
+-----+-----+-----+-----+-----+-----+
```

The following example shows how, after a `COMPUTE STATS` or `COMPUTE INCREMENTAL STATS` statement, the `#Rows` field is now filled in. Because the `STORE_SALES` table in this example is not partitioned, the `COMPUTE INCREMENTAL`

STATS statement produces regular stats rather than incremental stats, therefore the `Incremental stats` field remains false.

```

compute stats customer;
+-----+
| summary |
+-----+
| Updated 1 partition(s) and 18 column(s). |
+-----+

show table stats customer;
+-----+-----+-----+-----+-----+-----+
| #Rows | #Files | Size | Bytes Cached | Format | Incremental stats |
+-----+-----+-----+-----+-----+-----+
| 100000 | 1 | 12.60MB | NOT CACHED | TEXT | false |
+-----+-----+-----+-----+-----+-----+

compute incremental stats store_sales;
+-----+
| summary |
+-----+
| Updated 1 partition(s) and 23 column(s). |
+-----+

show table stats store_sales;
+-----+-----+-----+-----+-----+-----+
| #Rows | #Files | Size | Bytes Cached | Format | Incremental stats |
+-----+-----+-----+-----+-----+-----+
| 2880404 | 1 | 370.45MB | NOT CACHED | TEXT | false |
+-----+-----+-----+-----+-----+-----+

```

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have read and execute permissions for all directories that are part of the table. (A table could span multiple different HDFS directories if it is partitioned. The directories could be widely scattered because a partition can reside in an arbitrary HDFS directory based on its `LOCATION` attribute.) The Impala user must also have execute permission for the database directory, and any parent directories of the database directory in HDFS.

Related information:

[COMPUTE STATS Statement](#) on page 241, [SHOW COLUMN STATS Statement](#) on page 366

See [Table and Column Statistics](#) on page 533 for usage information and examples.

SHOW COLUMN STATS Statement

The `SHOW TABLE STATS` and `SHOW COLUMN STATS` variants are important for tuning performance and diagnosing performance issues, especially with the largest tables and the most complex join queries.

Security considerations:

When authorization is enabled, the output of the `SHOW` statement is limited to those objects for which you have some privilege. There might be other database, tables, and so on, but their names are concealed. If you believe an object exists but you cannot see it in the `SHOW` output, check with the system administrator if you need to be granted a new privilege for that object. See [Enabling Sentry Authorization for Impala](#) on page 105 for how to set up authorization and add privileges for specific kinds of objects.

Examples:

The following examples show the output of the `SHOW COLUMN STATS` statement for some tables, before the `COMPUTE STATS` statement is run. Impala deduces some information, such as maximum and average size for fixed-length columns, and leaves and unknown values as `-1`.

```

show column stats customer;
+-----+-----+-----+-----+-----+-----+
| Column | Type | #Distinct Values | #Nulls | Max Size | Avg Size |
+-----+-----+-----+-----+-----+-----+

```

c_customer_sk	INT	-1	-1	4	4
c_customer_id	STRING	-1	-1	-1	-1
c_current_cdemo_sk	INT	-1	-1	4	4
c_current_hdemo_sk	INT	-1	-1	4	4
c_current_addr_sk	INT	-1	-1	4	4
c_first_shipto_date_sk	INT	-1	-1	4	4
c_first_sales_date_sk	INT	-1	-1	4	4
c_salutation	STRING	-1	-1	-1	-1
c_first_name	STRING	-1	-1	-1	-1
c_last_name	STRING	-1	-1	-1	-1
c_preferred_cust_flag	STRING	-1	-1	-1	-1
c_birth_day	INT	-1	-1	4	4
c_birth_month	INT	-1	-1	4	4
c_birth_year	INT	-1	-1	4	4
c_birth_country	STRING	-1	-1	-1	-1
c_login	STRING	-1	-1	-1	-1
c_email_address	STRING	-1	-1	-1	-1
c_last_review_date	STRING	-1	-1	-1	-1

```
show column stats store_sales;
```

Column	Type	#Distinct Values	#Nulls	Max Size	Avg Size
ss_sold_date_sk	INT	-1	-1	4	4
ss_sold_time_sk	INT	-1	-1	4	4
ss_item_sk	INT	-1	-1	4	4
ss_customer_sk	INT	-1	-1	4	4
ss_cdemo_sk	INT	-1	-1	4	4
ss_hdemo_sk	INT	-1	-1	4	4
ss_addr_sk	INT	-1	-1	4	4
ss_store_sk	INT	-1	-1	4	4
ss_promo_sk	INT	-1	-1	4	4
ss_ticket_number	INT	-1	-1	4	4
ss_quantity	INT	-1	-1	4	4
ss_wholesale_cost	FLOAT	-1	-1	4	4
ss_list_price	FLOAT	-1	-1	4	4
ss_sales_price	FLOAT	-1	-1	4	4
ss_ext_discount_amt	FLOAT	-1	-1	4	4
ss_ext_sales_price	FLOAT	-1	-1	4	4
ss_ext_wholesale_cost	FLOAT	-1	-1	4	4
ss_ext_list_price	FLOAT	-1	-1	4	4
ss_ext_tax	FLOAT	-1	-1	4	4
ss_coupon_amt	FLOAT	-1	-1	4	4
ss_net_paid	FLOAT	-1	-1	4	4
ss_net_paid_inc_tax	FLOAT	-1	-1	4	4
ss_net_profit	FLOAT	-1	-1	4	4

The following examples show the output of the SHOW COLUMN STATS statement for some tables, after the COMPUTE STATS statement is run. Now most of the -1 values are changed to reflect the actual table data. The #Nulls column remains -1 because Impala does not use the number of NULL values to influence query planning.

```
compute stats customer;
```

```
+-----+
| summary |
+-----+
| Updated 1 partition(s) and 18 column(s). |
+-----+
```

```
compute stats store_sales;
```

```
+-----+
| summary |
+-----+
| Updated 1 partition(s) and 23 column(s). |
+-----+
```

```
show column stats customer;
```

Column	Type	#Distinct Values	#Nulls	Max Size	Avg Size
c_customer_sk	INT	139017	-1	4	4

c_customer_id	STRING	111904	-1	16	16
c_current_demo_sk	INT	95837	-1	4	4
c_current_hdemo_sk	INT	8097	-1	4	4
c_current_addr_sk	INT	57334	-1	4	4
c_first_shipto_date_sk	INT	4374	-1	4	4
c_first_sales_date_sk	INT	4409	-1	4	4
c_salutation	STRING	7	-1	4	3.1308
c_first_name	STRING	3887	-1	11	5.6356
c_last_name	STRING	4739	-1	13	5.9106
c_preferred_cust_flag	STRING	3	-1	1	0.9656
c_birth_day	INT	31	-1	4	4
c_birth_month	INT	12	-1	4	4
c_birth_year	INT	71	-1	4	4
c_birth_country	STRING	205	-1	20	8.4001
c_login	STRING	1	-1	0	0
c_email_address	STRING	94492	-1	46	26.485
c_last_review_date	STRING	349	-1	7	6.7561

show column stats store_sales;

Column	Type	#Distinct Values	#Nulls	Max Size	Avg Size
ss_sold_date_sk	INT	4395	-1	4	4
ss_sold_time_sk	INT	63617	-1	4	4
ss_item_sk	INT	19463	-1	4	4
ss_customer_sk	INT	122720	-1	4	4
ss_demo_sk	INT	242982	-1	4	4
ss_hdemo_sk	INT	8097	-1	4	4
ss_addr_sk	INT	70770	-1	4	4
ss_store_sk	INT	6	-1	4	4
ss_promo_sk	INT	355	-1	4	4
ss_ticket_number	INT	304098	-1	4	4
ss_quantity	INT	105	-1	4	4
ss_wholesale_cost	FLOAT	9600	-1	4	4
ss_list_price	FLOAT	22191	-1	4	4
ss_sales_price	FLOAT	20693	-1	4	4
ss_ext_discount_amt	FLOAT	228141	-1	4	4
ss_ext_sales_price	FLOAT	433550	-1	4	4
ss_ext_wholesale_cost	FLOAT	406291	-1	4	4
ss_ext_list_price	FLOAT	574871	-1	4	4
ss_ext_tax	FLOAT	91806	-1	4	4
ss_coupon_amt	FLOAT	228141	-1	4	4
ss_net_paid	FLOAT	493107	-1	4	4
ss_net_paid_inc_tax	FLOAT	653523	-1	4	4
ss_net_profit	FLOAT	611934	-1	4	4

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have read and execute permissions for all directories that are part of the table. (A table could span multiple different HDFS directories if it is partitioned. The directories could be widely scattered because a partition can reside in an arbitrary HDFS directory based on its `LOCATION` attribute.) The Impala user must also have execute permission for the database directory, and any parent directories of the database directory in HDFS.

Related information:

[COMPUTE STATS Statement](#) on page 241, [SHOW TABLE STATS Statement](#) on page 365

See [Table and Column Statistics](#) on page 533 for usage information and examples.

SHOW PARTITIONS Statement

`SHOW PARTITIONS` displays information about each partition for a partitioned table. (The output is the same as the `SHOW TABLE STATS` statement, but `SHOW PARTITIONS` only works on a partitioned table.) Because it displays table statistics for all partitions, the output is more informative if you have run the `COMPUTE STATS` statement after creating all the partitions. See [COMPUTE STATS Statement](#) on page 241 for details. For example, on a `CENSUS` table partitioned on the `YEAR` column:

Security considerations:

When authorization is enabled, the output of the `SHOW` statement is limited to those objects for which you have some privilege. There might be other database, tables, and so on, but their names are concealed. If you believe an object exists but you cannot see it in the `SHOW` output, check with the system administrator if you need to be granted a new privilege for that object. See [Enabling Sentry Authorization for Impala](#) on page 105 for how to set up authorization and add privileges for specific kinds of objects.

Examples:

```
[localhost:21000] > show partitions census;
```

year	#Rows	#Files	Size	Format
2000	-1	0	0B	TEXT
2004	-1	0	0B	TEXT
2008	-1	0	0B	TEXT
2010	-1	0	0B	TEXT
2011	4	1	22B	TEXT
2012	4	1	22B	TEXT
2013	1	1	231B	PARQUET
Total	9	3	275B	

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have read and execute permissions for all directories that are part of the table. (A table could span multiple different HDFS directories if it is partitioned. The directories could be widely scattered because a partition can reside in an arbitrary HDFS directory based on its `LOCATION` attribute.) The Impala user must also have execute permission for the database directory, and any parent directories of the database directory in HDFS.

Related information:

See [Table and Column Statistics](#) on page 533 for usage information and examples.

[SHOW TABLE STATS Statement](#) on page 365, [Partitioning for Impala Tables](#) on page 568

SHOW FUNCTIONS Statement

By default, `SHOW FUNCTIONS` displays user-defined functions (UDFs) and `SHOW AGGREGATE FUNCTIONS` displays user-defined aggregate functions (UDAFs) associated with a particular database. The output from `SHOW FUNCTIONS` includes the argument signature of each function. You specify this argument signature as part of the `DROP FUNCTION` statement. You might have several UDFs with the same name, each accepting different argument data types.

Usage notes:

In CDH 5.7 / Impala 2.5 and higher, the `SHOW FUNCTIONS` output includes a new column, labelled `is persistent`. This property is `true` for Impala built-in functions, C++ UDFs, and Java UDFs created using the new `CREATE FUNCTION` syntax with no signature. It is `false` for Java UDFs created using the old `CREATE FUNCTION` syntax that includes the types for the arguments and return value. Any functions with `false` shown for this property must be created again by the `CREATE FUNCTION` statement each time the Impala catalog server is restarted. See `CREATE FUNCTION` for information on switching to the new syntax, so that Java UDFs are preserved across restarts. Java UDFs that are persisted this way are also easier to share across Impala and Hive.

Security considerations:

When authorization is enabled, the output of the `SHOW` statement is limited to those objects for which you have some privilege. There might be other database, tables, and so on, but their names are concealed. If you believe an object exists but you cannot see it in the `SHOW` output, check with the system administrator if you need to be granted a new privilege for that object. See [Enabling Sentry Authorization for Impala](#) on page 105 for how to set up authorization and add privileges for specific kinds of objects.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Examples:

To display Impala built-in functions, specify the special database name `_impala_builtins`:

```
show functions in _impala_builtins;
```

return type	signature	binary type	is persistent
BIGINT	abs(BIGINT)	BUILTIN	true
DECIMAL(*,*)	abs(DECIMAL(*,*))	BUILTIN	true
DOUBLE	abs(DOUBLE)	BUILTIN	true
FLOAT	abs(FLOAT)	BUILTIN	true
...			

```
show functions in _impala_builtins like '*week*';
```

return type	signature	binary type	is persistent
INT	dayofweek(TIMESTAMP)	BUILTIN	true
INT	weekofyear(TIMESTAMP)	BUILTIN	true
TIMESTAMP	weeks_add(TIMESTAMP, BIGINT)	BUILTIN	true
TIMESTAMP	weeks_add(TIMESTAMP, INT)	BUILTIN	true
TIMESTAMP	weeks_sub(TIMESTAMP, BIGINT)	BUILTIN	true
TIMESTAMP	weeks_sub(TIMESTAMP, INT)	BUILTIN	true

Related information:

[Overview of Impala Functions](#) on page 220, [Impala Built-In Functions](#) on page 373, [Impala User-Defined Functions \(UDFs\)](#) on page 487, [SHOW DATABASES](#) on page 361, [SHOW TABLES Statement](#) on page 362

TRUNCATE TABLE Statement (CDH 5.5 or higher only)

Removes the data from an Impala table while leaving the table itself.

Syntax:

```
TRUNCATE [TABLE] [IF EXISTS] [db_name.]table_name
```

Statement type: DDL

Usage notes:

Often used to empty tables that are used during ETL cycles, after the data has been copied to another table for the next stage of processing. This statement is a low-overhead alternative to dropping and recreating the table, or using `INSERT OVERWRITE` to replace the data during the next ETL cycle.

This statement removes all the data and associated data files in the table. It can remove data files from internal tables, external tables, partitioned tables, and tables mapped to HBase or the Amazon Simple Storage Service (S3). The data removal applies to the entire table, including all partitions of a partitioned table.

Any statistics produced by the `COMPUTE STATS` statement are reset when the data is removed.

Make sure that you are in the correct database before truncating a table, either by issuing a `USE` statement first or by using a fully qualified name `db_name.table_name`.

The optional `TABLE` keyword does not affect the behavior of the statement.

The optional `IF EXISTS` clause makes the statement succeed whether or not the table exists. If the table does exist, it is truncated; if it does not exist, the statement has no effect. This capability is useful in standardized setup scripts that are might be run both before and after some of the tables exist. This clause is available in CDH 5.7 / Impala 2.5 and higher.

For other tips about managing and reclaiming Impala disk space, see [Managing Disk Space for Impala Data](#) on page 98.

Amazon S3 considerations:

Although Impala cannot write new data to a table stored in the Amazon S3 filesystem, the `TRUNCATE TABLE` statement can remove data files from S3. See [Using Impala with the Amazon S3 Filesystem](#) on page 617 for details about working with S3 tables.

Cancellation: Cannot be cancelled.

HDFS permissions:

The user ID that the `impalad` daemon runs under, typically the `impala` user, must have write permission for all the files and directories that make up the table.

Examples:

The following example shows a table containing some data and with table and column statistics. After the `TRUNCATE TABLE` statement, the data is removed and the statistics are reset.

```
CREATE TABLE truncate_demo (x INT);
INSERT INTO truncate_demo VALUES (1), (2), (4), (8);
SELECT COUNT(*) FROM truncate_demo;
+-----+
| count(*) |
+-----+
| 4        |
+-----+
COMPUTE STATS truncate_demo;
+-----+
| summary |
+-----+
| Updated 1 partition(s) and 1 column(s). |
+-----+
SHOW TABLE STATS truncate_demo;
+-----+
| #Rows | #Files | Size | Bytes Cached | Cache Replication | Format | Incremental stats |
+-----+
| 4     | 1     | 8B  | NOT CACHED  | NOT CACHED        | TEXT  | false             |
+-----+
SHOW COLUMN STATS truncate_demo;
+-----+
| Column | Type | #Distinct Values | #Nulls | Max Size | Avg Size |
+-----+
| x      | INT | 4                 | -1     | 4        | 4        |
+-----+

-- After this statement, the data and the table/column stats will be gone.
TRUNCATE TABLE truncate_demo;

SELECT COUNT(*) FROM truncate_demo;
+-----+
| count(*) |
+-----+
| 0        |
+-----+
SHOW TABLE STATS truncate_demo;
+-----+
| #Rows | #Files | Size | Bytes Cached | Cache Replication | Format | Incremental stats |
+-----+
| -1    | 0     | 0B  | NOT CACHED  | NOT CACHED        | TEXT  | false             |
+-----+
SHOW COLUMN STATS truncate_demo;
+-----+
| Column | Type | #Distinct Values | #Nulls | Max Size | Avg Size |
+-----+
```

```
| x          | INT  | -1          | -1          | 4          | 4          |
+-----+-----+-----+-----+-----+-----+
```

The following example shows how the `IF EXISTS` clause allows the `TRUNCATE TABLE` statement to be run without error whether or not the table exists:

```
CREATE TABLE staging_table1 (x INT, s STRING);
Fetched 0 row(s) in 0.33s

SHOW TABLES LIKE 'staging*';
+-----+
| name          |
+-----+
| staging_table1 |
+-----+
Fetched 1 row(s) in 0.25s

-- Our ETL process involves removing all data from several staging tables
-- even though some might be already dropped, or not created yet.

TRUNCATE TABLE IF EXISTS staging_table1;
Fetched 0 row(s) in 5.04s

TRUNCATE TABLE IF EXISTS staging_table2;
Fetched 0 row(s) in 0.25s

TRUNCATE TABLE IF EXISTS staging_table3;
Fetched 0 row(s) in 0.25s
```

Related information:

[Overview of Impala Tables](#) on page 222, [ALTER TABLE Statement](#) on page 230, [CREATE TABLE Statement](#) on page 254, [Partitioning for Impala Tables](#) on page 568, [Internal Tables](#) on page 223, [External Tables](#) on page 223

USE Statement

Switches the current session to a specified database. The **current database** is where any `CREATE TABLE`, `INSERT`, `SELECT`, or other statements act when you specify a table or other object name, without prefixing it with a database name. The new current database applies for the duration of the session or until another `USE` statement is executed.

Syntax:

```
USE db_name
```

By default, when you connect to an Impala instance, you begin in a database named `default`.

Usage notes:

Switching the default database is convenient in the following situations:

- To avoid qualifying each reference to a table with the database name. For example, `SELECT * FROM t1 JOIN t2` rather than `SELECT * FROM db.t1 JOIN db.t2`.
- To do a sequence of operations all within the same database, such as creating a table, inserting data, and querying the table.

To start the `impala-shell` interpreter and automatically issue a `USE` statement for a particular database, specify the option `-d db_name` for the `impala-shell` command. The `-d` option is useful to run SQL scripts, such as setup or test scripts, against multiple databases without hardcoding a `USE` statement into the SQL source.

Examples:

See [CREATE DATABASE Statement](#) on page 246 for examples covering `CREATE DATABASE`, `USE`, and `DROP DATABASE`.

Cancellation: Cannot be cancelled.

HDFS permissions: This statement does not touch any HDFS files or directories, therefore no HDFS permissions are required.

Related information:

[CREATE DATABASE Statement](#) on page 246, [DROP DATABASE Statement](#) on page 273, [SHOW DATABASES](#) on page 361

Impala Built-In Functions

Impala supports several categories of built-in functions. These functions let you perform mathematical calculations, string manipulation, date calculations, and other kinds of data transformations directly in `SELECT` statements. The built-in functions let a SQL query return results with all formatting, calculating, and type conversions applied, rather than performing time-consuming postprocessing in another application. By applying function calls where practical, you can make a SQL query that is as convenient as an expression in a procedural programming language or a formula in a spreadsheet.

The categories of functions supported by Impala are:

- [Impala Mathematical Functions](#) on page 374
- [Impala Type Conversion Functions](#) on page 395
- [Impala Date and Time Functions](#) on page 398
- [Impala Conditional Functions](#) on page 427
- [Impala String Functions](#) on page 430
- Aggregation functions, explained in [Impala Aggregate Functions](#) on page 443.

You call any of these functions through the `SELECT` statement. For most functions, you can omit the `FROM` clause and supply literal values for any required arguments:

```
select abs(-1);
+-----+
| abs(-1) |
+-----+
| 1       |
+-----+

select concat('The rain ', 'in Spain');
+-----+
| concat('the rain ', 'in spain') |
+-----+
| The rain in Spain                |
+-----+

select power(2,5);
+-----+
| power(2, 5) |
+-----+
| 32          |
+-----+
```

When you use a `FROM` clause and specify a column name as a function argument, the function is applied for each item in the result set:

```
select concat('Country = ',country_code) from all_countries where population > 100000000;
select round(price) as dollar_value from product_catalog where price between 0.0 and 100.0;
```

Typically, if any argument to a built-in function is `NULL`, the result value is also `NULL`:

```
select cos(null);
+-----+
| cos(null) |
+-----+
| NULL      |
+-----+

select power(2,null);
+-----+
```

```

| power(2, null) |
+-----+
| NULL          |
+-----+

select concat('a',null,'b');
+-----+
| concat('a', null, 'b') |
+-----+
| NULL                   |
+-----+

```

Aggregate functions are a special category with different rules. These functions calculate a return value across all the items in a result set, so they require a FROM clause in the query:

```

select count(product_id) from product_catalog;
select max(height), avg(height) from census_data where age > 20;

```

Aggregate functions also ignore NULL values rather than returning a NULL result. For example, if some rows have NULL for a particular column, those rows are ignored when computing the AVG() for that column. Likewise, specifying COUNT(*col_name*) in a query counts only those rows where *col_name* contains a non-NULL value.

Aggregate functions are a special category with different rules. These functions calculate a return value across all the items in a result set, so they do require a FROM clause in the query:

```

select count(product_id) from product_catalog;
select max(height), avg(height) from census_data where age > 20;

```

Aggregate functions also ignore NULL values rather than returning a NULL result. For example, if some rows have NULL for a particular column, those rows are ignored when computing the AVG() for that column. Likewise, specifying COUNT(*col_name*) in a query counts only those rows where *col_name* contains a non-NULL value.

Analytic functions are a variation on aggregate functions. Instead of returning a single value, or an identical value for each group of rows, they can compute values that vary based on a “window” consisting of other rows around them in the result set.

Impala Mathematical Functions

Mathematical functions, or arithmetic functions, perform numeric calculations that are typically more complex than basic addition, subtraction, multiplication, and division. For example, these functions include trigonometric, logarithmic, and base conversion operations.



Note: In Impala, exponentiation uses the `pow()` function rather than an exponentiation operator such as `**`.

Related information:

The mathematical functions operate mainly on these data types: [INT Data Type](#) on page 145, [BIGINT Data Type](#) on page 130, [SMALLINT Data Type](#) on page 150, [TINYINT Data Type](#) on page 164, [DOUBLE Data Type](#) on page 143, [FLOAT Data Type](#) on page 144, and [DECIMAL Data Type \(CDH 5.1 or higher only\)](#) on page 135. For the operators that perform the standard operations such as addition, subtraction, multiplication, and division, see [Arithmetic Operators](#) on page 199.

Functions that perform bitwise operations are explained in [Impala Bit Functions](#) on page 386.

Function reference:

Impala supports the following mathematical functions:

abs(*numeric_type a*)

Purpose: Returns the absolute value of the argument.

Return type: Same as the input value

Usage notes: Use this function to ensure all return values are positive. This is different than the `positive()` function, which returns its argument unchanged (even if the argument was negative).

`acos(double a)`

Purpose: Returns the arccosine of the argument.

Return type: double

`asin(double a)`

Purpose: Returns the arcsine of the argument.

Return type: double

`atan(double a)`

Purpose: Returns the arctangent of the argument.

Return type: double

`atan2(double a, double b)`

Purpose: Returns the arctangent of the two arguments, with the signs of the arguments used to determine the quadrant of the result.

Return type: double

`bin(bigint a)`

Purpose: Returns the binary representation of an integer value, that is, a string of 0 and 1 digits.

Return type: string

`ceil(double a), ceil(decimal(p,s) a), ceiling(double a), ceiling(decimal(p,s) a), dceil(double a), dceil(decimal(p,s) a)`

Purpose: Returns the smallest integer that is greater than or equal to the argument.

Return type: bigint or decimal(p,s) depending on the type of the input argument

`conv(bigint n, int from_base, int to_base), conv(string s, int from_base, int to_base)`

Purpose: Returns a string representation of the first argument converted from `from_base` to `to_base`. The first argument can be specified as a number or a string. For example, `conv(100, 2, 10)` and `conv('100', 2, 10)` both return '4'.

Return type: string

Usage notes:

If `to_base` is negative, the first argument is treated as signed, and otherwise, it is treated as unsigned. For example:

- `conv(-17, 10, -2)` returns '-10001', -17 in base 2.
- `conv(-17, 10, 10)` returns '18446744073709551599'. -17 is interpreted as an unsigned, $2^{64}-17$, and then the value is returned in base 10.

The function returns `NULL` when the following illegal arguments are specified:

- Any argument is `NULL`.
- `from_base` or `to_base` is below -36 or above 36.
- `from_base` or `to_base` is -1, 0, or 1.
- The first argument represents a positive number and `from_base` is a negative number.

If the first argument represents a negative number and `from_base` is a negative number, the function returns 0.

If the first argument represents a number larger than the maximum `bigint`, the function returns:

- The string representation of -1 in `to_base` if `to_base` is negative.
- The string representation of '18446744073709551615' ($2^{64} - 1$) in `to_base` if `to_base` is positive.

If the first argument does not represent a valid number in `from_base`, e.g. 3 in base 2 or '1a23' in base 10, the digits in the first argument are evaluated from left-to-right and used if a valid digit in `from_base`. The invalid digit and the digits to the right are ignored.

For example:

- `conv(445, 5, 10)` is converted to `conv(44, 5, 10)` and returns '24'.
- `conv('1a23', 10, 16)` is converted to `conv('1', 10, 16)` and returns '1'.

`cos(double a)`

Purpose: Returns the cosine of the argument.

Return type: double

`cosh(double a)`

Purpose: Returns the hyperbolic cosine of the argument.

Return type: double

`cot(double a)`

Purpose: Returns the cotangent of the argument.

Return type: double

Added in: CDH 5.5.0 (Impala 2.3.0)

`degrees(double a)`

Purpose: Converts argument value from radians to degrees.

Return type: double

`e()`

Purpose: Returns the [mathematical constant e](#).

Return type: double

`exp(double a), dexp(double a)`

Purpose: Returns the [mathematical constant e](#) raised to the power of the argument.

Return type: double

`factorial(integer_type a)`

Purpose: Computes the [factorial](#) of an integer value. It works with any integer type.

Added in: CDH 5.5.0 (Impala 2.3.0)

Usage notes: You can use either the `factorial()` function or the `!` operator. The factorial of 0 is 1. Likewise, the `factorial()` function returns 1 for any negative value. The maximum positive value for the input argument is 20; a value of 21 or greater overflows the range for a `BIGINT` and causes an error.

Return type: bigint

Added in: CDH 5.5.0 (Impala 2.3.0)

```
select factorial(5);
+-----+
| factorial(5) |
+-----+
| 120          |
+-----+

select 5!;
+-----+
| 5!        |
+-----+
| 120      |
+-----+
```



```

select factorial(0);
+-----+
| factorial(0) |
+-----+
| 1           |
+-----+

select factorial(-100);
+-----+
| factorial(-100) |
+-----+
| 1               |
+-----+

```

floor(double a), floor(decimal(p,s) a), dfloor(double a), dfloor(decimal(p,s) a)

Purpose: Returns the largest integer that is less than or equal to the argument.

Return type: bigint or decimal(p,s) depending on the type of the input argument

fmod(double a, double b), fmod(float a, float b)

Purpose: Returns the modulus of a floating-point number.

Return type: float or double, depending on type of arguments

Added in: Impala 1.1.1

Usage notes:

Because this function operates on DOUBLE or FLOAT values, it is subject to potential rounding errors for values that cannot be represented precisely. Prefer to use whole numbers, or values that you know can be represented precisely by the DOUBLE or FLOAT types.

Examples:

The following examples show equivalent operations with the fmod() function and the % arithmetic operator, for values not subject to any rounding error.

```

select fmod(10,3);
+-----+
| fmod(10, 3) |
+-----+
| 1           |
+-----+

select fmod(5.5,2);
+-----+
| fmod(5.5, 2) |
+-----+
| 1.5          |
+-----+

select 10 % 3;
+-----+
| 10 % 3      |
+-----+
| 1           |
+-----+

select 5.5 % 2;
+-----+
| 5.5 % 2    |
+-----+
| 1.5        |
+-----+

```

The following examples show operations with the fmod() function for values that cannot be represented precisely by the DOUBLE or FLOAT types, and thus are subject to rounding error. fmod(9.9, 3.0) returns a value slightly

different than the expected 0.9 because of rounding. `fmod(9.9, 3.3)` returns a value quite different from the expected value of 0 because of rounding error during intermediate calculations.

```
select fmod(9.9,3.0);
+-----+
| fmod(9.9, 3.0) |
+-----+
| 0.8999996185302734 |
+-----+

select fmod(9.9,3.3);
+-----+
| fmod(9.9, 3.3) |
+-----+
| 3.299999713897705 |
+-----+
```

fnv_hash(type v),

Purpose: Returns a consistent 64-bit value derived from the input argument, for convenience of implementing hashing logic in an application.

Return type: BIGINT

Usage notes:

You might use the return value in an application where you perform load balancing, bucketing, or some other technique to divide processing or storage.

Because the result can be any 64-bit value, to restrict the value to a particular range, you can use an expression that includes the `ABS()` function and the `%` (modulo) operator. For example, to produce a hash value in the range 0-9, you could use the expression `ABS(FNV_HASH(x)) % 10`.

This function implements the same algorithm that Impala uses internally for hashing, on systems where the CRC32 instructions are not available.

This function implements the [Fowler–Noll–Vo hash function](#), in particular the FNV-1a variation. This is not a perfect hash function: some combinations of values could produce the same result value. It is not suitable for cryptographic use.

Similar input values of different types could produce different hash values, for example the same numeric value represented as `SMALLINT` or `BIGINT`, `FLOAT` or `DOUBLE`, or `DECIMAL(5, 2)` or `DECIMAL(20, 5)`.

Examples:

```
[localhost:21000] > create table h (x int, s string);
[localhost:21000] > insert into h values (0, 'hello'), (1, 'world'),
(1234567890, 'antidisestablishmentarianism');
[localhost:21000] > select x, fnv_hash(x) from h;
+-----+-----+
| x          | fnv_hash(x) |
+-----+-----+
| 0          | -2611523532599129963 |
| 1          | 4307505193096137732  |
| 1234567890 | 3614724209955230832  |
+-----+-----+

[localhost:21000] > select s, fnv_hash(s) from h;
+-----+-----+
| s          | fnv_hash(s) |
+-----+-----+
| hello     | 6414202926103426347  |
| world    | 6535280128821139475  |
| antidisestablishmentarianism | -209330013948433970  |
+-----+-----+

[localhost:21000] > select s, abs(fnv_hash(s)) % 10 from h;
+-----+-----+
| s          | abs(fnv_hash(s)) % 10.0 |
+-----+-----+
| hello     | 8 |
| world    | 6 |
+-----+-----+
```

```
| antidisestablishmentarianism | 4 |
+-----+-----+
+-----+-----+
```

For short argument values, the high-order bits of the result have relatively low entropy:

```
[localhost:21000] > create table b (x boolean);
[localhost:21000] > insert into b values (true), (true), (false), (false);
[localhost:21000] > select x, fnv_hash(x) from b;
```

```
+-----+-----+
| x      | fnv_hash(x) |
+-----+-----+
| true   | 2062020650953872396 |
| true   | 2062020650953872396 |
| false  | 2062021750465500607 |
| false  | 2062021750465500607 |
+-----+-----+
```

Added in: Impala 1.2.2

greatest(bigint a[, bigint b ...]), greatest(double a[, double b ...]), greatest(decimal(p,s) a[, decimal(p,s) b ...]), greatest(string a[, string b ...]), greatest(timestamp a[, timestamp b ...])

Purpose: Returns the largest value from a list of expressions.

Return type: same as the initial argument value, except that integer values are promoted to `BIGINT` and floating-point values are promoted to `DOUBLE`; use `CAST()` when inserting into a smaller numeric column

hex(bigint a), hex(string a)

Purpose: Returns the hexadecimal representation of an integer value, or of the characters in a string.

Return type: `string`

is_inf(double a),

Purpose: Tests whether a value is equal to the special value “inf”, signifying infinity.

Return type: `boolean`

Usage notes:

Infinity and NaN can be specified in text data files as `inf` and `nan` respectively, and Impala interprets them as these special values. They can also be produced by certain arithmetic expressions; for example, `1/0` returns `Infinity` and `pow(-1, 0.5)` returns `NaN`. Or you can cast the literal values, such as `CAST('nan' AS DOUBLE)` or `CAST('inf' AS DOUBLE)`.

is_nan(double a),

Purpose: Tests whether a value is equal to the special value “NaN”, signifying “not a number”.

Return type: `boolean`

Usage notes:

Infinity and NaN can be specified in text data files as `inf` and `nan` respectively, and Impala interprets them as these special values. They can also be produced by certain arithmetic expressions; for example, `1/0` returns `Infinity` and `pow(-1, 0.5)` returns `NaN`. Or you can cast the literal values, such as `CAST('nan' AS DOUBLE)` or `CAST('inf' AS DOUBLE)`.

least(bigint a[, bigint b ...]), least(double a[, double b ...]), least(decimal(p,s) a[, decimal(p,s) b ...]), least(string a[, string b ...]), least(timestamp a[, timestamp b ...])

Purpose: Returns the smallest value from a list of expressions.

Return type: same as the initial argument value, except that integer values are promoted to `BIGINT` and floating-point values are promoted to `DOUBLE`; use `CAST()` when inserting into a smaller numeric column

`ln(double a), dlog1(double a)`

Purpose: Returns the [natural logarithm](#) of the argument.

Return type: double

`log(double base, double a)`

Purpose: Returns the logarithm of the second argument to the specified base.

Return type: double

`log10(double a), dlog10(double a)`

Purpose: Returns the logarithm of the argument to the base 10.

Return type: double

`log2(double a)`

Purpose: Returns the logarithm of the argument to the base 2.

Return type: double

`max_int(), max_tinyint(), max_smallint(), max_bigint()`

Purpose: Returns the largest value of the associated integral type.

Return type: The same as the integral type being checked.

Usage notes: Use the corresponding `min_` and `max_` functions to check if all values in a column are within the allowed range, before copying data or altering column definitions. If not, switch to the next higher integral type or to a `DECIMAL` with sufficient precision.

`min_int(), min_tinyint(), min_smallint(), min_bigint()`

Purpose: Returns the smallest value of the associated integral type (a negative number).

Return type: The same as the integral type being checked.

Usage notes: Use the corresponding `min_` and `max_` functions to check if all values in a column are within the allowed range, before copying data or altering column definitions. If not, switch to the next higher integral type or to a `DECIMAL` with sufficient precision.

`mod(numeric_type a, same_type b)`

Purpose: Returns the modulus of a number. Equivalent to the `%` arithmetic operator. Works with any size integer type, any size floating-point type, and `DECIMAL` with any precision and scale.

Return type: Same as the input value

Added in: CDH 5.4.0 (Impala 2.2.0)

Usage notes:

Because this function works with `DECIMAL` values, prefer it over `fmod()` when working with fractional values. It is not subject to the rounding errors that make `fmod()` problematic with floating-point numbers. The `%` arithmetic operator now uses the `mod()` function in cases where its arguments can be interpreted as `DECIMAL` values, increasing the accuracy of that operator.

Examples:

The following examples show how the `mod()` function works for whole numbers and fractional values, and how the `%` operator works the same way. In the case of `mod(9.9, 3)`, the type conversion for the second argument results in the first argument being interpreted as `DOUBLE`, so to produce an accurate `DECIMAL` result requires casting the second argument or writing it as a `DECIMAL` literal, `3.0`.

```
select mod(10,3);
+-----+
| fmod(10, 3) |
+-----+
| 1            |
```

```

+-----+
select mod(5.5,2);
+-----+
| fmod(5.5, 2) |
+-----+
| 1.5          |
+-----+

select 10 % 3;
+-----+
| 10 % 3      |
+-----+
| 1           |
+-----+

select 5.5 % 2;
+-----+
| 5.5 % 2    |
+-----+
| 1.5        |
+-----+

select mod(9.9,3.3);
+-----+
| mod(9.9, 3.3) |
+-----+
| 0.0           |
+-----+

select mod(9.9,3);
+-----+
| mod(9.9, 3)   |
+-----+
| 0.8999996185302734 |
+-----+

select mod(9.9, cast(3 as decimal(2,1)));
+-----+
| mod(9.9, cast(3 as decimal(2,1))) |
+-----+
| 0.9           |
+-----+

select mod(9.9,3.0);
+-----+
| mod(9.9, 3.0) |
+-----+
| 0.9           |
+-----+

```

negative(numeric_type a)

Purpose: Returns the argument with the sign reversed; returns a positive value if the argument was already negative.

Return type: Same as the input value

Usage notes: Use `-abs(a)` instead if you need to ensure all return values are negative.

pi()

Purpose: Returns the constant pi.

Return type: double

pmod(bigint a, bigint b), pmod(double a, double b)

Purpose: Returns the positive modulus of a number. Primarily for [HiveQL compatibility](#).

Return type: int or double, depending on type of arguments

Examples:

The following examples show how the `fmod()` function sometimes returns a negative value depending on the sign of its arguments, and the `pmod()` function returns the same value as `fmod()`, but sometimes with the sign flipped.

```
select fmod(-5,2);
+-----+
| fmod(-5, 2) |
+-----+
| -1          |
+-----+

select pmod(-5,2);
+-----+
| pmod(-5, 2) |
+-----+
| 1           |
+-----+

select fmod(-5,-2);
+-----+
| fmod(-5, -2) |
+-----+
| -1          |
+-----+

select pmod(-5,-2);
+-----+
| pmod(-5, -2) |
+-----+
| -1          |
+-----+

select fmod(5,-2);
+-----+
| fmod(5, -2)  |
+-----+
| 1           |
+-----+

select pmod(5,-2);
+-----+
| pmod(5, -2)  |
+-----+
| -1          |
+-----+
```

positive(numeric_type a)

Purpose: Returns the original argument unchanged (even if the argument is negative).

Return type: Same as the input value

Usage notes: Use `abs()` instead if you need to ensure all return values are positive.

pow(double a, double p), power(double a, double p), dpow(double a, double p), fpow(double a, double p)

Purpose: Returns the first argument raised to the power of the second argument.

Return type: double

precision(numeric_expression)

Purpose: Computes the precision (number of decimal digits) needed to represent the type of the argument expression as a `DECIMAL` value.

Usage notes:

Typically used in combination with the `scale()` function, to determine the appropriate `DECIMAL(precision,scale)` type to declare in a `CREATE TABLE` statement or `CAST()` function.

Return type: int

Examples:

The following examples demonstrate how to check the precision and scale of numeric literals or other numeric expressions. Impala represents numeric literals in the smallest appropriate type. 5 is a `TINYINT` value, which ranges from -128 to 127, therefore 3 decimal digits are needed to represent the entire range, and because it is an integer value there are no fractional digits. 1.333 is interpreted as a `DECIMAL` value, with 4 digits total and 3 digits after the decimal point.

```
[localhost:21000] > select precision(5), scale(5);
+-----+-----+
| precision(5) | scale(5) |
+-----+-----+
| 3           | 0        |
+-----+-----+
[localhost:21000] > select precision(1.333), scale(1.333);
+-----+-----+
| precision(1.333) | scale(1.333) |
+-----+-----+
| 4               | 3            |
+-----+-----+
[localhost:21000] > with t1 as
  ( select cast(12.34 as decimal(20,2)) x union select cast(1 as decimal(8,6)) x )
  select precision(x), scale(x) from t1 limit 1;
+-----+-----+
| precision(x) | scale(x) |
+-----+-----+
| 24          | 6        |
+-----+-----+
```

quotient(bigint numerator, bigint denominator), quotient(double numerator, double denominator)

Purpose: Returns the first argument divided by the second argument, discarding any fractional part. Avoids promoting integer arguments to `DOUBLE` as happens with the `/` SQL operator. Also includes an overload that accepts `DOUBLE` arguments, discards the fractional part of each argument value before dividing, and again returns `BIGINT`. This function is the same as the `DIV` operator.

Return type: `bigint`

radians(double a)

Purpose: Converts argument value from degrees to radians.

Return type: `double`

rand(), rand(bigint seed), random(), random(bigint seed)

Purpose: Returns a random value between 0 and 1. After `rand()` is called with a seed argument, it produces a consistent random sequence based on the seed value.

Return type: `double`

Usage notes: Currently, the random sequence is reset after each query, and multiple calls to `rand()` within the same query return the same value each time. For different number sequences that are different for each query, pass a unique seed value to each call to `rand()`. For example, `select rand(unix_timestamp()) from ...`

Examples:

The following examples show how `rand()` can produce sequences of varying predictability, so that you can reproduce query results involving random values or generate unique sequences of random values for each query. When `rand()` is called with no argument, it generates the same sequence of values each time, regardless of the ordering of the result set. When `rand()` is called with a constant integer, it generates a different sequence of values, but still always the same sequence for the same seed value. If you pass in a seed value that changes, such as the return value of the expression `unix_timestamp(now())`, each query will use a different sequence of random values, potentially more useful in probability calculations although more difficult to reproduce at a later time. Therefore,

the final two examples with an unpredictable seed value also include the seed in the result set, to make it possible to reproduce the same random sequence later.

```

select x, rand() from three_rows;
+-----+-----+
| x | rand() |
+-----+-----+
| 1 | 0.0004714746030380365 |
| 2 | 0.5895895192351144 |
| 3 | 0.4431900859080209 |
+-----+-----+

select x, rand() from three_rows order by x desc;
+-----+-----+
| x | rand() |
+-----+-----+
| 3 | 0.0004714746030380365 |
| 2 | 0.5895895192351144 |
| 1 | 0.4431900859080209 |
+-----+-----+

select x, rand(1234) from three_rows order by x;
+-----+-----+
| x | rand(1234) |
+-----+-----+
| 1 | 0.7377511392057646 |
| 2 | 0.009428468537250751 |
| 3 | 0.208117277924026 |
+-----+-----+

select x, rand(1234) from three_rows order by x desc;
+-----+-----+
| x | rand(1234) |
+-----+-----+
| 3 | 0.7377511392057646 |
| 2 | 0.009428468537250751 |
| 1 | 0.208117277924026 |
+-----+-----+

select x, unix_timestamp(now()), rand(unix_timestamp(now()))
from three_rows order by x;
+-----+-----+-----+
| x | unix_timestamp(now()) | rand(unix_timestamp(now())) |
+-----+-----+-----+
| 1 | 1440777752 | 0.002051228658320023 |
| 2 | 1440777752 | 0.5098743483004506 |
| 3 | 1440777752 | 0.9517714925817081 |
+-----+-----+-----+

select x, unix_timestamp(now()), rand(unix_timestamp(now()))
from three_rows order by x desc;
+-----+-----+-----+
| x | unix_timestamp(now()) | rand(unix_timestamp(now())) |
+-----+-----+-----+
| 3 | 1440777761 | 0.9985985015512437 |
| 2 | 1440777761 | 0.3251255333074953 |
| 1 | 1440777761 | 0.02422675025846192 |
+-----+-----+-----+

```

round(double a), round(double a, int d), round(decimal a, int_type d), dround(double a), dround(double a, int d), dround(decimal(p,s) a, int_type d)

Purpose: Rounds a floating-point value. By default (with a single argument), rounds to the nearest integer. Values ending in .5 are rounded up for positive numbers, down for negative numbers (that is, away from zero). The optional second argument specifies how many digits to leave after the decimal point; values greater than zero produce a floating-point return value rounded to the requested number of digits to the right of the decimal point.

Return type: bigint for single double argument. double for two-argument signature when second argument greater than zero. For DECIMAL values, the smallest DECIMAL(p,s) type with appropriate precision and scale.

scale(numeric_expression)

Purpose: Computes the scale (number of decimal digits to the right of the decimal point) needed to represent the type of the argument expression as a `DECIMAL` value.

Usage notes:

Typically used in combination with the `precision()` function, to determine the appropriate `DECIMAL(precision,scale)` type to declare in a `CREATE TABLE` statement or `CAST()` function.

Return type: `int`

Examples:

The following examples demonstrate how to check the precision and scale of numeric literals or other numeric expressions. Impala represents numeric literals in the smallest appropriate type. 5 is a `TINYINT` value, which ranges from -128 to 127, therefore 3 decimal digits are needed to represent the entire range, and because it is an integer value there are no fractional digits. 1.333 is interpreted as a `DECIMAL` value, with 4 digits total and 3 digits after the decimal point.

```
[localhost:21000] > select precision(5), scale(5);
+-----+-----+
| precision(5) | scale(5) |
+-----+-----+
| 3           | 0        |
+-----+-----+
[localhost:21000] > select precision(1.333), scale(1.333);
+-----+-----+
| precision(1.333) | scale(1.333) |
+-----+-----+
| 4               | 3            |
+-----+-----+
[localhost:21000] > with t1 as
( select cast(12.34 as decimal(20,2)) x union select cast(1 as decimal(8,6)) x )
  select precision(x), scale(x) from t1 limit 1;
+-----+-----+
| precision(x) | scale(x) |
+-----+-----+
| 24          | 6        |
+-----+-----+
```

sign(double a)

Purpose: Returns -1, 0, or 1 to indicate the signedness of the argument value.

Return type: `int`

sin(double a)

Purpose: Returns the sine of the argument.

Return type: `double`

sinh(double a)

Purpose: Returns the hyperbolic sine of the argument.

Return type: `double`

sqrt(double a), dsqrt(double a)

Purpose: Returns the square root of the argument.

Return type: `double`

tan(double a)

Purpose: Returns the tangent of the argument.

Return type: `double`

tanh(double a)

Purpose: Returns the hyperbolic tangent of the argument.

Return type: double

`truncate(double_or_decimal a[, digits_to_leave]), dtrunc(double_or_decimal a[, digits_to_leave])`

Purpose: Removes some or all fractional digits from a numeric value. With no argument, removes all fractional digits, leaving an integer value. The optional argument specifies the number of fractional digits to include in the return value, and only applies with the argument type is `DECIMAL`. `truncate()` and `dtrunc()` are aliases for the same function.

Return type: decimal for `DECIMAL` arguments; bigint for `DOUBLE` arguments

Examples:

```
select truncate(3.45)
```

```
+-----+
| truncate(3.45) |
+-----+
| 3              |
+-----+
```

```
select truncate(-3.45)
```

```
+-----+
| truncate(-3.45) |
+-----+
| -3              |
+-----+
```

```
select truncate(3.456,1)
```

```
+-----+
| truncate(3.456, 1) |
+-----+
| 3.4                |
+-----+
```

```
select dtrunc(3.456,1)
```

```
+-----+
| dtrunc(3.456, 1) |
+-----+
| 3.4                |
+-----+
```

```
select truncate(3.456,2)
```

```
+-----+
| truncate(3.456, 2) |
+-----+
| 3.45                |
+-----+
```

```
select truncate(3.456,7)
```

```
+-----+
| truncate(3.456, 7) |
+-----+
| 3.4560000          |
+-----+
```

unhex(string a)

Purpose: Returns a string of characters with ASCII values corresponding to pairs of hexadecimal digits in the argument.

Return type: string

Impala Bit Functions

Bit manipulation functions perform bitwise operations involved in scientific processing or computer science algorithms. For example, these functions include setting, clearing, or testing bits within an integer value, or changing the positions of bits with or without wraparound.

If a function takes two integer arguments that are required to be of the same type, the smaller argument is promoted to the type of the larger one if required. For example, `BITAND(1, 4096)` treats both arguments as `SMALLINT`, because 1 can be represented as a `TINYINT` but 4096 requires a `SMALLINT`.

Remember that all Impala integer values are signed. Therefore, when dealing with binary values where the most significant bit is 1, the specified or returned values might be negative when represented in base 10.

Whenever any argument is `NULL`, either the input value, bit position, or number of shift or rotate positions, the return value from any of these functions is also `NULL`.

Related information:

The bit functions operate on all the integral data types: [INT Data Type](#) on page 145, [BIGINT Data Type](#) on page 130, [SMALLINT Data Type](#) on page 150, and [TINYINT Data Type](#) on page 164.

Function reference:

Impala supports the following bit functions:

bitand(integer_type a, same_type b)

Purpose: Returns an integer value representing the bits that are set to 1 in both of the arguments. If the arguments are of different sizes, the smaller is promoted to the type of the larger.

Usage notes: The `bitand()` function is equivalent to the `&` binary operator.

Return type: Same as the input value

Added in: CDH 5.5.0 (Impala 2.3.0)

Examples:

The following examples show the results of ANDing integer values. 255 contains all 1 bits in its lowermost 7 bits. 32767 contains all 1 bits in its lowermost 15 bits. You can use the `bin()` function to check the binary representation of any integer value, although the result is always represented as a 64-bit value. If necessary, the smaller argument is promoted to the type of the larger one.

```
select bitand(255, 32767); /* 0000000011111111 & 0111111111111111 */
+-----+
| bitand(255, 32767) |
+-----+
| 255                |
+-----+

select bitand(32767, 1); /* 0111111111111111 & 0000000000000001 */
+-----+
| bitand(32767, 1)  |
+-----+
| 1                 |
+-----+

select bitand(32, 16); /* 00010000 & 00001000 */
+-----+
| bitand(32, 16)    |
+-----+
| 0                 |
+-----+

select bitand(12,5); /* 00001100 & 00000101 */
+-----+
| bitand(12, 5)     |
+-----+
| 4                 |
+-----+

select bitand(-1,15); /* 11111111 & 00001111 */
+-----+
| bitand(-1, 15)    |
+-----+
| 15                |
+-----+
```

bitnot(integer_type a)

Purpose: Inverts all the bits of the input argument.

Usage notes: The `bitnot()` function is equivalent to the `~` unary operator.

Return type: Same as the input value

Added in: CDH 5.5.0 (Impala 2.3.0)

Examples:

These examples illustrate what happens when you flip all the bits of an integer value. The sign always changes. The decimal representation is one different between the positive and negative values.

```
select bitnot(127); /* 01111111 -> 10000000 */
+-----+
| bitnot(127) |
+-----+
| -128        |
+-----+

select bitnot(16); /* 00010000 -> 11101111 */
+-----+
| bitnot(16)  |
+-----+
| -17        |
+-----+

select bitnot(0); /* 00000000 -> 11111111 */
+-----+
| bitnot(0)   |
+-----+
| -1         |
+-----+

select bitnot(-128); /* 10000000 -> 01111111 */
+-----+
| bitnot(-128)|
+-----+
| 127        |
+-----+
```

bitor(integer_type a, same_type b)

Purpose: Returns an integer value representing the bits that are set to 1 in either of the arguments. If the arguments are of different sizes, the smaller is promoted to the type of the larger.

Usage notes: The `bitor()` function is equivalent to the `|` binary operator.

Return type: Same as the input value

Added in: CDH 5.5.0 (Impala 2.3.0)

Examples:

The following examples show the results of ORing integer values.

```
select bitor(1,4); /* 00000001 | 00000100 */
+-----+
| bitor(1, 4) |
+-----+
| 5           |
+-----+

select bitor(16,48); /* 00001000 | 00011000 */
+-----+
| bitor(16, 48)|
+-----+
| 48         |
+-----+

select bitor(0,7); /* 00000000 | 00000111 */
+-----+
| bitor(0, 7)  |
+-----+
```

```
| 7 |
+-----+
```

bitxor(integer_type a, same_type b)

Purpose: Returns an integer value representing the bits that are set to 1 in one but not both of the arguments. If the arguments are of different sizes, the smaller is promoted to the type of the larger.

Usage notes: The `bitxor()` function is equivalent to the `^` binary operator.

Return type: Same as the input value

Added in: CDH 5.5.0 (Impala 2.3.0)

Examples:

The following examples show the results of XORing integer values. XORing a non-zero value with zero returns the non-zero value. XORing two identical values returns zero, because all the 1 bits from the first argument are also 1 bits in the second argument. XORing different non-zero values turns off some bits and leaves others turned on, based on whether the same bit is set in both arguments.

```
select bitxor(0,15); /* 00000000 ^ 00001111 */
+-----+
| bitxor(0, 15) |
+-----+
| 15            |
+-----+

select bitxor(7,7); /* 00000111 ^ 00000111 */
+-----+
| bitxor(7, 7) |
+-----+
| 0            |
+-----+

select bitxor(8,4); /* 00001000 ^ 00000100 */
+-----+
| bitxor(8, 4) |
+-----+
| 12           |
+-----+

select bitxor(3,7); /* 00000011 ^ 00000111 */
+-----+
| bitxor(3, 7) |
+-----+
| 4            |
+-----+
```

countset(integer_type a [, int zero_or_one])

Purpose: By default, returns the number of 1 bits in the specified integer value. If the optional second argument is set to zero, it returns the number of 0 bits instead.

Usage notes:

In discussions of information theory, this operation is referred to as the “[population count](#)” or “popcount”.

Return type: Same as the input value

Added in: CDH 5.5.0 (Impala 2.3.0)

Examples:

The following examples show how to count the number of 1 bits in an integer value.

```
select countset(1); /* 00000001 */
+-----+
| countset(1) |
+-----+
```

```

| 1 |
+-----+
select countset(3); /* 00000011 */
+-----+
| countset(3) |
+-----+
| 2 |
+-----+

select countset(16); /* 00010000 */
+-----+
| countset(16) |
+-----+
| 1 |
+-----+

select countset(17); /* 00010001 */
+-----+
| countset(17) |
+-----+
| 2 |
+-----+

select countset(7,1); /* 00000111 = 3 1 bits; the function counts 1 bits by default */
+-----+
| countset(7, 1) |
+-----+
| 3 |
+-----+

select countset(7,0); /* 00000111 = 5 0 bits; third argument can only be 0 or 1 */
+-----+
| countset(7, 0) |
+-----+
| 5 |
+-----+

```

getbit(integer_type a, int position)

Purpose: Returns a 0 or 1 representing the bit at a specified position. The positions are numbered right to left, starting at zero. The position argument cannot be negative.

Usage notes:

When you use a literal input value, it is treated as an 8-bit, 16-bit, and so on value, the smallest type that is appropriate. The type of the input value limits the range of the positions. Cast the input value to the appropriate type if you need to ensure it is treated as a 64-bit, 32-bit, and so on value.

Return type: Same as the input value

Added in: CDH 5.5.0 (Impala 2.3.0)

Examples:

The following examples show how to test a specific bit within an integer value.

```

select getbit(1,0); /* 00000001 */
+-----+
| getbit(1, 0) |
+-----+
| 1 |
+-----+

select getbit(16,1) /* 00010000 */
+-----+
| getbit(16, 1) |
+-----+
| 0 |
+-----+

select getbit(16,4) /* 00010000 */

```

```

+-----+
| getbit(16, 4) |
+-----+
| 1             |
+-----+

select getbit(16,5) /* 00010000 */
+-----+
| getbit(16, 5) |
+-----+
| 0             |
+-----+

select getbit(-1,3); /* 11111111 */
+-----+
| getbit(-1, 3) |
+-----+
| 1             |
+-----+

select getbit(-1,25); /* 11111111 */
ERROR: Invalid bit position: 25

select getbit(cast(-1 as int),25); /* 11111111111111111111111111111111 */
+-----+
| getbit(cast(-1 as int), 25) |
+-----+
| 1                             |
+-----+

```

rotateleft(integer_type a, int positions)

Purpose: Rotates an integer value left by a specified number of bits. As the most significant bit is taken out of the original value, if it is a 1 bit, it is “rotated” back to the least significant bit. Therefore, the final value has the same number of 1 bits as the original value, just in different positions. In computer science terms, this operation is a [“circular shift”](#).

Usage notes:

Specifying a second argument of zero leaves the original value unchanged. Rotating a -1 value by any number of positions still returns -1, because the original value has all 1 bits and all the 1 bits are preserved during rotation. Similarly, rotating a 0 value by any number of positions still returns 0. Rotating a value by the same number of bits as in the value returns the same value. Because this is a circular operation, the number of positions is not limited to the number of bits in the input value. For example, rotating an 8-bit value by 1, 9, 17, and so on positions returns an identical result in each case.

Return type: Same as the input value

Added in: CDH 5.5.0 (Impala 2.3.0)

Examples:

```

select rotateleft(1,4); /* 00000001 -> 00010000 */
+-----+
| rotateleft(1, 4) |
+-----+
| 16               |
+-----+

select rotateleft(-1,155); /* 11111111 -> 11111111 */
+-----+
| rotateleft(-1, 155) |
+-----+
| -1                 |
+-----+

select rotateleft(-128,1); /* 10000000 -> 00000001 */
+-----+
| rotateleft(-128, 1) |
+-----+

```

```

| 1 |
+-----+
select rotateleft(-127,3); /* 10000001 -> 00001100 */
+-----+
| rotateleft(-127, 3) |
+-----+
| 12 |
+-----+

```

rotateright(integer_type a, int positions)

Purpose: Rotates an integer value right by a specified number of bits. As the least significant bit is taken out of the original value, if it is a 1 bit, it is “rotated” back to the most significant bit. Therefore, the final value has the same number of 1 bits as the original value, just in different positions. In computer science terms, this operation is a [“circular shift”](#).

Usage notes:

Specifying a second argument of zero leaves the original value unchanged. Rotating a -1 value by any number of positions still returns -1, because the original value has all 1 bits and all the 1 bits are preserved during rotation. Similarly, rotating a 0 value by any number of positions still returns 0. Rotating a value by the same number of bits as in the value returns the same value. Because this is a circular operation, the number of positions is not limited to the number of bits in the input value. For example, rotating an 8-bit value by 1, 9, 17, and so on positions returns an identical result in each case.

Return type: Same as the input value

Added in: CDH 5.5.0 (Impala 2.3.0)

Examples:

```

select rotateright(16,4); /* 00010000 -> 00000001 */
+-----+
| rotateright(16, 4) |
+-----+
| 1 |
+-----+

select rotateright(-1,155); /* 11111111 -> 11111111 */
+-----+
| rotateright(-1, 155) |
+-----+
| -1 |
+-----+

select rotateright(-128,1); /* 10000000 -> 01000000 */
+-----+
| rotateright(-128, 1) |
+-----+
| 64 |
+-----+

select rotateright(-127,3); /* 10000001 -> 00110000 */
+-----+
| rotateright(-127, 3) |
+-----+
| 48 |
+-----+

```

setbit(integer_type a, int position [, int zero_or_one])

Purpose: By default, changes a bit at a specified position to a 1, if it is not already. If the optional third argument is set to zero, the specified bit is set to 0 instead.

Usage notes:

If the bit at the specified position was already 1 (by default) or 0 (with a third argument of zero), the return value is the same as the first argument. The positions are numbered right to left, starting at zero. (Therefore, the return

value could be different from the first argument even if the position argument is zero.) The position argument cannot be negative.

When you use a literal input value, it is treated as an 8-bit, 16-bit, and so on value, the smallest type that is appropriate. The type of the input value limits the range of the positions. Cast the input value to the appropriate type if you need to ensure it is treated as a 64-bit, 32-bit, and so on value.

Return type: Same as the input value

Added in: CDH 5.5.0 (Impala 2.3.0)

Examples:

```

select setbit(0,0); /* 00000000 -> 00000001 */
+-----+
| setbit(0, 0) |
+-----+
| 1           |
+-----+

select setbit(0,3); /* 00000000 -> 00001000 */
+-----+
| setbit(0, 3) |
+-----+
| 8           |
+-----+

select setbit(7,3); /* 00000111 -> 00001111 */
+-----+
| setbit(7, 3) |
+-----+
| 15          |
+-----+

select setbit(15,3); /* 00001111 -> 00001111 */
+-----+
| setbit(15, 3) |
+-----+
| 15           |
+-----+

select setbit(0,32); /* By default, 0 is a TINYINT with only 8 bits. */
ERROR: Invalid bit position: 32

select setbit(cast(0 as bigint),32); /* For BIGINT, the position can be 0..63. */
+-----+
| setbit(cast(0 as bigint), 32) |
+-----+
| 4294967296                    |
+-----+

select setbit(7,3,1); /* 00000111 -> 00001111; setting to 1 is the default */
+-----+
| setbit(7, 3, 1) |
+-----+
| 15              |
+-----+

select setbit(7,2,0); /* 00000111 -> 00000011; third argument of 0 clears instead of
sets */
+-----+
| setbit(7, 2, 0) |
+-----+
| 3               |
+-----+

```

shiftright(integer_type a, int positions)

Purpose: Shifts an integer value left by a specified number of bits. As the most significant bit is taken out of the original value, it is discarded and the least significant bit becomes 0. In computer science terms, this operation is a “[logical shift](#)”.

Usage notes:

The final value has either the same number of 1 bits as the original value, or fewer. Shifting an 8-bit value by 8 positions, a 16-bit value by 16 positions, and so on produces a result of zero.

Specifying a second argument of zero leaves the original value unchanged. Shifting any value by 0 returns the original value. Shifting any value by 1 is the same as multiplying it by 2, as long as the value is small enough; larger values eventually become negative when shifted, as the sign bit is set. Starting with the value 1 and shifting it left by N positions gives the same result as 2 to the Nth power, or `pow(2,N)`.

Return type: Same as the input value

Added in: CDH 5.5.0 (Impala 2.3.0)

Examples:

```

select shiftleft(1,0); /* 00000001 -> 00000001 */
+-----+
| shiftleft(1, 0) |
+-----+
| 1               |
+-----+

select shiftleft(1,3); /* 00000001 -> 00001000 */
+-----+
| shiftleft(1, 3) |
+-----+
| 8               |
+-----+

select shiftleft(8,2); /* 00001000 -> 00100000 */
+-----+
| shiftleft(8, 2) |
+-----+
| 32              |
+-----+

select shiftleft(127,1); /* 01111111 -> 11111110 */
+-----+
| shiftleft(127, 1) |
+-----+
| -2              |
+-----+

select shiftleft(127,5); /* 01111111 -> 11100000 */
+-----+
| shiftleft(127, 5) |
+-----+
| -32             |
+-----+

select shiftleft(-1,4); /* 11111111 -> 11110000 */
+-----+
| shiftleft(-1, 4) |
+-----+
| -16             |
+-----+

```

shiftright(integer_type a, int positions)

Purpose: Shifts an integer value right by a specified number of bits. As the least significant bit is taken out of the original value, it is discarded and the most significant bit becomes 0. In computer science terms, this operation is a “[logical shift](#)”.

Usage notes:

Therefore, the final value has either the same number of 1 bits as the original value, or fewer. Shifting an 8-bit value by 8 positions, a 16-bit value by 16 positions, and so on produces a result of zero.

Specifying a second argument of zero leaves the original value unchanged. Shifting any value by 0 returns the original value. Shifting any positive value right by 1 is the same as dividing it by 2. Negative values become positive when shifted right.

Return type: Same as the input value

Added in: CDH 5.5.0 (Impala 2.3.0)

Examples:

```

select shiftright(16,0); /* 00010000 -> 00010000 */
+-----+
| shiftright(16, 0) |
+-----+
| 16                |
+-----+

select shiftright(16,4); /* 00010000 -> 00000001 */
+-----+
| shiftright(16, 4) |
+-----+
| 1                  |
+-----+

select shiftright(16,5); /* 00010000 -> 00000000 */
+-----+
| shiftright(16, 5) |
+-----+
| 0                  |
+-----+

select shiftright(-1,1); /* 11111111 -> 01111111 */
+-----+
| shiftright(-1, 1) |
+-----+
| 127                |
+-----+

select shiftright(-1,5); /* 11111111 -> 00000111 */
+-----+
| shiftright(-1, 5) |
+-----+
| 7                  |
+-----+

```

Impala Type Conversion Functions

Conversion functions are usually used in combination with other functions, to explicitly pass the expected data types. Impala has strict rules regarding data types for function parameters. For example, Impala does not automatically convert a `DOUBLE` value to `FLOAT`, a `BIGINT` value to `INT`, or other conversion where precision could be lost or overflow could occur. Also, for reporting or dealing with loosely defined schemas in big data contexts, you might frequently need to convert values to or from the `STRING` type.



Note: Although in CDH 5.5.0, the `SHOW FUNCTIONS` output for database `__IMPALA_BUILTINS` contains some function signatures matching the pattern `castto*`, these functions are not intended for public use and are expected to be hidden in future.

Function reference:

Impala supports the following type conversion functions:

cast(expr AS type)

Purpose: Converts the value of an expression to any other type. If the expression value is of a type that cannot be converted to the target type, the result is `NULL`.

Usage notes: Use `CAST` when passing a column value or literal to a function that expects a parameter with a different type. Frequently used in SQL operations such as `CREATE TABLE AS SELECT` and `INSERT ... VALUES` to ensure

that values from various sources are of the appropriate type for the destination columns. Where practical, do a one-time `CAST()` operation during the ingestion process to make each column into the appropriate type, rather than using many `CAST()` operations in each query; doing type conversions for each row during each query can be expensive for tables with millions or billions of rows.

The way this function deals with time zones when converting to or from `TIMESTAMP` values is affected by the `--use_local_tz_for_unix_timestamp_conversions` startup flag for the `impalad` daemon. See [TIMESTAMP Data Type](#) on page 158 for details about how Impala handles time zone considerations for the `TIMESTAMP` data type.

Examples:

```
select concat('Here are the first ',10,' results.');
```

-- Fails

```
select concat('Here are the first ',cast(10 as string),' results.');
```

-- Succeeds

The following example starts with a text table where every column has a type of `STRING`, which might be how you ingest data of unknown schema until you can verify the cleanliness of the underlying values. Then it uses `CAST()` to create a new Parquet table with the same data, but using specific numeric data types for the columns with numeric data. Using numeric types of appropriate sizes can result in substantial space savings on disk and in memory, and performance improvements in queries, over using strings or larger-than-necessary numeric types.

```
create table t1 (name string, x string, y string, z string);

create table t2 stored as parquet
as select
  name,
  cast(x as bigint) x,
  cast(y as timestamp) y,
  cast(z as smallint) z
from t1;
```

```
describe t2;
```

name	type	comment
name	string	
x	bigint	
y	smallint	
z	tinyint	

Related information:

For details of casts from each kind of data type, see the description of the appropriate type: [TINYINT Data Type](#) on page 164, [SMALLINT Data Type](#) on page 150, [INT Data Type](#) on page 145, [BIGINT Data Type](#) on page 130, [FLOAT Data Type](#) on page 144, [DOUBLE Data Type](#) on page 143, [DECIMAL Data Type \(CDH 5.1 or higher only\)](#) on page 135, [STRING Data Type](#) on page 151, [CHAR Data Type \(CDH 5.2 or higher only\)](#) on page 132, [VARCHAR Data Type \(CDH 5.2 or higher only\)](#) on page 165, [TIMESTAMP Data Type](#) on page 158, [BOOLEAN Data Type](#) on page 131

`typeof(type value)`

Purpose: Returns the name of the data type corresponding to an expression. For types with extra attributes, such as length for `CHAR` and `VARCHAR`, or precision and scale for `DECIMAL`, includes the full specification of the type.

Return type: `string`

Usage notes: Typically used in interactive exploration of a schema, or in application code that programmatically generates schema definitions such as `CREATE TABLE` statements. For example, previously, to understand the type of an expression such as `col1 / col2` or `concat(col1, col2, col3)`, you might have created a dummy table with a single row, using syntax such as `CREATE TABLE foo AS SELECT 5 / 3.0`, and then doing a `DESCRIBE` to see the type of the row. Or you might have done a `CREATE TABLE AS SELECT` operation to create a table and copy data into it, only learning the types of the columns by doing a `DESCRIBE` afterward. This technique is especially useful for arithmetic expressions involving `DECIMAL` types, because the precision and scale of the result is typically different than that of the operands.

Added in: CDH 5.5.0 (Impala 2.3.0)

Examples:

These examples show how to check the type of a simple literal or function value. Notice how adding even tiny integers together changes the data type of the result to avoid overflow, and how the results of arithmetic operations on `DECIMAL` values have specific precision and scale attributes.

```

select typeof(2)
+-----+
| typeof(2) |
+-----+
| TINYINT   |
+-----+

select typeof(2+2)
+-----+
| typeof(2 + 2) |
+-----+
| SMALLINT      |
+-----+

select typeof('xyz')
+-----+
| typeof('xyz') |
+-----+
| STRING        |
+-----+

select typeof(now())
+-----+
| typeof(now()) |
+-----+
| TIMESTAMP     |
+-----+

select typeof(5.3 / 2.1)
+-----+
| typeof(5.3 / 2.1) |
+-----+
| DECIMAL(6,4)      |
+-----+

select typeof(5.30001 / 2342.1);
+-----+
| typeof(5.30001 / 2342.1) |
+-----+
| DECIMAL(13,11)          |
+-----+

select typeof(typeof(2+2))
+-----+
| typeof(typeof(2 + 2)) |
+-----+
| STRING                |
+-----+

```

This example shows how even if you do not have a record of the type of a column, for example because the type was changed by `ALTER TABLE` after the original `CREATE TABLE`, you can still find out the type in a more compact form than examining the full `DESCRIBE` output. Remember to use `LIMIT 1` in such cases, to avoid an identical result value for every row in the table.

```

create table typeof_example (a int, b tinyint, c smallint, d bigint);

/* Empty result set if there is no data in the table. */
select typeof(a) from typeof_example;

/* OK, now we have some data but the type of column A is being changed. */
insert into typeof_example values (1, 2, 3, 4);
alter table typeof_example change a a bigint;

```

```

/* We can always find out the current type of that column without doing a full DESCRIBE.
*/
select typeof(a) from typeof_example limit 1;
+-----+
| typeof(a) |
+-----+
| BIGINT    |
+-----+

```

This example shows how you might programmatically generate a `CREATE TABLE` statement with the appropriate column definitions to hold the result values of arbitrary expressions. The `typeof()` function lets you construct a detailed `CREATE TABLE` statement without actually creating the table, as opposed to `CREATE TABLE AS SELECT` operations where you create the destination table but only learn the column data types afterward through `DESCRIBE`.

```

describe typeof_example;
+-----+-----+-----+
| name | type   | comment |
+-----+-----+-----+
| a    | bigint|         |
| b    | tinyint|        |
| c    | smallint|       |
| d    | bigint|         |
+-----+-----+-----+

/* An ETL or business intelligence tool might create variations on a table with different
file formats,
different sets of columns, and so on. TYPEOF() lets an application introspect the
types of the original columns. */
select concat('create table derived_table (a ', typeof(a), ', b ', typeof(b), ', c ',
typeof(c), ', d ', typeof(d), ') stored as parquet;')
as 'create table statement'
from typeof_example limit 1;
+-----+
| create table statement
|
+-----+
| create table derived_table (a BIGINT, b TINYINT, c SMALLINT, d BIGINT) stored as
parquet; |
+-----+

```

Impala Date and Time Functions

The underlying Impala data type for date and time data is [TIMESTAMP](#), which has both a date and a time portion. Functions that extract a single field, such as `hour()` or `minute()`, typically return an integer value. Functions that format the date portion, such as `date_add()` or `to_date()`, typically return a string value.

You can also adjust a `TIMESTAMP` value by adding or subtracting an `INTERVAL` expression. See [TIMESTAMP Data Type](#) on page 158 for details. `INTERVAL` expressions are also allowed as the second argument for the `date_add()` and `date_sub()` functions, rather than integers.

Some of these functions are affected by the setting of the `--use_local_tz_for_unix_timestamp_conversions` startup flag for the `impalad` daemon. This setting is off by default, meaning that functions such as `from_unixtime()` and `unix_timestamp()` consider the input values to always represent the UTC time zone. This setting also applies when you `CAST()` a `BIGINT` value to `TIMESTAMP`, or a `TIMESTAMP` value to `BIGINT`. When this setting is enabled, these functions and operations convert to and from values representing the local time zone. See [TIMESTAMP Data Type](#) on page 158 for details about how Impala handles time zone considerations for the `TIMESTAMP` data type.

Function reference:

Impala supports the following data and time functions:

```
add_months(timestamp date, int months), add_months(timestamp date, bigint months)
```

Purpose: Returns the specified date and time plus some number of months.

Return type: `timestamp`

Usage notes:

Same as [months_add\(\)](#). Available in Impala 1.4 and higher. For compatibility when porting code with vendor extensions.

Examples:

The following examples demonstrate adding months to construct the same day of the month in a different month; how if the current day of the month does not exist in the target month, the last day of that month is substituted; and how a negative argument produces a return value from a previous month.

```
select now(), add_months(now(), 2);
+-----+-----+
| now() | add_months(now(), 2) |
+-----+-----+
| 2016-05-31 10:47:00.429109000 | 2016-07-31 10:47:00.429109000 |
+-----+-----+

select now(), add_months(now(), 1);
+-----+-----+
| now() | add_months(now(), 1) |
+-----+-----+
| 2016-05-31 10:47:14.540226000 | 2016-06-30 10:47:14.540226000 |
+-----+-----+

select now(), add_months(now(), -1);
+-----+-----+
| now() | add_months(now(), -1) |
+-----+-----+
| 2016-05-31 10:47:31.732298000 | 2016-04-30 10:47:31.732298000 |
+-----+-----+
```

adddate(timestamp startdate, int days), adddate(timestamp startdate, bigint days),

Purpose: Adds a specified number of days to a `TIMESTAMP` value. Similar to `date_add()`, but starts with an actual `TIMESTAMP` value instead of a string that is converted to a `TIMESTAMP`.

Return type: timestamp

Examples:

The following examples show how to add a number of days to a `TIMESTAMP`. The number of days can also be negative, which gives the same effect as the `subdate()` function.

```
select now() as right_now, adddate(now(), 30) as now_plus_30;
+-----+-----+
| right_now | now_plus_30 |
+-----+-----+
| 2016-05-20 10:23:08.640111000 | 2016-06-19 10:23:08.640111000 |
+-----+-----+

select now() as right_now, adddate(now(), -15) as now_minus_15;
+-----+-----+
| right_now | now_minus_15 |
+-----+-----+
| 2016-05-20 10:23:38.214064000 | 2016-05-05 10:23:38.214064000 |
+-----+-----+
```

current_timestamp()

Purpose: Alias for the `now()` function.

Return type: timestamp

Examples:

```
select now(), current_timestamp();
```

```

+-----+-----+
| now() | current_timestamp() |
+-----+-----+
| 2016-05-19 16:10:14.237849000 | 2016-05-19 16:10:14.237849000 |
+-----+-----+

select current_timestamp() as right_now,
       current_timestamp() + interval 3 hours as in_three_hours;
+-----+-----+
| right_now | in_three_hours |
+-----+-----+
| 2016-05-19 16:13:20.017117000 | 2016-05-19 19:13:20.017117000 |
+-----+-----+

```

date_add(timestamp startdate, int days), date_add(timestamp startdate, interval expression)

Purpose: Adds a specified number of days to a `TIMESTAMP` value. With an `INTERVAL` expression as the second argument, you can calculate a delta value using other units such as weeks, years, hours, seconds, and so on; see [TIMESTAMP Data Type](#) on page 158 for details.

Return type: timestamp

Examples:

The following example shows the simplest usage, of adding a specified number of days to a `TIMESTAMP` value:

```

select now() as right_now, date_add(now(), 7) as next_week;
+-----+-----+
| right_now | next_week |
+-----+-----+
| 2016-05-20 11:03:48.687055000 | 2016-05-27 11:03:48.687055000 |
+-----+-----+

```

The following examples show the shorthand notation of an `INTERVAL` expression, instead of specifying the precise number of days. The `INTERVAL` notation also lets you work with units smaller than a single day.

```

select now() as right_now, date_add(now(), interval 3 weeks) as in_3_weeks;
+-----+-----+
| right_now | in_3_weeks |
+-----+-----+
| 2016-05-20 11:05:39.173331000 | 2016-06-10 11:05:39.173331000 |
+-----+-----+

select now() as right_now, date_add(now(), interval 6 hours) as in_6_hours;
+-----+-----+
| right_now | in_6_hours |
+-----+-----+
| 2016-05-20 11:13:51.492536000 | 2016-05-20 17:13:51.492536000 |
+-----+-----+

```

Like all date/time functions that deal with months, `date_add()` handles nonexistent dates past the end of a month by setting the date to the last day of the month. The following example shows how the nonexistent date April 31st is normalized to April 30th:

```

select date_add(cast('2016-01-31' as timestamp), interval 3 months) as 'april_31st';
+-----+
| april_31st |
+-----+
| 2016-04-30 00:00:00 |
+-----+

```

date_part(string, timestamp)

Purpose: Similar to `EXTRACT()`, with the argument order reversed. Supports the same date and time units as `EXTRACT()`. For compatibility with SQL code containing vendor extensions.

Return type: int

Examples:

```
select date_part('year',now()) as current_year;
+-----+
| current_year |
+-----+
| 2016         |
+-----+

select date_part('hour',now()) as hour_of_day;
+-----+
| hour_of_day  |
+-----+
| 11           |
+-----+
```

date_sub(timestamp startdate, int days),date_sub(timestamp startdate, interval_expression)

Purpose: Subtracts a specified number of days from a `TIMESTAMP` value. With an `INTERVAL` expression as the second argument, you can calculate a delta value using other units such as weeks, years, hours, seconds, and so on; see [TIMESTAMP Data Type](#) on page 158 for details.

Return type: timestamp

Examples:

The following example shows the simplest usage, of subtracting a specified number of days from a `TIMESTAMP` value:

```
select now() as right_now, date_sub(now(), 7) as last_week;
+-----+-----+
| right_now          | last_week          |
+-----+-----+
| 2016-05-20 11:21:30.491011000 | 2016-05-13 11:21:30.491011000 |
+-----+-----+
```

The following examples show the shorthand notation of an `INTERVAL` expression, instead of specifying the precise number of days. The `INTERVAL` notation also lets you work with units smaller than a single day.

```
select now() as right_now, date_sub(now(), interval 3 weeks) as 3_weeks_ago;
+-----+-----+
| right_now          | 3_weeks_ago       |
+-----+-----+
| 2016-05-20 11:23:05.176953000 | 2016-04-29 11:23:05.176953000 |
+-----+-----+

select now() as right_now, date_sub(now(), interval 6 hours) as 6_hours_ago;
+-----+-----+
| right_now          | 6_hours_ago       |
+-----+-----+
| 2016-05-20 11:23:35.439631000 | 2016-05-20 05:23:35.439631000 |
+-----+-----+
```

Like all date/time functions that deal with months, `date_add()` handles nonexistent dates past the end of a month by setting the date to the last day of the month. The following example shows how the nonexistent date April 31st is normalized to April 30th:

```
select date_sub(cast('2016-05-31' as timestamp), interval 1 months) as 'april_31st';
+-----+
| april_31st      |
+-----+
| 2016-04-30 00:00:00 |
+-----+
```

datediff(timestamp enddate, timestamp startdate)

Purpose: Returns the number of days between two `TIMESTAMP` values.

Return type: `int`

Usage notes:

If the first argument represents a later date than the second argument, the return value is positive. If both arguments represent the same date, the return value is zero. The time portions of the `TIMESTAMP` values are irrelevant. For example, 11:59 PM on one day and 12:01 on the next day represent a `datediff()` of -1 because the date/time values represent different days, even though the `TIMESTAMP` values differ by only 2 minutes.

Examples:

The following example shows how comparing a “late” value with an “earlier” value produces a positive number. In this case, the result is $(365 * 5) + 1$, because one of the intervening years is a leap year.

```
select now() as right_now, datediff(now() + interval 5 years, now()) as in_5_years;
+-----+-----+
| right_now          | in_5_years |
+-----+-----+
| 2016-05-20 13:43:55.873826000 | 1826       |
+-----+-----+
```

The following examples show how the return value represent the number of days between the associated dates, regardless of the time portion of each `TIMESTAMP`. For example, different times on the same day produce a `date_diff()` of 0, regardless of which one is earlier or later. But if the arguments represent different dates, `date_diff()` returns a non-zero integer value, regardless of the time portions of the dates.

```
select now() as right_now, datediff(now(), now() + interval 4 hours) as in_4_hours;
+-----+-----+
| right_now          | in_4_hours |
+-----+-----+
| 2016-05-20 13:42:05.302747000 | 0          |
+-----+-----+

select now() as right_now, datediff(now(), now() - interval 4 hours) as 4_hours_ago;
+-----+-----+
| right_now          | 4_hours_ago |
+-----+-----+
| 2016-05-20 13:42:21.134958000 | 0          |
+-----+-----+

select now() as right_now, datediff(now(), now() + interval 12 hours) as in_12_hours;
+-----+-----+
| right_now          | in_12_hours |
+-----+-----+
| 2016-05-20 13:42:44.765873000 | -1         |
+-----+-----+

select now() as right_now, datediff(now(), now() - interval 18 hours) as 18_hours_ago;
+-----+-----+
| right_now          | 18_hours_ago |
+-----+-----+
| 2016-05-20 13:54:38.829827000 | 1          |
+-----+-----+
```

day(timestamp date), dayofmonth(timestamp date)

Purpose: Returns the day field from the date portion of a `TIMESTAMP`. The value represents the day of the month, therefore is in the range 1-31, or less for months without 31 days.

Return type: `int`

Examples:

The following examples show how the day value corresponds to the day of the month, resetting back to 1 at the start of each month.

```
select now(), day(now());
+-----+-----+
| now() | day(now()) |
+-----+-----+
| 2016-05-20 15:01:51.042185000 | 20 |
+-----+-----+

select now() + interval 11 days, day(now() + interval 11 days);
+-----+-----+
| now() + interval 11 days | day(now() + interval 11 days) |
+-----+-----+
| 2016-05-31 15:05:56.843139000 | 31 |
+-----+-----+

select now() + interval 12 days, day(now() + interval 12 days);
+-----+-----+
| now() + interval 12 days | day(now() + interval 12 days) |
+-----+-----+
| 2016-06-01 15:06:05.074236000 | 1 |
+-----+-----+
```

The following examples show how the day value is NULL for nonexistent dates or misformatted date strings.

```
-- 2016 is a leap year, so it has a Feb. 29.
select day('2016-02-29');
+-----+
| day('2016-02-29') |
+-----+
| 29 |
+-----+

-- 2015 is not a leap year, so Feb. 29 is nonexistent.
select day('2015-02-29');
+-----+
| day('2015-02-29') |
+-----+
| NULL |
+-----+

-- A string that does not match the expected YYYY-MM-DD format
-- produces an invalid TIMESTAMP, causing day() to return NULL.
select day('2016-02-028');
+-----+
| day('2016-02-028') |
+-----+
| NULL |
+-----+
```

dayname(timestamp date)

Purpose: Returns the day field from a `TIMESTAMP` value, converted to the string corresponding to that day name. The range of return values is 'Sunday' to 'Saturday'. Used in report-generating queries, as an alternative to calling `dayofweek()` and turning that numeric return value into a string using a `CASE` expression.

Return type: string

Examples:

The following examples show the day name associated with `TIMESTAMP` values representing different days.

```
select now() as right_now,
       dayofweek(now()) as todays_day_of_week,
       dayname(now()) as todays_day_name;
+-----+-----+-----+
| right_now | todays_day_of_week | todays_day_name |
+-----+-----+-----+
```

```

+-----+-----+-----+
| 2016-05-31 10:57:03.953670000 | 3 | Tuesday |
+-----+-----+-----+

select now() + interval 1 day as tomorrow,
       dayname(now() + interval 1 day) as tomorrows_day_name;
+-----+-----+-----+
| tomorrow | tomorrows_day_name |
+-----+-----+-----+
| 2016-06-01 10:58:53.945761000 | Wednesday |
+-----+-----+-----+

```

dayofweek(timestamp date)

Purpose: Returns the day field from the date portion of a `TIMESTAMP`, corresponding to the day of the week. The range of return values is 1 (Sunday) to 7 (Saturday).

Return type: int

Examples:

```

select now() as right_now,
       dayofweek(now()) as todays_day_of_week,
       dayname(now()) as todays_day_name;
+-----+-----+-----+
| right_now | todays_day_of_week | todays_day_name |
+-----+-----+-----+
| 2016-05-31 10:57:03.953670000 | 3 | Tuesday |
+-----+-----+-----+

```

dayofyear(timestamp date)

Purpose: Returns the day field from a `TIMESTAMP` value, corresponding to the day of the year. The range of return values is 1 (January 1) to 366 (December 31 of a leap year).

Return type: int

Examples:

The following examples show return values from the `dayofyear()` function. The same date in different years returns a different day number for all dates after February 28, because 2016 is a leap year while 2015 is not a leap year.

```

select now() as right_now,
       dayofyear(now()) as today_day_of_year;
+-----+-----+
| right_now | today_day_of_year |
+-----+-----+
| 2016-05-31 11:05:48.314932000 | 152 |
+-----+-----+

select now() - interval 1 year as last_year,
       dayofyear(now() - interval 1 year) as year_ago_day_of_year;
+-----+-----+
| last_year | year_ago_day_of_year |
+-----+-----+
| 2015-05-31 11:07:03.733689000 | 151 |
+-----+-----+

```

days_add(timestamp startdate, int days), days_add(timestamp startdate, bigint days)

Purpose: Adds a specified number of days to a `TIMESTAMP` value. Similar to `date_add()`, but starts with an actual `TIMESTAMP` value instead of a string that is converted to a `TIMESTAMP`.

Return type: timestamp

Examples:

```
select now() as right_now, days_add(now(), 31) as 31_days_later;
+-----+-----+
| right_now          | 31_days_later          |
+-----+-----+
| 2016-05-31 11:12:32.216764000 | 2016-07-01 11:12:32.216764000 |
+-----+-----+
```

days_sub(timestamp startdate, int days), days_sub(timestamp startdate, bigint days)

Purpose: Subtracts a specified number of days from a `TIMESTAMP` value. Similar to `date_sub()`, but starts with an actual `TIMESTAMP` value instead of a string that is converted to a `TIMESTAMP`.

Return type: `timestamp`

Examples:

```
select now() as right_now, days_sub(now(), 31) as 31_days_ago;
+-----+-----+
| right_now          | 31_days_ago            |
+-----+-----+
| 2016-05-31 11:13:42.163905000 | 2016-04-30 11:13:42.163905000 |
+-----+-----+
```

extract(timestamp, string unit) extract(unit FROM timestamp)

Purpose: Returns one of the numeric date or time fields from a `TIMESTAMP` value.

Unit argument: The unit string can be one of `year`, `month`, `day`, `hour`, `minute`, `second`, or `millisecond`. This argument value is case-insensitive.

In Impala 2.0 and higher, you can use special syntax rather than a regular function call, for compatibility with code that uses the SQL-99 format with the `FROM` keyword. With this style, the unit names are identifiers rather than `STRING` literals. For example, the following calls are both equivalent:

```
extract(year from now());
extract(now(), "year");
```

Usage notes:

Typically used in `GROUP BY` queries to arrange results by hour, day, month, and so on. You can also use this function in an `INSERT ... SELECT` into a partitioned table to split up `TIMESTAMP` values into individual parts, if the partitioned table has separate partition key columns representing year, month, day, and so on. If you need to divide by more complex units of time, such as by week or by quarter, use the `TRUNC()` function instead.

Return type: `int`

Examples:

```
select now() as right_now,
       extract(year from now()) as this_year,
       extract(month from now()) as this_month;
+-----+-----+-----+
| right_now          | this_year | this_month |
+-----+-----+-----+
| 2016-05-31 11:18:43.310328000 | 2016      | 5          |
+-----+-----+-----+
```

```
select now() as right_now,
       extract(day from now()) as this_day,
       extract(hour from now()) as this_hour;
+-----+-----+-----+
| right_now          | this_day | this_hour |
+-----+-----+-----+
```

```
| 2016-05-31 11:19:24.025303000 | 31 | 11 |
+-----+-----+-----+
```

from_timestamp(datetime timestamp, pattern string)

Purpose: Converts a `TIMESTAMP` value into a string representing the same value.

Return type: `string`

Added in: CDH 5.5.0 (Impala 2.3.0)

Usage notes:

The `from_timestamp()` function provides a flexible way to convert `TIMESTAMP` values into arbitrary string formats for reporting purposes.

Because Impala implicitly converts string values into `TIMESTAMP`, you can pass date/time values represented as strings (in the standard `yyyy-MM-dd HH:mm:ss.SSS` format) to this function. The result is a string using different separator characters, order of fields, spelled-out month names, or other variation of the date/time string representation.

The allowed tokens for the pattern string are the same as for the `from_unixtime()` function.

Examples:

The following examples show different ways to format a `TIMESTAMP` value as a string:

```
-- Reformat arbitrary TIMESTAMP value.
select from_timestamp(now(), 'yyyy/MM/dd');
+-----+-----+-----+
| from_timestamp(now(), 'yyyy/mm/dd') |
+-----+-----+-----+
| 2017/10/01 |
+-----+-----+-----+

-- Reformat string literal representing date/time.
select from_timestamp('1984-09-25', 'yyyy/MM/dd');
+-----+-----+-----+
| from_timestamp('1984-09-25', 'yyyy/mm/dd') |
+-----+-----+-----+
| 1984/09/25 |
+-----+-----+-----+

-- Alternative format for reporting purposes.
select from_timestamp('1984-09-25 16:45:30.125', 'MMM dd, yyyy HH:mm:ss.SSS');
+-----+-----+-----+
| from_timestamp('1984-09-25 16:45:30.125', 'mmm dd, yyyy hh:mm:ss.sss') |
+-----+-----+-----+
| Sep 25, 1984 16:45:30.125 |
+-----+-----+-----+
```

from_unixtime(bigint unixtime[, string format])

Purpose: Converts the number of seconds from the Unix epoch to the specified time into a string in the local time zone.

Return type: `string`

In Impala 2.2.0 and higher, built-in functions that accept or return integers representing `TIMESTAMP` values use the `BIGINT` type for parameters and return values, rather than `INT`. This change lets the date and time functions avoid an overflow error that would otherwise occur on January 19th, 2038 (known as the [“Year 2038 problem”](#) or [“Y2K38 problem”](#)). This change affects the `from_unixtime()` and `unix_timestamp()` functions. You might need to change application code that interacts with these functions, change the types of columns that store the return values, or add `CAST()` calls to SQL statements that call these functions.

Usage notes:

The format string accepts the variations allowed for the `TIMESTAMP` data type: date plus time, date by itself, time by itself, and optional fractional seconds for the time. See [TIMESTAMP Data Type](#) on page 158 for details.

Currently, the format string is case-sensitive, especially to distinguish `m` for minutes and `M` for months. In Impala 1.3 and later, you can switch the order of elements, use alternative separator characters, and use a different number of placeholders for each unit. Adding more instances of `y`, `d`, `H`, and so on produces output strings zero-padded to the requested number of characters. The exception is `M` for months, where `M` produces a non-padded value such as `3`, `MM` produces a zero-padded value such as `03`, `MMM` produces an abbreviated month name such as `Mar`, and sequences of 4 or more `M` are not allowed. A date string including all fields could be `"yyyy-MM-dd HH:mm:ss.SSSSSS"`, `"dd/MM/yyyy HH:mm:ss.SSSSSS"`, `"MMM dd, yyyy HH.mm.ss (SSSSSS)"` or other combinations of placeholders and separator characters.

The way this function deals with time zones when converting to or from `TIMESTAMP` values is affected by the `--use_local_tz_for_unix_timestamp_conversions` startup flag for the `impalad` daemon. See [TIMESTAMP Data Type](#) on page 158 for details about how Impala handles time zone considerations for the `TIMESTAMP` data type.



Note:

The more flexible format strings allowed with the built-in functions do not change the rules about using `CAST()` to convert from a string to a `TIMESTAMP` value. Strings being converted through `CAST()` must still have the elements in the specified order and use the specified delimiter characters, as described in [TIMESTAMP Data Type](#) on page 158.

Examples:

```
select from_unixtime(1392394861,"yyyy-MM-dd HH:mm:ss.SSSS");
+-----+
| from_unixtime(1392394861, 'yyyy-mm-dd hh:mm:ss.ssss') |
+-----+
| 2014-02-14 16:21:01.0000 |
+-----+

select from_unixtime(1392394861,"yyyy-MM-dd");
+-----+
| from_unixtime(1392394861, 'yyyy-mm-dd') |
+-----+
| 2014-02-14 |
+-----+

select from_unixtime(1392394861,"HH:mm:ss.SSSS");
+-----+
| from_unixtime(1392394861, 'hh:mm:ss.ssss') |
+-----+
| 16:21:01.0000 |
+-----+

select from_unixtime(1392394861,"HH:mm:ss");
+-----+
| from_unixtime(1392394861, 'hh:mm:ss') |
+-----+
| 16:21:01 |
+-----+
```

`unix_timestamp()` and `from_unixtime()` are often used in combination to convert a `TIMESTAMP` value into a particular string format. For example:

```
select from_unixtime(unix_timestamp(now() + interval 3 days),
'yyyy/MM/dd HH:mm') as yyyy_mm_dd_hh_mm;
+-----+
| yyyy_mm_dd_hh_mm |
+-----+
| 2016/06/03 11:38 |
+-----+
```

from_utc_timestamp(timestamp, string timezone)

Purpose: Converts a specified UTC timestamp value into the appropriate value for a specified time zone.

Return type: timestamp

Usage notes: Often used to translate UTC time zone data stored in a table back to the local date and time for reporting. The opposite of the `to_utc_timestamp()` function.

To determine the time zone of the server you are connected to, in CDH 5.5 / Impala 2.3 and higher you can call the `timeofday()` function, which includes the time zone specifier in its return value. Remember that with cloud computing, the server you interact with might be in a different time zone than you are, or different sessions might connect to servers in different time zones, or a cluster might include servers in more than one time zone.

Examples:

See discussion of time zones in [TIMESTAMP Data Type](#) on page 158 for information about using this function for conversions between the local time zone and UTC.

The following example shows how when `TIMESTAMP` values representing the UTC time zone are stored in a table, a query can display the equivalent local date and time for a different time zone.

```
with t1 as (select cast('2016-06-02 16:25:36.116143000' as timestamp) as utc_datetime)
select utc_datetime as 'Date/time in Greenwich UK',
       from_utc_timestamp(utc_datetime, 'PDT')
       as 'Equivalent in California USA'
from t1;
```

date/time in greenwich uk	equivalent in california usa
2016-06-02 16:25:36.116143000	2016-06-02 09:25:36.116143000

The following example shows that for a date and time when daylight savings is in effect (`PDT`), the UTC time is 7 hours ahead of the local California time; while when daylight savings is not in effect (`PST`), the UTC time is 8 hours ahead of the local California time.

```
select now() as local_datetime,
       to_utc_timestamp(now(), 'PDT') as utc_datetime;
```

local_datetime	utc_datetime
2016-05-31 11:50:02.316883000	2016-05-31 18:50:02.316883000

```
select '2016-01-05' as local_datetime,
       to_utc_timestamp('2016-01-05', 'PST') as utc_datetime;
```

local_datetime	utc_datetime
2016-01-05	2016-01-05 08:00:00

hour(timestamp date)

Purpose: Returns the hour field from a `TIMESTAMP` field.

Return type: int

Examples:

```
select now() as right_now, hour(now()) as current_hour;
```

right_now	current_hour
2016-06-01 14:14:12.472846000	14


```

+-----+-----+
select now() + interval 12 hours as 12_hours_from_now,
       hour(now() + interval 12 hours) as hour_in_12_hours;
+-----+-----+
| 12_hours_from_now          | hour_in_12_hours |
+-----+-----+
| 2016-06-02 02:15:32.454750000 | 2                |
+-----+-----+

```

hours_add(timestamp date, int hours), hours_add(timestamp date, bigint hours)

Purpose: Returns the specified date and time plus some number of hours.

Return type: timestamp

Examples:

```

select now() as right_now,
       hours_add(now(), 12) as in_12_hours;
+-----+-----+
| right_now                  | in_12_hours       |
+-----+-----+
| 2016-06-01 14:19:48.948107000 | 2016-06-02 02:19:48.948107000 |
+-----+-----+

```

hours_sub(timestamp date, int hours), hours_sub(timestamp date, bigint hours)

Purpose: Returns the specified date and time minus some number of hours.

Return type: timestamp

Examples:

```

select now() as right_now,
       hours_sub(now(), 18) as 18_hours_ago;
+-----+-----+
| right_now                  | 18_hours_ago      |
+-----+-----+
| 2016-06-01 14:23:13.868150000 | 2016-05-31 20:23:13.868150000 |
+-----+-----+

```

int_months_between(timestamp newer, timestamp older)

Purpose: Returns the number of months between the date portions of two `TIMESTAMP` values, as an `INT` representing only the full months that passed.

Return type: int

Added in: CDH 5.5.0 (Impala 2.3.0)

Usage notes:

Typically used in business contexts, for example to determine whether a specified number of months have passed or whether some end-of-month deadline was reached.

The method of determining the number of elapsed months includes some special handling of months with different numbers of days that creates edge cases for dates between the 28th and 31st days of certain months. See `months_between()` for details. The `int_months_between()` result is essentially the `floor()` of the `months_between()` result.

If either value is `NULL`, which could happen for example when converting a nonexistent date string such as `'2015-02-29'` to a `TIMESTAMP`, the result is also `NULL`.

If the first argument represents an earlier time than the second argument, the result is negative.

Examples:

```
/* Less than a full month = 0. */
select int_months_between('2015-02-28', '2015-01-29');
+-----+
| int_months_between('2015-02-28', '2015-01-29') |
+-----+
| 0 |
+-----+
```

```
/* Last day of month to last day of next month = 1. */
select int_months_between('2015-02-28', '2015-01-31');
+-----+
| int_months_between('2015-02-28', '2015-01-31') |
+-----+
| 1 |
+-----+
```

```
/* Slightly less than 2 months = 1. */
select int_months_between('2015-03-28', '2015-01-31');
+-----+
| int_months_between('2015-03-28', '2015-01-31') |
+-----+
| 1 |
+-----+
```

```
/* 2 full months (identical days of the month) = 2. */
select int_months_between('2015-03-31', '2015-01-31');
+-----+
| int_months_between('2015-03-31', '2015-01-31') |
+-----+
| 2 |
+-----+
```

```
/* Last day of month to last day of month-after-next = 2. */
select int_months_between('2015-03-31', '2015-01-30');
+-----+
| int_months_between('2015-03-31', '2015-01-30') |
+-----+
| 2 |
+-----+
```

microseconds_add(timestamp date, int microseconds),microseconds_add(timestamp date, bigint microseconds)

Purpose: Returns the specified date and time plus some number of microseconds.

Return type: timestamp

Examples:

```
select now() as right_now,
       microseconds_add(now(), 500000) as half_a_second_from_now;
+-----+-----+
| right_now | half_a_second_from_now |
+-----+-----+
| 2016-06-01 14:25:11.455051000 | 2016-06-01 14:25:11.955051000 |
+-----+-----+
```

microseconds_sub(timestamp date, int microseconds),microseconds_sub(timestamp date, bigint microseconds)

Purpose: Returns the specified date and time minus some number of microseconds.

Return type: timestamp

Examples:

```
select now() as right_now,
```

```

microseconds_sub(now(), 500000) as half_a_second_ago;
+-----+-----+
| right_now                | half_a_second_ago |
+-----+-----+
| 2016-06-01 14:26:16.509990000 | 2016-06-01 14:26:16.009990000 |
+-----+-----+

```

millisecond(timestamp)

Purpose: Returns the millisecond portion of a `TIMESTAMP` value.

Return type: `int`

Added in: CDH 5.7.0 (Impala 2.5.0)

Usage notes:

The millisecond value is truncated, not rounded, if the `TIMESTAMP` value contains more than 3 significant digits to the right of the decimal point.

Examples:

252.4 milliseconds truncated to 252.

```

select now(), millisecond(now());
+-----+-----+
| now()                | millisecond(now()) |
+-----+-----+
| 2016-03-14 22:30:25.252400000 | 252 |
+-----+-----+

```

761.767 milliseconds truncated to 761.

```

select now(), millisecond(now());
+-----+-----+
| now()                | millisecond(now()) |
+-----+-----+
| 2016-03-14 22:30:58.761767000 | 761 |
+-----+-----+

```

milliseconds_add(timestamp date, int milliseconds), milliseconds_add(timestamp date, bigint milliseconds)

Purpose: Returns the specified date and time plus some number of milliseconds.

Return type: `timestamp`

Examples:

```

select now() as right_now,
       milliseconds_add(now(), 1500) as 1_point_5_seconds_from_now;
+-----+-----+
| right_now                | 1_point_5_seconds_from_now |
+-----+-----+
| 2016-06-01 14:30:30.067366000 | 2016-06-01 14:30:31.567366000 |
+-----+-----+

```

milliseconds_sub(timestamp date, int milliseconds), milliseconds_sub(timestamp date, bigint milliseconds)

Purpose: Returns the specified date and time minus some number of milliseconds.

Return type: `timestamp`

Examples:

```

select now() as right_now,

```

```

milliseconds_sub(now(), 1500) as 1_point_5_seconds_ago;
+-----+-----+
| right_now          | 1_point_5_seconds_ago |
+-----+-----+
| 2016-06-01 14:30:53.467140000 | 2016-06-01 14:30:51.967140000 |
+-----+-----+

```

minute(timestamp date)

Purpose: Returns the minute field from a `TIMESTAMP` value.

Return type: int

Examples:

```

select now() as right_now, minute(now()) as current_minute;
+-----+-----+
| right_now          | current_minute |
+-----+-----+
| 2016-06-01 14:34:08.051702000 | 34 |
+-----+-----+

```

minutes_add(timestamp date, int minutes), minutes_add(timestamp date, bigint minutes)

Purpose: Returns the specified date and time plus some number of minutes.

Return type: timestamp

Examples:

```

select now() as right_now, minutes_add(now(), 90) as 90_minutes_from_now;
+-----+-----+
| right_now          | 90_minutes_from_now |
+-----+-----+
| 2016-06-01 14:36:04.887095000 | 2016-06-01 16:06:04.887095000 |
+-----+-----+

```

minutes_sub(timestamp date, int minutes), minutes_sub(timestamp date, bigint minutes)

Purpose: Returns the specified date and time minus some number of minutes.

Return type: timestamp

Examples:

```

select now() as right_now, minutes_sub(now(), 90) as 90_minutes_ago;
+-----+-----+
| right_now          | 90_minutes_ago |
+-----+-----+
| 2016-06-01 14:36:32.643061000 | 2016-06-01 13:06:32.643061000 |
+-----+-----+

```

month(timestamp date)

Purpose: Returns the month field, represented as an integer, from the date portion of a `TIMESTAMP`.

Return type: int

Examples:

```

select now() as right_now, month(now()) as current_month;
+-----+-----+
| right_now          | current_month |
+-----+-----+
| 2016-06-01 14:43:37.141542000 | 6 |
+-----+-----+

```

`months_add(timestamp date, int months), months_add(timestamp date, bigint months)`

Purpose: Returns the specified date and time plus some number of months.

Return type: timestamp

Examples:

The following example shows the effects of adding some number of months to a `TIMESTAMP` value, using both the `months_add()` function and its `add_months()` alias. These examples use `trunc()` to strip off the time portion and leave just the date.

```
with t1 as (select trunc(now(), 'dd') as today)
  select today, months_add(today,1) as next_month from t1;
```

today	next_month
2016-05-19 00:00:00	2016-06-19 00:00:00

```
with t1 as (select trunc(now(), 'dd') as today)
  select today, add_months(today,1) as next_month from t1;
```

today	next_month
2016-05-19 00:00:00	2016-06-19 00:00:00

The following examples show how if `months_add()` would return a nonexistent date, due to different months having different numbers of days, the function returns a `TIMESTAMP` from the last day of the relevant month. For example, adding one month to January 31 produces a date of February 29th in the year 2016 (a leap year), and February 28th in the year 2015 (a non-leap year).

```
with t1 as (select cast('2016-01-31' as timestamp) as jan_31)
  select jan_31, months_add(jan_31,1) as feb_31 from t1;
```

jan_31	feb_31
2016-01-31 00:00:00	2016-02-29 00:00:00

```
with t1 as (select cast('2015-01-31' as timestamp) as jan_31)
  select jan_31, months_add(jan_31,1) as feb_31 from t1;
```

jan_31	feb_31
2015-01-31 00:00:00	2015-02-28 00:00:00

`months_between(timestamp newer, timestamp older)`

Purpose: Returns the number of months between the date portions of two `TIMESTAMP` values. Can include a fractional part representing extra days in addition to the full months between the dates. The fractional component is computed by dividing the difference in days by 31 (regardless of the month).

Return type: double

Added in: CDH 5.5.0 (Impala 2.3.0)

Usage notes:

Typically used in business contexts, for example to determine whether a specified number of months have passed or whether some end-of-month deadline was reached.

If the only consideration is the number of full months and any fractional value is not significant, use `int_months_between()` instead.

The method of determining the number of elapsed months includes some special handling of months with different numbers of days that creates edge cases for dates between the 28th and 31st days of certain months.

If either value is `NULL`, which could happen for example when converting a nonexistent date string such as `'2015-02-29'` to a `TIMESTAMP`, the result is also `NULL`.

If the first argument represents an earlier time than the second argument, the result is negative.

Examples:

The following examples show how dates that are on the same day of the month are considered to be exactly N months apart, even if the months have different numbers of days.

```

select months_between('2015-02-28', '2015-01-28');
+-----+
| months_between('2015-02-28', '2015-01-28') |
+-----+
| 1 |
+-----+

select months_between(now(), now() + interval 1 month);
+-----+
| months_between(now(), now() + interval 1 month) |
+-----+
| -1 |
+-----+

select months_between(now() + interval 1 year, now());
+-----+
| months_between(now() + interval 1 year, now()) |
+-----+
| 12 |
+-----+
    
```

The following examples show how dates that are on the last day of the month are considered to be exactly N months apart, even if the months have different numbers of days. For example, from January 28th to February 28th is exactly one month because the day of the month is identical; January 31st to February 28th is exactly one month because in both cases it is the last day of the month; but January 29th or 30th to February 28th is considered a fractional month.

```

select months_between('2015-02-28', '2015-01-31');
+-----+
| months_between('2015-02-28', '2015-01-31') |
+-----+
| 1 |
+-----+

select months_between('2015-02-28', '2015-01-29');
+-----+
| months_between('2015-02-28', '2015-01-29') |
+-----+
| 0.967741935483871 |
+-----+

select months_between('2015-02-28', '2015-01-30');
+-----+
| months_between('2015-02-28', '2015-01-30') |
+-----+
| 0.935483870967742 |
+-----+
    
```

The following examples show how dates that are not a precise number of months apart result in a fractional return value.

```

select months_between('2015-03-01', '2015-01-28');
+-----+
| months_between('2015-03-01', '2015-01-28') |
+-----+
| 1.129032258064516 |
+-----+
    
```

```

+-----+
select months_between('2015-03-01', '2015-02-28');
+-----+
| months_between('2015-03-01', '2015-02-28') |
+-----+
| 0.1290322580645161 |
+-----+

select months_between('2015-06-02', '2015-05-29');
+-----+
| months_between('2015-06-02', '2015-05-29') |
+-----+
| 0.1290322580645161 |
+-----+

select months_between('2015-03-01', '2015-01-25');
+-----+
| months_between('2015-03-01', '2015-01-25') |
+-----+
| 1.225806451612903 |
+-----+

select months_between('2015-03-01', '2015-02-25');
+-----+
| months_between('2015-03-01', '2015-02-25') |
+-----+
| 0.2258064516129032 |
+-----+

select months_between('2015-02-28', '2015-02-01');
+-----+
| months_between('2015-02-28', '2015-02-01') |
+-----+
| 0.8709677419354839 |
+-----+

select months_between('2015-03-28', '2015-03-01');
+-----+
| months_between('2015-03-28', '2015-03-01') |
+-----+
| 0.8709677419354839 |
+-----+

```

The following examples show how the time portion of the `TIMESTAMP` values are irrelevant for calculating the month interval. Even the fractional part of the result only depends on the number of full days between the argument values, regardless of the time portion.

```

select months_between('2015-05-28 23:00:00', '2015-04-28 11:45:00');
+-----+
| months_between('2015-05-28 23:00:00', '2015-04-28 11:45:00') |
+-----+
| 1 |
+-----+

select months_between('2015-03-28', '2015-03-01');
+-----+
| months_between('2015-03-28', '2015-03-01') |
+-----+
| 0.8709677419354839 |
+-----+

select months_between('2015-03-28 23:00:00', '2015-03-01 11:45:00');
+-----+
| months_between('2015-03-28 23:00:00', '2015-03-01 11:45:00') |
+-----+
| 0.8709677419354839 |
+-----+

```

`months_sub(timestamp date, int months), months_sub(timestamp date, bigint months)`

Purpose: Returns the specified date and time minus some number of months.

Return type: timestamp

Examples:

```
with t1 as (select trunc(now(), 'dd') as today)
select today, months_sub(today,1) as last_month from t1;
```

today	last_month
2016-06-01 00:00:00	2016-05-01 00:00:00

nanoseconds_add(timestamp date, int nanoseconds), nanoseconds_add(timestamp date, bigint nanoseconds)

Purpose: Returns the specified date and time plus some number of nanoseconds.

Return type: timestamp

Examples:

```
select now() as right_now, nanoseconds_add(now(), 1) as 1_nanosecond_later;
```

right_now	1_nanosecond_later
2016-06-01 15:42:00.361026000	2016-06-01 15:42:00.361026001

-- 1 billion nanoseconds = 1 second.

```
select now() as right_now, nanoseconds_add(now(), 1e9) as 1_second_later;
```

right_now	1_second_later
2016-06-01 15:42:52.926706000	2016-06-01 15:42:53.926706000

nanoseconds_sub(timestamp date, int nanoseconds), nanoseconds_sub(timestamp date, bigint nanoseconds)

Purpose: Returns the specified date and time minus some number of nanoseconds.

Return type: timestamp

```
select now() as right_now, nanoseconds_sub(now(), 1) as 1_nanosecond_earlier;
```

right_now	1_nanosecond_earlier
2016-06-01 15:44:14.355837000	2016-06-01 15:44:14.355836999

-- 1 billion nanoseconds = 1 second.

```
select now() as right_now, nanoseconds_sub(now(), 1e9) as 1_second_earlier;
```

right_now	1_second_earlier
2016-06-01 15:44:54.474929000	2016-06-01 15:44:53.474929000

next_day(timestamp date, string weekday)

Purpose: Returns the date of the *weekday* that follows the specified *date*.

Return type: timestamp

Usage notes:

The *weekday* parameter is case-insensitive. The following values are accepted for *weekday*: "Sunday"/"Sun", "Monday"/"Mon", "Tuesday"/"Tue", "Wednesday"/"Wed", "Thursday"/"Thu", "Friday"/"Fri", "Saturday"/"Sat"

Calling the function with the current date and weekday returns the date that is one week later.

Examples:

```
select next_day('2013-12-25','Saturday');
-- Returns '2013-12-28 00:00:00' the first Saturday after December 25, 2013.
select next_day(to_timestamp('08-1987-21', 'mm-yyyy-dd'), 'Friday');
-- Returns '1987-08-28 00:00:00' the first Friday after August 28, 1987.

select next_day(now(), 'Thu');
-- Executed on 2018-07-12, the function returns '2018-07-13 00:00:00', one week
-- after the current date.
```

now()

Purpose: Returns the current date and time (in the local time zone) as a `TIMESTAMP` value.

Return type: `timestamp`

Usage notes:

To find a date/time value in the future or the past relative to the current date and time, add or subtract an `INTERVAL` expression to the return value of `now()`. See [TIMESTAMP Data Type](#) on page 158 for examples.

To produce a `TIMESTAMP` representing the current date and time that can be shared or stored without interoperability problems due to time zone differences, use the `to_utc_timestamp()` function and specify the time zone of the server. When `TIMESTAMP` data is stored in UTC form, any application that queries those values can convert them to the appropriate local time zone by calling the inverse function, `from_utc_timestamp()`.

To determine the time zone of the server you are connected to, in CDH 5.5 / Impala 2.3 and higher you can call the `timeofday()` function, which includes the time zone specifier in its return value. Remember that with cloud computing, the server you interact with might be in a different time zone than you are, or different sessions might connect to servers in different time zones, or a cluster might include servers in more than one time zone.

Any references to the `now()` function are evaluated at the start of a query. All calls to `now()` within the same query return the same value, and the value does not depend on how long the query takes.

Examples:

```
select now() as 'Current time in California USA',
       to_utc_timestamp(now(), 'PDT') as 'Current time in Greenwich UK';
+-----+-----+
| current time in california usa | current time in greenwich uk |
+-----+-----+
| 2016-06-01 15:52:08.980072000 | 2016-06-01 22:52:08.980072000 |
+-----+-----+

select now() as right_now,
       now() + interval 1 day as tomorrow,
       now() + interval 1 week - interval 3 hours as almost_a_week_from_now;
+-----+-----+-----+
| right_now | tomorrow | almost_a_week_from_now |
+-----+-----+-----+
| 2016-06-01 15:55:39.671690000 | 2016-06-02 15:55:39.671690000 | 2016-06-08
12:55:39.671690000 |
+-----+-----+-----+
```

second(timestamp date)

Purpose: Returns the second field from a `TIMESTAMP` value.

Return type: `int`

Examples:

```
select now() as right_now,
       second(now()) as seconds_in_current_minute;
```

right_now	seconds_in_current_minute
2016-06-01 16:03:57.006603000	57

seconds_add(timestamp date, int seconds), seconds_add(timestamp date, bigint seconds)

Purpose: Returns the specified date and time plus some number of seconds.

Return type: timestamp

Examples:

```
select now() as right_now,
       seconds_add(now(), 10) as 10_seconds_from_now;
```

right_now	10_seconds_from_now
2016-06-01 16:05:21.573935000	2016-06-01 16:05:31.573935000

seconds_sub(timestamp date, int seconds), seconds_sub(timestamp date, bigint seconds)

Purpose: Returns the specified date and time minus some number of seconds.

Return type: timestamp

Examples:

```
select now() as right_now,
       seconds_sub(now(), 10) as 10_seconds_ago;
```

right_now	10_seconds_ago
2016-06-01 16:06:03.467931000	2016-06-01 16:05:53.467931000

subdate(timestamp startdate, int days), subdate(timestamp startdate, bigint days),

Purpose: Subtracts a specified number of days from a `TIMESTAMP` value. Similar to `date_sub()`, but starts with an actual `TIMESTAMP` value instead of a string that is converted to a `TIMESTAMP`.

Return type: timestamp

Examples:

The following examples show how to subtract a number of days from a `TIMESTAMP`. The number of days can also be negative, which gives the same effect as the `adddate()` function.

```
select now() as right_now, subdate(now(), 30) as now_minus_30;
```

right_now	now_minus_30
2016-05-20 11:00:15.084991000	2016-04-20 11:00:15.084991000

```
select now() as right_now, subdate(now(), -15) as now_plus_15;
```

right_now	now_plus_15
2016-05-20 11:00:44.766091000	2016-06-04 11:00:44.766091000

timeofday()

Purpose: Returns a string representation of the current date and time, according to the time of the local system, including any time zone designation.

Return type: `string`

Added in: CDH 5.5.0 (Impala 2.3.0)

Usage notes: The result value represents similar information as the `now()` function, only as a `STRING` type and with somewhat different formatting. For example, the day of the week and the time zone identifier are included. This function is intended primarily for compatibility with SQL code from other systems that also have a `timeofday()` function. Prefer to use `now()` if practical for any new Impala code.

Examples:

The following examples show the format of the `timeofday()` return value, illustrate how that value is represented as a `STRING` that you can manipulate with string processing functions, and how the format compares with the return value from the `now()` function.

```
/* Date and time fields in a STRING return value. */
select timeofday();
+-----+
| timeofday() |
+-----+
| Tue Sep 01 15:13:18 2015 PDT |
+-----+

/* The return value can be processed by other string functions. */
select upper(timeofday());
+-----+
| upper(timeofday()) |
+-----+
| TUE SEP 01 15:13:38 2015 PDT |
+-----+

/* The TIMEOFDAY() result is formatted differently than NOW(). NOW() returns a TIMESTAMP.
*/
select now(), timeofday();
+-----+
| now() | timeofday() |
+-----+
| 2015-09-01 15:15:25.930021000 | Tue Sep 01 15:15:25 2015 PDT |
+-----+

/* You can strip out the time zone field to use in calls to from_utc_timestamp(). */
select regexp_replace(timeofday(), '.* ([A-Z]+)$', '\\1') as current_timezone;
+-----+
| current_timezone |
+-----+
| PDT |
+-----+
```

timestamp_cmp(timestamp t1, timestamp t2)

Purpose: Tests if one `TIMESTAMP` value is newer than, older than, or identical to another `TIMESTAMP`

Return type: `int` (either -1, 0, 1, or `NULL`)

Added in: CDH 5.5.0 (Impala 2.3.0)

Usage notes:

Usage notes: A comparison function for `TIMESTAMP` values that only tests whether the date and time increases, decreases, or stays the same. Similar to the `sign()` function for numeric values.

Examples:

The following examples show all the possible return values for `timestamp_cmp()`. If the first argument represents a later point in time than the second argument, the result is 1. The amount of the difference is irrelevant, only the fact that one argument is greater than or less than the other. If the first argument represents an earlier point in

time than the second argument, the result is -1. If the first and second arguments represent identical points in time, the result is 0. If either argument is NULL, the result is NULL.

```

/* First argument 'later' than second argument. */
select timestamp_cmp(now() + interval 70 minutes, now())
  as now_vs_in_70_minutes;
+-----+
| now_vs_in_70_minutes |
+-----+
| 1                    |
+-----+

select timestamp_cmp(now() +
  interval 3 days +
  interval 5 hours, now())
  as now_vs_days_from_now;
+-----+
| now_vs_days_from_now |
+-----+
| 1                    |
+-----+

/* First argument 'earlier' than second argument. */
select timestamp_cmp(now(), now() + interval 2 hours)
  as now_vs_2_hours_ago;
+-----+
| now_vs_2_hours_ago   |
+-----+
| -1                   |
+-----+

/* Both arguments represent the same point in time. */
select timestamp_cmp(now(), now())
  as identical_timestamps;
+-----+
| identical_timestamps |
+-----+
| 0                    |
+-----+

select timestamp_cmp
(
  now() + interval 1 hour,
  now() + interval 60 minutes
) as equivalent_date_times;
+-----+
| equivalent_date_times |
+-----+
| 0                    |
+-----+

/* Either argument NULL. */
select timestamp_cmp(now(), null)
  as now_vs_null;
+-----+
| now_vs_null          |
+-----+
| NULL                 |
+-----+

```

to_date(timestamp)

Purpose: Returns a string representation of the date field from a timestamp value.

Return type: string

Examples:

```
select now() as right_now,
       concat('The date today is ',to_date(now()),'.') as date_announcement;
+-----+-----+
| right_now                | date_announcement                |
+-----+-----+
| 2016-06-01 16:30:36.890325000 | The date today is 2016-06-01. |
+-----+-----+
```

to_timestamp(bigint unixtime),to_timestamp(string date, string pattern)

Purpose: Converts an integer or string representing a date/time value into the corresponding `TIMESTAMP` value.

Return type: `timestamp`

Added in: CDH 5.5.0 (Impala 2.3.0)

Usage notes:

An integer argument represents the number of seconds past the epoch (midnight on January 1, 1970). It is the converse of the `unix_timestamp()` function, which produces a `BIGINT` representing the number of seconds past the epoch.

A string argument, plus another string argument representing the pattern, turns an arbitrary string representation of a date and time into a true `TIMESTAMP` value. The ability to parse many kinds of date and time formats allows you to deal with temporal data from diverse sources, and if desired to convert to efficient `TIMESTAMP` values during your ETL process. Using `TIMESTAMP` directly in queries and expressions lets you perform date and time calculations without the overhead of extra function calls and conversions each time you reference the applicable columns.

Examples:

The following examples demonstrate how to convert an arbitrary string representation to `TIMESTAMP` based on a pattern string:

```
select to_timestamp('Sep 25, 1984', 'MMM dd, yyyy');
+-----+-----+
| to_timestamp('sep 25, 1984', 'mmm dd, yyyy') |
+-----+-----+
| 1984-09-25 00:00:00                          |
+-----+-----+

select to_timestamp('1984/09/25', 'yyyy/MM/dd');
+-----+-----+
| to_timestamp('1984/09/25', 'yyyy/mm/dd') |
+-----+-----+
| 1984-09-25 00:00:00                          |
+-----+-----+
```

The following examples show how to convert a `BIGINT` representing seconds past epoch into a `TIMESTAMP` value:

```
-- One day past the epoch.
select to_timestamp(24 * 60 * 60);
+-----+-----+
| to_timestamp(24 * 60 * 60) |
+-----+-----+
| 1970-01-02 00:00:00       |
+-----+-----+

-- 60 seconds in the past.
select now() as 'current date/time',
       unix_timestamp(now()) 'now in seconds',
       to_timestamp(unix_timestamp(now()) - 60) as '60 seconds ago';
+-----+-----+-----+
| current date/time                | now in seconds | 60 seconds ago |
+-----+-----+-----+
```

```
| 2017-10-01 22:03:46.885624000 | 1506895426 | 2017-10-01 22:02:46 |
+-----+-----+-----+
```

to_utc_timestamp(timestamp, string timezone)

Purpose: Converts a specified timestamp value in a specified time zone into the corresponding value for the UTC time zone.

Return type: timestamp

Usage notes:

Often used in combination with the `now()` function, to translate local date and time values to the UTC time zone for consistent representation on disk. The opposite of the `from_utc_timestamp()` function.

See discussion of time zones in [TIMESTAMP Data Type](#) on page 158 for information about using this function for conversions between the local time zone and UTC.

Examples:

The simplest use of this function is to turn a local date/time value to one with the standardized UTC time zone. Because the time zone specifier is not saved as part of the Impala `TIMESTAMP` value, all applications that refer to such data must agree in advance which time zone the values represent. If different parts of the ETL cycle, or different instances of the application, occur in different time zones, the ideal reference point is to convert all `TIMESTAMP` values to UTC for storage.

```
select now() as 'Current time in California USA',
       to_utc_timestamp(now(), 'PDT') as 'Current time in Greenwich UK';
+-----+-----+
| current time in california usa | current time in greenwich uk |
+-----+-----+
| 2016-06-01 15:52:08.980072000 | 2016-06-01 22:52:08.980072000 |
+-----+-----+
```

Once a value is converted to the UTC time zone by `to_utc_timestamp()`, it can be converted back to the local time zone with `from_utc_timestamp()`. You can combine these functions using different time zone identifiers to convert a `TIMESTAMP` between any two time zones. This example starts with a `TIMESTAMP` value representing Pacific Daylight Time, converts it to UTC, and converts it to the equivalent value in Eastern Daylight Time.

```
select now() as 'Current time in California USA',
       from_utc_timestamp(
         to_utc_timestamp(now(), 'PDT'),
         'EDT'
       ) as 'Current time in New York, USA';
+-----+-----+
| current time in california usa | current time in new york, usa |
+-----+-----+
| 2016-06-01 18:14:12.743658000 | 2016-06-01 21:14:12.743658000 |
+-----+-----+
```

trunc(timestamp, string unit)

Purpose: Strips off fields from a `TIMESTAMP` value.

Unit argument: The `unit` argument value is case-sensitive. This argument string can be one of:

- SYYYY, YYYY, YEAR, SYEAR, YYY, YY, Y: Year.
- Q: Quarter.
- MONTH, MON, MM, RM: Month.
- WW, W: Same day of the week as the first day of the month.
- DDD, DD, J: Day.
- DAY, DY, D: Starting day of the week. (Not necessarily the current day.)

- HH, HH12, HH24: Hour. A `TIMESTAMP` value truncated to the hour is always represented in 24-hour notation, even for the HH12 argument string.
- MI: Minute.

Usage notes:

Typically used in `GROUP BY` queries to aggregate results from the same hour, day, week, month, quarter, and so on. You can also use this function in an `INSERT ... SELECT` into a partitioned table to divide `TIMESTAMP` values into the correct partition.

Because the return value is a `TIMESTAMP`, if you cast the result of `TRUNC()` to `STRING`, you will often see zeroed-out portions such as `00:00:00` in the time field. If you only need the individual units such as hour, day, month, or year, use the `EXTRACT()` function instead. If you need the individual units from a truncated `TIMESTAMP` value, run the `TRUNCATE()` function on the original value, then run `EXTRACT()` on the result.

Return type: `timestamp`

Examples:

The following example shows how the argument 'Q' returns a `TIMESTAMP` representing the beginning of the appropriate calendar quarter. This return value is the same for input values that could be separated by weeks or months. If you stored the `trunc()` result in a partition key column, the table would have four partitions per year.

```
select now() as right_now, trunc(now(), 'Q') as current_quarter;
+-----+-----+
| right_now                | current_quarter      |
+-----+-----+
| 2016-06-01 18:32:02.097202000 | 2016-04-01 00:00:00 |
+-----+-----+

select now() + interval 2 weeks as 2_weeks_from_now,
       trunc(now() + interval 2 weeks, 'Q') as still_current_quarter;
+-----+-----+
| 2_weeks_from_now        | still_current_quarter |
+-----+-----+
| 2016-06-15 18:36:19.584257000 | 2016-04-01 00:00:00 |
+-----+-----+
```

`unix_timestamp()`, `unix_timestamp(string datetime)`, `unix_timestamp(string datetime, string format)`, `unix_timestamp(timestamp datetime)`

Purpose: Returns a Unix time, which is a number of seconds elapsed since '1970-01-01 00:00:00' UTC. If called with no argument, the current date and time is converted to its Unix time. If called with arguments, the first argument represented as the `TIMESTAMP` or `STRING` is converted to its Unix time.

Return type: `bigint`

Usage notes:

See `from_unixtime()` for details about the patterns you can use in the `format` string to represent the position of year, month, day, and so on in the `date` string. In Impala 1.3 and higher, you have more flexibility to switch the positions of elements and use different separator characters.

In CDH 5.4.3 and higher, you can include a trailing uppercase `Z` qualifier to indicate "Zulu" time, a synonym for UTC.

In CDH 5.5.0 and higher, you can include a timezone offset specified as minutes and hours, provided you also specify the details in the `format` string argument. The offset is specified in the `format` string as a plus or minus sign followed by `hh:mm`, `hhmm`, or `hh`. The `hh` must be lowercase, to distinguish it from the `HH` represent hours in the actual time value. Currently, only numeric timezone offsets are allowed, not symbolic names.

In Impala 2.2.0 and higher, built-in functions that accept or return integers representing `TIMESTAMP` values use the `BIGINT` type for parameters and return values, rather than `INT`. This change lets the date and time functions avoid an overflow error that would otherwise occur on January 19th, 2038 (known as the "[Year 2038 problem](#)" or "[Y2K38 problem](#)"). This change affects the `from_unixtime()` and `unix_timestamp()` functions. You might need to

change application code that interacts with these functions, change the types of columns that store the return values, or add `CAST()` calls to SQL statements that call these functions.

`unix_timestamp()` and `from_unixtime()` are often used in combination to convert a `TIMESTAMP` value into a particular string format. For example:

```
select from_unixtime(unix_timestamp(now() + interval 3 days),
  'yyyy/MM/dd HH:mm') as yyyy_mm_dd_hh_mm;
+-----+
| yyyy_mm_dd_hh_mm |
+-----+
| 2016/06/03 11:38 |
+-----+
```

The way this function deals with time zones when converting to or from `TIMESTAMP` values is affected by the `--use_local_tz_for_unix_timestamp_conversions` startup flag for the `impalad` daemon. See [TIMESTAMP Data Type](#) on page 158 for details about how Impala handles time zone considerations for the `TIMESTAMP` data type.

Examples:

The following examples show different ways of turning the same date and time into an integer value. A format string that Impala recognizes by default is interpreted as a UTC date and time. The trailing `Z` is a confirmation that the timezone is UTC. If the date and time string is formatted differently, a second argument specifies the position and units for each of the date and time values.

The final two examples show how to specify a timezone offset of Pacific Daylight Saving Time, which is 7 hours earlier than UTC. You can use the numeric offset `-07:00` and the equivalent suffix of `-hh:mm` in the format string, or specify the mnemonic name for the time zone in a call to `to_utc_timestamp()`. This particular date and time expressed in PDT translates to a different number than the same date and time expressed in UTC.

```
-- 3 ways of expressing the same date/time in UTC and converting to an integer.
select unix_timestamp('2015-05-15 12:00:00');
+-----+
| unix_timestamp('2015-05-15 12:00:00') |
+-----+
| 1431691200 |
+-----+

select unix_timestamp('2015-05-15 12:00:00Z');
+-----+
| unix_timestamp('2015-05-15 12:00:00z') |
+-----+
| 1431691200 |
+-----+

select unix_timestamp
(
  'May 15, 2015 12:00:00',
  'MMM dd, yyyy HH:mm:ss'
) as may_15_month_day_year;
+-----+
| may_15_month_day_year |
+-----+
| 1431691200 |
+-----+

-- 2 ways of expressing the same date and time but in a different timezone.
-- The resulting integer is different from the previous examples.
select unix_timestamp
(
  '2015-05-15 12:00:00-07:00',
  'yyyy-MM-dd HH:mm:ss-hh:mm'
) as may_15_year_month_day;
+-----+
| may_15_year_month_day |
```



```

+-----+
| 1431716400 |
+-----+

select unix_timestamp
  (to_utc_timestamp(
    '2015-05-15 12:00:00',
    'PDT'))
  ) as may_15_pdt;
+-----+
| may_15_pdt |
+-----+
| 1431716400 |
+-----+

```

weekofyear(timestamp date)

Purpose: Returns the corresponding week (1-53) from the date portion of a `TIMESTAMP`.

Return type: `int`

Examples:

```

select now() as right_now, weekofyear(now()) as this_week;
+-----+-----+
| right_now | this_week |
+-----+-----+
| 2016-06-01 22:40:06.763771000 | 22 |
+-----+-----+

select now() + interval 2 weeks as in_2_weeks,
  weekofyear(now() + interval 2 weeks) as week_after_next;
+-----+-----+
| in_2_weeks | week_after_next |
+-----+-----+
| 2016-06-15 22:41:22.098823000 | 24 |
+-----+-----+

```

weeks_add(timestamp date, int weeks), weeks_add(timestamp date, bigint weeks)

Purpose: Returns the specified date and time plus some number of weeks.

Return type: `timestamp`

Examples:

```

select now() as right_now, weeks_add(now(), 2) as week_after_next;
+-----+-----+
| right_now | week_after_next |
+-----+-----+
| 2016-06-01 22:43:20.973834000 | 2016-06-15 22:43:20.973834000 |
+-----+-----+

```

weeks_sub(timestamp date, int weeks), weeks_sub(timestamp date, bigint weeks)

Purpose: Returns the specified date and time minus some number of weeks.

Return type: `timestamp`

Examples:

```

select now() as right_now, weeks_sub(now(), 2) as week_before_last;
+-----+-----+
| right_now | week_before_last |
+-----+-----+
| 2016-06-01 22:44:21.291913000 | 2016-05-18 22:44:21.291913000 |
+-----+-----+

```

year(timestamp date)

Purpose: Returns the year field from the date portion of a `TIMESTAMP`.

Return type: `int`

Examples:

```
select now() as right_now, year(now()) as this_year;
+-----+-----+
| right_now                | this_year |
+-----+-----+
| 2016-06-01 22:46:23.647925000 | 2016      |
+-----+-----+
```

years_add(timestamp date, int years), years_add(timestamp date, bigint years)

Purpose: Returns the specified date and time plus some number of years.

Return type: `timestamp`

Examples:

```
select now() as right_now, years_add(now(), 1) as next_year;
+-----+-----+
| right_now                | next_year |
+-----+-----+
| 2016-06-01 22:47:45.556851000 | 2017-06-01 22:47:45.556851000 |
+-----+-----+
```

The following example shows how if the equivalent date does not exist in the year of the result due to a leap year, the date is changed to the last day of the appropriate month.

```
-- Spoiler alert: there is no Feb. 29, 2017
select cast('2016-02-29' as timestamp) as feb_29_2016,
       years_add('2016-02-29', 1) as feb_29_2017;
+-----+-----+
| feb_29_2016              | feb_29_2017 |
+-----+-----+
| 2016-02-29 00:00:00      | 2017-02-28 00:00:00 |
+-----+-----+
```

years_sub(timestamp date, int years), years_sub(timestamp date, bigint years)

Purpose: Returns the specified date and time minus some number of years.

Return type: `timestamp`

Examples:

```
select now() as right_now, years_sub(now(), 1) as last_year;
+-----+-----+
| right_now                | last_year |
+-----+-----+
| 2016-06-01 22:48:11.851780000 | 2015-06-01 22:48:11.851780000 |
+-----+-----+
```

The following example shows how if the equivalent date does not exist in the year of the result due to a leap year, the date is changed to the last day of the appropriate month.

```
-- Spoiler alert: there is no Feb. 29, 2015
select cast('2016-02-29' as timestamp) as feb_29_2016,
       years_sub('2016-02-29', 1) as feb_29_2015;
+-----+-----+
```

feb_29_2016	feb_29_2015
2016-02-29 00:00:00	2015-02-28 00:00:00

Impala Conditional Functions

Impala supports the following conditional functions for testing equality, comparison operators, and nullity:

CASE a WHEN b THEN c [WHEN d THEN e]... [ELSE f] END

Purpose: Compares an expression to one or more possible values, and returns a corresponding result when a match is found.

Return type: same as the initial argument value, except that integer values are promoted to `BIGINT` and floating-point values are promoted to `DOUBLE`; use `CAST()` when inserting into a smaller numeric column

Usage notes:

In this form of the `CASE` expression, the initial value `A` being evaluated for each row is typically a column reference, or an expression involving a column. This form can only compare against a set of specified values, not ranges, multi-value comparisons such as `BETWEEN` or `IN`, regular expressions, or `NULL`.

Examples:

Although this example is split across multiple lines, you can put any or all parts of a `CASE` expression on a single line, with no punctuation or other separators between the `WHEN`, `ELSE`, and `END` clauses.

```
select case x
  when 1 then 'one'
  when 2 then 'two'
  when 0 then 'zero'
  else 'out of range'
end
from t1;
```

CASE WHEN a THEN b [WHEN c THEN d]... [ELSE e] END

Purpose: Tests whether any of a sequence of expressions is true, and returns a corresponding result for the first true expression.

Return type: same as the initial argument value, except that integer values are promoted to `BIGINT` and floating-point values are promoted to `DOUBLE`; use `CAST()` when inserting into a smaller numeric column

Usage notes:

`CASE` expressions without an initial test value have more flexibility. For example, they can test different columns in different `WHEN` clauses, or use comparison operators such as `BETWEEN`, `IN` and `IS NULL` rather than comparing against discrete values.

`CASE` expressions are often the foundation of long queries that summarize and format results for easy-to-read reports. For example, you might use a `CASE` function call to turn values from a numeric column into category strings corresponding to integer values, or labels such as “Small”, “Medium” and “Large” based on ranges. Then subsequent parts of the query might aggregate based on the transformed values, such as how many values are classified as small, medium, or large. You can also use `CASE` to signal problems with out-of-bounds values, `NULL` values, and so on.

By using operators such as `OR`, `IN`, `REGEXP`, and so on in `CASE` expressions, you can build extensive tests and transformations into a single query. Therefore, applications that construct SQL statements often rely heavily on `CASE` calls in the generated SQL code.

Because this flexible form of the `CASE` expressions allows you to perform many comparisons and call multiple functions when evaluating each row, be careful applying elaborate `CASE` expressions to queries that process large amounts of data. For example, when practical, evaluate and transform values through `CASE` after applying operations such as aggregations that reduce the size of the result set; transform numbers to strings after performing joins with the original numeric values.

Examples:

Although this example is split across multiple lines, you can put any or all parts of a `CASE` expression on a single line, with no punctuation or other separators between the `WHEN`, `ELSE`, and `END` clauses.

```
select case
  when dayname(now()) in ('Saturday','Sunday') then 'result undefined on weekends'
  when x > y then 'x greater than y'
  when x = y then 'x and y are equal'
  when x is null or y is null then 'one of the columns is null'
  else null
end
from t1;
```

coalesce(type v1, type v2, ...)

Purpose: Returns the first specified argument that is not `NULL`, or `NULL` if all arguments are `NULL`.

Return type: same as the initial argument value, except that integer values are promoted to `BIGINT` and floating-point values are promoted to `DOUBLE`; use `CAST()` when inserting into a smaller numeric column

decode(type expression, type search1, type result1 [, type search2, type result2 ...] [, type default])

Purpose: Compares an expression to one or more possible values, and returns a corresponding result when a match is found.

Return type: same as the initial argument value, except that integer values are promoted to `BIGINT` and floating-point values are promoted to `DOUBLE`; use `CAST()` when inserting into a smaller numeric column

Usage notes:

Can be used as shorthand for a `CASE` expression.

The original expression and the search expressions must be of the same type or convertible types. The result expression can be a different type, but all result expressions must be of the same type.

Returns a successful match if the original expression is `NULL` and a search expression is also `NULL`. the

Returns `NULL` if the final `default` value is omitted and none of the search expressions match the original expression.

Examples:

The following example translates numeric day values into descriptive names:

```
SELECT event, decode(day_of_week, 1, "Monday", 2, "Tuesday", 3, "Wednesday",
  4, "Thursday", 5, "Friday", 6, "Saturday", 7, "Sunday", "Unknown day")
FROM calendar;
```

if(boolean condition, type ifTrue, type ifFalseOrNull)

Purpose: Tests an expression and returns a corresponding result depending on whether the result is true, false, or `NULL`.

Return type: Same as the `ifTrue` argument value

ifnull(type a, type ifNull)

Purpose: Alias for the `isnull()` function, with the same behavior. To simplify porting SQL with vendor extensions to Impala.

Added in: Impala 1.3.0

isfalse(boolean)

Purpose: Tests if a Boolean expression is `false` or not. Returns `true` if so. If the argument is `NULL`, returns `false`. Identical to `isnottrue()`, except it returns the opposite value for a `NULL` argument.

Return type: `BOOLEAN`

Added in: CDH 5.4.0 (Impala 2.2.0)

isnotfalse(*boolean*)

Purpose: Tests if a Boolean expression is not `false` (that is, either `true` or `NULL`). Returns `true` if so. If the argument is `NULL`, returns `true`. Identical to `istrue()`, except it returns the opposite value for a `NULL` argument.

Return type: `BOOLEAN`

Usage notes: Primarily for compatibility with code containing industry extensions to SQL.

Added in: CDH 5.4.0 (Impala 2.2.0)

isnottrue(*boolean*)

Purpose: Tests if a Boolean expression is not `true` (that is, either `false` or `NULL`). Returns `true` if so. If the argument is `NULL`, returns `true`. Identical to `isfalse()`, except it returns the opposite value for a `NULL` argument.

Return type: `BOOLEAN`

Added in: CDH 5.4.0 (Impala 2.2.0)

isnull(*type a*, *type ifNull*)

Purpose: Tests if an expression is `NULL`, and returns the expression result value if not. If the first argument is `NULL`, returns the second argument.

Compatibility notes: Equivalent to the `nvl()` function from Oracle Database or `ifnull()` from MySQL. The `nvl()` and `ifnull()` functions are also available in Impala.

Return type: Same as the first argument value

istrue(*boolean*)

Purpose: Tests if a Boolean expression is `true` or not. Returns `true` if so. If the argument is `NULL`, returns `false`. Identical to `isnotfalse()`, except it returns the opposite value for a `NULL` argument.

Return type: `BOOLEAN`

Usage notes: Primarily for compatibility with code containing industry extensions to SQL.

Added in: CDH 5.4.0 (Impala 2.2.0)

nonnullvalue(*expression*)

Purpose: Tests if an expression (of any type) is `NULL` or not. Returns `false` if so. The converse of `nullvalue()`.

Return type: `BOOLEAN`

Usage notes: Primarily for compatibility with code containing industry extensions to SQL.

Added in: CDH 5.4.0 (Impala 2.2.0)

nullif(*expr1*, *expr2*)

Purpose: Returns `NULL` if the two specified arguments are equal. If the specified arguments are not equal, returns the value of *expr1*. The data types of the expressions must be compatible, according to the conversion rules from [Data Types](#) on page 126. You cannot use an expression that evaluates to `NULL` for *expr1*; that way, you can distinguish a return value of `NULL` from an argument value of `NULL`, which would never match *expr2*.

Usage notes: This function is effectively shorthand for a `CASE` expression of the form:

```
CASE
  WHEN expr1 = expr2 THEN NULL
  ELSE expr1
END
```

It is commonly used in division expressions, to produce a `NULL` result instead of a divide-by-zero error when the divisor is equal to zero:

```
select 1.0 / nullif(c1,0) as reciprocal from t1;
```

You might also use it for compatibility with other database systems that support the same `NULLIF()` function.

Return type: same as the initial argument value, except that integer values are promoted to `BIGINT` and floating-point values are promoted to `DOUBLE`; use `CAST()` when inserting into a smaller numeric column

Added in: Impala 1.3.0

`nullifzero(numeric_expr)`

Purpose: Returns `NULL` if the numeric expression evaluates to 0, otherwise returns the result of the expression.

Usage notes: Used to avoid error conditions such as divide-by-zero in numeric calculations. Serves as shorthand for a more elaborate `CASE` expression, to simplify porting SQL with vendor extensions to Impala.

Return type: Same type as the input argument

Added in: Impala 1.3.0

`nullvalue(expression)`

Purpose: Tests if an expression (of any type) is `NULL` or not. Returns `true` if so. The converse of `nonnullvalue()`.

Return type: `BOOLEAN`

Usage notes: Primarily for compatibility with code containing industry extensions to SQL.

Added in: CDH 5.4.0 (Impala 2.2.0)

`nvl(type a, type ifNull)`

Purpose: Alias for the `isnull()` function. Tests if an expression is `NULL`, and returns the expression result value if not. If the first argument is `NULL`, returns the second argument. Equivalent to the `nvl()` function from Oracle Database or `ifnull()` from MySQL.

Return type: Same as the first argument value

Added in: Impala 1.1

`zeroifnull(numeric_expr)`

Purpose: Returns 0 if the numeric expression evaluates to `NULL`, otherwise returns the result of the expression.

Usage notes: Used to avoid unexpected results due to unexpected propagation of `NULL` values in numeric calculations. Serves as shorthand for a more elaborate `CASE` expression, to simplify porting SQL with vendor extensions to Impala.

Return type: Same type as the input argument

Added in: Impala 1.3.0

Impala String Functions

String functions are classified as those primarily accepting or returning `STRING`, `VARCHAR`, or `CHAR` data types, for example to measure the length of a string or concatenate two strings together.

- All the functions that accept `STRING` arguments also accept the `VARCHAR` and `CHAR` types introduced in Impala 2.0.
- Whenever `VARCHAR` or `CHAR` values are passed to a function that returns a string value, the return type is normalized to `STRING`. For example, a call to `concat()` with a mix of `STRING`, `VARCHAR`, and `CHAR` arguments produces a `STRING` result.

Related information:

The string functions operate mainly on these data types: [STRING Data Type](#) on page 151, [VARCHAR Data Type \(CDH 5.2 or higher only\)](#) on page 165, and [CHAR Data Type \(CDH 5.2 or higher only\)](#) on page 132.

Function reference:

Impala supports the following string functions:

`ascii(string str)`

Purpose: Returns the numeric ASCII code of the first character of the argument.

Return type: `int`

`base64decode(string str)`

Purpose:

Return type: string

Usage notes:

For general information about Base64 encoding, see <https://en.wikipedia.org/wiki/Base64>.

The functions `base64encode()` and `base64decode()` are typically used in combination, to store in an Impala table string data that is problematic to store or transmit. For example, you could use these functions to store string data that uses an encoding other than UTF-8, or to transform the values in contexts that require ASCII values, such as for partition key columns. Keep in mind that base64-encoded values produce different results for string functions such as `LENGTH()`, `MAX()`, and `MIN()` than when those functions are called with the unencoded string values.

The set of characters that can be generated as output from `base64encode()`, or specified in the argument string to `base64decode()`, are the ASCII uppercase and lowercase letters (A-Z, a-z), digits (0-9), and the punctuation characters `+`, `/`, and `=`.

All return values produced by `base64encode()` are a multiple of 4 bytes in length. All argument values supplied to `base64decode()` must also be a multiple of 4 bytes in length. If a base64-encoded value would otherwise have a different length, it can be padded with trailing `=` characters to reach a length that is a multiple of 4 bytes.

If the argument string to `base64decode()` does not represent a valid base64-encoded value, subject to the constraints of the Impala implementation such as the allowed character set, the function returns `NULL`.

Examples:

The following examples show how to use `base64encode()` and `base64decode()` together to store and retrieve string values:

```
-- An arbitrary string can be encoded in base 64.
-- The length of the output is a multiple of 4 bytes,
-- padded with trailing = characters if necessary.
select base64encode('hello world') as encoded,
       length(base64encode('hello world')) as length;
+-----+-----+
| encoded          | length |
+-----+-----+
| aGVsbG8gd29ybGQ= | 16     |
+-----+-----+

-- Passing an encoded value to base64decode() produces
-- the original value.
select base64decode('aGVsbG8gd29ybGQ=') as decoded;
+-----+
| decoded          |
+-----+
| hello world     |
+-----+
```

These examples demonstrate incorrect encoded values that produce `NULL` return values when decoded:

```
-- The input value to base64decode() must be a multiple of 4 bytes.
-- In this case, leaving off the trailing = padding character
-- produces a NULL return value.
select base64decode('aGVsbG8gd29ybGQ') as decoded;
+-----+
| decoded          |
+-----+
| NULL             |
+-----+
WARNINGS: UDF WARNING: Invalid base64 string; input length is 15,
          which is not a multiple of 4.

-- The input to base64decode() can only contain certain characters.
```

```
-- The $ character in this case causes a NULL return value.
select base64decode('abc$');
+-----+
| base64decode('abc$') |
+-----+
| NULL                  |
+-----+
WARNINGS: UDF WARNING: Could not base64 decode input in space 4; actual output length 0
```

These examples demonstrate “round-tripping” of an original string to an encoded string, and back again. This technique is applicable if the original source is in an unknown encoding, or if some intermediate processing stage might cause national characters to be misrepresented:

```
select 'circumflex accents: â, ê, î, ô, û' as original,
       base64encode('circumflex accents: â, ê, î, ô, û') as encoded;
+-----+-----+
| original                                | encoded |
+-----+-----+
| circumflex accents: â, ê, î, ô, û | Y2lyY3VtZmxleCBhY2NlbnRzOiDDoiw6osIMOuLCDDtCwgw7s= |
+-----+-----+

select base64encode('circumflex accents: â, ê, î, ô, û') as encoded,
       base64decode(base64encode('circumflex accents: â, ê, î, ô, û')) as decoded;
+-----+-----+
| encoded                                | decoded |
+-----+-----+
| Y2lyY3VtZmxleCBhY2NlbnRzOiDDoiw6osIMOuLCDDtCwgw7s= | circumflex accents: â, ê, î, ô, û |
+-----+-----+
```

base64encode(string str)

Purpose:

Return type: string

Usage notes:

For general information about Base64 encoding, see <https://en.wikipedia.org/wiki/Base64>.

The functions `base64encode()` and `base64decode()` are typically used in combination, to store in an Impala table string data that is problematic to store or transmit. For example, you could use these functions to store string data that uses an encoding other than UTF-8, or to transform the values in contexts that require ASCII values, such as for partition key columns. Keep in mind that base64-encoded values produce different results for string functions such as `LENGTH()`, `MAX()`, and `MIN()` than when those functions are called with the unencoded string values.

The set of characters that can be generated as output from `base64encode()`, or specified in the argument string to `base64decode()`, are the ASCII uppercase and lowercase letters (A-Z, a-z), digits (0-9), and the punctuation characters `+`, `/`, and `=`.

All return values produced by `base64encode()` are a multiple of 4 bytes in length. All argument values supplied to `base64decode()` must also be a multiple of 4 bytes in length. If a base64-encoded value would otherwise have a different length, it can be padded with trailing `=` characters to reach a length that is a multiple of 4 bytes.

Examples:

The following examples show how to use `base64encode()` and `base64decode()` together to store and retrieve string values:

```
-- An arbitrary string can be encoded in base 64.
-- The length of the output is a multiple of 4 bytes,
```



```
-- padded with trailing = characters if necessary.
select base64encode('hello world') as encoded,
       length(base64encode('hello world')) as length;
+-----+-----+
| encoded          | length |
+-----+-----+
| aGVsbG8gd29ybGQ= | 16     |
+-----+-----+

-- Passing an encoded value to base64decode() produces
-- the original value.
select base64decode('aGVsbG8gd29ybGQ=') as decoded;
+-----+
| decoded          |
+-----+
| hello world     |
+-----+
```

These examples demonstrate incorrect encoded values that produce NULL return values when decoded:

```
-- The input value to base64decode() must be a multiple of 4 bytes.
-- In this case, leaving off the trailing = padding character
-- produces a NULL return value.
select base64decode('aGVsbG8gd29ybGQ') as decoded;
+-----+
| decoded          |
+-----+
| NULL             |
+-----+
WARNINGS: UDF WARNING: Invalid base64 string; input length is 15,
          which is not a multiple of 4.

-- The input to base64decode() can only contain certain characters.
-- The $ character in this case causes a NULL return value.
select base64decode('abc$');
+-----+
| base64decode('abc$') |
+-----+
| NULL                 |
+-----+
WARNINGS: UDF WARNING: Could not base64 decode input in space 4; actual output length
0
```

These examples demonstrate “round-tripping” of an original string to an encoded string, and back again. This technique is applicable if the original source is in an unknown encoding, or if some intermediate processing stage might cause national characters to be misrepresented:

```
select 'circumflex accents: â, ê, î, ô, û' as original,
       base64encode('circumflex accents: â, ê, î, ô, û') as encoded;
+-----+-----+
| original          | encoded |
+-----+-----+
| circumflex accents: â, ê, î, ô, û | Y2lyY3VtZmxleCBhY2NlbnRzOiDDoiw6osIMOUcLDDtCw7s= |
+-----+-----+

select base64encode('circumflex accents: â, ê, î, ô, û') as encoded,
       base64decode(base64encode('circumflex accents: â, ê, î, ô, û')) as decoded;
+-----+-----+
| encoded          | decoded |
+-----+-----+
| Y2lyY3VtZmxleCBhY2NlbnRzOiDDoiw6osIMOUcLDDtCw7s= | circumflex accents: â, ê, î, ô, û |
+-----+-----+
```

btrim(string a), btrim(string a, string chars_to_trim)

Purpose: Removes all instances of one or more characters from the start and end of a `STRING` value. By default, removes only spaces. If a non-`NULL` optional second argument is specified, the function removes all occurrences of characters in that second argument from the beginning and end of the string.

Return type: `string`

Added in: CDH 5.5.0 (Impala 2.3.0)

Examples:

The following examples show the default `btrim()` behavior, and what changes when you specify the optional second argument. All the examples bracket the output value with `[]` so that you can see any leading or trailing spaces in the `btrim()` result. By default, the function removes a number of both leading and trailing spaces. When the second argument is specified, any number of occurrences of any character in the second argument are removed from the start and end of the input string; in this case, spaces are not removed (unless they are part of the second argument) and any instances of the characters are not removed if they do not come right at the beginning or end of the string.

```
-- Remove multiple spaces before and one space after.
select concat('[',btrim('  hello '),']');
+-----+
| concat('[', btrim('  hello '), ']') |
+-----+
| [hello] |
+-----+

-- Remove any instances of x or y or z at beginning or end. Leave spaces alone.
select concat('[',btrim('xy  hello zzzzxx','xyz'),']');
+-----+
| concat('[', btrim('xy  hello zzzzxx', 'xyz'), ']') |
+-----+
| [  hello ] |
+-----+

-- Remove any instances of x or y or z at beginning or end.
-- Leave x, y, z alone in the middle of the string.
select concat('[',btrim('xyhelxyzlozyzzxx','xyz'),']');
+-----+
| concat('[', btrim('xyhelxyzlozyzzxx', 'xyz'), ']') |
+-----+
| [helxyzlo] |
+-----+
```

char_length(string a), character_length(string a)

Purpose: Returns the length in characters of the argument string. Aliases for the `length()` function.

Return type: `int`

chr(int character_code)

Purpose: Returns a character specified by a decimal code point value. The interpretation and display of the resulting character depends on your system locale. Because consistent processing of Impala string values is only guaranteed for values within the ASCII range, only use this function for values corresponding to ASCII characters. In particular, parameter values greater than 255 return an empty string.

Return type: `string`

Usage notes: Can be used as the inverse of the `ascii()` function, which converts a character to its numeric ASCII code.

Added in: CDH 5.5.0 (Impala 2.3.0)

Examples:

```
SELECT chr(65);
+-----+
```

```

| chr(65) |
+-----+
| A       |
+-----+
SELECT chr(97);
+-----+
| chr(97) |
+-----+
| a       |
+-----+

```

concat(string a, string b...)

Purpose: Returns a single string representing all the argument values joined together.

Return type: string

Usage notes: `concat()` and `concat_ws()` are appropriate for concatenating the values of multiple columns within the same row, while `group_concat()` joins together values from different rows.

concat_ws(string sep, string a, string b...)

Purpose: Returns a single string representing the second and following argument values joined together, delimited by a specified separator.

Return type: string

Usage notes: `concat()` and `concat_ws()` are appropriate for concatenating the values of multiple columns within the same row, while `group_concat()` joins together values from different rows.

find_in_set(string str, string strList)

Purpose: Returns the position (starting from 1) of the first occurrence of a specified string within a comma-separated string. Returns `NULL` if either argument is `NULL`, 0 if the search string is not found, or 0 if the search string contains a comma.

Return type: int

group_concat(string s [, string sep])

Purpose: Returns a single string representing the argument value concatenated together for each row of the result set. If the optional separator string is specified, the separator is added between each pair of concatenated values.

Return type: string

Usage notes: `concat()` and `concat_ws()` are appropriate for concatenating the values of multiple columns within the same row, while `group_concat()` joins together values from different rows.

By default, returns a single string covering the whole result set. To include other columns or values in the result set, or to produce multiple concatenated strings for subsets of rows, include a `GROUP BY` clause in the query.

Strictly speaking, `group_concat()` is an aggregate function, not a scalar function like the others in this list. For additional details and examples, see [GROUP_CONCAT Function](#) on page 453.

initcap(string str)

Purpose: Returns the input string with the first letter capitalized.

Return type: string

instr(string str, string substr)

Purpose: Returns the position (starting from 1) of the first occurrence of a substring within a longer string.

Return type: int

length(string a)

Purpose: Returns the length in characters of the argument string.

Return type: int

`locate(string substr, string str[, int pos])`

Purpose: Returns the position (starting from 1) of the first occurrence of a substring within a longer string, optionally after a particular position.

Return type: `int`

`lower(string a), lcase(string a)`

Purpose: Returns the argument string converted to all-lowercase.

Return type: `string`

Usage notes:

In CDH 5.7 / Impala 2.5 and higher, you can simplify queries that use many `UPPER()` and `LOWER()` calls to do case-insensitive comparisons, by using the `ILIKE` or `IREGEXP` operators instead. See [LIKE Operator](#) on page 206 and [IREGEXP Operator](#) on page 210 for details.

`lpad(string str, int len, string pad)`

Purpose: Returns a string of a specified length, based on the first argument string. If the specified string is too short, it is padded on the left with a repeating sequence of the characters from the pad string. If the specified string is too long, it is truncated on the right.

Return type: `string`

`ltrim(string a)`

Purpose: Returns the argument string with any leading spaces removed from the left side.

Return type: `string`

`parse_url(string urlString, string partToExtract [, string keyToExtract])`

Purpose: Returns the portion of a URL corresponding to a specified part. The part argument can be 'PROTOCOL', 'HOST', 'PATH', 'REF', 'AUTHORITY', 'FILE', 'USERINFO', or 'QUERY'. Uppercase is required for these literal values. When requesting the `QUERY` portion of the URL, you can optionally specify a key to retrieve just the associated value from the key-value pairs in the query string.

Return type: `string`

Usage notes: This function is important for the traditional Hadoop use case of interpreting web logs. For example, if the web traffic data features raw URLs not divided into separate table columns, you can count visitors to a particular page by extracting the 'PATH' or 'FILE' field, or analyze search terms by extracting the corresponding key from the 'QUERY' field.

`regexp_extract(string subject, string pattern, int index)`

Purpose: Returns the specified () group from a string based on a regular expression pattern. Group 0 refers to the entire extracted string, while group 1, 2, and so on refers to the first, second, and so on (. . .) portion.

Return type: `string`

In Impala 2.0 and later, the Impala regular expression syntax conforms to the POSIX Extended Regular Expression syntax used by the Google RE2 library. For details, see [the RE2 documentation](#). It has most idioms familiar from regular expressions in Perl, Python, and so on, including `. * ?` for non-greedy matches.

In Impala 2.0 and later, a change in the underlying regular expression library could cause changes in the way regular expressions are interpreted by this function. Test any queries that use regular expressions and adjust the expression patterns if necessary. See [Incompatible Changes Introduced in Impala 2.0.0 / CDH 5.2.0](#) on page 690 for details.

Because the `impala-shell` interpreter uses the `\` character for escaping, use `\\` to represent the regular expression escape character in any regular expressions that you submit through `impala-shell`. You might prefer to use the equivalent character class names, such as `[[:digit:]]` instead of `\d` which you would have to escape as `\\d`.

Examples:

This example shows how group 0 matches the full pattern string, including the portion outside any () group:

```
[localhost:21000] > select regexp_extract('abcdef123ghi456jkl', '.*?(\\d+)', 0);
+-----+
| regexp_extract('abcdef123ghi456jkl', '.*?(\\d+)', 0) |
+-----+
| abcdef123ghi456                                     |
+-----+
Returned 1 row(s) in 0.11s
```

This example shows how group 1 matches just the contents inside the first () group in the pattern string:

```
[localhost:21000] > select regexp_extract('abcdef123ghi456jkl', '.*?(\\d+)', 1);
+-----+
| regexp_extract('abcdef123ghi456jkl', '.*?(\\d+)', 1) |
+-----+
| 456                                                    |
+-----+
Returned 1 row(s) in 0.11s
```

Unlike in earlier Impala releases, the regular expression library used in Impala 2.0 and later supports the `.*?` idiom for non-greedy matches. This example shows how a pattern string starting with `.*?` matches the shortest possible portion of the source string, returning the rightmost set of lowercase letters. A pattern string both starting and ending with `.*?` finds two potential matches of equal length, and returns the first one found (the leftmost set of lowercase letters).

```
[localhost:21000] > select regexp_extract('AbcdBCdefGHI', '.*?([[:lower:]]+)', 1);
+-----+
| regexp_extract('abcdbcdefghi', '.*?([[:lower:]]+)', 1) |
+-----+
| def                                                    |
+-----+
[localhost:21000] > select regexp_extract('AbcdBCdefGHI', '.*?([[:lower:]]+).*?', 1);
+-----+
| regexp_extract('abcdbcdefghi', '.*?([[:lower:]]+).*?', 1) |
+-----+
| bcd                                                    |
+-----+
```

regexp_like(string source, string pattern[, string options])

Purpose: Returns `true` or `false` to indicate whether the source string contains anywhere inside it the regular expression given by the pattern. The optional third argument consists of letter flags that change how the match is performed, such as `i` for case-insensitive matching.

Syntax:

The flags that you can include in the optional third argument are:

- `c`: Case-sensitive matching (the default).
- `i`: Case-insensitive matching. If multiple instances of `c` and `i` are included in the third argument, the last such option takes precedence.
- `m`: Multi-line matching. The `^` and `$` operators match the start or end of any line within the source string, not the start and end of the entire string.
- `n`: Newline matching. The `.` operator can match the newline character. A repetition operator such as `.*` can match a portion of the source string that spans multiple lines.

Return type: `boolean`

In Impala 2.0 and later, the Impala regular expression syntax conforms to the POSIX Extended Regular Expression syntax used by the Google RE2 library. For details, see [the RE2 documentation](#). It has most idioms familiar from regular expressions in Perl, Python, and so on, including `.*?` for non-greedy matches.

In Impala 2.0 and later, a change in the underlying regular expression library could cause changes in the way regular expressions are interpreted by this function. Test any queries that use regular expressions and adjust the expression patterns if necessary. See [Incompatible Changes Introduced in Impala 2.0.0 / CDH 5.2.0](#) on page 690 for details.

Because the `impala-shell` interpreter uses the `\` character for escaping, use `\\` to represent the regular expression escape character in any regular expressions that you submit through `impala-shell`. You might prefer to use the equivalent character class names, such as `[[:digit:]]` instead of `\\d` which you would have to escape as `\\d`.

Examples:

This example shows how `regexp_like()` can test for the existence of various kinds of regular expression patterns within a source string:

```
-- Matches because the 'f' appears somewhere in 'foo'.
select regexp_like('foo','f');
+-----+
| regexp_like('foo','f') |
+-----+
| true                   |
+-----+

-- Does not match because the comparison is case-sensitive by default.
select regexp_like('foo','F');
+-----+
| regexp_like('foo','F') |
+-----+
| false                  |
+-----+

-- The 3rd argument can change the matching logic, such as 'i' meaning case-insensitive.
select regexp_like('foo','F','i');
+-----+
| regexp_like('foo','F','i') |
+-----+
| true                       |
+-----+

-- The familiar regular expression notations work, such as ^ and $ anchors...
select regexp_like('foo','f$');
+-----+
| regexp_like('foo','f$') |
+-----+
| false                   |
+-----+

select regexp_like('foo','o$');
+-----+
| regexp_like('foo','o$') |
+-----+
| true                    |
+-----+

-- ...and repetition operators such as * and +
select regexp_like('foooooobar','fo+b');
+-----+
| regexp_like('foooooobar','fo+b') |
+-----+
| true                             |
+-----+

select regexp_like('foooooobar','fx*y*o*b');
+-----+
| regexp_like('foooooobar','fx*y*o*b') |
+-----+
| true                             |
+-----+
```

regexp_replace(string initial, string pattern, string replacement)

Purpose: Returns the initial argument with the regular expression pattern replaced by the final argument string.

Return type: string

In Impala 2.0 and later, the Impala regular expression syntax conforms to the POSIX Extended Regular Expression syntax used by the Google RE2 library. For details, see [the RE2 documentation](#). It has most idioms familiar from regular expressions in Perl, Python, and so on, including `. *?` for non-greedy matches.

In Impala 2.0 and later, a change in the underlying regular expression library could cause changes in the way regular expressions are interpreted by this function. Test any queries that use regular expressions and adjust the expression patterns if necessary. See [Incompatible Changes Introduced in Impala 2.0.0 / CDH 5.2.0](#) on page 690 for details.

Because the `impala-shell` interpreter uses the `\` character for escaping, use `\\` to represent the regular expression escape character in any regular expressions that you submit through `impala-shell`. You might prefer to use the equivalent character class names, such as `[[:digit:]]` instead of `\d` which you would have to escape as `\\d`.

Examples:

These examples show how you can replace parts of a string matching a pattern with replacement text, which can include backreferences to any `()` groups in the pattern string. The backreference numbers start at 1, and any `\` characters must be escaped as `\\`.

Replace a character pattern with new text:

```
[localhost:21000] > select regexp_replace('aaabbbbaaa', 'b+', 'xyz');
+-----+
| regexp_replace('aaabbbbaaa', 'b+', 'xyz') |
+-----+
| aaaxyzaaa                                |
+-----+
Returned 1 row(s) in 0.11s
```

Replace a character pattern with substitution text that includes the original matching text:

```
[localhost:21000] > select regexp_replace('aaabbbbaaa', '(b+)', '<\\1>');
+-----+
| regexp_replace('aaabbbbaaa', '(b+)', '<\\1>') |
+-----+
| aaa<bbb>aaa                                |
+-----+
Returned 1 row(s) in 0.11s
```

Remove all characters that are not digits:

```
[localhost:21000] > select regexp_replace('123-456-789', '[^[:digit:]]', '');
+-----+
| regexp_replace('123-456-789', '[^[:digit:]]', '') |
+-----+
| 123456789                                |
+-----+
Returned 1 row(s) in 0.12s
```

repeat(string str, int n)

Purpose: Returns the argument string repeated a specified number of times.

Return type: string

reverse(string a)

Purpose: Returns the argument string with characters in reversed order.

Return type: string

rpad(string str, int len, string pad)

Purpose: Returns a string of a specified length, based on the first argument string. If the specified string is too short, it is padded on the right with a repeating sequence of the characters from the pad string. If the specified string is too long, it is truncated on the right.

Return type: string

rtrim(string a)

Purpose: Returns the argument string with any trailing spaces removed from the right side.

Return type: string

space(int n)

Purpose: Returns a concatenated string of the specified number of spaces. Shorthand for `repeat(' ', n)`.

Return type: string

split_part(string source, string delimiter, bigint n)

Purpose: Returns the nth field within a delimited string. The fields are numbered starting from 1. The delimiter can consist of multiple characters, not just a single character. All matching of the delimiter is done exactly, not using any regular expression patterns.

Return type: string

In Impala 2.0 and later, the Impala regular expression syntax conforms to the POSIX Extended Regular Expression syntax used by the Google RE2 library. For details, see [the RE2 documentation](#). It has most idioms familiar from regular expressions in Perl, Python, and so on, including `. *?` for non-greedy matches.

In Impala 2.0 and later, a change in the underlying regular expression library could cause changes in the way regular expressions are interpreted by this function. Test any queries that use regular expressions and adjust the expression patterns if necessary. See [Incompatible Changes Introduced in Impala 2.0.0 / CDH 5.2.0](#) on page 690 for details.

Because the `impala-shell` interpreter uses the `\` character for escaping, use `\\` to represent the regular expression escape character in any regular expressions that you submit through `impala-shell`. You might prefer to use the equivalent character class names, such as `[[:digit:]]` instead of `\\d` which you would have to escape as `\\d`.

Examples:

These examples show how to retrieve the nth field from a delimited string:

```
select split_part('x,y,z',' ',1);
+-----+
| split_part('x,y,z', ' ', 1) |
+-----+
| x                             |
+-----+

select split_part('x,y,z',' ',2);
+-----+
| split_part('x,y,z', ' ', 2) |
+-----+
| y                             |
+-----+

select split_part('x,y,z',' ',3);
+-----+
| split_part('x,y,z', ' ', 3) |
+-----+
| z                             |
+-----+
```

These examples show what happens for out-of-range field positions. Specifying a value less than 1 produces an error. Specifying a value greater than the number of fields returns a zero-length string (which is not the same as NULL).

```
select split_part('x,y,z',' ',0);
ERROR: Invalid field position: 0

with t1 as (select split_part('x,y,z',' ',4) nonexistent_field)
select
  nonexistent_field
```



```

, concat(['',nonexistent_field,'])
, length(nonexistent_field);
from t1

```

nonexistent_field	concat(['', nonexistent_field, ''])	length(nonexistent_field)
	[]	0

These examples show how the delimiter can be a multi-character value:

```

select split_part('one***two***three','***',2);

```

split_part('one***two***three', '***', 2)
two

```

select split_part('one\|/two\|/three','\|/',3);

```

split_part('one\ /two\ /three', '\ /', 3)
three

strleft(string a, int num_chars)

Purpose: Returns the leftmost characters of the string. Shorthand for a call to `substr()` with 2 arguments.

Return type: string

strright(string a, int num_chars)

Purpose: Returns the rightmost characters of the string. Shorthand for a call to `substr()` with 2 arguments.

Return type: string

substr(string a, int start [, int len]), substring(string a, int start [, int len])

Purpose: Returns the portion of the string starting at a specified point, optionally with a specified maximum length. The characters in the string are indexed starting at 1.

Return type: string

translate(string input, string from, string to)

Purpose: Returns the `input` string with each character in the `from` argument replaced with the corresponding character in the `to` argument. The characters are matched in the order they appear in `from` and `to`.

For example: `translate ('hello world','world','earth')` returns 'hetta earth'.

Return type: string

Usage notes:

If `from` contains more characters than `to`, the `from` characters that are beyond the length of `to` are removed in the result.

For example:

`translate('abcdedg', 'bcd', '1')` returns 'aleg'.

`translate('Unit Number#2', '#', '_')` returns 'UnitNumber_2'.

If `from` is `NULL`, the function returns `NULL`.

If `to` contains more characters than `from`, the extra characters in `to` are ignored.

If `from` contains duplicate characters, the duplicate character is replaced with the first matching character in `to`.

For example: `translate ('hello', 'll', '67')` returns `'he66o'`.

trim(string a)

Purpose: Returns the input string with both leading and trailing spaces removed. The same as passing the string through both `ltrim()` and `rtrim()`.

Usage notes: Often used during data cleansing operations during the ETL cycle, if input values might still have surrounding spaces. For a more general-purpose function that can remove other leading and trailing characters besides spaces, see `btrim()`.

Return type: `string`

upper(string a), ucase(string a)

Purpose: Returns the argument string converted to all-uppercase.

Return type: `string`

Usage notes:

In CDH 5.7 / Impala 2.5 and higher, you can simplify queries that use many `UPPER()` and `LOWER()` calls to do case-insensitive comparisons, by using the `ILIKE` or `IREGEXP` operators instead. See [ILIKE Operator](#) on page 206 and [IREGEXP Operator](#) on page 210 for details.

Impala Miscellaneous Functions

Impala supports the following utility functions that do not operate on a particular column or data type:

current_database()

Purpose: Returns the database that the session is currently using, either `default` if no database has been selected, or whatever database the session switched to through a `USE` statement or the `impalad-d` option.

Return type: `string`

effective_user()

Purpose: Typically returns the same value as `user()`, except if delegation is enabled, in which case it returns the ID of the delegated user.

Return type: `string`

Added in: CDH 5.4.5

pid()

Purpose: Returns the process ID of the `impalad` daemon that the session is connected to. You can use it during low-level debugging, to issue Linux commands that trace, show the arguments, and so on the `impalad` process.

Return type: `int`

user()

Purpose: Returns the username of the Linux user who is connected to the `impalad` daemon. Typically called a single time, in a query without any `FROM` clause, to understand how authorization settings apply in a security context; once you know the logged-in username, you can check which groups that user belongs to, and from the list of groups you can check which roles are available to those groups through the authorization policy file.

In Impala 2.0 and later, `user()` returns the full Kerberos principal string, such as `user@example.com`, in a Kerberized environment.

When delegation is enabled, consider calling the `effective_user()` function instead.

Return type: `string`

uuid()

Purpose: Returns a [universal unique identifier](#), a 128-bit value encoded as a string with groups of hexadecimal digits separated by dashes.

Return type: `string`

Added in: CDH 5.7.0 (Impala 2.5.0)

Usage notes:

Ascending numeric sequences of type `BIGINT` are often used as identifiers within a table, and as join keys across multiple tables. The `uuid()` value is a convenient alternative that does not require storing or querying the highest sequence number. For example, you can use it to quickly construct new unique identifiers during a data import job, or to combine data from different tables without the likelihood of ID collisions.

Examples:

```
-- Each call to uuid() produces a new arbitrary value.
select uuid();
+-----+
| uuid() |
+-----+
| c7013e25-1455-457f-bf74-a2046e58caea |
+-----+

-- If you get a UUID for each row of a result set, you can use it as a
-- unique identifier within a table, or even a unique ID across tables.
select uuid() from four_row_table;
+-----+
| uuid() |
+-----+
| 51d3c540-85e5-4cb9-9110-604e53999e2e |
| 0bb40071-92f6-4a59-a6a4-60d46e9703e2 |
| 5e9d7c36-9842-4a96-862d-c13cd0457c02 |
| cae29095-0cc0-4053-a5ea-7fcd3c780861 |
+-----+
```

version()

Purpose: Returns information such as the precise version number and build date for the `impalad` daemon that you are currently connected to. Typically used to confirm that you are connected to the expected level of Impala to use a particular feature, or to connect to several nodes and confirm they are all running the same level of `impalad`.

Return type: `string` (with one or more embedded newlines)

Impala Aggregate Functions

Aggregate functions are a special category with different rules. These functions calculate a return value across all the items in a result set, so they require a `FROM` clause in the query:

```
select count(product_id) from product_catalog;
select max(height), avg(height) from census_data where age > 20;
```

Aggregate functions also ignore `NULL` values rather than returning a `NULL` result. For example, if some rows have `NULL` for a particular column, those rows are ignored when computing the `AVG()` for that column. Likewise, specifying `COUNT(col_name)` in a query counts only those rows where `col_name` contains a non-`NULL` value.

APPX_MEDIAN Function

An aggregate function that returns a value that is approximately the median (midpoint) of values in the set of input values.

Syntax:

```
APPX_MEDIAN([DISTINCT | ALL] expression)
```

This function works with any input type, because the only requirement is that the type supports less-than and greater-than comparison operators.

Usage notes:

Because the return value represents the estimated midpoint, it might not reflect the precise midpoint value, especially if the cardinality of the input values is very high. If the cardinality is low (up to approximately 20,000), the result is more accurate because the sampling considers all or almost all of the different values.

Return type: Same as the input value, except for CHAR and VARCHAR arguments which produce a STRING result

The return value is always the same as one of the input values, not an “in-between” value produced by averaging.

Restrictions:

This function cannot be used in an analytic context. That is, the OVER() clause is not allowed at all with this function.

Examples:

The following example uses a table of a million random floating-point numbers ranging up to approximately 50,000. The average is approximately 25,000. Because of the random distribution, we would expect the median to be close to this same number. Computing the precise median is a more intensive operation than computing the average, because it requires keeping track of every distinct value and how many times each occurs. The APPX_MEDIAN() function uses a sampling algorithm to return an approximate result, which in this case is close to the expected value. To make sure that the value is not substantially out of range due to a skewed distribution, subsequent queries confirm that there are approximately 500,000 values higher than the APPX_MEDIAN() value, and approximately 500,000 values lower than the APPX_MEDIAN() value.

```
[localhost:21000] > select min(x), max(x), avg(x) from million_numbers;
+-----+-----+-----+
| min(x) | max(x) | avg(x) |
+-----+-----+-----+
| 4.725693727250069 | 49994.56852674231 | 24945.38563793553 |
+-----+-----+-----+
[localhost:21000] > select appx_median(x) from million_numbers;
+-----+
| appx_median(x) |
+-----+
| 24721.6 |
+-----+
[localhost:21000] > select count(x) as higher from million_numbers where x > (select
appx_median(x) from million_numbers);
+-----+
| higher |
+-----+
| 502013 |
+-----+
[localhost:21000] > select count(x) as lower from million_numbers where x < (select
appx_median(x) from million_numbers);
+-----+
| lower |
+-----+
| 497987 |
+-----+
```

The following example computes the approximate median using a subset of the values from the table, and then confirms that the result is a reasonable estimate for the midpoint.

```
[localhost:21000] > select appx_median(x) from million_numbers where x between 1000 and
5000;
+-----+
| appx_median(x) |
+-----+
| 3013.107787358159 |
+-----+
[localhost:21000] > select count(x) as higher from million_numbers where x between 1000
and 5000 and x > 3013.107787358159;
+-----+
| higher |
+-----+
| 37692 |
+-----+
[localhost:21000] > select count(x) as lower from million_numbers where x between 1000
and 5000 and x < 3013.107787358159;
```

```
+-----+
| lower |
+-----+
| 37089 |
+-----+
```

AVG Function

An aggregate function that returns the average value from a set of numbers or `TIMESTAMP` values. Its single argument can be numeric column, or the numeric result of a function or expression applied to the column value. Rows with a `NULL` value for the specified column are ignored. If the table is empty, or all the values supplied to `AVG` are `NULL`, `AVG` returns `NULL`.

Syntax:

```
AVG([DISTINCT | ALL] expression) [OVER (analytic_clause)]
```

When the query contains a `GROUP BY` clause, returns one value for each combination of grouping values.

Return type: `DOUBLE` for numeric values; `TIMESTAMP` for `TIMESTAMP` values

Complex type considerations:

To access a column with a complex type (`ARRAY`, `STRUCT`, or `MAP`) in an aggregation function, you unpack the individual elements using join notation in the query, and then apply the function to the final scalar item, field, key, or value at the bottom of any nested type hierarchy in the column. See [Complex Types \(CDH 5.5 or higher only\)](#) on page 167 for details about using complex types in Impala.

The following example demonstrates calls to several aggregation functions using values from a column containing nested complex types (an `ARRAY` of `STRUCT` items). The array is unpacked inside the query using join notation. The array elements are referenced using the `ITEM` pseudocolumn, and the structure fields inside the array elements are referenced using dot notation. Numeric values such as `SUM()` and `AVG()` are computed using the numeric `R_NATIONKEY` field, and the general-purpose `MAX()` and `MIN()` values are computed from the string `N_NAME` field.

```
describe region;
+-----+-----+-----+
| name          | type                                     | comment |
+-----+-----+-----+
| r_regionkey   | smallint                                 |         |
| r_name        | string                                   |         |
| r_comment     | string                                   |         |
| r_nations     | array<struct<                             |         |
|               |   n_nationkey:smallint,                 |         |
|               |   n_name:string,                       |         |
|               |   n_comment:string                     |         |
|               | >>                                       |         |
+-----+-----+-----+

select r_name, r_nations.item.n_nationkey
  from region, region.r_nations as r_nations
 order by r_name, r_nations.item.n_nationkey;
+-----+-----+
| r_name      | item.n_nationkey |
+-----+-----+
| AFRICA     | 0                |
| AFRICA     | 5                |
| AFRICA     | 14               |
| AFRICA     | 15               |
| AFRICA     | 16               |
| AMERICA    | 1                |
| AMERICA    | 2                |
| AMERICA    | 3                |
| AMERICA    | 17               |
| AMERICA    | 24               |
| ASIA       | 8                |
| ASIA       | 9                |
| ASIA       | 12               |
| ASIA       | 18               |
+-----+-----+
```

ASIA	21
EUROPE	6
EUROPE	7
EUROPE	19
EUROPE	22
EUROPE	23
MIDDLE EAST	4
MIDDLE EAST	10
MIDDLE EAST	11
MIDDLE EAST	13
MIDDLE EAST	20

```
select
  r_name,
  count(r_nations.item.n_nationkey) as count,
  sum(r_nations.item.n_nationkey) as sum,
  avg(r_nations.item.n_nationkey) as avg,
  min(r_nations.item.n_name) as minimum,
  max(r_nations.item.n_name) as maximum,
  ndv(r_nations.item.n_nationkey) as distinct_vals
from
  region, region.r_nations as r_nations
group by r_name
order by r_name;
```

r_name	count	sum	avg	minimum	maximum	distinct_vals
AFRICA	5	50	10	ALGERIA	MOZAMBIQUE	5
AMERICA	5	47	9.4	ARGENTINA	UNITED STATES	5
ASIA	5	68	13.6	CHINA	VIETNAM	5
EUROPE	5	77	15.4	FRANCE	UNITED KINGDOM	5
MIDDLE EAST	5	58	11.6	EGYPT	SAUDI ARABIA	5

Examples:

```
-- Average all the non-NULL values in a column.
insert overwrite avg_t values (2),(4),(6),(null),(null);
-- The average of the above values is 4: (2+4+6) / 3. The 2 NULL values are ignored.
select avg(x) from avg_t;
-- Average only certain values from the column.
select avg(x) from t1 where month = 'January' and year = '2013';
-- Apply a calculation to the value of the column before averaging.
select avg(x/3) from t1;
-- Apply a function to the value of the column before averaging.
-- Here we are substituting a value of 0 for all NULLs in the column,
-- so that those rows do factor into the return value.
select avg(isnull(x,0)) from t1;
-- Apply some number-returning function to a string column and average the results.
-- If column s contains any NULLs, length(s) also returns NULL and those rows are ignored.
select avg(length(s)) from t1;
-- Can also be used in combination with DISTINCT and/or GROUP BY.
-- Return more than one result.
select month, year, avg(page_visits) from web_stats group by month, year;
-- Filter the input to eliminate duplicates before performing the calculation.
select avg(distinct x) from t1;
-- Filter the output after performing the calculation.
select avg(x) from t1 group by y having avg(x) between 1 and 20;
```

The following examples show how to use AVG() in an analytic context. They use a table containing integers from 1 to 10. Notice how the AVG() is reported for each input value, as opposed to the GROUP BY clause which condenses the result set.

```
select x, property, avg(x) over (partition by property) as avg from int_t where property
in ('odd','even');
```

x	property	avg
2	even	6
4	even	6

6	even	6
8	even	6
10	even	6
1	odd	5
3	odd	5
5	odd	5
7	odd	5
9	odd	5

Adding an `ORDER BY` clause lets you experiment with results that are cumulative or apply to a moving set of rows (the “window”). The following examples use `AVG()` in an analytic context (that is, with an `OVER()` clause) to produce a running average of all the even values, then a running average of all the odd values. The basic `ORDER BY x` clause implicitly activates a window clause of `RANGE BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW`, which is effectively the same as `ROWS BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW`, therefore all of these examples produce the same results:

```
select x, property,
       avg(x) over (partition by property order by x) as 'cumulative average'
from int_t where property in ('odd','even');
```

x	property	cumulative average
2	even	2
4	even	3
6	even	4
8	even	5
10	even	6
1	odd	1
3	odd	2
5	odd	3
7	odd	4
9	odd	5

```
select x, property,
       avg(x) over
       (
         partition by property
         order by x
         range between unbounded preceding and current row
       ) as 'cumulative average'
from int_t where property in ('odd','even');
```

x	property	cumulative average
2	even	2
4	even	3
6	even	4
8	even	5
10	even	6
1	odd	1
3	odd	2
5	odd	3
7	odd	4
9	odd	5

```
select x, property,
       avg(x) over
       (
         partition by property
         order by x
         rows between unbounded preceding and current row
       ) as 'cumulative average'
from int_t where property in ('odd','even');
```

x	property	cumulative average
2	even	2
4	even	3

6	even	4
8	even	5
10	even	6
1	odd	1
3	odd	2
5	odd	3
7	odd	4
9	odd	5

The following examples show how to construct a moving window, with a running average taking into account 1 row before and 1 row after the current row, within the same partition (all the even values or all the odd values). Because of a restriction in the Impala RANGE syntax, this type of moving window is possible with the ROWS BETWEEN clause but not the RANGE BETWEEN clause:

```
select x, property,
       avg(x) over
       (
         partition by property
         order by x
         rows between 1 preceding and 1 following
       ) as 'moving average'
from int_t where property in ('odd','even');
```

x	property	moving average
2	even	3
4	even	4
6	even	6
8	even	8
10	even	9
1	odd	2
3	odd	3
5	odd	5
7	odd	7
9	odd	8

-- Doesn't work because of syntax restriction on RANGE clause.

```
select x, property,
       avg(x) over
       (
         partition by property
         order by x
         range between 1 preceding and 1 following
       ) as 'moving average'
from int_t where property in ('odd','even');
```

ERROR: AnalysisException: RANGE is only supported with both the lower and upper bounds UNBOUNDED or one UNBOUNDED and the other CURRENT ROW.

Restrictions:

Due to the way arithmetic on FLOAT and DOUBLE columns uses high-performance hardware instructions, and distributed queries can perform these operations in different order for each query, results can vary slightly for aggregate function calls such as SUM() and AVG() for FLOAT and DOUBLE columns, particularly on large data sets where millions or billions of values are summed or averaged. For perfect consistency and repeatability, use the DECIMAL data type for such operations instead of FLOAT or DOUBLE.

Related information:

[Impala Analytic Functions](#) on page 470, [MAX Function](#) on page 454, [MIN Function](#) on page 457

COUNT Function

An aggregate function that returns the number of rows, or the number of non-NULL rows.

Syntax:

```
COUNT([DISTINCT | ALL] expression) [OVER (analytic_clause)]
```


Depending on the argument, `COUNT()` considers rows that meet certain conditions:

- The notation `COUNT(*)` includes `NULL` values in the total.
- The notation `COUNT(column_name)` only considers rows where the column contains a non-`NULL` value.
- You can also combine `COUNT` with the `DISTINCT` operator to eliminate duplicates before counting, and to count the combinations of values across multiple columns.

When the query contains a `GROUP BY` clause, returns one value for each combination of grouping values.

Return type: `BIGINT`

Usage notes:

If you frequently run aggregate functions such as `MIN()`, `MAX()`, and `COUNT(DISTINCT)` on partition key columns, consider enabling the `OPTIMIZE_PARTITION_KEY_SCANS` query option, which optimizes such queries. This feature is available in CDH 5.7 / Impala 2.5 and higher. See [OPTIMIZE_PARTITION_KEY_SCANS Query Option \(CDH 5.7 or higher only\)](#) on page 346 for the kinds of queries that this option applies to, and slight differences in how partitions are evaluated when this query option is enabled.

Complex type considerations:

To access a column with a complex type (`ARRAY`, `STRUCT`, or `MAP`) in an aggregation function, you unpack the individual elements using join notation in the query, and then apply the function to the final scalar item, field, key, or value at the bottom of any nested type hierarchy in the column. See [Complex Types \(CDH 5.5 or higher only\)](#) on page 167 for details about using complex types in Impala.

The following example demonstrates calls to several aggregation functions using values from a column containing nested complex types (an `ARRAY` of `STRUCT` items). The array is unpacked inside the query using join notation. The array elements are referenced using the `ITEM` pseudocolumn, and the structure fields inside the array elements are referenced using dot notation. Numeric values such as `SUM()` and `AVG()` are computed using the numeric `R_NATIONKEY` field, and the general-purpose `MAX()` and `MIN()` values are computed from the string `N_NAME` field.

```
describe region;
```

name	type	comment
r_regionkey	smallint	
r_name	string	
r_comment	string	
r_nations	array<struct< n_nationkey:smallint, n_name:string, n_comment:string >>	

```
select r_name, r_nations.item.n_nationkey
  from region, region.r_nations as r_nations
 order by r_name, r_nations.item.n_nationkey;
```

r_name	item.n_nationkey
AFRICA	0
AFRICA	5
AFRICA	14
AFRICA	15
AFRICA	16
AMERICA	1
AMERICA	2
AMERICA	3
AMERICA	17
AMERICA	24
ASIA	8
ASIA	9
ASIA	12
ASIA	18
ASIA	21
EUROPE	6
EUROPE	7

EUROPE	19
EUROPE	22
EUROPE	23
MIDDLE EAST	4
MIDDLE EAST	10
MIDDLE EAST	11
MIDDLE EAST	13
MIDDLE EAST	20

```
select
  r_name,
  count(r_nations.item.n_nationkey) as count,
  sum(r_nations.item.n_nationkey) as sum,
  avg(r_nations.item.n_nationkey) as avg,
  min(r_nations.item.n_name) as minimum,
  max(r_nations.item.n_name) as maximum,
  ndv(r_nations.item.n_nationkey) as distinct_vals
from
  region, region.r_nations as r_nations
group by r_name
order by r_name;
```

r_name	count	sum	avg	minimum	maximum	distinct_vals
AFRICA	5	50	10	ALGERIA	MOZAMBIQUE	5
AMERICA	5	47	9.4	ARGENTINA	UNITED STATES	5
ASIA	5	68	13.6	CHINA	VIETNAM	5
EUROPE	5	77	15.4	FRANCE	UNITED KINGDOM	5
MIDDLE EAST	5	58	11.6	EGYPT	SAUDI ARABIA	5

Examples:

```
-- How many rows total are in the table, regardless of NULL values?
select count(*) from t1;
-- How many rows are in the table with non-NULL values for a column?
select count(c1) from t1;
-- Count the rows that meet certain conditions.
-- Again, * includes NULLs, so COUNT(*) might be greater than COUNT(col).
select count(*) from t1 where x > 10;
select count(c1) from t1 where x > 10;
-- Can also be used in combination with DISTINCT and/or GROUP BY.
-- Combine COUNT and DISTINCT to find the number of unique values.
-- Must use column names rather than * with COUNT(DISTINCT ...) syntax.
-- Rows with NULL values are not counted.
select count(distinct c1) from t1;
-- Rows with a NULL value in _either_ column are not counted.
select count(distinct c1, c2) from t1;
-- Return more than one result.
select month, year, count(distinct visitor_id) from web_stats group by month, year;
```

The following examples show how to use COUNT() in an analytic context. They use a table containing integers from 1 to 10. Notice how the COUNT() is reported for each input value, as opposed to the GROUP BY clause which condenses the result set.

```
select x, property, count(x) over (partition by property) as count from int_t where
property in ('odd','even');
```

x	property	count
2	even	5
4	even	5
6	even	5
8	even	5
10	even	5
1	odd	5
3	odd	5
5	odd	5
7	odd	5

```
| 9 | odd | 5 |
+---+-----+-----+
```

Adding an `ORDER BY` clause lets you experiment with results that are cumulative or apply to a moving set of rows (the “window”). The following examples use `COUNT()` in an analytic context (that is, with an `OVER()` clause) to produce a running count of all the even values, then a running count of all the odd values. The basic `ORDER BY x` clause implicitly activates a window clause of `RANGE BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW`, which is effectively the same as `ROWS BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW`, therefore all of these examples produce the same results:

```
select x, property,
       count(x) over (partition by property order by x) as 'cumulative count'
from int_t where property in ('odd','even');
```

```
+---+-----+-----+
| x | property | cumulative count |
+---+-----+-----+
| 2 | even    | 1                |
| 4 | even    | 2                |
| 6 | even    | 3                |
| 8 | even    | 4                |
|10 | even    | 5                |
| 1 | odd     | 1                |
| 3 | odd     | 2                |
| 5 | odd     | 3                |
| 7 | odd     | 4                |
| 9 | odd     | 5                |
+---+-----+-----+
```

```
select x, property,
       count(x) over
       (
         partition by property
         order by x
         range between unbounded preceding and current row
       ) as 'cumulative total'
from int_t where property in ('odd','even');
```

```
+---+-----+-----+
| x | property | cumulative count |
+---+-----+-----+
| 2 | even    | 1                |
| 4 | even    | 2                |
| 6 | even    | 3                |
| 8 | even    | 4                |
|10 | even    | 5                |
| 1 | odd     | 1                |
| 3 | odd     | 2                |
| 5 | odd     | 3                |
| 7 | odd     | 4                |
| 9 | odd     | 5                |
+---+-----+-----+
```

```
select x, property,
       count(x) over
       (
         partition by property
         order by x
         rows between unbounded preceding and current row
       ) as 'cumulative total'
from int_t where property in ('odd','even');
```

```
+---+-----+-----+
| x | property | cumulative count |
+---+-----+-----+
| 2 | even    | 1                |
| 4 | even    | 2                |
| 6 | even    | 3                |
| 8 | even    | 4                |
|10 | even    | 5                |
| 1 | odd     | 1                |
| 3 | odd     | 2                |
| 5 | odd     | 3                |
| 7 | odd     | 4                |
+---+-----+-----+
```

```
| 9 | odd | 5 |
+-----+
```

The following examples show how to construct a moving window, with a running count taking into account 1 row before and 1 row after the current row, within the same partition (all the even values or all the odd values). Therefore, the count is consistently 3 for rows in the middle of the window, and 2 for rows near the ends of the window, where there is no preceding or no following row in the partition. Because of a restriction in the Impala `RANGE` syntax, this type of moving window is possible with the `ROWS BETWEEN` clause but not the `RANGE BETWEEN` clause:

```
select x, property,
       count(x) over
       (
         partition by property
         order by x
         rows between 1 preceding and 1 following
       ) as 'moving total'
from int_t where property in ('odd','even');
```

x	property	moving total
2	even	2
4	even	3
6	even	3
8	even	3
10	even	2
1	odd	2
3	odd	3
5	odd	3
7	odd	3
9	odd	2

```
-- Doesn't work because of syntax restriction on RANGE clause.
```

```
select x, property,
       count(x) over
       (
         partition by property
         order by x
         range between 1 preceding and 1 following
       ) as 'moving total'
from int_t where property in ('odd','even');
```

ERROR: AnalysisException: RANGE is only supported with both the lower and upper bounds UNBOUNDED or one UNBOUNDED and the other CURRENT ROW.



Note:

By default, Impala only allows a single `COUNT(DISTINCT columns)` expression in each query.

If you do not need precise accuracy, you can produce an estimate of the distinct values for a column by specifying `NDV(column)`; a query can contain multiple instances of `NDV(column)`. To make Impala automatically rewrite `COUNT(DISTINCT)` expressions to `NDV()`, enable the `APPX_COUNT_DISTINCT` query option.

To produce the same result as multiple `COUNT(DISTINCT)` expressions, you can use the following technique for queries involving a single table:

```
select v1.c1 result1, v2.c1 result2 from
  (select count(distinct col1) as c1 from t1) v1
  cross join
  (select count(distinct col2) as c1 from t1) v2;
```

Because `CROSS JOIN` is an expensive operation, prefer to use the `NDV()` technique wherever practical.

Related information:

[Impala Analytic Functions](#) on page 470

GROUP_CONCAT Function

An aggregate function that returns a single string representing the argument value concatenated together for each row of the result set. If the optional separator string is specified, the separator is added between each pair of concatenated values. The default separator is a comma followed by a space.

Syntax:

```
GROUP_CONCAT([ALL | DISTINCT] expression [, separator])
```

Usage notes: `concat()` and `concat_ws()` are appropriate for concatenating the values of multiple columns within the same row, while `group_concat()` joins together values from different rows.

By default, returns a single string covering the whole result set. To include other columns or values in the result set, or to produce multiple concatenated strings for subsets of rows, include a `GROUP BY` clause in the query.

Return type: `STRING`

This function cannot be used in an analytic context. That is, the `OVER()` clause is not allowed at all with this function.

Currently, Impala returns an error if the result value grows larger than 1 GiB.

Examples:

The following examples illustrate various aspects of the `GROUP_CONCAT()` function.

You can call the function directly on a `STRING` column. To use it with a numeric column, cast the value to `STRING`.

```
[localhost:21000] > create table t1 (x int, s string);
[localhost:21000] > insert into t1 values (1, "one"), (3, "three"), (2, "two"), (1,
"one");
[localhost:21000] > select group_concat(s) from t1;
+-----+
| group_concat(s) |
+-----+
| one, three, two, one |
+-----+
[localhost:21000] > select group_concat(cast(x as string)) from t1;
+-----+
| group_concat(cast(x as string)) |
+-----+
| 1, 3, 2, 1 |
+-----+
```

Specify the `DISTINCT` keyword to eliminate duplicate values from the concatenated result:

```
[localhost:21000] > select group_concat(distinct s) from t1;
+-----+
| group_concat(distinct s) |
+-----+
| three, two, one |
+-----+
```

The optional separator lets you format the result in flexible ways. The separator can be an arbitrary string expression, not just a single character.

```
[localhost:21000] > select group_concat(s,"|") from t1;
+-----+
| group_concat(s, '|') |
+-----+
| one|three|two|one |
+-----+
[localhost:21000] > select group_concat(s,'---') from t1;
+-----+
| group_concat(s, '---') |
+-----+
```

```
| one---three---two---one |
+-----+

```

The default separator is a comma followed by a space. To get a comma-delimited result without extra spaces, specify a delimiter character that is only a comma.

```
[localhost:21000] > select group_concat(s,',') from t1;
+-----+
| group_concat(s, ',') |
+-----+
| one,three,two,one    |
+-----+

```

Including a `GROUP BY` clause lets you produce a different concatenated result for each group in the result set. In this example, the only `x` value that occurs more than once is 1, so that is the only row in the result set where `GROUP_CONCAT()` returns a delimited value. For groups containing a single value, `GROUP_CONCAT()` returns the original value of its `STRING` argument.

```
[localhost:21000] > select x, group_concat(s) from t1 group by x;
+-----+
| x | group_concat(s) |
+-----+
| 2 | two             |
| 3 | three           |
| 1 | one, one       |
+-----+

```

MAX Function

An aggregate function that returns the maximum value from a set of numbers. Opposite of the `MIN` function. Its single argument can be numeric column, or the numeric result of a function or expression applied to the column value. Rows with a `NULL` value for the specified column are ignored. If the table is empty, or all the values supplied to `MAX` are `NULL`, `MAX` returns `NULL`.

Syntax:

```
MAX([DISTINCT | ALL] expression) [OVER (analytic_clause)]
```

When the query contains a `GROUP BY` clause, returns one value for each combination of grouping values.

Restrictions: In Impala 2.0 and higher, this function can be used as an analytic function, but with restrictions on any window clause. For `MAX()` and `MIN()`, the window clause is only allowed if the start bound is `UNBOUNDED PRECEDING`.

Return type: Same as the input value, except for `CHAR` and `VARCHAR` arguments which produce a `STRING` result

Usage notes:

If you frequently run aggregate functions such as `MIN()`, `MAX()`, and `COUNT(DISTINCT)` on partition key columns, consider enabling the `OPTIMIZE_PARTITION_KEY_SCANS` query option, which optimizes such queries. This feature is available in CDH 5.7 / Impala 2.5 and higher. See [OPTIMIZE_PARTITION_KEY_SCANS Query Option \(CDH 5.7 or higher only\)](#) on page 346 for the kinds of queries that this option applies to, and slight differences in how partitions are evaluated when this query option is enabled.

Complex type considerations:

To access a column with a complex type (`ARRAY`, `STRUCT`, or `MAP`) in an aggregation function, you unpack the individual elements using join notation in the query, and then apply the function to the final scalar item, field, key, or value at the bottom of any nested type hierarchy in the column. See [Complex Types \(CDH 5.5 or higher only\)](#) on page 167 for details about using complex types in Impala.

The following example demonstrates calls to several aggregation functions using values from a column containing nested complex types (an `ARRAY` of `STRUCT` items). The array is unpacked inside the query using join notation. The array elements are referenced using the `ITEM` pseudocolumn, and the structure fields inside the array elements are

referenced using dot notation. Numeric values such as `SUM()` and `AVG()` are computed using the numeric `R_NATIONKEY` field, and the general-purpose `MAX()` and `MIN()` values are computed from the string `N_NAME` field.

```
describe region;
```

name	type	comment
r_regionkey	smallint	
r_name	string	
r_comment	string	
r_nations	array<struct< n_nationkey:smallint, n_name:string, n_comment:string >>	

```
select r_name, r_nations.item.n_nationkey
  from region, region.r_nations as r_nations
 order by r_name, r_nations.item.n_nationkey;
```

r_name	item.n_nationkey
AFRICA	0
AFRICA	5
AFRICA	14
AFRICA	15
AFRICA	16
AMERICA	1
AMERICA	2
AMERICA	3
AMERICA	17
AMERICA	24
ASIA	8
ASIA	9
ASIA	12
ASIA	18
ASIA	21
EUROPE	6
EUROPE	7
EUROPE	19
EUROPE	22
EUROPE	23
MIDDLE EAST	4
MIDDLE EAST	10
MIDDLE EAST	11
MIDDLE EAST	13
MIDDLE EAST	20

```
select
  r_name,
  count(r_nations.item.n_nationkey) as count,
  sum(r_nations.item.n_nationkey) as sum,
  avg(r_nations.item.n_nationkey) as avg,
  min(r_nations.item.n_name) as minimum,
  max(r_nations.item.n_name) as maximum,
  ndv(r_nations.item.n_nationkey) as distinct_vals
  from
    region, region.r_nations as r_nations
  group by r_name
  order by r_name;
```

r_name	count	sum	avg	minimum	maximum	distinct_vals
AFRICA	5	50	10	ALGERIA	MOZAMBIQUE	5
AMERICA	5	47	9.4	ARGENTINA	UNITED STATES	5
ASIA	5	68	13.6	CHINA	VIETNAM	5
EUROPE	5	77	15.4	FRANCE	UNITED KINGDOM	5
MIDDLE EAST	5	58	11.6	EGYPT	SAUDI ARABIA	5

Examples:

```
-- Find the largest value for this column in the table.
select max(c1) from t1;
-- Find the largest value for this column from a subset of the table.
select max(c1) from t1 where month = 'January' and year = '2013';
-- Find the largest value from a set of numeric function results.
select max(length(s)) from t1;
-- Can also be used in combination with DISTINCT and/or GROUP BY.
-- Return more than one result.
select month, year, max(purchase_price) from store_stats group by month, year;
-- Filter the input to eliminate duplicates before performing the calculation.
select max(distinct x) from t1;
```

The following examples show how to use `MAX()` in an analytic context. They use a table containing integers from 1 to 10. Notice how the `MAX()` is reported for each input value, as opposed to the `GROUP BY` clause which condenses the result set.

```
select x, property, max(x) over (partition by property) as max from int_t where property
in ('odd','even');
```

x	property	max
2	even	10
4	even	10
6	even	10
8	even	10
10	even	10
1	odd	9
3	odd	9
5	odd	9
7	odd	9
9	odd	9

Adding an `ORDER BY` clause lets you experiment with results that are cumulative or apply to a moving set of rows (the “window”). The following examples use `MAX()` in an analytic context (that is, with an `OVER()` clause) to display the smallest value of `x` encountered up to each row in the result set. The examples use two columns in the `ORDER BY` clause to produce a sequence of values that rises and falls, to illustrate how the `MAX()` result only increases or stays the same throughout each partition within the result set. The basic `ORDER BY x` clause implicitly activates a window clause of `RANGE BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW`, which is effectively the same as `ROWS BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW`, therefore all of these examples produce the same results:

```
select x, property,
max(x) over (order by property, x desc) as 'maximum to this point'
from int_t where property in ('prime','square');
```

x	property	maximum to this point
7	prime	7
5	prime	7
3	prime	7
2	prime	7
9	square	9
4	square	9
1	square	9

```
select x, property,
max(x) over
(
order by property, x desc
rows between unbounded preceding and current row
) as 'maximum to this point'
from int_t where property in ('prime','square');
```

x	property	maximum to this point
7	prime	7

5	prime	7
3	prime	7
2	prime	7
9	square	9
4	square	9
1	square	9

```
select x, property,
       max(x) over
       (
         order by property, x desc
         range between unbounded preceding and current row
       ) as 'maximum to this point'
from int_t where property in ('prime','square');
```

x	property	maximum to this point
7	prime	7
5	prime	7
3	prime	7
2	prime	7
9	square	9
4	square	9
1	square	9

The following examples show how to construct a moving window, with a running maximum taking into account all rows before and 1 row after the current row. Because of a restriction in the Impala RANGE syntax, this type of moving window is possible with the ROWS BETWEEN clause but not the RANGE BETWEEN clause. Because of an extra Impala restriction on the MAX() and MIN() functions in an analytic context, the lower bound must be UNBOUNDED PRECEDING.

```
select x, property,
       max(x) over
       (
         order by property, x
         rows between unbounded preceding and 1 following
       ) as 'local maximum'
from int_t where property in ('prime','square');
```

x	property	local maximum
2	prime	3
3	prime	5
5	prime	7
7	prime	7
1	square	7
4	square	9
9	square	9

-- Doesn't work because of syntax restriction on RANGE clause.

```
select x, property,
       max(x) over
       (
         order by property, x
         range between unbounded preceding and 1 following
       ) as 'local maximum'
from int_t where property in ('prime','square');
```

ERROR: AnalysisException: RANGE is only supported with both the lower and upper bounds UNBOUNDED or one UNBOUNDED and the other CURRENT ROW.

Related information:

[Impala Analytic Functions](#) on page 470, [MIN Function](#) on page 457, [AVG Function](#) on page 445

MIN Function

An aggregate function that returns the minimum value from a set of numbers. Opposite of the MAX function. Its single argument can be numeric column, or the numeric result of a function or expression applied to the column value. Rows

with a NULL value for the specified column are ignored. If the table is empty, or all the values supplied to MIN are NULL, MIN returns NULL.

Syntax:

```
MIN([DISTINCT | ALL] expression) [OVER (analytic_clause)]
```

When the query contains a GROUP BY clause, returns one value for each combination of grouping values.

Restrictions: In Impala 2.0 and higher, this function can be used as an analytic function, but with restrictions on any window clause. For MAX() and MIN(), the window clause is only allowed if the start bound is UNBOUNDED PRECEDING.

Return type: Same as the input value, except for CHAR and VARCHAR arguments which produce a STRING result

Usage notes:

If you frequently run aggregate functions such as MIN(), MAX(), and COUNT(DISTINCT) on partition key columns, consider enabling the OPTIMIZE_PARTITION_KEY_SCANS query option, which optimizes such queries. This feature is available in CDH 5.7 / Impala 2.5 and higher. See [OPTIMIZE_PARTITION_KEY_SCANS Query Option \(CDH 5.7 or higher only\)](#) on page 346 for the kinds of queries that this option applies to, and slight differences in how partitions are evaluated when this query option is enabled.

Complex type considerations:

To access a column with a complex type (ARRAY, STRUCT, or MAP) in an aggregation function, you unpack the individual elements using join notation in the query, and then apply the function to the final scalar item, field, key, or value at the bottom of any nested type hierarchy in the column. See [Complex Types \(CDH 5.5 or higher only\)](#) on page 167 for details about using complex types in Impala.

The following example demonstrates calls to several aggregation functions using values from a column containing nested complex types (an ARRAY of STRUCT items). The array is unpacked inside the query using join notation. The array elements are referenced using the ITEM pseudocolumn, and the structure fields inside the array elements are referenced using dot notation. Numeric values such as SUM() and AVG() are computed using the numeric R_NATIONKEY field, and the general-purpose MAX() and MIN() values are computed from the string N_NAME field.

```
describe region;
+-----+-----+-----+
| name          | type                               | comment |
+-----+-----+-----+
| r_regionkey   | smallint                           |         |
| r_name        | string                             |         |
| r_comment     | string                             |         |
| r_nations     | array<struct<                      |         |
|               |   n_nationkey:smallint,            |         |
|               |   n_name:string,                  |         |
|               |   n_comment:string                |         |
|               | >>                                |         |
+-----+-----+-----+

select r_name, r_nations.item.n_nationkey
from region, region.r_nations as r_nations
order by r_name, r_nations.item.n_nationkey;
+-----+-----+
| r_name          | item.n_nationkey |
+-----+-----+
| AFRICA          | 0                |
| AFRICA          | 5                |
| AFRICA          | 14               |
| AFRICA          | 15               |
| AFRICA          | 16               |
| AMERICA         | 1                |
| AMERICA         | 2                |
| AMERICA         | 3                |
| AMERICA         | 17               |
| AMERICA         | 24               |
| ASIA            | 8                |
| ASIA            | 9                |
| ASIA            | 12               |
+-----+-----+
```

ASIA	18
ASIA	21
EUROPE	6
EUROPE	7
EUROPE	19
EUROPE	22
EUROPE	23
MIDDLE EAST	4
MIDDLE EAST	10
MIDDLE EAST	11
MIDDLE EAST	13
MIDDLE EAST	20

```
select
  r_name,
  count(r_nations.item.n_nationkey) as count,
  sum(r_nations.item.n_nationkey) as sum,
  avg(r_nations.item.n_nationkey) as avg,
  min(r_nations.item.n_name) as minimum,
  max(r_nations.item.n_name) as maximum,
  ndv(r_nations.item.n_nationkey) as distinct_vals
from
  region, region.r_nations as r_nations
group by r_name
order by r_name;
```

r_name	count	sum	avg	minimum	maximum	distinct_vals
AFRICA	5	50	10	ALGERIA	MOZAMBIQUE	5
AMERICA	5	47	9.4	ARGENTINA	UNITED STATES	5
ASIA	5	68	13.6	CHINA	VIETNAM	5
EUROPE	5	77	15.4	FRANCE	UNITED KINGDOM	5
MIDDLE EAST	5	58	11.6	EGYPT	SAUDI ARABIA	5

Examples:

```
-- Find the smallest value for this column in the table.
select min(c1) from t1;
-- Find the smallest value for this column from a subset of the table.
select min(c1) from t1 where month = 'January' and year = '2013';
-- Find the smallest value from a set of numeric function results.
select min(length(s)) from t1;
-- Can also be used in combination with DISTINCT and/or GROUP BY.
-- Return more than one result.
select month, year, min(purchase_price) from store_stats group by month, year;
-- Filter the input to eliminate duplicates before performing the calculation.
select min(distinct x) from t1;
```

The following examples show how to use `MIN()` in an analytic context. They use a table containing integers from 1 to 10. Notice how the `MIN()` is reported for each input value, as opposed to the `GROUP BY` clause which condenses the result set.

```
select x, property, min(x) over (partition by property) as min from int_t where property
in ('odd', 'even');
```

x	property	min
2	even	2
4	even	2
6	even	2
8	even	2
10	even	2
1	odd	1
3	odd	1
5	odd	1
7	odd	1
9	odd	1

Adding an `ORDER BY` clause lets you experiment with results that are cumulative or apply to a moving set of rows (the “window”). The following examples use `MIN()` in an analytic context (that is, with an `OVER()` clause) to display the smallest value of `x` encountered up to each row in the result set. The examples use two columns in the `ORDER BY` clause to produce a sequence of values that rises and falls, to illustrate how the `MIN()` result only decreases or stays the same throughout each partition within the result set. The basic `ORDER BY x` clause implicitly activates a window clause of `RANGE BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW`, which is effectively the same as `ROWS BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW`, therefore all of these examples produce the same results:

```
select x, property, min(x) over (order by property, x desc) as 'minimum to this point'
from int_t where property in ('prime','square');
```

x	property	minimum to this point
7	prime	7
5	prime	5
3	prime	3
2	prime	2
9	square	2
4	square	2
1	square	1

```
select x, property,
min(x) over
(
  order by property, x desc
  range between unbounded preceding and current row
) as 'minimum to this point'
from int_t where property in ('prime','square');
```

x	property	minimum to this point
7	prime	7
5	prime	5
3	prime	3
2	prime	2
9	square	2
4	square	2
1	square	1

```
select x, property,
min(x) over
(
  order by property, x desc
  rows between unbounded preceding and current row
) as 'minimum to this point'
from int_t where property in ('prime','square');
```

x	property	minimum to this point
7	prime	7
5	prime	5
3	prime	3
2	prime	2
9	square	2
4	square	2
1	square	1

The following examples show how to construct a moving window, with a running minimum taking into account all rows before and 1 row after the current row. Because of a restriction in the Impala `RANGE` syntax, this type of moving window is possible with the `ROWS BETWEEN` clause but not the `RANGE BETWEEN` clause. Because of an extra Impala restriction on the `MAX()` and `MIN()` functions in an analytic context, the lower bound must be `UNBOUNDED PRECEDING`.

```
select x, property,
min(x) over
(
  order by property, x desc
  rows between unbounded preceding and 1 following
)
```

```
) as 'local minimum'
from int_t where property in ('prime','square');
```

x	property	local minimum
7	prime	5
5	prime	3
3	prime	2
2	prime	2
9	square	2
4	square	1
1	square	1

```
-- Doesn't work because of syntax restriction on RANGE clause.
```

```
select x, property,
min(x) over
```

```
(
  order by property, x desc
  range between unbounded preceding and 1 following
) as 'local minimum'
```

```
from int_t where property in ('prime','square');
```

```
ERROR: AnalysisException: RANGE is only supported with both the lower and upper bounds
UNBOUNDED or one UNBOUNDED and the other CURRENT ROW.
```

Related information:

[Impala Analytic Functions](#) on page 470, [MAX Function](#) on page 454, [AVG Function](#) on page 445

NDV Function

An aggregate function that returns an approximate value similar to the result of `COUNT(DISTINCT col)`, the “number of distinct values”. It is much faster than the combination of `COUNT` and `DISTINCT`, and uses a constant amount of memory and thus is less memory-intensive for columns with high cardinality.

Syntax:

```
NDV([DISTINCT | ALL] expression)
```

Usage notes:

This is the mechanism used internally by the `COMPUTE STATS` statement for computing the number of distinct values in a column.

Because this number is an estimate, it might not reflect the precise number of different values in the column, especially if the cardinality is very low or very high. If the estimated number is higher than the number of rows in the table, Impala adjusts the value internally during query planning.

Return type: `DOUBLE` in Impala 2.0 and higher; `STRING` in earlier releases

Complex type considerations:

To access a column with a complex type (`ARRAY`, `STRUCT`, or `MAP`) in an aggregation function, you unpack the individual elements using join notation in the query, and then apply the function to the final scalar item, field, key, or value at the bottom of any nested type hierarchy in the column. See [Complex Types \(CDH 5.5 or higher only\)](#) on page 167 for details about using complex types in Impala.

The following example demonstrates calls to several aggregation functions using values from a column containing nested complex types (an `ARRAY` of `STRUCT` items). The array is unpacked inside the query using join notation. The array elements are referenced using the `ITEM` pseudocolumn, and the structure fields inside the array elements are referenced using dot notation. Numeric values such as `SUM()` and `AVG()` are computed using the numeric `R_NATIONKEY` field, and the general-purpose `MAX()` and `MIN()` values are computed from the string `N_NAME` field.

```
describe region;
```

name	type	comment

r_regionkey	smallint		
r_name	string		
r_comment	string		
r_nations	array<struct< n_nationkey:smallint, n_name:string, n_comment:string >>		

```
select r_name, r_nations.item.n_nationkey
  from region, region.r_nations as r_nations
 order by r_name, r_nations.item.n_nationkey;
```

r_name	item.n_nationkey
AFRICA	0
AFRICA	5
AFRICA	14
AFRICA	15
AFRICA	16
AMERICA	1
AMERICA	2
AMERICA	3
AMERICA	17
AMERICA	24
ASIA	8
ASIA	9
ASIA	12
ASIA	18
ASIA	21
EUROPE	6
EUROPE	7
EUROPE	19
EUROPE	22
EUROPE	23
MIDDLE EAST	4
MIDDLE EAST	10
MIDDLE EAST	11
MIDDLE EAST	13
MIDDLE EAST	20

```
select
  r_name,
  count(r_nations.item.n_nationkey) as count,
  sum(r_nations.item.n_nationkey) as sum,
  avg(r_nations.item.n_nationkey) as avg,
  min(r_nations.item.n_name) as minimum,
  max(r_nations.item.n_name) as maximum,
  ndv(r_nations.item.n_nationkey) as distinct_vals
  from
  region, region.r_nations as r_nations
  group by r_name
  order by r_name;
```

r_name	count	sum	avg	minimum	maximum	distinct_vals
AFRICA	5	50	10	ALGERIA	MOZAMBIQUE	5
AMERICA	5	47	9.4	ARGENTINA	UNITED STATES	5
ASIA	5	68	13.6	CHINA	VIETNAM	5
EUROPE	5	77	15.4	FRANCE	UNITED KINGDOM	5
MIDDLE EAST	5	58	11.6	EGYPT	SAUDI ARABIA	5

Restrictions:

This function cannot be used in an analytic context. That is, the `OVER()` clause is not allowed at all with this function.

Examples:

The following example queries a billion-row table to illustrate the relative performance of `COUNT(DISTINCT)` and `NDV()`. It shows how `COUNT(DISTINCT)` gives a precise answer, but is inefficient for large-scale data where an approximate result is sufficient. The `NDV()` function gives an approximate result but is much faster.

```
select count(distinct col1) from sample_data;
+-----+
| count(distinct col1) |
+-----+
| 100000                |
+-----+
Fetched 1 row(s) in 20.13s

select cast(ndv(col1) as bigint) as col1 from sample_data;
+-----+
| col1                |
+-----+
| 139017              |
+-----+
Fetched 1 row(s) in 8.91s
```

The following example shows how you can code multiple `NDV()` calls in a single query, to easily learn which columns have substantially more or fewer distinct values. This technique is faster than running a sequence of queries with `COUNT(DISTINCT)` calls.

```
select cast(ndv(col1) as bigint) as col1, cast(ndv(col2) as bigint) as col2,
       cast(ndv(col3) as bigint) as col3, cast(ndv(col4) as bigint) as col4
from sample_data;
+-----+-----+-----+-----+
| col1    | col2    | col3    | col4    |
+-----+-----+-----+-----+
| 139017  | 282     | 46      | 145636240 |
+-----+-----+-----+-----+
Fetched 1 row(s) in 34.97s

select count(distinct col1) from sample_data;
+-----+
| count(distinct col1) |
+-----+
| 100000                |
+-----+
Fetched 1 row(s) in 20.13s

select count(distinct col2) from sample_data;
+-----+
| count(distinct col2) |
+-----+
| 278                  |
+-----+
Fetched 1 row(s) in 20.09s

select count(distinct col3) from sample_data;
+-----+
| count(distinct col3) |
+-----+
| 46                   |
+-----+
Fetched 1 row(s) in 19.12s

select count(distinct col4) from sample_data;
+-----+
| count(distinct col4) |
+-----+
| 147135880            |
+-----+
Fetched 1 row(s) in 266.95s
```

STDDEV, STDDEV_SAMP, STDDEV_POP Functions

An aggregate function that [standard deviation](#) of a set of numbers.

Syntax:

```
{ STDDEV | STDDEV_SAMP | STDDEV_POP } ([DISTINCT | ALL] expression)
```

This function works with any numeric data type.

Return type: DOUBLE in Impala 2.0 and higher; STRING in earlier releases

This function is typically used in mathematical formulas related to probability distributions.

The `STDDEV_POP()` and `STDDEV_SAMP()` functions compute the population standard deviation and sample standard deviation, respectively, of the input values. (`STDDEV()` is an alias for `STDDEV_SAMP()`.) Both functions evaluate all input rows matched by the query. The difference is that `STDDEV_SAMP()` is scaled by $1/(N-1)$ while `STDDEV_POP()` is scaled by $1/N$.

If no input rows match the query, the result of any of these functions is NULL. If a single input row matches the query, the result of any of these functions is "0.0".

Examples:

This example demonstrates how `STDDEV()` and `STDDEV_SAMP()` return the same result, while `STDDEV_POP()` uses a slightly different calculation to reflect that the input data is considered part of a larger "population".

```
[localhost:21000] > select stddev(score) from test_scores;
+-----+
| stddev(score) |
+-----+
| 28.5          |
+-----+
[localhost:21000] > select stddev_samp(score) from test_scores;
+-----+
| stddev_samp(score) |
+-----+
| 28.5              |
+-----+
[localhost:21000] > select stddev_pop(score) from test_scores;
+-----+
| stddev_pop(score) |
+-----+
| 28.4858          |
+-----+
```

This example demonstrates that, because the return value of these aggregate functions is a STRING, you must currently convert the result with `CAST`.

```
[localhost:21000] > create table score_stats as select cast(stddev(score) as decimal(7,4))
`standard_deviation`, cast(variance(score) as decimal(7,4)) `variance` from test_scores;
+-----+
| summary          |
+-----+
| Inserted 1 row(s) |
+-----+
[localhost:21000] > desc score_stats;
+-----+-----+-----+
| name              | type              | comment |
+-----+-----+-----+
| standard_deviation | decimal(7,4)     |         |
| variance          | decimal(7,4)     |         |
+-----+-----+-----+
```

Restrictions:

This function cannot be used in an analytic context. That is, the `OVER()` clause is not allowed at all with this function.

Related information:

The `STDDEV()`, `STDDEV_POP()`, and `STDDEV_SAMP()` functions compute the standard deviation (square root of the variance) based on the results of `VARIANCE()`, `VARIANCE_POP()`, and `VARIANCE_SAMP()` respectively. See [VARIANCE, VARIANCE_SAMP, VARIANCE_POP, VAR_SAMP, VAR_POP Functions](#) on page 469 for details about the variance property.

SUM Function

An aggregate function that returns the sum of a set of numbers. Its single argument can be numeric column, or the numeric result of a function or expression applied to the column value. Rows with a `NULL` value for the specified column are ignored. If the table is empty, or all the values supplied to `MIN` are `NULL`, `SUM` returns `NULL`.

Syntax:

```
SUM([DISTINCT | ALL] expression) [OVER (analytic_clause)]
```

When the query contains a `GROUP BY` clause, returns one value for each combination of grouping values.

Return type: `BIGINT` for integer arguments, `DOUBLE` for floating-point arguments

Complex type considerations:

To access a column with a complex type (`ARRAY`, `STRUCT`, or `MAP`) in an aggregation function, you unpack the individual elements using join notation in the query, and then apply the function to the final scalar item, field, key, or value at the bottom of any nested type hierarchy in the column. See [Complex Types \(CDH 5.5 or higher only\)](#) on page 167 for details about using complex types in Impala.

The following example demonstrates calls to several aggregation functions using values from a column containing nested complex types (an `ARRAY` of `STRUCT` items). The array is unpacked inside the query using join notation. The array elements are referenced using the `ITEM` pseudocolumn, and the structure fields inside the array elements are referenced using dot notation. Numeric values such as `SUM()` and `AVG()` are computed using the numeric `R_NATIONKEY` field, and the general-purpose `MAX()` and `MIN()` values are computed from the string `N_NAME` field.

```
describe region;
```

name	type	comment
r_regionkey	smallint	
r_name	string	
r_comment	string	
r_nations	array<struct< n_nationkey:smallint, n_name:string, n_comment:string >>	

```
select r_name, r_nations.item.n_nationkey
from region, region.r_nations as r_nations
order by r_name, r_nations.item.n_nationkey;
```

r_name	item.n_nationkey
AFRICA	0
AFRICA	5
AFRICA	14
AFRICA	15
AFRICA	16
AMERICA	1
AMERICA	2
AMERICA	3
AMERICA	17
AMERICA	24
ASIA	8
ASIA	9
ASIA	12
ASIA	18
ASIA	21
EUROPE	6
EUROPE	7
EUROPE	19
EUROPE	22
EUROPE	23
MIDDLE EAST	4
MIDDLE EAST	10

MIDDLE EAST	11
MIDDLE EAST	13
MIDDLE EAST	20

```
select
  r_name,
  count(r_nations.item.n_nationkey) as count,
  sum(r_nations.item.n_nationkey) as sum,
  avg(r_nations.item.n_nationkey) as avg,
  min(r_nations.item.n_name) as minimum,
  max(r_nations.item.n_name) as maximum,
  ndv(r_nations.item.n_nationkey) as distinct_vals
from
  region, region.r_nations as r_nations
group by r_name
order by r_name;
```

r_name	count	sum	avg	minimum	maximum	distinct_vals
AFRICA	5	50	10	ALGERIA	MOZAMBIQUE	5
AMERICA	5	47	9.4	ARGENTINA	UNITED STATES	5
ASIA	5	68	13.6	CHINA	VIETNAM	5
EUROPE	5	77	15.4	FRANCE	UNITED KINGDOM	5
MIDDLE EAST	5	58	11.6	EGYPT	SAUDI ARABIA	5

Examples:

The following example shows how to use SUM() to compute the total for all the values in the table, a subset of values, or the sum for each combination of values in the GROUP BY clause:

```
-- Total all the values for this column in the table.
select sum(c1) from t1;
-- Find the total for this column from a subset of the table.
select sum(c1) from t1 where month = 'January' and year = '2013';
-- Find the total from a set of numeric function results.
select sum(length(s)) from t1;
-- Often used with functions that return predefined values to compute a score.
select sum(case when grade = 'A' then 1.0 when grade = 'B' then 0.75 else 0) as
class_honors from test_scores;
-- Can also be used in combination with DISTINCT and/or GROUP BY.
-- Return more than one result.
select month, year, sum(purchase_price) from store_stats group by month, year;
-- Filter the input to eliminate duplicates before performing the calculation.
select sum(distinct x) from t1;
```

The following examples show how to use SUM() in an analytic context. They use a table containing integers from 1 to 10. Notice how the SUM() is reported for each input value, as opposed to the GROUP BY clause which condenses the result set.

```
select x, property, sum(x) over (partition by property) as sum from int_t where property
in ('odd', 'even');
```

x	property	sum
2	even	30
4	even	30
6	even	30
8	even	30
10	even	30
1	odd	25
3	odd	25
5	odd	25
7	odd	25
9	odd	25

Adding an ORDER BY clause lets you experiment with results that are cumulative or apply to a moving set of rows (the “window”). The following examples use SUM() in an analytic context (that is, with an OVER() clause) to produce a

running total of all the even values, then a running total of all the odd values. The basic `ORDER BY x` clause implicitly activates a window clause of `RANGE BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW`, which is effectively the same as `ROWS BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW`, therefore all of these examples produce the same results:

```
select x, property,
       sum(x) over (partition by property order by x) as 'cumulative total'
from int_t where property in ('odd','even');
```

x	property	cumulative total
2	even	2
4	even	6
6	even	12
8	even	20
10	even	30
1	odd	1
3	odd	4
5	odd	9
7	odd	16
9	odd	25

```
select x, property,
       sum(x) over
       (
         partition by property
         order by x
         range between unbounded preceding and current row
       ) as 'cumulative total'
from int_t where property in ('odd','even');
```

x	property	cumulative total
2	even	2
4	even	6
6	even	12
8	even	20
10	even	30
1	odd	1
3	odd	4
5	odd	9
7	odd	16
9	odd	25

```
select x, property,
       sum(x) over
       (
         partition by property
         order by x
         rows between unbounded preceding and current row
       ) as 'cumulative total'
from int_t where property in ('odd','even');
```

x	property	cumulative total
2	even	2
4	even	6
6	even	12
8	even	20
10	even	30
1	odd	1
3	odd	4
5	odd	9
7	odd	16
9	odd	25

Changing the direction of the `ORDER BY` clause causes the intermediate results of the cumulative total to be calculated in a different order:

```
select sum(x) over (partition by property order by x desc) as 'cumulative total'
from int_t where property in ('odd','even');
```

x	property	cumulative total
10	even	10
8	even	18
6	even	24
4	even	28
2	even	30
9	odd	9
7	odd	16
5	odd	21
3	odd	24
1	odd	25

The following examples show how to construct a moving window, with a running total taking into account 1 row before and 1 row after the current row, within the same partition (all the even values or all the odd values). Because of a restriction in the Impala `RANGE` syntax, this type of moving window is possible with the `ROWS BETWEEN` clause but not the `RANGE BETWEEN` clause:

```
select x, property,
sum(x) over
(
  partition by property
  order by x
  rows between 1 preceding and 1 following
) as 'moving total'
from int_t where property in ('odd','even');
```

x	property	moving total
2	even	6
4	even	12
6	even	18
8	even	24
10	even	18
1	odd	4
3	odd	9
5	odd	15
7	odd	21
9	odd	16

```
-- Doesn't work because of syntax restriction on RANGE clause.
select x, property,
sum(x) over
(
  partition by property
  order by x
  range between 1 preceding and 1 following
) as 'moving total'
from int_t where property in ('odd','even');
```

ERROR: AnalysisException: RANGE is only supported with both the lower and upper bounds UNBOUNDED or one UNBOUNDED and the other CURRENT ROW.

Restrictions:

Due to the way arithmetic on `FLOAT` and `DOUBLE` columns uses high-performance hardware instructions, and distributed queries can perform these operations in different order for each query, results can vary slightly for aggregate function calls such as `SUM()` and `AVG()` for `FLOAT` and `DOUBLE` columns, particularly on large data sets where millions or billions of values are summed or averaged. For perfect consistency and repeatability, use the `DECIMAL` data type for such operations instead of `FLOAT` or `DOUBLE`.

Related information:

[Impala Analytic Functions](#) on page 470

VARIANCE, VARIANCE_SAMP, VARIANCE_POP, VAR_SAMP, VAR_POP Functions

An aggregate function that returns the [variance](#) of a set of numbers. This is a mathematical property that signifies how far the values spread apart from the mean. The return value can be zero (if the input is a single value, or a set of identical values), or a positive number otherwise.

Syntax:

```
{ VARIANCE | VAR[IANCE]_SAMP | VAR[IANCE]_POP } ([DISTINCT | ALL] expression)
```

This function works with any numeric data type.

Return type: DOUBLE in Impala 2.0 and higher; STRING in earlier releases

This function is typically used in mathematical formulas related to probability distributions.

The VARIANCE_SAMP() and VARIANCE_POP() functions compute the sample variance and population variance, respectively, of the input values. (VARIANCE() is an alias for VARIANCE_SAMP().) Both functions evaluate all input rows matched by the query. The difference is that STDDEV_SAMP() is scaled by $1/(N-1)$ while STDDEV_POP() is scaled by $1/N$.

The functions VAR_SAMP() and VAR_POP() are the same as VARIANCE_SAMP() and VARIANCE_POP(), respectively. These aliases are available in Impala 2.0 and later.

If no input rows match the query, the result of any of these functions is NULL. If a single input row matches the query, the result of any of these functions is "0.0".

Examples:

This example demonstrates how VARIANCE() and VARIANCE_SAMP() return the same result, while VARIANCE_POP() uses a slightly different calculation to reflect that the input data is considered part of a larger "population".

```
[localhost:21000] > select variance(score) from test_scores;
+-----+
| variance(score) |
+-----+
| 812.25          |
+-----+
[localhost:21000] > select variance_samp(score) from test_scores;
+-----+
| variance_samp(score) |
+-----+
| 812.25              |
+-----+
[localhost:21000] > select variance_pop(score) from test_scores;
+-----+
| variance_pop(score) |
+-----+
| 811.438             |
+-----+
```

This example demonstrates that, because the return value of these aggregate functions is a STRING, you convert the result with CAST if you need to do further calculations as a numeric value.

```
[localhost:21000] > create table score_stats as select cast(stddev(score) as decimal(7,4))
`standard_deviation`, cast(variance(score) as decimal(7,4)) `variance` from test_scores;
+-----+
| summary |
+-----+
| Inserted 1 row(s) |
+-----+
[localhost:21000] > desc score_stats;
+-----+-----+-----+
| name | type | comment |
+-----+-----+-----+
| standard_deviation | decimal(7,4) | |
+-----+-----+-----+
```

variance	decimal(7,4)
----------	--------------

Restrictions:

This function cannot be used in an analytic context. That is, the `OVER()` clause is not allowed at all with this function.

Related information:

The `STDDEV()`, `STDDEV_POP()`, and `STDDEV_SAMP()` functions compute the standard deviation (square root of the variance) based on the results of `VARIANCE()`, `VARIANCE_POP()`, and `VARIANCE_SAMP()` respectively. See [STDDEV, STDDEV_SAMP, STDDEV_POP Functions](#) on page 463 for details about the standard deviation property.

Impala Analytic Functions

Analytic functions (also known as window functions) are a special category of built-in functions. Like aggregate functions, they examine the contents of multiple input rows to compute each output value. However, rather than being limited to one result value per `GROUP BY` group, they operate on **windows** where the input rows are ordered and grouped using flexible conditions expressed through an `OVER()` clause.

Added in: CDH 5.2.0 (Impala 2.0.0)

Some functions, such as `LAG()` and `RANK()`, can only be used in this analytic context. Some aggregate functions do double duty: when you call the aggregation functions such as `MAX()`, `SUM()`, `AVG()`, and so on with an `OVER()` clause, they produce an output value for each row, based on computations across other rows in the window.

Although analytic functions often compute the same value you would see from an aggregate function in a `GROUP BY` query, the analytic functions produce a value for each row in the result set rather than a single value for each group. This flexibility lets you include additional columns in the `SELECT` list, offering more opportunities for organizing and filtering the result set.

Analytic function calls are only allowed in the `SELECT` list and in the outermost `ORDER BY` clause of the query. During query processing, analytic functions are evaluated after other query stages such as joins, `WHERE`, and `GROUP BY`,

The rows that are part of each partition are analyzed by computations across an ordered or unordered set of rows. For example, `COUNT()` and `SUM()` might be applied to all the rows in the partition, in which case the order of analysis does not matter. The `ORDER BY` clause might be used inside the `OVER()` clause to define the ordering that applies to functions such as `LAG()` and `FIRST_VALUE()`.

Analytic functions are frequently used in fields such as finance and science to provide trend, outlier, and bucketed analysis for large data sets. You might also see the term “window functions” in database literature, referring to the sequence of rows (the “window”) that the function call applies to, particularly when the `OVER` clause includes a `ROWS` or `RANGE` keyword.

The following sections describe the analytic query clauses and the pure analytic functions provided by Impala. For usage information about aggregate functions in an analytic context, see [Impala Aggregate Functions](#) on page 443.

OVER Clause

The `OVER` clause is required for calls to pure analytic functions such as `LEAD()`, `RANK()`, and `FIRST_VALUE()`. When you include an `OVER` clause with calls to aggregate functions such as `MAX()`, `COUNT()`, or `SUM()`, they operate as analytic functions.

Syntax:

```
function(args) OVER([partition_by_clause] [order_by_clause [window_clause]])

partition_by_clause ::= PARTITION BY expr [, expr ...]
order_by_clause ::= ORDER BY expr [ASC | DESC] [NULLS FIRST | NULLS LAST] [, expr [ASC
| DESC] [NULLS FIRST | NULLS LAST] ...]
window_clause: See Window Clause
```

PARTITION BY clause:

The `PARTITION BY` clause acts much like the `GROUP BY` clause in the outermost block of a query. It divides the rows into groups containing identical values in one or more columns. These logical groups are known as *partitions*. Throughout the discussion of analytic functions, “partitions” refers to the groups produced by the `PARTITION BY` clause, not to partitioned tables. However, note the following limitation that applies specifically to analytic function calls involving partitioned tables.

In queries involving both analytic functions and partitioned tables, partition pruning only occurs for columns named in the `PARTITION BY` clause of the analytic function call. For example, if an analytic function query has a clause such as `WHERE year=2016`, the way to make the query prune all other `YEAR` partitions is to include `PARTITION BY year` in the analytic function call; for example, `OVER (PARTITION BY year, other_columns other_analytic_clauses)`.

The sequence of results from an analytic function “resets” for each new partition in the result set. That is, the set of preceding or following rows considered by the analytic function always come from a single partition. Any `MAX()`, `SUM()`, `ROW_NUMBER()`, and so on apply to each partition independently. Omit the `PARTITION BY` clause to apply the analytic operation to all the rows in the table.

ORDER BY clause:

The `ORDER BY` clause works much like the `ORDER BY` clause in the outermost block of a query. It defines the order in which rows are evaluated for the entire input set, or for each group produced by a `PARTITION BY` clause. You can order by one or multiple expressions, and for each expression optionally choose ascending or descending order and whether nulls come first or last in the sort order. Because this `ORDER BY` clause only defines the order in which rows are evaluated, if you want the results to be output in a specific order, also include an `ORDER BY` clause in the outer block of the query.

When the `ORDER BY` clause is omitted, the analytic function applies to all items in the group produced by the `PARTITION BY` clause. When the `ORDER BY` clause is included, the analysis can apply to all or a subset of the items in the group, depending on the optional window clause.

The order in which the rows are analyzed is only defined for those columns specified in `ORDER BY` clauses.

One difference between the analytic and outer uses of the `ORDER BY` clause: inside the `OVER` clause, `ORDER BY 1` or other integer value is interpreted as a constant sort value (effectively a no-op) rather than referring to column 1.

Window clause:

The window clause is only allowed in combination with an `ORDER BY` clause. If the `ORDER BY` clause is specified but the window clause is not, the default window is `RANGE BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW`. See [Window Clause](#) on page 472 for full details.

HBase considerations:

Because HBase tables are optimized for single-row lookups rather than full scans, analytic functions using the `OVER()` clause are not recommended for HBase tables. Although such queries work, their performance is lower than on comparable tables using HDFS data files.

Parquet considerations:

Analytic functions are very efficient for Parquet tables. The data that is examined during evaluation of the `OVER()` clause comes from a specified set of columns, and the values for each column are arranged sequentially within each data file.

Text table considerations:

Analytic functions are convenient to use with text tables for exploratory business intelligence. When the volume of data is substantial, prefer to use Parquet tables for performance-critical analytic queries.

Added in: CDH 5.2.0 (Impala 2.0.0)

Examples:

The following example shows how to synthesize a numeric sequence corresponding to all the rows in a table. The new table has the same columns as the old one, plus an additional column `ID` containing the integers 1, 2, 3, and so on, corresponding to the order of a `TIMESTAMP` column in the original table.

```
CREATE TABLE events_with_id AS
SELECT
  row_number() OVER (ORDER BY date_and_time) AS id,
  c1, c2, c3, c4
FROM events;
```

The following example shows how to determine the number of rows containing each value for a column. Unlike a corresponding `GROUP BY` query, this one can analyze a single column and still return all values (not just the distinct ones) from the other columns.

```
SELECT x, y, z,
  count() OVER (PARTITION BY x) AS how_many_x
FROM t1;
```

Restrictions:

You cannot directly combine the `DISTINCT` operator with analytic function calls. You can put the analytic function call in a `WITH` clause or an inline view, and apply the `DISTINCT` operator to its result set.

```
WITH t1 AS (SELECT x, sum(x) OVER (PARTITION BY x) AS total FROM t1)
SELECT DISTINCT x, total FROM t1;
```

Window Clause

Certain analytic functions accept an optional **window clause**, which makes the function analyze only certain rows “around” the current row rather than all rows in the partition. For example, you can get a moving average by specifying some number of preceding and following rows, or a running count or running total by specifying all rows up to the current position. This clause can result in different analytic results for rows within the same partition.

The window clause is supported with the `AVG()`, `COUNT()`, `FIRST_VALUE()`, `LAST_VALUE()`, and `SUM()` functions. For `MAX()` and `MIN()`, the window clause only allowed if the start bound is `UNBOUNDED PRECEDING`.

Syntax:

```
ROWS BETWEEN [ { m | UNBOUNDED } PRECEDING | CURRENT ROW ] [ AND [ CURRENT ROW | { UNBOUNDED
| n } FOLLOWING ] ]
RANGE BETWEEN [ { m | UNBOUNDED } PRECEDING | CURRENT ROW ] [ AND [ CURRENT ROW | { UNBOUNDED
| n } FOLLOWING ] ]
```

`ROWS BETWEEN` defines the size of the window in terms of the indexes of the rows in the result set. The size of the window is predictable based on the clauses the position within the result set.

`RANGE BETWEEN` does not currently support numeric arguments to define a variable-size sliding window.

Currently, Impala supports only some combinations of arguments to the `RANGE` clause:

- `RANGE BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW` (the default when `ORDER BY` is specified and the window clause is omitted)
- `RANGE BETWEEN CURRENT ROW AND UNBOUNDED FOLLOWING`
- `RANGE BETWEEN UNBOUNDED PRECEDING AND UNBOUNDED FOLLOWING`

When `RANGE` is used, `CURRENT ROW` includes not just the current row but all rows that are tied with the current row based on the `ORDER BY` expressions.

Added in: CDH 5.2.0 (Impala 2.0.0)

Examples:

The following examples show financial data for a fictional stock symbol JDR. The closing price moves up and down each day.

```
create table stock_ticker (stock_symbol string, closing_price decimal(8,2), closing_date
timestamp);
...load some data...
select * from stock_ticker order by stock_symbol, closing_date
```

stock_symbol	closing_price	closing_date
JDR	12.86	2014-10-02 00:00:00
JDR	12.89	2014-10-03 00:00:00
JDR	12.94	2014-10-04 00:00:00
JDR	12.55	2014-10-05 00:00:00
JDR	14.03	2014-10-06 00:00:00
JDR	14.75	2014-10-07 00:00:00
JDR	13.98	2014-10-08 00:00:00

The queries use analytic functions with window clauses to compute moving averages of the closing price. For example, `ROWS BETWEEN 1 PRECEDING AND 1 FOLLOWING` produces an average of the value from a 3-day span, producing a different value for each row. The first row, which has no preceding row, only gets averaged with the row following it. If the table contained more than one stock symbol, the `PARTITION BY` clause would limit the window for the moving average to only consider the prices for a single stock.

```
select stock_symbol, closing_date, closing_price,
avg(closing_price) over (partition by stock_symbol order by closing_date
rows between 1 preceding and 1 following) as moving_average
from stock_ticker;
```

stock_symbol	closing_date	closing_price	moving_average
JDR	2014-10-02 00:00:00	12.86	12.87
JDR	2014-10-03 00:00:00	12.89	12.89
JDR	2014-10-04 00:00:00	12.94	12.79
JDR	2014-10-05 00:00:00	12.55	13.17
JDR	2014-10-06 00:00:00	14.03	13.77
JDR	2014-10-07 00:00:00	14.75	14.25
JDR	2014-10-08 00:00:00	13.98	14.36

The clause `ROWS BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW` produces a cumulative moving average, from the earliest data up to the value for each day.

```
select stock_symbol, closing_date, closing_price,
avg(closing_price) over (partition by stock_symbol order by closing_date
rows between unbounded preceding and current row) as moving_average
from stock_ticker;
```

stock_symbol	closing_date	closing_price	moving_average
JDR	2014-10-02 00:00:00	12.86	12.86
JDR	2014-10-03 00:00:00	12.89	12.87
JDR	2014-10-04 00:00:00	12.94	12.89
JDR	2014-10-05 00:00:00	12.55	12.81
JDR	2014-10-06 00:00:00	14.03	13.05
JDR	2014-10-07 00:00:00	14.75	13.33
JDR	2014-10-08 00:00:00	13.98	13.42

AVG Function - Analytic Context

You can include an `OVER` clause with a call to this function to use it as an analytic function. See [AVG Function](#) on page 445 for details and examples.

COUNT Function - Analytic Context

You can include an `OVER` clause with a call to this function to use it as an analytic function. See [COUNT Function](#) on page 448 for details and examples.

CUME_DIST Function (CDH 5.5 or higher only)

Returns the cumulative distribution of a value. The value for each row in the result set is greater than 0 and less than or equal to 1.

Syntax:

```
CUME_DIST (expr)
  OVER ([partition_by_clause] order_by_clause)
```

The `ORDER BY` clause is required. The `PARTITION BY` clause is optional. The window clause is not allowed.

Usage notes:

Within each partition of the result set, the `CUME_DIST()` value represents an ascending sequence that ends at 1. Each value represents the proportion of rows in the partition whose values are less than or equal to the value in the current row.

If the sequence of input values contains ties, the `CUME_DIST()` results are identical for the tied values.

Impala only supports the `CUME_DIST()` function in an analytic context, not as a regular aggregate function.

Examples:

This example uses a table with 9 rows. The `CUME_DIST()` function evaluates the entire table because there is no `PARTITION BY` clause, with the rows ordered by the weight of the animal. the sequence of values shows that 1/9 of the values are less than or equal to the lightest animal (mouse), 2/9 of the values are less than or equal to the second-lightest animal, and so on up to the heaviest animal (elephant), where 9/9 of the rows are less than or equal to its weight.

```
create table animals (name string, kind string, kilos decimal(9,3));
insert into animals values
  ('Elephant', 'Mammal', 4000), ('Giraffe', 'Mammal', 1200), ('Mouse', 'Mammal', 0.020),
  ('Condor', 'Bird', 15), ('Horse', 'Mammal', 500), ('Owl', 'Bird', 2.5),
  ('Ostrich', 'Bird', 145), ('Polar bear', 'Mammal', 700), ('Housecat', 'Mammal', 5);

select name, cume_dist() over (order by kilos) from animals;
```

name	cume_dist() OVER(...)
Elephant	1
Giraffe	0.8888888888888888
Polar bear	0.7777777777777778
Horse	0.6666666666666666
Ostrich	0.5555555555555556
Condor	0.4444444444444444
Housecat	0.3333333333333333
Owl	0.2222222222222222
Mouse	0.1111111111111111

Using a `PARTITION BY` clause produces a separate sequence for each partition group, in this case one for mammals and one for birds. Because there are 3 birds and 6 mammals, the sequence illustrates how 1/3 of the “Bird” rows have a `kilos` value that is less than or equal to the lightest bird, 1/6 of the “Mammal” rows have a `kilos` value that is less than or equal to the lightest mammal, and so on until both the heaviest bird and heaviest mammal have a `CUME_DIST()` value of 1.

```
select name, kind, cume_dist() over (partition by kind order by kilos) from animals
```

name	kind	cume_dist() OVER(...)
Elephant	Mammal	1
Giraffe	Mammal	0.8888888888888888
Polar bear	Mammal	0.7777777777777778
Horse	Mammal	0.6666666666666666
Ostrich	Mammal	0.5555555555555556
Condor	Bird	1
Housecat	Mammal	0.3333333333333333
Owl	Bird	0.5
Mouse	Mammal	0.1111111111111111

Ostrich	Bird	1
Condor	Bird	0.6666666666666666
Owl	Bird	0.3333333333333333
Elephant	Mammal	1
Giraffe	Mammal	0.8333333333333334
Polar bear	Mammal	0.6666666666666666
Horse	Mammal	0.5
Housecat	Mammal	0.3333333333333333
Mouse	Mammal	0.1666666666666667

We can reverse the ordering within each partition group by using an `ORDER BY ... DESC` clause within the `OVER()` clause. Now the lightest (smallest value of `kilos`) animal of each kind has a `CUME_DIST()` value of 1.

```
select name, kind, cume_dist() over (partition by kind order by kilos desc) from animals
```

name	kind	cume_dist() OVER(...)
Owl	Bird	1
Condor	Bird	0.6666666666666666
Ostrich	Bird	0.3333333333333333
Mouse	Mammal	1
Housecat	Mammal	0.8333333333333334
Horse	Mammal	0.6666666666666666
Polar bear	Mammal	0.5
Giraffe	Mammal	0.3333333333333333
Elephant	Mammal	0.1666666666666667

The following example manufactures some rows with identical values in the `kilos` column, to demonstrate how the results look in case of tie values. For simplicity, it only shows the `CUME_DIST()` sequence for the “Bird” rows. Now with 3 rows all with a value of 15, all of those rows have the same `CUME_DIST()` value. 4/5 of the rows have a value for `kilos` that is less than or equal to 15.

```
insert into animals values ('California Condor', 'Bird', 15), ('Andean Condor', 'Bird', 15)
```

```
select name, kind, cume_dist() over (order by kilos) from animals where kind = 'Bird';
```

name	kind	cume_dist() OVER(...)
Ostrich	Bird	1
Condor	Bird	0.8
California Condor	Bird	0.8
Andean Condor	Bird	0.8
Owl	Bird	0.2

The following example shows how to use an `ORDER BY` clause in the outer block to order the result set in case of ties. Here, all the “Bird” rows are together, then in descending order by the result of the `CUME_DIST()` function, and all tied `CUME_DIST()` values are ordered by the animal name.

```
select name, kind, cume_dist() over (partition by kind order by kilos) as ordering
from animals
where
  kind = 'Bird'
order by kind, ordering desc, name;
```

name	kind	ordering
Ostrich	Bird	1
Andean Condor	Bird	0.8
California Condor	Bird	0.8
Condor	Bird	0.8
Owl	Bird	0.2

DENSE_RANK Function

Returns an ascending sequence of integers, starting with 1. The output sequence produces duplicate integers for duplicate values of the ORDER BY expressions. After generating duplicate output values for the “tied” input values, the function continues the sequence with the next higher integer. Therefore, the sequence contains duplicates but no gaps when the input contains duplicates. Starts the sequence over for each group produced by the PARTITIONED BY clause.

Syntax:

```
DENSE_RANK() OVER([partition_by_clause] order_by_clause)
```

The PARTITION BY clause is optional. The ORDER BY clause is required. The window clause is not allowed.

Usage notes:

Often used for top-N and bottom-N queries. For example, it could produce a “top 10” report including all the items with the 10 highest values, even if several items tied for 1st place.

Similar to ROW_NUMBER and RANK. These functions differ in how they treat duplicate combinations of values.

Added in: CDH 5.2.0 (Impala 2.0.0)

Examples:

The following example demonstrates how the DENSE_RANK() function identifies where each value “places” in the result set, producing the same result for duplicate values, but with a strict sequence from 1 to the number of groups. For example, when results are ordered by the x column, both 1 values are tied for first; both 2 values are tied for second; and so on.

```
select x, dense_rank() over(order by x) as rank, property from int_t;
```

x	rank	property
1	1	square
1	1	odd
2	2	even
2	2	prime
3	3	prime
3	3	odd
4	4	even
4	4	square
5	5	odd
5	5	prime
6	6	even
6	6	perfect
7	7	lucky
7	7	lucky
7	7	lucky
7	7	odd
7	7	prime
8	8	even
9	9	square
9	9	odd
10	10	round
10	10	even

The following examples show how the DENSE_RANK() function is affected by the PARTITION property within the ORDER BY clause.

Partitioning by the PROPERTY column groups all the even, odd, and so on values together, and DENSE_RANK() returns the place of each value within the group, producing several ascending sequences.

```
select x, dense_rank() over(partition by property order by x) as rank, property from int_t;
```

x	rank	property
---	------	----------

2	1	even
4	2	even
6	3	even
8	4	even
10	5	even
7	1	lucky
7	1	lucky
7	1	lucky
1	1	odd
3	2	odd
5	3	odd
7	4	odd
9	5	odd
6	1	perfect
2	1	prime
3	2	prime
5	3	prime
7	4	prime
10	1	round
1	1	square
4	2	square
9	3	square

Partitioning by the `x` column groups all the duplicate numbers together and returns the place each value within the group; because each value occurs only 1 or 2 times, `DENSE_RANK()` designates each `x` value as either first or second within its group.

```
select x, dense_rank() over(partition by x order by property) as rank, property from
int_t;
```

x	rank	property
1	1	odd
1	2	square
2	1	even
2	2	prime
3	1	odd
3	2	prime
4	1	even
4	2	square
5	1	odd
5	2	prime
6	1	even
6	2	perfect
7	1	lucky
7	1	lucky
7	1	lucky
7	2	odd
7	3	prime
8	1	even
9	1	odd
9	2	square
10	1	even
10	2	round

The following example shows how `DENSE_RANK()` produces a continuous sequence while still allowing for ties. In this case, Croesus and Midas both have the second largest fortune, while Crassus has the third largest. (In [RANK Function](#) on page 484, you see a similar query with the `RANK()` function that shows that while Crassus has the third largest fortune, he is the fourth richest person.)

```
select dense_rank() over (order by net_worth desc) as placement, name, net_worth from
wealth order by placement, name;
```

placement	name	net_worth
1	Solomon	2000000000.00
2	Croesus	1000000000.00

2	Midas	1000000000.00
3	Crassus	500000000.00
4	Scrooge	80000000.00

Related information:

[RANK Function](#) on page 484, [ROW_NUMBER Function](#) on page 486

FIRST_VALUE Function

Returns the expression value from the first row in the window. The return value is NULL if the input expression is NULL.

Syntax:

```
FIRST_VALUE(expr) OVER([partition_by_clause] order_by_clause [window_clause])
```

The PARTITION BY clause is optional. The ORDER BY clause is required. The window clause is optional.

Usage notes:

If any duplicate values occur in the tuples evaluated by the ORDER BY clause, the result of this function is not deterministic. Consider adding additional ORDER BY columns to ensure consistent ordering.

Added in: CDH 5.2.0 (Impala 2.0.0)

Examples:

The following example shows a table with a wide variety of country-appropriate greetings. For consistency, we want to standardize on a single greeting for each country. The FIRST_VALUE() function helps to produce a mail merge report where every person from the same country is addressed with the same greeting.

```
select name, country, greeting from mail_merge
```

name	country	greeting
Pete	USA	Hello
John	USA	Hi
Boris	Germany	Guten tag
Michael	Germany	Guten morgen
Bjorn	Sweden	Hej
Mats	Sweden	Tja

```
select country, name,
       first_value(greeting)
         over (partition by country order by name, greeting) as greeting
  from mail_merge;
```

country	name	greeting
Germany	Boris	Guten tag
Germany	Michael	Guten tag
Sweden	Bjorn	Hej
Sweden	Mats	Hej
USA	John	Hi
USA	Pete	Hi

Changing the order in which the names are evaluated changes which greeting is applied to each group.

```
select country, name,
       first_value(greeting)
         over (partition by country order by name desc, greeting) as greeting
  from mail_merge;
```

country	name	greeting
Germany	Michael	Guten morgen

Germany	Boris	Guten morgen
Sweden	Mats	Tja
Sweden	Bjorn	Tja
USA	Pete	Hello
USA	John	Hello

Related information:

[LAST_VALUE Function](#) on page 480

LAG Function

This function returns the value of an expression using column values from a preceding row. You specify an integer offset, which designates a row position some number of rows previous to the current row. Any column references in the expression argument refer to column values from that prior row. Typically, the table contains a time sequence or numeric sequence column that clearly distinguishes the ordering of the rows.

Syntax:

```
LAG (expr [, offset] [, default])
  OVER ([partition_by_clause] order_by_clause)
```

The ORDER BY clause is required. The PARTITION BY clause is optional. The window clause is not allowed.

Usage notes:

Sometimes used as an alternative to doing a self-join.

Added in: CDH 5.2.0 (Impala 2.0.0)

Examples:

The following example uses the same stock data created in [Window Clause](#) on page 472. For each day, the query prints the closing price alongside the previous day's closing price. The first row for each stock symbol has no previous row, so that LAG() value is NULL.

```
select stock_symbol, closing_date, closing_price,
       lag(closing_price,1) over (partition by stock_symbol order by closing_date) as
"yesterday closing"
  from stock_ticker
  order by closing_date;
```

stock_symbol	closing_date	closing_price	yesterday closing
JDR	2014-09-13 00:00:00	12.86	NULL
JDR	2014-09-14 00:00:00	12.89	12.86
JDR	2014-09-15 00:00:00	12.94	12.89
JDR	2014-09-16 00:00:00	12.55	12.94
JDR	2014-09-17 00:00:00	14.03	12.55
JDR	2014-09-18 00:00:00	14.75	14.03
JDR	2014-09-19 00:00:00	13.98	14.75

The following example does an arithmetic operation between the current row and a value from the previous row, to produce a delta value for each day. This example also demonstrates how ORDER BY works independently in the different parts of the query. The ORDER BY closing_date in the OVER clause makes the query analyze the rows in chronological order. Then the outer query block uses ORDER BY closing_date DESC to present the results with the most recent date first.

```
select stock_symbol, closing_date, closing_price,
       cast(
         closing_price - lag(closing_price,1) over
         (partition by stock_symbol order by closing_date)
         as decimal(8,2)
       )
  as "change from yesterday"
```

```
from stock_ticker
order by closing_date desc;
```

stock_symbol	closing_date	closing_price	change from yesterday
JDR	2014-09-19 00:00:00	13.98	-0.76
JDR	2014-09-18 00:00:00	14.75	0.72
JDR	2014-09-17 00:00:00	14.03	1.47
JDR	2014-09-16 00:00:00	12.55	-0.38
JDR	2014-09-15 00:00:00	12.94	0.04
JDR	2014-09-14 00:00:00	12.89	0.03
JDR	2014-09-13 00:00:00	12.86	NULL

Related information:

This function is the converse of [LEAD Function](#) on page 480.

LAST_VALUE Function

Returns the expression value from the last row in the window. This same value is repeated for all result rows for the group. The return value is NULL if the input expression is NULL.

Syntax:

```
LAST_VALUE(expr) OVER([partition_by_clause] order_by_clause [window_clause])
```

The PARTITION BY clause is optional. The ORDER BY clause is required. The window clause is optional.

Usage notes:

If any duplicate values occur in the tuples evaluated by the ORDER BY clause, the result of this function is not deterministic. Consider adding additional ORDER BY columns to ensure consistent ordering.

Added in: CDH 5.2.0 (Impala 2.0.0)

Examples:

The following example uses the same MAIL_MERGE table as in the example for [FIRST_VALUE Function](#) on page 478. Because the default window when ORDER BY is used is BETWEEN UNBOUNDED PRECEDING AND CURRENT ROW, the query requires the UNBOUNDED FOLLOWING to look ahead to subsequent rows and find the last value for each country.

```
select country, name,
last_value(greeting) over (
partition by country order by name, greeting
rows between unbounded preceding and unbounded following
) as greeting
from mail_merge
```

country	name	greeting
Germany	Boris	Guten morgen
Germany	Michael	Guten morgen
Sweden	Bjorn	Tja
Sweden	Mats	Tja
USA	John	Hello
USA	Pete	Hello

Related information:

[FIRST_VALUE Function](#) on page 478

LEAD Function

This function returns the value of an expression using column values from a following row. You specify an integer offset, which designates a row position some number of rows after to the current row. Any column references in the

expression argument refer to column values from that later row. Typically, the table contains a time sequence or numeric sequence column that clearly distinguishes the ordering of the rows.

Syntax:

```
LEAD (expr [, offset] [, default])
  OVER ([partition_by_clause] order_by_clause)
```

The ORDER BY clause is required. The PARTITION BY clause is optional. The window clause is not allowed.

Usage notes:

Sometimes used as an alternative to doing a self-join.

Added in: CDH 5.2.0 (Impala 2.0.0)

Examples:

The following example uses the same stock data created in [Window Clause](#) on page 472. The query analyzes the closing price for a stock symbol, and for each day evaluates if the closing price for the following day is higher or lower.

```
select stock_symbol, closing_date, closing_price,
  case
    (lead(closing_price,1)
     over (partition by stock_symbol order by closing_date)
     - closing_price) > 0
    when true then "higher"
    when false then "flat or lower"
  end as "trending"
from stock_ticker
order by closing_date;
```

stock_symbol	closing_date	closing_price	trending
JDR	2014-09-13 00:00:00	12.86	higher
JDR	2014-09-14 00:00:00	12.89	higher
JDR	2014-09-15 00:00:00	12.94	flat or lower
JDR	2014-09-16 00:00:00	12.55	higher
JDR	2014-09-17 00:00:00	14.03	higher
JDR	2014-09-18 00:00:00	14.75	flat or lower
JDR	2014-09-19 00:00:00	13.98	NULL

Related information:

This function is the converse of [LAG Function](#) on page 479.

MAX Function - Analytic Context

You can include an OVER clause with a call to this function to use it as an analytic function. See [MAX Function](#) on page 454 for details and examples.

MIN Function - Analytic Context

You can include an OVER clause with a call to this function to use it as an analytic function. See [MIN Function](#) on page 457 for details and examples.

NTILE Function (CDH 5.5 or higher only)

Returns the “bucket number” associated with each row, between 1 and the value of an expression. For example, creating 100 buckets puts the lowest 1% of values in the first bucket, while creating 10 buckets puts the lowest 10% of values in the first bucket. Each partition can have a different number of buckets.

Syntax:

```
NTILE (expr [, offset ...])
  OVER ([partition_by_clause] order_by_clause)
```

The `ORDER BY` clause is required. The `PARTITION BY` clause is optional. The window clause is not allowed.

Usage notes:

The “ntile” name is derived from the practice of dividing result sets into fourths (quartile), tenths (decile), and so on. The `NTILE()` function divides the result set based on an arbitrary percentile value.

The number of buckets must be a positive integer.

The number of items in each bucket is identical or almost so, varying by at most 1. If the number of items does not divide evenly between the buckets, the remaining N items are divided evenly among the first N buckets.

If the number of buckets N is greater than the number of input rows in the partition, then the first N buckets each contain one item, and the remaining buckets are empty.

Examples:

The following example shows divides groups of animals into 4 buckets based on their weight. The `ORDER BY ... DESC` clause in the `OVER()` clause means that the heaviest 25% are in the first group, and the lightest 25% are in the fourth group. (The `ORDER BY` in the outermost part of the query shows how you can order the final result set independently from the order in which the rows are evaluated by the `OVER()` clause.) Because there are 9 rows in the group, divided into 4 buckets, the first bucket receives the extra item.

```
create table animals (name string, kind string, kilos decimal(9,3));
insert into animals values
  ('Elephant', 'Mammal', 4000), ('Giraffe', 'Mammal', 1200), ('Mouse', 'Mammal', 0.020),
  ('Condor', 'Bird', 15), ('Horse', 'Mammal', 500), ('Owl', 'Bird', 2.5),
  ('Ostrich', 'Bird', 145), ('Polar bear', 'Mammal', 700), ('Housecat', 'Mammal', 5);

select name, ntile(4) over (order by kilos desc) as quarter
from animals
order by quarter desc;
```

name	quarter
Owl	4
Mouse	4
Condor	3
Housecat	3
Horse	2
Ostrich	2
Elephant	1
Giraffe	1
Polar bear	1

The following examples show how the `PARTITION` clause works for the `NTILE()` function. Here, we divide each kind of animal (mammal or bird) into 2 buckets, the heavier half and the lighter half.

```
select name, kind, ntile(2) over (partition by kind order by kilos desc) as half
from animals
order by kind;
```

name	kind	half
Ostrich	Bird	1
Condor	Bird	1
Owl	Bird	2
Elephant	Mammal	1
Giraffe	Mammal	1
Polar bear	Mammal	1
Horse	Mammal	2
Housecat	Mammal	2
Mouse	Mammal	2

Again, the result set can be ordered independently from the analytic evaluation. This next example lists all the animals heaviest to lightest, showing that elephant and giraffe are in the “top half” of mammals by weight, while housecat and mouse are in the “bottom half”.

```
select name, kind, ntile(2) over (partition by kind order by kilos desc) as half
from animals
order by kilos desc;
```

name	kind	half
Elephant	Mammal	1
Giraffe	Mammal	1
Polar bear	Mammal	1
Horse	Mammal	2
Ostrich	Bird	1
Condor	Bird	1
Housecat	Mammal	2
Owl	Bird	2
Mouse	Mammal	2

PERCENT_RANK Function (CDH 5.5 or higher only)

Syntax:

```
PERCENT_RANK (expr)
OVER ([partition_by_clause] order_by_clause)
```

Calculates the rank, expressed as a percentage, of each row within a group of rows. If `rank` is the value for that same row from the `RANK()` function (from 1 to the total number of rows in the partition group), then the `PERCENT_RANK()` value is calculated as $(rank - 1) / (rows_in_group - 1)$. If there is only a single item in the partition group, its `PERCENT_RANK()` value is 0.

The `ORDER BY` clause is required. The `PARTITION BY` clause is optional. The window clause is not allowed.

Usage notes:

This function is similar to the `RANK` and `CUME_DIST()` functions: it returns an ascending sequence representing the position of each row within the rows of the same partition group. The actual numeric sequence is calculated differently, and the handling of duplicate (tied) values is different.

The return values range from 0 to 1 inclusive. The first row in each partition group always has the value 0. A `NULL` value is considered the lowest possible value. In the case of duplicate input values, all the corresponding rows in the result set have an identical value: the lowest `PERCENT_RANK()` value of those tied rows. (In contrast to `CUME_DIST()`, where all tied rows have the highest `CUME_DIST()` value.)

Examples:

The following example uses the same `ANIMALS` table as the examples for `CUME_DIST()` and `NTILE()`, with a few additional rows to illustrate the results where some values are `NULL` or there is only a single row in a partition group.

```
insert into animals values ('Komodo dragon', 'Reptile', 70);
insert into animals values ('Unicorn', 'Mythical', NULL);
insert into animals values ('Fire-breathing dragon', 'Mythical', NULL);
```

As with `CUME_DIST()`, there is an ascending sequence for each kind of animal. For example, the “Birds” and “Mammals” rows each have a `PERCENT_RANK()` sequence that ranges from 0 to 1. The “Reptile” row has a `PERCENT_RANK()` of 0 because that partition group contains only a single item. Both “Mythical” animals have a `PERCENT_RANK()` of 0 because a `NULL` is considered the lowest value within its partition group.

```
select name, kind, percent_rank() over (partition by kind order by kilos) from animals;
```

name	kind	percent_rank() OVER(...)
Mouse	Mammal	0

Housecat	Mammal	0.2
Horse	Mammal	0.4
Polar bear	Mammal	0.6
Giraffe	Mammal	0.8
Elephant	Mammal	1
Komodo dragon	Reptile	0
Owl	Bird	0
California Condor	Bird	0.25
Andean Condor	Bird	0.25
Condor	Bird	0.25
Ostrich	Bird	1
Fire-breathing dragon	Mythical	0
Unicorn	Mythical	0

RANK Function

Returns an ascending sequence of integers, starting with 1. The output sequence produces duplicate integers for duplicate values of the ORDER BY expressions. After generating duplicate output values for the “tied” input values, the function increments the sequence by the number of tied values. Therefore, the sequence contains both duplicates and gaps when the input contains duplicates. Starts the sequence over for each group produced by the PARTITIONED BY clause.

Syntax:

```
RANK() OVER([partition_by_clause] order_by_clause)
```

The PARTITION BY clause is optional. The ORDER BY clause is required. The window clause is not allowed.

Usage notes:

Often used for top-N and bottom-N queries. For example, it could produce a “top 10” report including several items that were tied for 10th place.

Similar to ROW_NUMBER and DENSE_RANK. These functions differ in how they treat duplicate combinations of values.

Added in: CDH 5.2.0 (Impala 2.0.0)

Examples:

The following example demonstrates how the RANK() function identifies where each value “places” in the result set, producing the same result for duplicate values, and skipping values in the sequence to account for the number of duplicates. For example, when results are ordered by the x column, both 1 values are tied for first; both 2 values are tied for third; and so on.

```
select x, rank() over(order by x) as rank, property from int_t;
```

x	rank	property
1	1	square
1	1	odd
2	3	even
2	3	prime
3	5	prime
3	5	odd
4	7	even
4	7	square
5	9	odd
5	9	prime
6	11	even
6	11	perfect
7	13	lucky
7	13	lucky
7	13	lucky
7	13	odd
7	13	prime
8	18	even
9	19	square

9	19	odd
10	21	round
10	21	even

The following examples show how the `RANK()` function is affected by the `PARTITION` property within the `ORDER BY` clause.

Partitioning by the `PROPERTY` column groups all the even, odd, and so on values together, and `RANK()` returns the place of each value within the group, producing several ascending sequences.

```
select x, rank() over(partition by property order by x) as rank, property from int_t;
```

x	rank	property
2	1	even
4	2	even
6	3	even
8	4	even
10	5	even
7	1	lucky
7	1	lucky
7	1	lucky
1	1	odd
3	2	odd
5	3	odd
7	4	odd
9	5	odd
6	1	perfect
2	1	prime
3	2	prime
5	3	prime
7	4	prime
10	1	round
1	1	square
4	2	square
9	3	square

Partitioning by the `x` column groups all the duplicate numbers together and returns the place each value within the group; because each value occurs only 1 or 2 times, `RANK()` designates each `x` value as either first or second within its group.

```
select x, rank() over(partition by x order by property) as rank, property from int_t;
```

x	rank	property
1	1	odd
1	2	square
2	1	even
2	2	prime
3	1	odd
3	2	prime
4	1	even
4	2	square
5	1	odd
5	2	prime
6	1	even
6	2	perfect
7	1	lucky
7	1	lucky
7	1	lucky
7	4	odd
7	5	prime
8	1	even
9	1	odd
9	2	square
10	1	even
10	2	round

The following example shows how a magazine might prepare a list of history's wealthiest people. Croesus and Midas are tied for second, then Crassus is fourth.

```
select rank() over (order by net_worth desc) as rank, name, net_worth from wealth order
by rank, name;
```

rank	name	net_worth
1	Solomon	2000000000.00
2	Croesus	1000000000.00
2	Midas	1000000000.00
4	Crassus	500000000.00
5	Scrooge	80000000.00

Related information:

[DENSE_RANK Function](#) on page 476, [ROW_NUMBER Function](#) on page 486

ROW_NUMBER Function

Returns an ascending sequence of integers, starting with 1. Starts the sequence over for each group produced by the `PARTITIONED BY` clause. The output sequence includes different values for duplicate input values. Therefore, the sequence never contains any duplicates or gaps, regardless of duplicate input values.

Syntax:

```
ROW_NUMBER() OVER([partition_by_clause] order_by_clause)
```

The `ORDER BY` clause is required. The `PARTITION BY` clause is optional. The window clause is not allowed.

Usage notes:

Often used for top-N and bottom-N queries where the input values are known to be unique, or precisely N rows are needed regardless of duplicate values.

Because its result value is different for each row in the result set (when used without a `PARTITION BY` clause), `ROW_NUMBER()` can be used to synthesize unique numeric ID values, for example for result sets involving unique values or tuples.

Similar to `RANK` and `DENSE_RANK`. These functions differ in how they treat duplicate combinations of values.

Added in: CDH 5.2.0 (Impala 2.0.0)

Examples:

The following example demonstrates how `ROW_NUMBER()` produces a continuous numeric sequence, even though some values of `x` are repeated.

```
select x, row_number() over(order by x, property) as row_number, property from int_t;
```

x	row_number	property
1	1	odd
1	2	square
2	3	even
2	4	prime
3	5	odd
3	6	prime
4	7	even
4	8	square
5	9	odd
5	10	prime
6	11	even
6	12	perfect
7	13	lucky
7	14	lucky
7	15	lucky

7	16	odd
7	17	prime
8	18	even
9	19	odd
9	20	square
10	21	even
10	22	round

The following example shows how a financial institution might assign customer IDs to some of history's wealthiest figures. Although two of the people have identical net worth figures, unique IDs are required for this purpose. `ROW_NUMBER()` produces a sequence of five different values for the five input rows.

```
select row_number() over (order by net_worth desc) as account_id, name, net_worth
from wealth order by account_id, name;
```

account_id	name	net_worth
1	Solomon	2000000000.00
2	Croesus	1000000000.00
3	Midas	1000000000.00
4	Crassus	500000000.00
5	Scrooge	80000000.00

Related information:

[RANK Function](#) on page 484, [DENSE_RANK Function](#) on page 476

SUM Function - Analytic Context

You can include an `OVER` clause with a call to this function to use it as an analytic function. See [SUM Function](#) on page 465 for details and examples.

Impala User-Defined Functions (UDFs)

User-defined functions (frequently abbreviated as UDFs) let you code your own application logic for processing column values during an Impala query. For example, a UDF could perform calculations using an external math library, combine several column values into one, do geospatial calculations, or other kinds of tests and transformations that are outside the scope of the built-in SQL operators and functions.

You can use UDFs to simplify query logic when producing reports, or to transform data in flexible ways when copying from one table to another with the `INSERT ... SELECT` syntax.

You might be familiar with this feature from other database products, under names such as stored functions or stored routines.

Impala support for UDFs is available in Impala 1.2 and higher:

- In Impala 1.1, using UDFs in a query required using the Hive shell. (Because Impala and Hive share the same metastore database, you could switch to Hive to run just those queries requiring UDFs, then switch back to Impala.)
- Starting in Impala 1.2, Impala can run both high-performance native code UDFs written in C++, and Java-based Hive UDFs that you might already have written.
- Impala can run scalar UDFs that return a single value for each row of the result set, and user-defined aggregate functions (UDAFs) that return a value based on a set of rows. Currently, Impala does not support user-defined table functions (UDTFs) or window functions.

UDF Concepts

Depending on your use case, you might write all-new functions, reuse Java UDFs that you have already written for Hive, or port Hive Java UDF code to higher-performance native Impala UDFs in C++. You can code either scalar functions for producing results one row at a time, or more complex aggregate functions for doing analysis across. The following sections discuss these different aspects of working with UDFs.

UDFs and UDAFs

Depending on your use case, the user-defined functions (UDFs) you write might accept or produce different numbers of input and output values:

- The most general kind of user-defined function (the one typically referred to by the abbreviation UDF) takes a single input value and produces a single output value. When used in a query, it is called once for each row in the result set. For example:

```
select customer_name, is_frequent_customer(customer_id) from customers;
select obfuscate(sensitive_column) from sensitive_data;
```

- A user-defined aggregate function (UDAF) accepts a group of values and returns a single value. You use UDAFs to summarize and condense sets of rows, in the same style as the built-in `COUNT`, `MAX()`, `SUM()`, and `AVG()` functions. When called in a query that uses the `GROUP BY` clause, the function is called once for each combination of `GROUP BY` values. For example:

```
-- Evaluates multiple rows but returns a single value.
select closest_restaurant(latitude, longitude) from places;

-- Evaluates batches of rows and returns a separate value for each batch.
select most_profitable_location(store_id, sales, expenses, tax_rate, depreciation) from
franchise_data group by year;
```

- Currently, Impala does not support other categories of user-defined functions, such as user-defined table functions (UDTFs) or window functions.

Native Impala UDFs

Impala supports UDFs written in C++, in addition to supporting existing Hive UDFs written in Java. Cloudera recommends using C++ UDFs because the compiled native code can yield higher performance, with UDF execution time often 10x faster for a C++ UDF than the equivalent Java UDF.

Using Hive UDFs with Impala

Impala can run Java-based user-defined functions (UDFs), originally written for Hive, with no changes, subject to the following conditions:

- The parameters and return value must all use scalar data types supported by Impala. For example, complex or nested types are not supported.
- Currently, Hive UDFs that accept or return the `TIMESTAMP` type are not supported.
- Prior to CDH 5.7 / Impala 2.5, the return type must be a “Writable” type such as `Text` or `IntWritable`, rather than a Java primitive type such as `String` or `int`. Otherwise, the UDF returns `NULL`. In CDH 5.7 / Impala 2.5 and higher, this restriction is lifted, and both UDF arguments and return values can be Java primitive types.
- Hive UDAFs and UDTFs are not supported.
- Typically, a Java UDF will execute several times slower in Impala than the equivalent native UDF written in C++.
- In CDH 5.7 / Impala 2.5 and higher, you can transparently call Hive Java UDFs through Impala, or call Impala Java UDFs through Hive. This feature does not apply to built-in Hive functions. Any Impala Java UDFs created with older versions must be re-created using new `CREATE FUNCTION` syntax, without any signature for arguments or the return value.

To take full advantage of the Impala architecture and performance features, you can also write Impala-specific UDFs in C++.

For background about Java-based Hive UDFs, see the [Hive documentation for UDFs](#). For examples or tutorials for writing such UDFs, search the web for related blog posts.

The ideal way to understand how to reuse Java-based UDFs (originally written for Hive) with Impala is to take some of the Hive built-in functions (implemented as Java UDFs) and take the applicable JAR files through the UDF deployment process for Impala, creating new UDFs with different names:

1. Take a copy of the Hive JAR file containing the Hive built-in functions. For example, the path might be like `/usr/lib/hive/lib/hive-exec-0.10.0-cdh4.2.0.jar`, with different version numbers corresponding to your specific level of CDH.
2. Use `jar tf jar_file` to see a list of the classes inside the JAR. You will see names like `org/apache/hadoop/hive/ql/udf/UDFLower.class` and `org/apache/hadoop/hive/ql/udf/UDFOPNegative.class`. Make a note of the names of the functions you want to experiment with. When you specify the entry points for the Impala `CREATE FUNCTION` statement, change the slash characters to dots and strip off the `.class` suffix, for example `org.apache.hadoop.hive.ql.udf.UDFLower` and `org.apache.hadoop.hive.ql.udf.UDFOPNegative`.
3. Copy that file to an HDFS location that Impala can read. (In the examples here, we renamed the file to `hive-builtins.jar` in HDFS for simplicity.)
4. For each Java-based UDF that you want to call through Impala, issue a `CREATE FUNCTION` statement, with a `LOCATION` clause containing the full HDFS path of the JAR file, and a `SYMBOL` clause with the fully qualified name of the class, using dots as separators and without the `.class` extension. Remember that user-defined functions are associated with a particular database, so issue a `USE` statement for the appropriate database first, or specify the SQL function name as `db_name.function_name`. Use completely new names for the SQL functions, because Impala UDFs cannot have the same name as Impala built-in functions.
5. Call the function from your queries, passing arguments of the correct type to match the function signature. These arguments could be references to columns, arithmetic or other kinds of expressions, the results of `CAST` functions to ensure correct data types, and so on.

Java UDF Example: Reusing `lower()` Function

For example, the following `impala-shell` session creates an Impala UDF `my_lower()` that reuses the Java code for the Hive `lower()`: built-in function. We cannot call it `lower()` because Impala does not allow UDFs to have the same name as built-in functions. From SQL, we call the function in a basic way (in a query with no `WHERE` clause), directly on a column, and on the results of a string expression:

```
[localhost:21000] > create database udfs;
[localhost:21000] > use udfs;
localhost:21000] > create function lower(string) returns string location
'/user/hive/udfs/hive.jar' symbol='org.apache.hadoop.hive.ql.udf.UDFLower';
ERROR: AnalysisException: Function cannot have the same name as a builtin: lower
[localhost:21000] > create function my_lower(string) returns string location
'/user/hive/udfs/hive.jar' symbol='org.apache.hadoop.hive.ql.udf.UDFLower';
[localhost:21000] > select my_lower('Some String NOT ALREADY LOWERCASE');
+-----+
| udfs.my_lower('some string not already lowercase') |
+-----+
| some string not already lowercase                 |
+-----+
Returned 1 row(s) in 0.11s
[localhost:21000] > create table t2 (s string);
[localhost:21000] > insert into t2 values ('lower'),('UPPER'),('Init cap'),('CamelCase');
Inserted 4 rows in 2.28s
[localhost:21000] > select * from t2;
+-----+
| s |
+-----+
| lower |
| UPPER |
| Init cap |
| CamelCase |
+-----+
Returned 4 row(s) in 0.47s
[localhost:21000] > select my_lower(s) from t2;
+-----+
| udfs.my_lower(s) |
+-----+
| lower |
| upper |
| init cap |
| camelcase |
+-----+
Returned 4 row(s) in 0.54s
```

```
[localhost:21000] > select my_lower(concat('ABC ',s,' XYZ')) from t2;
+-----+
| udfs.my_lower(concat('abc ', s, ' xyz')) |
+-----+
| abc lower xyz                          |
| abc upper xyz                          |
| abc init cap xyz                       |
| abc camelcase xyz                      |
+-----+
Returned 4 row(s) in 0.22s
```

Java UDF Example: Reusing negative() Function

Here is an example that reuses the Hive Java code for the `negative()` built-in function. This example demonstrates how the data types of the arguments must match precisely with the function signature. At first, we create an Impala SQL function that can only accept an integer argument. Impala cannot find a matching function when the query passes a floating-point argument, although we can call the integer version of the function by casting the argument. Then we overload the same function name to also accept a floating-point argument.

```
[localhost:21000] > create table t (x int);
[localhost:21000] > insert into t values (1), (2), (4), (100);
Inserted 4 rows in 1.43s
[localhost:21000] > create function my_neg(bigint) returns bigint location
'/user/hive/udfs/hive.jar' symbol='org.apache.hadoop.hive ql.udf.UDFOPNegative';
[localhost:21000] > select my_neg(4);
+-----+
| udfs.my_neg(4) |
+-----+
| -4             |
+-----+
[localhost:21000] > select my_neg(x) from t;
+-----+
| udfs.my_neg(x) |
+-----+
| -2             |
| -4             |
| -100          |
+-----+
Returned 3 row(s) in 0.60s
[localhost:21000] > select my_neg(4.0);
ERROR: AnalysisException: No matching function with signature: udfs.my_neg(FLOAT).
[localhost:21000] > select my_neg(cast(4.0 as int));
+-----+
| udfs.my_neg(cast(4.0 as int)) |
+-----+
| -4                             |
+-----+
Returned 1 row(s) in 0.11s
[localhost:21000] > create function my_neg(double) returns double location
'/user/hive/udfs/hive.jar' symbol='org.apache.hadoop.hive ql.udf.UDFOPNegative';
[localhost:21000] > select my_neg(4.0);
+-----+
| udfs.my_neg(4.0) |
+-----+
| -4               |
+-----+
Returned 1 row(s) in 0.11s
```

You can find the sample files mentioned here in [the Impala github repo](#).

Runtime Environment for UDFs

By default, Impala copies UDFs into `/tmp`, and you can configure this location through the `--local_library_dir` startup flag for the `impalad` daemon.

Installing the UDF Development Package

To develop UDFs for Impala, download and install the `impala-udf-devel` package (RHEL-based distributions) or `impala-udf-dev` (Ubuntu and Debian). This package contains header files, sample source, and build configuration files.

1. Start at <https://archive.cloudera.com/cdh5/> for the CDH 5 package, or <https://archive.cloudera.com/impala/> for the CDH 4 package.
2. Locate the appropriate `.repo` or list file for your operating system version, such as [the .repo file for CDH 4 on RHEL 6](#).
3. Use the familiar `yum`, `zypper`, or `apt-get` commands depending on your operating system. For the package name, specify `impala-udf-devel` (RHEL-based distributions) or `impala-udf-dev` (Ubuntu and Debian).



Note: The UDF development code does not rely on Impala being installed on the same machine. You can write and compile UDFs on a minimal development system, then deploy them on a different one for use with Impala. If you develop UDFs on a server managed by Cloudera Manager through the parcel mechanism, you still install the UDF development kit through the package mechanism; this small standalone package does not interfere with the parcels containing the main Impala code.

When you are ready to start writing your own UDFs, download the sample code and build scripts from [the Cloudera sample UDF github](#). Then see [Writing User-Defined Functions \(UDFs\)](#) on page 491 for how to code UDFs, and [Examples of Creating and Using UDFs](#) on page 497 for how to build and run UDFs.

Writing User-Defined Functions (UDFs)

Before starting UDF development, make sure to install the development package and download the UDF code samples, as described in [Installing the UDF Development Package](#) on page 491.

When writing UDFs:

- Keep in mind the data type differences as you transfer values from the high-level SQL to your lower-level UDF code. For example, in the UDF code you might be much more aware of how many bytes different kinds of integers require.
- Use best practices for function-oriented programming: choose arguments carefully, avoid side effects, make each function do a single thing, and so on.

Getting Started with UDF Coding

To understand the layout and member variables and functions of the predefined UDF data types, examine the header file `/usr/include/impala_udf/udf.h`:

```
// This is the only Impala header required to develop UDFs and UDAs. This header
// contains the types that need to be used and the FunctionContext object. The context
// object serves as the interface object between the UDF/UDA and the impala process.
```

For the basic declarations needed to write a scalar UDF, see the header file `udf-sample.h` within the sample build environment, which defines a simple function named `AddUdf()`:

```
#ifndef IMPALA_UDF_SAMPLE_UDF_H
#define IMPALA_UDF_SAMPLE_UDF_H

#include <impala_udf/udf.h>

using namespace impala_udf;

IntVal AddUdf(FunctionContext* context, const IntVal& arg1, const IntVal& arg2);

#endif
```

For sample C++ code for a simple function named `AddUdf()`, see the source file `udf-sample.cc` within the sample build environment:

```
#include "udf-sample.h"

// In this sample we are declaring a UDF that adds two ints and returns an int.
IntVal AddUdf(FunctionContext* context, const IntVal& arg1, const IntVal& arg2) {
    if (arg1.is_null || arg2.is_null) return IntVal::null();
    return IntVal(arg1.val + arg2.val);
}

// Multiple UDFs can be defined in the same file
```

Data Types for Function Arguments and Return Values

Each value that a user-defined function can accept as an argument or return as a result value must map to a SQL data type that you could specify for a table column.

Currently, Impala UDFs cannot accept arguments or return values of the Impala complex types (`STRUCT`, `ARRAY`, or `MAP`).

Each data type has a corresponding structure defined in the C++ and Java header files, with two member fields and some predefined comparison operators and constructors:

- `is_null` indicates whether the value is `NULL` or not. `val` holds the actual argument or return value when it is non-`NULL`.
- Each struct also defines a `null()` member function that constructs an instance of the struct with the `is_null` flag set.
- The built-in SQL comparison operators and clauses such as `<`, `>=`, `BETWEEN`, and `ORDER BY` all work automatically based on the SQL return type of each UDF. For example, Impala knows how to evaluate `BETWEEN 1 AND udf_returning_int(col1)` or `ORDER BY udf_returning_string(col2)` without you declaring any comparison operators within the UDF itself.

For convenience within your UDF code, each struct defines `==` and `!=` operators for comparisons with other structs of the same type. These are for typical C++ comparisons within your own code, not necessarily reproducing SQL semantics. For example, if the `is_null` flag is set in both structs, they compare as equal. That behavior of `null` comparisons is different from SQL (where `NULL == NULL` is `NULL` rather than `true`), but more in line with typical C++ behavior.

- Each kind of struct has one or more constructors that define a filled-in instance of the struct, optionally with default values.
- Impala cannot process UDFs that accept the composite or nested types as arguments or return them as result values. This limitation applies both to Impala UDFs written in C++ and Java-based Hive UDFs.
- You can overload functions by creating multiple functions with the same SQL name but different argument types. For overloaded functions, you must use different C++ or Java entry point names in the underlying functions.

The data types defined on the C++ side (in `/usr/include/impala_udf/udf.h`) are:

- `IntVal` represents an `INT` column.
- `BigIntVal` represents a `BIGINT` column. Even if you do not need the full range of a `BIGINT` value, it can be useful to code your function arguments as `BigIntVal` to make it convenient to call the function with different kinds of integer columns and expressions as arguments. Impala automatically casts smaller integer types to larger ones when appropriate, but does not implicitly cast large integer types to smaller ones.
- `SmallIntVal` represents a `SMALLINT` column.
- `TinyIntVal` represents a `TINYINT` column.
- `StringVal` represents a `STRING` column. It has a `len` field representing the length of the string, and a `ptr` field pointing to the string data. It has constructors that create a new `StringVal` struct based on a null-terminated

C-style string, or a pointer plus a length; these new structs still refer to the original string data rather than allocating a new buffer for the data. It also has a constructor that takes a pointer to a `FunctionContext` struct and a length, that does allocate space for a new copy of the string data, for use in UDFs that return string values.

- `BooleanVal` represents a `BOOLEAN` column.
- `FloatVal` represents a `FLOAT` column.
- `DoubleVal` represents a `DOUBLE` column.
- `TimestampVal` represents a `TIMESTAMP` column. It has a `date` field, a 32-bit integer representing the Gregorian date, that is, the days past the epoch date. It also has a `time_of_day` field, a 64-bit integer representing the current time of day in nanoseconds.

Variable-Length Argument Lists

UDFs typically take a fixed number of arguments, with each one named explicitly in the signature of your C++ function. Your function can also accept additional optional arguments, all of the same type. For example, you can concatenate two strings, three strings, four strings, and so on. Or you can compare two numbers, three numbers, four numbers, and so on.

To accept a variable-length argument list, code the signature of your function like this:

```
StringVal Concat(FunctionContext* context, const StringVal& separator,
                int num_var_args, const StringVal* args);
```

In the `CREATE FUNCTION` statement, after the type of the first optional argument, include `...` to indicate it could be followed by more arguments of the same type. For example, the following function accepts a `STRING` argument, followed by one or more additional `STRING` arguments:

```
[localhost:21000] > create function my_concat(string, string ...) returns string location
'/user/test_user/udfs/sample.so' symbol='Concat';
```

The call from the SQL query must pass at least one argument to the variable-length portion of the argument list.

When Impala calls the function, it fills in the initial set of required arguments, then passes the number of extra arguments and a pointer to the first of those optional arguments.

Handling NULL Values

For correctness, performance, and reliability, it is important for each UDF to handle all situations where any `NULL` values are passed to your function. For example, when passed a `NULL`, UDFs typically also return `NULL`. In an aggregate function, which could be passed a combination of real and `NULL` values, you might make the final value into a `NULL` (as in `CONCAT()`), ignore the `NULL` value (as in `AVG()`), or treat it the same as a numeric zero or empty string.

Each parameter type, such as `IntVal` or `StringVal`, has an `is_null` Boolean member. Test this flag immediately for each argument to your function, and if it is set, do not refer to the `val` field of the argument structure. The `val` field is undefined when the argument is `NULL`, so your function could go into an infinite loop or produce incorrect results if you skip the special handling for `NULL`.

If your function returns `NULL` when passed a `NULL` value, or in other cases such as when a search string is not found, you can construct a null instance of the return type by using its `null()` member function.

Memory Allocation for UDFs

By default, memory allocated within a UDF is deallocated when the function exits, which could be before the query is finished. The input arguments remain allocated for the lifetime of the function, so you can refer to them in the expressions for your return values. If you use temporary variables to construct all-new string values, use the `StringVal()` constructor that takes an initial `FunctionContext*` argument followed by a length, and copy the data into the newly allocated memory buffer.

Thread-Safe Work Area for UDFs

One way to improve performance of UDFs is to specify the optional `PREPARE_FN` and `CLOSE_FN` clauses on the `CREATE FUNCTION` statement. The “prepare” function sets up a thread-safe data structure in memory that you can use as a work area. The “close” function deallocates that memory. Each subsequent call to the UDF within the same thread can access that same memory area. There might be several such memory areas allocated on the same host, as UDFs are parallelized using multiple threads.

Within this work area, you can set up predefined lookup tables, or record the results of complex operations on data types such as `STRING` or `TIMESTAMP`. Saving the results of previous computations rather than repeating the computation each time is an optimization known as <http://en.wikipedia.org/wiki/Memoization>. For example, if your UDF performs a regular expression match or date manipulation on a column that repeats the same value over and over, you could store the last-computed value or a hash table of already-computed values, and do a fast lookup to find the result for subsequent iterations of the UDF.

Each such function must have the signature:

```
void function_name(impala_udf::FunctionContext*,
impala_udf::FunctionContext::FunctionScope)
```

Currently, only `THREAD_SCOPE` is implemented, not `FRAGMENT_SCOPE`. See `udf.h` for details about the scope values.

Error Handling for UDFs

To handle errors in UDFs, you call functions that are members of the initial `FunctionContext*` argument passed to your function.

A UDF can record one or more warnings, for conditions that indicate minor, recoverable problems that do not cause the query to stop. The signature for this function is:

```
bool AddWarning(const char* warning_msg);
```

For a serious problem that requires cancelling the query, a UDF can set an error flag that prevents the query from returning any results. The signature for this function is:

```
void SetError(const char* error_msg);
```

Writing User-Defined Aggregate Functions (UDAFs)

User-defined aggregate functions (UDAFs or UDAs) are a powerful and flexible category of user-defined functions. If a query processes *N* rows, calling a UDAF during the query condenses the result set, anywhere from a single value (such as with the `SUM` or `MAX` functions), or some number less than or equal to *N* (as in queries using the `GROUP BY` or `HAVING` clause).

The Underlying Functions for a UDA

A UDAF must maintain a state value across subsequent calls, so that it can accumulate a result across a set of calls, rather than derive it purely from one set of arguments. For that reason, a UDAF is represented by multiple underlying functions:

- An initialization function that sets any counters to zero, creates empty buffers, and does any other one-time setup for a query.
- An update function that processes the arguments for each row in the query result set and accumulates an intermediate result for each node. For example, this function might increment a counter, append to a string buffer, or set flags.
- A merge function that combines the intermediate results from two different nodes.
- A serialize function that flattens any intermediate values containing pointers, and frees any memory allocated during the init, update, and merge phases.
- A finalize function that either passes through the combined result unchanged, or does one final transformation.

In the SQL syntax, you create a UDAF by using the statement `CREATE AGGREGATE FUNCTION`. You specify the entry points of the underlying C++ functions using the clauses `INIT_FN`, `UPDATE_FN`, `MERGE_FN`, `SERIALIZE_FN`, and `FINALIZE_FN`.

For convenience, you can use a naming convention for the underlying functions and Impala automatically recognizes those entry points. Specify the `UPDATE_FN` clause, using an entry point name containing the string `update` or `Update`. When you omit the other `_FN` clauses from the SQL statement, Impala looks for entry points with names formed by substituting the `update` or `Update` portion of the specified name.

`uda-sample.h`:

See this file online at: <https://github.com/cloudera/impala-udf-samples/blob/master/uda-sample.h>

`uda-sample.cc`:

See this file online at: <https://github.com/cloudera/impala-udf-samples/blob/master/uda-sample.cc>

Intermediate Results for UDAs

A user-defined aggregate function might produce and combine intermediate results during some phases of processing, using a different data type than the final return value. For example, if you implement a function similar to the built-in `AVG()` function, it must keep track of two values, the number of values counted and the sum of those values. Or, you might accumulate a string value over the course of a UDA, then in the end return a numeric or Boolean result.

In such a case, specify the data type of the intermediate results using the optional `INTERMEDIATE type_name` clause of the `CREATE AGGREGATE FUNCTION` statement. If the intermediate data is a typeless byte array (for example, to represent a C++ struct or array), specify the type name as `CHAR(n)`, with `n` representing the number of bytes in the intermediate result buffer.

For an example of this technique, see the `trunc_sum()` aggregate function, which accumulates intermediate results of type `DOUBLE` and returns `BIGINT` at the end. View [the `CREATE FUNCTION` statement](#) and [the implementation of the underlying `TruncSum*\(\)` functions](#) on Github.

Building and Deploying UDFs

This section explains the steps to compile Impala UDFs from C++ source code, and deploy the resulting libraries for use in Impala queries.

Impala ships with a sample build environment for UDFs, that you can study, experiment with, and adapt for your own use. This sample build environment starts with the `cmake` configuration command, which reads the file `CMakeLists.txt` and generates a `Makefile` customized for your particular directory paths. Then the `make` command runs the actual build steps based on the rules in the `Makefile`.

Impala loads the shared library from an HDFS location. After building a shared library containing one or more UDFs, use `hdfs dfs` or `hadoop fs` commands to copy the binary file to an HDFS location readable by Impala.

The final step in deployment is to issue a `CREATE FUNCTION` statement in the `impala-shell` interpreter to make Impala aware of the new function. See [CREATE FUNCTION Statement](#) on page 248 for syntax details. Because each function is associated with a particular database, always issue a `USE` statement to the appropriate database before creating a function, or specify a fully qualified name, that is, `CREATE FUNCTION db_name.function_name`.

As you update the UDF code and redeploy updated versions of a shared library, use `DROP FUNCTION` and `CREATE FUNCTION` to let Impala pick up the latest version of the code.

**Note:**

In CDH 5.7 / Impala 2.5 and higher, Impala UDFs and UDAs written in C++ are persisted in the metastore database. Java UDFs are also persisted, if they were created with the new `CREATE FUNCTION` syntax for Java UDFs, where the Java function argument and return types are omitted. Java-based UDFs created with the old `CREATE FUNCTION` syntax do not persist across restarts because they are held in the memory of the `catalogd` daemon. Until you re-create such Java UDFs using the new `CREATE FUNCTION` syntax, you must reload those Java-based UDFs by running the original `CREATE FUNCTION` statements again each time you restart the `catalogd` daemon. Prior to CDH 5.7 / Impala 2.5, the requirement to reload functions after a restart applied to both C++ and Java functions.

See [CREATE FUNCTION Statement](#) on page 248 and [DROP FUNCTION Statement](#) on page 275 for the new syntax for the persistent Java UDFs.

Prerequisites for the build environment are:

```
# Use the appropriate package installation command for your Linux distribution.
sudo yum install gcc-c++ cmake boost-devel
sudo yum install impala-udf-devel
# The package name on Ubuntu and Debian is impala-udf-dev.
```

Then, unpack the sample code in `udf_samples.tar.gz` and use that as a template to set up your build environment.

To build the original samples:

```
# Process CMakeLists.txt and set up appropriate Makefiles.
cmake .
# Generate shared libraries from UDF and UDAF sample code,
# udf_samples/libudfsample.so and udf_samples/libudasample.so
make
```

The sample code to examine, experiment with, and adapt is in these files:

- `udf-sample.h`: Header file that declares the signature for a scalar UDF (`AddUDF`).
- `udf-sample.cc`: Sample source for a simple UDF that adds two integers. Because Impala can reference multiple function entry points from the same shared library, you could add other UDF functions in this file and add their signatures to the corresponding header file.
- `udf-sample-test.cc`: Basic unit tests for the sample UDF.
- `uda-sample.h`: Header file that declares the signature for sample aggregate functions. The SQL functions will be called `COUNT`, `AVG`, and `STRINGCONCAT`. Because aggregate functions require more elaborate coding to handle the processing for multiple phases, there are several underlying C++ functions such as `CountInit`, `AvgUpdate`, and `StringConcatFinalize`.
- `uda-sample.cc`: Sample source for simple UDAFs that demonstrate how to manage the state transitions as the underlying functions are called during the different phases of query processing.
 - The UDAF that imitates the `COUNT` function keeps track of a single incrementing number; the merge functions combine the intermediate count values from each Impala node, and the combined number is returned verbatim by the finalize function.
 - The UDAF that imitates the `AVG` function keeps track of two numbers, a count of rows processed and the sum of values for a column. These numbers are updated and merged as with `COUNT`, then the finalize function divides them to produce and return the final average value.
 - The UDAF that concatenates string values into a comma-separated list demonstrates how to manage storage for a string that increases in length as the function is called for multiple rows.
- `uda-sample-test.cc`: basic unit tests for the sample UDAFs.

Performance Considerations for UDFs

Because a UDF typically processes each row of a table, potentially being called billions of times, the performance of each UDF is a critical factor in the speed of the overall ETL or ELT pipeline. Tiny optimizations you can make within the function body can pay off in a big way when the function is called over and over when processing a huge result set.

Examples of Creating and Using UDFs

This section demonstrates how to create and use all kinds of user-defined functions (UDFs).

For downloadable examples that you can experiment with, adapt, and use as templates for your own functions, see [the Cloudera sample UDF github](#). You must have already installed the appropriate header files, as explained in [Installing the UDF Development Package](#) on page 491.

Sample C++ UDFs: HasVowels, CountVowels, StripVowels

This example shows 3 separate UDFs that operate on strings and return different data types. In the C++ code, the functions are `HasVowels()` (checks if a string contains any vowels), `CountVowels()` (returns the number of vowels in a string), and `StripVowels()` (returns a new string with vowels removed).

First, we add the signatures for these functions to `udf-sample.h` in the demo build environment:

```
BooleanVal HasVowels(FunctionContext* context, const StringVal& input);
IntVal CountVowels(FunctionContext* context, const StringVal& arg1);
StringVal StripVowels(FunctionContext* context, const StringVal& arg1);
```

Then, we add the bodies of these functions to `udf-sample.cc`:

```
BooleanVal HasVowels(FunctionContext* context, const StringVal& input)
{
    if (input.is_null) return BooleanVal::null();

    int index;
    uint8_t *ptr;

    for (ptr = input.ptr, index = 0; index <= input.len; index++, ptr++)
    {
        uint8_t c = tolower(*ptr);
        if (c == 'a' || c == 'e' || c == 'i' || c == 'o' || c == 'u')
        {
            return BooleanVal(true);
        }
    }
    return BooleanVal(false);
}

IntVal CountVowels(FunctionContext* context, const StringVal& arg1)
{
    if (arg1.is_null) return IntVal::null();

    int count;
    int index;
    uint8_t *ptr;

    for (ptr = arg1.ptr, count = 0, index = 0; index <= arg1.len; index++, ptr++)
    {
        uint8_t c = tolower(*ptr);
        if (c == 'a' || c == 'e' || c == 'i' || c == 'o' || c == 'u')
        {
            count++;
        }
    }
    return IntVal(count);
}

StringVal StripVowels(FunctionContext* context, const StringVal& arg1)
{
    if (arg1.is_null) return StringVal::null();

    int index;
```

```

std::string original((const char *)arg1.ptr,arg1.len);
std::string shorter("");

for (index = 0; index < original.length(); index++)
{
    uint8_t c = original[index];
    uint8_t l = tolower(c);

    if (l == 'a' || l == 'e' || l == 'i' || l == 'o' || l == 'u')
    {
        ;
    }
    else
    {
        shorter.append(1, (char)c);
    }
}
// The modified string is stored in 'shorter', which is destroyed when this function
// ends. We need to make a string val
// and copy the contents.
StringVal result(context, shorter.size()); // Only the version of the ctor that
// takes a context object allocates new memory
memcpy(result.ptr, shorter.c_str(), shorter.size());
return result;
}

```

We build a shared library, `libudfsample.so`, and put the library file into HDFS where Impala can read it:

```

$ make
[ 0%] Generating udf_samples/uda-sample.ll
[ 16%] Built target uda-sample-ir
[ 33%] Built target udasample
[ 50%] Built target uda-sample-test
[ 50%] Generating udf_samples/udf-sample.ll
[ 66%] Built target udf-sample-ir
Scanning dependencies of target udfsample
[ 83%] Building CXX object CMakeFiles/udfsample.dir/udf-sample.o
Linking CXX shared library udf_samples/libudfsample.so
[ 83%] Built target udfsample
Linking CXX executable udf_samples/udf-sample-test
[100%] Built target udf-sample-test
$ hdfs dfs -put ./udf_samples/libudfsample.so /user/hive/udfs/libudfsample.so

```

Finally, we go into the `impala-shell` interpreter where we set up some sample data, issue `CREATE FUNCTION` statements to set up the SQL function names, and call the functions in some queries:

```

[localhost:21000] > create database udf_testing;
[localhost:21000] > use udf_testing;

[localhost:21000] > create function has_vowels (string) returns boolean location
'/user/hive/udfs/libudfsample.so' symbol='HasVowels';
[localhost:21000] > select has_vowels('abc');
+-----+
| udfs.has_vowels('abc') |
+-----+
| true                    |
+-----+
Returned 1 row(s) in 0.13s
[localhost:21000] > select has_vowels('zxcvbnm');
+-----+
| udfs.has_vowels('zxcvbnm') |
+-----+
| false                      |
+-----+
Returned 1 row(s) in 0.12s
[localhost:21000] > select has_vowels(null);
+-----+
| udfs.has_vowels(null) |
+-----+
| NULL                  |
+-----+

```

```

Returned 1 row(s) in 0.11s
[localhost:21000] > select s, has_vowels(s) from t2;
+-----+-----+
| s          | udfs.has_vowels(s) |
+-----+-----+
| lower     | true               |
| UPPER     | true               |
| Init cap  | true               |
| CamelCase | true               |
+-----+-----+
Returned 4 row(s) in 0.24s

[localhost:21000] > create function count_vowels (string) returns int location
'/user/hive/udfs/libudfsample.so' symbol='CountVowels';
[localhost:21000] > select count_vowels('cat in the hat');
+-----+-----+
| udfs.count_vowels('cat in the hat') |
+-----+-----+
| 4                                     |
+-----+-----+
Returned 1 row(s) in 0.12s
[localhost:21000] > select s, count_vowels(s) from t2;
+-----+-----+
| s          | udfs.count_vowels(s) |
+-----+-----+
| lower     | 2                     |
| UPPER     | 2                     |
| Init cap  | 3                     |
| CamelCase | 4                     |
+-----+-----+
Returned 4 row(s) in 0.23s
[localhost:21000] > select count_vowels(null);
+-----+-----+
| udfs.count_vowels(null) |
+-----+-----+
| NULL                    |
+-----+-----+
Returned 1 row(s) in 0.12s

[localhost:21000] > create function strip_vowels (string) returns string location
'/user/hive/udfs/libudfsample.so' symbol='StripVowels';
[localhost:21000] > select strip_vowels('abcdefg');
+-----+-----+
| udfs.strip_vowels('abcdefg') |
+-----+-----+
| bcdfg                         |
+-----+-----+
Returned 1 row(s) in 0.11s
[localhost:21000] > select strip_vowels('ABCDEFGH');
+-----+-----+
| udfs.strip_vowels('abcdefg') |
+-----+-----+
| BCDFG                         |
+-----+-----+
Returned 1 row(s) in 0.12s
[localhost:21000] > select strip_vowels(null);
+-----+-----+
| udfs.strip_vowels(null) |
+-----+-----+
| NULL                      |
+-----+-----+
Returned 1 row(s) in 0.16s
[localhost:21000] > select s, strip_vowels(s) from t2;
+-----+-----+
| s          | udfs.strip_vowels(s) |
+-----+-----+
| lower     | lwr                  |
| UPPER     | PPR                  |
| Init cap  | nt cp                |
| CamelCase | CmlCs                |
+-----+-----+
Returned 4 row(s) in 0.24s

```

Sample C++ UDA: SumOfSquares

This example demonstrates a user-defined aggregate function (UDA) that produces the sum of the squares of its input values.

The coding for a UDA is a little more involved than a scalar UDF, because the processing is split into several phases, each implemented by a different function. Each phase is relatively straightforward: the “update” and “merge” phases, where most of the work is done, read an input value and combine it with some accumulated intermediate value.

As in our sample UDF from the previous example, we add function signatures to a header file (in this case, `uda-sample.h`). Because this is a math-oriented UDA, we make two versions of each function, one accepting an integer value and the other accepting a floating-point value.

```
void SumOfSquaresInit(FunctionContext* context, BigIntVal* val);
void SumOfSquaresInit(FunctionContext* context, DoubleVal* val);

void SumOfSquaresUpdate(FunctionContext* context, const BigIntVal& input, BigIntVal*
val);
void SumOfSquaresUpdate(FunctionContext* context, const DoubleVal& input, DoubleVal*
val);

void SumOfSquaresMerge(FunctionContext* context, const BigIntVal& src, BigIntVal* dst);
void SumOfSquaresMerge(FunctionContext* context, const DoubleVal& src, DoubleVal* dst);

BigIntVal SumOfSquaresFinalize(FunctionContext* context, const BigIntVal& val);
DoubleVal SumOfSquaresFinalize(FunctionContext* context, const DoubleVal& val);
```

We add the function bodies to a C++ source file (in this case, `uda-sample.cc`):

```
void SumOfSquaresInit(FunctionContext* context, BigIntVal* val) {
    val->is_null = false;
    val->val = 0;
}
void SumOfSquaresInit(FunctionContext* context, DoubleVal* val) {
    val->is_null = false;
    val->val = 0.0;
}

void SumOfSquaresUpdate(FunctionContext* context, const BigIntVal& input, BigIntVal*
val) {
    if (input.is_null) return;
    val->val += input.val * input.val;
}
void SumOfSquaresUpdate(FunctionContext* context, const DoubleVal& input, DoubleVal*
val) {
    if (input.is_null) return;
    val->val += input.val * input.val;
}

void SumOfSquaresMerge(FunctionContext* context, const BigIntVal& src, BigIntVal* dst)
{
    dst->val += src.val;
}
void SumOfSquaresMerge(FunctionContext* context, const DoubleVal& src, DoubleVal* dst)
{
    dst->val += src.val;
}

BigIntVal SumOfSquaresFinalize(FunctionContext* context, const BigIntVal& val) {
    return val;
}
DoubleVal SumOfSquaresFinalize(FunctionContext* context, const DoubleVal& val) {
    return val;
}
```

As with the sample UDF, we build a shared library and put it into HDFS:

```
$ make
[ 0%] Generating udf_samples/uda-sample.ll
```

```
[ 16%] Built target uda-sample-ir
Scanning dependencies of target udasample
[ 33%] Building CXX object CMakeFiles/udasample.dir/uda-sample.o
Linking CXX shared library udf_samples/libudasample.so
[ 33%] Built target udasample
Scanning dependencies of target uda-sample-test
[ 50%] Building CXX object CMakeFiles/uda-sample-test.dir/uda-sample-test.o
Linking CXX executable udf_samples/uda-sample-test
[ 50%] Built target uda-sample-test
[ 50%] Generating udf_samples/udf-sample.ll
[ 66%] Built target udf-sample-ir
[ 83%] Built target udfsamples
[100%] Built target udf-sample-test
$ hdfs dfs -put ./udf_samples/libudasample.so /user/hive/udfs/libudasample.so
```

To create the SQL function, we issue a `CREATE AGGREGATE FUNCTION` statement and specify the underlying C++ function names for the different phases:

```
[localhost:21000] > use udf_testing;

[localhost:21000] > create table sos (x bigint, y double);
[localhost:21000] > insert into sos values (1, 1.1), (2, 2.2), (3, 3.3), (4, 4.4);
Inserted 4 rows in 1.10s

[localhost:21000] > create aggregate function sum_of_squares(bigint) returns bigint
  > location '/user/hive/udfs/libudasample.so'
  > init_fn='SumOfSquaresInit'
  > update_fn='SumOfSquaresUpdate'
  > merge_fn='SumOfSquaresMerge'
  > finalize_fn='SumOfSquaresFinalize';

[localhost:21000] > -- Compute the same value using literals or the UDA;
[localhost:21000] > select 1*1 + 2*2 + 3*3 + 4*4;
+-----+
| 1 * 1 + 2 * 2 + 3 * 3 + 4 * 4 |
+-----+
| 30                             |
+-----+
Returned 1 row(s) in 0.12s
[localhost:21000] > select sum_of_squares(x) from sos;
+-----+
| udfs.sum_of_squares(x) |
+-----+
| 30                       |
+-----+
Returned 1 row(s) in 0.35s
```

Until we create the overloaded version of the UDA, it can only handle a single data type. To allow it to handle `DOUBLE` as well as `BIGINT`, we issue another `CREATE AGGREGATE FUNCTION` statement:

```
[localhost:21000] > select sum_of_squares(y) from sos;
ERROR: AnalysisException: No matching function with signature:
udfs.sum_of_squares(DOUBLE).

[localhost:21000] > create aggregate function sum_of_squares(double) returns double
  > location '/user/hive/udfs/libudasample.so'
  > init_fn='SumOfSquaresInit'
  > update_fn='SumOfSquaresUpdate'
  > merge_fn='SumOfSquaresMerge'
  > finalize_fn='SumOfSquaresFinalize';

[localhost:21000] > -- Compute the same value using literals or the UDA;
[localhost:21000] > select 1.1*1.1 + 2.2*2.2 + 3.3*3.3 + 4.4*4.4;
+-----+
| 1.1 * 1.1 + 2.2 * 2.2 + 3.3 * 3.3 + 4.4 * 4.4 |
+-----+
| 36.3                                           |
+-----+
Returned 1 row(s) in 0.12s
[localhost:21000] > select sum_of_squares(y) from sos;
```

```
+-----+
| udfs.sum_of_squares(y) |
+-----+
| 36.3                    |
+-----+
Returned 1 row(s) in 0.35s
```

Typically, you use a UDA in queries with `GROUP BY` clauses, to produce a result set with a separate aggregate value for each combination of values from the `GROUP BY` clause. Let's change our sample table to use 0 to indicate rows containing even values, and 1 to flag rows containing odd values. Then the `GROUP BY` query can return two values, the sum of the squares for the even values, and the sum of the squares for the odd values:

```
[localhost:21000] > insert overwrite sos values (1, 1), (2, 0), (3, 1), (4, 0);
Inserted 4 rows in 1.24s

[localhost:21000] > -- Compute 1 squared + 3 squared, and 2 squared + 4 squared;
[localhost:21000] > select y, sum_of_squares(x) from sos group by y;
+-----+-----+
| y | udfs.sum_of_squares(x) |
+-----+-----+
| 1 | 10                     |
| 0 | 20                     |
+-----+-----+
Returned 2 row(s) in 0.43s
```

Security Considerations for User-Defined Functions

When the Impala authorization feature is enabled:

- To call a UDF in a query, you must have the required read privilege for any databases and tables used in the query.
- Because incorrectly coded UDFs could cause performance or capacity problems, for example by going into infinite loops or allocating excessive amounts of memory, only an administrative user can create UDFs. That is, to execute the `CREATE FUNCTION` statement requires the `ALL` privilege on the server.

See [Enabling Sentry Authorization for Impala](#) on page 105 for details about authorization in Impala.

Limitations and Restrictions for Impala UDFs

The following limitations and restrictions apply to Impala UDFs in the current release:

- Impala does not support Hive UDFs that accept or return composite or nested types, or other types not available in Impala tables.
- The Hive `current_user()` function cannot be called from a Java UDF through Impala.
- All Impala UDFs must be deterministic, that is, produce the same output each time when passed the same argument values. For example, an Impala UDF must not call functions such as `rand()` to produce different values for each invocation. It must not retrieve data from external sources, such as from disk or over the network.
- An Impala UDF must not spawn other threads or processes.
- Prior to CDH 5.7 / Impala 2.5, when the `catalogd` process is restarted, all UDFs become undefined and must be reloaded. In CDH 5.7 / Impala 2.5 and higher, this limitation only applies to older Java UDFs. Re-create those UDFs using the new `CREATE FUNCTION` syntax for Java UDFs, which excludes the function signature, to remove the limitation entirely.
- Impala currently does not support user-defined table functions (UDTFs).
- The `CHAR` and `VARCHAR` types cannot be used as input arguments or return values for UDFs.

SQL Differences Between Impala and Hive

Impala's SQL syntax follows the SQL-92 standard, and includes many industry extensions in areas such as built-in functions. See [Porting SQL from Other Database Systems to Impala](#) on page 505 for a general discussion of adapting SQL code from a variety of database systems to Impala.

Because Impala and Hive share the same metastore database and their tables are often used interchangeably, the following section covers differences between Impala and Hive in detail.

HiveQL Features not Available in Impala

The current release of Impala does not support the following SQL features that you might be familiar with from HiveQL:

- Extensibility mechanisms such as `TRANSFORM`, custom file formats, or custom SerDes.
- The `DATE` data type.
- XML and JSON functions.
- Certain aggregate functions from HiveQL: `covar_pop`, `covar_samp`, `corr`, `percentile`, `percentile_approx`, `histogram_numeric`, `collect_set`; Impala supports the set of aggregate functions listed in [Impala Aggregate Functions](#) on page 443 and analytic functions listed in [Impala Analytic Functions](#) on page 470.
- Sampling.
- Lateral views. In CDH 5.5 / Impala 2.3 and higher, Impala supports queries on complex types (`STRUCT`, `ARRAY`, or `MAP`), using join notation rather than the `EXPLODE()` keyword. See [Complex Types \(CDH 5.5 or higher only\)](#) on page 167 for details about Impala support for complex types.
- Multiple `DISTINCT` clauses per query, although Impala includes some workarounds for this limitation.



Note:

By default, Impala only allows a single `COUNT(DISTINCT columns)` expression in each query.

If you do not need precise accuracy, you can produce an estimate of the distinct values for a column by specifying `NDV(column)`; a query can contain multiple instances of `NDV(column)`. To make Impala automatically rewrite `COUNT(DISTINCT)` expressions to `NDV()`, enable the `APPX_COUNT_DISTINCT` query option.

To produce the same result as multiple `COUNT(DISTINCT)` expressions, you can use the following technique for queries involving a single table:

```
select v1.c1 result1, v2.c1 result2 from
  (select count(distinct col1) as c1 from t1) v1
  cross join
  (select count(distinct col2) as c1 from t1) v2;
```

Because `CROSS JOIN` is an expensive operation, prefer to use the `NDV()` technique wherever practical.

User-defined functions (UDFs) are supported starting in Impala 1.2. See [Impala User-Defined Functions \(UDFs\)](#) on page 487 for full details on Impala UDFs.

- Impala supports high-performance UDFs written in C++, as well as reusing some Java-based Hive UDFs.
- Impala supports scalar UDFs and user-defined aggregate functions (UDAFs). Impala does not currently support user-defined table generating functions (UDTFs).
- Only Impala-supported column types are supported in Java-based UDFs.
- The Hive `current_user()` function cannot be called from a Java UDF through Impala.

Impala does not currently support these HiveQL statements:

- `ANALYZE TABLE` (the Impala equivalent is `COMPUTE STATS`)
- `DESCRIBE COLUMN`
- `DESCRIBE DATABASE`
- `EXPORT TABLE`
- `IMPORT TABLE`
- `SHOW TABLE EXTENDED`

- SHOW TBLPROPERTIES
- SHOW INDEXES
- SHOW COLUMNS
- INSERT OVERWRITE DIRECTORY; use INSERT OVERWRITE *table_name* or CREATE TABLE AS SELECT to materialize query results into the HDFS directory associated with an Impala table.

Impala respects the `serialization.null.format` table property only for TEXT tables and ignores the property for Parquet and other formats. Hive respects the `serialization.null.format` property for Parquet and other formats and converts matching values to NULL during the scan. See [for using the table property in Impala](#).

Semantic Differences Between Impala and HiveQL Features

This section covers instances where Impala and Hive have similar functionality, sometimes including the same syntax, but there are differences in the runtime semantics of those features.

Security:

Impala utilizes the [Apache Sentry](#) authorization framework, which provides fine-grained role-based access control to protect data against unauthorized access or tampering.

The Hive component included in CDH 5.1 and higher now includes Sentry-enabled GRANT, REVOKE, and CREATE/DROP ROLE statements. Earlier Hive releases had a privilege system with GRANT and REVOKE statements that were primarily intended to prevent accidental deletion of data, rather than a security mechanism to protect against malicious users.

Impala can make use of privileges set up through Hive GRANT and REVOKE statements. Impala has its own GRANT and REVOKE statements in Impala 2.0 and higher. See [Enabling Sentry Authorization for Impala](#) on page 105 for the details of authorization in Impala, including how to switch from the original policy file-based privilege model to the Sentry service using privileges stored in the metastore database.

SQL statements and clauses:

The semantics of Impala SQL statements varies from HiveQL in some cases where they use similar SQL statement and clause names:

- Impala uses different syntax and names for query hints, [SHUFFLE] and [NOSHUFFLE] rather than MapJoin or StreamJoin. See [Joins in Impala SELECT Statements](#) on page 306 for the Impala details.
- Impala does not expose MapReduce specific features of SORT BY, DISTRIBUTE BY, or CLUSTER BY.
- Impala does not require queries to include a FROM clause.

Data types:

- Impala supports a limited set of implicit casts. This can help avoid undesired results from unexpected casting behavior.
 - Impala does not implicitly cast between string and numeric or Boolean types. Always use CAST() for these conversions.
 - Impala does perform implicit casts among the numeric types, when going from a smaller or less precise type to a larger or more precise one. For example, Impala will implicitly convert a SMALLINT to a BIGINT or FLOAT, but to convert from DOUBLE to FLOAT or INT to TINYINT requires a call to CAST() in the query.
 - Impala does perform implicit casts from string to timestamp. Impala has a restricted set of literal formats for the TIMESTAMP data type and the from_unixtime() format string; see [TIMESTAMP Data Type](#) on page 158 for details.

See [Data Types](#) on page 126 for full details on implicit and explicit casting for all types, and [Impala Type Conversion Functions](#) on page 395 for details about the CAST() function.

- Impala does not store or interpret timestamps using the local timezone, to avoid undesired results from unexpected time zone issues. Timestamps are stored and interpreted relative to UTC. This difference can produce different results for some calls to similarly named date/time functions between Impala and Hive. See [Impala Date and Time Functions](#) on page 398 for details about the Impala functions. See [TIMESTAMP Data Type](#) on page 158 for a discussion of how Impala handles time zones, and configuration options you can use to make Impala match the Hive behavior

more closely when dealing with Parquet-encoded `TIMESTAMP` data or when converting between the local time zone and UTC.

- The Impala `TIMESTAMP` type can represent dates ranging from 1400-01-01 to 9999-12-31. This is different from the Hive date range, which is 0000-01-01 to 9999-12-31.
- Impala does not return column overflows as `NULL`, so that customers can distinguish between `NULL` data and overflow conditions similar to how they do so with traditional database systems. Impala returns the largest or smallest value in the range for the type. For example, valid values for a `tinyint` range from -128 to 127. In Impala, a `tinyint` with a value of -200 returns -128 rather than `NULL`. A `tinyint` with a value of 200 returns 127.

Miscellaneous features:

- Impala does not provide virtual columns.
- Impala does not expose locking.
- Impala does not expose some configuration properties.

Porting SQL from Other Database Systems to Impala

Although Impala uses standard SQL for queries, you might need to modify SQL source when bringing applications to Impala, due to variations in data types, built-in functions, vendor language extensions, and Hadoop-specific syntax. Even when SQL is working correctly, you might make further minor modifications for best performance.

Porting DDL and DML Statements

When adapting SQL code from a traditional database system to Impala, expect to find a number of differences in the DDL statements that you use to set up the schema. Clauses related to physical layout of files, tablespaces, and indexes have no equivalent in Impala. You might restructure your schema considerably to account for the Impala partitioning scheme and Hadoop file formats.

Expect SQL queries to have a much higher degree of compatibility. With modest rewriting to address vendor extensions and features not yet supported in Impala, you might be able to run identical or almost-identical query text on both systems.

Therefore, consider separating out the DDL into a separate Impala-specific setup script. Focus your reuse and ongoing tuning efforts on the code for SQL queries.

Porting Data Types from Other Database Systems

- Change any `VARCHAR`, `VARCHAR2`, and `CHAR` columns to `STRING`. Remove any length constraints from the column declarations; for example, change `VARCHAR(32)` or `CHAR(1)` to `STRING`. Impala is very flexible about the length of string values; it does not impose any length constraints or do any special processing (such as blank-padding) for `STRING` columns. (In Impala 2.0 and higher, there are data types `VARCHAR` and `CHAR`, with length constraints for both types and blank-padding for `CHAR`. However, for performance reasons, it is still preferable to use `STRING` columns where practical.)
- For national language character types such as `NCHAR`, `NVARCHAR`, or `NCLOB`, be aware that while Impala can store and query UTF-8 character data, currently some string manipulation operations only work correctly with ASCII data. See [STRING Data Type](#) on page 151 for details.
- Change any `DATE`, `DATETIME`, or `TIME` columns to `TIMESTAMP`. Remove any precision constraints. Remove any timezone clauses, and make sure your application logic or ETL process accounts for the fact that Impala expects all `TIMESTAMP` values to be in [Coordinated Universal Time \(UTC\)](#). See [TIMESTAMP Data Type](#) on page 158 for information about the `TIMESTAMP` data type, and [Impala Date and Time Functions](#) on page 398 for conversion functions for different date and time formats.

You might also need to adapt date- and time-related literal values and format strings to use the supported Impala date and time formats. If you have date and time literals with different separators or different numbers of `YY`, `MM`, and so on placeholders than Impala expects, consider using calls to `regexp_replace()` to transform those values to the Impala-compatible format. See [TIMESTAMP Data Type](#) on page 158 for information about the allowed

formats for date and time literals, and [Impala String Functions](#) on page 430 for string conversion functions such as `regexp_replace()`.

Instead of `SYSDATE`, call the function `NOW()`.

Instead of adding or subtracting directly from a date value to produce a value *N* days in the past or future, use an `INTERVAL` expression, for example `NOW() + INTERVAL 30 DAYS`.

- Although Impala supports `INTERVAL` expressions for datetime arithmetic, as shown in [TIMESTAMP Data Type](#) on page 158, `INTERVAL` is not available as a column data type in Impala. For any `INTERVAL` values stored in tables, convert them to numeric values that you can add or subtract using the functions in [Impala Date and Time Functions](#) on page 398. For example, if you had a table `DEADLINES` with an `INT` column `TIME_PERIOD`, you could construct dates *N* days in the future like so:

```
SELECT NOW() + INTERVAL time_period DAYS from deadlines;
```

- For `YEAR` columns, change to the smallest Impala integer type that has sufficient range. See [Data Types](#) on page 126 for details about ranges, casting, and so on for the various numeric data types.
- Change any `DECIMAL` and `NUMBER` types. If fixed-point precision is not required, you can use `FLOAT` or `DOUBLE` on the Impala side depending on the range of values. For applications that require precise decimal values, such as financial data, you might need to make more extensive changes to table structure and application logic, such as using separate integer columns for dollars and cents, or encoding numbers as string values and writing UDFs to manipulate them. See [Data Types](#) on page 126 for details about ranges, casting, and so on for the various numeric data types.
- `FLOAT`, `DOUBLE`, and `REAL` types are supported in Impala. Remove any precision and scale specifications. (In Impala, `REAL` is just an alias for `DOUBLE`; columns declared as `REAL` are turned into `DOUBLE` behind the scenes.) See [Data Types](#) on page 126 for details about ranges, casting, and so on for the various numeric data types.
- Most integer types from other systems have equivalents in Impala, perhaps under different names such as `BIGINT` instead of `INT8`. For any that are unavailable, for example `MEDIUMINT`, switch to the smallest Impala integer type that has sufficient range. Remove any precision specifications. See [Data Types](#) on page 126 for details about ranges, casting, and so on for the various numeric data types.
- Remove any `UNSIGNED` constraints. All Impala numeric types are signed. See [Data Types](#) on page 126 for details about ranges, casting, and so on for the various numeric data types.
- For any types holding bitwise values, use an integer type with enough range to hold all the relevant bits within a positive integer. See [Data Types](#) on page 126 for details about ranges, casting, and so on for the various numeric data types.

For example, `TINYINT` has a maximum positive value of 127, not 256, so to manipulate 8-bit bitfields as positive numbers switch to the next largest type `SMALLINT`.

```
[localhost:21000] > select cast(127*2 as tinyint);
+-----+
| cast(127 * 2 as tinyint) |
+-----+
| -2                       |
+-----+
[localhost:21000] > select cast(128 as tinyint);
+-----+
| cast(128 as tinyint)    |
+-----+
| -128                   |
+-----+
[localhost:21000] > select cast(127*2 as smallint);
+-----+
| cast(127 * 2 as smallint) |
+-----+
| 254                     |
+-----+
```

Impala does not support notation such as `b'0101'` for bit literals.

- For BLOB values, use `STRING` to represent `CLOB` or `TEXT` types (character based large objects) up to 32 KB in size. Binary large objects such as `BLOB`, `RAW BINARY`, and `VARBINARY` do not currently have an equivalent in Impala.
- For Boolean-like types such as `BOOL`, use the Impala `BOOLEAN` type.
- Because Impala currently does not support composite or nested types, any spatial data types in other database systems do not have direct equivalents in Impala. You could represent spatial values in string format and write UDFs to process them. See [Impala User-Defined Functions \(UDFs\)](#) on page 487 for details. Where practical, separate spatial types into separate tables so that Impala can still work with the non-spatial data.
- Take out any `DEFAULT` clauses. Impala can use data files produced from many different sources, such as Pig, Hive, or MapReduce jobs. The fast import mechanisms of `LOAD DATA` and external tables mean that Impala is flexible about the format of data files, and Impala does not necessarily validate or cleanse data before querying it. When copying data through Impala `INSERT` statements, you can use conditional functions such as `CASE` or `NVL` to substitute some other value for `NULL` fields; see [Impala Conditional Functions](#) on page 427 for details.
- Take out any constraints from your `CREATE TABLE` and `ALTER TABLE` statements, for example `PRIMARY KEY`, `FOREIGN KEY`, `UNIQUE`, `NOT NULL`, `UNSIGNED`, or `CHECK` constraints. Impala can use data files produced from many different sources, such as Pig, Hive, or MapReduce jobs. Therefore, Impala expects initial data validation to happen earlier during the ETL or ELT cycle. After data is loaded into Impala tables, you can perform queries to test for `NULL` values. When copying data through Impala `INSERT` statements, you can use conditional functions such as `CASE` or `NVL` to substitute some other value for `NULL` fields; see [Impala Conditional Functions](#) on page 427 for details.

Do as much verification as practical before loading data into Impala. After data is loaded into Impala, you can do further verification using SQL queries to check if values have expected ranges, if values are `NULL` or not, and so on. If there is a problem with the data, you will need to re-run earlier stages of the ETL process, or do an `INSERT ... SELECT` statement in Impala to copy the faulty data to a new table and transform or filter out the bad values.

- Take out any `CREATE INDEX`, `DROP INDEX`, and `ALTER INDEX` statements, and equivalent `ALTER TABLE` statements. Remove any `INDEX`, `KEY`, or `PRIMARY KEY` clauses from `CREATE TABLE` and `ALTER TABLE` statements. Impala is optimized for bulk read operations for data warehouse-style queries, and therefore does not support indexes for its tables.
- Calls to built-in functions with out-of-range or otherwise incorrect arguments, return `NULL` in Impala as opposed to raising exceptions. (This rule applies even when the `ABORT_ON_ERROR=true` query option is in effect.) Run small-scale queries using representative data to doublecheck that calls to built-in functions are returning expected values rather than `NULL`. For example, unsupported `CAST` operations do not raise an error in Impala:

```
select cast('foo' as int);
+-----+
| cast('foo' as int) |
+-----+
| NULL                |
+-----+
```

- For any other type not supported in Impala, you could represent their values in string format and write UDFs to process them. See [Impala User-Defined Functions \(UDFs\)](#) on page 487 for details.
- To detect the presence of unsupported or unconvertible data types in data files, do initial testing with the `ABORT_ON_ERROR=true` query option in effect. This option causes queries to fail immediately if they encounter disallowed type conversions. See [ABORT_ON_ERROR Query Option](#) on page 332 for details. For example:

```
set abort_on_error=true;
select count(*) from (select * from t1);
-- The above query will fail if the data files for T1 contain any
-- values that can't be converted to the expected Impala data types.
-- For example, if T1.C1 is defined as INT but the column contains
-- floating-point values like 1.1, the query will return an error.
```

SQL Statements to Remove or Adapt

The following SQL statements or clauses are not currently supported or supported with limitations in Impala:

- Impala supports the `DELETE` statement only for Kudu tables.

Impala is intended for data warehouse-style operations where you do bulk moves and transforms of large quantities of data. When not using Kudu tables, instead of `DELETE`, use `INSERT OVERWRITE` to entirely replace the contents of a table or partition, or use `INSERT ... SELECT` to copy a subset of data (everything but the rows you intended to delete) from one table to another. See [DML Statements](#) on page 229 for an overview of Impala DML statements.

- Impala supports the `UPDATE` statement only for Kudu tables.

When not using Kudu tables, instead of `UPDATE`, do all necessary transformations early in the ETL process, such as in the job that generates the original data, or when copying from one table to another to convert to a particular file format or partitioning scheme. See [DML Statements](#) on page 229 for an overview of Impala DML statements.

- Impala has no transactional statements, such as `COMMIT` or `ROLLBACK`.

Impala effectively works like the `AUTOCOMMIT` mode in some database systems, where changes take effect as soon as they are made.

- If your database, table, column, or other names conflict with Impala reserved words, use different names or quote the names with backticks.

See [Impala Reserved Words](#) on page 641 for the current list of Impala reserved words.

Conversely, if you use a keyword that Impala does not recognize, it might be interpreted as a table or column alias.

For example, in `SELECT * FROM t1 NATURAL JOIN t2`, Impala does not recognize the `NATURAL` keyword and interprets it as an alias for the table `t1`. If you experience any unexpected behavior with queries, check the list of reserved words to make sure all keywords in `JOIN` and `WHERE` clauses are supported keywords in Impala.

- Impala has some restrictions on subquery support. See [Subqueries](#) for the current details.
- Impala supports `UNION` and `UNION ALL` set operators, but not `INTERSECT`.

Prefer `UNION ALL` over `UNION` when you know the data sets are disjoint or duplicate values are not a problem; `UNION ALL` is more efficient because it avoids materializing and sorting the entire result set to eliminate duplicate values.

- Impala requires query aliases for the subqueries used as inline views in the `FROM` clause.

For example, without the alias `contents_of_t1` at the end, the following query gives a syntax error:

```
SELECT COUNT(*) FROM (SELECT * FROM t1) contents_of_t1;
```

Aliases are not required for the subqueries used in other parts of queries. For example:

```
SELECT * FROM functional.alltypes WHERE id = (SELECT MIN(id) FROM functional.alltypes);
```

- When an alias is declared for an expression in a query, that alias cannot be referenced again within the same `SELECT` list.

For example, the `average` alias cannot be referenced twice in the `SELECT` list as below. You will receive an error:

```
SELECT AVG(x) AS average, average+1 FROM t1 GROUP BY x;
```

An alias can be referenced again in the same query if not in the `SELECT` list. For example, the `average` alias can be referenced twice as shown below:

```
SELECT AVG(x) AS average FROM t1 GROUP BY x HAVING average > 3;
```

- Impala does not support `NATURAL JOIN`, and it does not support the `USING` clause in joins. See [Joins in Impala SELECT Statements](#) on page 306 for details on the syntax for Impala join clauses.
- Impala supports a limited choice of partitioning types.

Partitions are defined based on each distinct combination of values for one or more partition key columns. Impala does not redistribute or check data to create evenly distributed partitions. You must choose partition key columns based on your knowledge of the data volume and distribution. Adapt any tables that use range, list, hash, or key partitioning to use the Impala partition syntax for `CREATE TABLE` and `ALTER TABLE` statements.

Impala partitioning is similar to range partitioning where every range has exactly one value, or key partitioning where the hash function produces a separate bucket for every combination of key values. See [Partitioning for Impala Tables](#) on page 568 for usage details, and [CREATE TABLE Statement](#) on page 254 and [ALTER TABLE Statement](#) on page 230 for syntax.



Note: Because the number of separate partitions is potentially higher than in other database systems, keep a close eye on the number of partitions and the volume of data in each one; scale back the number of partition key columns if you end up with too many partitions with a small volume of data in each one.

To distribute work for a query across a cluster, you need at least one HDFS block per node. HDFS blocks are typically multiple megabytes, especially for Parquet files. Therefore, if each partition holds only a few megabytes of data, you are unlikely to see much parallelism in the query because such a small amount of data is typically processed by a single node.

- For the “top-N” queries, Impala uses the `LIMIT` clause rather than comparing against a pseudo column named `ROWNUM` or `ROW_NUM`.

See [LIMIT Clause](#) on page 318 for details.

SQL Constructs to Double-check

Some SQL constructs that are supported have behavior or defaults more oriented towards convenience than optimal performance. Also, sometimes machine-generated SQL, perhaps issued through JDBC or ODBC applications, might have inefficiencies or exceed internal Impala limits. As you port SQL code, examine and possibly update the following where appropriate:

- A `CREATE TABLE` statement with no `STORED AS` clause creates data files in plain text format, which is convenient for data interchange but not a good choice for high-volume data with high-performance queries. See [How Impala Works with Hadoop File Formats](#) on page 575 for why and how to use specific file formats for compact data and high-performance queries. Especially see [Using the Parquet File Format with Impala Tables](#) on page 584, for details about the file format most heavily optimized for large-scale data warehouse queries.
- Adapting tables that were already partitioned in a different database system could produce an Impala table with a high number of partitions and not enough data in each one, leading to underutilization of Impala's parallel query features.
See [Partitioning for Impala Tables](#) on page 568 for details about setting up partitioning and tuning the performance of queries on partitioned tables.
- The `INSERT . . . VALUES` syntax is suitable for setting up toy tables with a few rows for functional testing when used with HDFS. Each such statement creates a separate tiny file in HDFS, and it is not a scalable technique for loading megabytes or gigabytes (let alone petabytes) of data.

Consider revising your data load process to produce raw data files outside of Impala, then setting up Impala external tables or using the `LOAD DATA` statement to use those data files instantly in Impala tables, with no conversion or indexing stage. See [External Tables](#) on page 223 and [LOAD DATA Statement](#) on page 297 for details about the Impala techniques for working with data files produced outside of Impala; see [Data Loading and Querying Examples](#) on page 58 for examples of ETL workflow for Impala.

`INSERT` works fine for Kudu tables even though not particularly fast.

- If your ETL process is not optimized for Hadoop, you might end up with highly fragmented small data files, or a single giant data file that cannot take advantage of distributed parallel queries or partitioning. In this case, use an `INSERT ... SELECT` statement to copy the data into a new table and reorganize into a more efficient layout in the same operation. See [INSERT Statement](#) on page 286 for details about the `INSERT` statement.

You can do `INSERT ... SELECT` into a table with a more efficient file format (see [How Impala Works with Hadoop File Formats](#) on page 575) or from an unpartitioned table into a partitioned one. See [Partitioning for Impala Tables](#) on page 568.

- Complex queries may have high codegen time. As a workaround, set the query option `DISABLE_CODEGEN=true` if queries fail for this reason. See [DISABLE_CODEGEN Query Option](#) on page 334 for details.
- If practical, rewrite `UNION` queries to use the `UNION ALL` operator instead. Prefer `UNION ALL` over `UNION` when you know the data sets are disjoint or duplicate values are not a problem; `UNION ALL` is more efficient because it avoids materializing and sorting the entire result set to eliminate duplicate values.

Next Porting Steps after Verifying Syntax and Semantics

Some of the decisions you make during the porting process can have an impact on performance. After your SQL code is ported and working correctly, examine the performance-related aspects of your schema design, physical layout, and queries to make sure that the ported application is taking full advantage of Impala's parallelism, performance-related SQL features, and integration with Hadoop components. The following are a few of the areas you should examine:

- For the optimal performance, we recommend that you run `COMPUTE STATS` on all tables.
- Use the most efficient file format for your data volumes, table structure, and query characteristics.
- Partition on columns that are often used for filtering in `WHERE` clauses.
- Your ETL process should produce a relatively small number of multi-megabyte data files rather than a huge number of small files.

See [Tuning Impala for Performance](#) on page 523 for details about the performance tuning process.

Using the Impala Shell (`impala-shell` Command)

You can use the Impala shell tool (`impala-shell`) to set up databases and tables, insert data, and issue queries. For ad hoc queries and exploration, you can submit SQL statements in an interactive session. To automate your work, you can specify command-line options to process a single statement or a script file. The `impala-shell` interpreter accepts all the same SQL statements listed in [Impala SQL Statements](#) on page 228, plus some shell-only commands that you can use for tuning performance and diagnosing problems.

The `impala-shell` command fits into the familiar Unix toolchain:

- The `-q` option lets you issue a single query from the command line, without starting the interactive interpreter. You could use this option to run `impala-shell` from inside a shell script or with the command invocation syntax from a Python, Perl, or other kind of script.
- The `-f` option lets you process a file containing multiple SQL statements, such as a set of reports or DDL statements to create a group of tables and views.
- The `--var` option lets you pass substitution variables to the statements that are executed by that `impala-shell` session, for example the statements in a script file processed by the `-f` option. You encode the substitution variable on the command line using the notation `--var=variable_name=value`. Within a SQL statement, you substitute the value by using the notation `${var:variable_name}`. This feature is available in CDH 5.7 / Impala 2.5 and higher.
- The `-o` option lets you save query output to a file.
- The `-B` option turns off pretty-printing, so that you can produce comma-separated, tab-separated, or other delimited text files as output. (Use the `--output_delimiter` option to choose the delimiter character; the default is the tab character.)
- In non-interactive mode, query output is printed to `stdout` or to the file specified by the `-o` option, while incidental output is printed to `stderr`, so that you can process just the query output as part of a Unix pipeline.
- In interactive mode, `impala-shell` uses the `readline` facility to recall and edit previous commands.

For information on installing the Impala shell, see [Installing Impala](#) on page 29. In Cloudera Manager 4.1 and higher, Cloudera Manager installs `impala-shell` automatically. You might install `impala-shell` manually on other systems not managed by Cloudera Manager, so that you can issue queries from client systems that are not also running the Impala daemon or other Apache Hadoop components.

For information about establishing a connection to a DataNode running the `impalad` daemon through the `impala-shell` command, see [Connecting to impalad through impala-shell](#) on page 515.

For a list of the `impala-shell` command-line options, see [impala-shell Configuration Options](#) on page 511. For reference information about the `impala-shell` interactive commands, see [impala-shell Command Reference](#) on page 520.

impala-shell Configuration Options

You can specify the following options when starting the `impala-shell` command to change how shell commands are executed. The table shows the format to use when specifying each option on the command line, or through the `$HOME/.impalarc` configuration file.



Note:

These options are different than the configuration options for the `impalad` daemon itself. For the `impalad` options, see [Modifying Impala Startup Options](#) on page 45.

Summary of `impala-shell` Configuration Options

The following table shows the names and allowed arguments for the `impala-shell` configuration options. You can specify options on the command line, or in a configuration file as described in [impala-shell Configuration File](#) on page 514.

Command-Line Option	Configuration File Setting	Explanation
<code>-B</code> or <code>--delimited</code>	<code>write_delimited=true</code>	Causes all query results to be printed in plain format as a delimited text file. Useful for producing data files to be used with other Hadoop components. Also useful for avoiding the performance overhead of pretty-printing all output, especially when running benchmark tests using queries returning large result sets. Specify the delimiter character with the <code>--output_delimiter</code> option. Store all query results in a file rather than printing to the screen with the <code>-B</code> option. Added in Impala 1.0.1.
<code>--print_header</code>	<code>print_header=true</code>	
<code>-o filename</code> or <code>--output_file filename</code>	<code>output_file=filename</code>	Stores all query results in the specified file. Typically used to store the results of a single query issued from the command line with the <code>-q</code> option. Also works for interactive sessions; you see the messages such as number of rows fetched, but not the actual result set. To suppress these incidental messages when combining the <code>-q</code> and <code>-o</code> options, redirect <code>stderr</code> to <code>/dev/null</code> . Added in Impala 1.0.1.
<code>--output_delimiter=character</code>	<code>output_delimiter=character</code>	Specifies the character to use as a delimiter between fields when query results are printed in plain format by the <code>-B</code> option. Defaults to tab (<code>'\t'</code>). If an output value contains the delimiter character, that field is quoted, escaped by doubling quotation marks, or both. Added in Impala 1.0.1.
<code>-p</code> or <code>--show_profiles</code>	<code>show_profiles=true</code>	Displays the query execution plan (same output as the <code>EXPLAIN</code> statement) and a more detailed low-level breakdown of execution steps, for every query executed by the shell.
<code>-h</code> or <code>--help</code>	N/A	Displays help information.
<code>-i hostname</code> or <code>--impalad=hostname[:portnum]</code>	<code>impalad=hostname[:portnum]</code>	Connects to the <code>impalad</code> daemon on the specified host. The default port of 21000 is assumed unless you provide another value. You can connect to any host in your cluster that is running <code>impalad</code> . If you connect to an instance of <code>impalad</code> that was started with an alternate port specified by the <code>--fe_port</code> flag, provide that alternative port.
<code>-q query</code> or <code>--query=query</code>	<code>query=query</code>	Passes a query or other <code>impala-shell</code> command from the command line. The <code>impala-shell</code> interpreter immediately exits after processing the statement. It is limited to a single statement, which could be a <code>SELECT</code> , <code>CREATE TABLE</code> , <code>SHOW TABLES</code> , or any other statement recognized in <code>impala-shell</code> . Because you cannot pass a <code>USE</code> statement and another query, fully qualify the names for any tables outside the <code>default</code> database. (Or

Command-Line Option	Configuration File Setting	Explanation
		use the <code>-f</code> option to pass a file with a <code>USE</code> statement followed by other queries.)
<code>-f query_file</code> or <code>--query_file=query_file</code>	<code>query_file=path_to_query_file</code>	Passes a SQL query from a file. Multiple statements must be semicolon (;) delimited. In CDH 5.5 / Impala 2.3 and higher, you can specify a filename of <code>-</code> to represent standard input. This feature makes it convenient to use <code>impala-shell</code> as part of a Unix pipeline where SQL statements are generated dynamically by other tools.
<code>-k</code> or <code>--kerberos</code>	<code>use_kerberos=true</code>	Kerberos authentication is used when the shell connects to <code>impalad</code> . If Kerberos is not enabled on the instance of <code>impalad</code> to which you are connecting, errors are displayed. See for the steps to set up and use Kerberos authentication in Impala.
<code>-s kerberos_service_name</code> or <code>--kerberos_service_name=name</code>	<code>kerberos_service_name=name</code>	Instructs <code>impala-shell</code> to authenticate to a particular <code>impalad</code> service principal. If a <code>kerberos_service_name</code> is not specified, <code>impala</code> is used by default. If this option is used in conjunction with a connection in which Kerberos is not supported, errors are returned.
<code>-V</code> or <code>--verbose</code>	<code>verbose=true</code>	Enables verbose output.
<code>--quiet</code>	<code>verbose=false</code>	Disables verbose output.
<code>-v</code> or <code>--version</code>	<code>version=true</code>	Displays version information.
<code>-c</code>	<code>ignore_query_failure=true</code>	Continues on query failure.
<code>-r</code> or <code>--refresh_after_connect</code>	<code>refresh_after_connect=true</code>	Updates Impala metadata upon connection. Same as running the <code>INVALIDATE METADATA</code> statement after connecting. (This option was originally named when the <code>REFRESH</code> statement did the extensive metadata updates now performed by <code>INVALIDATE METADATA</code> .)
<code>-d default_db</code> or <code>--database=default_db</code>	<code>default_db=default_db</code>	Specifies the database to be used on startup. Same as running the <code>USE</code> statement after connecting. If not specified, a database named <code>DEFAULT</code> is used.
<code>--ssl</code>	<code>ssl=true</code>	Enables TLS/SSL for <code>impala-shell</code> .
<code>--ca_cert=path_to_certificate</code>	<code>ca_cert=path_to_certificate</code>	The local pathname pointing to the third-party CA certificate, or to a copy of the server certificate for self-signed server certificates. If <code>--ca_cert</code> is not set, <code>impala-shell</code> enables TLS/SSL, but does not validate the server certificate. This is useful for connecting to a known-good Impala that is only running over TLS/SSL, when a copy of the certificate is not available (such as when debugging customer installations).
<code>-l</code>	<code>use_ldap=true</code>	Enables LDAP authentication.
<code>-u</code>	<code>user=user_name</code>	Supplies the username, when LDAP authentication is enabled by the <code>-l</code> option. (Specify the short username,

Using the Impala Shell (impala-shell Command)

Command-Line Option	Configuration File Setting	Explanation
		not the full LDAP distinguished name.) The shell then prompts interactively for the password.
<code>-ldap_password_cmd=command</code>	N/A	Specifies a command to run to retrieve the LDAP password, when LDAP authentication is enabled by the <code>-l</code> option. If the command includes space-separated arguments, enclose the command and its arguments in quotation marks.
<code>--config_file=path_to_config_file</code>	N/A	Specifies the path of the file containing <code>impala-shell</code> configuration settings. The default is <code>\$HOME/.impalarc</code> . This setting can only be specified on the command line.
<code>--live_progress</code>	N/A	Prints a progress bar showing roughly the percentage complete for each query. The information is updated interactively as the query progresses. See LIVE_PROGRESS Query Option (CDH 5.5 or higher only) on page 341.
<code>--live_summary</code>	N/A	Prints a detailed report, similar to the <code>SUMMARY</code> command, showing progress details for each phase of query execution. The information is updated interactively as the query progresses. See LIVE_SUMMARY Query Option (CDH 5.5 or higher only) on page 342.
<code>--var=variable_name=value</code>	N/A	Defines a substitution variable that can be used within the <code>impala-shell</code> session. The variable can be substituted into statements processed by the <code>-q</code> or <code>-f</code> options, or in an interactive shell session. Within a SQL statement, you substitute the value by using the notation <code>\${var:variable_name}</code> . This feature is available in CDH 5.7 / Impala 2.5 and higher.

impala-shell Configuration File

You can define a set of default options for your `impala-shell` environment, stored in the file `$HOME/.impalarc`. This file consists of key-value pairs, one option per line. Everything after a `#` character on a line is treated as a comment and ignored.

The configuration file must contain a header label `[impala]`, followed by the options specific to `impala-shell`. (This standard convention for configuration files lets you use a single file to hold configuration options for multiple applications.)

To specify a different filename or path for the configuration file, specify the argument `--config_file=path_to_config_file` on the `impala-shell` command line.

The names of the options in the configuration file are similar (although not necessarily identical) to the long-form command-line arguments to the `impala-shell` command. For the names to use, see [Summary of impala-shell Configuration Options](#) on page 512.

Any options you specify on the `impala-shell` command line override any corresponding options within the configuration file.

The following example shows a configuration file that you might use during benchmarking tests. It sets verbose mode, so that the output from each SQL query is followed by timing information. `impala-shell` starts inside the database containing the tables with the benchmark data, avoiding the need to issue a `USE` statement or use fully qualified table names.

In this example, the query output is formatted as delimited text rather than enclosed in ASCII art boxes, and is stored in a file rather than printed to the screen. Those options are appropriate for benchmark situations, so that the overhead of `impala-shell` formatting and printing the result set does not factor into the timing measurements. It also enables

the `show_profiles` option. That option prints detailed performance information after each query, which might be valuable in understanding the performance of benchmark queries.

```
[impala]
verbose=true
default_db=tpc_benchmarking
write_delimited=true
output_delimiter=,
output_file=/home/tester1/benchmark_results.csv
show_profiles=true
```

The following example shows a configuration file that connects to a specific remote Impala node, runs a single query within a particular database, then exits. You would typically use this kind of single-purpose configuration setting with the `impala-shell` command-line option `--config_file=path_to_config_file`, to easily select between many predefined queries that could be run against different databases, hosts, or even different clusters. To run a sequence of statements instead of a single query, specify the configuration option `query_file=path_to_query_file` instead.

```
[impala]
impalad=impala-test-nodel.example.com
default_db=site_stats
# Issue a predefined query and immediately exit.
query=select count(*) from web_traffic where event_date = trunc(now(),'dd')
```

Connecting to `impalad` through `impala-shell`

Within an `impala-shell` session, you can only issue queries while connected to an instance of the `impalad` daemon. You can specify the connection information:

- Through command-line options when you run the `impala-shell` command.
- Through a configuration file that is read when you run the `impala-shell` command.
- During an `impala-shell` session, by issuing a `CONNECT` command.

See [impala-shell Configuration Options](#) on page 511 for the command-line and configuration file options you can use.

You can connect to any DataNode where an instance of `impalad` is running, and that host coordinates the execution of all queries sent to it.

For simplicity during development, you might always connect to the same host, perhaps running `impala-shell` on the same host as `impalad` and specifying the hostname as `localhost`.

In a production environment, you might enable load balancing, in which you connect to specific host/port combination but queries are forwarded to arbitrary hosts. This technique spreads the overhead of acting as the coordinator node among all the DataNodes in the cluster. See [Using Impala through a Proxy for High Availability](#) on page 93 for details.

To connect the Impala shell during shell startup:

1. Locate the hostname of a DataNode within the cluster that is running an instance of the `impalad` daemon. If that DataNode uses a non-default port (something other than port 21000) for `impala-shell` connections, find out the port number also.
2. Use the `-i` option to the `impala-shell` interpreter to specify the connection information for that instance of `impalad`:

```
# When you are logged into the same machine running impalad.
# The prompt will reflect the current hostname.
$ impala-shell

# When you are logged into the same machine running impalad.
# The host will reflect the hostname 'localhost'.
$ impala-shell -i localhost

# When you are logged onto a different host, perhaps a client machine
# outside the Hadoop cluster.
$ impala-shell -i some.other.hostname
```

Using the Impala Shell (`impala-shell` Command)

```
# When you are logged onto a different host, and impalad is listening
# on a non-default port. Perhaps a load balancer is forwarding requests
# to a different host/port combination behind the scenes.
$ impala-shell -i some.other.hostname:port_number
```

To connect the Impala shell after shell startup:

1. Start the Impala shell with no connection:

```
$ impala-shell
```

You should see a prompt like the following:

```
Welcome to the Impala shell. Press TAB twice to see a list of available commands.
Copyright (c) year Cloudera, Inc. All rights reserved.

(Shell
  build version: Impala Shell v2.7.x (hash) built on
  date)
[Not connected] >
```

2. Locate the hostname of a DataNode within the cluster that is running an instance of the `impalad` daemon. If that DataNode uses a non-default port (something other than port 21000) for `impala-shell` connections, find out the port number also.
3. Use the `connect` command to connect to an Impala instance. Enter a command of the form:

```
[Not connected] > connect impalad-host
[impalad-host:21000] >
```



Note: Replace `impalad-host` with the hostname you have configured for any DataNode running Impala in your environment. The changed prompt indicates a successful connection.

To start `impala-shell` in a specific database:

You can use all the same connection options as in previous examples. For simplicity, these examples assume that you are logged into one of the DataNodes that is running the `impalad` daemon.

1. Find the name of the database containing the relevant tables, views, and so on that you want to operate on.
2. Use the `-d` option to the `impala-shell` interpreter to connect and immediately switch to the specified database, without the need for a `USE` statement or fully qualified names:

```
# Subsequent queries with unqualified names operate on
# tables, views, and so on inside the database named 'staging'.
$ impala-shell -i localhost -d staging

# It is common during development, ETL, benchmarking, and so on
# to have different databases containing the same table names
# but with different contents or layouts.
$ impala-shell -i localhost -d parquet_snappy_compression
$ impala-shell -i localhost -d parquet_gzip_compression
```

To run one or several statements in non-interactive mode:

You can use all the same connection options as in previous examples. For simplicity, these examples assume that you are logged into one of the DataNodes that is running the `impalad` daemon.

1. Construct a statement, or a file containing a sequence of statements, that you want to run in an automated way, without typing or copying and pasting each time.

2. Invoke `impala-shell` with the `-q` option to run a single statement, or the `-f` option to run a sequence of statements from a file. The `impala-shell` command returns immediately, without going into the interactive interpreter.

```
# A utility command that you might run while developing shell scripts
# to manipulate HDFS files.
$ impala-shell -i localhost -d database_of_interest -q 'show tables'

# A sequence of CREATE TABLE, CREATE VIEW, and similar DDL statements
# can go into a file to make the setup process repeatable.
$ impala-shell -i localhost -d database_of_interest -f recreate_tables.sql
```

Running Commands and SQL Statements in impala-shell

For information on available commands, see [impala-shell Command Reference](#) on page 520. You can see the full set of available commands by pressing TAB twice, for example:

```
[impalad-host:21000] >
connect describe explain help history insert quit refresh select
set shell show use version
[impalad-host:21000] >
```



Note: Commands must be terminated by a semi-colon. A command can span multiple lines.

For example:

```
[localhost:21000] > select *
> from t1
> limit 5;

+-----+-----+
| s1      | s2      |
+-----+-----+
| hello   | world   |
| goodbye | cleveland |
+-----+-----+
```

A comment is considered part of the statement it precedes, so when you enter a `--` or `/* */` comment, you get a continuation prompt until you finish entering a statement ending with a semicolon:

```
[localhost:21000] > -- This is a test comment
> show tables like 't*';

+-----+
| name |
+-----+
| t1   |
| t2   |
| tab1 |
| tab2 |
| tab3 |
| text_t |
+-----+
```

Use the up-arrow and down-arrow keys to cycle through and edit previous commands. `impala-shell` uses the `readline` library and so supports a standard set of keyboard shortcuts for editing and cursor movement, such as `Ctrl-A` for beginning of line and `Ctrl-E` for end of line.

In CDH 5.7 / Impala 2.5 and higher, you can define substitution variables to be used within SQL statements processed by `impala-shell`. On the command line, you specify the option `--var=variable_name=value`. Within an interactive session or a script file processed by the `-f` option, you specify a `SET` command using the notation `SET`

Using the Impala Shell (impala-shell Command)

`VAR:variable_name=value`. Within a SQL statement, you substitute the value by using the notation `${var:variable_name}`.



Note: Because this feature is part of `impala-shell` rather than the `impalad` backend, make sure the client system you are connecting from has the most recent `impala-shell`. You can use this feature with a new `impala-shell` connecting to an older `impalad`, but not the reverse.

For example, here are some `impala-shell` commands that define substitution variables and then use them in SQL statements executed through the `-q` and `-f` options. Notice how the `-q` argument strings are single-quoted to prevent shell expansion of the `${var:value}` notation, and any string literals within the queries are enclosed by double quotation marks.

```
$ impala-shell --var=tname=table1 --var=colname=x --var=coltype=string -q 'create table
${var:tname} (${var:colname} ${var:coltype}) stored as parquet'
Starting Impala Shell without Kerberos authentication
Connected to hostname
Server version: impalad_version
Query: create table table1 (x string) stored as parquet

$ NEW_STRING="hello world"
$ impala-shell --var=tname=table1 --var=insert_val="$NEW_STRING" -q 'insert into
${var:tname} values ("${var:insert_val}")'
Starting Impala Shell without Kerberos authentication
Connected to hostname
Server version: impalad_version
Query: insert into table1 values ("hello world")
Inserted 1 row(s) in 1.40s

$ for VAL in foo bar bleetch
do
  impala-shell --var=tname=table1 --var=insert_val="$VAL" -q 'insert into ${var:tname}
  values ("${var:insert_val}")'
done
...
Query: insert into table1 values ("foo")
Inserted 1 row(s) in 0.22s
Query: insert into table1 values ("bar")
Inserted 1 row(s) in 0.11s
Query: insert into table1 values ("bleetch")
Inserted 1 row(s) in 0.21s

$ echo "Search for what substring?" ; read answer
Search for what substring?
b
$ impala-shell --var=tname=table1 -q 'select x from ${var:tname} where x like
"%${var:answer}%"'
Starting Impala Shell without Kerberos authentication
Connected to hostname
Server version: impalad_version
Query: select x from table1 where x like "%b%"
+-----+
| x      |
+-----+
| bleetch |
| bar    |
+-----+
Fetched 2 row(s) in 0.83s
```

Here is a substitution variable passed in by the `--var` option, and then referenced by statements issued interactively. Then the variable is cleared with the `UNSET` command, and defined again with the `SET` command.

```
$ impala-shell --quiet --var=tname=table1
Starting Impala Shell without Kerberos authentication
*****
banner_message
*****
```

```
[hostname:21000] > select count(*) from ${var:tname};
+-----+
| count(*) |
+-----+
| 4         |
+-----+
[hostname:21000] > unset var:tname;
Unsetting variable TNAME
[hostname:21000] > select count(*) from ${var:tname};
Error: Unknown variable TNAME
[hostname:21000] > set var:tname=table1;
[hostname:21000] > select count(*) from ${var:tname};
+-----+
| count(*) |
+-----+
| 4         |
+-----+
```

The following example shows how the `SOURCE` command can execute a series of statements from a file:

```
$ cat commands.sql
show databases;
show tables in default;
show functions in _impala_builtins like '*minute*';

$ impala-shell -i localhost
...
[localhost:21000] > source commands.sql;
Query: show databases
+-----+-----+
| name          | comment                                     |
+-----+-----+
| _impala_builtins | System database for Impala builtin functions |
| default        | Default Hive database                       |
+-----+-----+
Fetched 2 row(s) in 0.06s
Query: show tables in default
+-----+
| name          |
+-----+
| customers     |
| sample_07    |
| sample_08    |
| web_logs     |
+-----+
Fetched 4 row(s) in 0.02s
Query: show functions in _impala_builtins like '*minute*'
+-----+-----+-----+-----+
| return type | signature                                     | binary type | is persistent |
+-----+-----+-----+-----+
| INT         | minute(TIMESTAMP)                           | BUILTIN    | true          |
| TIMESTAMP  | minutes_add(TIMESTAMP, BIGINT)               | BUILTIN    | true          |
| TIMESTAMP  | minutes_add(TIMESTAMP, INT)                  | BUILTIN    | true          |
| TIMESTAMP  | minutes_sub(TIMESTAMP, BIGINT)               | BUILTIN    | true          |
| TIMESTAMP  | minutes_sub(TIMESTAMP, INT)                  | BUILTIN    | true          |
+-----+-----+-----+-----+
Fetched 5 row(s) in 0.03s
```

The following example shows how a file that is run by the `SOURCE` command, or through the `-q` or `-f` options of `impala-shell`, can contain additional `SOURCE` commands. The first file, `nested1.sql`, runs an `impala-shell` command and then also runs the commands from `nested2.sql`. This ability for scripts to call each other is often useful for code that sets up schemas for applications or test environments.

```
$ cat nested1.sql
show functions in _impala_builtins like '*minute*';
source nested2.sql
$ cat nested2.sql
show functions in _impala_builtins like '*hour*'
```

Using the Impala Shell (impala-shell Command)


```
$ impala-shell -i localhost -f nested1.sql
Starting Impala Shell without Kerberos authentication
Connected to localhost:21000
...
Query: show functions in _impala_builtins like '*minute*'
+-----+-----+-----+-----+
| return type | signature | binary type | is persistent |
+-----+-----+-----+-----+
| INT         | minute(TIMESTAMP) | BUILTIN    | true          |
| TIMESTAMP  | minutes_add(TIMESTAMP, BIGINT) | BUILTIN    | true          |
| TIMESTAMP  | minutes_add(TIMESTAMP, INT) | BUILTIN    | true          |
| TIMESTAMP  | minutes_sub(TIMESTAMP, BIGINT) | BUILTIN    | true          |
| TIMESTAMP  | minutes_sub(TIMESTAMP, INT) | BUILTIN    | true          |
+-----+-----+-----+-----+
Fetched 5 row(s) in 0.01s
Query: show functions in _impala_builtins like '*hour*'
+-----+-----+-----+-----+
| return type | signature | binary type | is persistent |
+-----+-----+-----+-----+
| INT         | hour(TIMESTAMP) | BUILTIN    | true          |
| TIMESTAMP  | hours_add(TIMESTAMP, BIGINT) | BUILTIN    | true          |
| TIMESTAMP  | hours_add(TIMESTAMP, INT) | BUILTIN    | true          |
| TIMESTAMP  | hours_sub(TIMESTAMP, BIGINT) | BUILTIN    | true          |
| TIMESTAMP  | hours_sub(TIMESTAMP, INT) | BUILTIN    | true          |
+-----+-----+-----+-----+
Fetched 5 row(s) in 0.01s
```

impala-shell Command Reference

Use the following commands within `impala-shell` to pass requests to the `impalad` daemon that the shell is connected to. You can enter a command interactively at the prompt, or pass it as the argument to the `-q` option of `impala-shell`. Most of these commands are passed to the Impala daemon as SQL statements; refer to the corresponding [SQL language reference sections](#) for full syntax details.

Command	Explanation
<code>alter</code>	Changes the underlying structure or settings of an Impala table, or a table shared between Impala and Hive. See ALTER TABLE Statement on page 230 and ALTER VIEW Statement on page 240 for details.
<code>compute stats</code>	Gathers important performance-related information for a table, used by Impala to optimize queries. See COMPUTE STATS Statement on page 241 for details.
<code>connect</code>	Connects to the specified instance of <code>impalad</code> . The default port of 21000 is assumed unless you provide another value. You can connect to any host in your cluster that is running <code>impalad</code> . If you connect to an instance of <code>impalad</code> that was started with an alternate port specified by the <code>--fe_port</code> flag, you must provide that alternate port. See Connecting to impalad through impala-shell on page 515 for examples. The <code>SET</code> statement has no effect until the <code>impala-shell</code> interpreter is connected to an Impala server. Once you are connected, any query options you set remain in effect as you issue a subsequent <code>CONNECT</code> command to connect to a different Impala host.
<code>describe</code>	Shows the columns, column data types, and any column comments for a specified table. <code>DESCRIBE FORMATTED</code> shows additional information such as the HDFS data directory, partitions, and internal properties for the table. See DESCRIBE Statement on page 264 for details about the basic <code>DESCRIBE</code> output and the <code>DESCRIBE FORMATTED</code> variant. You can use <code>DESC</code> as shorthand for the <code>DESCRIBE</code> command.
<code>drop</code>	Removes a schema object, and in some cases its associated data files. See DROP TABLE Statement on page 280, DROP VIEW Statement on page 282, DROP DATABASE Statement on page 273, and DROP FUNCTION Statement on page 275 for details.

Command	Explanation
<code>explain</code>	Provides the execution plan for a query. <code>EXPLAIN</code> represents a query as a series of steps. For example, these steps might be map/reduce stages, metastore operations, or file system operations such as move or rename. See EXPLAIN Statement on page 283 and Using the EXPLAIN Plan for Performance Tuning on page 557 for details.
<code>help</code>	Help provides a list of all available commands and options.
<code>history</code>	Maintains an enumerated cross-session command history. This history is stored in the <code>~/ .impalahistory</code> file.
<code>insert</code>	Writes the results of a query to a specified table. This either overwrites table data or appends data to the existing table content. See INSERT Statement on page 286 for details.
<code>invalidate metadata</code>	Updates <code>impalad</code> metadata for table existence and structure. Use this command after creating, dropping, or altering databases, tables, or partitions in Hive. See INVALIDATE METADATA Statement on page 294 for details.
<code>profile</code>	Displays low-level information about the most recent query. Used for performance diagnosis and tuning. The report starts with the same information as produced by the <code>EXPLAIN</code> statement and the <code>SUMMARY</code> command. See Using the Query Profile for Performance Tuning on page 558 for details.
<code>quit</code>	Exits the shell. Remember to include the final semicolon so that the shell recognizes the end of the command.
<code>refresh</code>	Refreshes <code>impalad</code> metadata for the locations of HDFS blocks corresponding to Impala data files. Use this command after loading new data files into an Impala table through Hive or through HDFS commands. See REFRESH Statement on page 300 for details.
<code>select</code>	Specifies the data set on which to complete some action. All information returned from <code>select</code> can be sent to some output such as the console or a file or can be used to complete some other element of query. See SELECT Statement on page 304 for details.
<code>set</code>	<p>Manages query options for an <code>impala-shell</code> session. The available options are the ones listed in Query Options for the SET Statement on page 331. These options are used for query tuning and troubleshooting. Issue <code>SET</code> with no arguments to see the current query options, either based on the <code>impalad</code> defaults, as specified by you at <code>impalad</code> startup, or based on earlier <code>SET</code> statements in the same session. To modify option values, issue commands with the syntax <code>set option=value</code>. To restore an option to its default, use the <code>unset</code> command. Some options take Boolean values of <code>true</code> and <code>false</code>. Others take numeric arguments, or quoted string values.</p> <p>The <code>SET</code> statement has no effect until the <code>impala-shell</code> interpreter is connected to an Impala server. Once you are connected, any query options you set remain in effect as you issue a subsequent <code>CONNECT</code> command to connect to a different Impala host.</p> <p>In Impala 2.0 and later, <code>SET</code> is available as a SQL statement for any kind of application, not only through <code>impala-shell</code>. See SET Statement on page 329 for details.</p> <p>In Impala 2.5 and later, you can use <code>SET</code> to define your own substitution variables within an <code>impala-shell</code> session. Within a SQL statement, you substitute the value by using the notation <code>`\${var:variable_name}</code>.</p>
<code>shell</code>	Executes the specified command in the operating system shell without exiting <code>impala-shell</code> . You can use the <code>!</code> character as shorthand for the <code>shell</code> command.

Command	Explanation
	 Note: Quote any instances of the <code>--</code> or <code>/*</code> tokens to avoid them being interpreted as the start of a comment. To embed comments within <code>source</code> or <code>!</code> commands, use the shell comment character <code>#</code> before the comment portion of the line.
<code>show</code>	Displays metastore data for schema objects created and accessed through Impala, Hive, or both. <code>show</code> can be used to gather information about objects such as databases, tables, and functions. See SHOW Statement on page 356 for details.
<code>source</code> or <code>src</code>	Executes one or more statements residing in a specified file from the local filesystem. Allows you to perform the same kinds of batch operations as with the <code>-f</code> option, but interactively within the interpreter. The file can contain SQL statements and other <code>impala-shell</code> commands, including additional <code>SOURCE</code> commands to perform a flexible sequence of actions. Each command or statement, except the last one in the file, must end with a semicolon. See Running Commands and SQL Statements in impala-shell on page 517 for examples.
<code>summary</code>	<p>Summarizes the work performed in various stages of a query. It provides a higher-level view of the information displayed by the <code>EXPLAIN</code> command. Added in Impala 1.4.0. See Using the SUMMARY Report for Performance Tuning on page 557 for details about the report format and how to interpret it.</p> <p>The time, memory usage, and so on reported by <code>SUMMARY</code> only include the portions of the statement that read data, not when data is written. Therefore, the <code>PROFILE</code> command is better for checking the performance and scalability of <code>INSERT</code> statements.</p> <p>In CDH 5.5 / Impala 2.3 and higher, you can see a continuously updated report of the summary information while a query is in progress. See LIVE_SUMMARY Query Option (CDH 5.5 or higher only) on page 342 for details.</p>
<code>unset</code>	<p>Removes any user-specified value for a query option and returns the option to its default value. See Query Options for the SET Statement on page 331 for the available query options.</p> <p>In CDH 5.7 / Impala 2.5 and higher, it can also remove user-specified substitution variables using the notation <code>UNSET VAR:variable_name</code>.</p>
<code>use</code>	Indicates the database against which to execute subsequent commands. Lets you avoid using fully qualified names when referring to tables in databases other than <code>default</code> . See USE Statement on page 372 for details. Not effective with the <code>-q</code> option, because that option only allows a single statement in the argument.
<code>version</code>	Returns Impala version information.

Tuning Impala for Performance

The following sections explain the factors affecting the performance of Impala features, and procedures for tuning, monitoring, and benchmarking Impala queries and other SQL operations.

This section also describes techniques for maximizing Impala scalability. Scalability is tied to performance: it means that performance remains high as the system workload increases. For example, reducing the disk I/O performed by a query can speed up an individual query, and at the same time improve scalability by making it practical to run more queries simultaneously. Sometimes, an optimization technique improves scalability more than performance. For example, reducing memory usage for a query might not change the query performance much, but might improve scalability by allowing more Impala queries or other kinds of jobs to run at the same time without running out of memory.



Note:

Before starting any performance tuning or benchmarking, make sure your system is configured with all the recommended minimum hardware requirements from [Hardware Requirements](#) on page 25 and software settings from [Post-Installation Configuration for Impala](#) on page 32.

- [Partitioning for Impala Tables](#) on page 568. This technique physically divides the data based on the different values in frequently queried columns, allowing queries to skip reading a large percentage of the data in a table.
- [Performance Considerations for Join Queries](#) on page 526. Joins are the main class of queries that you can tune at the SQL level, as opposed to changing physical factors such as the file format or the hardware configuration. The related topics [Overview of Column Statistics](#) on page 534 and [Overview of Table Statistics](#) on page 533 are also important primarily for join performance.
- [Overview of Table Statistics](#) on page 533 and [Overview of Column Statistics](#) on page 534. Gathering table and column statistics, using the `COMPUTE STATS` statement, helps Impala automatically optimize the performance for join queries, without requiring changes to SQL query statements. (This process is greatly simplified in Impala 1.2.2 and higher, because the `COMPUTE STATS` statement gathers both kinds of statistics in one operation, and does not require any setup and configuration as was previously necessary for the `ANALYZE TABLE` statement in Hive.)
- [Testing Impala Performance](#) on page 555. Do some post-setup testing to ensure Impala is using optimal settings for performance, before conducting any benchmark tests.
- [Benchmarking Impala Queries](#) on page 544. The configuration and sample data that you use for initial experiments with Impala is often not appropriate for doing performance tests.
- [Controlling Impala Resource Usage](#) on page 545. The more memory Impala can utilize, the better query performance you can expect. In a cluster running other kinds of workloads as well, you must make tradeoffs to make sure all Hadoop components have enough memory to perform well, so you might cap the memory that Impala can use.
- [Using Impala with the Amazon S3 Filesystem](#) on page 617. Queries against data stored in the Amazon Simple Storage Service (S3) have different performance characteristics than when the data is stored in HDFS.

A good source of tips related to scalability and performance tuning is the [Impala Cookbook](#) presentation. These slides are updated periodically as new features come out and new benchmarks are performed.

Impala Performance Guidelines and Best Practices

Here are performance guidelines and best practices that you can use during planning, experimentation, and performance tuning for an Impala-enabled CDH cluster. All of this information is also available in more detail elsewhere in the Impala documentation; it is gathered together here to serve as a cookbook and emphasize which performance techniques typically provide the highest return on investment

Choose the appropriate file format for the data

Typically, for large volumes of data (multiple gigabytes per table or partition), the Parquet file format performs best because of its combination of columnar storage layout, large I/O request size, and compression and encoding. See [How Impala Works with Hadoop File Formats](#) on page 575 for comparisons of all file formats supported by Impala, and [Using the Parquet File Format with Impala Tables](#) on page 584 for details about the Parquet file format.



Note: For smaller volumes of data, a few gigabytes or less for each table or partition, you might not see significant performance differences between file formats. At small data volumes, reduced I/O from an efficient compressed file format can be counterbalanced by reduced opportunity for parallel execution. When planning for a production deployment or conducting benchmarks, always use realistic data volumes to get a true picture of performance and scalability.

Avoid data ingestion processes that produce many small files

When producing data files outside of Impala, prefer either text format or Avro, where you can build up the files row by row. Once the data is in Impala, you can convert it to the more efficient Parquet format and split into multiple data files using a single `INSERT ... SELECT` statement. Or, if you have the infrastructure to produce multi-megabyte Parquet files as part of your data preparation process, do that and skip the conversion step inside Impala.

Always use `INSERT ... SELECT` to copy significant volumes of data from table to table within Impala. Avoid `INSERT ... VALUES` for any substantial volume of data or performance-critical tables, because each such statement produces a separate tiny data file. See [INSERT Statement](#) on page 286 for examples of the `INSERT ... SELECT` syntax.

For example, if you have thousands of partitions in a Parquet table, each with less than 256 MB of data, consider partitioning in a less granular way, such as by year / month rather than year / month / day. If an inefficient data ingestion process produces thousands of data files in the same table or partition, consider compacting the data by performing an `INSERT ... SELECT` to copy all the data to a different table; the data will be reorganized into a smaller number of larger files by this process.

Choose partitioning granularity based on actual data volume

Partitioning is a technique that physically divides the data based on values of one or more columns, such as by year, month, day, region, city, section of a web site, and so on. When you issue queries that request a specific value or range of values for the partition key columns, Impala can avoid reading the irrelevant data, potentially yielding a huge savings in disk I/O.

When deciding which column(s) to use for partitioning, choose the right level of granularity. For example, should you partition by year, month, and day, or only by year and month? Choose a partitioning strategy that puts at least 256 MB of data in each partition, to take advantage of HDFS bulk I/O and Impala distributed queries.

Over-partitioning can also cause query planning to take longer than necessary, as Impala prunes the unnecessary partitions. Ideally, keep the number of partitions in the table under 30 thousand.

When preparing data files to go in a partition directory, create several large files rather than many small ones. If you receive data in the form of many small files and have no control over the input format, consider using the `INSERT ... SELECT` syntax to copy data from one table or partition to another, which compacts the files into a relatively small number (based on the number of nodes in the cluster).

If you need to reduce the overall number of partitions and increase the amount of data in each partition, first look for partition key columns that are rarely referenced or are referenced in non-critical queries (not subject to an SLA). For example, your web site log data might be partitioned by year, month, day, and hour, but if most queries roll up the results by day, perhaps you only need to partition by year, month, and day.

If you need to reduce the granularity even more, consider creating “buckets”, computed values corresponding to different sets of partition key values. For example, you can use the `TRUNC()` function with a `TIMESTAMP` column to group date and time values based on intervals such as week or quarter. See [Impala Date and Time Functions](#) on page 398 for details.

See [Partitioning for Impala Tables](#) on page 568 for full details and performance considerations for partitioning.

Use smallest appropriate integer types for partition key columns

Although it is tempting to use strings for partition key columns, since those values are turned into HDFS directory names anyway, you can minimize memory usage by using numeric values for common partition key fields such as YEAR, MONTH, and DAY. Use the smallest integer type that holds the appropriate range of values, typically TINYINT for MONTH and DAY, and SMALLINT for YEAR. Use the EXTRACT() function to pull out individual date and time fields from a TIMESTAMP value, and CAST() the return value to the appropriate integer type.

Choose an appropriate Parquet block size

By default, the Impala INSERT ... SELECT statement creates Parquet files with a 256 MB block size. (This default was changed in Impala 2.0. Formerly, the limit was 1 GB, but Impala made conservative estimates about compression, resulting in files that were smaller than 1 GB.)

Each Parquet file written by Impala is a single block, allowing the whole file to be processed as a unit by a single host. As you copy Parquet files into HDFS or between HDFS filesystems, use `hdfs dfs -pb` to preserve the original block size.

If there is only one or a few data block in your Parquet table, or in a partition that is the only one accessed by a query, then you might experience a slowdown for a different reason: not enough data to take advantage of Impala's parallel distributed queries. Each data block is processed by a single core on one of the DataNodes. In a 100-node cluster of 16-core machines, you could potentially process thousands of data files simultaneously. You want to find a sweet spot between “many tiny files” and “single giant file” that balances bulk I/O and parallel processing. You can set the PARQUET_FILE_SIZE query option before doing an INSERT ... SELECT statement to reduce the size of each generated Parquet file. (Specify the file size as an absolute number of bytes, or in Impala 2.0 and later, in units ending with m for megabytes or g for gigabytes.) Run benchmarks with different file sizes to find the right balance point for your particular data volume.

Gather statistics for all tables used in performance-critical or high-volume join queries

Gather the statistics with the COMPUTE STATS statement. See [Performance Considerations for Join Queries](#) on page 526 for details.

Minimize the overhead of transmitting results back to the client

Use techniques such as:

- **Aggregation.** If you need to know how many rows match a condition, the total values of matching values from some column, the lowest or highest matching value, and so on, call aggregate functions such as COUNT(), SUM(), and MAX() in the query rather than sending the result set to an application and doing those computations there. Remember that the size of an unaggregated result set could be huge, requiring substantial time to transmit across the network.
- **Filtering.** Use all applicable tests in the WHERE clause of a query to eliminate rows that are not relevant, rather than producing a big result set and filtering it using application logic.
- **LIMIT clause.** If you only need to see a few sample values from a result set, or the top or bottom values from a query using ORDER BY, include the LIMIT clause to reduce the size of the result set rather than asking for the full result set and then throwing most of the rows away.
- **Avoid overhead from pretty-printing the result set and displaying it on the screen.** When you retrieve the results through `impala-shell`, use `impala-shell` options such as `-B` and `--output_delimiter` to produce results without special formatting, and redirect output to a file rather than printing to the screen. Consider using INSERT ... SELECT to write the results directly to new files in HDFS. See [impala-shell Configuration Options](#) on page 511 for details about the `impala-shell` command-line options.

Verify that your queries are planned in an efficient logical manner

Examine the EXPLAIN plan for a query before actually running it. See [EXPLAIN Statement](#) on page 283 and [Using the EXPLAIN Plan for Performance Tuning](#) on page 557 for details.

Tuning Impala for Performance

Verify performance characteristics of queries

Verify that the low-level aspects of I/O, memory usage, network bandwidth, CPU utilization, and so on are within expected ranges by examining the query profile for a query after running it. See [Using the Query Profile for Performance Tuning](#) on page 558 for details.

Use appropriate operating system settings

See [Optimizing Performance in CDH](#) for recommendations about operating system settings that you can change to influence Impala performance. In particular, you might find that changing the `vm.swappiness` Linux kernel setting to a non-zero value improves overall performance.

Hotspot analysis

In the context of Impala, a hotspot is defined as “an Impala daemon that for a single query or a workload is spending a far greater amount of time processing data relative to its neighbours”.

Before discussing the options to tackle this issue some background is first required to understand how this problem can occur.

By default, the scheduling of scan based plan fragments is deterministic. This means that for multiple queries needing to read the same block of data, the same node will be picked to host the scan. The default scheduling logic does not take into account node workload from prior queries. The complexity of materializing a tuple depends on a few factors, namely: decoding and decompression. If the tuples are densely packed into data pages due to good encoding/compression ratios, there will be more work required when reconstructing the data. Each compression codec offers different performance tradeoffs and should be considered before writing the data. Due to the deterministic nature of the scheduler, single nodes can become bottlenecks for highly concurrent queries that use the same tables.

If, for example, a Parquet based dataset is tiny, e.g. a small dimension table, such that it fits into a single HDFS block (Impala by default will create 256 MB blocks when Parquet is used, each containing a single row group) then there are a number of options that can be considered to resolve the potential scheduling hotspots when querying this data:

- In `and higher`, the scheduler’s deterministic behaviour can be changed using the following query options: `REPLICA_PREFERENCE` and `RANDOM_REPLICA`. For a detailed description of each of these modes see `IMPALA-2696`.
- HDFS caching can be used to cache block replicas. This will cause the Impala scheduler to randomly pick (from `and higher`) a node that is hosting a cached block replica for the scan. Note, although HDFS caching has benefits, it serves only to help with the reading of raw block data and not cached tuple data, but with the right number of cached replicas (by default, HDFS only caches one replica), even load distribution can be achieved for smaller datasets.
- Do not compress the table data. The uncompressed table data spans more nodes and eliminates skew caused by compression.
- Reduce the Parquet file size via the `PARQUET_FILE_SIZE` query option when writing the table data. Using this approach the data will span more nodes. However it’s not recommended to drop the size below 32 MB.

Performance Considerations for Join Queries

Queries involving join operations often require more tuning than queries that refer to only one table. The maximum size of the result set from a join query is the product of the number of rows in all the joined tables. When joining several tables with millions or billions of rows, any missed opportunity to filter the result set, or other inefficiency in the query, could lead to an operation that does not finish in a practical time and has to be cancelled.

The simplest technique for tuning an Impala join query is to collect statistics on each table involved in the join using the `COMPUTE STATS` statement, and then let Impala automatically optimize the query based on the size of each table, number of distinct values of each column, and so on. The `COMPUTE STATS` statement and the join optimization are new features introduced in Impala 1.2.2. For accurate statistics about each table, issue the `COMPUTE STATS` statement after loading the data into that table, and again if the amount of data changes substantially due to an `INSERT`, `LOAD DATA`, adding a partition, and so on.

If statistics are not available for all the tables in the join query, or if Impala chooses a join order that is not the most efficient, you can override the automatic join order optimization by specifying the `STRAIGHT_JOIN` keyword immediately after the `SELECT` and any `DISTINCT` or `ALL` keywords. In this case, Impala uses the order the tables appear in the query to guide how the joins are processed.

When you use the `STRAIGHT_JOIN` technique, you must order the tables in the join query manually instead of relying on the Impala optimizer. The optimizer uses sophisticated techniques to estimate the size of the result set at each stage of the join. For manual ordering, use this heuristic approach to start with, and then experiment to fine-tune the order:

- Specify the largest table first. This table is read from disk by each Impala node and so its size is not significant in terms of memory usage during the query.
- Next, specify the smallest table. The contents of the second, third, and so on tables are all transmitted across the network. You want to minimize the size of the result set from each subsequent stage of the join query. The most likely approach involves joining a small table first, so that the result set remains small even as subsequent larger tables are processed.
- Join the next smallest table, then the next smallest, and so on.

For example, if you had tables `BIG`, `MEDIUM`, `SMALL`, and `TINY`, the logical join order to try would be `BIG`, `TINY`, `SMALL`, `MEDIUM`.

The terms “largest” and “smallest” refers to the size of the intermediate result set based on the number of rows and columns from each table that are part of the result set. For example, if you join one table `sales` with another table `customers`, a query might find results from 100 different customers who made a total of 5000 purchases. In that case, you would specify `SELECT ... FROM sales JOIN customers ...`, putting `customers` on the right side because it is smaller in the context of this query.

The Impala query planner chooses between different techniques for performing join queries, depending on the absolute and relative sizes of the tables. **Broadcast joins** are the default, where the right-hand table is considered to be smaller than the left-hand table, and its contents are sent to all the other nodes involved in the query. The alternative technique is known as a **partitioned join** (not related to a partitioned table), which is more suitable for large tables of roughly equal size. With this technique, portions of each table are sent to appropriate other nodes where those subsets of rows can be processed in parallel. The choice of broadcast or partitioned join also depends on statistics being available for all tables in the join, gathered by the `COMPUTE STATS` statement.

To see which join strategy is used for a particular query, issue an `EXPLAIN` statement for the query. If you find that a query uses a broadcast join when you know through benchmarking that a partitioned join would be more efficient, or vice versa, add a hint to the query to specify the precise join mechanism to use. See [Query Hints in Impala SELECT Statements](#) on page 326 for details.

How Joins Are Processed when Statistics Are Unavailable

If table or column statistics are not available for some tables in a join, Impala still reorders the tables using the information that is available. Tables with statistics are placed on the left side of the join order, in descending order of cost based on overall size and cardinality. Tables without statistics are treated as zero-size, that is, they are always placed on the right side of the join order.

Overriding Join Reordering with `STRAIGHT_JOIN`

If an Impala join query is inefficient because of outdated statistics or unexpected data distribution, you can keep Impala from reordering the joined tables by using the `STRAIGHT_JOIN` keyword immediately after the `SELECT` and any `DISTINCT` or `ALL` keywords. The `STRAIGHT_JOIN` keyword turns off the reordering of join clauses that Impala does internally, and produces a plan that relies on the join clauses being ordered optimally in the query text.



Note:

The `STRAIGHT_JOIN` hint affects the join order of table references in the query block containing the hint. It does not affect the join order of nested queries, such as views, inline views, or `WHERE`-clause subqueries. To use this hint for performance tuning of complex queries, apply the hint to all query blocks that need a fixed join order.

In this example, the subselect from the `BIG` table produces a very small result set, but the table might still be treated as if it were the biggest and placed first in the join order. Using `STRAIGHT_JOIN` for the last join clause prevents the final table from being reordered, keeping it as the rightmost table in the join order.

```
select straight_join x from medium join small join (select * from big where c1 < 10) as
big
  where medium.id = small.id and small.id = big.id;

-- If the query contains [DISTINCT | ALL], the hint goes after those keywords.
select distinct straight_join x from medium join small join (select * from big where c1
< 10) as big
  where medium.id = small.id and small.id = big.id;
```

Examples of Join Order Optimization

Here are examples showing joins between tables with 1 billion, 200 million, and 1 million rows. (In this case, the tables are unpartitioned and using Parquet format.) The smaller tables contain subsets of data from the largest one, for convenience of joining on the unique `ID` column. The smallest table only contains a subset of columns from the others.

```
[localhost:21000] > create table big stored as parquet as select * from raw_data;
+-----+
| summary |
+-----+
| Inserted 1000000000 row(s) |
+-----+
Returned 1 row(s) in 671.56s
[localhost:21000] > desc big;
+-----+-----+-----+
| name | type | comment |
+-----+-----+-----+
| id | int | |
| val | int | |
| zfill | string | |
| name | string | |
| assertion | boolean | |
+-----+-----+-----+
Returned 5 row(s) in 0.01s
[localhost:21000] > create table medium stored as parquet as select * from big limit
200 * floor(1e6);
+-----+
| summary |
+-----+
| Inserted 200000000 row(s) |
+-----+
Returned 1 row(s) in 138.31s
[localhost:21000] > create table small stored as parquet as select id,val,name from big
where assertion = true limit 1 * floor(1e6);
+-----+
| summary |
+-----+
| Inserted 1000000 row(s) |
+-----+
Returned 1 row(s) in 6.32s
```

For any kind of performance experimentation, use the `EXPLAIN` statement to see how any expensive query will be performed without actually running it, and enable verbose `EXPLAIN` plans containing more performance-oriented detail: The most interesting plan lines are highlighted in bold, showing that without statistics for the joined tables,

Impala cannot make a good estimate of the number of rows involved at each stage of processing, and is likely to stick with the BROADCAST join mechanism that sends a complete copy of one of the tables to each node.

```
[localhost:21000] > set explain_level=verbose;
EXPLAIN_LEVEL set to verbose
[localhost:21000] > explain select count(*) from big join medium where big.id = medium.id;
+-----+
| Explain String
```

```

+-----+
| Estimated Per-Host Requirements: Memory=2.10GB VCores=2
```

```

PLAN FRAGMENT 0
PARTITION: UNPARTITIONED

6:AGGREGATE (merge finalize)
  output: SUM(COUNT(*))
  cardinality: 1
  per-host memory: unavailable
  tuple ids: 2

5:EXCHANGE
  cardinality: 1
  per-host memory: unavailable
  tuple ids: 2

PLAN FRAGMENT 1
PARTITION: RANDOM

STREAM DATA SINK
EXCHANGE ID: 5
UNPARTITIONED

3:AGGREGATE
  output: COUNT(*)
  cardinality: 1
  per-host memory: 10.00MB
  tuple ids: 2

2:HASH JOIN
  join op: INNER JOIN (BROADCAST)
  hash predicates:
    big.id = medium.id
  cardinality: unavailable
  per-host memory: 2.00GB
  tuple ids: 0 1

----4:EXCHANGE
  cardinality: unavailable
  per-host memory: 0B
  tuple ids: 1

0:SCAN HDFS
  table=join_order.big #partitions=1/1 size=23.12GB
  table stats: unavailable
  column stats: unavailable
  cardinality: unavailable
  per-host memory: 88.00MB
  tuple ids: 0

PLAN FRAGMENT 2
PARTITION: RANDOM

STREAM DATA SINK
EXCHANGE ID: 4
UNPARTITIONED

1:SCAN HDFS
  table=join_order.medium #partitions=1/1 size=4.62GB
  table stats: unavailable
  column stats: unavailable
  cardinality: unavailable
  per-host memory: 88.00MB
  tuple ids: 1
```

```
+-----+
Returned 64 row(s) in 0.04s
```

Gathering statistics for all the tables is straightforward, one `COMPUTE STATS` statement per table:

```
[localhost:21000] > compute stats small;
+-----+
| summary |
+-----+
| Updated 1 partition(s) and 3 column(s). |
+-----+
Returned 1 row(s) in 4.26s
[localhost:21000] > compute stats medium;
+-----+
| summary |
+-----+
| Updated 1 partition(s) and 5 column(s). |
+-----+
Returned 1 row(s) in 42.11s
[localhost:21000] > compute stats big;
+-----+
| summary |
+-----+
| Updated 1 partition(s) and 5 column(s). |
+-----+
Returned 1 row(s) in 165.44s
```

With statistics in place, Impala can choose a more effective join order rather than following the left-to-right sequence of tables in the query, and can choose `BROADCAST` or `PARTITIONED` join strategies based on the overall sizes and number of rows in the table:

```
[localhost:21000] > explain select count(*) from medium join big where big.id = medium.id;
Query: explain select count(*) from medium join big where big.id = medium.id
+-----+
| Explain String |
+-----+
| Estimated Per-Host Requirements: Memory=937.23MB VCores=2 |
+-----+
| PLAN FRAGMENT 0 |
| PARTITION: UNPARTITIONED |
| |
| 6:AGGREGATE (merge finalize) |
|   output: SUM(COUNT(*)) |
|   cardinality: 1 |
|   per-host memory: unavailable |
|   tuple ids: 2 |
| |
| 5:EXCHANGE |
|   cardinality: 1 |
|   per-host memory: unavailable |
|   tuple ids: 2 |
| |
| PLAN FRAGMENT 1 |
| PARTITION: RANDOM |
| |
| STREAM DATA SINK |
|   EXCHANGE ID: 5 |
|   UNPARTITIONED |
| |
| 3:AGGREGATE |
|   output: COUNT(*) |
|   cardinality: 1 |
|   per-host memory: 10.00MB |
|   tuple ids: 2 |
| |
| 2:HASH JOIN |
|   join op: INNER JOIN (BROADCAST) |
|   hash predicates: |
|     big.id = medium.id |
|   cardinality: 1443004441 |
|   per-host memory: 839.23MB |
+-----+
```

```

tuple ids: 1 0
----4:EXCHANGE
    cardinality: 200000000
    per-host memory: 0B
    tuple ids: 0

1:SCAN HDFS
    table=join_order.big #partitions=1/1 size=23.12GB
    table stats: 1000000000 rows total
    column stats: all
    cardinality: 1000000000
    per-host memory: 88.00MB
    tuple ids: 1

PLAN FRAGMENT 2
PARTITION: RANDOM

STREAM DATA SINK
EXCHANGE ID: 4
UNPARTITIONED

0:SCAN HDFS
    table=join_order.medium #partitions=1/1 size=4.62GB
    table stats: 200000000 rows total
    column stats: all
    cardinality: 200000000
    per-host memory: 88.00MB
    tuple ids: 0
+-----+
Returned 64 row(s) in 0.04s

```

```

[localhost:21000] > explain select count(*) from small join big where big.id = small.id;
Query: explain select count(*) from small join big where big.id = small.id
+-----+

```

```

| Explain String
+-----+
Estimated Per-Host Requirements: Memory=101.15MB VCoers=2

PLAN FRAGMENT 0
PARTITION: UNPARTITIONED

6:AGGREGATE (merge finalize)
    output: SUM(COUNT(*))
    cardinality: 1
    per-host memory: unavailable
    tuple ids: 2

5:EXCHANGE
    cardinality: 1
    per-host memory: unavailable
    tuple ids: 2

PLAN FRAGMENT 1
PARTITION: RANDOM

STREAM DATA SINK
EXCHANGE ID: 5
UNPARTITIONED

3:AGGREGATE
    output: COUNT(*)
    cardinality: 1
    per-host memory: 10.00MB
    tuple ids: 2

2:HASH JOIN
    join op: INNER JOIN (BROADCAST)
    hash predicates:
        big.id = small.id
    cardinality: 1000000000
    per-host memory: 3.15MB
    tuple ids: 1 0

```

```

    ----4:EXCHANGE
      cardinality: 1000000
      per-host memory: 0B
      tuple ids: 0

1:SCAN HDFS
  table=join_order.big #partitions=1/1 size=23.12GB
  table stats: 1000000000 rows total
  column stats: all
  cardinality: 1000000000
  per-host memory: 88.00MB
  tuple ids: 1

PLAN FRAGMENT 2
PARTITION: RANDOM

STREAM DATA SINK
EXCHANGE ID: 4
UNPARTITIONED

0:SCAN HDFS
  table=join_order.small #partitions=1/1 size=17.93MB
  table stats: 1000000 rows total
  column stats: all
  cardinality: 1000000
  per-host memory: 32.00MB
  tuple ids: 0
+-----+
Returned 64 row(s) in 0.03s

```

When queries like these are actually run, the execution times are relatively consistent regardless of the table order in the query text. Here are examples using both the unique ID column and the VAL column containing duplicate values:

```

[localhost:21000] > select count(*) from big join small on (big.id = small.id);
Query: select count(*) from big join small on (big.id = small.id)
+-----+
| count(*) |
+-----+
| 1000000  |
+-----+
Returned 1 row(s) in 21.68s
[localhost:21000] > select count(*) from small join big on (big.id = small.id);
Query: select count(*) from small join big on (big.id = small.id)
+-----+
| count(*) |
+-----+
| 1000000  |
+-----+
Returned 1 row(s) in 20.45s

[localhost:21000] > select count(*) from big join small on (big.val = small.val);
+-----+
| count(*) |
+-----+
| 2000948962 |
+-----+
Returned 1 row(s) in 108.85s
[localhost:21000] > select count(*) from small join big on (big.val = small.val);
+-----+
| count(*) |
+-----+
| 2000948962 |
+-----+
Returned 1 row(s) in 100.76s

```



Note: When examining the performance of join queries and the effectiveness of the join order optimization, make sure the query involves enough data and cluster resources to see a difference depending on the query plan. For example, a single data file of just a few megabytes will reside in a single HDFS block and be processed on a single node. Likewise, if you use a single-node or two-node cluster, there might not be much difference in efficiency for the broadcast or partitioned join strategies.

Table and Column Statistics

Impala can do better optimization for complex or multi-table queries when it has access to statistics about the volume of data and how the values are distributed. Impala uses this information to help parallelize and distribute the work for a query. For example, optimizing join queries requires a way of determining if one table is “bigger” than another, which is a function of the number of rows and the average row size for each table. The following sections describe the categories of statistics Impala can work with, and how to produce them and keep them up to date.



Note:

Originally, Impala relied on the Hive mechanism for collecting statistics, through the Hive `ANALYZE TABLE` statement which initiates a MapReduce job. For better user-friendliness and reliability, Impala implements its own `COMPUTE STATS` statement in Impala 1.2.2 and higher, along with the `DROP STATS`, `SHOW TABLE STATS`, and `SHOW COLUMN STATS` statements.

Overview of Table Statistics

The Impala query planner can make use of statistics about entire tables and partitions. This information includes physical characteristics such as the number of rows, number of data files, the total size of the data files, and the file format. For partitioned tables, the numbers are calculated per partition, and as totals for the whole table. This metadata is stored in the metastore database, and can be updated by either Impala or Hive. If a number is not available, the value -1 is used as a placeholder. Some numbers, such as number and total sizes of data files, are always kept up to date because they can be calculated cheaply, as part of gathering HDFS block metadata.

The following example shows table stats for an unpartitioned Parquet table. The values for the number and sizes of files are always available. Initially, the number of rows is not known, because it requires a potentially expensive scan through the entire table, and so that value is displayed as -1. The `COMPUTE STATS` statement fills in any unknown table stats values.

```
show table stats parquet_snappy;
+-----+-----+-----+-----+-----+-----+-----+
| #Rows | #Files | Size   | Bytes Cached | Cache Replication | Format | Incremental |
stats | ...
+-----+-----+-----+-----+-----+-----+-----+
| -1    | 96     | 23.35GB | NOT CACHED   | NOT CACHED         | PARQUET | false
| ...
+-----+-----+-----+-----+-----+-----+-----+

compute stats parquet_snappy;
+-----+-----+
| summary |
+-----+-----+
| Updated 1 partition(s) and 6 column(s). |
+-----+-----+

show table stats parquet_snappy;
+-----+-----+-----+-----+-----+-----+-----+
| #Rows   | #Files | Size   | Bytes Cached | Cache Replication | Format | Incremental |
stats | ...
+-----+-----+-----+-----+-----+-----+-----+
| 1000000000 | 96     | 23.35GB | NOT CACHED   | NOT CACHED         | PARQUET | false
```

```

+-----+-----+-----+-----+-----+-----+-----+-----+
|...

```

Impala performs some optimizations using this metadata on its own, and other optimizations by using a combination of table and column statistics.

To check that table statistics are available for a table, and see the details of those statistics, use the statement `SHOW TABLE STATS table_name`. See [SHOW Statement](#) on page 356 for details.

If you use the Hive-based methods of gathering statistics, see [the Hive wiki](#) for information about the required configuration on the Hive side. Cloudera recommends using the Impala `COMPUTE STATS` statement to avoid potential configuration and scalability issues with the statistics-gathering process.

If you run the Hive statement `ANALYZE TABLE COMPUTE STATISTICS FOR COLUMNS`, Impala can only use the resulting column statistics if the table is unpartitioned. Impala cannot use Hive-generated column statistics for a partitioned table.

Overview of Column Statistics

The Impala query planner can make use of statistics about individual columns when that metadata is available in the metastore database. This technique is most valuable for columns compared across tables in [join queries](#), to help estimate how many rows the query will retrieve from each table. These statistics are also important for correlated subqueries using the `EXISTS()` or `IN()` operators, which are processed internally the same way as join queries.

The following example shows column stats for an unpartitioned Parquet table. The values for the maximum and average sizes of some types are always available, because those figures are constant for numeric and other fixed-size types. Initially, the number of distinct values is not known, because it requires a potentially expensive scan through the entire table, and so that value is displayed as -1. The same applies to maximum and average sizes of variable-sized types, such as `STRING`. The `COMPUTE STATS` statement fills in most unknown column stats values. (It does not record the number of `NULL` values, because currently Impala does not use that figure for query optimization.)

```

show column stats parquet_snappy;
+-----+-----+-----+-----+-----+-----+
| Column      | Type      | #Distinct Values | #Nulls | Max Size | Avg Size |
+-----+-----+-----+-----+-----+-----+
| id          | BIGINT    | -1                | -1     | 8        | 8        |
| val        | INT       | -1                | -1     | 4        | 4        |
| zerofill    | STRING    | -1                | -1     | -1       | -1       |
| name        | STRING    | -1                | -1     | -1       | -1       |
| assertion   | BOOLEAN   | -1                | -1     | 1        | 1        |
| location_id | SMALLINT  | -1                | -1     | 2        | 2        |
+-----+-----+-----+-----+-----+-----+

compute stats parquet_snappy;
+-----+-----+-----+-----+-----+-----+
| summary
+-----+-----+-----+-----+-----+-----+
| Updated 1 partition(s) and 6 column(s).
+-----+-----+-----+-----+-----+-----+

show column stats parquet_snappy;
+-----+-----+-----+-----+-----+-----+
| Column      | Type      | #Distinct Values | #Nulls | Max Size | Avg Size |
+-----+-----+-----+-----+-----+-----+
| id          | BIGINT    | 183861280         | -1     | 8        | 8        |
| val        | INT       | 139017            | -1     | 4        | 4        |
| zerofill    | STRING    | 101761            | -1     | 6        | 6        |
| name        | STRING    | 145636240         | -1     | 22       | 13.00020027160645 |
| assertion   | BOOLEAN   | 2                 | -1     | 1        | 1        |
| location_id | SMALLINT  | 339               | -1     | 2        | 2        |
+-----+-----+-----+-----+-----+-----+

```

**Note:**

For column statistics to be effective in Impala, you also need to have table statistics for the applicable tables, as described in [Overview of Table Statistics](#) on page 533. When you use the Impala `COMPUTE STATS` statement, both table and column statistics are automatically gathered at the same time, for all columns in the table.

Currently, the `COMPUTE STATS` statement under CDH 4 does not store any statistics for `DECIMAL` columns. When Impala runs under CDH 5, which has better support for `DECIMAL` in the metastore database, `COMPUTE STATS` does collect statistics for `DECIMAL` columns and Impala uses the statistics to optimize query performance.



Note: Prior to Impala 1.4.0, `COMPUTE STATS` counted the number of `NULL` values in each column and recorded that figure in the metastore database. Because Impala does not currently use the `NULL` count during query planning, Impala 1.4.0 and higher speeds up the `COMPUTE STATS` statement by skipping this `NULL` counting.

To check whether column statistics are available for a particular set of columns, use the `SHOW COLUMN STATS table_name` statement, or check the extended `EXPLAIN` output for a query against that table that refers to those columns. See [SHOW Statement](#) on page 356 and [EXPLAIN Statement](#) on page 283 for details.

If you run the Hive statement `ANALYZE TABLE COMPUTE STATISTICS FOR COLUMNS`, Impala can only use the resulting column statistics if the table is unpartitioned. Impala cannot use Hive-generated column statistics for a partitioned table.

How Table and Column Statistics Work for Partitioned Tables

When you use Impala for “big data”, you are highly likely to use partitioning for your biggest tables, the ones representing data that can be logically divided based on dates, geographic regions, or similar criteria. The table and column statistics are especially useful for optimizing queries on such tables. For example, a query involving one year might involve substantially more or less data than a query involving a different year, or a range of several years. Each query might be optimized differently as a result.

The following examples show how table and column stats work with a partitioned table. The table for this example is partitioned by year, month, and day. For simplicity, the sample data consists of 5 partitions, all from the same year and month. Table stats are collected independently for each partition. (In fact, the `SHOW PARTITIONS` statement displays exactly the same information as `SHOW TABLE STATS` for a partitioned table.) Column stats apply to the entire table, not to individual partitions. Because the partition key column values are represented as HDFS directories, their characteristics are typically known in advance, even when the values for non-key columns are shown as -1.

```
show partitions year_month_day;
```

year Format	month	day	#Rows	#Files	Size	Bytes Cached	Cache Replication
2013	12	1	-1	1	2.51MB	NOT CACHED	NOT CACHED
PARQUET	...						
2013	12	2	-1	1	2.53MB	NOT CACHED	NOT CACHED
PARQUET	...						
2013	12	3	-1	1	2.52MB	NOT CACHED	NOT CACHED
PARQUET	...						
2013	12	4	-1	1	2.51MB	NOT CACHED	NOT CACHED
PARQUET	...						
2013	12	5	-1	1	2.52MB	NOT CACHED	NOT CACHED
PARQUET	...						
Total			-1	5	12.58MB	0B	
...	...						

```
show table stats year_month_day;
```

```

+-----+-----+-----+-----+-----+-----+-----+-----+
| year  | month | day  | #Rows | #Files | Size   | Bytes Cached | Cache Replication |
| Format | ...   |      |        |         |        |              |                   |
+-----+-----+-----+-----+-----+-----+-----+-----+
| 2013  | 12    | 1    | -1    | 1      | 2.51MB | NOT CACHED   | NOT CACHED        |
| PARQUET | ...   |      |        |         |        |              |                   |
| 2013  | 12    | 2    | -1    | 1      | 2.53MB | NOT CACHED   | NOT CACHED        |
| PARQUET | ...   |      |        |         |        |              |                   |
| 2013  | 12    | 3    | -1    | 1      | 2.52MB | NOT CACHED   | NOT CACHED        |
| PARQUET | ...   |      |        |         |        |              |                   |
| 2013  | 12    | 4    | -1    | 1      | 2.51MB | NOT CACHED   | NOT CACHED        |
| PARQUET | ...   |      |        |         |        |              |                   |
| 2013  | 12    | 5    | -1    | 1      | 2.52MB | NOT CACHED   | NOT CACHED        |
| PARQUET | ...   |      |        |         |        |              |                   |
| Total  |       |      | -1    | 5      | 12.58MB | 0B           |                   |
| ...   |       |      |        |         |        |              |                   |
+-----+-----+-----+-----+-----+-----+-----+-----+

```

```
show column stats year_month_day;
```

```

+-----+-----+-----+-----+-----+-----+
| Column      | Type      | #Distinct Values | #Nulls | Max Size | Avg Size |
+-----+-----+-----+-----+-----+-----+
| id          | INT       | -1                | -1     | 4        | 4        |
| val         | INT       | -1                | -1     | 4        | 4        |
| zfill       | STRING    | -1                | -1     | -1       | -1       |
| name        | STRING    | -1                | -1     | -1       | -1       |
| assertion   | BOOLEAN   | -1                | -1     | 1        | 1        |
| year        | INT       | 1                 | 0      | 4        | 4        |
| month       | INT       | 1                 | 0      | 4        | 4        |
| day         | INT       | 5                 | 0      | 4        | 4        |
+-----+-----+-----+-----+-----+-----+

```

```
compute stats year_month_day;
```

```

+-----+-----+
| summary |
+-----+-----+
| Updated 5 partition(s) and 5 column(s). |
+-----+-----+

```

```
show table stats year_month_day;
```

```

+-----+-----+-----+-----+-----+-----+-----+-----+
| year  | month | day  | #Rows | #Files | Size   | Bytes Cached | Cache Replication |
| Format | ...   |      |        |         |        |              |                   |
+-----+-----+-----+-----+-----+-----+-----+-----+
| 2013  | 12    | 1    | 93606 | 1      | 2.51MB | NOT CACHED   | NOT CACHED        |
| PARQUET | ...   |      |        |         |        |              |                   |
| 2013  | 12    | 2    | 94158 | 1      | 2.53MB | NOT CACHED   | NOT CACHED        |
| PARQUET | ...   |      |        |         |        |              |                   |
| 2013  | 12    | 3    | 94122 | 1      | 2.52MB | NOT CACHED   | NOT CACHED        |
| PARQUET | ...   |      |        |         |        |              |                   |
| 2013  | 12    | 4    | 93559 | 1      | 2.51MB | NOT CACHED   | NOT CACHED        |
| PARQUET | ...   |      |        |         |        |              |                   |
| 2013  | 12    | 5    | 93845 | 1      | 2.52MB | NOT CACHED   | NOT CACHED        |
| PARQUET | ...   |      |        |         |        |              |                   |
| Total  |       |      | 469290 | 5      | 12.58MB | 0B           |                   |
| ...   |       |      |        |         |        |              |                   |
+-----+-----+-----+-----+-----+-----+-----+-----+

```

```
show column stats year_month_day;
```

```

+-----+-----+-----+-----+-----+-----+
| Column      | Type      | #Distinct Values | #Nulls | Max Size | Avg Size |
+-----+-----+-----+-----+-----+-----+
| id          | INT       | 511129           | -1     | 4        | 4        |
| val         | INT       | 364853           | -1     | 4        | 4        |
| zfill       | STRING    | 311430           | -1     | 6        | 6        |
| name        | STRING    | 471975           | -1     | 22       | 13.00160026550293 |
| assertion   | BOOLEAN   | 2                | -1     | 1        | 1        |
| year        | INT       | 1                 | 0      | 4        | 4        |
| month       | INT       | 1                 | 0      | 4        | 4        |
| day         | INT       | 5                 | 0      | 4        | 4        |
+-----+-----+-----+-----+-----+-----+

```




Note: Partitioned tables can grow so large that scanning the entire table, as the `COMPUTE STATS` statement does, is impractical just to update the statistics for a new partition. The standard `COMPUTE STATS` statement might take hours, or even days. That situation is where you switch to using incremental statistics, a feature available in CDH 5.3 / Impala 2.1 and higher. See [Overview of Incremental Statistics](#) on page 537 for details about this feature and the `COMPUTE INCREMENTAL STATS` syntax.

If you run the Hive statement `ANALYZE TABLE COMPUTE STATISTICS FOR COLUMNS`, Impala can only use the resulting column statistics if the table is unpartitioned. Impala cannot use Hive-generated column statistics for a partitioned table.

Overview of Incremental Statistics

In Impala 2.1.0 and higher, you can use the syntax `COMPUTE INCREMENTAL STATS` and `DROP INCREMENTAL STATS`. The `INCREMENTAL` clauses work with incremental statistics, a specialized feature for partitioned tables that are large or frequently updated with new partitions.

When you compute incremental statistics for a partitioned table, by default Impala only processes those partitions that do not yet have incremental statistics. By processing only newly added partitions, you can keep statistics up to date for large partitioned tables, without incurring the overhead of reprocessing the entire table each time.

You can also compute or drop statistics for a single partition by including a `PARTITION` clause in the `COMPUTE INCREMENTAL STATS` or `DROP INCREMENTAL STATS` statement.

The metadata for incremental statistics is handled differently from the original style of statistics:

- If you have an existing partitioned table for which you have already computed statistics, issuing `COMPUTE INCREMENTAL STATS` without a partition clause causes Impala to rescan the entire table. Once the incremental statistics are computed, any future `COMPUTE INCREMENTAL STATS` statements only scan any new partitions and any partitions where you performed `DROP INCREMENTAL STATS`.
- The `SHOW TABLE STATS` and `SHOW PARTITIONS` statements now include an additional column showing whether incremental statistics are available for each column. A partition could already be covered by the original type of statistics based on a prior `COMPUTE STATS` statement, as indicated by a value other than `-1` under the `#Rows` column. Impala query planning uses either kind of statistics when available.
- `COMPUTE INCREMENTAL STATS` takes more time than `COMPUTE STATS` for the same volume of data. Therefore it is most suitable for tables with large data volume where new partitions are added frequently, making it impractical to run a full `COMPUTE STATS` operation for each new partition. For unpartitioned tables, or partitioned tables that are loaded once and not updated with new partitions, use the original `COMPUTE STATS` syntax.
- `COMPUTE INCREMENTAL STATS` uses some memory in the `catalogd` process, proportional to the number of partitions and number of columns in the applicable table. The memory overhead is approximately 400 bytes for each column in each partition. This memory is reserved in the `catalogd` daemon, the `statedored` daemon, and in each instance of the `impalad` daemon.
- In cases where new files are added to an existing partition, issue a `REFRESH` statement for the table, followed by a `DROP INCREMENTAL STATS` and `COMPUTE INCREMENTAL STATS` sequence for the changed partition.
- The `DROP INCREMENTAL STATS` statement operates only on a single partition at a time. To remove statistics (whether incremental or not) from all partitions of a table, issue a `DROP STATS` statement with no `INCREMENTAL` or `PARTITION` clauses.

The following considerations apply to incremental statistics when the structure of an existing table is changed (known as *schema evolution*):

- If you use an `ALTER TABLE` statement to drop a column, the existing statistics remain valid and `COMPUTE INCREMENTAL STATS` does not rescan any partitions.

- If you use an `ALTER TABLE` statement to add a column, Impala rescans all partitions and fills in the appropriate column-level values the next time you run `COMPUTE INCREMENTAL STATS`.
- If you use an `ALTER TABLE` statement to change the data type of a column, Impala rescans all partitions and fills in the appropriate column-level values the next time you run `COMPUTE INCREMENTAL STATS`.
- If you use an `ALTER TABLE` statement to change the file format of a table, the existing statistics remain valid and a subsequent `COMPUTE INCREMENTAL STATS` does not rescan any partitions.

See [COMPUTE STATS Statement](#) on page 241 and [DROP STATS Statement](#) on page 277 for syntax details.

Generating Table and Column Statistics (COMPUTE STATS Statement)

To gather table statistics after loading data into a table or partition, you typically use the `COMPUTE STATS` statement. This statement is available in Impala 1.2.2 and higher. It gathers both table statistics and column statistics for all columns in a single operation. For large partitioned tables, where you frequently need to update statistics and it is impractical to scan the entire table each time, use the syntax `COMPUTE INCREMENTAL STATS`, which is available in CDH 5.3 / Impala 2.1 and higher.

If you use Hive as part of your ETL workflow, you can also use Hive to generate table and column statistics. You might need to do extra configuration within Hive itself, the metastore, or even set up a separate database to hold Hive-generated statistics. You might need to run multiple statements to generate all the necessary statistics. Therefore, prefer the Impala `COMPUTE STATS` statement where that technique is practical. For details about collecting statistics through Hive, see [the Hive wiki](#).

If you run the Hive statement `ANALYZE TABLE COMPUTE STATISTICS FOR COLUMNS`, Impala can only use the resulting column statistics if the table is unpartitioned. Impala cannot use Hive-generated column statistics for a partitioned table.

For your very largest tables, you might find that `COMPUTE STATS` or even `COMPUTE INCREMENTAL STATS` take so long to scan the data that it is impractical to use them regularly. In such a case, after adding a partition or inserting new data, you can update just the number of rows property through an `ALTER TABLE` statement. See [Setting the NUMROWS Value Manually through ALTER TABLE](#) on page 540 for details. Because the column statistics might be left in a stale state, do not use this technique as a replacement for `COMPUTE STATS`. Only use this technique if all other means of collecting statistics are impractical, or as a low-overhead operation that you run in between periodic `COMPUTE STATS` or `COMPUTE INCREMENTAL STATS` operations.

Detecting Missing Statistics

You can check whether a specific table has statistics using the `SHOW TABLE STATS` statement (for any table) or the `SHOW PARTITIONS` statement (for a partitioned table). Both statements display the same information. If a table or a partition does not have any statistics, the `#Rows` field contains `-1`. Once you compute statistics for the table or partition, the `#Rows` field changes to an accurate value.

The following example shows a table that initially does not have any statistics. The `SHOW TABLE STATS` statement displays different values for `#Rows` before and after the `COMPUTE STATS` operation.

```
[localhost:21000] > create table no_stats (x int);
[localhost:21000] > show table stats no_stats;
+-----+-----+-----+-----+-----+-----+
| #Rows | #Files | Size | Bytes Cached | Format | Incremental stats |
+-----+-----+-----+-----+-----+-----+
| -1    | 0      | 0B   | NOT CACHED   | TEXT  | false             |
+-----+-----+-----+-----+-----+-----+
[localhost:21000] > compute stats no_stats;
+-----+-----+
| summary |
+-----+-----+
| Updated 1 partition(s) and 1 column(s). |
+-----+-----+
[localhost:21000] > show table stats no_stats;
+-----+-----+-----+-----+-----+-----+
| #Rows | #Files | Size | Bytes Cached | Format | Incremental stats |
+-----+-----+-----+-----+-----+-----+
```

0	0	0B	NOT CACHED	TEXT	false
---	---	----	------------	------	-------

The following example shows a similar progression with a partitioned table. Initially, #Rows is -1. After a `COMPUTE STATS` operation, #Rows changes to an accurate value. Any newly added partition starts with no statistics, meaning that you must collect statistics after adding a new partition.

```
[localhost:21000] > create table no_stats_partitioned (x int) partitioned by (year
smallint);
[localhost:21000] > show table stats no_stats_partitioned;
```

year	#Rows	#Files	Size	Bytes Cached	Format	Incremental stats
Total	-1	0	0B	0B		

```
[localhost:21000] > show partitions no_stats_partitioned;
```

year	#Rows	#Files	Size	Bytes Cached	Format	Incremental stats
Total	-1	0	0B	0B		

```
[localhost:21000] > alter table no_stats_partitioned add partition (year=2013);
[localhost:21000] > compute stats no_stats_partitioned;
```

```
summary
Updated 1 partition(s) and 1 column(s).
```

```
[localhost:21000] > alter table no_stats_partitioned add partition (year=2014);
[localhost:21000] > show partitions no_stats_partitioned;
```

year	#Rows	#Files	Size	Bytes Cached	Format	Incremental stats
2013	0	0	0B	NOT CACHED	TEXT	false
2014	-1	0	0B	NOT CACHED	TEXT	false
Total	0	0	0B	0B		



Note: Because the default `COMPUTE STATS` statement creates and updates statistics for all partitions in a table, if you expect to frequently add new partitions, use the `COMPUTE INCREMENTAL STATS` syntax instead, which lets you compute stats for a single specified partition, or only for those partitions that do not already have incremental stats.

If checking each individual table is impractical, due to a large number of tables or views that hide the underlying base tables, you can also check for missing statistics for a particular query. Use the `EXPLAIN` statement to preview query efficiency before actually running the query. Use the query profile output available through the `PROFILE` command in `impala-shell` or the web UI to verify query execution and timing after running the query. Both the `EXPLAIN` plan and the `PROFILE` output display a warning if any tables or partitions involved in the query do not have statistics.

```
[localhost:21000] > create table no_stats (x int);
[localhost:21000] > explain select count(*) from no_stats;
```

```
Explain String
```

```
Estimated Per-Host Requirements: Memory=10.00MB VCoers=1
WARNING: The following tables are missing relevant table and/or column statistics.
incremental_stats.no_stats
```

```
03:AGGREGATE [FINALIZE]
|   output: count:merge(*)
02:EXCHANGE [UNPARTITIONED]
|
01:AGGREGATE
|   output: count(*)
```

```
00:SCAN HDFS [incremental_stats.no_stats]
    partitions=1/1 files=0 size=0B
```

Because Impala uses the **partition pruning** technique when possible to only evaluate certain partitions, if you have a partitioned table with statistics for some partitions and not others, whether or not the `EXPLAIN` statement shows the warning depends on the actual partitions used by the query. For example, you might see warnings or not for different queries against the same table:

```
-- No warning because all the partitions for the year 2012 have stats.
EXPLAIN SELECT ... FROM t1 WHERE year = 2012;

-- Missing stats warning because one or more partitions in this range
-- do not have stats.
EXPLAIN SELECT ... FROM t1 WHERE year BETWEEN 2006 AND 2009;
```

To confirm if any partitions at all in the table are missing statistics, you might explain a query that scans the entire table, such as `SELECT COUNT(*) FROM table_name`.

Keeping Statistics Up to Date

When the contents of a table or partition change significantly, recompute the stats for the relevant table or partition. The degree of change that qualifies as “significant” varies, depending on the absolute and relative sizes of the tables. Typically, if you add more than 30% more data to a table, it is worthwhile to recompute stats, because the differences in number of rows and number of distinct values might cause Impala to choose a different join order when that table is used in join queries. This guideline is most important for the largest tables. For example, adding 30% new data to a table containing 1 TB has a greater effect on join order than adding 30% to a table containing only a few megabytes, and the larger table has a greater effect on query performance if Impala chooses a suboptimal join order as a result of outdated statistics.

If you reload a complete new set of data for a table, but the number of rows and number of distinct values for each column is relatively unchanged from before, you do not need to recompute stats for the table.

If the statistics for a table are out of date, and the table's large size makes it impractical to recompute new stats immediately, you can use the `DROP STATS` statement to remove the obsolete statistics, making it easier to identify tables that need a new `COMPUTE STATS` operation.

For a large partitioned table, consider using the incremental stats feature available in Impala 2.1.0 and higher, as explained in [Overview of Incremental Statistics](#) on page 537. If you add a new partition to a table, it is worthwhile to recompute incremental stats, because the operation only scans the data for that one new partition.

Setting the NUMROWS Value Manually through ALTER TABLE

The most crucial piece of data in all the statistics is the number of rows in the table (for an unpartitioned or partitioned table) and for each partition (for a partitioned table). The `COMPUTE STATS` statement always gathers statistics about all columns, as well as overall table statistics. If it is not practical to do a full `COMPUTE STATS` or `COMPUTE INCREMENTAL STATS` operation after adding a partition or inserting data, or if you can see that Impala would produce a more efficient plan if the number of rows was different, you can manually set the number of rows through an `ALTER TABLE` statement:

```
-- Set total number of rows. Applies to both unpartitioned and partitioned tables.
alter table table_name set tblproperties('numRows'='new_value',
'STATS_GENERATED_VIA_STATS_TASK'='true');

-- Set total number of rows for a specific partition. Applies to partitioned tables
only.
-- You must specify all the partition key columns in the PARTITION clause.
alter table table_name partition (keycol1=val1,keycol2=val2...) set
tblproperties('numRows'='new_value', 'STATS_GENERATED_VIA_STATS_TASK'='true');
```

This statement avoids re-scanning any data files. (The requirement to include the `STATS_GENERATED_VIA_STATS_TASK` property is relatively new, as a result of the issue [HIVE-8648](#) for the Hive metastore.)

```
create table analysis_data stored as parquet as select * from raw_data;
Inserted 1000000000 rows in 181.98s
compute stats analysis_data;
insert into analysis_data select * from smaller_table_we_forgot_before;
Inserted 1000000 rows in 15.32s
-- Now there are 1001000000 rows. We can update this single data point in the stats.
alter table analysis_data set tblproperties('numRows'='1001000000',
'STATS_GENERATED_VIA_STATS_TASK'='true');
```

For a partitioned table, update both the per-partition number of rows and the number of rows for the whole table:

```
-- If the table originally contained 1 million rows, and we add another partition with
30 thousand rows,
-- change the numRows property for the partition and the overall table.
alter table partitioned_data partition(year=2009, month=4) set tblproperties
('numRows'='30000', 'STATS_GENERATED_VIA_STATS_TASK'='true');
alter table partitioned_data set tblproperties ('numRows'='1030000',
'STATS_GENERATED_VIA_STATS_TASK'='true');
```

In practice, the `COMPUTE STATS` statement, or `COMPUTE INCREMENTAL STATS` for a partitioned table, should be fast and convenient enough that this technique is only useful for the very largest partitioned tables. Because the column statistics might be left in a stale state, do not use this technique as a replacement for `COMPUTE STATS`. Only use this technique if all other means of collecting statistics are impractical, or as a low-overhead operation that you run in between periodic `COMPUTE STATS` or `COMPUTE INCREMENTAL STATS` operations.

Setting Column Stats Manually through ALTER TABLE

In CDH 5.8 / Impala 2.6 and higher, you can also use the `SET COLUMN STATS` clause of `ALTER TABLE` to manually set or change column statistics. Only use this technique in cases where it is impractical to run `COMPUTE STATS` or `COMPUTE INCREMENTAL STATS` frequently enough to keep up with data changes for a huge table.

You specify a case-insensitive symbolic name for the kind of statistics: `numDVs`, `numNulls`, `avgSize`, `maxSize`. The key names and values are both quoted. This operation applies to an entire table, not a specific partition. For example:

```
create table t1 (x int, s string);
insert into t1 values (1, 'one'), (2, 'two'), (2, 'deux');
show column stats t1;
```

Column	Type	#Distinct Values	#Nulls	Max Size	Avg Size
x	INT	-1	-1	4	4
s	STRING	-1	-1	-1	-1

```
alter table t1 set column stats x ('numDVs'='2', 'numNulls'='0');
alter table t1 set column stats s ('numdvs'='3', 'maxsize'='4');
show column stats t1;
```

Column	Type	#Distinct Values	#Nulls	Max Size	Avg Size
x	INT	2	0	4	4
s	STRING	3	-1	4	-1

Examples of Using Table and Column Statistics with Impala

The following examples walk through a sequence of `SHOW TABLE STATS`, `SHOW COLUMN STATS`, `ALTER TABLE`, and `SELECT` and `INSERT` statements to illustrate various aspects of how Impala uses statistics to help optimize queries.

This example shows table and column statistics for the `STORE` column used in the [TPC-DS benchmarks for decision support](#) systems. It is a tiny table holding data for 12 stores. Initially, before any statistics are gathered by a `COMPUTE STATS` statement, most of the numeric fields show placeholder values of -1, indicating that the figures are unknown. The figures that are filled in are values that are easily countable or deducible at the physical level, such as the number

of files, total data size of the files, and the maximum and average sizes for data types that have a constant size such as INT, FLOAT, and TIMESTAMP.

```
[localhost:21000] > show table stats store;
+-----+-----+-----+-----+
| #Rows | #Files | Size   | Format |
+-----+-----+-----+-----+
| -1    | 1      | 3.08KB | TEXT   |
+-----+-----+-----+-----+
Returned 1 row(s) in 0.03s
[localhost:21000] > show column stats store;
+-----+-----+-----+-----+-----+-----+
| Column                | Type          | #Distinct Values | #Nulls | Max Size | Avg Size |
+-----+-----+-----+-----+-----+-----+
| s_store_sk            | INT           | -1                | -1     | 4        | 4        |
| s_store_id            | STRING        | -1                | -1     | -1       | -1       |
| s_rec_start_date      | TIMESTAMP     | -1                | -1     | 16       | 16       |
| s_rec_end_date        | TIMESTAMP     | -1                | -1     | 16       | 16       |
| s_closed_date_sk      | INT           | -1                | -1     | 4        | 4        |
| s_store_name          | STRING        | -1                | -1     | -1       | -1       |
| s_number_employees    | INT           | -1                | -1     | 4        | 4        |
| s_floor_space         | INT           | -1                | -1     | 4        | 4        |
| s_hours               | STRING        | -1                | -1     | -1       | -1       |
| s_manager             | STRING        | -1                | -1     | -1       | -1       |
| s_market_id           | INT           | -1                | -1     | 4        | 4        |
| s_geography_class     | STRING        | -1                | -1     | -1       | -1       |
| s_market_desc         | STRING        | -1                | -1     | -1       | -1       |
| s_market_manager      | STRING        | -1                | -1     | -1       | -1       |
| s_division_id         | INT           | -1                | -1     | 4        | 4        |
| s_division_name       | STRING        | -1                | -1     | -1       | -1       |
| s_company_id          | INT           | -1                | -1     | 4        | 4        |
| s_company_name        | STRING        | -1                | -1     | -1       | -1       |
| s_street_number       | STRING        | -1                | -1     | -1       | -1       |
| s_street_name         | STRING        | -1                | -1     | -1       | -1       |
| s_street_type         | STRING        | -1                | -1     | -1       | -1       |
| s_suite_number        | STRING        | -1                | -1     | -1       | -1       |
| s_city                | STRING        | -1                | -1     | -1       | -1       |
| s_county              | STRING        | -1                | -1     | -1       | -1       |
| s_state               | STRING        | -1                | -1     | -1       | -1       |
| s_zip                 | STRING        | -1                | -1     | -1       | -1       |
| s_country             | STRING        | -1                | -1     | -1       | -1       |
| s_gmt_offset          | FLOAT        | -1                | -1     | 4        | 4        |
| s_tax_percentage      | FLOAT        | -1                | -1     | 4        | 4        |
+-----+-----+-----+-----+-----+-----+
Returned 29 row(s) in 0.04s
```

With the Hive ANALYZE TABLE statement for column statistics, you had to specify each column for which to gather statistics. The Impala COMPUTE STATS statement automatically gathers statistics for all columns, because it reads through the entire table relatively quickly and can efficiently compute the values for all the columns. This example shows how after running the COMPUTE STATS statement, statistics are filled in for both the table and all its columns:

```
[localhost:21000] > compute stats store;
+-----+-----+
| summary |
+-----+-----+
| Updated 1 partition(s) and 29 column(s). |
+-----+-----+
Returned 1 row(s) in 1.88s
[localhost:21000] > show table stats store;
+-----+-----+-----+-----+
| #Rows | #Files | Size   | Format |
+-----+-----+-----+-----+
| 12    | 1      | 3.08KB | TEXT   |
+-----+-----+-----+-----+
Returned 1 row(s) in 0.02s
[localhost:21000] > show column stats store;
+-----+-----+-----+-----+-----+-----+
| Column                | Type          | #Distinct Values | #Nulls | Max Size | Avg Size |
+-----+-----+-----+-----+-----+-----+
| s_store_sk            | INT           | 12                | -1     | 4        | 4        |
+-----+-----+-----+-----+-----+-----+
```

```

| s_store_id          | STRING | 6 | -1 | 16 | 16 |
| s_rec_start_date   | TIMESTAMP | 4 | -1 | 16 | 16 |
| s_rec_end_date     | TIMESTAMP | 3 | -1 | 16 | 16 |
| s_closed_date_sk   | INT | 3 | -1 | 4 | 4 |
| s_store_name       | STRING | 8 | -1 | 5 | 4.25 |
| s_number_employees | INT | 9 | -1 | 4 | 4 |
| s_floor_space      | INT | 10 | -1 | 4 | 4 |
| s_hours            | STRING | 2 | -1 | 8 | |
7.083300113677979 |
| s_manager          | STRING | 7 | -1 | 15 | 12 |
| s_market_id        | INT | 7 | -1 | 4 | 4 |
| s_geography_class  | STRING | 1 | -1 | 7 | 7 |
| s_market_desc      | STRING | 10 | -1 | 94 | 55.5 |
| s_market_manager   | STRING | 7 | -1 | 16 | 14 |
| s_division_id      | INT | 1 | -1 | 4 | 4 |
| s_division_name    | STRING | 1 | -1 | 7 | 7 |
| s_company_id       | INT | 1 | -1 | 4 | 4 |
| s_company_name     | STRING | 1 | -1 | 7 | 7 |
| s_street_number    | STRING | 9 | -1 | 3 | |
2.833300113677979 |
| s_street_name      | STRING | 12 | -1 | 11 | |
6.583300113677979 |
| s_street_type      | STRING | 8 | -1 | 9 | |
4.833300113677979 |
| s_suite_number     | STRING | 11 | -1 | 9 | 8.25 |
| s_city             | STRING | 2 | -1 | 8 | 6.5 |
| s_county           | STRING | 1 | -1 | 17 | 17 |
| s_state            | STRING | 1 | -1 | 2 | 2 |
| s_zip              | STRING | 2 | -1 | 5 | 5 |
| s_country          | STRING | 1 | -1 | 13 | 13 |
| s_gmt_offset       | FLOAT | 1 | -1 | 4 | 4 |
| s_tax_percentage   | FLOAT | 5 | -1 | 4 | 4 |
+-----+-----+-----+-----+-----+
Returned 29 row(s) in 0.04s

```

The following example shows how statistics are represented for a partitioned table. In this case, we have set up a table to hold the world's most trivial census data, a single `STRING` field, partitioned by a `YEAR` column. The table statistics include a separate entry for each partition, plus final totals for the numeric fields. The column statistics include some easily deducible facts for the partitioning column, such as the number of distinct values (the number of partition subdirectories).

```

localhost:21000] > describe census;
+-----+-----+-----+
| name | type | comment |
+-----+-----+-----+
| name | string | |

```

```

| year | smallint |
+-----+-----+
Returned 2 row(s) in 0.02s
[localhost:21000] > show table stats census;
+-----+-----+-----+-----+-----+
| year | #Rows | #Files | Size | Format |
+-----+-----+-----+-----+-----+
| 2000 | -1    | 0      | 0B   | TEXT  |
| 2004 | -1    | 0      | 0B   | TEXT  |
| 2008 | -1    | 0      | 0B   | TEXT  |
| 2010 | -1    | 0      | 0B   | TEXT  |
| 2011 | 0     | 1      | 22B  | TEXT  |
| 2012 | -1    | 1      | 22B  | TEXT  |
| 2013 | -1    | 1      | 231B | PARQUET |
| Total | 0     | 3      | 275B |       |
+-----+-----+-----+-----+-----+
Returned 8 row(s) in 0.02s
[localhost:21000] > show column stats census;
+-----+-----+-----+-----+-----+-----+
| Column | Type      | #Distinct Values | #Nulls | Max Size | Avg Size |
+-----+-----+-----+-----+-----+-----+
| name   | STRING    | -1               | -1     | -1       | -1       |
| year   | SMALLINT  | 7               | -1     | 2        | 2        |
+-----+-----+-----+-----+-----+-----+
Returned 2 row(s) in 0.02s

```

The following example shows how the statistics are filled in by a `COMPUTE STATS` statement in Impala.

```

[localhost:21000] > compute stats census;
+-----+-----+
| summary |
+-----+-----+
| Updated 3 partition(s) and 1 column(s). |
+-----+-----+
Returned 1 row(s) in 2.16s
[localhost:21000] > show table stats census;
+-----+-----+-----+-----+-----+
| year | #Rows | #Files | Size | Format |
+-----+-----+-----+-----+-----+
| 2000 | -1    | 0      | 0B   | TEXT  |
| 2004 | -1    | 0      | 0B   | TEXT  |
| 2008 | -1    | 0      | 0B   | TEXT  |
| 2010 | -1    | 0      | 0B   | TEXT  |
| 2011 | 4     | 1      | 22B  | TEXT  |
| 2012 | 4     | 1      | 22B  | TEXT  |
| 2013 | 1     | 1      | 231B | PARQUET |
| Total | 9     | 3      | 275B |       |
+-----+-----+-----+-----+-----+
Returned 8 row(s) in 0.02s
[localhost:21000] > show column stats census;
+-----+-----+-----+-----+-----+-----+
| Column | Type      | #Distinct Values | #Nulls | Max Size | Avg Size |
+-----+-----+-----+-----+-----+-----+
| name   | STRING    | 4               | -1     | 5        | 4.5      |
| year   | SMALLINT  | 7               | -1     | 2        | 2        |
+-----+-----+-----+-----+-----+-----+
Returned 2 row(s) in 0.02s

```

For examples showing how some queries work differently when statistics are available, see [Examples of Join Order Optimization](#) on page 528. You can see how Impala executes a query differently in each case by observing the `EXPLAIN` output before and after collecting statistics. Measure the before and after query times, and examine the throughput numbers in before and after `SUMMARY` or `PROFILE` output, to verify how much the improved plan speeds up performance.

Benchmarking Impala Queries

Because Impala, like other Hadoop components, is designed to handle large data volumes in a distributed environment, conduct any performance tests using realistic data and cluster configurations. Use a multi-node cluster rather than a

single node; run queries against tables containing terabytes of data rather than tens of gigabytes. The parallel processing techniques used by Impala are most appropriate for workloads that are beyond the capacity of a single server.

When you run queries returning large numbers of rows, the CPU time to pretty-print the output can be substantial, giving an inaccurate measurement of the actual query time. Consider using the `-B` option on the `impala-shell` command to turn off the pretty-printing, and optionally the `-o` option to store query results in a file rather than printing to the screen. See [impala-shell Configuration Options](#) on page 511 for details.

Controlling Impala Resource Usage

Sometimes, balancing raw query performance against scalability requires limiting the amount of resources, such as memory or CPU, used by a single query or group of queries. Impala can use several mechanisms that help to smooth out the load during heavy concurrent usage, resulting in faster overall query times and sharing of resources across Impala queries, MapReduce jobs, and other kinds of workloads across a CDH cluster:

- The Impala admission control feature uses a fast, distributed mechanism to hold back queries that exceed limits on the number of concurrent queries or the amount of memory used. The queries are queued, and executed as other queries finish and resources become available. You can control the concurrency limits, and specify different limits for different groups of users to divide cluster resources according to the priorities of different classes of users. This feature is new in Impala 1.3, and works with both CDH 4 and CDH 5. See [Admission Control and Query Queuing](#) on page 77 for details.
- You can restrict the amount of memory Impala reserves during query execution by specifying the `-mem_limit` option for the `impalad` daemon. See [Modifying Impala Startup Options](#) on page 45 for details. This limit applies only to the memory that is directly consumed by queries; Impala reserves additional memory at startup, for example to hold cached metadata.
- For production deployment, Cloudera recommends that you implement resource isolation using mechanisms such as `cgroups`, which you can configure using Cloudera Manager. For details, see the [Static Resource Pools](#) in the Cloudera Manager documentation.

Runtime Filtering for Impala Queries

Runtime filtering is a wide-ranging optimization feature available in CDH 5.7 / Impala 2.5 and higher. When only a fraction of the data in a table is needed for a query against a partitioned table or to evaluate a join condition, Impala determines the appropriate conditions while the query is running, and broadcasts that information to all the `impalad` nodes that are reading the table so that they can avoid unnecessary I/O to read partition data, and avoid unnecessary network transmission by sending only the subset of rows that match the join keys across the network.

This feature is primarily used to optimize queries against large partitioned tables (under the name **dynamic partition pruning**) and joins of large tables. The information in this section includes concepts, internals, and troubleshooting information for the entire runtime filtering feature. For specific tuning steps for partitioned tables, see [Dynamic Partition Pruning](#) on page 571.



Important:

When this feature made its debut in CDH 5.7 / Impala 2.5, the default setting was `RUNTIME_FILTER_MODE=LOCAL`. Now the default is `RUNTIME_FILTER_MODE=GLOBAL` in CDH 5.8 / Impala 2.6 and higher, which enables more wide-ranging and ambitious query optimization without requiring you to explicitly set any query options.

Background Information for Runtime Filtering

To understand how runtime filtering works at a detailed level, you must be familiar with some terminology from the field of distributed database technology:

- What a **plan fragment** is. Impala decomposes each query into smaller units of work that are distributed across the cluster. Wherever possible, a data block is read, filtered, and aggregated by plan fragments executing on the same host. For some operations, such as joins and combining intermediate results into a final result set, data is transmitted across the network from one DataNode to another.
- What `SCAN` and `HASH JOIN` plan nodes are, and their role in computing query results:

In the Impala query plan, a **scan node** performs the I/O to read from the underlying data files. Although this is an expensive operation from the traditional database perspective, Hadoop clusters and Impala are optimized to do this kind of I/O in a highly parallel fashion. The major potential cost savings come from using the columnar Parquet format (where Impala can avoid reading data for unneeded columns) and partitioned tables (where Impala can avoid reading data for unneeded partitions).

Most Impala joins use the **hash join** mechanism. (It is only fairly recently that Impala started using the nested-loop join technique, for certain kinds of non-equijoin queries.) In a hash join, when evaluating join conditions from two tables, Impala constructs a hash table in memory with all the different column values from the table on one side of the join. Then, for each row from the table on the other side of the join, Impala tests whether the relevant column values are in this hash table or not.

A **hash join node** constructs such an in-memory hash table, then performs the comparisons to identify which rows match the relevant join conditions and should be included in the result set (or at least sent on to the subsequent intermediate stage of query processing). Because some of the input for a hash join might be transmitted across the network from another host, it is especially important from a performance perspective to prune out ahead of time any data that is known to be irrelevant.

The more distinct values are in the columns used as join keys, the larger the in-memory hash table and thus the more memory required to process the query.

- The difference between a **broadcast join** and a **shuffle join**. (The Hadoop notion of a shuffle join is sometimes referred to in Impala as a **partitioned join**.) In a broadcast join, the table from one side of the join (typically the smaller table) is sent in its entirety to all the hosts involved in the query. Then each host can compare its portion of the data from the other (larger) table against the full set of possible join keys. In a shuffle join, there is no obvious “smaller” table, and so the contents of both tables are divided up, and corresponding portions of the data are transmitted to each host involved in the query. See [Query Hints in Impala SELECT Statements](#) on page 326 for information about how these different kinds of joins are processed.
- The notion of the build phase and probe phase when Impala processes a join query. The **build phase** is where the rows containing the join key columns, typically for the smaller table, are transmitted across the network and built into an in-memory hash table data structure on one or more destination nodes. The **probe phase** is where data is read locally (typically from the larger table) and the join key columns are compared to the values in the in-memory hash table. The corresponding input sources (tables, subqueries, and so on) for these phases are referred to as the **build side** and the **probe side**.
- How to set Impala query options: interactively within an `impala-shell` session through the `SET` command, for a JDBC or ODBC application through the `SET` statement, or globally for all `impalad` daemons through the `default_query_options` configuration setting.

Runtime Filtering Internals

The **filter** that is transmitted between plan fragments is essentially a list of values for join key columns. When this list of values is transmitted in time to a scan node, Impala can filter out non-matching values immediately after reading them, rather than transmitting the raw data to another host to compare against the in-memory hash table on that host. This data structure is implemented as a **Bloom filter**, which uses a probability-based algorithm to determine all possible matching values. (The probability-based aspects means that the filter might include some non-matching values, but if so, that does not cause any inaccuracy in the final results.)

There are different kinds of filters to match the different kinds of joins (partitioned and broadcast). A broadcast filter is a complete list of relevant values that can be immediately evaluated by a scan node. A partitioned filter is a partial list of relevant values (based on the data processed by one host in the cluster); all the partitioned filters must be

combined into one (by the coordinator node) before the scan nodes can use the results to accurately filter the data as it is read from storage.

Broadcast filters are also classified as local or global. With a local broadcast filter, the information in the filter is used by a subsequent query fragment that is running on the same host that produced the filter. A non-local broadcast filter must be transmitted across the network to a query fragment that is running on a different host. Impala designates 3 hosts to each produce non-local broadcast filters, to guard against the possibility of a single slow host taking too long. Depending on the setting of the `RUNTIME_FILTER_MODE` query option (`LOCAL` or `GLOBAL`), Impala either uses a conservative optimization strategy where filters are only consumed on the same host that produced them, or a more aggressive strategy where filters are eligible to be transmitted across the network.



Note: In CDH 5.8 / Impala 2.6 and higher, the default for runtime filtering is the `GLOBAL` setting.

File Format Considerations for Runtime Filtering

Parquet tables get the most benefit from the runtime filtering optimizations. Runtime filtering can speed up join queries against partitioned or unpartitioned Parquet tables, and single-table queries against partitioned Parquet tables. See [Using the Parquet File Format with Impala Tables](#) on page 584 for information about using Parquet tables with Impala.

For other file formats (text, Avro, RCFile, and SequenceFile), runtime filtering speeds up queries against partitioned tables only. Because partitioned tables can use a mixture of formats, Impala produces the filters in all cases, even if they are not ultimately used to optimize the query.

Wait Intervals for Runtime Filters

Because it takes time to produce runtime filters, especially for partitioned filters that must be combined by the coordinator node, there is a time interval above which it is more efficient for the scan nodes to go ahead and construct their intermediate result sets, even if that intermediate data is larger than optimal. If it only takes a few seconds to produce the filters, it is worth the extra time if pruning the unnecessary data can save minutes in the overall query time. You can specify the maximum wait time in milliseconds using the `RUNTIME_FILTER_WAIT_TIME_MS` query option.

By default, each scan node waits for up to 1 second (1000 milliseconds) for filters to arrive. If all filters have not arrived within the specified interval, the scan node proceeds, using whatever filters did arrive to help avoid reading unnecessary data. If a filter arrives after the scan node begins reading data, the scan node applies that filter to the data that is read after the filter arrives, but not to the data that was already read.

If the cluster is relatively busy and your workload contains many resource-intensive or long-running queries, consider increasing the wait time so that complicated queries do not miss opportunities for optimization. If the cluster is lightly loaded and your workload contains many small queries taking only a few seconds, consider decreasing the wait time to avoid the 1 second delay for each query.

Query Options for Runtime Filtering

See the following sections for information about the query options that control runtime filtering:

- The first query option adjusts the “sensitivity” of this feature. By default, it is set to the highest level (`GLOBAL`). (This default applies to CDH 5.8 / Impala 2.6 and higher. In previous releases, the default was `LOCAL`.)
 - [RUNTIME_FILTER_MODE Query Option \(CDH 5.7 or higher only\)](#) on page 353
- The other query options are tuning knobs that you typically only adjust after doing performance testing, and that you might want to change only for the duration of a single expensive query:
 - [MAX_NUM_RUNTIME_FILTERS Query Option \(CDH 5.7 or higher only\)](#) on page 344
 - [DISABLE_ROW_RUNTIME_FILTERING Query Option \(CDH 5.7 or higher only\)](#) on page 334
 - [RUNTIME_FILTER_MAX_SIZE Query Option \(CDH 5.8 or higher only\)](#) on page 352

- [RUNTIME_FILTER_MIN_SIZE Query Option \(CDH 5.8 or higher only\)](#) on page 353
- [RUNTIME_BLOOM_FILTER_SIZE Query Option \(CDH 5.7 or higher only\)](#) on page 351; in CDH 5.8 / Impala 2.6 and higher, this setting acts as a fallback when statistics are not available, rather than as a directive.

Runtime Filtering and Query Plans

In the same way the query plan displayed by the `EXPLAIN` statement includes information about predicates used by each plan fragment, it also includes annotations showing whether a plan fragment produces or consumes a runtime filter. A plan fragment that produces a filter includes an annotation such as `runtime filters: filter_id <- table.column`, while a plan fragment that consumes a filter includes an annotation such as `runtime filters: filter_id -> table.column`.

The following example shows a query that uses a single runtime filter, labeled `RF000`, to prune the partitions based on evaluating the result set of a subquery at runtime:

```
CREATE TABLE yy (s STRING) PARTITIONED BY (year INT);
INSERT INTO yy PARTITION (year) VALUES ('1999', 1999), ('2000', 2000),
('2001', 2001), ('2010', 2010), ('2018', 2018);
COMPUTE STATS yy;

CREATE TABLE yy2 (s STRING, year INT);
INSERT INTO yy2 VALUES ('1999', 1999), ('2000', 2000), ('2001', 2001);
COMPUTE STATS yy2;

-- The following query reads an unknown number of partitions, whose key values
-- are only known at run time. The runtime filters line shows the
-- information used in query fragment 02 to decide which partitions to skip.

EXPLAIN SELECT s FROM yy WHERE year IN (SELECT year FROM yy2);
```

PLAN-ROOT SINK	
04:EXCHANGE [UNPARTITIONED]	
02:HASH JOIN [LEFT SEMI JOIN, BROADCAST]	
hash predicates: year = year	
runtime filters: RF000 <- year	
--03:EXCHANGE [BROADCAST]	
01:SCAN HDFS [default.yy2]	
partitions=1/1 files=1 size=620B	
00:SCAN HDFS [default.yy]	
partitions=5/5 files=5 size=1.71KB	
runtime filters: RF000 -> year	

```
SELECT s FROM yy WHERE year IN (SELECT year FROM yy2); -- Returns 3 rows from yy
PROFILE;
```

The query profile (displayed by the `PROFILE` command in `impala-shell`) contains both the `EXPLAIN` plan and more detailed information about the internal workings of the query. The profile output includes the `Filter routing table` section with information about each filter based on its ID.

Examples of Queries that Benefit from Runtime Filtering

In this example, Impala would normally do extra work to interpret the columns `C1`, `C2`, `C3`, and `ID` for each row in `HUGE_T1`, before checking the `ID` value against the in-memory hash table constructed from all the `TINY_T2.ID` values. By producing a filter containing all the `TINY_T2.ID` values even before the query starts scanning the `HUGE_T1` table, Impala can skip the unnecessary work to parse the column info as soon as it determines that an `ID` value does not match any of the values from the other table.

The example shows `COMPUTE STATS` statements for both the tables (even though that is a one-time operation after loading data into those tables) because Impala relies on up-to-date statistics to determine which one has more distinct ID values than the other. That information lets Impala make effective decisions about which table to use to construct the in-memory hash table, and which table to read from disk and compare against the entries in the hash table.

```
COMPUTE STATS huge_t1;
COMPUTE STATS tiny_t2;
SELECT c1, c2, c3 FROM huge_t1 JOIN tiny_t2 WHERE huge_t1.id = tiny_t2.id;
```

In this example, T1 is a table partitioned by year. The subquery on T2 produces multiple values, and transmits those values as a filter to the plan fragments that are reading from T1. Any non-matching partitions in T1 are skipped.

```
select c1 from t1 where year in (select distinct year from t2);
```

Now the `WHERE` clause contains an additional test that does not apply to the partition key column. A filter on a column that is not a partition key is called a per-row filter. Because per-row filters only apply for Parquet, T1 must be a Parquet table.

The subqueries result in two filters being transmitted to the scan nodes that read from T1. The filter on `YEAR` helps the query eliminate entire partitions based on non-matching years. The filter on `C2` lets Impala discard rows with non-matching `C2` values immediately after reading them. Without runtime filtering, Impala would have to keep the non-matching values in memory, assemble `C1`, `C2`, and `C3` into rows in the intermediate result set, and transmit all the intermediate rows back to the coordinator node, where they would be eliminated only at the very end of the query.

```
select c1, c2, c3 from t1
  where year in (select distinct year from t2)
     and c2 in (select other_column from t3);
```

This example involves a broadcast join. The fact that the `ON` clause would return a small number of matching rows (because there are not very many rows in `TINY_T2`) means that the corresponding filter is very selective. Therefore, runtime filtering will probably be effective in optimizing this query.

```
select c1 from huge_t1 join [broadcast] tiny_t2
  on huge_t1.id = tiny_t2.id
  where huge_t1.year in (select distinct year from tiny_t2)
     and c2 in (select other_column from t3);
```

This example involves a shuffle or partitioned join. Assume that most rows in `HUGE_T1` have a corresponding row in `HUGE_T2`. The fact that the `ON` clause could return a large number of matching rows means that the corresponding filter would not be very selective. Therefore, runtime filtering might be less effective in optimizing this query.

```
select c1 from huge_t1 join [shuffle] huge_t2
  on huge_t1.id = huge_t2.id
  where huge_t1.year in (select distinct year from huge_t2)
     and c2 in (select other_column from t3);
```

Tuning and Troubleshooting Queries that Use Runtime Filtering

These tuning and troubleshooting procedures apply to queries that are resource-intensive enough, long-running enough, and frequent enough that you can devote special attention to optimizing them individually.

Use the `EXPLAIN` statement and examine the `runtime filters:` lines to determine whether runtime filters are being applied to the `WHERE` predicates and join clauses that you expect. For example, runtime filtering does not apply to queries that use the nested loop join mechanism due to non-equi-join operators.

Tuning Impala for Performance

Make sure statistics are up-to-date for all tables involved in the queries. Use the `COMPUTE STATS` statement after loading data into non-partitioned tables, and `COMPUTE INCREMENTAL STATS` after adding new partitions to partitioned tables.

If join queries involving large tables use unique columns as the join keys, for example joining a primary key column with a foreign key column, the overhead of producing and transmitting the filter might outweigh the performance benefit because not much data could be pruned during the early stages of the query. For such queries, consider setting the query option `RUNTIME_FILTER_MODE=OFF`.

Limitations and Restrictions for Runtime Filtering

The runtime filtering feature is most effective for the Parquet file formats. For other file formats, filtering only applies for partitioned tables. See [File Format Considerations for Runtime Filtering](#) on page 547.

When the spill-to-disk mechanism is activated on a particular host during a query, that host does not produce any filters while processing that query. This limitation does not affect the correctness of results; it only reduces the amount of optimization that can be applied to the query.

Using HDFS Caching with Impala (CDH 5.1 or higher only)

HDFS caching provides performance and scalability benefits in production environments where Impala queries and other Hadoop jobs operate on quantities of data much larger than the physical RAM on the DataNodes, making it impractical to rely on the Linux OS cache, which only keeps the most recently used data in memory. Data read from the HDFS cache avoids the overhead of checksumming and memory-to-memory copying involved when using data from the Linux OS cache.

**Note:**

On a small or lightly loaded cluster, HDFS caching might not produce any speedup. It might even lead to slower queries, if I/O read operations that were performed in parallel across the entire cluster are replaced by in-memory operations operating on a smaller number of hosts. The hosts where the HDFS blocks are cached can become bottlenecks because they experience high CPU load while processing the cached data blocks, while other hosts remain idle. Therefore, always compare performance with and without this feature enabled, using a realistic workload.

In CDH 5.4 / Impala 2.2 and higher, you can spread the CPU load more evenly by specifying the `WITH REPLICATION` clause of the `CREATE TABLE` and `ALTER TABLE` statements. This clause lets you control the replication factor for HDFS caching for a specific table or partition. By default, each cached block is only present on a single host, which can lead to CPU contention if the same host processes each cached block. Increasing the replication factor lets Impala choose different hosts to process different cached blocks, to better distribute the CPU load. Always use a `WITH REPLICATION` setting of at least 3, and adjust upward if necessary to match the replication factor for the underlying HDFS data files.

In CDH 5.7 / Impala 2.5 and higher, Impala automatically randomizes which host processes a cached HDFS block, to avoid CPU hotspots. For tables where HDFS caching is not applied, Impala designates which host to process a data block using an algorithm that estimates the load on each host. If CPU hotspots still arise during queries, you can enable additional randomization for the scheduling algorithm for non-HDFS cached data by setting the `SCHEDULE_RANDOM_REPLICA` query option.

For background information about how to set up and manage HDFS caching for a CDH cluster, see [the CDH documentation](#).

Overview of HDFS Caching for Impala

On CDH 5.1 and higher, Impala can use the HDFS caching feature to make more effective use of RAM, so that repeated queries can take advantage of data “pinned” in memory regardless of how much data is processed overall. The HDFS caching feature lets you designate a subset of frequently accessed data to be pinned permanently in memory, remaining

in the cache across multiple queries and never being evicted. This technique is suitable for tables or partitions that are frequently accessed and are small enough to fit entirely within the HDFS memory cache. For example, you might designate several dimension tables to be pinned in the cache, to speed up many different join queries that reference them. Or in a partitioned table, you might pin a partition holding data from the most recent time period because that data will be queried intensively; then when the next set of data arrives, you could unpin the previous partition and pin the partition holding the new data.

Because this Impala performance feature relies on HDFS infrastructure, it only applies to Impala tables that use HDFS data files. HDFS caching for Impala does not apply to HBase tables, S3 tables, Kudu tables, or Isilon tables.

Setting Up HDFS Caching for Impala

To use HDFS caching with Impala, first set up that feature for your CDH cluster:

- Decide how much memory to devote to the HDFS cache on each host. Remember that the total memory available for cached data is the sum of the cache sizes on all the hosts. By default, any data block is only cached on one host, although you can cache a block across multiple hosts by increasing the replication factor.
- Issue `hdfs cacheadmin` commands to set up one or more cache pools, owned by the same user as the `impalad` daemon (typically `impala`). For example:

```
hdfs cacheadmin -addPool four_gig_pool -owner impala -limit 4000000000
```

For details about the `hdfs cacheadmin` command, see [the CDH documentation](#).

Once HDFS caching is enabled and one or more pools are available, see [Enabling HDFS Caching for Impala Tables and Partitions](#) on page 551 for how to choose which Impala data to load into the HDFS cache. On the Impala side, you specify the cache pool name defined by the `hdfs cacheadmin` command in the Impala DDL statements that enable HDFS caching for a table or partition, such as `CREATE TABLE ... CACHED IN pool` or `ALTER TABLE ... SET CACHED IN pool`.

Enabling HDFS Caching for Impala Tables and Partitions

Begin by choosing which tables or partitions to cache. For example, these might be lookup tables that are accessed by many different join queries, or partitions corresponding to the most recent time period that are analyzed by different reports or ad hoc queries.

In your SQL statements, you specify logical divisions such as tables and partitions to be cached. Impala translates these requests into HDFS-level directives that apply to particular directories and files. For example, given a partitioned table `CENSUS` with a partition key column `YEAR`, you could choose to cache all or part of the data as follows:

In Impala 2.2 / CDH 5.4 and higher, the optional `WITH REPLICATION` clause for `CREATE TABLE` and `ALTER TABLE` lets you specify a **replication factor**, the number of hosts on which to cache the same data blocks. When Impala processes a cached data block, where the cache replication factor is greater than 1, Impala randomly selects a host that has a cached copy of that data block. This optimization avoids excessive CPU usage on a single host when the same cached data block is processed multiple times. Cloudera recommends specifying a value greater than or equal to the HDFS block replication factor.

```
-- Cache the entire table (all partitions).
alter table census set cached in 'pool_name';

-- Remove the entire table from the cache.
alter table census set uncached;

-- Cache a portion of the table (a single partition).
-- If the table is partitioned by multiple columns (such as year, month, day),
-- the ALTER TABLE command must specify values for all those columns.
alter table census partition (year=1960) set cached in 'pool_name';

-- Cache the data from one partition on up to 4 hosts, to minimize CPU load on any
-- single host when the same data block is processed multiple times.
alter table census partition (year=1970)
  set cached in 'pool_name' with replication = 4;
```

```
-- At each stage, check the volume of cached data.  
-- For large tables or partitions, the background loading might take some time,  
-- so you might have to wait and reissue the statement until all the data  
-- has finished being loaded into the cache.  
show table stats census;
```

year	#Rows	#Files	Size	Bytes Cached	Format
1900	-1	1	11B	NOT CACHED	TEXT
1940	-1	1	11B	NOT CACHED	TEXT
1960	-1	1	11B	11B	TEXT
1970	-1	1	11B	NOT CACHED	TEXT
Total	-1	4	44B	11B	

CREATE TABLE considerations:

The HDFS caching feature affects the Impala `CREATE TABLE` statement as follows:

- You can put a `CACHED IN 'pool_name'` clause and optionally a `WITH REPLICATION = number_of_hosts` clause at the end of a `CREATE TABLE` statement to automatically cache the entire contents of the table, including any partitions added later. The `pool_name` is a pool that you previously set up with the `hdfs cacheadmin` command.
- Once a table is designated for HDFS caching through the `CREATE TABLE` statement, if new partitions are added later through `ALTER TABLE ... ADD PARTITION` statements, the data in those new partitions is automatically cached in the same pool.
- If you want to perform repetitive queries on a subset of data from a large table, and it is not practical to designate the entire table or specific partitions for HDFS caching, you can create a new cached table with just a subset of the data by using `CREATE TABLE ... CACHED IN 'pool_name' AS SELECT ... WHERE ...`. When you are finished with generating reports from this subset of data, drop the table and both the data files and the data cached in RAM are automatically deleted.

See [CREATE TABLE Statement](#) on page 254 for the full syntax.

Other memory considerations:

Certain DDL operations, such as `ALTER TABLE ... SET LOCATION`, are blocked while the underlying HDFS directories contain cached files. You must uncache the files first, before changing the location, dropping the table, and so on.

When data is requested to be pinned in memory, that process happens in the background without blocking access to the data while the caching is in progress. Loading the data from disk could take some time. Impala reads each HDFS data block from memory if it has been pinned already, or from disk if it has not been pinned yet.

The amount of data that you can pin on each node through the HDFS caching mechanism is subject to a quota that is enforced by the underlying HDFS service. Before requesting to pin an Impala table or partition in memory, check that its size does not exceed this quota.



Note: Because the HDFS cache consists of combined memory from all the DataNodes in the cluster, cached tables or partitions can be bigger than the amount of HDFS cache memory on any single host.

Loading and Removing Data with HDFS Caching Enabled

When HDFS caching is enabled, extra processing happens in the background when you add or remove data through statements such as `INSERT` and `DROP TABLE`.

Inserting or loading data:

- When Impala performs an [INSERT](#) or [LOAD DATA](#) statement for a table or partition that is cached, the new data files are automatically cached and Impala recognizes that fact automatically.

- If you perform an `INSERT` or `LOAD DATA` through Hive, as always, Impala only recognizes the new data files after a `REFRESH table_name` statement in Impala.
- If the cache pool is entirely full, or becomes full before all the requested data can be cached, the Impala DDL statement returns an error. This is to avoid situations where only some of the requested data could be cached.
- When HDFS caching is enabled for a table or partition, new data files are cached automatically when they are added to the appropriate directory in HDFS, without the need for a `REFRESH` statement in Impala. Impala automatically performs a `REFRESH` once the new data is loaded into the HDFS cache.

Dropping tables, partitions, or cache pools:

The HDFS caching feature interacts with the Impala [DROP TABLE](#) and [ALTER TABLE ... DROP PARTITION](#) statements as follows:

- When you issue a `DROP TABLE` for a table that is entirely cached, or has some partitions cached, the `DROP TABLE` succeeds and all the cache directives Impala submitted for that table are removed from the HDFS cache system.
- The same applies to `ALTER TABLE ... DROP PARTITION`. The operation succeeds and any cache directives are removed.
- As always, the underlying data files are removed if the dropped table is an internal table, or the dropped partition is in its default location underneath an internal table. The data files are left alone if the dropped table is an external table, or if the dropped partition is in a non-default location.
- If you designated the data files as cached through the `hdfs cacheadmin` command, and the data files are left behind as described in the previous item, the data files remain cached. Impala only removes the cache directives submitted by Impala through the `CREATE TABLE` or `ALTER TABLE` statements. It is OK to have multiple redundant cache directives pertaining to the same files; the directives all have unique IDs and owners so that the system can tell them apart.
- If you drop an HDFS cache pool through the `hdfs cacheadmin` command, all the Impala data files are preserved, just no longer cached. After a subsequent `REFRESH`, `SHOW TABLE STATS` reports 0 bytes cached for each associated Impala table or partition.

Relocating a table or partition:

The HDFS caching feature interacts with the Impala [ALTER TABLE ... SET LOCATION](#) statement as follows:

- If you have designated a table or partition as cached through the `CREATE TABLE` or `ALTER TABLE` statements, subsequent attempts to relocate the table or partition through an `ALTER TABLE ... SET LOCATION` statement will fail. You must issue an `ALTER TABLE ... SET UNCACHED` statement for the table or partition first. Otherwise, Impala would lose track of some cached data files and have no way to uncache them later.

Administration for HDFS Caching with Impala

Here are the guidelines and steps to check or change the status of HDFS caching for Impala data:

hdfs cacheadmin command:

- If you drop a cache pool with the `hdfs cacheadmin` command, Impala queries against the associated data files will still work, by falling back to reading the files from disk. After performing a `REFRESH` on the table, Impala reports the number of bytes cached as 0 for all associated tables and partitions.
- You might use `hdfs cacheadmin` to get a list of existing cache pools, or detailed information about the pools, as follows:

```
hdfs cacheadmin -listDirectives          # Basic info
Found 122 entries
ID POOL      REPL EXPIRY  PATH
123 testPool 1 never  /user/hive/warehouse/tpcds.store_sales
124 testPool 1 never  /user/hive/warehouse/tpcds.store_sales/ss_date=1998-01-15
125 testPool 1 never  /user/hive/warehouse/tpcds.store_sales/ss_date=1998-02-01
...

hdfs cacheadmin -listDirectives -stats # More details
Found 122 entries
ID POOL      REPL EXPIRY  PATH                                     BYTES_NEEDED  BYTES_CACHED  FILES_NEEDED
FILES_CACHED
123 testPool 0         1 never  /user/hive/warehouse/tpcds.store_sales 0             0             0
124 testPool 1         1 never  /user/hive/warehouse/tpcds.store_sales/ss_date=1998-01-15 143169        143169        1
125 testPool 1         1 never  /user/hive/warehouse/tpcds.store_sales/ss_date=1998-02-01 112447        112447        1
...
```

Impala SHOW statement:

- For each table or partition, the `SHOW TABLE STATS` or `SHOW PARTITIONS` statement displays the number of bytes currently cached by the HDFS caching feature. If there are no cache directives in place for that table or partition, the result set displays `NOT CACHED`. A value of 0, or a smaller number than the overall size of the table or partition, indicates that the cache request has been submitted but the data has not been entirely loaded into memory yet. See [SHOW Statement](#) on page 356 for details.

Cloudera Manager:

- You can enable or disable HDFS caching through Cloudera Manager, using the configuration setting **Maximum Memory Used for Caching** for the HDFS service. This control sets the HDFS configuration parameter `dfs_datanode_max_locked_memory`, which specifies the upper limit of HDFS cache size on each node.
- All the other manipulation of the HDFS caching settings, such as what files are cached, is done through the command line, either Impala DDL statements or the Linux `hdfs cacheadmin` command.

Impala memory limits:

The Impala HDFS caching feature interacts with the Impala memory limits as follows:

- The maximum size of each HDFS cache pool is specified externally to Impala, through the `hdfs cacheadmin` command.
- All the memory used for HDFS caching is separate from the `impalad` daemon address space and does not count towards the limits of the `--mem_limit` startup option, `MEM_LIMIT` query option, or further limits imposed through YARN resource management or the Linux `cgroups` mechanism.
- Because accessing HDFS cached data avoids a memory-to-memory copy operation, queries involving cached data require less memory on the Impala side than the equivalent queries on uncached data. In addition to any performance benefits in a single-user environment, the reduced memory helps to improve scalability under high-concurrency workloads.

Performance Considerations for HDFS Caching with Impala

In Impala 1.4.0 and higher, Impala supports efficient reads from data that is pinned in memory through HDFS caching. Impala takes advantage of the HDFS API and reads the data from memory rather than from disk whether the data files are pinned using Impala DDL statements, or using the command-line mechanism where you specify HDFS paths.

When you examine the output of the `impala-shell SUMMARY` command, or look in the metrics report for the `impalad` daemon, you see how many bytes are read from the HDFS cache. For example, this excerpt from a query profile illustrates that all the data read during a particular phase of the query came from the HDFS cache, because the `BytesRead` and `BytesReadDataNodeCache` values are identical.

```
HDFS_SCAN_NODE (id=0):(Total: 11s114ms, non-child: 11s114ms, % non-child: 100.00%)
- AverageHdfsReadThreadConcurrency: 0.00
- AverageScannerThreadConcurrency: 32.75
- BytesRead: 10.47 GB (11240756479)
- BytesReadDataNodeCache: 10.47 GB (11240756479)
- BytesReadLocal: 10.47 GB (11240756479)
- BytesReadShortCircuit: 10.47 GB (11240756479)
- DecompressionTime: 27s572ms
```

For queries involving smaller amounts of data, or in single-user workloads, you might not notice a significant difference in query response time with or without HDFS caching. Even with HDFS caching turned off, the data for the query might still be in the Linux OS buffer cache. The benefits become clearer as data volume increases, and especially as the system processes more concurrent queries. HDFS caching improves the scalability of the overall system. That is, it prevents query performance from declining when the workload outstrips the capacity of the Linux OS cache.

Due to a limitation of HDFS, zero-copy reads are not supported with encryption. Cloudera recommends not using HDFS caching for Impala data files in encryption zones. The queries fall back to the normal read path during query execution, which might cause some performance overhead.

SELECT considerations:

The Impala HDFS caching feature interacts with the [SELECT](#) statement and query performance as follows:

- Impala automatically reads from memory any data that has been designated as cached and actually loaded into the HDFS cache. (It could take some time after the initial request to fully populate the cache for a table with large size or many partitions.) The speedup comes from two aspects: reading from RAM instead of disk, and accessing the data straight from the cache area instead of copying from one RAM area to another. This second aspect yields further performance improvement over the standard OS caching mechanism, which still results in memory-to-memory copying of cached data.
- For small amounts of data, the query speedup might not be noticeable in terms of wall clock time. The performance might be roughly the same with HDFS caching turned on or off, due to recently used data being held in the Linux OS cache. The difference is more pronounced with:
 - Data volumes (for all queries running concurrently) that exceed the size of the Linux OS cache.
 - A busy cluster running many concurrent queries, where the reduction in memory-to-memory copying and overall memory usage during queries results in greater scalability and throughput.
 - Thus, to really exercise and benchmark this feature in a development environment, you might need to simulate realistic workloads and concurrent queries that match your production environment.
 - One way to simulate a heavy workload on a lightly loaded system is to flush the OS buffer cache (on each DataNode) between iterations of queries against the same tables or partitions:

```
$ sync
$ echo 1 > /proc/sys/vm/drop_caches
```

- Impala queries take advantage of HDFS cached data regardless of whether the cache directive was issued by Impala or externally through the `hdfs cacheadmin` command, for example for an external table where the cached data files might be accessed by several different Hadoop components.
- If your query returns a large result set, the time reported for the query could be dominated by the time needed to print the results on the screen. To measure the time for the underlying query processing, query the `COUNT()` of the big result set, which does all the same processing but only prints a single line to the screen.

Testing Impala Performance

Test to ensure that Impala is configured for optimal performance. If you have installed Impala without Cloudera Manager, complete the processes described in this topic to help ensure a proper configuration. Even if you installed Impala with Cloudera Manager, which automatically applies appropriate configurations, these procedures can be used to verify that Impala is set up correctly.

Checking Impala Configuration Values

You can inspect Impala configuration values by connecting to your Impala server using a browser.

To check Impala configuration values:

1. Use a browser to connect to one of the hosts running `impalad` in your environment. Connect using an address of the form `http://hostname:port/varz`.



Note: In the preceding example, replace `hostname` and `port` with the name and port of your Impala server. The default port is 25000.

2. Review the configured values.

For example, to check that your system is configured to use block locality tracking information, you would check that the value for `dfs.datanode.hdfs-blocks-metadata.enabled` is `true`.

To check data locality:

Tuning Impala for Performance

1. Execute a query on a dataset that is available across multiple nodes. For example, for a table named `MyTable` that has a reasonable chance of being spread across multiple `DataNodes`:

```
[impalad-host:21000] > SELECT COUNT (*) FROM MyTable
```

2. After the query completes, review the contents of the Impala logs. You should find a recent message similar to the following:

```
Total remote scan volume = 0
```

The presence of remote scans may indicate `impalad` is not running on the correct nodes. This can be because some `DataNodes` do not have `impalad` running or it can be because the `impalad` instance that is starting the query is unable to contact one or more of the `impalad` instances.

To understand the causes of this issue:

1. Connect to the debugging web server. By default, this server runs on port 25000. This page lists all `impalad` instances running in your cluster. If there are fewer instances than you expect, this often indicates some `DataNodes` are not running `impalad`. Ensure `impalad` is started on all `DataNodes`.
2. If you are using multi-homed hosts, ensure that the Impala daemon's hostname resolves to the interface on which `impalad` is running. The hostname Impala is using is displayed when `impalad` starts. To explicitly set the hostname, use the `--hostname` flag.
3. Check that `statestore` is running as expected. Review the contents of the state store log to ensure all instances of `impalad` are listed as having connected to the state store.

Reviewing Impala Logs

You can review the contents of the Impala logs for signs that short-circuit reads or block location tracking are not functioning. Before checking logs, execute a simple query against a small HDFS dataset. Completing a query task generates log messages using current settings. Information on starting Impala and executing queries can be found in [Starting Impala](#) on page 44 and [Using the Impala Shell \(impala-shell Command\)](#) on page 511. Information on logging can be found in [Using Impala Logging](#) on page 627. Log messages and their interpretations are as follows:

Log Message	Interpretation
Unknown disk id. This will negatively affect performance. Check your hdfs settings to enable block location metadata	Tracking block locality is not enabled.
Unable to load native-hadoop library for your platform... using builtin-java classes where applicable	Native checksumming is not enabled.

Understanding Impala Query Performance - EXPLAIN Plans and Query Profiles

To understand the high-level performance considerations for Impala queries, read the output of the `EXPLAIN` statement for the query. You can get the `EXPLAIN` plan without actually running the query itself.

For an overview of the physical performance characteristics for a query, issue the `SUMMARY` statement in `impala-shell` immediately after executing a query. This condensed information shows which phases of execution took the most time, and how the estimates for memory usage and number of rows at each phase compare to the actual values.

To understand the detailed performance characteristics for a query, issue the `PROFILE` statement in `impala-shell` immediately after executing a query. This low-level information includes physical details about memory, CPU, I/O, and network usage, and thus is only available after the query is actually run.

Also, see [Performance Considerations for the Impala-HBase Integration](#) on page 609 and [Understanding and Tuning Impala Query Performance for S3 Data](#) on page 622 for examples of interpreting `EXPLAIN` plans for queries against HBase tables and data stored in the Amazon Simple Storage System (S3).

Using the EXPLAIN Plan for Performance Tuning

The [EXPLAIN](#) statement gives you an outline of the logical steps that a query will perform, such as how the work will be distributed among the nodes and how intermediate results will be combined to produce the final result set. You can see these details before actually running the query. You can use this information to check that the query will not operate in some very unexpected or inefficient way.

```
[impalad-host:21000] > explain select count(*) from customer_address;
+-----+
| Explain String                                     |
+-----+
| Estimated Per-Host Requirements: Memory=42.00MB VCores=1 |
| 03:AGGREGATE [MERGE FINALIZE]                       |
|   output: sum(count(*))                             |
| 02:EXCHANGE [PARTITION=UNPARTITIONED]              |
| 01:AGGREGATE                                         |
|   output: count(*)                                   |
| 00:SCAN HDFS [default.customer_address]             |
|   partitions=1/1 size=5.25MB                       |
+-----+
```

Read the EXPLAIN plan from bottom to top:

- The last part of the plan shows the low-level details such as the expected amount of data that will be read, where you can judge the effectiveness of your partitioning strategy and estimate how long it will take to scan a table based on total data size and the size of the cluster.
- As you work your way up, next you see the operations that will be parallelized and performed on each Impala node.
- At the higher levels, you see how data flows when intermediate result sets are combined and transmitted from one node to another.
- See [EXPLAIN_LEVEL Query Option](#) on page 336 for details about the `EXPLAIN_LEVEL` query option, which lets you customize how much detail to show in the EXPLAIN plan depending on whether you are doing high-level or low-level tuning, dealing with logical or physical aspects of the query.

The EXPLAIN plan is also printed at the beginning of the query profile report described in [Using the Query Profile for Performance Tuning](#) on page 558, for convenience in examining both the logical and physical aspects of the query side-by-side.

The amount of detail displayed in the EXPLAIN output is controlled by the [EXPLAIN_LEVEL](#) query option. You typically increase this setting from `standard` to `extended` (or from 1 to 2) when doublechecking the presence of table and column statistics during performance tuning, or when estimating query resource usage in conjunction with the resource management features in CDH 5.

Using the SUMMARY Report for Performance Tuning

The [SUMMARY](#) command within the `impala-shell` interpreter gives you an easy-to-digest overview of the timings for the different phases of execution for a query. Like the EXPLAIN plan, it is easy to see potential performance bottlenecks. Like the PROFILE output, it is available after the query is run and so displays actual timing numbers.

The SUMMARY report is also printed at the beginning of the query profile report described in [Using the Query Profile for Performance Tuning](#) on page 558, for convenience in examining high-level and low-level aspects of the query side-by-side.

For example, here is a query involving an aggregate function, on a single-node VM. The different stages of the query and their timings are shown (rolled up for all nodes), along with estimated and actual values used in planning the query. In this case, the `AVG()` function is computed for a subset of data on each node (stage 01) and then the aggregated results from all nodes are combined at the end (stage 03). You can see which stages took the most time, and whether any estimates were substantially different than the actual data distribution. (When examining the time values, be sure

to consider the suffixes such as `us` for microseconds and `ms` for milliseconds, rather than just looking for the largest numbers.)

```
[localhost:21000] > select avg(ss_sales_price) from store_sales where ss_coupon_amt = 0;
+-----+
| avg(ss_sales_price) |
+-----+
| 37.80770926328327  |
+-----+
[localhost:21000] > summary;
+-----+-----+-----+-----+-----+-----+-----+-----+
| Operator          | #Hosts | Avg Time | Max Time | #Rows | Est. #Rows | Peak Mem | Est. |
| Peak Mem | Detail |         |         |       |           |         |     |
+-----+-----+-----+-----+-----+-----+-----+-----+
| 03:AGGREGATE     | 1      | 1.03ms  | 1.03ms  | 1     | 1         | 48.00 KB | -1 B |
|   | MERGE FINALIZE |         |         |       |           |         |     |
| 02:EXCHANGE     | 1      | 0ns     | 0ns     | 1     | 1         | 0 B      | -1 B |
|   | UNPARTITIONED  |         |         |       |           |         |     |
| 01:AGGREGATE     | 1      | 30.79ms | 30.79ms | 1     | 1         | 80.00 KB | 10.00 |
| MB |               |         |         |       |           |         |     |
| 00:SCAN HDFS    | 1      | 5.45s   | 5.45s   | 2.21M | -1        | 64.05 MB | 432.00 |
| MB | tpc.store_sales |         |         |       |           |         |     |
+-----+-----+-----+-----+-----+-----+-----+-----+
```

Notice how the longest initial phase of the query is measured in seconds (s), while later phases working on smaller intermediate results are measured in milliseconds (ms) or even nanoseconds (ns).

Here is an example from a more complicated query, as it would appear in the `PROFILE` output:

```
Operator          #Hosts  Avg Time  Max Time  #Rows  Est. #Rows  Peak Mem  Est.
Peak Mem  Detail
-----
09:MERGING-EXCHANGE 1  79.738us  79.738us  5      5      0
-1.00 B UNPARTITIONED
05:TOP-N           3  84.693us  88.810us  5      5     12.00 KB
120.00 B
04:AGGREGATE       3  5.263ms  6.432ms  5      5     44.00 KB
10.00 MB MERGE FINALIZE
08:AGGREGATE       3  16.659ms  27.444ms  52.52K  600.12K  3.20 MB
15.11 MB MERGE
07:EXCHANGE        3  2.644ms   5.1ms    52.52K  600.12K  0
0 HASH(o_orderpriority)
03:AGGREGATE       3  342.913ms 966.291ms  52.52K  600.12K  10.80 MB
15.11 MB
02:HASH JOIN       3  2s165ms  2s171ms  144.87K  600.12K  13.63 MB
941.01 KB INNER JOIN, BROADCAST
|--06:EXCHANGE     3  8.296ms  8.692ms  57.22K  15.00K  0
0 BROADCAST
| 01:SCAN HDFS     2  1s412ms  1s978ms  57.22K  15.00K  24.21 MB
176.00 MB tpch.orders o
00:SCAN HDFS       3  8s032ms  8s558ms  3.79M  600.12K  32.29 MB
264.00 MB tpch.lineitem l
```

Using the Query Profile for Performance Tuning

The `PROFILE` statement, available in the `impala-shell` interpreter, produces a detailed low-level report showing how the most recent query was executed. Unlike the `EXPLAIN` plan described in [Using the EXPLAIN Plan for Performance Tuning](#) on page 557, this information is only available after the query has finished. It shows physical details such as the number of bytes read, maximum memory usage, and so on for each node. You can use this information to determine if the query is I/O-bound or CPU-bound, whether some network condition is imposing a bottleneck, whether a slowdown is affecting some nodes but not others, and to check that recommended configuration settings such as short-circuit local reads are in effect.

By default, time values in the profile output reflect the wall-clock time taken by an operation. For values denoting system time or user time, the measurement unit is reflected in the metric name, such as `ScannerThreadsSysTime` or `ScannerThreadsUserTime`. For example, a multi-threaded I/O operation might show a small figure for wall-clock

time, while the corresponding system time is larger, representing the sum of the CPU time taken by each thread. Or a wall-clock time figure might be larger because it counts time spent waiting, while the corresponding system and user time figures only measure the time while the operation is actively using CPU cycles.

The [EXPLAIN plan](#) is also printed at the beginning of the query profile report, for convenience in examining both the logical and physical aspects of the query side-by-side. The [EXPLAIN_LEVEL](#) query option also controls the verbosity of the `EXPLAIN` output printed by the `PROFILE` command.

See [Query Details](#) for the steps to download the query profile in the text format in Cloudera Manager.

Detecting and Correcting HDFS Block Skew Conditions

For best performance of Impala parallel queries, the work is divided equally across hosts in the cluster, and all hosts take approximately equal time to finish their work. If one host takes substantially longer than others, the extra time needed for the slow host can become the dominant factor in query performance. Therefore, one of the first steps in performance tuning for Impala is to detect and correct such conditions.

The main cause of uneven performance that you can correct within Impala is *skew* in the number of HDFS data blocks processed by each host, where some hosts process substantially more data blocks than others. This condition can occur because of uneven distribution of the data values themselves, for example causing certain data files or partitions to be large while others are very small. (Although it is possible to have unevenly distributed data without any problems with the distribution of HDFS blocks.) Block skew could also be due to the underlying block allocation policies within HDFS, the replication factor of the data files, and the way that Impala chooses the host to process each data block.

The most convenient way to detect block skew, or slow-host issues in general, is to examine the “executive summary” information from the query profile after running a query:

- In `impala-shell`, issue the `SUMMARY` command immediately after the query is complete, to see just the summary information. If you detect issues involving skew, you might switch to issuing the `PROFILE` command, which displays the summary information followed by a detailed performance analysis.
- In the Cloudera Manager interface or the Impala debug web UI, click on the **Profile** link associated with the query after it is complete. The executive summary information is displayed early in the profile output.

For each phase of the query, you see an **Avg Time** and a **Max Time** value, along with **#Hosts** indicating how many hosts are involved in that query phase. For all the phases with **#Hosts** greater than one, look for cases where the maximum time is substantially greater than the average time. Focus on the phases that took the longest, for example, those taking multiple seconds rather than milliseconds or microseconds.

If you detect that some hosts take longer than others, first rule out non-Impala causes. One reason that some hosts could be slower than others is if those hosts have less capacity than the others, or if they are substantially busier due to unevenly distributed non-Impala workloads:

- For clusters running Impala, keep the relative capacities of all hosts roughly equal. Any cost savings from including some underpowered hosts in the cluster will likely be outweighed by poor or uneven performance, and the time spent diagnosing performance issues.
- If non-Impala workloads cause slowdowns on some hosts but not others, use the appropriate load-balancing techniques for the non-Impala components to smooth out the load across the cluster.

If the hosts on your cluster are evenly powered and evenly loaded, examine the detailed profile output to determine which host is taking longer than others for the query phase in question. Examine how many bytes are processed during that phase on that host, how much memory is used, and how many bytes are transmitted across the network.

The most common symptom is a higher number of bytes read on one host than others, due to one host being requested to process a higher number of HDFS data blocks. This condition is more likely to occur when the number of blocks accessed by the query is relatively small. For example, if you have a 10-node cluster and the query processes 10 HDFS blocks, each node might not process exactly one block. If one node sits idle while another node processes two blocks, the query could take twice as long as if the data was perfectly distributed.

Possible solutions in this case include:

- If the query is artificially small, perhaps for benchmarking purposes, scale it up to process a larger data set. For example, if some nodes read 10 HDFS data blocks while others read 11, the overall effect of the uneven distribution is much lower than when some nodes did twice as much work as others. As a guideline, aim for a “sweet spot” where each node reads 2 GB or more from HDFS per query. Queries that process lower volumes than that could experience inconsistent performance that smooths out as queries become more data-intensive.
- If the query processes only a few large blocks, so that many nodes sit idle and cannot help to parallelize the query, consider reducing the overall block size. For example, you might adjust the `PARQUET_FILE_SIZE` query option before copying or converting data into a Parquet table. Or you might adjust the granularity of data files produced earlier in the ETL pipeline by non-Impala components. In Impala 2.0 and later, the default Parquet block size is 256 MB, reduced from 1 GB, to improve parallelism for common cluster sizes and data volumes.
- Reduce the amount of compression applied to the data. For text data files, the highest degree of compression (gzip) produces unsplittable files that are more difficult for Impala to process in parallel, and require extra memory during processing to hold the compressed and uncompressed data simultaneously. For binary formats such as Parquet and Avro, compression can result in fewer data blocks overall, but remember that when queries process relatively few blocks, there is less opportunity for parallel execution and many nodes in the cluster might sit idle. Note that when Impala writes Parquet data with the query option `COMPRESSION_CODEC=NONE` enabled, the data is still typically compact due to the encoding schemes used by Parquet, independent of the final compression step.

Scalability Considerations for Impala

This section explains how the size of your cluster and the volume of data influences SQL performance and schema design for Impala tables. Typically, adding more cluster capacity reduces problems due to memory limits or disk throughput. On the other hand, larger clusters are more likely to have other kinds of scalability issues, such as a single slow node that causes performance problems for queries.

A good source of tips related to scalability and performance tuning is the [Impala Cookbook](#) presentation. These slides are updated periodically as new features come out and new benchmarks are performed.

Impact of Many Tables or Partitions on Impala Catalog Performance and Memory Usage

Because Hadoop I/O is optimized for reading and writing large files, Impala is optimized for tables containing relatively few, large data files. Schemas containing thousands of tables, or tables containing thousands of partitions, can encounter performance issues during startup or during DDL operations such as `ALTER TABLE` statements.



Important:

Because of a change in the default heap size for the `catalogd` daemon in CDH 5.7 / Impala 2.5 and higher, the following procedure to increase the `catalogd` memory limit might be required following an upgrade to CDH 5.7 / Impala 2.5, even if not needed previously.

For schemas with large numbers of tables, partitions, and data files, the `catalogd` daemon might encounter an out-of-memory error. To increase the memory limit for the `catalogd` daemon:

1. Check current memory usage for the `catalogd` daemon by running the following commands on the host where that daemon runs on your cluster:

```

jcmd catalogd_pid VM.flags
jmap -heap catalogd_pid

```

2. Decide on a large enough value for the `catalogd` heap. You express it as an environment variable value as follows:

```

JAVA_TOOL_OPTIONS="-Xmx8g"

```

3. On systems managed by Cloudera Manager, include this value in the configuration field **Java Heap Size of Catalog Server in Bytes** (Cloudera Manager 5.7 and higher), or **Impala Catalog Server Environment Advanced Configuration Snippet (Safety Valve)** (prior to Cloudera Manager 5.7). Then restart the Impala service.
4. On systems not managed by Cloudera Manager, put this environment variable setting into the startup script for the `catalogd` daemon, then restart the `catalogd` daemon.
5. Use the same `jcmd` and `jmap` commands as earlier to verify that the new settings are in effect.

Scalability Considerations for the Impala Statestore

Before CDH 5.3, the statestore sent only one kind of message to its subscribers. This message contained all updates for any topics that a subscriber had subscribed to. It also served to let subscribers know that the statestore had not failed, and conversely the statestore used the success of sending a heartbeat to a subscriber to decide whether or not the subscriber had failed.

Combining topic updates and failure detection in a single message led to bottlenecks in clusters with large numbers of tables, partitions, and HDFS data blocks. When the statestore was overloaded with metadata updates to transmit, heartbeat messages were sent less frequently, sometimes causing subscribers to time out their connection with the statestore. Increasing the subscriber timeout and decreasing the frequency of statestore heartbeats worked around the problem, but reduced responsiveness when the statestore failed or restarted.

As of CDH 5.3, the statestore now sends topic updates and heartbeats in separate messages. This allows the statestore to send and receive a steady stream of lightweight heartbeats, and removes the requirement to send topic updates according to a fixed schedule, reducing statestore network overhead.

The statestore now has the following relevant configuration flags for the `statestored` daemon:

`-statestore_num_update_threads`

The number of threads inside the statestore dedicated to sending topic updates. You should not typically need to change this value.

Default: 10

`-statestore_update_frequency_ms`

The frequency, in milliseconds, with which the statestore tries to send topic updates to each subscriber. This is a best-effort value; if the statestore is unable to meet this frequency, it sends topic updates as fast as it can. You should not typically need to change this value.

Default: 2000

`-statestore_num_heartbeat_threads`

The number of threads inside the statestore dedicated to sending heartbeats. You should not typically need to change this value.

Default: 10

`-statestore_heartbeat_frequency_ms`

The frequency, in milliseconds, with which the statestore tries to send heartbeats to each subscriber. This value should be good for large catalogs and clusters up to approximately 150 nodes. Beyond that, you might need to increase this value to make the interval longer between heartbeat messages.

Default: 1000 (one heartbeat message every second)

As of CDH 5.3, not all of these flags are present in the Cloudera Manager user interface. Some must be set using the **Advanced Configuration Snippet** fields for the statestore component.

If it takes a very long time for a cluster to start up, and `impala-shell` consistently displays `This Impala daemon is not ready to accept user requests`, the statestore might be taking too long to send the entire catalog topic to the cluster. In this case, consider adding `--load_catalog_in_background=false` to your catalog service configuration. This setting stops the statestore from loading the entire catalog into memory at cluster startup. Instead, metadata for each table is loaded when the table is accessed for the first time.

SQL Operations that Spill to Disk

Certain memory-intensive operations write temporary data to disk (known as *spilling* to disk) when Impala is close to exceeding its memory limit on a particular host.

The result is a query that completes successfully, rather than failing with an out-of-memory error. The tradeoff is decreased performance due to the extra disk I/O to write the temporary data and read it back in. The slowdown could be potentially be significant. Thus, while this feature improves reliability, you should optimize your queries, system parameters, and hardware configuration to make this spilling a rare occurrence.

What kinds of queries might spill to disk:

Several SQL clauses and constructs require memory allocations that could activate the spilling mechanism:

- when a query uses a `GROUP BY` clause for columns with millions or billions of distinct values, Impala keeps a similar number of temporary results in memory, to accumulate the aggregate results for each value in the group.
- When large tables are joined together, Impala keeps the values of the join columns from one table in memory, to compare them to incoming values from the other table.
- When a large result set is sorted by the `ORDER BY` clause, each node sorts its portion of the result set in memory.
- The `DISTINCT` and `UNION` operators build in-memory data structures to represent all values found so far, to eliminate duplicates as the query progresses.

When the spill-to-disk feature is activated for a join node within a query, Impala does not produce any runtime filters for that join operation on that host. Other join nodes within the query are not affected.

How Impala handles scratch disk space for spilling:

By default, intermediate files used during large sort, join, aggregation, or analytic function operations are stored in the directory `/tmp/impala-scratch`. These files are removed when the operation finishes. (Multiple concurrent queries can perform operations that use the “spill to disk” technique, without any name conflicts for these temporary files.) You can specify a different location by starting the `impalad` daemon with the

```
--scratch_dirs="path_to_directory"
```

configuration option or the equivalent configuration option in the Cloudera Manager user interface. You can specify a single directory, or a comma-separated list of directories. The scratch directories must be on the local filesystem, not in HDFS. You might specify different directory paths for different hosts, depending on the capacity and speed of the available storage devices. In CDH 5.5 / Impala 2.3 or higher, Impala successfully starts (with a warning written to the log) if it cannot create or read and write files in one of the scratch directories. If there is less than 1 GB free on the filesystem where that directory resides, Impala still runs, but writes a warning message to its log. If Impala encounters an error reading or writing files in a scratch directory during a query, Impala logs the error and the query fails.

Memory usage for SQL operators:

The infrastructure of the spilling feature affects the way the affected SQL operators, such as `GROUP BY`, `DISTINCT`, and joins, use memory. On each host that participates in the query, each such operator in a query accumulates memory while building the data structure to process the aggregation or join operation. The amount of memory used depends on the portion of the data being handled by that host, and thus might be different from one host to another. When the amount of memory being used for the operator on a particular host reaches a threshold amount, Impala reserves an additional memory buffer to use as a work area in case that operator causes the query to exceed the memory limit for that host. After allocating the memory buffer, the memory used by that operator remains essentially stable or grows only slowly, until the point where the memory limit is reached and the query begins writing temporary data to disk.

Prior to Impala 2.2 (CDH 5.4), the extra memory buffer for an operator that might spill to disk was allocated when the data structure used by the applicable SQL operator reaches 16 MB in size, and the memory buffer itself was 512 MB. In Impala 2.2, these values are halved: the threshold value is 8 MB and the memory buffer is 256 MB. In Impala 2.3 / CDH 5.5 and higher, the memory for the buffer is allocated in pieces, only as needed, to avoid sudden large jumps in memory usage. A query that uses multiple such operators might allocate multiple such memory buffers, as the size of the data structure for each operator crosses the threshold on a particular host.

Therefore, a query that processes a relatively small amount of data on each host would likely never reach the threshold for any operator, and would never allocate any extra memory buffers. A query that did process millions of groups, distinct values, join keys, and so on might cross the threshold, causing its memory requirement to rise suddenly and then flatten out. The larger the cluster, less data is processed on any particular host, thus reducing the chance of requiring the extra memory allocation.

Added in: This feature was added to the `ORDER BY` clause in Impala 1.4 for CDH 4, and in CDH 5.1. This feature was extended to cover join queries, aggregation functions, and analytic functions in Impala 2.0 for CDH 4, and in CDH 5.2. The size of the memory work area required by each operator that spills was reduced from 512 megabytes to 256 megabytes in Impala 2.2 (CDH 5.4).

Avoiding queries that spill to disk:

Because the extra I/O can impose significant performance overhead on these types of queries, try to avoid this situation by using the following steps:

1. Detect how often queries spill to disk, and how much temporary data is written. Refer to the following sources:
 - The output of the `PROFILE` command in the `impala-shell` interpreter. This data shows the memory usage for each host and in total across the cluster. The `BlockMgr.BytesWritten` counter reports how much data was written to disk during the query.
 - The **Impala Queries** dialog in Cloudera Manager. You can see the peak memory usage for a query, combined across all nodes in the cluster.
 - The **Queries** tab in the Impala debug web user interface. Select the query to examine and click the corresponding **Profile** link. This data breaks down the memory usage for a single host within the cluster, the host whose web interface you are connected to.
2. Use one or more techniques to reduce the possibility of the queries spilling to disk:
 - Increase the Impala memory limit if practical, for example, if you can increase the available memory by more than the amount of temporary data written to disk on a particular node. Remember that in Impala 2.0 and later, you can issue `SET MEM_LIMIT` as a SQL statement, which lets you fine-tune the memory usage for queries from JDBC and ODBC applications.
 - Increase the number of nodes in the cluster, to increase the aggregate memory available to Impala and reduce the amount of memory required on each node.
 - Increase the overall memory capacity of each DataNode at the hardware level.
 - On a cluster with resources shared between Impala and other Hadoop components, use resource management features to allocate more memory for Impala. See [Resource Management for Impala](#) on page 85 for details.
 - If the memory pressure is due to running many concurrent queries rather than a few memory-intensive ones, consider using the Impala admission control feature to lower the limit on the number of concurrent queries. By spacing out the most resource-intensive queries, you can avoid spikes in memory usage and improve overall response times. See [Admission Control and Query Queuing](#) on page 77 for details.
 - Tune the queries with the highest memory requirements, using one or more of the following techniques:
 - Run the `COMPUTE STATS` statement for all tables involved in large-scale joins and aggregation queries.
 - Minimize your use of `STRING` columns in join columns. Prefer numeric values instead.
 - Examine the `EXPLAIN` plan to understand the execution strategy being used for the most resource-intensive queries. See [Using the EXPLAIN Plan for Performance Tuning](#) on page 557 for details.
 - If Impala still chooses a suboptimal execution strategy even with statistics available, or if it is impractical to keep the statistics up to date for huge or rapidly changing tables, add hints to the most resource-intensive queries to select the right execution strategy. See [Query Hints in Impala SELECT Statements](#) on page 326 for details.
 - If your queries experience substantial performance overhead due to spilling, enable the `DISABLE_UNSAFE_SPILLS` query option. This option prevents queries whose memory usage is likely to be exorbitant from spilling to disk. See [DISABLE_UNSAFE_SPILLS Query Option \(CDH 5.2 or higher only\)](#) on page 335 for details. As you tune problematic queries using the preceding steps, fewer and fewer will be cancelled by this option setting.

Testing performance implications of spilling to disk:

To artificially provoke spilling, to test this feature and understand the performance implications, use a test environment with a memory limit of at least 2 GB. Issue the `SET` command with no arguments to check the current setting for the `MEM_LIMIT` query option. Set the query option `DISABLE_UNSAFE_SPILLS=true`. This option limits the spill-to-disk feature to prevent runaway disk usage from queries that are known in advance to be suboptimal. Within `impala-shell`, run a query that you expect to be memory-intensive, based on the criteria explained earlier. A self-join of a large table is a good candidate:

```
select count(*) from big_table a join big_table b using (column_with_many_values);
```

Issue the `PROFILE` command to get a detailed breakdown of the memory usage on each node during the query. The crucial part of the profile output concerning memory is the `BlockMgr` portion. For example, this profile shows that the query did not quite exceed the memory limit.

```
BlockMgr:
- BlockWritesIssued: 1
- BlockWritesOutstanding: 0
- BlocksCreated: 24
- BlocksRecycled: 1
- BufferedPins: 0
- MaxBlockSize: 8.00 MB (8388608)
- MemoryLimit: 200.00 MB (209715200)
- PeakMemoryUsage: 192.22 MB (201555968)
- TotalBufferWaitTime: 0ns
- TotalEncryptionTime: 0ns
- TotalIntegrityCheckTime: 0ns
- TotalReadBlockTime: 0ns
```

In this case, because the memory limit was already below any recommended value, I increased the volume of data for the query rather than reducing the memory limit any further.

Set the `MEM_LIMIT` query option to a value that is smaller than the peak memory usage reported in the profile output. Do not specify a memory limit lower than about 300 MB, because with such a low limit, queries could fail to start for other reasons. Now try the memory-intensive query again.

Check if the query fails with a message like the following:

```
WARNINGS: Spilling has been disabled for plans that do not have stats and are not hinted
to prevent potentially bad plans from using too many cluster resources. Compute stats
on
these tables, hint the plan or disable this behavior via query options to enable spilling.
```

If so, the query could have consumed substantial temporary disk space, slowing down so much that it would not complete in any reasonable time. Rather than rely on the spill-to-disk feature in this case, issue the `COMPUTE STATS` statement for the table or tables in your sample query. Then run the query again, check the peak memory usage again in the `PROFILE` output, and adjust the memory limit again if necessary to be lower than the peak memory usage.

At this point, you have a query that is memory-intensive, but Impala can optimize it efficiently so that the memory usage is not exorbitant. You have set an artificial constraint through the `MEM_LIMIT` option so that the query would normally fail with an out-of-memory error. But the automatic spill-to-disk feature means that the query should actually succeed, at the expense of some extra disk I/O to read and write temporary work data.

Try the query again, and confirm that it succeeds. Examine the `PROFILE` output again. This time, look for lines of this form:

```
- SpilledPartitions: N
```

If you see any such lines with `N` greater than 0, that indicates the query would have failed in Impala releases prior to 2.0, but now it succeeded because of the spill-to-disk feature. Examine the total time taken by the `AGGREGATION_NODE` or other query fragments containing non-zero `SpilledPartitions` values. Compare the times to similar fragments that did not spill, for example in the `PROFILE` output when the same query is run with a higher memory limit. This gives you an idea of the performance penalty of the spill operation for a particular query with a particular memory limit. If you make the memory limit just a little lower than the peak memory usage, the query only needs to write a small amount of temporary data to disk. The lower you set the memory limit, the more temporary data is written and the slower the query becomes.

Now repeat this procedure for actual queries used in your environment. Use the `DISABLE_UNSAFE_SPILLS` setting to identify cases where queries used more memory than necessary due to lack of statistics on the relevant tables and columns, and issue `COMPUTE STATS` where necessary.

When to use `DISABLE_UNSAFE_SPILLS`:

Scalability Considerations for Impala

You might wonder, why not leave `DISABLE_UNSAFE_SPILLS` turned on all the time. Whether and how frequently to use this option depends on your system environment and workload.

`DISABLE_UNSAFE_SPILLS` is suitable for an environment with ad hoc queries whose performance characteristics and memory usage are not known in advance. It prevents “worst-case scenario” queries that use large amounts of memory unnecessarily. Thus, you might turn this option on within a session while developing new SQL code, even though it is turned off for existing applications.

Organizations where table and column statistics are generally up-to-date might leave this option turned on all the time, again to avoid worst-case scenarios for untested queries or if a problem in the ETL pipeline results in a table with no statistics. Turning on `DISABLE_UNSAFE_SPILLS` lets you “fail fast” in this case and immediately gather statistics or tune the problematic queries.

Some organizations might leave this option turned off. For example, you might have tables large enough that the `COMPUTE STATS` takes substantial time to run, making it impractical to re-run after loading new data. If you have examined the `EXPLAIN` plans of your queries and know that they are operating efficiently, you might leave `DISABLE_UNSAFE_SPILLS` turned off. In that case, you know that any queries that spill will not go overboard with their memory consumption.

Limits on Query Size and Complexity

There are hardcoded limits on the maximum size and complexity of queries. Currently, the maximum number of expressions in a query is 2000. You might exceed the limits with large or deeply nested queries produced by business intelligence tools or other query generators.

If you have the ability to customize such queries or the query generation logic that produces them, replace sequences of repetitive expressions with single operators such as `IN` or `BETWEEN` that can represent multiple values or ranges. For example, instead of a large number of `OR` clauses:

```
WHERE val = 1 OR val = 2 OR val = 6 OR val = 100 ...
```

use a single `IN` clause:

```
WHERE val IN (1,2,6,100,...)
```

Scalability Considerations for Impala I/O

Impala parallelizes its I/O operations aggressively, therefore the more disks you can attach to each host, the better. Impala retrieves data from disk so quickly using bulk read operations on large blocks, that most queries are CPU-bound rather than I/O-bound.

Because the kind of sequential scanning typically done by Impala queries does not benefit much from the random-access capabilities of SSDs, spinning disks typically provide the most cost-effective kind of storage for Impala data, with little or no performance penalty as compared to SSDs.

Resource management features such as YARN, Llama, and admission control typically constrain the amount of memory, CPU, or overall number of queries in a high-concurrency environment. Currently, there is no throttling mechanism for Impala I/O.

Scalability Considerations for Table Layout

Due to the overhead of retrieving and updating table metadata in the metastore database, try to limit the number of columns in a table to a maximum of approximately 2000. Although Impala can handle wider tables than this, the metastore overhead can become significant, leading to query performance that is slower than expected based on the actual data volume.

To minimize overhead related to the metastore database and Impala query planning, try to limit the number of partitions for any partitioned table to a few tens of thousands.

Kerberos-Related Network Overhead for Large Clusters

When Impala starts up, or after each `kinit` refresh, Impala sends a number of simultaneous requests to the KDC. For a cluster with 100 hosts, the KDC might be able to process all the requests within roughly 5 seconds. For a cluster with 1000 hosts, the time to process the requests would be roughly 500 seconds. Impala also makes a number of DNS requests at the same time as these Kerberos-related requests.

While these authentication requests are being processed, any submitted Impala queries will fail, with errors like the following:

```
Query Status: Couldn't open transport for hostname
(SASL(-1): generic failure: GSSAPI Error: Unspecified GSS failure.
Minor code may provide more information
(Cannot contact any KDC for realm 'realm'))
```

During this period, the KDC and DNS may be slow to respond to requests from components other than Impala, so other secure services might be affected temporarily.

If you encounter this problem, consider taking one or more of these actions to address it:

- Scale your KDC implementation to support more load. Contact your KDC provider support to discuss options.
- Initiate the KDC ticket acquisition process after the cluster starts up by issuing a warm-up query. An ideal query is a `SHUFFLE JOIN` between two tables, so that all Impala daemons try to communicate with all others. Repeat the warm-up query until it successfully completes. For example, a 175 node cluster might take approximately 5 minutes.
- To reduce the frequency of the `kinit` renewal that initiates a new set of authentication requests, increase the `kerberos_reinit_interval` configuration setting for the `impalad` daemons. Currently, the default for a cluster not managed by Cloudera Manager is 60 minutes, while the default under Cloudera Manager is 10 minutes. Consider using a higher value such as 360 (6 hours).

Avoiding CPU Hotspots for HDFS Cached Data

You can use the HDFS caching feature, described in [Using HDFS Caching with Impala \(CDH 5.1 or higher only\)](#) on page 550, with Impala to reduce I/O and memory-to-memory copying for frequently accessed tables or partitions.

In the early days of this feature, you might have found that enabling HDFS caching resulted in little or no performance improvement, because it could result in “hotspots”: instead of the I/O to read the table data being parallelized across the cluster, the I/O was reduced but the CPU load to process the data blocks might be concentrated on a single host.

To avoid hotspots, include the `WITH REPLICATION` clause with the `CREATE TABLE` or `ALTER TABLE` statements for tables that use HDFS caching. This clause allows more than one host to cache the relevant data blocks, so the CPU load can be shared, reducing the load on any one host. See [CREATE TABLE Statement](#) on page 254 and [ALTER TABLE Statement](#) on page 230 for details.

Hotspots with high CPU load for HDFS cached data could still arise in some cases, due to the way that Impala schedules the work of processing data blocks on different hosts. In CDH 5.7 / Impala 2.5 and higher, scheduling improvements mean that the work for HDFS cached data is divided better among all the hosts that have cached replicas for a particular data block. When more than one host has a cached replica for a data block, Impala assigns the work of processing that block to whichever host has done the least work (in terms of number of bytes read) for the current query. If hotspots persist even with this load-based scheduling algorithm, you can enable the query option `SCHEDULE_RANDOM_REPLICA=TRUE` to further distribute the CPU load. This setting causes Impala to randomly pick a host to process a cached data block if the scheduling algorithm encounters a tie when deciding which host has done the least work.

Partitioning for Impala Tables

By default, all the data files for a table are located in a single directory. Partitioning is a technique for physically dividing the data during loading, based on values from one or more columns, to speed up queries that test those columns. For example, with a `school_records` table partitioned on a `year` column, there is a separate data directory for each different year value, and all the data for that year is stored in a data file in that directory. A query that includes a `WHERE` condition such as `YEAR=1966`, `YEAR IN (1989,1999)`, or `YEAR BETWEEN 1984 AND 1989` can examine only the data files from the appropriate directory or directories, greatly reducing the amount of data to read and test.

See [Attaching an External Partitioned Table to an HDFS Directory Structure](#) on page 60 for an example that illustrates the syntax for creating partitioned tables, the underlying directory structure in HDFS, and how to attach a partitioned Impala external table to data files stored elsewhere in HDFS.

Parquet is a popular format for partitioned Impala tables because it is well suited to handle huge data volumes. See [Query Performance for Impala Parquet Tables](#) on page 587 for performance considerations for partitioned Parquet tables.

See [NULL](#) on page 198 for details about how `NULL` values are represented in partitioned tables.

See [Using Impala with the Amazon S3 Filesystem](#) on page 617 for details about setting up tables where some or all partitions reside on the Amazon Simple Storage Service (S3).

When to Use Partitioned Tables

Partitioning is typically appropriate for:

- Tables that are very large, where reading the entire data set takes an impractical amount of time.
- Tables that are always or almost always queried with conditions on the partitioning columns. In our example of a table partitioned by year, `SELECT COUNT(*) FROM school_records WHERE year = 1985` is efficient, only examining a small fraction of the data; but `SELECT COUNT(*) FROM school_records` has to process a separate data file for each year, resulting in more overall work than in an unpartitioned table. You would probably not partition this way if you frequently queried the table based on last name, student ID, and so on without testing the year.
- Columns that have reasonable cardinality (number of different values). If a column only has a small number of values, for example `Male` or `Female`, you do not gain much efficiency by eliminating only about 50% of the data to read for each query. If a column has only a few rows matching each value, the number of directories to process can become a limiting factor, and the data file in each directory could be too small to take advantage of the Hadoop mechanism for transmitting data in multi-megabyte blocks. For example, you might partition census data by year, store sales data by year and month, and web traffic data by year, month, and day. (Some users with high volumes of incoming data might even partition down to the individual hour and minute.)
- Data that already passes through an extract, transform, and load (ETL) pipeline. The values of the partitioning columns are stripped from the original data files and represented by directory names, so loading data into a partitioned table involves some sort of transformation or preprocessing.

SQL Statements for Partitioned Tables

In terms of Impala SQL syntax, partitioning affects these statements:

- [CREATE TABLE](#): you specify a `PARTITIONED BY` clause when creating the table to identify names and data types of the partitioning columns. These columns are not included in the main list of columns for the table.
- In CDH 5.7 / Impala 2.5 and higher, you can also use the `PARTITIONED BY` clause in a `CREATE TABLE AS SELECT` statement. This syntax lets you use a single statement to create a partitioned table, copy data into it, and create new partitions based on the values in the inserted data.

- [ALTER TABLE](#): you can add or drop partitions, to work with different portions of a huge data set. You can designate the HDFS directory that holds the data files for a specific partition. With data partitioned by date values, you might “age out” data that is no longer relevant.



Note: If you are creating a partition for the first time and specifying its location, for maximum efficiency, use a single `ALTER TABLE` statement including both the `ADD PARTITION` and `LOCATION` clauses, rather than separate statements with `ADD PARTITION` and `SET LOCATION` clauses.

- [INSERT](#): When you insert data into a partitioned table, you identify the partitioning columns. One or more values from each inserted row are not stored in data files, but instead determine the directory where that row value is stored. You can also specify which partition to load a set of data into, with `INSERT OVERWRITE` statements; you can replace the contents of a specific partition but you cannot append data to a specific partition.

By default, if an `INSERT` statement creates any new subdirectories underneath a partitioned table, those subdirectories are assigned default HDFS permissions for the `impala` user. To make each subdirectory have the same permissions as its parent directory in HDFS, specify the `--insert_inherit_permissions` startup option for the `impalad` daemon.

- Although the syntax of the [SELECT](#) statement is the same whether or not the table is partitioned, the way queries interact with partitioned tables can have a dramatic impact on performance and scalability. The mechanism that lets queries skip certain partitions during a query is known as partition pruning; see [Partition Pruning for Queries](#) on page 570 for details.
- In Impala 1.4 and later, there is a `SHOW PARTITIONS` statement that displays information about each partition in a table. See [SHOW Statement](#) on page 356 for details.

Static and Dynamic Partitioning Clauses

Specifying all the partition columns in a SQL statement is called **static partitioning**, because the statement affects a single predictable partition. For example, you use static partitioning with an `ALTER TABLE` statement that affects only one partition, or with an `INSERT` statement that inserts all values into the same partition:

```
insert into t1 partition(x=10, y='a') select c1 from some_other_table;
```

When you specify some partition key columns in an `INSERT` statement, but leave out the values, Impala determines which partition to insert. This technique is called **dynamic partitioning**:

```
insert into t1 partition(x, y='b') select c1, c2 from some_other_table;
-- Create new partition if necessary based on variable year, month, and day; insert a
single value.
insert into weather partition (year, month, day) select 'cloudy',2014,4,21;
-- Create new partition if necessary for specified year and month but variable day;
insert a single value.
insert into weather partition (year=2014, month=04, day) select 'sunny',22;
```

The more key columns you specify in the `PARTITION` clause, the fewer columns you need in the `SELECT` list. The trailing columns in the `SELECT` list are substituted in order for the partition key columns with no specified value.

Refreshing a Single Partition

The `REFRESH` statement is typically used with partitioned tables when new data files are loaded into a partition by some non-Impala mechanism, such as a Hive or Spark job. The `REFRESH` statement makes Impala aware of the new data files so that they can be used in Impala queries. Because partitioned tables typically contain a high volume of data, the `REFRESH` operation for a full partitioned table can take significant time.

In CDH 5.9 / Impala 2.7 and higher, you can include a `PARTITION (partition_spec)` clause in the `REFRESH` statement so that only a single partition is refreshed. For example, `REFRESH big_table PARTITION (year=2017,`

month=9, day=30). The partition spec must include all the partition key columns. See [REFRESH Statement](#) on page 300 for more details and examples of REFRESH syntax and usage.

Permissions for Partition Subdirectories

By default, if an INSERT statement creates any new subdirectories underneath a partitioned table, those subdirectories are assigned default HDFS permissions for the `impala` user. To make each subdirectory have the same permissions as its parent directory in HDFS, specify the `--insert_inherit_permissions` startup option for the `impalad` daemon.

Partition Pruning for Queries

Partition pruning refers to the mechanism where a query can skip reading the data files corresponding to one or more partitions. If you can arrange for queries to prune large numbers of unnecessary partitions from the query execution plan, the queries use fewer resources and are thus proportionally faster and more scalable.

For example, if a table is partitioned by columns YEAR, MONTH, and DAY, then WHERE clauses such as WHERE year = 2013, WHERE year < 2010, or WHERE year BETWEEN 1995 AND 1998 allow Impala to skip the data files in all partitions outside the specified range. Likewise, WHERE year = 2013 AND month BETWEEN 1 AND 3 could prune even more partitions, reading the data files for only a portion of one year.

Checking if Partition Pruning Happens for a Query

To check the effectiveness of partition pruning for a query, check the EXPLAIN output for the query before running it. For example, this example shows a table with 3 partitions, where the query only reads 1 of them. The notation `#partitions=1/3` in the EXPLAIN plan confirms that Impala can do the appropriate partition pruning.

```
[localhost:21000] > insert into census partition (year=2010) values ('Smith'),('Jones');
[localhost:21000] > insert into census partition (year=2011) values
('Smith'),('Jones'),('Doe');
[localhost:21000] > insert into census partition (year=2012) values ('Smith'),('Doe');
[localhost:21000] > select name from census where year=2010;
+-----+
| name  |
+-----+
| Smith |
| Jones |
+-----+
[localhost:21000] > explain select name from census where year=2010;
+-----+
| Explain String
+-----+
| PLAN FRAGMENT 0
|   PARTITION: UNPARTITIONED
|
|   1:EXCHANGE
|
| PLAN FRAGMENT 1
|   PARTITION: RANDOM
|
|   STREAM DATA SINK
|     EXCHANGE ID: 1
|     UNPARTITIONED
|
|   0:SCAN HDFS
|     table=predicate_propagation.census #partitions=1/3 size=12B
+-----+
```

For a report of the volume of data that was actually read and processed at each stage of the query, check the output of the SUMMARY command immediately after running the query. For a more detailed analysis, look at the output of the PROFILE command; it includes this same summary report near the start of the profile output.

What SQL Constructs Work with Partition Pruning

Impala can even do partition pruning in cases where the partition key column is not directly compared to a constant, by applying the transitive property to other parts of the `WHERE` clause. This technique is known as predicate propagation, and is available in Impala 1.2.2 and later. In this example, the census table includes another column indicating when the data was collected, which happens in 10-year intervals. Even though the query does not compare the partition key column (`YEAR`) to a constant value, Impala can deduce that only the partition `YEAR=2010` is required, and again only reads 1 out of 3 partitions.

```
[localhost:21000] > drop table census;
[localhost:21000] > create table census (name string, census_year int) partitioned by
(year int);
[localhost:21000] > insert into census partition (year=2010) values
('Smith',2010),('Jones',2010);
[localhost:21000] > insert into census partition (year=2011) values
('Smith',2020),('Jones',2020),('Doe',2020);
[localhost:21000] > insert into census partition (year=2012) values
('Smith',2020),('Doe',2020);
[localhost:21000] > select name from census where year = census_year and census_year=2010;
+-----+
| name |
+-----+
| Smith|
| Jones|
+-----+
[localhost:21000] > explain select name from census where year = census_year and
census_year=2010;
+-----+
| Explain String |
+-----+
| PLAN FRAGMENT 0 |
| PARTITION: UNPARTITIONED |
| |
| 1:EXCHANGE |
| |
| PLAN FRAGMENT 1 |
| PARTITION: RANDOM |
| |
| STREAM DATA SINK |
| EXCHANGE ID: 1 |
| UNPARTITIONED |
| |
| 0:SCAN HDFS |
| table=predicate_propagation.census #partitions=1/3 size=22B |
| predicates: census_year = 2010, year = census_year |
+-----+
```

If a view applies to a partitioned table, any partition pruning considers the clauses on both the original query and any additional `WHERE` predicates in the query that refers to the view. Prior to Impala 1.4, only the `WHERE` clauses on the original query from the `CREATE VIEW` statement were used for partition pruning.

In queries involving both analytic functions and partitioned tables, partition pruning only occurs for columns named in the `PARTITION BY` clause of the analytic function call. For example, if an analytic function query has a clause such as `WHERE year=2016`, the way to make the query prune all other `YEAR` partitions is to include `PARTITION BY year` in the analytic function call; for example, `OVER (PARTITION BY year, other_columns other_analytic_clauses)`.

Dynamic Partition Pruning

The original mechanism uses to prune partitions is **static partition pruning**, in which the conditions in the `WHERE` clause are analyzed to determine in advance which partitions can be safely skipped. In Impala 2.5 / CDH 5.7 and higher, Impala can perform **dynamic partition pruning**, where information about the partitions is collected during the query, and Impala prunes unnecessary partitions in ways that were impractical to predict in advance.

Partitioning for Impala Tables

For example, if partition key columns are compared to literal values in a `WHERE` clause, Impala can perform static partition pruning during the planning phase to only read the relevant partitions:

```
-- The query only needs to read 3 partitions whose key values are known ahead of time.
-- That's static partition pruning.
SELECT COUNT(*) FROM sales_table WHERE year IN (2005, 2010, 2015);
```

Dynamic partition pruning involves using information only available at run time, such as the result of a subquery. The following example shows a simple dynamic partition pruning.

```
CREATE TABLE yy (s STRING) PARTITIONED BY (year INT);
INSERT INTO yy PARTITION (year) VALUES ('1999', 1999), ('2000', 2000),
    ('2001', 2001), ('2010', 2010), ('2018', 2018);
COMPUTE STATS yy;

CREATE TABLE yy2 (s STRING, year INT);
INSERT INTO yy2 VALUES ('1999', 1999), ('2000', 2000), ('2001', 2001);
COMPUTE STATS yy2;

-- The following query reads an unknown number of partitions, whose key values
-- are only known at run time. The runtime filters line shows the
-- information used in query fragment 02 to decide which partitions to skip.

EXPLAIN SELECT s FROM yy WHERE year IN (SELECT year FROM yy2);
+-----+
| PLAN-ROOT SINK |
| 04:EXCHANGE [UNPARTITIONED] |
| 02:HASH JOIN [LEFT SEMI JOIN, BROADCAST] |
|   hash predicates: year = year |
|   runtime filters: RF000 <- year |
| --03:EXCHANGE [BROADCAST] |
|   |
|   01:SCAN HDFS [default.yy2] |
|     partitions=1/1 files=1 size=620B |
| 00:SCAN HDFS [default.yy] |
|   partitions=5/5 files=5 size=1.71KB |
|   runtime filters: RF000 -> year |
+-----+

SELECT s FROM yy WHERE year IN (SELECT year FROM yy2); -- Returns 3 rows from yy
PROFILE;
```

In the above example, Impala evaluates the subquery, sends the subquery results to all Impala nodes participating in the query, and then each `impalad` daemon uses the dynamic partition pruning optimization to read only the partitions with the relevant key values.

The output query plan from the `EXPLAIN` statement shows that runtime filters are enabled. The plan also shows that it expects to read all 5 partitions of the `yy` table, indicating that static partition pruning will not happen.

The Filter summary in the `PROFILE` output shows that the scan node filtered out based on a runtime filter of dynamic partition pruning.

```
Filter 0 (1.00 MB):
- Files processed: 3
- Files rejected: 1 (1)
- Files total: 3 (3)
```

Dynamic partition pruning is especially effective for queries involving joins of several large partitioned tables. Evaluating the `ON` clauses of the join predicates might normally require reading data from all partitions of certain tables. If the `WHERE` clauses of the query refer to the partition key columns, Impala can now often skip reading many of the partitions while evaluating the `ON` clauses. The dynamic partition pruning optimization reduces the amount of I/O and the amount of intermediate data stored and transmitted across the network during the query.

When the spill-to-disk feature is activated for a join node within a query, Impala does not produce any runtime filters for that join operation on that host. Other join nodes within the query are not affected.

Dynamic partition pruning is part of the runtime filtering feature, which applies to other kinds of queries in addition to queries against partitioned tables. See [Runtime Filtering for Impala Queries](#) on page 545 for full details about this feature.

Partition Key Columns

The columns you choose as the partition keys should be ones that are frequently used to filter query results in important, large-scale queries. Popular examples are some combination of year, month, and day when the data has associated time values, and geographic region when the data is associated with some place.

- For time-based data, split out the separate parts into their own columns, because Impala cannot partition based on a `TIMESTAMP` column.
- The data type of the partition columns does not have a significant effect on the storage required, because the values from those columns are not stored in the data files, rather they are represented as strings inside HDFS directory names.
- In CDH 5.7 / Impala 2.5 and higher, you can enable the `OPTIMIZE_PARTITION_KEY_SCANS` query option to speed up queries that only refer to partition key columns, such as `SELECT MAX(year)`. This setting is not enabled by default because the query behavior is slightly different if the table contains partition directories without actual data inside. See [OPTIMIZE_PARTITION_KEY_SCANS Query Option \(CDH 5.7 or higher only\)](#) on page 346 for details.
- Partitioned tables can contain complex type columns. All the partition key columns must be scalar types.
- Remember that when Impala queries data stored in HDFS, it is most efficient to use multi-megabyte files to take advantage of the HDFS block size. For Parquet tables, the block size (and ideal size of the data files) is 256 MB in Impala 2.0 and later. Therefore, avoid specifying too many partition key columns, which could result in individual partitions containing only small amounts of data. For example, if you receive 1 GB of data per day, you might partition by year, month, and day; while if you receive 5 GB of data per minute, you might partition by year, month, day, hour, and minute. If you have data with a geographic component, you might partition based on postal code if you have many megabytes of data for each postal code, but if not, you might partition by some larger region such as city, state, or country. state

If you frequently run aggregate functions such as `MIN()`, `MAX()`, and `COUNT(DISTINCT)` on partition key columns, consider enabling the `OPTIMIZE_PARTITION_KEY_SCANS` query option, which optimizes such queries. This feature is available in CDH 5.7 / Impala 2.5 and higher. See [OPTIMIZE_PARTITION_KEY_SCANS Query Option \(CDH 5.7 or higher only\)](#) on page 346 for the kinds of queries that this option applies to, and slight differences in how partitions are evaluated when this query option is enabled.

Setting Different File Formats for Partitions

Partitioned tables have the flexibility to use different file formats for different partitions. (For background information about the different file formats Impala supports, see [How Impala Works with Hadoop File Formats](#) on page 575.) For example, if you originally received data in text format, then received new data in RCFile format, and eventually began receiving data in Parquet format, all that data could reside in the same table for queries. You just need to ensure that the table is structured so that the data files that use different file formats reside in separate partitions.

For example, here is how you might switch from text to Parquet data as you receive data for different years:

```
[localhost:21000] > create table census (name string) partitioned by (year smallint);
[localhost:21000] > alter table census add partition (year=2012); -- Text format;

[localhost:21000] > alter table census add partition (year=2013); -- Text format switches
to Parquet before data loaded;
[localhost:21000] > alter table census partition (year=2013) set fileformat parquet;
```

```
[localhost:21000] > insert into census partition (year=2012) values
('Smith'),('Jones'),('Lee'),('Singh');
[localhost:21000] > insert into census partition (year=2013) values
('Flores'),('Bogomolov'),('Cooper'),('Appiah');
```

At this point, the HDFS directory for `year=2012` contains a text-format data file, while the HDFS directory for `year=2013` contains a Parquet data file. As always, when loading non-trivial data, you would use `INSERT ... SELECT` or `LOAD DATA` to import data in large batches, rather than `INSERT ... VALUES` which produces small files that are inefficient for real-world queries.

For other file types that Impala cannot create natively, you can switch into Hive and issue the `ALTER TABLE ... SET FILEFORMAT` statements and `INSERT` or `LOAD DATA` statements there. After switching back to Impala, issue a `REFRESH table_name` statement so that Impala recognizes any partitions or new data added through Hive.

Managing Partitions

You can add, drop, set the expected file format, or set the HDFS location of the data files for individual partitions within an Impala table. See [ALTER TABLE Statement](#) on page 230 for syntax details, and [Setting Different File Formats for Partitions](#) on page 573 for tips on managing tables containing partitions with different file formats.



Note: If you are creating a partition for the first time and specifying its location, for maximum efficiency, use a single `ALTER TABLE` statement including both the `ADD PARTITION` and `LOCATION` clauses, rather than separate statements with `ADD PARTITION` and `SET LOCATION` clauses.

What happens to the data files when a partition is dropped depends on whether the partitioned table is designated as internal or external. For an internal (managed) table, the data files are deleted. For example, if data in the partitioned table is a copy of raw data files stored elsewhere, you might save disk space by dropping older partitions that are no longer required for reporting, knowing that the original data is still available if needed later. For an external table, the data files are left alone. For example, dropping a partition without deleting the associated files lets Impala consider a smaller set of partitions, improving query efficiency and reducing overhead for DDL operations on the table; if the data is needed again later, you can add the partition again. See [Overview of Impala Tables](#) on page 222 for details and examples.

How Impala Works with Hadoop File Formats

Impala supports several familiar file formats used in Apache Hadoop. Impala can load and query data files produced by other Hadoop components such as Pig or MapReduce, and data files produced by Impala can be used by other components also. The following sections discuss the procedures, limitations, and performance considerations for using each file format with Impala.

The file format used for an Impala table has significant performance consequences. Some file formats include compression support that affects the size of data on the disk and, consequently, the amount of I/O and CPU resources required to deserialize data. The amounts of I/O and CPU resources required can be a limiting factor in query performance since querying often begins with moving and decompressing data. To reduce the potential impact of this part of the process, data is often compressed. By compressing data, a smaller total number of bytes are transferred from disk to memory. This reduces the amount of time taken to transfer the data, but a tradeoff occurs when the CPU decompresses the content.

Impala can query files encoded with most of the popular file formats and compression codecs used in Hadoop. Impala can create and insert data into tables that use some file formats but not others; for file formats that Impala cannot write to, create the table in Hive, issue the `INVALIDATE METADATA table_name` statement in `impala-shell`, and query the table through Impala. File formats can be structured, in which case they may include metadata and built-in compression. Supported formats include:

Table 3: File Format Support in Impala

File Type	Format	Compression Codecs	Impala Can CREATE?	Impala Can INSERT?
Parquet	Structured	Snappy, gzip; currently Snappy by default	Yes.	Yes: CREATE TABLE, INSERT, LOAD DATA, and query.
Text	Unstructured	LZO, gzip, bzip2, Snappy	Yes. For CREATE TABLE with no STORED AS clause, the default file format is uncompressed text, with values separated by ASCII 0x01 characters (typically represented as Ctrl-A).	Yes: CREATE TABLE, INSERT, LOAD DATA, and query. If LZO compression is used, you must create the table and load data in Hive. If other kinds of compression are used, you must load data through LOAD DATA, Hive, or manually in HDFS.
Avro	Structured	Snappy, gzip, deflate, bzip2	Yes, in Impala 1.4.0 and higher. Before that, create the table using Hive.	No. Import data by using LOAD DATA on data files already in the right format, or use INSERT in Hive followed by REFRESH table_name in Impala.
RCFile	Structured	Snappy, gzip, deflate, bzip2	Yes.	No. Import data by using LOAD DATA on data files already in the right format, or use INSERT in Hive followed by REFRESH table_name in Impala.
SequenceFile	Structured	Snappy, gzip, deflate, bzip2	Yes.	No. Import data by using LOAD DATA on data files already in the right format, or use INSERT in Hive followed by REFRESH table_name in Impala.

Impala can only query the file formats listed in the preceding table. In particular, Impala does not support the ORC file format.

Impala supports the following compression codecs:

- Snappy. Recommended for its effective balance between compression ratio and decompression speed. Snappy compression is very fast, but gzip provides greater space savings. Supported for text files in Impala 2.0 and higher.
- Gzip. Recommended when achieving the highest level of compression (and therefore greatest disk-space savings) is desired. Supported for text files in Impala 2.0 and higher.
- Deflate. Not supported for text files.
- Bzip2. Supported for text files in Impala 2.0 and higher.
- LZO, for text files only. Impala can query LZO-compressed text tables, but currently cannot create them or insert data into them; perform these operations in Hive.

Choosing the File Format for a Table

Different file formats and compression codecs work better for different data sets. While Impala typically provides performance gains regardless of file format, choosing the proper format for your data can yield further performance improvements. Use the following considerations to decide which combination of file format and compression to use for a particular table:

- If you are working with existing files that are already in a supported file format, use the same format for the Impala table where practical. If the original format does not yield acceptable query performance or resource usage, consider creating a new Impala table with different file format or compression characteristics, and doing a one-time conversion by copying the data to the new table using the `INSERT` statement. Depending on the file format, you might run the `INSERT` statement in `impala-shell` or in Hive.
- Text files are convenient to produce through many different tools, and are human-readable for ease of verification and debugging. Those characteristics are why text is the default format for an Impala `CREATE TABLE` statement. When performance and resource usage are the primary considerations, use one of the other file formats and consider using compression. A typical workflow might involve bringing data into an Impala table by copying CSV or TSV files into the appropriate data directory, and then using the `INSERT ... SELECT` syntax to copy the data into a table using a different, more compact file format.
- If your architecture involves storing data to be queried in memory, do not compress the data. There is no I/O savings since the data does not need to be moved from disk, but there is a CPU cost to decompress the data.

Using Text Data Files with Impala Tables

Impala supports using text files as the storage format for input and output. Text files are a convenient format to use for interchange with other applications or scripts that produce or read delimited text files, such as CSV or TSV with commas or tabs for delimiters.

Text files are also very flexible in their column definitions. For example, a text file could have more fields than the Impala table, and those extra fields are ignored during queries; or it could have fewer fields than the Impala table, and those missing fields are treated as `NULL` values in queries. You could have fields that were treated as numbers or timestamps in a table, then use `ALTER TABLE ... REPLACE COLUMNS` to switch them to strings, or the reverse.

Table 4: Text Format Support in Impala

File Type	Format	Compression Codecs	Impala Can CREATE?	Impala Can INSERT?
Text	Unstructured	LZO, gzip, bzip2, Snappy	Yes. For <code>CREATE TABLE</code> with no <code>STORED AS</code> clause, the default file format is uncompressed text, with values separated by ASCII <code>0x01</code> characters (typically represented as <code>Ctrl-A</code>).	Yes: <code>CREATE TABLE</code> , <code>INSERT</code> , <code>LOAD DATA</code> , and query. If LZO compression is used, you must create the table and load data in Hive. If other kinds of compression are used, you must load data through <code>LOAD DATA</code> , Hive, or manually in HDFS.

Query Performance for Impala Text Tables

Data stored in text format is relatively bulky, and not as efficient to query as binary formats such as Parquet. You typically use text tables with Impala if that is the format you receive the data and you do not have control over that process, or if you are a relatively new Hadoop user and not familiar with techniques to generate files in other formats. (Because the default format for `CREATE TABLE` is text, you might create your first Impala tables as text without giving performance much thought.) Either way, look for opportunities to use more efficient file formats for the tables used in your most performance-critical queries.

For frequently queried data, you might load the original text data files into one Impala table, then use an `INSERT` statement to transfer the data to another table that uses the Parquet file format; the data is converted automatically as it is stored in the destination table.

For more compact data, consider using LZO compression for the text files. LZO is the only compression codec that Impala supports for text data, because the “splittable” nature of LZO data files lets different nodes work on different parts of the same file in parallel. See [Using LZO-Compressed Text Files](#) on page 580 for details.

In Impala 2.0 and later, you can also use text data compressed in the gzip, bzip2, or Snappy formats. Because these compressed formats are not “splittable” in the way that LZO is, there is less opportunity for Impala to parallelize queries on them. Therefore, use these types of compressed data only for convenience if that is the format in which you receive the data. Prefer to use LZO compression for text data if you have the choice, or convert the data to Parquet using an `INSERT ... SELECT` statement to copy the original data into a Parquet table.



Note:

Impala supports bzip files created by the `bzip2` command, but not bzip files with multiple streams created by the `pbzip2` command. Impala decodes only the data from the first part of such files, leading to incomplete results.

The maximum size that Impala can accommodate for an individual bzip file is 1 GB (after uncompression).

In CDH 5.8 / Impala 2.6 and higher, Impala queries are optimized for files stored in Amazon S3. For Impala tables that use the file formats Parquet, RCFile, SequenceFile, Avro, and uncompressed text, the setting `fs.s3a.block.size` in the `core-site.xml` configuration file determines how Impala divides the I/O work of reading the data files. This configuration setting is specified in bytes. By default, this value is 33554432 (32 MB), meaning that Impala parallelizes S3 read operations on the files as if they were made up of 32 MB blocks. For example, if your S3 queries primarily access Parquet files written by MapReduce or Hive, increase `fs.s3a.block.size` to 134217728 (128 MB) to match the row group size of those files. If most S3 queries involve Parquet files written by Impala, increase `fs.s3a.block.size` to 268435456 (256 MB) to match the row group size produced by Impala.

Creating Text Tables

To create a table using text data files:

If the exact format of the text data files (such as the delimiter character) is not significant, use the `CREATE TABLE` statement with no extra clauses at the end to create a text-format table. For example:

```
create table my_table(id int, s string, n int, t timestamp, b boolean);
```

The data files created by any `INSERT` statements will use the Ctrl-A character (hex 01) as a separator between each column value.

A common use case is to import existing text files into an Impala table. The syntax is more verbose; the significant part is the `FIELDS TERMINATED BY` clause, which must be preceded by the `ROW FORMAT DELIMITED` clause. The statement

How Impala Works with Hadoop File Formats

can end with a `STORED AS TEXTFILE` clause, but that clause is optional because text format tables are the default. For example:

```
create table csv(id int, s string, n int, t timestamp, b boolean)
  row format delimited
  fields terminated by ',';

create table tsv(id int, s string, n int, t timestamp, b boolean)
  row format delimited
  fields terminated by '\t';

create table pipe_separated(id int, s string, n int, t timestamp, b boolean)
  row format delimited
  fields terminated by '|'
  stored as textfile;
```

You can create tables with specific separator characters to import text files in familiar formats such as CSV, TSV, or pipe-separated. You can also use these tables to produce output data files, by copying data into them through the `INSERT ... SELECT` syntax and then extracting the data files from the Impala data directory.

In Impala 1.3.1 and higher, you can specify a delimiter character `'\0'` to use the ASCII 0 (`null`) character for text tables:

```
create table nul_separated(id int, s string, n int, t timestamp, b boolean)
  row format delimited
  fields terminated by '\0'
  stored as textfile;
```



Note:

Do not surround string values with quotation marks in text data files that you construct. If you need to include the separator character inside a field value, for example to put a string value with a comma inside a CSV-format data file, specify an escape character on the `CREATE TABLE` statement with the `ESCAPED BY` clause, and insert that character immediately before any separator characters that need escaping.

Issue a `DESCRIBE FORMATTED table_name` statement to see the details of how each table is represented internally in Impala.

Complex type considerations: Although you can create tables in this file format using the complex types (`ARRAY`, `STRUCT`, and `MAP`) available in CDH 5.5 / Impala 2.3 and higher, currently, Impala can query these types only in Parquet tables. The one exception to the preceding rule is `COUNT(*)` queries on RCFile tables that include complex types. Such queries are allowed in CDH 5.8 / Impala 2.6 and higher.

Data Files for Text Tables

When Impala queries a table with data in text format, it consults all the data files in the data directory for that table, with some exceptions:

- Impala ignores any hidden files, that is, files whose names start with a dot or an underscore.
- Impala queries ignore files with extensions commonly used for temporary work files by Hadoop tools. Any files with extensions `.tmp` or `.copying` are not considered part of the Impala table. The suffix matching is case-insensitive, so for example Impala ignores both `.copying` and `.COPYING` suffixes.
- Impala uses suffixes to recognize when text data files are compressed text. For Impala to recognize the compressed text files, they must have the appropriate file extension corresponding to the compression codec, either `.gz`, `.bz2`, or `.snappy`. The extensions can be in uppercase or lowercase.
- Otherwise, the file names are not significant. When you put files into an HDFS directory through ETL jobs, or point Impala to an existing HDFS directory with the `CREATE EXTERNAL TABLE` statement, or move data files under external control with the `LOAD DATA` statement, Impala preserves the original file names.

File names for data produced through Impala `INSERT` statements are given unique names to avoid file name conflicts.

An `INSERT ... SELECT` statement produces one data file from each node that processes the `SELECT` part of the statement. An `INSERT ... VALUES` statement produces a separate data file for each statement; because Impala is more efficient querying a small number of huge files than a large number of tiny files, the `INSERT ... VALUES` syntax is not recommended for loading a substantial volume of data. If you find yourself with a table that is inefficient due to too many small data files, reorganize the data into a few large files by doing `INSERT ... SELECT` to transfer the data to a new table.

Special values within text data files:

- Impala recognizes the literal strings `inf` for infinity and `nan` for “Not a Number”, for `FLOAT` and `DOUBLE` columns.
- Impala recognizes the literal string `\N` to represent `NULL`. When using Sqoop, specify the options `--null-non-string` and `--null-string` to ensure all `NULL` values are represented correctly in the Sqoop output files. `\N` needs to be escaped as in the below example:

```
--null-string '\\N' --null-non-string '\\N'
```

- By default, Sqoop writes `NULL` values using the string `null`, which causes a conversion error when such rows are evaluated by Impala. A workaround for existing tables and data files is to change the table properties through `ALTER TABLE name SET TBLPROPERTIES("serialization.null.format"="null")`.
- In CDH 5.8 / Impala 2.6 and higher, Impala can optionally skip an arbitrary number of header lines from text input files on HDFS based on the `skip.header.line.count` value in the `TBLPROPERTIES` field of the table metadata. For example:

```
create table header_line(first_name string, age int)
  row format delimited fields terminated by ',';

-- Back in the shell, load data into the table with commands such as:
-- cat >data.csv
-- Name,Age
-- Alice,25
-- Bob,19
-- hdfs dfs -put data.csv /user/hive/warehouse/header_line

refresh header_line;

-- Initially, the Name,Age header line is treated as a row of the table.
select * from header_line limit 10;
+-----+-----+
| first_name | age |
+-----+-----+
| Name       | NULL |
| Alice      | 25   |
| Bob        | 19   |
+-----+-----+

alter table header_line set tblproperties('skip.header.line.count'=1);

-- Once the table property is set, queries skip the specified number of lines
-- at the beginning of each text data file. Therefore, all the files in the table
-- should follow the same convention for header lines.
select * from header_line limit 10;
+-----+-----+
| first_name | age |
+-----+-----+
| Alice      | 25   |
| Bob        | 19   |
+-----+-----+
```

Loading Data into Impala Text Tables

To load an existing text file into an Impala text table, use the `LOAD DATA` statement and specify the path of the file in HDFS. That file is moved into the appropriate Impala data directory.

How Impala Works with Hadoop File Formats

To load multiple existing text files into an Impala text table, use the `LOAD DATA` statement and specify the HDFS path of the directory containing the files. All non-hidden files are moved into the appropriate Impala data directory.

To convert data to text from any other file format supported by Impala, use a SQL statement such as:

```
-- Text table with default delimiter, the hex 01 character.
CREATE TABLE text_table AS SELECT * FROM other_file_format_table;

-- Text table with user-specified delimiter. Currently, you cannot specify
-- the delimiter as part of CREATE TABLE LIKE or CREATE TABLE AS SELECT.
-- But you can change an existing text table to have a different delimiter.
CREATE TABLE csv LIKE other_file_format_table;
ALTER TABLE csv SET SERDEPROPERTIES ('serialization.format'=',', 'field.delim'=',');
INSERT INTO csv SELECT * FROM other_file_format_table;
```

This can be a useful technique to see how Impala represents special values within a text-format data file. Use the `DESCRIBE FORMATTED` statement to see the HDFS directory where the data files are stored, then use Linux commands such as `hdfs dfs -ls hdfs_directory` and `hdfs dfs -cat hdfs_file` to display the contents of an Impala-created text file.

To create a few rows in a text table for test purposes, you can use the `INSERT ... VALUES` syntax:

```
INSERT INTO text_table VALUES ('string_literal',100,hex('hello world'));
```



Note: Because Impala and the HDFS infrastructure are optimized for multi-megabyte files, avoid the `INSERT ... VALUES` notation when you are inserting many rows. Each `INSERT ... VALUES` statement produces a new tiny file, leading to fragmentation and reduced performance. When creating any substantial volume of new data, use one of the bulk loading techniques such as `LOAD DATA` or `INSERT ... SELECT`. Or, [use an HBase table](#) for single-row `INSERT` operations, because HBase tables are not subject to the same fragmentation issues as tables stored on HDFS.

When you create a text file for use with an Impala text table, specify `\N` to represent a `NULL` value. For the differences between `NULL` and empty strings, see [NULL](#) on page 198.

If a text file has fewer fields than the columns in the corresponding Impala table, all the corresponding columns are set to `NULL` when the data in that file is read by an Impala query.

If a text file has more fields than the columns in the corresponding Impala table, the extra fields are ignored when the data in that file is read by an Impala query.

You can also use manual HDFS operations such as `hdfs dfs -put` or `hdfs dfs -cp` to put data files in the data directory for an Impala table. When you copy or move new data files into the HDFS directory for the Impala table, issue a `REFRESH table_name` statement in `impala-shell` before issuing the next query against that table, to make Impala recognize the newly added files.

Using LZO-Compressed Text Files

Impala supports using text data files that employ LZO compression. Cloudera recommends compressing text data files when practical. Impala queries are usually I/O-bound; reducing the amount of data read from disk typically speeds up a query, despite the extra CPU work to uncompress the data in memory.

Impala can work with LZO-compressed text files. LZO-compressed files are preferable to text files compressed by other codecs, because LZO-compressed files are “splittable”, meaning that different portions of a file can be uncompressed and processed independently by different nodes.

Impala does not currently support writing LZO-compressed text files.

Because Impala can query LZO-compressed files but currently cannot write them, you use Hive to do the initial `CREATE TABLE` and load the data, then switch back to Impala to run queries. For instructions on setting up LZO compression for Hive `CREATE TABLE` and `INSERT` statements, see [the LZO page on the Hive wiki](#). Once you have created an LZO text table, you can also manually add LZO-compressed text files to it, produced by the `_lzop` command or similar method.

Preparing to Use LZO-Compressed Text Files

Before using LZO-compressed tables in Impala, do the following one-time setup for each machine in the cluster. Install the necessary packages using either the Cloudera public repository, a private repository you establish, or by using packages. You must do these steps manually, whether or not the cluster is managed by the Cloudera Manager product.

1. Prepare your systems to work with LZO using Cloudera repositories:

On systems managed by Cloudera Manager using parcels:

See the setup instructions for the LZO parcel in the Cloudera Manager documentation for [Cloudera Manager 5](#).

On systems managed by Cloudera Manager using packages, or not managed by Cloudera Manager:

Download and install the appropriate file to each machine on which you intend to use LZO with Impala. These files all come from the Cloudera [GPL extras](#) download site. Install the:

- [Red Hat 5 repo file](#) to `/etc/yum.repos.d/`.
- [Red Hat 6 repo file](#) to `/etc/yum.repos.d/`.
- [SUSE repo file](#) to `/etc/zypp/repos.d/`.
- [Ubuntu 10.04 list file](#) to `/etc/apt/sources.list.d/`.
- [Ubuntu 12.04 list file](#) to `/etc/apt/sources.list.d/`.
- [Debian list file](#) to `/etc/apt/sources.list.d/`.

2. Configure Impala to use LZO:

Use **one** of the following sets of commands to refresh your package management system's repository information, install the base LZO support for Hadoop, and install the LZO support for Impala.

For RHEL/CentOS systems:

```
$ sudo yum update
$ sudo yum install hadoop-lzo
$ sudo yum install impala-lzo
```

For SUSE systems:

```
$ sudo apt-get update
$ sudo zypper install hadoop-lzo
$ sudo zypper install impala-lzo
```

For Debian/Ubuntu systems:

```
$ sudo zypper update
$ sudo apt-get install hadoop-lzo
$ sudo apt-get install impala-lzo
```



Note:

The level of the `impala-lzo` package is closely tied to the version of Impala you use. Any time you upgrade Impala, re-do the installation command for `impala-lzo` on each applicable machine to make sure you have the appropriate version of that package.

3. For `core-site.xml` on the client **and** server (that is, in the configuration directories for both Impala and Hadoop), append `com.hadoop.compression.lzo.LzopCodec` to the comma-separated list of codecs. For example:

```
<property>
  <name>io.compression.codecs</name>
  <value>org.apache.hadoop.io.compress.DefaultCodec,org.apache.hadoop.io.compress.GzipCodec,
```

```
org.apache.hadoop.io.compress.BZip2Codec,org.apache.hadoop.io.compress.DeflateCodec,  
org.apache.hadoop.io.compress.SnappyCodec,com.hadoop.compression.lzo.LzopCodec</value>  
</property>
```



Note:

If this is the first time you have edited the Hadoop `core-site.xml` file, note that the `/etc/hadoop/conf` directory is typically a symbolic link, so the canonical `core-site.xml` might reside in a different directory:

```
$ ls -l /etc/hadoop  
total 8  
lrwxrwxrwx. 1 root root 29 Feb 26 2013 conf ->  
/etc/alternatives/hadoop-conf  
lrwxrwxrwx. 1 root root 10 Feb 26 2013 conf.dist -> conf.empty  
drwxr-xr-x. 2 root root 4096 Feb 26 2013 conf.empty  
drwxr-xr-x. 2 root root 4096 Oct 28 15:46 conf.pseudo
```

If the `io.compression.codecs` property is missing from `core-site.xml`, only add `com.hadoop.compression.lzo.LzopCodec` to the new property value, not all the names from the preceding example.

4. Restart the MapReduce and Impala services.

Creating LZO Compressed Text Tables

A table containing LZO-compressed text files must be created in Hive with the following storage clause:

```
STORED AS  
  INPUTFORMAT 'com.hadoop.mapred.DeprecatedLzoTextInputFormat'  
  OUTPUTFORMAT 'org.apache.hadoop.hive.ql.io.HiveIgnoreKeyTextOutputFormat'
```

Also, certain Hive settings need to be in effect. For example:

```
hive> SET mapreduce.output.fileoutputformat.compress=true;  
hive> SET hive.exec.compress.output=true;  
hive> SET  
mapreduce.output.fileoutputformat.compress.codec=com.hadoop.compression.lzo.LzopCodec;  
hive> CREATE TABLE lzo_t (s string) STORED AS  
  > INPUTFORMAT 'com.hadoop.mapred.DeprecatedLzoTextInputFormat'  
  > OUTPUTFORMAT 'org.apache.hadoop.hive.ql.io.HiveIgnoreKeyTextOutputFormat';  
hive> INSERT INTO TABLE lzo_t SELECT col1, col2 FROM uncompressed_text_table;
```

Once you have created LZO-compressed text tables, you can convert data stored in other tables (regardless of file format) by using the `INSERT ... SELECT` statement in Hive.

Files in an LZO-compressed table must use the `.lzo` extension. Examine the files in the HDFS data directory after doing the `INSERT` in Hive, to make sure the files have the right extension. If the required settings are not in place, you end up with regular uncompressed files, and Impala cannot access the table because it finds data files with the wrong (uncompressed) format.

After loading data into an LZO-compressed text table, index the files so that they can be split. You index the files by running a Java class, `com.hadoop.compression.lzo.DistributedLzoIndexer`, through the Linux command line. This Java class is included in the `hadoop-lzo` package.

Run the indexer using a command like the following:

```
$ hadoop jar /usr/lib/hadoop/lib/hadoop-lzo-version-gplextras.jar  
com.hadoop.compression.lzo.DistributedLzoIndexer /hdfs_location_of_table/
```



Note: If the path of the JAR file in the preceding example is not recognized, do a `find` command to locate `hadoop-lzo-*-gplextras.jar` and use that path.

Indexed files have the same name as the file they index, with the `.index` extension. If the data files are not indexed, Impala queries still work, but the queries read the data from remote DataNodes, which is very inefficient.

Once the LZO-compressed tables are created, and data is loaded and indexed, you can query them through Impala. As always, the first time you start `impala-shell` after creating a table in Hive, issue an `INVALIDATE METADATA` statement so that Impala recognizes the new table. (In Impala 1.2 and higher, you only have to run `INVALIDATE METADATA` on one node, rather than on all the Impala nodes.)

Using gzip, bzip2, or Snappy-Compressed Text Files

In Impala 2.0 and later, Impala supports using text data files that employ `gzip`, `bzip2`, or `Snappy` compression. These compression types are primarily for convenience within an existing ETL pipeline rather than maximum performance. Although it requires less I/O to read compressed text than the equivalent uncompressed text, files compressed by these codecs are not “splittable” and therefore cannot take full advantage of the Impala parallel query capability.

As each `bzip2`- or `Snappy`-compressed text file is processed, the node doing the work reads the entire file into memory and then decompresses it. Therefore, the node must have enough memory to hold both the compressed and uncompressed data from the text file. The memory required to hold the uncompressed data is difficult to estimate in advance, potentially causing problems on systems with low memory limits or with resource management enabled. In Impala 2.1 and higher, this memory overhead is reduced for `gzip`-compressed text files. The gzipped data is decompressed as it is read, rather than all at once.

To create a table to hold `gzip`, `bzip2`, or `Snappy`-compressed text, create a text table with no special compression options. Specify the delimiter and escape character if required, using the `ROW FORMAT` clause.

Because Impala can query compressed text files but currently cannot write them, produce the compressed text files outside Impala and use the `LOAD DATA` statement, manual HDFS commands to move them to the appropriate Impala data directory. (Or, you can use `CREATE EXTERNAL TABLE` and point the `LOCATION` attribute at a directory containing existing compressed text files.)

For Impala to recognize the compressed text files, they must have the appropriate file extension corresponding to the compression codec, either `.gz`, `.bz2`, or `.snappy`. The extensions can be in uppercase or lowercase.

The following example shows how you can create a regular text table, put different kinds of compressed and uncompressed files into it, and Impala automatically recognizes and decompresses each one based on their file extensions:

```
create table csv_compressed (a string, b string, c string)
  row format delimited fields terminated by ",";

insert into csv_compressed values
  ('one - uncompressed', 'two - uncompressed', 'three - uncompressed'),
  ('abc - uncompressed', 'xyz - uncompressed', '123 - uncompressed');
...make equivalent .gz, .bz2, and .snappy files and load them into same table directory...

select * from csv_compressed;
```

a	b	c
one - snappy	two - snappy	three - snappy
one - uncompressed	two - uncompressed	three - uncompressed
abc - uncompressed	xyz - uncompressed	123 - uncompressed
one - bz2	two - bz2	three - bz2
abc - bz2	xyz - bz2	123 - bz2
one - gzip	two - gzip	three - gzip
abc - gzip	xyz - gzip	123 - gzip

```
$ hdfs dfs -ls
'hdfs://127.0.0.1:8020/user/hive/warehouse/file_formats.db/csv_compressed/';
...truncated for readability...
```

```

75 hdfs://127.0.0.1:8020/user/hive/warehouse/file_formats.db/csv_compressed/csv_compressed.snappy
79 hdfs://127.0.0.1:8020/user/hive/warehouse/file_formats.db/csv_compressed/csv_compressed_bz2.csv.bz2
80 hdfs://127.0.0.1:8020/user/hive/warehouse/file_formats.db/csv_compressed/csv_compressed_gzip.csv.gz
116 hdfs://127.0.0.1:8020/user/hive/warehouse/file_formats.db/csv_compressed/dd414df64d67d49b_data.0.

```

Using the Parquet File Format with Impala Tables

Impala helps you to create, manage, and query Parquet tables. Parquet is a column-oriented binary file format intended to be highly efficient for the types of large-scale queries that Impala is best at. Parquet is especially good for queries scanning particular columns within a table, for example to query “wide” tables with many columns, or to perform aggregation operations such as `SUM()` and `AVG()` that need to process most or all of the values from a column. Each data file contains the values for a set of rows (the “row group”). Within a data file, the values from each column are organized so that they are all adjacent, enabling good compression for the values from that column. Queries against a Parquet table can retrieve and analyze these values from any column quickly and with minimal I/O.

Table 5: Parquet Format Support in Impala

File Type	Format	Compression Codecs	Impala Can CREATE?	Impala Can INSERT?
Parquet	Structured	Snappy, gzip; currently Snappy by default	Yes.	Yes: CREATE TABLE, INSERT, LOAD DATA, and query.

Creating Parquet Tables in Impala

To create a table named `PARQUET_TABLE` that uses the Parquet format, you would use a command like the following, substituting your own table name, column names, and data types:

```
[impala-host:21000] > create table parquet_table_name (x INT, y STRING) STORED AS PARQUET;
```

Or, to clone the column names and data types of an existing table:

```
[impala-host:21000] > create table parquet_table_name LIKE other_table_name STORED AS PARQUET;
```

In Impala 1.4.0 and higher, you can derive column definitions from a raw Parquet data file, even without an existing Impala table. For example, you can create an external table pointing to an HDFS directory, and base the column definitions on one of the files in that directory:

```
CREATE EXTERNAL TABLE ingest_existing_files LIKE PARQUET
'/user/etl/destination/datafile1.dat'
STORED AS PARQUET
LOCATION '/user/etl/destination';
```

Or, you can refer to an existing data file and create a new empty table with suitable column definitions. Then you can use `INSERT` to create new data files or `LOAD DATA` to transfer existing data files into the new table.

```
CREATE TABLE columns_from_data_file LIKE PARQUET '/user/etl/destination/datafile1.dat'
STORED AS PARQUET;
```

The default properties of the newly created table are the same as for any other `CREATE TABLE` statement. For example, the default file format is text; if you want the new table to use the Parquet file format, include the `STORED AS PARQUET` file also.

In this example, the new table is partitioned by year, month, and day. These partition key columns are not part of the data file, so you specify them in the `CREATE TABLE` statement:

```
CREATE TABLE columns_from_data_file LIKE PARQUET '/user/etl/destination/datafile1.dat'
PARTITION (year INT, month TINYINT, day TINYINT)
STORED AS PARQUET;
```

See [CREATE TABLE Statement](#) on page 254 for more details about the `CREATE TABLE LIKE PARQUET` syntax.

Once you have created a table, to insert data into that table, use a command similar to the following, again with your own table names:

```
[impala-host:21000] > insert overwrite table parquet_table_name select * from
other_table_name;
```

If the Parquet table has a different number of columns or different column names than the other table, specify the names of columns from the other table rather than `*` in the `SELECT` statement.

Loading Data into Parquet Tables

Choose from the following techniques for loading data into Parquet tables, depending on whether the original data is already in an Impala table, or exists as raw data files outside Impala.

If you already have data in an Impala or Hive table, perhaps in a different file format or partitioning scheme, you can transfer the data to a Parquet table using the Impala `INSERT . . . SELECT` syntax. You can convert, filter, repartition, and do other things to the data as part of this same `INSERT` statement. See [Snappy and GZip Compression for Parquet Data Files](#) on page 588 for some examples showing how to insert data into Parquet tables.

When inserting into partitioned tables, especially using the Parquet file format, you can include a hint in the `INSERT` statement to fine-tune the overall performance of the operation and its resource usage:

- These hints are available in Impala 1.2.2 and higher.
- You would only use these hints if an `INSERT` into a partitioned Parquet table was failing due to capacity limits, or if such an `INSERT` was succeeding but with less-than-optimal performance.
- To use these hints, put the hint keyword `[SHUFFLE]` or `[NOSHUFFLE]` (including the square brackets) after the `PARTITION` clause, immediately before the `SELECT` keyword.
- `[SHUFFLE]` selects an execution plan that minimizes the number of files being written simultaneously to HDFS, and the number of memory buffers holding data for individual partitions. Thus it reduces overall resource usage for the `INSERT` operation, allowing some `INSERT` operations to succeed that otherwise would fail. It does involve some data transfer between the nodes so that the data files for a particular partition are all constructed on the same node.
- `[NOSHUFFLE]` selects an execution plan that might be faster overall, but might also produce a larger number of small data files or exceed capacity limits, causing the `INSERT` operation to fail. Use `[SHUFFLE]` in cases where an `INSERT` statement fails or runs inefficiently due to all nodes attempting to construct data for all partitions.
- Impala automatically uses the `[SHUFFLE]` method if any partition key column in the source table, mentioned in the `INSERT . . . SELECT` query, does not have column statistics. In this case, only the `[NOSHUFFLE]` hint would have any effect.
- If column statistics are available for all partition key columns in the source table mentioned in the `INSERT . . . SELECT` query, Impala chooses whether to use the `[SHUFFLE]` or `[NOSHUFFLE]` technique based on the estimated number of distinct values in those columns and the number of nodes involved in the `INSERT` operation. In this case, you might need the `[SHUFFLE]` or the `[NOSHUFFLE]` hint to override the execution plan selected by Impala.

Any `INSERT` statement for a Parquet table requires enough free space in the HDFS filesystem to write one block. Because Parquet data files use a block size of 1 GB by default, an `INSERT` might fail (even for a very small amount of data) if your HDFS is running low on space.

Avoid the `INSERT . . . VALUES` syntax for Parquet tables, because `INSERT . . . VALUES` produces a separate tiny data file for each `INSERT . . . VALUES` statement, and the strength of Parquet is in its handling of data (compressing, parallelizing, and so on) in large chunks.

If you have one or more Parquet data files produced outside of Impala, you can quickly make the data queryable through Impala by one of the following methods:

- The `LOAD DATA` statement moves a single data file or a directory full of data files into the data directory for an Impala table. It does no validation or conversion of the data. The original data files must be somewhere in HDFS, not the local filesystem.
- The `CREATE TABLE` statement with the `LOCATION` clause creates a table where the data continues to reside outside the Impala data directory. The original data files must be somewhere in HDFS, not the local filesystem. For extra safety, if the data is intended to be long-lived and reused by other applications, you can use the `CREATE EXTERNAL TABLE` syntax so that the data files are not deleted by an Impala `DROP TABLE` statement.
- If the Parquet table already exists, you can copy Parquet data files directly into it, then use the `REFRESH` statement to make Impala recognize the newly added data. Remember to preserve the block size of the Parquet data files by using the `hadoop distcp -pb` command rather than a `-put` or `-cp` operation on the Parquet files. See [Example of Copying Parquet Data Files](#) on page 590 for an example of this kind of operation.



Note:

Currently, Impala always decodes the column data in Parquet files based on the ordinal position of the columns, not by looking up the position of each column based on its name. Parquet files produced outside of Impala must write column data in the same order as the columns are declared in the Impala table. Any optional columns that are omitted from the data files must be the rightmost columns in the Impala table definition.

If you created compressed Parquet files through some tool other than Impala, make sure that any compression codecs are supported in Parquet by Impala. For example, Impala does not currently support LZO compression in Parquet files. Also doublecheck that you used any recommended compatibility settings in the other tool, such as `spark.sql.parquet.binaryAsString` when writing Parquet files through Spark.

Recent versions of Sqoop can produce Parquet output files using the `--as-parquetfile` option.

If you use Sqoop to convert RDBMS data to Parquet, be careful with interpreting any resulting values from `DATE`, `DATETIME`, or `TIMESTAMP` columns. The underlying values are represented as the Parquet `INT64` type, which is represented as `BIGINT` in the Impala table. The Parquet values represent the time in milliseconds, while Impala interprets `BIGINT` as the time in seconds. Therefore, if you have a `BIGINT` column in a Parquet table that was imported this way from Sqoop, divide the values by 1000 when interpreting as the `TIMESTAMP` type.

If the data exists outside Impala and is in some other format, combine both of the preceding techniques. First, use a `LOAD DATA` or `CREATE EXTERNAL TABLE ... LOCATION` statement to bring the data into an Impala table that uses the appropriate file format. Then, use an `INSERT ... SELECT` statement to copy the data to the Parquet table, converting to Parquet format as part of the process.

Loading data into Parquet tables is a memory-intensive operation, because the incoming data is buffered until it reaches one data block in size, then that chunk of data is organized and compressed in memory before being written out. The memory consumption can be larger when inserting data into partitioned Parquet tables, because a separate data file is written for each combination of partition key column values, potentially requiring several large chunks to be manipulated in memory at once.

When inserting into a partitioned Parquet table, Impala redistributes the data among the nodes to reduce memory consumption. You might still need to temporarily increase the memory dedicated to Impala during the insert operation, or break up the load operation into several `INSERT` statements, or both.



Note: All the preceding techniques assume that the data you are loading matches the structure of the destination table, including column order, column names, and partition layout. To transform or reorganize the data, start by loading the data into a Parquet table that matches the underlying structure of the data, then use one of the table-copying techniques such as `CREATE TABLE AS SELECT` or `INSERT ... SELECT` to reorder or rename columns, divide the data among multiple partitions, and so on. For example to take a single comprehensive Parquet data file and load it into a partitioned table, you would use an `INSERT ... SELECT` statement with dynamic partitioning to let Impala create separate data files with the appropriate partition values; for an example, see [INSERT Statement](#) on page 286.

Query Performance for Impala Parquet Tables

Query performance for Parquet tables depends on the number of columns needed to process the `SELECT` list and `WHERE` clauses of the query, the way data is divided into large data files with block size equal to file size, the reduction in I/O by reading the data for each column in compressed format, which data files can be skipped (for partitioned tables), and the CPU overhead of decompressing the data for each column.

For example, the following is an efficient query for a Parquet table:

```
select avg(income) from census_data where state = 'CA';
```

The query processes only 2 columns out of a large number of total columns. If the table is partitioned by the `STATE` column, it is even more efficient because the query only has to read and decode 1 column from each data file, and it can read only the data files in the partition directory for the state 'CA', skipping the data files for all the other states, which will be physically located in other directories.

The following is a relatively inefficient query for a Parquet table:

```
select * from census_data;
```

Impala would have to read the entire contents of each large data file, and decompress the contents of each column for each row group, negating the I/O optimizations of the column-oriented format. This query might still be faster for a Parquet table than a table with some other file format, but it does not take advantage of the unique strengths of Parquet data files.

Impala can optimize queries on Parquet tables, especially join queries, better when statistics are available for all the tables. Issue the `COMPUTE STATS` statement for each table after substantial amounts of data are loaded into or appended to it. See [COMPUTE STATS Statement](#) on page 241 for details.

The runtime filtering feature, available in CDH 5.7 / Impala 2.5 and higher, works best with Parquet tables. The per-row filtering aspect only applies to Parquet tables. See [Runtime Filtering for Impala Queries](#) on page 545 for details.

In CDH 5.8 / Impala 2.6 and higher, Impala queries are optimized for files stored in Amazon S3. For Impala tables that use the file formats Parquet, RCFile, SequenceFile, Avro, and uncompressed text, the setting `fs.s3a.block.size` in the `core-site.xml` configuration file determines how Impala divides the I/O work of reading the data files. This configuration setting is specified in bytes. By default, this value is 33554432 (32 MB), meaning that Impala parallelizes S3 read operations on the files as if they were made up of 32 MB blocks. For example, if your S3 queries primarily access Parquet files written by MapReduce or Hive, increase `fs.s3a.block.size` to 134217728 (128 MB) to match the row group size of those files. If most S3 queries involve Parquet files written by Impala, increase `fs.s3a.block.size` to 268435456 (256 MB) to match the row group size produced by Impala.

Partitioning for Parquet Tables

As explained in [Partitioning for Impala Tables](#) on page 568, partitioning is an important performance technique for Impala generally. This section explains some of the performance considerations for partitioned Parquet tables.

The Parquet file format is ideal for tables containing many columns, where most queries only refer to a small subset of the columns. As explained in [How Parquet Data Files Are Organized](#) on page 593, the physical layout of Parquet data files lets Impala read only a small fraction of the data for many queries. The performance benefits of this approach are

amplified when you use Parquet tables in combination with partitioning. Impala can skip the data files for certain partitions entirely, based on the comparisons in the `WHERE` clause that refer to the partition key columns. For example, queries on partitioned tables often analyze data for time intervals based on columns such as `YEAR`, `MONTH`, and/or `DAY`, or for geographic regions. Remember that Parquet data files use a large block size, so when deciding how finely to partition the data, try to find a granularity where each partition contains 256 MB or more of data, rather than creating a large number of smaller files split among many partitions.

Inserting into a partitioned Parquet table can be a resource-intensive operation, because each Impala node could potentially be writing a separate data file to HDFS for each combination of different values for the partition key columns. The large number of simultaneous open files could exceed the HDFS “transceivers” limit. To avoid exceeding this limit, consider the following techniques:

- Load different subsets of data using separate `INSERT` statements with specific values for the `PARTITION` clause, such as `PARTITION (year=2010)`.
- Increase the “transceivers” value for HDFS, sometimes spelled “xcievers” (sic). The property value in the `hdfs-site.xml` configuration file is `dfs.datanode.max.transfer.threads`. For example, if you were loading 12 years of data partitioned by year, month, and day, even a value of 4096 might not be high enough. This [blog post](#) explores the considerations for setting this value higher or lower, using HBase examples for illustration.
- Use the `COMPUTE STATS` statement to collect [column statistics](#) on the source table from which data is being copied, so that the Impala query can estimate the number of different values in the partition key columns and distribute the work accordingly.

Snappy and GZip Compression for Parquet Data Files

When Impala writes Parquet data files using the `INSERT` statement, the underlying compression is controlled by the `COMPRESSION_CODEC` query option. (Prior to Impala 2.0, the query option name was `PARQUET_COMPRESSION_CODEC`.) The allowed values for this query option are `snappy` (the default), `gzip`, and `none`. The option value is not case-sensitive. If the option is set to an unrecognized value, all kinds of queries will fail due to the invalid option setting, not just queries involving Parquet tables.

Example of Parquet Table with Snappy Compression

By default, the underlying data files for a Parquet table are compressed with Snappy. The combination of fast compression and decompression makes it a good choice for many data sets. To ensure Snappy compression is used, for example after experimenting with other compression codecs, set the `COMPRESSION_CODEC` query option to `snappy` before inserting the data:

```
[localhost:21000] > create database parquet_compression;
[localhost:21000] > use parquet_compression;
[localhost:21000] > create table parquet_snappy like raw_text_data;
[localhost:21000] > set COMPRESSION_CODEC=snappy;
[localhost:21000] > insert into parquet_snappy select * from raw_text_data;
Inserted 1000000000 rows in 181.98s
```

Example of Parquet Table with GZip Compression

If you need more intensive compression (at the expense of more CPU cycles for uncompressing during queries), set the `COMPRESSION_CODEC` query option to `gzip` before inserting the data:

```
[localhost:21000] > create table parquet_gzip like raw_text_data;
[localhost:21000] > set COMPRESSION_CODEC=gzip;
[localhost:21000] > insert into parquet_gzip select * from raw_text_data;
Inserted 1000000000 rows in 1418.24s
```

Example of Uncompressed Parquet Table

If your data compresses very poorly, or you want to avoid the CPU overhead of compression and decompression entirely, set the `COMPRESSION_CODEC` query option to `none` before inserting the data:

```
[localhost:21000] > create table parquet_none like raw_text_data;
[localhost:21000] > set COMPRESSION_CODEC=none;
[localhost:21000] > insert into parquet_none select * from raw_text_data;
Inserted 1000000000 rows in 146.90s
```

Examples of Sizes and Speeds for Compressed Parquet Tables

Here are some examples showing differences in data sizes and query speeds for 1 billion rows of synthetic data, compressed with each kind of codec. As always, run similar tests with realistic data sets of your own. The actual compression ratios, and relative insert and query speeds, will vary depending on the characteristics of the actual data.

In this case, switching from Snappy to GZip compression shrinks the data by an additional 40% or so, while switching from Snappy compression to no compression expands the data also by about 40%:

```
$ hdfs dfs -du -h /user/hive/warehouse/parquet_compression.db
23.1 G /user/hive/warehouse/parquet_compression.db/parquet_snappy
13.5 G /user/hive/warehouse/parquet_compression.db/parquet_gzip
32.8 G /user/hive/warehouse/parquet_compression.db/parquet_none
```

Because Parquet data files are typically large, each directory will have a different number of data files and the row groups will be arranged differently.

At the same time, the less aggressive the compression, the faster the data can be decompressed. In this case using a table with a billion rows, a query that evaluates all the values for a particular column runs faster with no compression than with Snappy compression, and faster with Snappy compression than with Gzip compression. Query performance depends on several other factors, so as always, run your own benchmarks with your own data to determine the ideal tradeoff between data size, CPU efficiency, and speed of insert and query operations.

```
[localhost:21000] > desc parquet_snappy;
Query finished, fetching results ...
+-----+-----+-----+
| name   | type  | comment |
+-----+-----+-----+
| id     | int   |         |
| val    | int   |         |
| zfill  | string |         |
| name   | string |         |
| assertion | boolean |         |
+-----+-----+-----+
Returned 5 row(s) in 0.14s
[localhost:21000] > select avg(val) from parquet_snappy;
Query finished, fetching results ...
+-----+
| _c0 |
+-----+
| 250000.93577915 |
+-----+
Returned 1 row(s) in 4.29s
[localhost:21000] > select avg(val) from parquet_gzip;
Query finished, fetching results ...
+-----+
| _c0 |
+-----+
| 250000.93577915 |
+-----+
Returned 1 row(s) in 6.97s
[localhost:21000] > select avg(val) from parquet_none;
Query finished, fetching results ...
+-----+
| _c0 |
+-----+
| 250000.93577915 |
+-----+
```

```
+-----+  
Returned 1 row(s) in 3.67s
```

Example of Copying Parquet Data Files

Here is a final example, to illustrate how the data files using the various compression codecs are all compatible with each other for read operations. The metadata about the compression format is written into each data file, and can be decoded during queries regardless of the `COMPRESSION_CODEC` setting in effect at the time. In this example, we copy data files from the `PARQUET_SNAPPY`, `PARQUET_GZIP`, and `PARQUET_NONE` tables used in the previous examples, each containing 1 billion rows, all to the data directory of a new table `PARQUET_EVERYTHING`. A couple of sample queries demonstrate that the new table now contains 3 billion rows featuring a variety of compression codecs for the data files.

First, we create the table in Impala so that there is a destination directory in HDFS to put the data files:

```
[localhost:21000] > create table parquet_everything like parquet_snappy;  
Query: create table parquet_everything like parquet_snappy
```

Then in the shell, we copy the relevant data files into the data directory for this new table. Rather than using `hdfs dfs -cp` as with typical files, we use `hadoop distcp -pb` to ensure that the special block size of the Parquet data files is preserved.

```
$ hadoop distcp -pb /user/hive/warehouse/parquet_compression.db/parquet_snappy \  
/user/hive/warehouse/parquet_compression.db/parquet_everything  
...MapReduce output...  
$ hadoop distcp -pb /user/hive/warehouse/parquet_compression.db/parquet_gzip \  
/user/hive/warehouse/parquet_compression.db/parquet_everything  
...MapReduce output...  
$ hadoop distcp -pb /user/hive/warehouse/parquet_compression.db/parquet_none \  
/user/hive/warehouse/parquet_compression.db/parquet_everything  
...MapReduce output...
```

Back in the `impala-shell` interpreter, we use the `REFRESH` statement to alert the Impala server to the new data files for this table, then we can run queries demonstrating that the data files represent 3 billion rows, and the values for one of the numeric columns match what was in the original smaller tables:

```
[localhost:21000] > refresh parquet_everything;  
Query finished, fetching results ...  
  
Returned 0 row(s) in 0.32s  
[localhost:21000] > select count(*) from parquet_everything;  
Query finished, fetching results ...  
+-----+  
| _c0 |  
+-----+  
| 3000000000 |  
+-----+  
Returned 1 row(s) in 8.18s  
[localhost:21000] > select avg(val) from parquet_everything;  
Query finished, fetching results ...  
+-----+  
| _c0 |  
+-----+  
| 250000.93577915 |  
+-----+  
Returned 1 row(s) in 13.35s
```

Parquet Tables for Impala Complex Types

In CDH 5.5 / Impala 2.3 and higher, Impala supports the complex types `ARRAY`, `STRUCT`, and `MAP`. See [Complex Types \(CDH 5.5 or higher only\)](#) on page 167 for details. Because these data types are currently supported only for the Parquet file format, if you plan to use them, become familiar with the performance and storage aspects of Parquet first.

Exchanging Parquet Data Files with Other Hadoop Components

Starting in CDH 4.5, you can read and write Parquet data files from other CDH components. See [Using Apache Parquet Data Files with CDH](#) for details.

Previously, it was not possible to create Parquet data through Impala and reuse that table within Hive. Now that Parquet support is available for Hive in CDH 4.5, reusing existing Impala Parquet data files in Hive requires updating the table metadata. Use the following command if you are already running Impala 1.1.1 or higher:

```
ALTER TABLE table_name SET FILEFORMAT PARQUET;
```

If you are running a level of Impala that is older than 1.1.1, do the metadata update through Hive:

```
ALTER TABLE table_name SET SERDE 'parquet.hive.serde.ParquetHiveSerDe';
ALTER TABLE table_name SET FILEFORMAT
INPUTFORMAT "parquet.hive.DeprecatedParquetInputFormat"
OUTPUTFORMAT "parquet.hive.DeprecatedParquetOutputFormat";
```

Impala 1.1.1 and higher can reuse Parquet data files created by Hive, without any action required.

Impala supports the scalar data types that you can encode in a Parquet data file, but not composite or nested types such as maps or arrays. In Impala 2.2.0 / CDH 5.4.0 and higher, Impala can query Parquet data files that include composite or nested types, as long as the query only refers to columns with scalar types.

If you copy Parquet data files between nodes, or even between different directories on the same node, make sure to preserve the block size by using the command `hadoop distcp -pb`. To verify that the block size was preserved, issue the command `hdfs fsck -blocks HDFS_path_of_impala_table_dir` and check that the average block size is at or near 256 MB (or whatever other size is defined by the `PARQUET_FILE_SIZE` query option).. (The `hadoop distcp` operation typically leaves some directories behind, with names matching `_distcp_logs_*`, that you can delete from the destination directory afterward.) Issue the command `hadoop distcp` for details about `distcp` command syntax.

Impala can query Parquet files that use the `PLAIN`, `PLAIN_DICTIONARY`, `BIT_PACKED`, and `RLE` encodings. Currently, Impala does not support `RLE_DICTIONARY` encoding. When creating files outside of Impala for use by Impala, make sure to use one of the supported encodings. In particular, for MapReduce jobs, `parquet.writer.version` must not be defined (especially as `PARQUET_2_0`) for writing the configurations of Parquet MR jobs. Use the default version (or format). The default format, 1.0, includes some enhancements that are compatible with older versions. Data using the 2.0 format might not be consumable by Impala, due to use of the `RLE_DICTIONARY` encoding.

To examine the internal structure and data of Parquet files, you can use the `parquet-tools` command that comes with CDH. Make sure this command is in your `$PATH`. (Typically, it is symlinked from `/usr/bin`; sometimes, depending on your installation setup, you might need to locate it under a CDH-specific `bin` directory.) The arguments to this command let you perform operations such as:

- `cat`: Print a file's contents to standard out. In CDH 5.5 and higher, you can use the `-j` option to output JSON.
- `head`: Print the first few records of a file to standard output.
- `schema`: Print the Parquet schema for the file.
- `meta`: Print the file footer metadata, including key-value properties (like Avro schema), compression ratios, encodings, compression used, and row group information.
- `dump`: Print all data and metadata.

Use `parquet-tools -h` to see usage information for all the arguments. Here are some examples showing `parquet-tools` usage:

```
$ # Be careful doing this for a big file! Use parquet-tools head to be safe.
$ parquet-tools cat sample.parq
year = 1992
month = 1
day = 2
dayofweek = 4
dep_time = 748
crs_dep_time = 750
```

How Impala Works with Hadoop File Formats

```
arr_time = 851
crs_arr_time = 846
carrier = US
flight_num = 53
actual_elapsed_time = 63
crs_elapsed_time = 56
arrdelay = 5
depdelay = -2
origin = CMH
dest = IND
distance = 182
cancelled = 0
diverted = 0

year = 1992
month = 1
day = 3
...
```

```
$ parquet-tools head -n 2 sample.parq
year = 1992
month = 1
day = 2
dayofweek = 4
dep_time = 748
crs_dep_time = 750
arr_time = 851
crs_arr_time = 846
carrier = US
flight_num = 53
actual_elapsed_time = 63
crs_elapsed_time = 56
arrdelay = 5
depdelay = -2
origin = CMH
dest = IND
distance = 182
cancelled = 0
diverted = 0

year = 1992
month = 1
day = 3
...
```

```
$ parquet-tools schema sample.parq
message schema {
  optional int32 year;
  optional int32 month;
  optional int32 day;
  optional int32 dayofweek;
  optional int32 dep_time;
  optional int32 crs_dep_time;
  optional int32 arr_time;
  optional int32 crs_arr_time;
  optional binary carrier;
  optional int32 flight_num;
  ...
}
```

```
$ parquet-tools meta sample.parq
creator:          impala version 2.2.0-cdh5.4.3 (build
517bb0f71cd604a00369254ac6d88394df83e0f6)

file schema:      schema
```



```

year:                OPTIONAL INT32 R:0 D:1
month:              OPTIONAL INT32 R:0 D:1
day:               OPTIONAL INT32 R:0 D:1
dayofweek:         OPTIONAL INT32 R:0 D:1
dep_time:          OPTIONAL INT32 R:0 D:1
crs_dep_time:      OPTIONAL INT32 R:0 D:1
arr_time:          OPTIONAL INT32 R:0 D:1
crs_arr_time:      OPTIONAL INT32 R:0 D:1
carrier:           OPTIONAL BINARY R:0 D:1
flight_num:        OPTIONAL INT32 R:0 D:1
...

row group 1:        RC:20636601 TS:265103674
-----
year:                INT32 SNAPPY DO:4 FPO:35 SZ:10103/49723/4.92 VC:20636601
ENC:PLAIN_DICTIONARY,RLE,PLAIN
month:              INT32 SNAPPY DO:10147 FPO:10210 SZ:11380/35732/3.14 VC:20636601
ENC:PLAIN_DICTIONARY,RLE,PLAIN
day:               INT32 SNAPPY DO:21572 FPO:21714 SZ:3071658/9868452/3.21 VC:20636601
ENC:PLAIN_DICTIONARY,RLE,PLAIN
dayofweek:         INT32 SNAPPY DO:3093276 FPO:3093319 SZ:2274375/5941876/2.61
VC:20636601 ENC:PLAIN_DICTIONARY,RLE,PLAIN
dep_time:          INT32 SNAPPY DO:5367705 FPO:5373967 SZ:28281281/28573175/1.01
VC:20636601 ENC:PLAIN_DICTIONARY,RLE,PLAIN
crs_dep_time:      INT32 SNAPPY DO:33649039 FPO:33654262 SZ:10220839/11574964/1.13
VC:20636601 ENC:PLAIN_DICTIONARY,RLE,PLAIN
arr_time:          INT32 SNAPPY DO:43869935 FPO:43876489 SZ:28562410/28797767/1.01
VC:20636601 ENC:PLAIN_DICTIONARY,RLE,PLAIN
crs_arr_time:      INT32 SNAPPY DO:72432398 FPO:72438151 SZ:10908972/12164626/1.12
VC:20636601 ENC:PLAIN_DICTIONARY,RLE,PLAIN
carrier:           BINARY SNAPPY DO:83341427 FPO:83341558 SZ:114916/128611/1.12
VC:20636601 ENC:PLAIN_DICTIONARY,RLE,PLAIN
flight_num:        INT32 SNAPPY DO:83456393 FPO:83488603 SZ:10216514/11474301/1.12
VC:20636601 ENC:PLAIN_DICTIONARY,RLE,PLAIN
...

```

How Parquet Data Files Are Organized

Although Parquet is a column-oriented file format, do not expect to find one data file for each column. Parquet keeps all the data for a row within the same data file, to ensure that the columns for a row are always available on the same node for processing. What Parquet does is to set a large HDFS block size and a matching maximum data file size, to ensure that I/O and network transfer requests apply to large batches of data.

Within that data file, the data for a set of rows is rearranged so that all the values from the first column are organized in one contiguous block, then all the values from the second column, and so on. Putting the values from the same column next to each other lets Impala use effective compression techniques on the values in that column.



Note:

Impala `INSERT` statements write Parquet data files using an HDFS block size that matches the data file size, to ensure that each data file is represented by a single HDFS block, and the entire file can be processed on a single node without requiring any remote reads.

If you create Parquet data files outside of Impala, such as through a MapReduce or Pig job, ensure that the HDFS block size is greater than or equal to the file size, so that the “one file per block” relationship is maintained. Set the `dfs.block.size` or the `dfs.blocksize` property large enough that each file fits within a single HDFS block, even if that size is larger than the normal HDFS block size.

If the block size is reset to a lower value during a file copy, you will see lower performance for queries involving those files, and the `PROFILE` statement will reveal that some I/O is being done suboptimally, through remote reads. See [Example of Copying Parquet Data Files](#) on page 590 for an example showing how to preserve the block size when copying Parquet data files.

How Impala Works with Hadoop File Formats

When Impala retrieves or tests the data for a particular column, it opens all the data files, but only reads the portion of each file containing the values for that column. The column values are stored consecutively, minimizing the I/O required to process the values within a single column. If other columns are named in the `SELECT` list or `WHERE` clauses, the data for all columns in the same row is available within that same data file.

If an `INSERT` statement brings in less than one Parquet block's worth of data, the resulting data file is smaller than ideal. Thus, if you do split up an ETL job to use multiple `INSERT` statements, try to keep the volume of data for each `INSERT` statement to approximately 256 MB, or a multiple of 256 MB.

RLE and Dictionary Encoding for Parquet Data Files

Parquet uses some automatic compression techniques, such as run-length encoding (RLE) and dictionary encoding, based on analysis of the actual data values. Once the data values are encoded in a compact form, the encoded data can optionally be further compressed using a compression algorithm. Parquet data files created by Impala can use Snappy, GZip, or no compression; the Parquet spec also allows LZO compression, but currently Impala does not support LZO-compressed Parquet files.

RLE and dictionary encoding are compression techniques that Impala applies automatically to groups of Parquet data values, in addition to any Snappy or GZip compression applied to the entire data files. These automatic optimizations can save you time and planning that are normally needed for a traditional data warehouse. For example, dictionary encoding reduces the need to create numeric IDs as abbreviations for longer string values.

Run-length encoding condenses sequences of repeated data values. For example, if many consecutive rows all contain the same value for a country code, those repeating values can be represented by the value followed by a count of how many times it appears consecutively.

Dictionary encoding takes the different values present in a column, and represents each one in compact 2-byte form rather than the original value, which could be several bytes. (Additional compression is applied to the compacted values, for extra space savings.) This type of encoding applies when the number of different values for a column is less than 2^{16} (16,384). It does not apply to columns of data type `BOOLEAN`, which are already very short. `TIMESTAMP` columns sometimes have a unique value for each row, in which case they can quickly exceed the 2^{16} limit on distinct values. The 2^{16} limit on different values within a column is reset for each data file, so if several different data files each contained 10,000 different city names, the city name column in each data file could still be condensed using dictionary encoding.

Compacting Data Files for Parquet Tables

If you reuse existing table structures or ETL processes for Parquet tables, you might encounter a “many small files” situation, which is suboptimal for query efficiency. For example, statements like these might produce inefficiently organized data files:

```
-- In an N-node cluster, each node produces a data file
-- for the INSERT operation. If you have less than
-- N GB of data to copy, some files are likely to be
-- much smaller than the default Parquet block size.
insert into parquet_table select * from text_table;

-- Even if this operation involves an overall large amount of data,
-- when split up by year/month/day, each partition might only
-- receive a small amount of data. Then the data files for
-- the partition might be divided between the N nodes in the cluster.
-- A multi-gigabyte copy operation might produce files of only
-- a few MB each.
insert into partitioned_parquet_table partition (year, month, day)
select year, month, day, url, referer, user_agent, http_code, response_time
from web_stats;
```

Here are techniques to help you produce large data files in Parquet `INSERT` operations, and to compact existing too-small data files:

- When inserting into a partitioned Parquet table, use statically partitioned `INSERT` statements where the partition key values are specified as constant values. Ideally, use a separate `INSERT` statement for each partition.

- You might set the `NUM_NODES` option to 1 briefly, during `INSERT` or `CREATE TABLE AS SELECT` statements. Normally, those statements produce one or more data files per data node. If the write operation involves small amounts of data, a Parquet table, and/or a partitioned table, the default behavior could produce many small files when intuitively you might expect only a single output file. `SET NUM_NODES=1` turns off the “distributed” aspect of the write operation, making it more likely to produce only one or a few data files.
- Be prepared to reduce the number of partition key columns from what you are used to with traditional analytic database systems.
- Do not expect Impala-written Parquet files to fill up the entire Parquet block size. Impala estimates on the conservative side when figuring out how much data to write to each Parquet file. Typically, the of uncompressed data in memory is substantially reduced on disk by the compression and encoding techniques in the Parquet file format. The final data file size varies depending on the compressibility of the data. Therefore, it is not an indication of a problem if 256 MB of text data is turned into 2 Parquet data files, each less than 256 MB.
- If you accidentally end up with a table with many small data files, consider using one or more of the preceding techniques and copying all the data into a new Parquet table, either through `CREATE TABLE AS SELECT` or `INSERT ... SELECT` statements.

To avoid rewriting queries to change table names, you can adopt a convention of always running important queries against a view. Changing the view definition immediately switches any subsequent queries to use the new underlying tables:

```
create view production_table as select * from table_with_many_small_files;
-- CTAS or INSERT...SELECT all the data into a more efficient layout...
alter view production_table as select * from table_with_few_big_files;
select * from production_table where c1 = 100 and c2 < 50 and ...;
```

Schema Evolution for Parquet Tables

Schema evolution refers to using the statement `ALTER TABLE ... REPLACE COLUMNS` to change the names, data type, or number of columns in a table. You can perform schema evolution for Parquet tables as follows:

- The Impala `ALTER TABLE` statement never changes any data files in the tables. From the Impala side, schema evolution involves interpreting the same data files in terms of a new table definition. Some types of schema changes make sense and are represented correctly. Other types of changes cannot be represented in a sensible way, and produce special result values or conversion errors during queries.
- The `INSERT` statement always creates data using the latest table definition. You might end up with data files with different numbers of columns or internal data representations if you do a sequence of `INSERT` and `ALTER TABLE ... REPLACE COLUMNS` statements.
- If you use `ALTER TABLE ... REPLACE COLUMNS` to define additional columns at the end, when the original data files are used in a query, these final columns are considered to be all `NULL` values.
- If you use `ALTER TABLE ... REPLACE COLUMNS` to define fewer columns than before, when the original data files are used in a query, the unused columns still present in the data file are ignored.
- Parquet represents the `TINYINT`, `SMALLINT`, and `INT` types the same internally, all stored in 32-bit integers.
 - That means it is easy to promote a `TINYINT` column to `SMALLINT` or `INT`, or a `SMALLINT` column to `INT`. The numbers are represented exactly the same in the data file, and the columns being promoted would not contain any out-of-range values.
 - If you change any of these column types to a smaller type, any values that are out-of-range for the new type are returned incorrectly, typically as negative numbers.
 - You cannot change a `TINYINT`, `SMALLINT`, or `INT` column to `BIGINT`, or the other way around. Although the `ALTER TABLE` succeeds, any attempt to query those columns results in conversion errors.
 - Any other type conversion for columns produces a conversion error during queries. For example, `INT` to `STRING`, `FLOAT` to `DOUBLE`, `TIMESTAMP` to `STRING`, `DECIMAL(9, 0)` to `DECIMAL(5, 2)`, and so on.

You might find that you have Parquet files where the columns do not line up in the same order as in your Impala table. For example, you might have a Parquet file that was part of a table with columns `c1`, `c2`, `c3`, `c4`, and now you want to reuse the same Parquet file in a table with columns `c4`, `c2`. By default, Impala expects the columns in the data file to appear in the same order as the columns defined for the table, making it impractical to do some kinds of file reuse or schema evolution. In CDH 5.8 / Impala 2.6 and higher, the query option `PARQUET_FALLBACK_SCHEMA_RESOLUTION=name` lets Impala resolve columns by name, and therefore handle out-of-order or extra columns in the data file. For example:

```
create database schema_evolution;
use schema_evolution;
create table t1 (c1 int, c2 boolean, c3 string, c4 timestamp)
  stored as parquet;
insert into t1 values
  (1, true, 'yes', now()),
  (2, false, 'no', now() + interval 1 day);

select * from t1;
+-----+-----+-----+-----+
| c1 | c2      | c3   | c4                                     |
+-----+-----+-----+-----+
| 1  | true    | yes  | 2016-06-28 14:53:26.554369000        |
| 2  | false   | no   | 2016-06-29 14:53:26.554369000        |
+-----+-----+-----+-----+

desc formatted t1;
...
| Location:      | /user/hive/warehouse/schema_evolution.db/t1 |
...

-- Make T2 have the same data file as in T1, including 2
-- unused columns and column order different than T2 expects.
load data inpath '/user/hive/warehouse/schema_evolution.db/t1'
  into table t2;

+-----+-----+
| summary                                     |
+-----+-----+
| Loaded 1 file(s). Total files in destination location: 1 |
+-----+-----+

-- 'position' is the default setting.
-- Impala cannot read the Parquet file if the column order does not match.
set PARQUET_FALLBACK_SCHEMA_RESOLUTION=position;
PARQUET_FALLBACK_SCHEMA_RESOLUTION set to position

select * from t2;
WARNINGS:
File 'schema_evolution.db/t2/45331705_data.0.parq'
has an incompatible Parquet schema for column 'schema_evolution.t2.c4'.
Column type: TIMESTAMP, Parquet schema: optional int32 c1 [i:0 d:1 r:0]

File 'schema_evolution.db/t2/45331705_data.0.parq'
has an incompatible Parquet schema for column 'schema_evolution.t2.c4'.
Column type: TIMESTAMP, Parquet schema: optional int32 c1 [i:0 d:1 r:0]

-- With the 'name' setting, Impala can read the Parquet data files
-- despite mismatching column order.
set PARQUET_FALLBACK_SCHEMA_RESOLUTION=name;
PARQUET_FALLBACK_SCHEMA_RESOLUTION set to name

select * from t2;
+-----+-----+
| c4                                     | c2      |
+-----+-----+
| 2016-06-28 14:53:26.554369000        | true    |
| 2016-06-29 14:53:26.554369000        | false   |
+-----+-----+
```

See [PARQUET_FALLBACK_SCHEMA_RESOLUTION Query Option \(CDH 5.8 or higher only\)](#) on page 349 for more details.

Data Type Considerations for Parquet Tables

The Parquet format defines a set of data types whose names differ from the names of the corresponding Impala data types. If you are preparing Parquet files using other Hadoop components such as Pig or MapReduce, you might need to work with the type names defined by Parquet. The following figure lists the Parquet-defined types and the equivalent types in Impala.

Primitive types:

```
BINARY -> STRING
BOOLEAN -> BOOLEAN
DOUBLE -> DOUBLE
FLOAT -> FLOAT
INT32 -> INT
INT64 -> BIGINT
INT96 -> TIMESTAMP
```

Logical types:

```
BINARY + OriginalType UTF8 -> STRING
BINARY + OriginalType DECIMAL -> DECIMAL
```

Complex types:

For the complex types (ARRAY, MAP, and STRUCT) available in CDH 5.5 / Impala 2.3 and higher, Impala only supports queries against those types in Parquet tables.

Using the Avro File Format with Impala Tables

Impala supports using tables whose data files use the Avro file format. Impala can query Avro tables, and in Impala 1.4.0 and higher can create them, but currently cannot insert data into them. For insert operations, use Hive, then switch back to Impala to run queries.

Table 6: Avro Format Support in Impala

File Type	Format	Compression Codecs	Impala Can CREATE?	Impala Can INSERT?
Avro	Structured	Snappy, gzip, deflate, bzip2	Yes, in Impala 1.4.0 and higher. Before that, create the table using Hive.	No. Import data by using <code>LOAD DATA</code> on data files already in the right format, or use <code>INSERT</code> in Hive followed by <code>REFRESH table_name</code> in Impala.

Creating Avro Tables

To create a new table using the Avro file format, issue the `CREATE TABLE` statement through Impala with the `STORED AS AVRO` clause, or through Hive. If you create the table through Impala, you must include column definitions that match the fields specified in the Avro schema. With Hive, you can omit the columns and just specify the Avro schema.

In CDH 5.5 / Impala 2.3 and higher, the `CREATE TABLE` for Avro tables can include SQL-style column definitions rather than specifying Avro notation through the `TBLPROPERTIES` clause. Impala issues warning messages if there are any mismatches between the types specified in the SQL column definitions and the underlying types; for example, any `TINYINT` or `SMALLINT` columns are treated as `INT` in the underlying Avro files, and therefore are displayed as `INT` in any `DESCRIBE` or `SHOW CREATE TABLE` output.

**Note:**

Currently, Avro tables cannot contain `TIMESTAMP` columns. If you need to store date and time values in Avro tables, as a workaround you can use a `STRING` representation of the values, convert the values to `BIGINT` with the `UNIX_TIMESTAMP()` function, or create separate numeric columns for individual date and time fields using the `EXTRACT()` function.

The following examples demonstrate creating an Avro table in Impala, using either an inline column specification or one taken from a JSON file stored in HDFS:

```
[localhost:21000] > CREATE TABLE avro_only_sql_columns
> (
>   id INT,
>   bool_col BOOLEAN,
>   tinyint_col TINYINT, /* Gets promoted to INT */
>   smallint_col SMALLINT, /* Gets promoted to INT */
>   int_col INT,
>   bigint_col BIGINT,
>   float_col FLOAT,
>   double_col DOUBLE,
>   date_string_col STRING,
>   string_col STRING
> )
> STORED AS AVRO;

[localhost:21000] > CREATE TABLE impala_avro_table
> (bool_col BOOLEAN, int_col INT, long_col BIGINT, float_col FLOAT,
double_col DOUBLE, string_col STRING, nullable_int INT)
> STORED AS AVRO
> TBLPROPERTIES ('avro.schema.literal'='{
>   "name": "my_record",
>   "type": "record",
>   "fields": [
>     {"name": "bool_col", "type": "boolean"},
>     {"name": "int_col", "type": "int"},
>     {"name": "long_col", "type": "long"},
>     {"name": "float_col", "type": "float"},
>     {"name": "double_col", "type": "double"},
>     {"name": "string_col", "type": "string"},
>     {"name": "nullable_int", "type": ["null", "int"]}]}');

[localhost:21000] > CREATE TABLE avro_examples_of_all_types (
>   id INT,
>   bool_col BOOLEAN,
>   tinyint_col TINYINT,
>   smallint_col SMALLINT,
>   int_col INT,
>   bigint_col BIGINT,
>   float_col FLOAT,
>   double_col DOUBLE,
>   date_string_col STRING,
>   string_col STRING
> )
> STORED AS AVRO
> TBLPROPERTIES
('avro.schema.url'='hdfs://localhost:8020/avro_schemas/alltypes.json');
```

The following example demonstrates creating an Avro table in Hive:

```
hive> CREATE TABLE hive_avro_table
> ROW FORMAT SERDE 'org.apache.hadoop.hive.serde2.avro.AvroSerDe'
> STORED AS INPUTFORMAT 'org.apache.hadoop.hive.ql.io.avro.AvroContainerInputFormat'
> OUTPUTFORMAT 'org.apache.hadoop.hive.ql.io.avro.AvroContainerOutputFormat'
> TBLPROPERTIES ('avro.schema.literal'='{
>   "name": "my_record",
```

```

>   "type": "record",
>   "fields": [
>     { "name": "bool_col", "type": "boolean" },
>     { "name": "int_col", "type": "int" },
>     { "name": "long_col", "type": "long" },
>     { "name": "float_col", "type": "float" },
>     { "name": "double_col", "type": "double" },
>     { "name": "string_col", "type": "string" },
>     { "name": "nullable_int", "type": [ "null", "int" ] } ] } );

```

Each field of the record becomes a column of the table. Note that any other information, such as the record name, is ignored.



Note: For nullable Avro columns, make sure to put the "null" entry before the actual type name. In Impala, all columns are nullable; Impala currently does not have a NOT NULL clause. Any non-nullable property is only enforced on the Avro side.

Most column types map directly from Avro to Impala under the same names. These are the exceptions and special cases to consider:

- The `DECIMAL` type is defined in Avro as a `BYTE` type with the `logicalType` property set to "decimal" and a specified precision and scale. Use `DECIMAL` in Avro tables only under CDH 5. The infrastructure and components under CDH 4 do not have reliable `DECIMAL` support.
- The Avro `long` type maps to `BIGINT` in Impala.

If you create the table through Hive, switch back to `impala-shell` and issue an `INVALIDATE METADATA table_name` statement. Then you can run queries for that table through `impala-shell`.

In rare instances, a mismatch could occur between the Avro schema and the column definitions in the metastore database. In CDH 5.5 / Impala 2.3 and higher, Impala checks for such inconsistencies during a `CREATE TABLE` statement and each time it loads the metadata for a table (for example, after `INVALIDATE METADATA`). Impala uses the following rules to determine how to treat mismatching columns, a process known as **schema reconciliation**:

- If there is a mismatch in the number of columns, Impala uses the column definitions from the Avro schema.
- If there is a mismatch in column name or type, Impala uses the column definition from the Avro schema. Because a `CHAR` or `VARCHAR` column in Impala maps to an Avro `STRING`, this case is not considered a mismatch and the column is preserved as `CHAR` or `VARCHAR` in the reconciled schema. Prior to CDH 5.9 / Impala 2.7, the column name and comment for such `CHAR` and `VARCHAR` columns was also taken from the SQL column definition. In CDH 5.9 / Impala 2.7 and higher, the column name and comment from the Avro schema file take precedence for such columns, and only the `CHAR` or `VARCHAR` type is preserved from the SQL column definition.
- An Impala `TIMESTAMP` column definition maps to an Avro `STRING` and is presented as a `STRING` in the reconciled schema, because Avro has no binary `TIMESTAMP` representation. As a result, no Avro table can have a `TIMESTAMP` column; this restriction is the same as in earlier CDH and Impala releases.

Complex type considerations: Although you can create tables in this file format using the complex types (`ARRAY`, `STRUCT`, and `MAP`) available in CDH 5.5 / Impala 2.3 and higher, currently, Impala can query these types only in Parquet tables. The one exception to the preceding rule is `COUNT(*)` queries on RCFile tables that include complex types. Such queries are allowed in CDH 5.8 / Impala 2.6 and higher.

Using a Hive-Created Avro Table in Impala

If you have an Avro table created through Hive, you can use it in Impala as long as it contains only Impala-compatible data types. It cannot contain:

- Complex types: `array`, `map`, `record`, `struct`, `union` other than `[supported_type, null]` or `[null, supported_type]`
- The Avro-specific types `enum`, `bytes`, and `fixed`
- Any scalar type other than those listed in [Data Types](#) on page 126

How Impala Works with Hadoop File Formats

Because Impala and Hive share the same metastore database, Impala can directly access the table definitions and data for tables that were created in Hive.

If you create an Avro table in Hive, issue an `INVALIDATE METADATA` the next time you connect to Impala through `impala-shell`. This is a one-time operation to make Impala aware of the new table. You can issue the statement while connected to any Impala node, and the catalog service broadcasts the change to all other Impala nodes.

If you load new data into an Avro table through Hive, either through a Hive `LOAD DATA` or `INSERT` statement, or by manually copying or moving files into the data directory for the table, issue a `REFRESH table_name` statement the next time you connect to Impala through `impala-shell`. You can issue the statement while connected to any Impala node, and the catalog service broadcasts the change to all other Impala nodes. If you issue the `LOAD DATA` statement through Impala, you do not need a `REFRESH` afterward.

Impala only supports fields of type `boolean`, `int`, `long`, `float`, `double`, and `string`, or unions of these types with `null`; for example, `["string", "null"]`. Unions with `null` essentially create a nullable type.

Specifying the Avro Schema through JSON

While you can embed a schema directly in your `CREATE TABLE` statement, as shown above, column width restrictions in the Hive metastore limit the length of schema you can specify. If you encounter problems with long schema literals, try storing your schema as a JSON file in HDFS instead. Specify your schema in HDFS using table properties similar to the following:

```
tblproperties ('avro.schema.url'='hdfs://your-name-node:port/path/to/schema.json');
```

Loading Data into an Avro Table

Currently, Impala cannot write Avro data files. Therefore, an Avro table cannot be used as the destination of an Impala `INSERT` statement or `CREATE TABLE AS SELECT`.

To copy data from another table, issue any `INSERT` statements through Hive. For information about loading data into Avro tables through Hive, see [Avro page on the Hive wiki](#).

If you already have data files in Avro format, you can also issue `LOAD DATA` in either Impala or Hive. Impala can move existing Avro data files into an Avro table, it just cannot create new Avro data files.

Enabling Compression for Avro Tables

To enable compression for Avro tables, specify settings in the Hive shell to enable compression and to specify a codec, then issue a `CREATE TABLE` statement as in the preceding examples. Impala supports the `snappy` and `deflate` codecs for Avro tables.

For example:

```
hive> set hive.exec.compress.output=true;
hive> set avro.output.codec=snappy;
```

How Impala Handles Avro Schema Evolution

Starting in Impala 1.1, Impala can deal with Avro data files that employ *schema evolution*, where different data files within the same table use slightly different type definitions. (You would perform the schema evolution operation by issuing an `ALTER TABLE` statement in the Hive shell.) The old and new types for any changed columns must be compatible, for example a column might start as an `int` and later change to a `bigint` or `float`.

As with any other tables where the definitions are changed or data is added outside of the current `impalad` node, ensure that Impala loads the latest metadata for the table if the Avro schema is modified through Hive. Issue a `REFRESH table_name` or `INVALIDATE METADATA table_name` statement. `REFRESH` reloads the metadata immediately, `INVALIDATE METADATA` reloads the metadata the next time the table is accessed.

When Avro data files or columns are not consulted during a query, Impala does not check for consistency. Thus, if you issue `SELECT c1, c2 FROM t1`, Impala does not return any error if the column `c3` changed in an incompatible way.

If a query retrieves data from some partitions but not others, Impala does not check the data files for the unused partitions.

In the Hive DDL statements, you can specify an `avro.schema.literal` table property (if the schema definition is short) or an `avro.schema.url` property (if the schema definition is long, or to allow convenient editing for the definition).

For example, running the following SQL code in the Hive shell creates a table using the Avro file format and puts some sample data into it:

```
CREATE TABLE avro_table (a string, b string)
ROW FORMAT SERDE 'org.apache.hadoop.hive.serde2.avro.AvroSerDe'
STORED AS INPUTFORMAT 'org.apache.hadoop.hive.ql.io.avro.AvroContainerInputFormat'
OUTPUTFORMAT 'org.apache.hadoop.hive.ql.io.avro.AvroContainerOutputFormat'
TBLPROPERTIES (
  'avro.schema.literal'='{
    "type": "record",
    "name": "my_record",
    "fields": [
      {"name": "a", "type": "int"},
      {"name": "b", "type": "string"}
    ]}' );

INSERT OVERWRITE TABLE avro_table SELECT 1, "avro" FROM functional.alltypes LIMIT 1;
```

Once the Avro table is created and contains data, you can query it through the `impala-shell` command:

```
[localhost:21000] > select * from avro_table;
+----+-----+
| a  | b      |
+----+-----+
| 1  | avro  |
+----+-----+
```

Now in the Hive shell, you change the type of a column and add a new column with a default value:

```
-- Promote column "a" from INT to FLOAT (no need to update Avro schema)
ALTER TABLE avro_table CHANGE A A FLOAT;

-- Add column "c" with default
ALTER TABLE avro_table ADD COLUMNS (c int);
ALTER TABLE avro_table SET TBLPROPERTIES (
  'avro.schema.literal'='{
    "type": "record",
    "name": "my_record",
    "fields": [
      {"name": "a", "type": "int"},
      {"name": "b", "type": "string"},
      {"name": "c", "type": "int", "default": 10}
    ]}' );
```

Once again in `impala-shell`, you can query the Avro table based on its latest schema definition. Because the table metadata was changed outside of Impala, you issue a `REFRESH` statement first so that Impala has up-to-date metadata for the table.

```
[localhost:21000] > refresh avro_table;
[localhost:21000] > select * from avro_table;
+----+-----+-----+
| a  | b      | c      |
+----+-----+-----+
| 1  | avro  | 10     |
+----+-----+-----+
```

Data Type Considerations for Avro Tables

The Avro format defines a set of data types whose names differ from the names of the corresponding Impala data types. If you are preparing Avro files using other Hadoop components such as Pig or MapReduce, you might need to

How Impala Works with Hadoop File Formats

work with the type names defined by Avro. The following figure lists the Avro-defined types and the equivalent types in Impala.

```
Primitive Types (Avro -> Impala)
-----
STRING -> STRING
STRING -> CHAR
STRING -> VARCHAR
INT -> INT
BOOLEAN -> BOOLEAN
LONG -> BIGINT
FLOAT -> FLOAT
DOUBLE -> DOUBLE

Logical Types
-----
BYTES + logicalType = "decimal" -> DECIMAL

Avro Types with No Impala Equivalent
-----
RECORD, MAP, ARRAY, UNION, ENUM, FIXED, NULL

Impala Types with No Avro Equivalent
-----
TIMESTAMP
```

The Avro specification allows string values up to 2^{64} bytes in length. Impala queries for Avro tables use 32-bit integers to hold string lengths. In CDH 5.7 / Impala 2.5 and higher, Impala truncates `CHAR` and `VARCHAR` values in Avro tables to $(2^{31})-1$ bytes. If a query encounters a `STRING` value longer than $(2^{31})-1$ bytes in an Avro table, the query fails. In earlier releases, encountering such long values in an Avro table could cause a crash.

Query Performance for Impala Avro Tables

In general, expect query performance with Avro tables to be faster than with tables using text data, but slower than with Parquet tables. See [Using the Parquet File Format with Impala Tables](#) on page 584 for information about using the Parquet file format for high-performance analytic queries.

In CDH 5.8 / Impala 2.6 and higher, Impala queries are optimized for files stored in Amazon S3. For Impala tables that use the file formats Parquet, RCFile, SequenceFile, Avro, and uncompressed text, the setting `fs.s3a.block.size` in the `core-site.xml` configuration file determines how Impala divides the I/O work of reading the data files. This configuration setting is specified in bytes. By default, this value is 33554432 (32 MB), meaning that Impala parallelizes S3 read operations on the files as if they were made up of 32 MB blocks. For example, if your S3 queries primarily access Parquet files written by MapReduce or Hive, increase `fs.s3a.block.size` to 134217728 (128 MB) to match the row group size of those files. If most S3 queries involve Parquet files written by Impala, increase `fs.s3a.block.size` to 268435456 (256 MB) to match the row group size produced by Impala.

Using the RCFile File Format with Impala Tables

Impala supports using RCFile data files.

Table 7: RCFile Format Support in Impala

File Type	Format	Compression Codecs	Impala Can CREATE?	Impala Can INSERT?
RCFile	Structured	Snappy, gzip, deflate, bzip2	Yes.	No. Import data by using <code>LOAD DATA</code> on data files already in the right format, or use <code>INSERT</code> in Hive followed by <code>REFRESH table_name</code> in Impala.

Creating RCFile Tables and Loading Data

If you do not have an existing data file to use, begin by creating one in the appropriate format.

To create an RCFile table:

In the `impala-shell` interpreter, issue a command similar to:

```
create table rcfile_table (column_specs) stored as rcfile;
```

Because Impala can query some kinds of tables that it cannot currently write to, after creating tables of certain file formats, you might use the Hive shell to load the data. See [How Impala Works with Hadoop File Formats](#) on page 575 for details. After loading data into a table through Hive or other mechanism outside of Impala, issue a `REFRESH table_name` statement the next time you connect to the Impala node, before querying the table, to make Impala recognize the new data.



Important: See [Known Issues and Workarounds in Impala](#) on page 697 for potential compatibility issues with RCFile tables created in Hive 0.12, due to a change in the default RCFile SerDe for Hive.

For example, here is how you might create some RCFile tables in Impala (by specifying the columns explicitly, or cloning the structure of another table), load data through Hive, and query them through Impala:

```
$ impala-shell -i localhost
[localhost:21000] > create table rcfile_table (x int) stored as rcfile;
[localhost:21000] > create table rcfile_clone like some_other_table stored as rcfile;
[localhost:21000] > quit;

$ hive
hive> insert into table rcfile_table select x from some_other_table;
3 Rows loaded to rcfile_table
Time taken: 19.015 seconds
hive> quit;

$ impala-shell -i localhost
[localhost:21000] > select * from rcfile_table;
Returned 0 row(s) in 0.23s
[localhost:21000] > -- Make Impala recognize the data loaded through Hive;
[localhost:21000] > refresh rcfile_table;
[localhost:21000] > select * from rcfile_table;
+----+
| x   |
+----+
| 1   |
| 2   |
| 3   |
+----+
Returned 3 row(s) in 0.23s
```

Complex type considerations: Although you can create tables in this file format using the complex types (`ARRAY`, `STRUCT`, and `MAP`) available in CDH 5.5 / Impala 2.3 and higher, currently, Impala can query these types only in Parquet tables. The one exception to the preceding rule is `COUNT(*)` queries on RCFile tables that include complex types. Such queries are allowed in CDH 5.8 / Impala 2.6 and higher.

Enabling Compression for RCFile Tables

You may want to enable compression on existing tables. Enabling compression provides performance gains in most cases and is supported for RCFile tables. For example, to enable Snappy compression, you would specify the following additional settings when loading data through the Hive shell:

```
hive> SET hive.exec.compress.output=true;
hive> SET mapred.max.split.size=256000000;
hive> SET mapred.output.compression.type=BLOCK;
hive> SET mapred.output.compression.codec=org.apache.hadoop.io.compress.SnappyCodec;
hive> INSERT OVERWRITE TABLE new_table SELECT * FROM old_table;
```

How Impala Works with Hadoop File Formats

If you are converting partitioned tables, you must complete additional steps. In such a case, specify additional settings similar to the following:

```
hive> CREATE TABLE new_table (your_cols) PARTITIONED BY (partition_cols) STORED AS
new_format;
hive> SET hive.exec.dynamic.partition.mode=nonstrict;
hive> SET hive.exec.dynamic.partition=true;
hive> INSERT OVERWRITE TABLE new_table PARTITION(comma_separated_partition_cols) SELECT
* FROM old_table;
```

Remember that Hive does not require that you specify a source format for it. Consider the case of converting a table with two partition columns called `year` and `month` to a Snappy compressed RCFile. Combining the components outlined previously to complete this table conversion, you would specify settings similar to the following:

```
hive> CREATE TABLE tbl_rc (int_col INT, string_col STRING) STORED AS RCFILE;
hive> SET hive.exec.compress.output=true;
hive> SET mapred.max.split.size=256000000;
hive> SET mapred.output.compression.type=BLOCK;
hive> SET mapred.output.compression.codec=org.apache.hadoop.io.compress.SnappyCodec;
hive> SET hive.exec.dynamic.partition.mode=nonstrict;
hive> SET hive.exec.dynamic.partition=true;
hive> INSERT OVERWRITE TABLE tbl_rc SELECT * FROM tbl;
```

To complete a similar process for a table that includes partitions, you would specify settings similar to the following:

```
hive> CREATE TABLE tbl_rc (int_col INT, string_col STRING) PARTITIONED BY (year INT)
STORED AS RCFILE;
hive> SET hive.exec.compress.output=true;
hive> SET mapred.max.split.size=256000000;
hive> SET mapred.output.compression.type=BLOCK;
hive> SET mapred.output.compression.codec=org.apache.hadoop.io.compress.SnappyCodec;
hive> SET hive.exec.dynamic.partition.mode=nonstrict;
hive> SET hive.exec.dynamic.partition=true;
hive> INSERT OVERWRITE TABLE tbl_rc PARTITION(year) SELECT * FROM tbl;
```



Note:

The compression type is specified in the following command:

```
SET
mapred.output.compression.codec=org.apache.hadoop.io.compress.SnappyCodec;
```

You could elect to specify alternative codecs such as `GzipCodec` here.

Query Performance for Impala RCFile Tables

In general, expect query performance with RCFile tables to be faster than with tables using text data, but slower than with Parquet tables. See [Using the Parquet File Format with Impala Tables](#) on page 584 for information about using the Parquet file format for high-performance analytic queries.

In CDH 5.8 / Impala 2.6 and higher, Impala queries are optimized for files stored in Amazon S3. For Impala tables that use the file formats Parquet, RCFile, SequenceFile, Avro, and uncompressed text, the setting `fs.s3a.block.size` in the `core-site.xml` configuration file determines how Impala divides the I/O work of reading the data files. This configuration setting is specified in bytes. By default, this value is 33554432 (32 MB), meaning that Impala parallelizes S3 read operations on the files as if they were made up of 32 MB blocks. For example, if your S3 queries primarily access Parquet files written by MapReduce or Hive, increase `fs.s3a.block.size` to 134217728 (128 MB) to match the row group size of those files. If most S3 queries involve Parquet files written by Impala, increase `fs.s3a.block.size` to 268435456 (256 MB) to match the row group size produced by Impala.

Using the SequenceFile File Format with Impala Tables

Impala supports using SequenceFile data files.

Table 8: SequenceFile Format Support in Impala

File Type	Format	Compression Codecs	Impala Can CREATE?	Impala Can INSERT?
SequenceFile	Structured	Snappy, gzip, deflate, bzip2	Yes.	No. Import data by using <code>LOAD DATA</code> on data files already in the right format, or use <code>INSERT</code> in Hive followed by <code>REFRESH table_name</code> in Impala.

Creating SequenceFile Tables and Loading Data

If you do not have an existing data file to use, begin by creating one in the appropriate format.

To create a SequenceFile table:

In the `impala-shell` interpreter, issue a command similar to:

```
create table sequencefile_table (column_specs) stored as sequencefile;
```

Because Impala can query some kinds of tables that it cannot currently write to, after creating tables of certain file formats, you might use the Hive shell to load the data. See [How Impala Works with Hadoop File Formats](#) on page 575 for details. After loading data into a table through Hive or other mechanism outside of Impala, issue a `REFRESH table_name` statement the next time you connect to the Impala node, before querying the table, to make Impala recognize the new data.

For example, here is how you might create some SequenceFile tables in Impala (by specifying the columns explicitly, or cloning the structure of another table), load data through Hive, and query them through Impala:

```
$ impala-shell -i localhost
[localhost:21000] > create table seqfile_table (x int) stored as sequencefile;
[localhost:21000] > create table seqfile_clone like some_other_table stored as
sequencefile;
[localhost:21000] > quit;

$ hive
hive> insert into table seqfile_table select x from some_other_table;
3 Rows loaded to seqfile_table
Time taken: 19.047 seconds
hive> quit;

$ impala-shell -i localhost
[localhost:21000] > select * from seqfile_table;
Returned 0 row(s) in 0.23s
[localhost:21000] > -- Make Impala recognize the data loaded through Hive;
[localhost:21000] > refresh seqfile_table;
[localhost:21000] > select * from seqfile_table;
+----+
| x |
+----+
| 1 |
| 2 |
| 3 |
+----+
Returned 3 row(s) in 0.23s
```

Complex type considerations: Although you can create tables in this file format using the complex types (`ARRAY`, `STRUCT`, and `MAP`) available in CDH 5.5 / Impala 2.3 and higher, currently, Impala can query these types only in Parquet tables. The one exception to the preceding rule is `COUNT(*)` queries on RCFile tables that include complex types. Such queries are allowed in CDH 5.8 / Impala 2.6 and higher.

Enabling Compression for SequenceFile Tables

You may want to enable compression on existing tables. Enabling compression provides performance gains in most cases and is supported for SequenceFile tables. For example, to enable Snappy compression, you would specify the following additional settings when loading data through the Hive shell:

```
hive> SET hive.exec.compress.output=true;
hive> SET mapred.max.split.size=256000000;
hive> SET mapred.output.compression.type=BLOCK;
hive> SET mapred.output.compression.codec=org.apache.hadoop.io.compress.SnappyCodec;
hive> insert overwrite table new_table select * from old_table;
```

If you are converting partitioned tables, you must complete additional steps. In such a case, specify additional settings similar to the following:

```
hive> create table new_table (your_cols) partitioned by (partition_cols) stored as
new_format;
hive> SET hive.exec.dynamic.partition.mode=nonstrict;
hive> SET hive.exec.dynamic.partition=true;
hive> insert overwrite table new_table partition(comma_separated_partition_cols) select
* from old_table;
```

Remember that Hive does not require that you specify a source format for it. Consider the case of converting a table with two partition columns called `year` and `month` to a Snappy compressed SequenceFile. Combining the components outlined previously to complete this table conversion, you would specify settings similar to the following:

```
hive> create table TBL_SEQ (int_col int, string_col string) STORED AS SEQUENCEFILE;
hive> SET hive.exec.compress.output=true;
hive> SET mapred.max.split.size=256000000;
hive> SET mapred.output.compression.type=BLOCK;
hive> SET mapred.output.compression.codec=org.apache.hadoop.io.compress.SnappyCodec;
hive> SET hive.exec.dynamic.partition.mode=nonstrict;
hive> SET hive.exec.dynamic.partition=true;
hive> INSERT OVERWRITE TABLE tbl_seq SELECT * FROM tbl;
```

To complete a similar process for a table that includes partitions, you would specify settings similar to the following:

```
hive> CREATE TABLE tbl_seq (int_col INT, string_col STRING) PARTITIONED BY (year INT)
STORED AS SEQUENCEFILE;
hive> SET hive.exec.compress.output=true;
hive> SET mapred.max.split.size=256000000;
hive> SET mapred.output.compression.type=BLOCK;
hive> SET mapred.output.compression.codec=org.apache.hadoop.io.compress.SnappyCodec;
hive> SET hive.exec.dynamic.partition.mode=nonstrict;
hive> SET hive.exec.dynamic.partition=true;
hive> INSERT OVERWRITE TABLE tbl_seq PARTITION(year) SELECT * FROM tbl;
```



Note:

The compression type is specified in the following command:

```
SET
mapred.output.compression.codec=org.apache.hadoop.io.compress.SnappyCodec;
```

You could elect to specify alternative codecs such as `GzipCodec` here.

Query Performance for Impala SequenceFile Tables

In general, expect query performance with SequenceFile tables to be faster than with tables using text data, but slower than with Parquet tables. See [Using the Parquet File Format with Impala Tables](#) on page 584 for information about using the Parquet file format for high-performance analytic queries.

In CDH 5.8 / Impala 2.6 and higher, Impala queries are optimized for files stored in Amazon S3. For Impala tables that use the file formats Parquet, RCFile, SequenceFile, Avro, and uncompressed text, the setting `fs.s3a.block.size` in the `core-site.xml` configuration file determines how Impala divides the I/O work of reading the data files. This configuration setting is specified in bytes. By default, this value is 33554432 (32 MB), meaning that Impala parallelizes S3 read operations on the files as if they were made up of 32 MB blocks. For example, if your S3 queries primarily access Parquet files written by MapReduce or Hive, increase `fs.s3a.block.size` to 134217728 (128 MB) to match the row group size of those files. If most S3 queries involve Parquet files written by Impala, increase `fs.s3a.block.size` to 268435456 (256 MB) to match the row group size produced by Impala.

Using Impala to Query HBase Tables

You can use Impala to query HBase tables. This capability allows convenient access to a storage system that is tuned for different kinds of workloads than the default with Impala. The default Impala tables use data files stored on HDFS, which are ideal for bulk loads and queries using full-table scans. In contrast, HBase can do efficient queries for data organized for OLTP-style workloads, with lookups of individual rows or ranges of values.

From the perspective of an Impala user, coming from an RDBMS background, HBase is a kind of key-value store where the value consists of multiple fields. The key is mapped to one column in the Impala table, and the various fields of the value are mapped to the other columns in the Impala table.

For background information on HBase, see the snapshot of the Apache HBase site (including documentation) for the level of HBase that comes with [CDH 5](#). To install HBase on a CDH cluster, see the installation instructions for [CDH 5](#).

Overview of Using HBase with Impala

When you use Impala with HBase:

- You create the tables on the Impala side using the Hive shell, because the Impala `CREATE TABLE` statement currently does not support custom SerDes and some other syntax needed for these tables:
 - You designate it as an HBase table using the `STORED BY 'org.apache.hadoop.hive.hbase.HBaseStorageHandler'` clause on the Hive `CREATE TABLE` statement.
 - You map these specially created tables to corresponding tables that exist in HBase, with the clause `TBLPROPERTIES("hbase.table.name" = "table_name_in_hbase")` on the Hive `CREATE TABLE` statement.
 - See [Examples of Querying HBase Tables from Impala](#) on page 614 for a full example.
- You define the column corresponding to the HBase row key as a string with the `#string` keyword, or map it to a `STRING` column.
- Because Impala and Hive share the same metastore database, once you create the table in Hive, you can query or insert into it through Impala. (After creating a new table through Hive, issue the `INVALIDATE METADATA` statement in `impala-shell` to make Impala aware of the new table.)
- You issue queries against the Impala tables. For efficient queries, use `WHERE` clauses to find a single key value or a range of key values wherever practical, by testing the Impala column corresponding to the HBase row key. Avoid queries that do full-table scans, which are efficient for regular Impala tables but inefficient in HBase.

To work with an HBase table from Impala, ensure that the `impala` user has read/write privileges for the HBase table, using the `GRANT` command in the HBase shell. For details about HBase security, see the [Security chapter in the HBase Reference Guide](#).

Configuring HBase for Use with Impala

HBase works out of the box with Impala. There is no mandatory configuration needed to use these two components together.

To avoid delays if HBase is unavailable during Impala startup or after an `INVALIDATE METADATA` statement, Cloudera recommends setting timeout values as follows in `/etc/impala/conf/hbase-site.xml` (for environments not managed by Cloudera Manager):

```
<property>
  <name>hbase.client.retries.number</name>
  <value>3</value>
</property>
```



```
<property>
  <name>hbase.rpc.timeout</name>
  <value>3000</value>
</property>
```

Currently, Cloudera Manager does not have an Impala-only override for HBase settings, so any HBase configuration change you make through Cloudera Manager would take affect for all HBase applications. Therefore, this change is not recommended on systems managed by Cloudera Manager.

Supported Data Types for HBase Columns

To understand how Impala column data types are mapped to fields in HBase, you should have some background knowledge about HBase first. You set up the mapping by running the `CREATE TABLE` statement in the Hive shell. See [the Hive wiki](#) for a starting point, and [Examples of Querying HBase Tables from Impala](#) on page 614 for examples.

HBase works as a kind of “bit bucket”, in the sense that HBase does not enforce any typing for the key or value fields. All the type enforcement is done on the Impala side.

For best performance of Impala queries against HBase tables, most queries will perform comparisons in the `WHERE` against the column that corresponds to the HBase row key. When creating the table through the Hive shell, use the `STRING` data type for the column that corresponds to the HBase row key. Impala can translate conditional tests (through operators such as `=`, `<`, `BETWEEN`, and `IN`) against this column into fast lookups in HBase, but this optimization (“predicate pushdown”) only works when that column is defined as `STRING`.

Starting in Impala 1.1, Impala also supports reading and writing to columns that are defined in the Hive `CREATE TABLE` statement using binary data types, represented in the Hive table definition using the `#binary` keyword, often abbreviated as `#b`. Defining numeric columns as binary can reduce the overall data volume in the HBase tables. You should still define the column that corresponds to the HBase row key as a `STRING`, to allow fast lookups using those columns.

Performance Considerations for the Impala-HBase Integration

To understand the performance characteristics of SQL queries against data stored in HBase, you should have some background knowledge about how HBase interacts with SQL-oriented systems first. See [the Hive wiki](#) for a starting point; because Impala shares the same metastore database as Hive, the information about mapping columns from Hive tables to HBase tables is generally applicable to Impala too.

Impala uses the HBase client API via Java Native Interface (JNI) to query data stored in HBase. This querying does not read HFiles directly. The extra communication overhead makes it important to choose what data to store in HBase or in HDFS, and construct efficient queries that can retrieve the HBase data efficiently:

- Use HBase table for queries that return a single row or a range of rows, not queries that scan the entire table. (If a query has no `WHERE` clause, that is a strong indicator that it is an inefficient query for an HBase table.)
- If you have join queries that do aggregation operations on large fact tables and join the results against small dimension tables, consider using Impala for the fact tables and HBase for the dimension tables. (Because Impala does a full scan on the HBase table in this case, rather than doing single-row HBase lookups based on the join column, only use this technique where the HBase table is small enough that doing a full table scan does not cause a performance bottleneck for the query.)

Query predicates are applied to row keys as start and stop keys, thereby limiting the scope of a particular lookup. If row keys are not mapped to string columns, then ordering is typically incorrect and comparison operations do not work. For example, if row keys are not mapped to string columns, evaluating for greater than (`>`) or less than (`<`) cannot be completed.

Predicates on non-key columns can be sent to HBase to scan as `SingleColumnValueFilters`, providing some performance gains. In such a case, HBase returns fewer rows than if those same predicates were applied using Impala. While there is some improvement, it is not as great when start and stop rows are used. This is because the number of rows that HBase must examine is not limited as it is when start and stop rows are used. As long as the row key predicate

Using Impala to Query HBase Tables

only applies to a single row, HBase will locate and return that row. Conversely, if a non-key predicate is used, even if it only applies to a single row, HBase must still scan the entire table to find the correct result.

Interpreting EXPLAIN Output for HBase Queries

For example, here are some queries against the following Impala table, which is mapped to an HBase table. The examples show excerpts from the output of the `EXPLAIN` statement, demonstrating what things to look for to indicate an efficient or inefficient query against an HBase table.

The first column (`cust_id`) was specified as the key column in the `CREATE EXTERNAL TABLE` statement; for performance, it is important to declare this column as `STRING`. Other columns, such as `BIRTH_YEAR` and `NEVER_LOGGED_ON`, are also declared as `STRING`, rather than their “natural” types of `INT` or `BOOLEAN`, because Impala can optimize those types more effectively in HBase tables. For comparison, we leave one column, `YEAR_REGISTERED`, as `INT` to show that filtering on this column is inefficient.

```
describe hbase_table;
Query: describe hbase_table
+-----+-----+-----+
| name          | type   | comment |
+-----+-----+-----+
| cust_id       | string |         |
| birth_year    | string |         |
| never_logged_on | string |         |
| private_email_address | string |         |
| year_registered | int   |         |
+-----+-----+-----+
```

The best case for performance involves a single row lookup using an equality comparison on the column defined as the row key:

```
explain select count(*) from hbase_table where cust_id = 'some_user@example.com';
+-----+-----+-----+
| Explain String |
+-----+-----+-----+
| Estimated Per-Host Requirements: Memory=1.01GB VCores=1
| WARNING: The following tables are missing relevant table and/or column statistics.
| hbase.hbase_table
|
| 03:AGGREGATE [MERGE FINALIZE]
|   output: sum(count(*))
|
| 02:EXCHANGE [PARTITION=UNPARTITIONED]
|
| 01:AGGREGATE
|   output: count(*)
|
| 00:SCAN HBASE [hbase.hbase_table]
|   start key: some_user@example.com
|   stop key: some_user@example.com\0
+-----+-----+-----+
```

Another type of efficient query involves a range lookup on the row key column, using SQL operators such as greater than (or equal), less than (or equal), or `BETWEEN`. This example also includes an equality test on a non-key column; because that column is a `STRING`, Impala can let HBase perform that test, indicated by the `hbase filters:` line in the `EXPLAIN` output. Doing the filtering within HBase is more efficient than transmitting all the data to Impala and doing the filtering on the Impala side.

```
explain select count(*) from hbase_table where cust_id between 'a' and 'b'
and never_logged_on = 'true';
+-----+-----+-----+
| Explain String |
+-----+-----+-----+
| ...
|
| 01:AGGREGATE
|   output: count(*)
+-----+-----+-----+
```

```

00:SCAN HBASE [hbase.hbase_table]
  start key: a
  stop key: b\0
  hbase filters: cols:never_logged_on EQUAL 'true'

```

The query is less efficient if Impala has to evaluate any of the predicates, because Impala must scan the entire HBase table. Impala can only push down predicates to HBase for columns declared as `STRING`. This example tests a column declared as `INT`, and the `predicates:` line in the `EXPLAIN` output indicates that the test is performed after the data is transmitted to Impala.

```

explain select count(*) from hbase_table where year_registered = 2010;
+-----+
| Explain String                                     |
+-----+
...
| 01:AGGREGATE                                       |
|   output: count(*)                                 |
| 00:SCAN HBASE [hbase.hbase_table]                 |
|   predicates: year_registered = 2010              |
+-----+

```

The same inefficiency applies if the key column is compared to any non-constant value. Here, even though the key column is a `STRING`, and is tested using an equality operator, Impala must scan the entire HBase table because the key column is compared to another column value rather than a constant.

```

explain select count(*) from hbase_table where cust_id = private_email_address;
+-----+
| Explain String                                     |
+-----+
...
| 01:AGGREGATE                                       |
|   output: count(*)                                 |
| 00:SCAN HBASE [hbase.hbase_table]                 |
|   predicates: cust_id = private_email_address     |
+-----+

```

Currently, tests on the row key using `OR` or `IN` clauses are not optimized into direct lookups either. Such limitations might be lifted in the future, so always check the `EXPLAIN` output to be sure whether a particular SQL construct results in an efficient query or not for HBase tables.

```

explain select count(*) from hbase_table where
  cust_id = 'some_user@example.com' or cust_id = 'other_user@example.com';
+-----+
| Explain String                                     |
+-----+
...
| 01:AGGREGATE                                       |
|   output: count(*)                                 |
| 00:SCAN HBASE [hbase.hbase_table]                 |
|   predicates: cust_id = 'some_user@example.com' OR cust_id = 'other_user@example.com' |
+-----+

explain select count(*) from hbase_table where
  cust_id in ('some_user@example.com', 'other_user@example.com');
+-----+

```

Using Impala to Query HBase Tables

```
| Explain String
+-----+
...
| 01:AGGREGATE
|   output: count(*)
|
| 00:SCAN HBASE [hbase.hbase_table]
|   predicates: cust_id IN ('some_user@example.com', 'other_user@example.com')
```

Either rewrite into separate queries for each value and combine the results in the application, or combine the single-row queries using UNION ALL:

```
select count(*) from hbase_table where cust_id = 'some_user@example.com';
select count(*) from hbase_table where cust_id = 'other_user@example.com';

explain
  select count(*) from hbase_table where cust_id = 'some_user@example.com'
  union all
  select count(*) from hbase_table where cust_id = 'other_user@example.com';
```

```
| Explain String
+-----+
...
|
| 04:AGGREGATE
|   output: count(*)
|
| 03:SCAN HBASE [hbase.hbase_table]
|   start key: other_user@example.com
|   stop key: other_user@example.com\0
|
| 10:MERGE
|
...
| 02:AGGREGATE
|   output: count(*)
|
| 01:SCAN HBASE [hbase.hbase_table]
|   start key: some_user@example.com
|   stop key: some_user@example.com\0
```

Configuration Options for Java HBase Applications

If you have an HBase Java application that calls the `setCacheBlocks` or `setCaching` methods of the class [org.apache.hadoop.hbase.client.Scan](#), you can set these same caching behaviors through Impala query options, to control the memory pressure on the HBase RegionServer. For example, when doing queries in HBase that result in full-table scans (which by default are inefficient for HBase), you can reduce memory usage and speed up the queries by turning off the `HBASE_CACHE_BLOCKS` setting and specifying a large number for the `HBASE_CACHING` setting.

To set these options, issue commands like the following in `impala-shell`:

```
-- Same as calling setCacheBlocks(true) or setCacheBlocks(false).
set hbase_cache_blocks=true;
set hbase_cache_blocks=false;

-- Same as calling setCaching(rows).
set hbase_caching=1000;
```

Or update the `impalad` defaults file `/etc/default/impala` and include settings for `HBASE_CACHE_BLOCKS` and/or `HBASE_CACHING` in the `-default_query_options` setting for `IMPALA_SERVER_ARGS`. See [Modifying Impala Startup Options](#) on page 45 for details.



Note: In Impala 2.0 and later, these options are settable through the JDBC or ODBC interfaces using the `SET` statement.

Use Cases for Querying HBase through Impala

The following are popular use cases for using Impala to query HBase tables:

- Keeping large fact tables in Impala, and smaller dimension tables in HBase. The fact tables use Parquet or other binary file format optimized for scan operations. Join queries scan through the large Impala fact tables, and cross-reference the dimension tables using efficient single-row lookups in HBase.
- Using HBase to store rapidly incrementing counters, such as how many times a web page has been viewed, or on a social network, how many connections a user has or how many votes a post received. HBase is efficient for capturing such changeable data: the append-only storage mechanism is efficient for writing each change to disk, and a query always returns the latest value. An application could query specific totals like these from HBase, and combine the results with a broader set of data queried from Impala.
- Storing very wide tables in HBase. Wide tables have many columns, possibly thousands, typically recording many attributes for an important subject such as a user of an online service. These tables are also often sparse, that is, most of the columns values are `NULL`, `0`, `false`, empty string, or other blank or placeholder value. (For example, any particular web site user might have never used some site feature, filled in a certain field in their profile, visited a particular part of the site, and so on.) A typical query against this kind of table is to look up a single row to retrieve all the information about a specific subject, rather than summing, averaging, or filtering millions of rows as in typical Impala-managed tables.

Or the HBase table could be joined with a larger Impala-managed table. For example, analyze the large Impala table representing web traffic for a site and pick out 50 users who view the most pages. Join that result with the wide user table in HBase to look up attributes of those users. The HBase side of the join would result in 50 efficient single-row lookups in HBase, rather than scanning the entire user table.

Loading Data into an HBase Table

The Impala `INSERT` statement works for HBase tables. The `INSERT . . . VALUES` syntax is ideally suited to HBase tables, because inserting a single row is an efficient operation for an HBase table. (For regular Impala tables, with data files in HDFS, the tiny data files produced by `INSERT . . . VALUES` are extremely inefficient, so you would not use that technique with tables containing any significant data volume.)

When you use the `INSERT . . . SELECT` syntax, the result in the HBase table could be fewer rows than you expect. HBase only stores the most recent version of each unique row key, so if an `INSERT . . . SELECT` statement copies over multiple rows containing the same value for the key column, subsequent queries will only return one row with each key column value:

Although Impala does not have an `UPDATE` statement, you can achieve the same effect by doing successive `INSERT` statements using the same value for the key column each time:

Limitations and Restrictions of the Impala and HBase Integration

The Impala integration with HBase has the following limitations and restrictions, some inherited from the integration between HBase and Hive, and some unique to Impala:

- If you issue a `DROP TABLE` for an internal (Impala-managed) table that is mapped to an HBase table, the underlying table is not removed in HBase. The Hive `DROP TABLE` statement also removes the HBase table in this case.
- The `INSERT OVERWRITE` statement is not available for HBase tables. You can insert new data, or modify an existing row by inserting a new row with the same key value, but not replace the entire contents of the table. You can do an `INSERT OVERWRITE` in Hive if you need this capability.

Using Impala to Query HBase Tables

- If you issue a `CREATE TABLE LIKE` statement for a table mapped to an HBase table, the new table is also an HBase table, but inherits the same underlying HBase table name as the original. The new table is effectively an alias for the old one, not a new table with identical column structure. Avoid using `CREATE TABLE LIKE` for HBase tables, to avoid any confusion.
- Copying data into an HBase table using the Impala `INSERT ... SELECT` syntax might produce fewer new rows than are in the query result set. If the result set contains multiple rows with the same value for the key column, each row supercedes any previous rows with the same key value. Because the order of the inserted rows is unpredictable, you cannot rely on this technique to preserve the “latest” version of a particular key value.
- Because the complex data types (`ARRAY`, `STRUCT`, and `MAP`) available in CDH 5.5 / Impala 2.3 and higher are currently only supported in Parquet tables, you cannot use these types in HBase tables that are queried through Impala.
- The `LOAD DATA` statement cannot be used with HBase tables.

Examples of Querying HBase Tables from Impala

The following examples create an HBase table with four column families, create a corresponding table through Hive, then insert and query the table through Impala.

In HBase shell, the table name is quoted in `CREATE` and `DROP` statements. Tables created in HBase begin in “enabled” state; before dropping them through the HBase shell, you must issue a `disable 'table_name'` statement.

```
$ hbase shell
15/02/10 16:07:45
HBase Shell; enter 'help<RETURN>' for list of supported commands.
Type "exit<RETURN>" to leave the HBase Shell
Version 0.94.2-cdh4.2.0, rUnknown, Fri Feb 15 11:51:18 PST 2013

hbase(main):001:0> create 'hbasealltypesmall', 'boolsCF', 'intsCF', 'floatsCF',
'stringsCF'
0 row(s) in 4.6520 seconds

=> Hbase::Table - hbasealltypesmall
hbase(main):006:0> quit
```

Issue the following `CREATE TABLE` statement in the Hive shell. (The Impala `CREATE TABLE` statement currently does not support the `STORED BY` clause, so you switch into Hive to create the table, then back to Impala and the `impala-shell` interpreter to issue the queries.)

This example creates an external table mapped to the HBase table, usable by both Impala and Hive. It is defined as an external table so that when dropped by Impala or Hive, the original HBase table is not touched at all.

The `WITH SERDEPROPERTIES` clause specifies that the first column (`ID`) represents the row key, and maps the remaining columns of the SQL table to HBase column families. The mapping relies on the ordinal order of the columns in the table, not the column names in the `CREATE TABLE` statement. The first column is defined to be the lookup key; the `STRING` data type produces the fastest key-based lookups for HBase tables.



Note: For Impala with HBase tables, the most important aspect to ensure good performance is to use a `STRING` column as the row key, as shown in this example.

```
$ hive
Logging initialized using configuration in file:/etc/hive/conf.dist/hive-log4j.properties
Hive history file=/tmp/cloudera/hive_job_log_cloudera_201502101610_1980712808.txt
hive> use hbase;
OK
Time taken: 4.095 seconds
hive> CREATE EXTERNAL TABLE hbasestringids (
  > id string,
  > bool_col boolean,
```

```

> tinyint_col tinyint,
> smallint_col smallint,
> int_col int,
> bigint_col bigint,
> float_col float,
> double_col double,
> date_string_col string,
> string_col string,
> timestamp_col timestamp)
> STORED BY 'org.apache.hadoop.hive.hbase.HBaseStorageHandler'
> WITH SERDEPROPERTIES (
>   "hbase.columns.mapping" =
>
":key,boolsCF:bool_col,intsCF:tinyint_col,intsCF:smallint_col,intsCF:int_col,intsCF:\
>   bigint_col,floatsCF:float_col,floatsCF:double_col,stringsCF:date_string_col,\
>   stringsCF:string_col,stringsCF:timestamp_col"
> )
> TBLPROPERTIES("hbase.table.name" = "hbasealltypesmall");
OK
Time taken: 2.879 seconds
hive> quit;

```

Once you have established the mapping to an HBase table, you can issue DML statements and queries from Impala. The following example shows a series of `INSERT` statements followed by a query. The ideal kind of query from a performance standpoint retrieves a row from the table based on a row key mapped to a string column. An initial `INVALIDATE METADATA table_name` statement makes the table created through Hive visible to Impala.

```

$ impala-shell -i localhost -d hbase
Starting Impala Shell without Kerberos authentication
Connected to localhost:21000
Server version: impalad version 2.1.0-cdh4 RELEASE (build
d520a9cdea2fc97e8d5da9fbb0244e60ee416bfa)
Welcome to the Impala shell. Press TAB twice to see a list of available commands.

Copyright (c) 2012 Cloudera, Inc. All rights reserved.

(Shell build version: Impala Shell v2.1.0-cdh4 (d520a9c) built on Mon Dec 8 21:41:17
PST 2014)
Query: use `hbase`
[localhost:21000] > invalidate metadata hbasestringids;
Fetched 0 row(s) in 0.09s
[localhost:21000] > desc hbasestringids;
+-----+-----+-----+
| name          | type          | comment |
+-----+-----+-----+
| id            | string        |         |
| bool_col      | boolean       |         |
| double_col    | double        |         |
| float_col     | float         |         |
| bigint_col    | bigint        |         |
| int_col       | int           |         |
| smallint_col  | smallint      |         |
| tinyint_col   | tinyint       |         |
| date_string_col | string        |         |
| string_col    | string        |         |
| timestamp_col | timestamp     |         |
+-----+-----+-----+
Fetched 11 row(s) in 0.02s
[localhost:21000] > insert into hbasestringids values
('0001',true,3.141,9.94,1234567,32768,4000,76,'2014-12-31','Hello world',now());
Inserted 1 row(s) in 0.26s
[localhost:21000] > insert into hbasestringids values
('0002',false,2.004,6.196,1500,8000,129,127,'2014-01-01','Foo bar',now());
Inserted 1 row(s) in 0.12s
[localhost:21000] > select * from hbasestringids where id = '0001';
+-----+-----+-----+-----+-----+-----+-----+
| id      | bool_col | double_col | float_col          | bigint_col | int_col | smallint_col |
| tinyint_col | date_string_col | string_col | timestamp_col      |             |         |               |
+-----+-----+-----+-----+-----+-----+-----+
| 0001   | true     | 3.141      | 9.939999580383301 | 1234567    | 32768  | 4000         |
| 76     | 2014-12-31 | Hello world | 2015-02-10 16:36:59.764838000 |             |         |               |
+-----+-----+-----+-----+-----+-----+-----+

```

Fetches 1 row(s) in 0.54s



Note: After you create a table in Hive, such as the HBase mapping table in this example, issue an `INVALIDATE METADATA table_name` statement the next time you connect to Impala, make Impala aware of the new table. (Prior to Impala 1.2.4, you could not specify the table name if Impala was not aware of the table yet; in Impala 1.2.4 and higher, specifying the table name avoids reloading the metadata for other tables that are not changed.)

Using Impala with the Amazon S3 Filesystem



Important:

In CDH 5.8 / Impala 2.6 and higher, Impala supports both queries (`SELECT`) and DML (`INSERT`, `LOAD DATA`, `CREATE TABLE AS SELECT`) for data residing on Amazon S3. With the inclusion of write support, the Impala support for S3 is now considered ready for production use.

You can use Impala to query data residing on the Amazon S3 filesystem. This capability allows convenient access to a storage system that is remotely managed, accessible from anywhere, and integrated with various cloud-based services. Impala can query files in any supported file format from S3. The S3 storage location can be for an entire table, or individual partitions in a partitioned table.

The default Impala tables use data files stored on HDFS, which are ideal for bulk loads and queries using full-table scans. In contrast, queries against S3 data are less performant, making S3 suitable for holding “cold” data that is only queried occasionally, while more frequently accessed “hot” data resides in HDFS. In a partitioned table, you can set the `LOCATION` attribute for individual partitions to put some partitions on HDFS and others on S3, typically depending on the age of the data.

How Impala SQL Statements Work with S3

Impala SQL statements work with data on S3 as follows:

- The [CREATE TABLE Statement](#) on page 254 or [ALTER TABLE Statement](#) on page 230 statements can specify that a table resides on the S3 filesystem by encoding an `s3a://` prefix for the `LOCATION` property. `ALTER TABLE` can also set the `LOCATION` property for an individual partition, so that some data in a table resides on S3 and other data in the same table resides on HDFS.
- Once a table or partition is designated as residing on S3, the [SELECT Statement](#) on page 304 statement transparently accesses the data files from the appropriate storage layer.
- If the S3 table is an internal table, the [DROP TABLE Statement](#) on page 280 statement removes the corresponding data files from S3 when the table is dropped.
- The [TRUNCATE TABLE Statement \(CDH 5.5 or higher only\)](#) on page 370 statement always removes the corresponding data files from S3 when the table is truncated.
- The [LOAD DATA Statement](#) on page 297 can move data files residing in HDFS into an S3 table.
- The [INSERT Statement](#) on page 286 statement, or the `CREATE TABLE AS SELECT` form of the `CREATE TABLE` statement, can copy data from an HDFS table or another S3 table into an S3 table. The [S3_SKIP_INSERT_STAGING Query Option \(CDH 5.8 or higher only\)](#) on page 354 query option chooses whether or not to use a fast code path for these write operations to S3, with the tradeoff of potential inconsistency in the case of a failure during the statement.

For usage information about Impala SQL statements with S3 tables, see [Creating Impala Databases, Tables, and Partitions for Data Stored on S3](#) on page 619 and [Using Impala DML Statements for S3 Data](#) on page 618.

Specifying Impala Credentials to Access Data in S3

To allow Impala to access data in S3, specify values for the following configuration settings in your `core-site.xml` file:

```
<property>
<name>fs.s3a.access.key</name>
<value>your_access_key</value>
</property>
<property>
<name>fs.s3a.secret.key</name>
<value>your_secret_key</value>
</property>
```

As of CDH 5.8, these settings do not have corresponding controls in the Cloudera Manager user interface. Specify them in the **HDFS Client Advanced Configuration Snippet (Safety Valve) for `core-site.xml`** field. After specifying the credentials, restart both the Impala and Hive services. (Restarting Hive is required because Impala queries, `CREATE TABLE` statements, and so on go through the Hive metastore.)



Important:

Although you can specify the access key ID and secret key as part of the `s3a://` URL in the `LOCATION` attribute, doing so makes this sensitive information visible in many places, such as `DESCRIBE FORMATTED` output and Impala log files. Therefore, specify this information centrally in the `core-site.xml` file, and restrict read access to that file to only trusted users.

Loading Data into S3 for Impala Queries

If your ETL pipeline involves moving data into S3 and then querying through Impala, you can either use Impala DML statements to create, move, or copy the data, or use the same data loading techniques as you would for non-Impala data.

Using Impala DML Statements for S3 Data

In CDH 5.8 / Impala 2.6 and higher, the Impala DML statements (`INSERT`, `LOAD DATA`, and `CREATE TABLE AS SELECT`) can write data into a table or partition that resides in the Amazon Simple Storage Service (S3). The syntax of the DML statements is the same as for any other tables, because the S3 location for tables and partitions is specified by an `s3a://` prefix in the `LOCATION` attribute of `CREATE TABLE` or `ALTER TABLE` statements. If you bring data into S3 using the normal S3 transfer mechanisms instead of Impala DML statements, issue a `REFRESH` statement for the table before using Impala to query the S3 data.

Because of differences between S3 and traditional filesystems, DML operations for S3 tables can take longer than for tables on HDFS. For example, both the `LOAD DATA` statement and the final stage of the `INSERT` and `CREATE TABLE AS SELECT` statements involve moving files from one directory to another. (In the case of `INSERT` and `CREATE TABLE AS SELECT`, the files are moved from a temporary staging directory to the final destination directory.) Because S3 does not support a “rename” operation for existing objects, in these cases Impala actually copies the data files from one location to another and then removes the original files. In CDH 5.8 / Impala 2.6, the `S3_SKIP_INSERT_STAGING` query option provides a way to speed up `INSERT` statements for S3 tables and partitions, with the tradeoff that a problem during statement execution could leave data in an inconsistent state. It does not apply to `INSERT OVERWRITE` or `LOAD DATA` statements. See [S3_SKIP_INSERT_STAGING Query Option \(CDH 5.8 or higher only\)](#) on page 354 for details.

Manually Loading Data into Impala Tables on S3

As an alternative, or on earlier Impala releases without DML support for S3, you can use the Amazon-provided methods to bring data files into S3 for querying through Impala. See [the Amazon S3 web site](#) for details.

**Important:**

For best compatibility with the S3 write support in CDH 5.8 / Impala 2.6 and higher:

- Use native Hadoop techniques to create data files in S3 for querying through Impala.
- Use the `PURGE` clause of `DROP TABLE` when dropping internal (managed) tables.

By default, when you drop an internal (managed) table, the data files are moved to the HDFS trashcan. This operation is expensive for tables that reside on the Amazon S3 filesystem. Therefore, for S3 tables, prefer to use `DROP TABLE table_name PURGE` rather than the default `DROP TABLE` statement. The `PURGE` clause makes Impala delete the data files immediately, skipping the HDFS trashcan. For the `PURGE` clause to work effectively, you must originally create the data files on S3 using one of the tools from the Hadoop ecosystem, such as `hadoop fs -cp`, or `INSERT` in Impala or Hive.

Alternative file creation techniques (less compatible with the `PURGE` clause) include:

- The [Amazon AWS / S3 web interface](#) to upload from a web browser.
- The [Amazon AWS CLI](#) to manipulate files from the command line.
- Other S3-enabled software, such as [the S3Tools client software](#).

After you upload data files to a location already mapped to an Impala table or partition, or if you delete files in S3 from such a location, issue the `REFRESH table_name` statement to make Impala aware of the new set of data files.

Creating Impala Databases, Tables, and Partitions for Data Stored on S3

Impala reads data for a table or partition from S3 based on the `LOCATION` attribute for the table or partition. Specify the S3 details in the `LOCATION` clause of a `CREATE TABLE` or `ALTER TABLE` statement. The notation for the `LOCATION` clause is `s3a://bucket_name/path/to/file`. The filesystem prefix is always `s3a://` because Impala does not support the `s3://` or `s3n://` prefixes.

For a partitioned table, either specify a separate `LOCATION` clause for each new partition, or specify a base `LOCATION` for the table and set up a directory structure in S3 to mirror the way Impala partitioned tables are structured in HDFS. Although, strictly speaking, S3 filenames do not have directory paths, Impala treats S3 filenames with `/` characters the same as HDFS pathnames that include directories.

You point a nonpartitioned table or an individual partition at S3 by specifying a single directory path in S3, which could be any arbitrary directory. To replicate the structure of an entire Impala partitioned table or database in S3 requires more care, with directories and subdirectories nested and named to match the equivalent directory tree in HDFS. Consider setting up an empty staging area if necessary in HDFS, and recording the complete directory structure so that you can replicate it in S3.

For convenience when working with multiple tables with data files stored in S3, you can create a database with a `LOCATION` attribute pointing to an S3 path. Specify a URL of the form `s3a://bucket/root/path/for/database` for the `LOCATION` attribute of the database. Any tables created inside that database automatically create directories underneath the one specified by the database `LOCATION` attribute.

For example, the following session creates a partitioned table where only a single partition resides on S3. The partitions for years 2013 and 2014 are located on HDFS. The partition for year 2015 includes a `LOCATION` attribute with an `s3a://` URL, and so refers to data residing on S3, under a specific path underneath the bucket `impala-demo`.

```
[localhost:21000] > create database db_on_hdfs;
[localhost:21000] > use db_on_hdfs;
[localhost:21000] > create table mostly_on_hdfs (x int) partitioned by (year int);
[localhost:21000] > alter table mostly_on_hdfs add partition (year=2013);
[localhost:21000] > alter table mostly_on_hdfs add partition (year=2014);
[localhost:21000] > alter table mostly_on_hdfs add partition (year=2015)
>   location 's3a://impala-demo/dir1/dir2/dir3/t1';
```

The following session creates a database and two partitioned tables residing entirely on S3, one partitioned by a single column and the other partitioned by multiple columns. Because a `LOCATION` attribute with an `s3a://` URL is specified

for the database, the tables inside that database are automatically created on S3 underneath the database directory. To see the names of the associated subdirectories, including the partition key values, we use an S3 client tool to examine how the directory structure is organized on S3. For example, Impala partition directories such as `month=1` do not include leading zeroes, which sometimes appear in partition directories created through Hive.

```
[localhost:21000] > create database db_on_s3 location 's3a://impala-demo/dir1/dir2/dir3';
[localhost:21000] > use db_on_s3;

[localhost:21000] > create table partitioned_on_s3 (x int) partitioned by (year int);
[localhost:21000] > alter table partitioned_on_s3 add partition (year=2013);
[localhost:21000] > alter table partitioned_on_s3 add partition (year=2014);
[localhost:21000] > alter table partitioned_on_s3 add partition (year=2015);

[localhost:21000] > !aws s3 ls s3://impala-demo/dir1/dir2/dir3 --recursive;
2015-03-17 13:56:34      0 dir1/dir2/dir3/
2015-03-17 16:43:28      0 dir1/dir2/dir3/partitioned_on_s3/
2015-03-17 16:43:49      0 dir1/dir2/dir3/partitioned_on_s3/year=2013/
2015-03-17 16:43:53      0 dir1/dir2/dir3/partitioned_on_s3/year=2014/
2015-03-17 16:43:58      0 dir1/dir2/dir3/partitioned_on_s3/year=2015/

[localhost:21000] > create table partitioned_multiple_keys (x int)
>   partitioned by (year smallint, month tinyint, day tinyint);
[localhost:21000] > alter table partitioned_multiple_keys
>   add partition (year=2015,month=1,day=1);
[localhost:21000] > alter table partitioned_multiple_keys
>   add partition (year=2015,month=1,day=31);
[localhost:21000] > alter table partitioned_multiple_keys
>   add partition (year=2015,month=2,day=28);

[localhost:21000] > !aws s3 ls s3://impala-demo/dir1/dir2/dir3 --recursive;
2015-03-17 13:56:34      0 dir1/dir2/dir3/
2015-03-17 16:47:13      0 dir1/dir2/dir3/partitioned_multiple_keys/
2015-03-17 16:47:44      0
dir1/dir2/dir3/partitioned_multiple_keys/year=2015/month=1/day=1/
2015-03-17 16:47:50      0
dir1/dir2/dir3/partitioned_multiple_keys/year=2015/month=1/day=31/
2015-03-17 16:47:57      0
dir1/dir2/dir3/partitioned_multiple_keys/year=2015/month=2/day=28/
2015-03-17 16:43:28      0 dir1/dir2/dir3/partitioned_on_s3/
2015-03-17 16:43:49      0 dir1/dir2/dir3/partitioned_on_s3/year=2013/
2015-03-17 16:43:53      0 dir1/dir2/dir3/partitioned_on_s3/year=2014/
2015-03-17 16:43:58      0 dir1/dir2/dir3/partitioned_on_s3/year=2015/
```

The `CREATE DATABASE` and `CREATE TABLE` statements create the associated directory paths if they do not already exist. You can specify multiple levels of directories, and the `CREATE` statement creates all appropriate levels, similar to using `mkdir -p`.

Use the standard S3 file upload methods to actually put the data files into the right locations. You can also put the directory paths and data files in place before creating the associated Impala databases or tables, and Impala automatically uses the data from the appropriate location after the associated databases and tables are created.

You can switch whether an existing table or partition points to data in HDFS or S3. For example, if you have an Impala table or partition pointing to data files in HDFS or S3, and you later transfer those data files to the other filesystem, use an `ALTER TABLE` statement to adjust the `LOCATION` attribute of the corresponding table or partition to reflect that change. Because Impala does not have an `ALTER DATABASE` statement, this location-switching technique is not practical for entire databases that have a custom `LOCATION` attribute.

Internal and External Tables Located on S3

Just as with tables located on HDFS storage, you can designate S3-based tables as either internal (managed by Impala) or external, by using the syntax `CREATE TABLE` or `CREATE EXTERNAL TABLE` respectively. When you drop an internal table, the files associated with the table are removed, even if they are on S3 storage. When you drop an external table, the files associated with the table are left alone, and are still available for access by other tools or components. See [Overview of Impala Tables](#) on page 222 for details.

If the data on S3 is intended to be long-lived and accessed by other tools in addition to Impala, create any associated S3 tables with the `CREATE EXTERNAL TABLE` syntax, so that the files are not deleted from S3 when the table is dropped.

If the data on S3 is only needed for querying by Impala and can be safely discarded once the Impala workflow is complete, create the associated S3 tables using the `CREATE TABLE` syntax, so that dropping the table also deletes the corresponding data files on S3.

For example, this session creates a table in S3 with the same column layout as a table in HDFS, then examines the S3 table and queries some data from it. The table in S3 works the same as a table in HDFS as far as the expected file format of the data, table and column statistics, and other table properties. The only indication that it is not an HDFS table is the `s3a://` URL in the `LOCATION` property. Many data files can reside in the S3 directory, and their combined contents form the table data. Because the data in this example is uploaded after the table is created, a `REFRESH` statement prompts Impala to update its cached information about the data files.

```
[localhost:21000] > create table usa_cities_s3 like usa_cities location
's3a://impala-demo/usa_cities';
[localhost:21000] > desc usa_cities_s3;
+-----+-----+-----+
| name | type | comment |
+-----+-----+-----+
| id | smallint | |
| city | string | |
| state | string | |
+-----+-----+-----+

-- Now from a web browser, upload the same data file(s) to S3 as in the HDFS table,
-- under the relevant bucket and path. If you already have the data in S3, you would
-- point the table LOCATION at an existing path.

[localhost:21000] > refresh usa_cities_s3;
[localhost:21000] > select count(*) from usa_cities_s3;
+-----+
| count(*) |
+-----+
| 289 |
+-----+

[localhost:21000] > select distinct state from sample_data_s3 limit 5;
+-----+
| state |
+-----+
| Louisiana |
| Minnesota |
| Georgia |
| Alaska |
| Ohio |
+-----+

[localhost:21000] > desc formatted usa_cities_s3;
+-----+-----+-----+
| name | type | comment |
+-----+-----+-----+
| # col_name | data_type | comment |
| id | smallint | NULL |
| city | string | NULL |
| state | string | NULL |
| # Detailed Table Information | NULL | NULL |
| Database: | s3_testing | NULL |
| Owner: | jrussell | NULL |
| CreateTime: | Mon Mar 16 11:36:25 PDT 2015 | NULL |
| LastAccessTime: | UNKNOWN | NULL |
| Protect Mode: | None | NULL |
| Retention: | 0 | NULL |
| Location: | s3a://impala-demo/usa_cities | NULL |
| Table Type: | MANAGED_TABLE | NULL |
| ... | | |
+-----+-----+-----+
```

In this case, we have already uploaded a Parquet file with a million rows of data to the `sample_data` directory underneath the `impala-demo` bucket on S3. This session creates a table with matching column settings pointing to the corresponding location in S3, then queries the table. Because the data is already in place on S3 when the table is created, no `REFRESH` statement is required.

```
[localhost:21000] > create table sample_data_s3
> (id int, id bigint, val int, zerofill string,
> name string, assertion boolean, city string, state string)
> stored as parquet location 's3a://impala-demo/sample_data';
[localhost:21000] > select count(*) from sample_data_s3;;
+-----+
| count(*) |
+-----+
| 1000000  |
+-----+
[localhost:21000] > select count(*) howmany, assertion from sample_data_s3 group by
assertion;
+-----+-----+
| howmany | assertion |
+-----+-----+
| 667149  | true      |
| 332851  | false     |
+-----+-----+
```

Running and Tuning Impala Queries for Data Stored on S3

Once the appropriate `LOCATION` attributes are set up at the table or partition level, you query data stored in S3 exactly the same as data stored on HDFS or in HBase:

- Queries against S3 data support all the same file formats as for HDFS data.
- Tables can be unpartitioned or partitioned. For partitioned tables, either manually construct paths in S3 corresponding to the HDFS directories representing partition key values, or use `ALTER TABLE ... ADD PARTITION` to set up the appropriate paths in S3.
- HDFS and HBase tables can be joined to S3 tables, or S3 tables can be joined with each other.
- Authorization using the Sentry framework to control access to databases, tables, or columns works the same whether the data is in HDFS or in S3.
- The `catalogd` daemon caches metadata for both HDFS and S3 tables. Use `REFRESH` and `INVALIDATE METADATA` for S3 tables in the same situations where you would issue those statements for HDFS tables.
- Queries against S3 tables are subject to the same kinds of admission control and resource management as HDFS tables.
- Metadata about S3 tables is stored in the same metastore database as for HDFS tables.
- You can set up views referring to S3 tables, the same as for HDFS tables.
- The `COMPUTE STATS`, `SHOW TABLE STATS`, and `SHOW COLUMN STATS` statements work for S3 tables also.

Understanding and Tuning Impala Query Performance for S3 Data

Although Impala queries for data stored in S3 might be less performant than queries against the equivalent data stored in HDFS, you can still do some tuning. Here are techniques you can use to interpret explain plans and profiles for queries against S3 data, and tips to achieve the best performance possible for such queries.

All else being equal, performance is expected to be lower for queries running against data on S3 rather than HDFS. The actual mechanics of the `SELECT` statement are somewhat different when the data is in S3. Although the work is still distributed across the datanodes of the cluster, Impala might parallelize the work for a distributed query differently for data on HDFS and S3. S3 does not have the same block notion as HDFS, so Impala uses heuristics to determine how to split up large S3 files for processing in parallel. Because all hosts can access any S3 data file with equal efficiency, the distribution of work might be different than for HDFS data, where the data blocks are physically read using short-circuit local reads by hosts that contain the appropriate block replicas. Although the I/O to read the S3 data might be spread evenly across the hosts of the cluster, the fact that all data is initially retrieved across the network means that the overall query performance is likely to be lower for S3 data than for HDFS data.

In CDH 5.8 / Impala 2.6 and higher, Impala queries are optimized for files stored in Amazon S3. For Impala tables that use the file formats Parquet, RCFile, SequenceFile, Avro, and uncompressed text, the setting `fs.s3a.block.size` in the `core-site.xml` configuration file determines how Impala divides the I/O work of reading the data files. This configuration setting is specified in bytes. By default, this value is 33554432 (32 MB), meaning that Impala parallelizes S3 read operations on the files as if they were made up of 32 MB blocks. For example, if your S3 queries primarily access Parquet files written by MapReduce or Hive, increase `fs.s3a.block.size` to 134217728 (128 MB) to match the row group size of those files. If most S3 queries involve Parquet files written by Impala, increase `fs.s3a.block.size` to 268435456 (256 MB) to match the row group size produced by Impala.

Because of differences between S3 and traditional filesystems, DML operations for S3 tables can take longer than for tables on HDFS. For example, both the `LOAD DATA` statement and the final stage of the `INSERT` and `CREATE TABLE AS SELECT` statements involve moving files from one directory to another. (In the case of `INSERT` and `CREATE TABLE AS SELECT`, the files are moved from a temporary staging directory to the final destination directory.) Because S3 does not support a “rename” operation for existing objects, in these cases Impala actually copies the data files from one location to another and then removes the original files. In CDH 5.8 / Impala 2.6, the `S3_SKIP_INSERT_STAGING` query option provides a way to speed up `INSERT` statements for S3 tables and partitions, with the tradeoff that a problem during statement execution could leave data in an inconsistent state. It does not apply to `INSERT OVERWRITE` or `LOAD DATA` statements. See [S3_SKIP_INSERT_STAGING Query Option \(CDH 5.8 or higher only\)](#) on page 354 for details.

When optimizing aspects of for complex queries such as the join order, Impala treats tables on HDFS and S3 the same way. Therefore, follow all the same tuning recommendations for S3 tables as for HDFS ones, such as using the `COMPUTE STATS` statement to help Impala construct accurate estimates of row counts and cardinality. See [Tuning Impala for Performance](#) on page 523 for details.

In query profile reports, the numbers for `BytesReadLocal`, `BytesReadShortCircuit`, `BytesReadDataNodeCached`, and `BytesReadRemoteUnexpected` are blank because those metrics come from HDFS. If you do see any indications that a query against an S3 table performed “remote read” operations, do not be alarmed. That is expected because, by definition, all the I/O for S3 tables involves remote reads.

Restrictions on Impala Support for S3

Impala requires that the default filesystem for the cluster be HDFS. You cannot use S3 as the only filesystem in the cluster.

Prior to CDH 5.8 / Impala 2.6, Impala could not perform DML operations (`INSERT`, `LOAD DATA`, or `CREATE TABLE AS SELECT`) where the destination is a table or partition located on an S3 filesystem. This restriction is lifted in CDH 5.8 / Impala 2.6 and higher.

Impala does not support the old `s3://` block-based and `s3n://` filesystem schemes, only `s3a://`.

Although S3 is often used to store JSON-formatted data, the current Impala support for S3 does not include directly querying JSON data. For Impala queries, use data files in one of the file formats listed in [How Impala Works with Hadoop File Formats](#) on page 575. If you have data in JSON format, you can prepare a flattened version of that data for querying by Impala as part of your ETL cycle.

You cannot use the `ALTER TABLE ... SET CACHED` statement for tables or partitions that are located in S3.

Best Practices for Using Impala with S3

The following guidelines represent best practices derived from testing and field experience with Impala on S3:

- Any reference to an S3 location must be fully qualified. (This rule applies when S3 is not designated as the default filesystem.)
- Set the safety valve `fs.s3a.connection.maximum` to 1500 for `impalad`.

Using Impala with the Amazon S3 Filesystem

- Set safety valve `fs.s3a.block.size` to 134217728 (128 MB in bytes) if most Parquet files queried by Impala were written by Hive or ParquetMR jobs. Set the block size to 268435456 (256 MB in bytes) if most Parquet files queried by Impala were written by Impala.
- `DROP TABLE ... PURGE` is much faster than the default `DROP TABLE ... DROP PARTITION PURGE` versus the default `DROP PARTITION` operation. However, due to the eventually consistent nature of S3, the files for that table or partition could remain for some unbounded time when using `PURGE`. The default `DROP TABLE/PARTITION` is slow because Impala copies the files to the HDFS trash folder, and Impala waits until all the data is moved. `DROP TABLE/PARTITION ... PURGE` is a fast delete operation, and the Impala statement finishes quickly even though the change might not have propagated fully throughout S3.
- `INSERT` statements are faster than `INSERT OVERWRITE` for S3. The query option `S3_SKIP_INSERT_STAGING`, which is set to `true` by default, skips the staging step for regular `INSERT` (but not `INSERT OVERWRITE`). This makes the operation much faster, but consistency is not guaranteed: if a node fails during execution, the table could end up with inconsistent data. Set this option to `false` if stronger consistency is required, however this setting will make the `INSERT` operations slower.
- Too many files in a table can make metadata loading and updating slow on S3. If too many requests are made to S3, S3 has a back-off mechanism and responds slower than usual. You might have many small files because of:
 - Too many partitions due to over-granular partitioning. Prefer partitions with many megabytes of data, so that even a query against a single partition can be parallelized effectively.
 - Many small `INSERT` queries. Prefer bulk `INSERTS` so that more data is written to fewer files.

Using Impala with Isilon Storage

You can use Impala to query data files that reside on EMC Isilon storage devices, rather than in HDFS. This capability allows convenient query access to a storage system where you might already be managing large volumes of data. The combination of the Impala query engine and Isilon storage is certified on CDH versions 5.4.4 through 5.15.

Because the EMC Isilon storage devices use a global value for the block size rather than a configurable value for each file, the `PARQUET_FILE_SIZE` query option has no effect when Impala inserts data into a table or partition residing on Isilon storage. Use the `isi` command to set the default block size globally on the Isilon device. For example, to set the Isilon default block size to 256 MB, the recommended size for Parquet data files for Impala, issue the following command:

```
isi hdfs settings modify --default-block-size=256MB
```

The typical use case for Impala and Isilon together is to use Isilon for the default filesystem, replacing HDFS entirely. In this configuration, when you create a database, table, or partition, the data always resides on Isilon storage and you do not need to specify any special `LOCATION` attribute. If you do specify a `LOCATION` attribute, its value refers to a path within the Isilon filesystem. For example:

```
-- If the default filesystem is Isilon, all Impala data resides there
-- and all Impala databases and tables are located there.
CREATE TABLE t1 (x INT, s STRING);

-- You can specify LOCATION for database, table, or partition,
-- using values from the Isilon filesystem.
CREATE DATABASE d1 LOCATION '/some/path/on/isilon/server/d1.db';
CREATE TABLE d1.t2 (a TINYINT, b BOOLEAN);
```

Impala can write to, delete, and rename data files and database, table, and partition directories on Isilon storage. Therefore, Impala statements such as `CREATE TABLE`, `DROP TABLE`, `CREATE DATABASE`, `DROP DATABASE`, `ALTER TABLE`, and `INSERT` work the same with Isilon storage as with HDFS.

When the Impala spill-to-disk feature is activated by a query that approaches the memory limit, Impala writes all the temporary data to a local (not Isilon) storage device. Because the I/O bandwidth for the temporary data depends on the number of local disks, and clusters using Isilon storage might not have as many local disks attached, pay special attention on Isilon-enabled clusters to any queries that use the spill-to-disk feature. Where practical, tune the queries or allocate extra memory for Impala to avoid spilling. Although you can specify an Isilon storage device as the destination for the temporary data for the spill-to-disk feature, that configuration is not recommended due to the need to transfer the data both ways using remote I/O.

When tuning Impala queries on HDFS, you typically try to avoid any remote reads. When the data resides on Isilon storage, all the I/O consists of remote reads. Do not be alarmed when you see non-zero numbers for remote read measurements in query profile output. The benefit of the Impala and Isilon integration is primarily convenience of not having to move or copy large volumes of data to HDFS, rather than raw query performance. You can increase the performance of Impala I/O for Isilon systems by increasing the value for the `num_remote_hdfs_io_threads` configuration parameter, in the Cloudera Manager user interface for clusters using Cloudera Manager, or through the `--num_remote_hdfs_io_threads` startup option for the `impalad` daemon on clusters not using Cloudera Manager.

For information about managing Isilon storage devices through Cloudera Manager, see http://www.cloudera.com/documentation/enterprise/latest/topics/cm_mc_isilon_service.html.

Required Configurations

Specify the following configurations in Cloudera Manager on the **Clusters > Isilon Service > Configuration** tab:

- In **HDFS Client Advanced Configuration Snippet (Safety Valve) for hdfs-site.xml** `hdfs-site.xml` and the **Cluster-wide Advanced Configuration Snippet (Safety Valve) for core-site.xml** properties for the Isilon service, set the value of the `dfs.client.file-block-storage-locations.timeout.millis` property to 10000.
- In the Isilon **Cluster-wide Advanced Configuration Snippet (Safety Valve) for core-site.xml** property for the Isilon service, set the value of the `hadoop.security.token.service.use_ip` property to `FALSE`.
- If you see errors that reference the `.Trash` directory, make sure that the **Use Trash** property is selected.

Using Impala Logging

The Impala logs record information about:

- Any errors Impala encountered. If Impala experienced a serious error during startup, you must diagnose and troubleshoot that problem before you can do anything further with Impala.
- How Impala is configured.
- Jobs Impala has completed.



Note:

Formerly, the logs contained the query profile for each query, showing low-level details of how the work is distributed among nodes and how intermediate and final results are transmitted across the network. To save space, those query profiles are now stored in zlib-compressed files in `/var/log/impala/profiles`. You can access them through the Impala web user interface. For example, at `http://impalad-node-hostname:25000/queries`, each query is followed by a `Profile` link leading to a page showing extensive analytical data for the query execution.

The auditing feature introduced in Impala 1.1.1 produces a separate set of audit log files when enabled. See [Auditing Impala Operations](#) on page 123 for details.

The lineage feature introduced in Impala 2.2.0 produces a separate lineage log file when enabled. See [Viewing Lineage Information for Impala Data](#) on page 124 for details.

Locations and Names of Impala Log Files

- By default, the log files are under the directory `/var/log/impala`. To change log file locations, modify the defaults file described in [Starting Impala](#) on page 44.
- The significant files for the `impalad` process are `impalad.INFO`, `impalad.WARNING`, and `impalad.ERROR`. You might also see a file `impalad.FATAL`, although this is only present in rare conditions.
- The significant files for the `statedored` process are `statedored.INFO`, `statedored.WARNING`, and `statedored.ERROR`. You might also see a file `statedored.FATAL`, although this is only present in rare conditions.
- The significant files for the `catalogd` process are `catalogd.INFO`, `catalogd.WARNING`, and `catalogd.ERROR`. You might also see a file `catalogd.FATAL`, although this is only present in rare conditions.
- Examine the `.INFO` files to see configuration settings for the processes.
- Examine the `.WARNING` files to see all kinds of problem information, including such things as suboptimal settings and also serious runtime errors.
- Examine the `.ERROR` and/or `.FATAL` files to see only the most serious errors, if the processes crash, or queries fail to complete. These messages are also in the `.WARNING` file.
- A new set of log files is produced each time the associated daemon is restarted. These log files have long names including a timestamp. The `.INFO`, `.WARNING`, and `.ERROR` files are physically represented as symbolic links to the latest applicable log files.
- The init script for the `impala-server` service also produces a consolidated log file `/var/log/impalad/impala-server.log`, with all the same information as the corresponding `.INFO`, `.WARNING`, and `.ERROR` files.
- The init script for the `impala-state-store` service also produces a consolidated log file `/var/log/impalad/impala-state-store.log`, with all the same information as the corresponding `.INFO`, `.WARNING`, and `.ERROR` files.

Impala stores information using the `glog_v` logging system. You will see some messages referring to C++ file names. Logging is affected by:

- The `GLOG_v` environment variable specifies which types of messages are logged. See [Setting Logging Levels](#) on page 629 for details.
- The `-logbuflevel` startup flag for the `impalad` daemon specifies how often the log information is written to disk. The default is 0, meaning that the log is immediately flushed to disk when Impala outputs an important messages such as a warning or an error, but less important messages such as informational ones are buffered in memory rather than being flushed to disk immediately.
- Cloudera Manager has an Impala configuration setting that sets the `-logbuflevel` startup option.

Managing Impala Logs through Cloudera Manager or Manually

Cloudera recommends installing Impala through the Cloudera Manager administration interface. To assist with troubleshooting, Cloudera Manager collects front-end and back-end logs together into a single view, and let you do a search across log data for all the managed nodes rather than examining the logs on each node separately. If you installed Impala using Cloudera Manager, refer to the topics on Monitoring Services ([CDH 5](#)) or Logs ([CDH 5](#)).

If you are using Impala in an environment not managed by Cloudera Manager, review Impala log files on each host, when you have traced an issue back to a specific system.

Rotating Impala Logs

Impala periodically switches the physical files representing the current log files, after which it is safe to remove the old files if they are no longer needed.

Impala can automatically remove older unneeded log files, a feature known as **log rotation**.

In Impala 2.2 and higher, the `-max_log_files` configuration option specifies how many log files to keep at each severity level. You can specify an appropriate setting for each Impala-related daemon (`impalad`, `statestored`, and `catalogd`). The default value is 10, meaning that Impala preserves the latest 10 log files for each severity level (`INFO`, `WARNING`, `ERROR`, and `FATAL`). Impala checks to see if any old logs need to be removed based on the interval specified in the `logbufsecs` setting, every 5 seconds by default.

A value of 0 preserves all log files, in which case you would set up set up manual log rotation using your Linux tool or technique of choice. A value of 1 preserves only the very latest log file.

To set up log rotation on a system managed by Cloudera Manager 5.4.0 and higher, search for the `max_log_files` option name and set the appropriate value for the `Maximum Log Files` field for each Impala configuration category (Impala, Catalog Server, and StateStore). Then restart the Impala service. In earlier Cloudera Manager releases, specify the `-max_log_files=maximum` option in the **Command Line Argument Advanced Configuration Snippet (Safety Valve)** field for each Impala configuration category.

Reviewing Impala Logs

By default, the Impala log is stored at `/var/log/impalad/`. The most comprehensive log, showing informational, warning, and error messages, is in the file name `impalad.INFO`. View log file contents by using the web interface or by examining the contents of the log file. (When you examine the logs through the file system, you can troubleshoot problems by reading the `impalad.WARNING` and/or `impalad.ERROR` files, which contain the subsets of messages indicating potential problems.)

On a machine named `impala.example.com` with default settings, you could view the Impala logs on that machine by using a browser to access `http://impala.example.com:25000/logs`.



Note:

The web interface limits the amount of logging information displayed. To view every log entry, access the log files directly through the file system.

You can view the contents of the `impalad.INFO` log file in the file system. With the default configuration settings, the start of the log file appears as follows:

```
[user@example impalad]$ pwd
/var/log/impalad
[user@example impalad]$ more impalad.INFO
Log file created at: 2013/01/07 08:42:12
Running on machine: impala.example.com
Log line format: [IWEF]mmdd hh:mm:ss.uuuuuu threadid file:line] msg
I0107 08:42:12.292155 14876 daemon.cc:34] impalad version 0.4 RELEASE (build
9d7fadca0461ab40b9e9df8cdb47107ec6b27cff)
Built on Fri, 21 Dec 2012 12:55:19 PST
I0107 08:42:12.292484 14876 daemon.cc:35] Using hostname: impala.example.com
I0107 08:42:12.292706 14876 logging.cc:76] Flags (see also /varz are on debug webserver):
--dump_ir=false
--module_output=
--be_port=22000
--classpath=
--hostname=impala.example.com
```



Note: The preceding example shows only a small part of the log file. Impala log files are often several megabytes in size.

Understanding Impala Log Contents

The logs store information about Impala startup options. This information appears once for each time Impala is started and may include:

- Machine name.
- Impala version number.
- Flags used to start Impala.
- CPU information.
- The number of available disks.

There is information about each job Impala has run. Because each Impala job creates an additional set of data about queries, the amount of job specific data may be very large. Logs may contain detailed information on jobs. These detailed log entries may include:

- The composition of the query.
- The degree of data locality.
- Statistics on data throughput and response times.

Setting Logging Levels

Impala uses the GLOG system, which supports three logging levels. You can adjust the logging levels using the Cloudera Manager Admin Console. You can adjust logging levels without going through the Cloudera Manager Admin Console by exporting variable settings. To change logging settings manually, use a command similar to the following on each node before starting `impalad`:

```
export GLOG_v=1
```



Note: For performance reasons, Cloudera highly recommends not enabling the most verbose logging level of 3.

For more information on how to configure GLOG, including how to set variable logging levels for different system components, see [documentation for the glog project on github](#).

Understanding What is Logged at Different Logging Levels

As logging levels increase, the categories of information logged are cumulative. For example, GLOG_v=2 records everything GLOG_v=1 records, as well as additional information.

Increasing logging levels imposes performance overhead and increases log size. Cloudera recommends using GLOG_v=1 for most cases: this level has minimal performance impact but still captures useful troubleshooting information.

Additional information logged at each level is as follows:

- GLOG_v=1 - The default level. Logs information about each connection and query that is initiated to an `impalad` instance, including runtime profiles.
- GLOG_v=2 - Everything from the previous level plus information for each RPC initiated. This level also records query execution progress information, including details on each file that is read.
- GLOG_v=3 - Everything from the previous level plus logging of every row that is read. This level is only applicable for the most serious troubleshooting and tuning scenarios, because it can produce exceptionally large and detailed log files, potentially leading to its own set of performance and capacity problems.

Redacting Sensitive Information from Impala Log Files

Log redaction is a security feature that prevents sensitive information from being displayed in locations used by administrators for monitoring and troubleshooting, such as log files, the Cloudera Manager user interface, and the Impala debug web user interface. You configure regular expressions that match sensitive types of information processed by your system, such as credit card numbers or tax IDs, and literals matching these patterns are obfuscated wherever they would normally be recorded in log files or displayed in administration or debugging user interfaces.

In a security context, the log redaction feature is complementary to the Sentry authorization framework. Sentry prevents unauthorized users from being able to directly access table data. Redaction prevents administrators or support personnel from seeing the smaller amounts of sensitive or personally identifying information (PII) that might appear in queries issued by those authorized users.

See http://www.cloudera.com/documentation/enterprise/latest/topics/sg_redaction.html for details about how to enable this feature and set up the regular expressions to detect and redact sensitive information within SQL statement text.

Troubleshooting Impala

Troubleshooting for Impala requires being able to diagnose and debug problems with performance, network connectivity, out-of-memory conditions, disk space usage, and crash or hang conditions in any of the Impala-related daemons.

Troubleshooting Impala SQL Syntax Issues

In general, if queries issued against Impala fail, you can try running these same queries against Hive.

- If a query fails against both Impala and Hive, it is likely that there is a problem with your query or other elements of your CDH environment:
 - Review the [Language Reference](#) to ensure your query is valid.
 - Check [Impala Reserved Words](#) on page 641 to see if any database, table, column, or other object names in your query conflict with Impala reserved words. Quote those names with backticks (``) if so.
 - Check [Impala Built-In Functions](#) on page 373 to confirm whether Impala supports all the built-in functions being used by your query, and whether argument and return types are the same as you expect.
 - Review the [contents of the Impala logs](#) for any information that may be useful in identifying the source of the problem.
- If a query fails against Impala but not Hive, it is likely that there is a problem with your Impala installation.

Troubleshooting I/O Capacity Problems

Impala queries are typically I/O-intensive. If there is an I/O problem with storage devices, or with HDFS itself, Impala queries could show slow response times with no obvious cause on the Impala side. Slow I/O on even a single Impala daemon could result in an overall slowdown, because queries involving clauses such as `ORDER BY`, `GROUP BY`, or `JOIN` do not start returning results until all executor Impala daemons have finished their work.


To test whether the Linux I/O system itself is performing as expected, run Linux commands like the following on each host Impala daemon is running:

```
$ sudo sysctl -w vm.drop_caches=3 vm.drop_caches=0
vm.drop_caches = 3
vm.drop_caches = 0
$ sudo dd if=/dev/sda bs=1M of=/dev/null count=1k
1024+0 records in
1024+0 records out
1073741824 bytes (1.1 GB) copied, 5.60373 s, 192 MB/s
$ sudo dd if=/dev/sdb bs=1M of=/dev/null count=1k
1024+0 records in
1024+0 records out
1073741824 bytes (1.1 GB) copied, 5.51145 s, 195 MB/s
$ sudo dd if=/dev/sdc bs=1M of=/dev/null count=1k
1024+0 records in
1024+0 records out
1073741824 bytes (1.1 GB) copied, 5.58096 s, 192 MB/s
$ sudo dd if=/dev/sdd bs=1M of=/dev/null count=1k
1024+0 records in
1024+0 records out
1073741824 bytes (1.1 GB) copied, 5.43924 s, 197 MB/s
```

On modern hardware, a throughput rate of less than 100 MB/s typically indicates a performance issue with the storage device. Correct the hardware problem before continuing with Impala tuning or benchmarking.

Impala Troubleshooting Quick Reference

The following table lists common problems and potential solutions.

Symptom	Explanation	Recommendation
Impala takes a long time to start.	Impala instances with large numbers of tables, partitions, or data files take longer to start because the metadata for these objects is broadcast to all <code>impalad</code> nodes and cached.	Adjust timeout and synchronicity settings.
Joins fail to complete.	There may be insufficient memory. During a join, data from the second, third, and so on sets to be joined is loaded into memory. If Impala chooses an inefficient join order or join mechanism, the query could exceed the total memory available.	Start by gathering statistics with the <code>COMPUTE STATS</code> statement for each table involved in the join. Consider specifying the <code>[SHUFFLE]</code> hint so that data from the joined tables is split up between nodes rather than broadcast to each node. If tuning at the SQL level is not sufficient, add more memory to your system or join smaller data sets.
Queries return incorrect results.	Impala metadata may be outdated after changes are performed in Hive.	Where possible, use the appropriate Impala statement (<code>INSERT</code> , <code>LOAD DATA</code> , <code>CREATE TABLE</code> , <code>ALTER TABLE</code> , <code>COMPUTE STATS</code> , and so on) rather than switching back and forth between Impala and Hive. Impala automatically broadcasts the results of DDL and DML operations to all Impala nodes in the cluster, but does not automatically recognize when such changes are made through Hive. After inserting data, adding a partition, or other operation in Hive, refresh the metadata for the table as described in REFRESH Statement on page 300.
Queries are slow to return results.	<p>Some <code>impalad</code> instances may not have started. Using a browser, connect to the host running the Impala state store. Connect using an address of the form <code>http://hostname:port/metrics</code>.</p> <div style="border: 1px solid black; padding: 5px; margin: 10px 0;"> <p> Note: Replace <i>hostname</i> and <i>port</i> with the hostname and port of your Impala state store host machine and web server port. The default port is 25010.</p> </div> <p>The number of <code>impalad</code> instances listed should match the expected number of <code>impalad</code> instances installed in the cluster. There should also be one <code>impalad</code> instance installed on each DataNode.</p>	Ensure Impala is installed on all DataNodes. Start any <code>impalad</code> instances that are not running.
Queries are slow to return results.	Impala may not be configured to use native checksumming. Native checksumming uses machine-specific instructions to compute checksums over HDFS data very quickly. Review Impala logs. If you find instances of <code>"INFO util.NativeCodeLoader: Loaded the</code>	Ensure Impala is configured to use native checksumming as described in Post-Installation Configuration for Impala on page 32.

Symptom	Explanation	Recommendation
	native-hadoop" messages, native checksumming is not enabled.	
Queries are slow to return results.	Impala may not be configured to use data locality tracking.	Test Impala for data locality tracking and make configuration changes as necessary. Information on this process can be found in Post-Installation Configuration for Impala on page 32.
Attempts to complete Impala tasks such as executing INSERT-SELECT actions fail. The Impala logs include notes that files could not be opened due to permission denied.	This can be the result of permissions issues. For example, you could use the Hive shell as the hive user to create a table. After creating this table, you could attempt to complete some action, such as an INSERT-SELECT on the table. Because the table was created using one user and the INSERT-SELECT is attempted by another, this action may fail due to permissions issues.	In general, ensure the Impala user has sufficient permissions. In the preceding example, ensure the Impala user has sufficient permissions to the table that the Hive user created.
Impala fails to start up, with the <code>impalad</code> logs referring to errors connecting to the statestore service and attempts to re-register.	A large number of databases, tables, partitions, and so on can require metadata synchronization, particularly on startup, that takes longer than the default timeout for the statestore service.	Configure the statestore timeout value and possibly other settings related to the frequency of statestore updates and metadata loading. See Increasing the Statestore Timeout on page 92 and Scalability Considerations for the Impala Statestore on page 561.

Impala Web User Interface for Debugging

Each of the Impala daemons (`impalad`, `statedored`, and `catalogd`) includes a built-in web server that displays diagnostic and status information:

- The `impalad` web UI (default port: 25000) includes information about configuration settings, running and completed queries, and associated performance and resource usage for queries. In particular, the **Details** link for each query displays alternative views of the query including a graphical representation of the plan, and the output of the `EXPLAIN`, `SUMMARY`, and `PROFILE` statements from `impala-shell`. Each host that runs the `impalad` daemon has its own instance of the web UI, with details about those queries for which that host served as the coordinator. To get a consolidated view for all queries, it is usually more convenient to use the charts, graphs, and other monitoring features in Cloudera Manager. The `impalad` web UI is mainly for diagnosing query problems that can be traced to a particular node.
- The `statedored` web UI (default port: 25010) includes information about memory usage, configuration settings, and ongoing health checks performed by this daemon. Because there is only a single instance of this daemon within any cluster, you view the web UI only on the particular host that serves as the Impala Statestore.
- The `catalogd` web UI (default port: 25020) includes information about the databases, tables, and other objects managed by Impala, in addition to the resource usage and configuration settings of the daemon itself. The catalog information is represented as the underlying Thrift data structures. Because there is only a single instance of this

daemon within any cluster, you view the web UI only on the particular host that serves as the Impala Catalog Server.

**Note:**

The web user interface is primarily for problem diagnosis and troubleshooting. The items listed and their formats are subject to change. To monitor Impala health, particularly across the entire cluster at once, use the Cloudera Manager interface.

Debug Web UI for `impalad`

To debug and troubleshoot the `impalad` daemon using a web-based interface, open the URL `http://impala-server-hostname:25000/` in a browser. (For secure clusters, use the prefix `https://` instead of `http://`.) Because each Impala node produces its own set of debug information, choose a specific node that you are curious about or suspect is having problems.



Note: To get a convenient picture of the health of all Impala nodes in a cluster, use the Cloudera Manager interface, which collects the low-level operational information from all Impala nodes, and presents a unified view of the entire cluster.

Main Page

By default, the main page of the debug web UI is at `http://impala-server-hostname:25000/` (non-secure cluster) or `https://impala-server-hostname:25000/` (secure cluster).

This page lists the version of the `impalad` daemon, plus basic hardware and software information about the corresponding host, such as information about the CPU, memory, disks, and operating system version.

Backends Page

By default, the **backends** page of the debug web UI is at `http://impala-server-hostname:25000/backends` (non-secure cluster) or `https://impala-server-hostname:25000/backends` (secure cluster).

This page lists the host and port info for each of the `impalad` nodes in the cluster. Because each `impalad` daemon knows about every other `impalad` daemon through the statestore, this information should be the same regardless of which node you select. Links take you to the corresponding debug web pages for any of the other nodes in the cluster.

Catalog Page

By default, the **catalog** page of the debug web UI is at `http://impala-server-hostname:25000/catalog` (non-secure cluster) or `https://impala-server-hostname:25000/catalog` (secure cluster).

This page displays a list of databases and associated tables recognized by this instance of `impalad`. You can use this page to locate which database a table is in, check the exact spelling of a database or table name, look for identical table names in multiple databases, and so on.

Logs Page

By default, the **logs** page of the debug web UI is at `http://impala-server-hostname:25000/logs` (non-secure cluster) or `https://impala-server-hostname:25000/logs` (secure cluster).

This page shows the last portion of the `impalad.INFO` log file, the most detailed of the info, warning, and error logs for the `impalad` daemon. You can refer here to see the details of the most recent operations, whether the operations succeeded or encountered errors. This central page can be more convenient than looking around the filesystem for the log files, which could be in different locations on clusters that use Cloudera Manager or not.

Memz Page

By default, the **memz** page of the debug web UI is at `http://impala-server-hostname:25000/memz` (non-secure cluster) or `https://impala-server-hostname:25000/memz` (secure cluster).

This page displays summary and detailed information about memory usage by the `impalad` daemon. You can see the memory limit in effect for the node, and how much of that memory Impala is currently using.

Metrics Page

By default, the **metrics** page of the debug web UI is at `http://impala-server-hostname:25000/metrics` (non-secure cluster) or `https://impala-server-hostname:25000/metrics` (secure cluster).

This page displays the current set of metrics: counters and flags representing various aspects of `impalad` internal operation. For the meanings of these metrics, see [Impala Metrics](#) in the Cloudera Manager documentation.

Queries Page

By default, the **queries** page of the debug web UI is at `http://impala-server-hostname:25000/queries` (non-secure cluster) or `https://impala-server-hostname:25000/queries` (secure cluster).

This page lists all currently running queries, plus any completed queries whose details still reside in memory. The queries are listed in reverse chronological order, with the most recent at the top. (You can control the amount of memory devoted to completed queries by specifying the `--query_log_size` startup option for `impalad`.)

On this page, you can see at a glance how many SQL statements are failing (State value of `EXCEPTION`), how large the result sets are (# `rows fetched`), and how long each statement took (Start Time and End Time).

Each query has an associated link that displays the detailed query profile, which you can examine to understand the performance characteristics of that query. See [Using the Query Profile for Performance Tuning](#) on page 558 for details.

Sessions Page

By default, the **sessions** page of the debug web UI is at `http://impala-server-hostname:25000/sessions` (non-secure cluster) or `https://impala-server-hostname:25000/sessions` (secure cluster).

This page displays information about the sessions currently connected to this `impalad` instance. For example, sessions could include connections from the `impala-shell` command, JDBC or ODBC applications, or the Impala Query UI in the Hue web interface.

Threadz Page

By default, the **threadz** page of the debug web UI is at `http://impala-server-hostname:25000/threadz` (non-secure cluster) or `https://impala-server-hostname:25000/threadz` (secure cluster).

This page displays information about the threads used by this instance of `impalad`, and shows which categories they are grouped into. Making use of this information requires substantial knowledge about Impala internals.

Varz Page

By default, the **varz** page of the debug web UI is at `http://impala-server-hostname:25000/varz` (non-secure cluster) or `https://impala-server-hostname:25000/varz` (secure cluster).

This page shows the configuration settings in effect when this instance of `impalad` communicates with other Hadoop components such as HDFS and YARN. These settings are collected from a set of configuration files; Impala might not actually make use of all settings.

The bottom of this page also lists all the command-line settings in effect for this instance of `impalad`. See [Modifying Impala Startup Options](#) on page 45 for information about modifying these values.

Breakpad Minidumps for Impala (CDH 5.8 or higher only)

The [breakpad](#) project is an open-source framework for crash reporting. In CDH 5.8 / Impala 2.6 and higher, Impala can use `breakpad` to record stack information and register values when any of the Impala-related daemons crash due to an error such as `SIGSEGV` or unhandled exceptions. The dump files are much smaller than traditional core dump files. The dump mechanism itself uses very little memory, which improves reliability if the crash occurs while the system is low on memory.



Important: Because of the internal mechanisms involving Impala memory allocation and Linux signalling for out-of-memory (OOM) errors, if an Impala-related daemon experiences a crash due to an OOM condition, it does *not* generate a minidump for that error.

Enabling or Disabling Minidump Generation

By default, a minidump file is generated when an Impala-related daemon crashes. To turn off generation of the minidump files, change the `minidump_path` configuration setting of one or more Impala-related daemons to the empty string, and restart the corresponding services or daemons.

In CDH 5.9 / Impala 2.7 and higher, you can send a `SIGUSR1` signal to any Impala-related daemon to write a Breakpad minidump. For advanced troubleshooting, you can now produce a minidump without triggering a crash.

Specifying the Location for Minidump Files

By default, all minidump files are written to the following location on the host where a crash occurs:

- Clusters managed by Cloudera Manager: `/var/log/impala-minidumps/daemon_name`
- Clusters not managed by Cloudera Manager: `impala_log_dir/daemon_name/minidumps/daemon_name`

The minidump files for `impalad`, `catalogd`, and `statestored` are each written to a separate directory.

To specify a different location, set the `minidump_path` configuration setting of one or more Impala-related daemons, and restart the corresponding services or daemons.

If you specify a relative path for this setting, the value is interpreted relative to the default `minidump_path` directory.

Controlling the Number of Minidump Files

Like any files used for logging or troubleshooting, consider limiting the number of minidump files, or removing unneeded ones, depending on the amount of free storage space on the hosts in the cluster.

Because the minidump files are only used for problem resolution, you can remove any such files that are not needed to debug current issues.

To control how many minidump files Impala keeps around at any one time, set the `max_minidumps` configuration setting for one or more Impala-related daemon, and restart the corresponding services or daemons. The default for this setting is 9. A zero or negative value is interpreted as “unlimited”.

Detecting Crash Events

You can see in the Impala log files or in the Cloudera Manager charts for Impala when crash events occur that generate minidump files. Because each restart begins a new log file, the “crashed” message is always at or near the bottom of the log file. (There might be another later message if core dumps are also enabled.)

Using the Minidump Files for Problem Resolution

Typically, you provide minidump files to Cloudera Support as part of problem resolution, in the same way that you might provide a core dump. The **Send Diagnostic Data** under the **Support** menu in Cloudera Manager guides you

through the process of selecting a time period and volume of diagnostic data, then collects the data from all hosts and transmits the relevant information for you.




Figure 6: Send Diagnostic Data choice under Support menu

Cloudera Support might provide additional instructions about collecting minidumps to better isolate a specific problem. Because the information in the minidump files is limited to stack traces and register contents, the possibility of including sensitive information is much lower than with core dump files. If any sensitive information is included in the minidump, Cloudera Support preserves the confidentiality of that information.

Demonstration of Breakpad Feature

The following example uses the command `kill -11` to simulate a `SIGSEGV` crash for an `impalad` process on a single DataNode, then examines the relevant log files and minidump file.

First, as root on a worker node, we kill the `impalad` process with a `SIGSEGV` error. The original process ID was 23114. (Cloudera Manager restarts the process with a new pid, as shown by the second `ps` command.)

```
# ps ax | grep impalad
23114 ?        Sl      0:18
/opt/cloudera/parcels/<parcel_version>/lib/impala/sbin-retail/impalad
--flagfile=/var/run/cloudera-scm-agent/process/114-impala-IMPALAD/impala-conf/impalad_flags
31259 pts/0    S+     0:00 grep impalad
#
# kill -11 23114
#
# ps ax | grep impalad
31374 ?        Rl      0:04
/opt/cloudera/parcels/<parcel_version>/lib/impala/sbin-retail/impalad
--flagfile=/var/run/cloudera-scm-agent/process/114-impala-IMPALAD/impala-conf/impalad_flags
31475 pts/0    S+     0:00 grep impalad
```

We locate the log directory underneath `/var/log`. There is a `.INFO`, `.WARNING`, and `.ERROR` log file for the 23114 process ID. The minidump message is written to the `.INFO` file and the `.ERROR` file, but not the `.WARNING` file. In this case, a large core file was also produced.

```
# cd /var/log/impalad
# ls -la | grep 23114
-rw----- 1 impala impala 3539079168 Jun 23 15:20 core.23114
-rw-r--r-- 1 impala impala          99057 Jun 23 15:20 hs_err_pid23114.log
```

```
-rw-r--r--  1 impala impala          351 Jun 23 15:20
impalad.worker_node_123.impala.log.ERROR.20160623-140343.23114
-rw-r--r--  1 impala impala        29101 Jun 23 15:20
impalad.worker_node_123.impala.log.INFO.20160623-140343.23114
-rw-r--r--  1 impala impala         228 Jun 23 14:03
impalad.worker_node_123.impala.log.WARNING.20160623-140343.23114
```

The `.INFO` log includes the location of the minidump file, followed by a report of a core dump. With the `breakpad minidump` feature enabled, now we might disable core dumps or keep fewer of them around.

```
# cat impalad.worker_node_123.impala.log.INFO.20160623-140343.23114
...
Wrote minidump to
/var/log/impala-minidumps/impalad/0980da2d-a905-01e1-25ff883a-04ee027a.dmp
#
# A fatal error has been detected by the Java Runtime Environment:
#
# SIGSEGV (0xb) at pc=0x00000030c0e0b68a, pid=23114, tid=139869541455968
#
# JRE version: Java(TM) SE Runtime Environment (7.0_67-b01) (build 1.7.0_67-b01)
# Java VM: Java HotSpot(TM) 64-Bit Server VM (24.65-b04 mixed mode linux-amd64 compressed
oops)
# Problematic frame:
# C [libpthread.so.0+0xb68a] pthread_cond_wait+0xca
#
# Core dump written. Default location: /var/log/impalad/core or core.23114
#
# An error report file with more information is saved as:
# /var/log/impalad/hs_err_pid23114.log
#
# If you would like to submit a bug report, please visit:
# http://bugreport.sun.com/bugreport/crash.jsp
# The crash happened outside the Java Virtual Machine in native code.
# See problematic frame for where to report the bug.
...
# cat impalad.worker_node_123.impala.log.ERROR.20160623-140343.23114

Log file created at: 2016/06/23 14:03:43
Running on machine:.worker_node_123
Log line format: [IWEF]mmdd hh:mm:ss.uuuuuu threadid file:line] msg
E0623 14:03:43.911002 23114 logging.cc:118] stderr will be logged to this file.
Wrote minidump to
/var/log/impala-minidumps/impalad/0980da2d-a905-01e1-25ff883a-04ee027a.dmp
```

The resulting minidump file is much smaller than the corresponding core file, making it much easier to supply diagnostic information to Cloudera Support. The transmission process for the minidump files is automated through Cloudera Manager.

```
# pwd
/var/log/impalad
# cd ../impala-minidumps/impalad
# ls
0980da2d-a905-01e1-25ff883a-04ee027a.dmp
# du -kh *
2.4M 0980da2d-a905-01e1-25ff883a-04ee027a.dmp
```

Ports Used by Impala

Impala uses the TCP ports listed in the following table. Before deploying Impala, ensure these ports are open on each system.

Component	Service	Port	Access Requirement	Comment
Impala Daemon	Impala Daemon Frontend Port	21000	External	Used to transmit commands and receive results by <code>impala-shell</code> and version 1.2 of the Cloudera ODBC driver.
Impala Daemon	Impala Daemon Frontend Port	21050	External	Used to transmit commands and receive results by applications, such as Business Intelligence tools, using JDBC, the Beeswax query editor in Hue, and version 2.0 or higher of the Cloudera ODBC driver.
Impala Daemon	Impala Daemon Backend Port	22000	Internal	Internal use only. Impala daemons use this port to communicate with each other.
Impala Daemon	StateStoreSubscriber Service Port	23000	Internal	Internal use only. Impala daemons listen on this port for updates from the statestore daemon.
Catalog Daemon	StateStoreSubscriber Service Port	23020	Internal	Internal use only. The catalog daemon listens on this port for updates from the statestore daemon.
Impala Daemon	Impala Daemon HTTP Server Port	25000	External	Impala web interface for administrators to monitor and troubleshoot.
Impala StateStore Daemon	StateStore HTTP Server Port	25010	External	StateStore web interface for administrators to monitor and troubleshoot.
Impala Catalog Daemon	Catalog HTTP Server Port	25020	External	Catalog service web interface for administrators to monitor and troubleshoot. New in Impala 1.2 and higher.
Impala StateStore Daemon	StateStore Service Port	24000	Internal	Internal use only. The statestore daemon listens on this port for registration/unregistration requests.

Ports Used by Impala

Component	Service	Port	Access Requirement	Comment
Impala Catalog Daemon	Catalog Service Port	26000	Internal	Internal use only. The catalog service uses this port to communicate with the Impala daemons. New in Impala 1.2 and higher.
Impala Daemon	Llama Callback Port	28000	Internal	Internal use only. Impala daemons use to communicate with Llama. New in CDH 5.0.0 and higher.
Impala Llama ApplicationMaster	Llama Thrift Admin Port	15002	Internal	Internal use only. New in CDH 5.0.0 and higher.
Impala Llama ApplicationMaster	Llama Thrift Port	15000	Internal	Internal use only. New in CDH 5.0.0 and higher.
Impala Llama ApplicationMaster	Llama HTTP Port	15001	External	Llama service web interface for administrators to monitor and troubleshoot. New in CDH 5.0.0 and higher.

Impala Reserved Words

The following are the reserved words for the current release of Impala. A reserved word is one that cannot be used directly as an identifier; you must quote it with backticks. For example, a statement `CREATE TABLE select (x INT)` fails, while `CREATE TABLE `select` (x INT)` succeeds. Impala does not reserve the names of aggregate or scalar built-in functions. (Formerly, Impala did reserve the names of some aggregate functions.)

Because different database systems have different sets of reserved words, and the reserved words change from release to release, carefully consider database, table, and column names to ensure maximum compatibility between products and versions.

Because you might switch between Impala and Hive when doing analytics and ETL, also consider whether your object names are the same as any Hive keywords, and rename or quote any that conflict. Consult the [list of Hive keywords](#).

List of Current Reserved Words

```
add
aggregate
all
alter
analytic
and
anti
api_version
as
asc
avro
between
bigint
binary
boolean
buckets
by
cached
cascade
case
cast
change
char
class
close_fn
column
columns
comment
compute
create
cross
current
data
database
databases
date
datetime
decimal
delete
delimited
desc
describe
distinct
distribute
div
double
drop
else
end
```

Impala Reserved Words

```
escaped
exists
explain
extended
external
false
fields
fileformat
finalize_fn
first
float
following
for
format
formatted
from
full
function
functions
grant
group
hash
having
if
ignore
ilike
in
incremental
init_fn
inner
inpath
insert
int
integer
intermediate
interval
into
invalidate
iregexp
is
join
last
left
like
limit
lines
load
location
merge_fn
metadata
not
null
nulls
offset
on
or
order
outer
over
overwrite
parquet
parquetfile
partition
partitioned
partitions
preceding
prepare_fn
produced
purge
range
rcfile
real
refresh
```

```
regexp
rename
replace
restrict
returns
revoke
right
rlike
role
roles
row
rows
schema
schemas
select
semi
sequencefile
serdeproperties
serialize_fn
set
show
smallint
split
stats
stored
straight_join
string
symbol
table
tables
tblproperties
terminated
textfile
then
timestamp
tinyint
to
true
truncate
unbounded
uncached
union
update
update_fn
use
using
values
varchar
view
when
where
with
```

Planning for Future Reserved Words

The previous list of reserved words includes all the keywords used in the current level of Impala SQL syntax. To future-proof your code, you should avoid additional words in case they become reserved words if Impala adds features in later releases. This kind of planning can also help to avoid name conflicts in case you port SQL from other systems that have different sets of reserved words.

The following list contains additional words that Cloudera recommends avoiding for table, column, or other object names, even though they are not currently reserved by Impala.

```
any
authorization
backup
begin
break
```

Impala Reserved Words

```
browse
bulk
cascade
check
checkpoint
close
clustered
coalesce
collate
commit
constraint
contains
continue
convert
current
current_date
current_time
current_timestamp
current_user
cursor
dbcc
deallocate
declare
default
deny
disk
distributed
dump
errlvl
escape
except
exec
execute
exit
fetch
file
fillfactor
for
foreign
freetext
goto
holdlock
identity
index
intersect
key
kill
lineno
merge
national
nocheck
nonclustered
nullif
of
off
offsets
open
option
percent
pivot
plan
precision
primary
print
proc
procedure
public
raiserror
read
readtext
reconfigure
references
replication
```

```
restore
restrict
return
revert
rollback
rowcount
rule
save
securityaudit
session_user
setuser
shutdown
some
statistics
system_user
tablesample
textsize
then
top
tran
transaction
trigger
try_convert
unique
unpivot
updatetext
user
varying
waitfor
while
within
writetext
```

Impala Frequently Asked Questions

Here are the categories of frequently asked questions for Apache Impala, the interactive SQL engine included with CDH.

Transition to Apache Governance

Does "Apache Impala (incubating)" mean Impala is not production-ready?

No. The "(incubating)" label was only applied to the Apache Impala project while it was transitioning to governance by the Apache Software Foundation. Impala graduated to a top-level Apache project on November 15, 2017.

Impala has always been Apache-licensed. The software itself is the same production-ready and battle-tested analytic database that has been supported by Cloudera since Impala 1.0 in 2013.

Trying Impala

How do I try Impala out?

To look at the core features and functionality on Impala, the easiest way to try out Impala is to download the Cloudera QuickStart VM and start the Impala service through Cloudera Manager, then use `impala-shell` in a terminal window or the Impala Query UI in the Hue web interface.

To do performance testing and try out the management features for Impala on a cluster, you need to move beyond the QuickStart VM with its virtualized single-node environment. Ideally, download the Cloudera Manager software to set up the cluster, then install the Impala software through Cloudera Manager.

Does Cloudera offer a VM for demonstrating Impala?

Cloudera offers a demonstration VM called the QuickStart VM, available in VMWare, VirtualBox, and KVM formats. For more information, see [the Cloudera QuickStart VM](#). After booting the QuickStart VM, many services are turned off by default; in the Cloudera Manager UI that appears automatically, turn on Impala and any other components that you want to try out.

Where can I find Impala documentation?

Starting with Impala 1.3.0, Impala documentation is integrated with the CDH 5 documentation, in addition to the standalone Impala documentation for use with CDH 4. For CDH 5, the core Impala developer and administrator information remains in the associated [Impala documentation](#) portion. Information about Impala release notes, installation, configuration, startup, and security is embedded in the corresponding CDH 5 guides.

- [New features](#)
- [Known and fixed issues](#)
- [Incompatible changes](#)
- [Installing Impala](#)
- [Upgrading Impala](#)
- [Configuring Impala](#)
- [Starting Impala](#)
- [Security for Impala](#)
- [CDH Version and Packaging Information](#)

Information about the latest CDH 4-compatible Impala release remains at the [Impala for CDH 4 Documentation](#) page.

Where can I get more information about Impala?

More product information is available here:

- O'Reilly introductory e-book: [Cloudera Impala: Bringing the SQL and Hadoop Worlds Together](#)
- O'Reilly getting started guide for developers: [Getting Started with Impala: Interactive SQL for Apache Hadoop](#)
- Blog: [Cloudera Impala: Real-Time Queries in Apache Hadoop, For Real](#)
- Webinar: [Introduction to Impala](#)
- Product website page: [Cloudera Enterprise RTQ](#)

To see the latest release announcements for Impala, see the [Cloudera Announcements](#) forum.

How can I ask questions and provide feedback about Impala?

- Join the [Impala discussion forum](#) and the [Impala mailing list](#) to ask questions and provide feedback.
- Use the [Impala Jira project](#) to log bug reports and requests for features.

Where can I get sample data to try?

You can get scripts that produce data files and set up an environment for TPC-DS style benchmark tests from [this Github repository](#). In addition to being useful for experimenting with performance, the tables are suited to experimenting with many aspects of SQL on Impala: they contain a good mixture of data types, data distributions, partitioning, and relational data suitable for join queries.

Impala System Requirements

What are the software and hardware requirements for running Impala?

For information on Impala requirements, see [Impala Requirements](#) on page 24. Note that there is often a minimum required level of Cloudera Manager for any given Impala version.

How much memory is required?

Although Impala is not an in-memory database, when dealing with large tables and large result sets, you should expect to dedicate a substantial portion of physical memory for the `impalad` daemon. Recommended physical memory for an Impala node is 128 GB or higher. If practical, devote approximately 80% of physical memory to Impala.

The amount of memory required for an Impala operation depends on several factors:

- The file format of the table. Different file formats represent the same data in more or fewer data files. The compression and encoding for each file format might require a different amount of temporary memory to decompress the data for analysis.
- Whether the operation is a `SELECT` or an `INSERT`. For example, Parquet tables require relatively little memory to query, because Impala reads and decompresses data in 8 MB chunks. Inserting into a Parquet table is a more memory-intensive operation because the data for each data file (potentially hundreds of megabytes, depending on the value of the `PARQUET_FILE_SIZE` query option) is stored in memory until encoded, compressed, and written to disk.
- Whether the table is partitioned or not, and whether a query against a partitioned table can take advantage of partition pruning.
- Whether the final result set is sorted by the `ORDER BY` clause. Each Impala node scans and filters a portion of the total data, and applies the `LIMIT` to its own portion of the result set. In Impala 1.4.0 and higher, if the sort operation requires more memory than is available on any particular host, Impala uses a temporary disk work area to perform the sort. The intermediate result sets are all sent back to the coordinator node, which does the final sorting and then applies the `LIMIT` clause to the final result set.

Impala Frequently Asked Questions

For example, if you execute the query:

```
select * from giant_table order by some_column limit 1000;
```

and your cluster has 50 nodes, then each of those 50 nodes will transmit a maximum of 1000 rows back to the coordinator node. The coordinator node needs enough memory to sort (`LIMIT * cluster_size`) rows, although in the end the final result set is at most `LIMIT` rows, 1000 in this case.

Likewise, if you execute the query:

```
select * from giant_table where test_val > 100 order by some_column;
```

then each node filters out a set of rows matching the `WHERE` conditions, sorts the results (with no size limit), and sends the sorted intermediate rows back to the coordinator node. The coordinator node might need substantial memory to sort the final result set, and so might use a temporary disk work area for that final phase of the query.

- Whether the query contains any join clauses, `GROUP BY` clauses, analytic functions, or `DISTINCT` operators. These operations all require some in-memory work areas that vary depending on the volume and distribution of data. In Impala 2.0 and later, these kinds of operations utilize temporary disk work areas if memory usage grows too large to handle. See [SQL Operations that Spill to Disk](#) on page 562 for details.
- The size of the result set. When intermediate results are being passed around between nodes, the amount of data depends on the number of columns returned by the query. For example, it is more memory-efficient to query only the columns that are actually needed in the result set rather than always issuing `SELECT *`.
- The mechanism by which work is divided for a join query. You use the `COMPUTE STATS` statement, and query hints in the most difficult cases, to help Impala pick the most efficient execution plan. See [Performance Considerations for Join Queries](#) on page 526 for details.

See [Hardware Requirements](#) on page 25 for more details and recommendations about Impala hardware prerequisites.

What processor type and speed does Cloudera recommend?

Impala makes use of SSE 4.1 instructions.

What EC2 instances are recommended for Impala?

For large storage capacity and large I/O bandwidth, consider the `hs1.8xlarge` and `cc2.8xlarge` instance types. Impala I/O patterns typically do not benefit enough from SSD storage to make up for the lower overall size. For performance and security considerations for deploying CDH and its components on AWS, see [Cloudera Enterprise Reference Architecture for AWS Deployments](#).

Supported and Unsupported Functionality In Impala

What are the main features of Impala?

- A large set of SQL statements, including [SELECT](#) and [INSERT](#), with [joins](#), [Subqueries in Impala SELECT Statements](#) on page 322, and [Impala Analytic Functions](#) on page 470. Highly compatible with HiveQL, and also including some vendor extensions. For more information, see [Impala SQL Language Reference](#) on page 126.
- Distributed, high-performance queries. See [Tuning Impala for Performance](#) on page 523 for information about Impala performance optimizations and tuning techniques for queries.
- Using Cloudera Manager, you can deploy and manage your Impala services. Cloudera Manager is the best way to get started with Impala on your cluster.
- Using Hue for queries.
- Appending and inserting data into tables through the [INSERT](#) statement. See [How Impala Works with Hadoop File Formats](#) on page 575 for the details about which operations are supported for which file formats.

- ODBC: Impala is certified to run against MicroStrategy and Tableau, with restrictions. For more information, see [Configuring Impala to Work with ODBC](#) on page 33.
- Querying data stored in HDFS and HBase in a single query. See [Using Impala to Query HBase Tables](#) on page 608 for details.
- In Impala 2.2.0 and higher, querying data stored in the Amazon Simple Storage Service (S3). See [Using Impala with the Amazon S3 Filesystem](#) on page 617 for details.
- Concurrent client requests. Each Impala daemon can handle multiple concurrent client requests. The effects on performance depend on your particular hardware and workload.
- Kerberos authentication. For more information, see [Impala Security](#) on page 100.
- Partitions. With Impala SQL, you can create partitioned tables with the `CREATE TABLE` statement, and add and drop partitions with the `ALTER TABLE` statement. Impala also takes advantage of the partitioning present in Hive tables. See [Partitioning for Impala Tables](#) on page 568 for details.

What features from relational databases or Hive are not available in Impala?

- Querying streaming data.
- Deleting individual rows. You delete data in bulk by overwriting an entire table or partition, or by dropping a table.
- Indexing (not currently). LZO-compressed text files can be indexed outside of Impala, as described in [Using LZO-Compressed Text Files](#) on page 580.
- Full text search on text fields. The Cloudera Search product is appropriate for this use case.
- Custom Hive Serializer/Deserializer classes (SerDes). Impala supports a set of common native file formats that have built-in SerDes in CDH. See [How Impala Works with Hadoop File Formats](#) on page 575 for details.
- Checkpointing within a query. That is, Impala does not save intermediate results to disk during long-running queries. Currently, Impala cancels a running query if any host on which that query is executing fails. When one or more hosts are down, Impala reroutes future queries to only use the available hosts, and Impala detects when the hosts come back up and begins using them again. Because a query can be submitted through any Impala node, there is no single point of failure. In the future, we will consider adding additional work allocation features to Impala, so that a running query would complete even in the presence of host failures.
- Hive indexes.
- Non-Hadoop data stores, such as relational databases.

For the detailed list of features that are different between Impala and HiveQL, see [SQL Differences Between Impala and Hive](#) on page 502.

Does Impala support generic JDBC?

Impala supports the HiveServer2 JDBC driver.

Is Avro supported?

Yes, Avro is supported. Impala has always been able to query Avro tables. You can use the Impala `LOAD DATA` statement to load existing Avro data files into a table. Starting with Impala 1.4, you can create Avro tables with Impala. Currently, you still use the `INSERT` statement in Hive to copy data from another table into an Avro table. See [Using the Avro File Format with Impala Tables](#) on page 597 for details.

How do I?

How do I prevent users from seeing the text of SQL queries?

For instructions on making the Impala log files unreadable by unprivileged users, see [Securing Impala Data and Log Files](#) on page 101.

For instructions on password-protecting the web interface to the Impala log files and other internal server information, see [Securing the Impala Web User Interface](#) on page 102.

Impala Frequently Asked Questions

In Impala 2.2 / CDH 5.4 and higher, you can use the log redaction feature to obfuscate sensitive information in Impala log files. See http://www.cloudera.com/documentation/enterprise/latest/topics/sg_redaction.html for details.

How do I know how many Impala nodes are in my cluster?

The Impala statestore keeps track of how many `impalad` nodes are currently available. You can see this information through the statestore web interface. For example, at the URL `http://statestore_host:25010/metrics` you might see lines like the following:

```
statestore.live-backends:3
statestore.live-backends.list:[host1:22000, host1:26000, host2:22000]
```

The number of `impalad` nodes is the number of list items referring to port 22000, in this case two. (Typically, this number is one less than the number reported by the `statestore.live-backends` line.) If an `impalad` node became unavailable or came back after an outage, the information reported on this page would change appropriately.

Impala Performance

Are results returned as they become available, or all at once when a query completes?

Impala streams results whenever they are available, when possible. Certain SQL operations (aggregation or `ORDER BY`) require all of the input to be ready before Impala can return results.

Why does my query run slowly?

There are many possible reasons why a given query could be slow. Use the following checklist to diagnose performance issues with existing queries, and to avoid such issues when writing new queries, setting up new nodes, creating new tables, or loading data.

- Immediately after the query finishes, issue a `SUMMARY` command in `impala-shell`. You can check which phases of execution took the longest, and compare estimated values for memory usage and number of rows with the actual values.
- Immediately after the query finishes, issue a `PROFILE` command in `impala-shell`. The numbers in the `BytesRead`, `BytesReadLocal`, and `BytesReadShortCircuit` should be identical for a specific node. For example:

```
- BytesRead: 180.33 MB
- BytesReadLocal: 180.33 MB
- BytesReadShortCircuit: 180.33 MB
```

If `BytesReadLocal` is lower than `BytesRead`, something in your cluster is misconfigured, such as the `impalad` daemon not running on all the data nodes. If `BytesReadShortCircuit` is lower than `BytesRead`, short-circuit reads are not enabled properly on that node; see [Post-Installation Configuration for Impala](#) on page 32 for instructions.

- If the table was just created, or this is the first query that accessed the table after an `INVALIDATE METADATA` statement or after the `impalad` daemon was restarted, there might be a one-time delay while the metadata for the table is loaded and cached. Check whether the slowdown disappears when the query is run again. When doing performance comparisons, consider issuing a `DESCRIBE table_name` statement for each table first, to make sure any timings only measure the actual query time and not the one-time wait to load the table metadata.
- Is the table data in uncompressed text format? Check by issuing a `DESCRIBE FORMATTED table_name` statement. A text table is indicated by the line:

```
InputFormat: org.apache.hadoop.mapred.TextInputFormat
```

Although uncompressed text is the default format for a `CREATE TABLE` statement with no `STORED AS` clauses, it is also the bulkiest format for disk storage and consequently usually the slowest format for queries. For data where query performance is crucial, particularly for tables that are frequently queried, consider starting with or

converting to a compact binary file format such as Parquet, Avro, RCFile, or SequenceFile. For details, see [How Impala Works with Hadoop File Formats](#) on page 575.

- If your table has many columns, but the query refers to only a few columns, consider using the Parquet file format. Its data files are organized with a column-oriented layout that lets queries minimize the amount of I/O needed to retrieve, filter, and aggregate the values for specific columns. See [Using the Parquet File Format with Impala Tables](#) on page 584 for details.
- If your query involves any joins, are the tables in the query ordered so that the tables or subqueries are ordered with the one returning the largest number of rows on the left, followed by the smallest (most selective), the second smallest, and so on? That ordering allows Impala to optimize the way work is distributed among the nodes and how intermediate results are routed from one node to another. For example, all other things being equal, the following join order results in an efficient query:

```
select some_col from
  huge_table join big_table join small_table join medium_table
where
  huge_table.id = big_table.id
  and big_table.id = medium_table.id
  and medium_table.id = small_table.id;
```

See [Performance Considerations for Join Queries](#) on page 526 for performance tips for join queries.

- Also for join queries, do you have table statistics for the table, and column statistics for the columns used in the join clauses? Column statistics let Impala better choose how to distribute the work for the various pieces of a join query. See [Table and Column Statistics](#) on page 533 for details about gathering statistics.
- Does your table consist of many small data files? Impala works most efficiently with data files in the multi-megabyte range; Parquet, a format optimized for data warehouse-style queries, uses large files (originally 1 GB, now 256 MB in Impala 2.0 and higher) with a block size matching the file size. Use the `DESCRIBE FORMATTED table_name` statement in `impala-shell` to see where the data for a table is located, and use the `hadoop fs -ls` or `hdfs dfs -ls` Unix commands to see the files and their sizes. If you have thousands of small data files, that is a signal that you should consolidate into a smaller number of large files. Use an `INSERT ... SELECT` statement to copy the data to a new table, reorganizing into new data files as part of the process. Prefer to construct large data files and import them in bulk through the `LOAD DATA` or `CREATE EXTERNAL TABLE` statements, rather than issuing many `INSERT ... VALUES` statements; each `INSERT ... VALUES` statement creates a separate tiny data file. If you have thousands of files all in the same directory, but each one is megabytes in size, consider using a partitioned table so that each partition contains a smaller number of files. See the following point for more on partitioning.
- If your data is easy to group according to time or geographic region, have you partitioned your table based on the corresponding columns such as `YEAR`, `MONTH`, and/or `DAY`? Partitioning a table based on certain columns allows queries that filter based on those same columns to avoid reading the data files for irrelevant years, postal codes, and so on. (Do not partition down to too fine a level; try to structure the partitions so that there is still sufficient data in each one to take advantage of the multi-megabyte HDFS block size.) See [Partitioning for Impala Tables](#) on page 568 for details.

Why does my SELECT statement fail?

When a `SELECT` statement fails, the cause usually falls into one of the following categories:

- A timeout because of a performance, capacity, or network issue affecting one particular node.
- Excessive memory use for a join query, resulting in automatic cancellation of the query.
- A low-level issue affecting how native code is generated on each node to handle particular `WHERE` clauses in the query. For example, a machine instruction could be generated that is not supported by the processor of a certain node. If the error message in the log suggests the cause was an illegal instruction, consider turning off native code generation temporarily, and trying the query again.
- Malformed input data, such as a text data file with an enormously long line, or with a delimiter that does not match the character specified in the `FIELDS TERMINATED BY` clause of the `CREATE TABLE` statement.

Impala Frequently Asked Questions

Why does my INSERT statement fail?

When an `INSERT` statement fails, it is usually the result of exceeding some limit within a Hadoop component, typically HDFS.

- An `INSERT` into a partitioned table can be a strenuous operation due to the possibility of opening many files and associated threads simultaneously in HDFS. Impala 1.1.1 includes some improvements to distribute the work more efficiently, so that the values for each partition are written by a single node, rather than as a separate data file from each node.
- Certain expressions in the `SELECT` part of the `INSERT` statement can complicate the execution planning and result in an inefficient `INSERT` operation. Try to make the column data types of the source and destination tables match up, for example by doing `ALTER TABLE ... REPLACE COLUMNS` on the source table if necessary. Try to avoid `CASE` expressions in the `SELECT` portion, because they make the result values harder to predict than transferring a column unchanged or passing the column through a built-in function.
- Be prepared to raise some limits in the HDFS configuration settings, either temporarily during the `INSERT` or permanently if you frequently run such `INSERT` statements as part of your ETL pipeline.
- The resource usage of an `INSERT` statement can vary depending on the file format of the destination table. Inserting into a Parquet table is memory-intensive, because the data for each partition is buffered in memory until it reaches 1 gigabyte, at which point the data file is written to disk. Impala can distribute the work for an `INSERT` more efficiently when statistics are available for the source table that is queried during the `INSERT` statement. See [Table and Column Statistics](#) on page 533 for details about gathering statistics.

Does Impala performance improve as it is deployed to more hosts in a cluster in much the same way that Hadoop performance does?

Yes. Impala scales with the number of hosts. It is important to install Impala on all the DataNodes in the cluster, because otherwise some of the nodes must do remote reads to retrieve data not available for local reads. Data locality is an important architectural aspect for Impala performance. See [this Impala performance blog post](#) for background. Note that this blog post refers to benchmarks with Impala 1.1.1; Impala has added even more performance features in the 1.2.x series.

Is the HDFS block size reduced to achieve faster query results?

No. Impala does not make any changes to the HDFS or HBase data sets.

The default Parquet block size is relatively large (256 MB in Impala 2.0 and later; 1 GB in earlier releases). You can control the block size when creating Parquet files using the `PARQUET_FILE_SIZE` query option.

Does Impala use caching?

Impala does not cache table data. It does cache some table and file metadata. Although queries might run faster on subsequent iterations because the data set was cached in the OS buffer cache, Impala does not explicitly control this.

Impala takes advantage of the HDFS caching feature in CDH 5. You can designate which tables or partitions are cached through the `CACHED` and `UNCACHED` clauses of the `CREATE TABLE` and `ALTER TABLE` statements. Impala can also take advantage of data that is pinned in the HDFS cache through the `hdfs-cache-admin` command. See [Using HDFS Caching with Impala \(CDH 5.1 or higher only\)](#) on page 550 for details.

Impala Use Cases

What are good use cases for Impala as opposed to Hive or MapReduce?

Impala is well-suited to executing SQL queries for interactive exploratory analytics on large data sets. Hive and MapReduce are appropriate for very long running, batch-oriented tasks such as ETL.

Is MapReduce required for Impala? Will Impala continue to work as expected if MapReduce is stopped?

Impala does not use MapReduce at all.

Can Impala be used for complex event processing?

For example, in an industrial environment, many agents may generate large amounts of data. Can Impala be used to analyze this data, checking for notable changes in the environment?

Complex Event Processing (CEP) is usually performed by dedicated stream-processing systems. Impala is not a stream-processing system, as it most closely resembles a relational database.

Is Impala intended to handle real time queries in low-latency applications or is it for ad hoc queries for the purpose of data exploration?

Ad-hoc queries are the primary use case for Impala. We anticipate it being used in many other situations where low-latency is required. Whether Impala is appropriate for any particular use-case depends on the workload, data size and query volume. See [Impala Benefits](#) on page 17 for the primary benefits you can expect when using Impala.

Questions about Impala And Hive

How does Impala compare to Hive and Pig?

Impala is different from Hive and Pig because it uses its own daemons that are spread across the cluster for queries. Because Impala does not rely on MapReduce, it avoids the startup overhead of MapReduce jobs, allowing Impala to return results in real time.

Can I do transforms or add new functionality?

Impala adds support for UDFs in Impala 1.2. You can write your own functions in C++, or reuse existing Java-based Hive UDFs. The UDF support includes scalar functions and user-defined aggregate functions (UDAs). User-defined table functions (UDTFs) are not currently supported.

Impala does not currently support an extensible serialization-deserialization framework (SerDes), and so adding extra functionality to Impala is not as straightforward as for Hive or Pig.

Can any Impala query also be executed in Hive?

Yes. There are some minor differences in how some queries are handled, but Impala queries can also be completed in Hive. Impala SQL is a subset of HiveQL, with some functional limitations such as transforms. For details of the Impala SQL dialect, see [Impala SQL Statements](#) on page 228. For the Impala built-in functions, see [Impala Built-In Functions](#) on page 373. For the detailed list of differences between Impala and HiveQL, see [SQL Differences Between Impala and Hive](#) on page 502.

Can I use Impala to query data already loaded into Hive and HBase?

There are no additional steps to allow Impala to query tables managed by Hive, whether they are stored in HDFS or HBase. Make sure that Impala is configured to access the Hive metastore correctly and you should be ready to go. Keep in mind that `impalad`, by default, runs as the `impala` user, so you might need to adjust some file permissions depending on how strict your permissions are currently.

See [Using Impala to Query HBase Tables](#) on page 608 for details about querying data in HBase.

Is Hive an Impala requirement?

The Hive metastore service is a requirement. Impala shares the same metastore database as Hive, allowing Impala and Hive to access the same tables transparently.

Hive itself is optional, and does not need to be installed on the same nodes as Impala. Currently, Impala supports a wider variety of read (query) operations than write (insert) operations; you use Hive to insert data into tables that use certain file formats. See [How Impala Works with Hadoop File Formats](#) on page 575 for details.

Impala Availability

Is Impala production ready?

Impala has finished its beta release cycle, and the 1.0, 1.1, and 1.2 GA releases are production ready. The 1.1.x series includes additional security features for authorization, an important requirement for production use in many organizations. The 1.2.x series includes important performance features, particularly for large join queries. Some Cloudera customers are already using Impala for large workloads.

The Impala 1.3.0 and higher releases are bundled with corresponding levels of CDH 5. The number of new features grows with each release. See [New Features in Apache Impala](#) on page 660 for a full list.

How do I configure Hadoop high availability (HA) for Impala?

You can set up a proxy server to relay requests back and forth to the Impala servers, for load balancing and high availability. See [Using Impala through a Proxy for High Availability](#) on page 93 for details.

You can enable HDFS HA for the Hive metastore. See the [CDH5 High Availability Guide](#) for details.

What happens if there is an error in Impala?

There is not a single point of failure in Impala. All Impala daemons are fully able to handle incoming queries. If a machine fails however, all queries with fragments running on that machine will fail. Because queries are expected to return quickly, you can just rerun the query if there is a failure. See [Impala Concepts and Architecture](#) on page 19 for details about the Impala architecture.

The longer answer: Impala must be able to connect to the Hive metastore. Impala aggressively caches metadata so the metastore host should have minimal load. Impala relies on the HDFS NameNode, and, in CDH4, you can configure HA for HDFS. Impala also has centralized services, known as the [statestore](#) and [catalog](#) services, that run on one host only. Impala continues to execute queries if the statestore host is down, but it will not get state updates. For example, if a host is added to the cluster while the statestore host is down, the existing instances of `impalad` running on the other hosts will not find out about this new host. Once the statestore process is restarted, all the information it serves is automatically reconstructed from all running Impala daemons.

What is the maximum number of rows in a table?

There is no defined maximum. Some customers have used Impala to query a table with over a trillion rows.

Can Impala and MapReduce jobs run on the same cluster without resource contention?

Yes. See [Controlling Impala Resource Usage](#) on page 545 for how to control Impala resource usage using the Linux cgroup mechanism, and [Resource Management for Impala](#) on page 85 for how to use Impala with the YARN resource management framework. Impala is designed to run on the DataNode hosts. Any contention depends mostly on the cluster setup and workload.

For a detailed information about configuring a cluster to share resources between Impala queries and MapReduce jobs, see [How to Configure Resource Management for Impala](#) on page 86.

Impala Internals

On which hosts does Impala run?

Cloudera strongly recommends running the `impalad` daemon on each DataNode for good performance. Although this topology is not a hard requirement, if there are data blocks with no Impala daemons running on any of the hosts containing replicas of those blocks, queries involving that data could be very inefficient. In that case, the data must be transmitted from one host to another for processing by “remote reads”, a condition Impala normally tries to avoid.

See [Impala Concepts and Architecture](#) on page 19 for details about the Impala architecture. Impala schedules query fragments on all hosts holding data relevant to the query, if possible.

In cases where some hosts in the cluster have much greater CPU and memory capacity than others, or where some hosts have extra CPU capacity because some CPU-intensive phases are single-threaded, some users have run multiple `impalad` daemons on a single host to take advantage of the extra CPU capacity. This configuration is only practical for specific workloads that rely heavily on aggregation, and the physical hosts must have sufficient memory to accommodate the requirements for multiple `impalad` instances.

How are joins performed in Impala?

By default, Impala automatically determines the most efficient order in which to join tables using a cost-based method, based on their overall size and number of rows. (This is a new feature in Impala 1.2.2 and higher.) The `COMPUTE STATS` statement gathers information about each table that is crucial for efficient join performance. Impala chooses between two techniques for join queries, known as “broadcast joins” and “partitioned joins”. See [Joins in Impala SELECT Statements](#) on page 306 for syntax details and [Performance Considerations for Join Queries](#) on page 526 for performance considerations.

How does Impala process join queries for large tables?

Impala utilizes multiple strategies to allow joins between tables and result sets of various sizes. When joining a large table with a small one, the data from the small table is transmitted to each node for intermediate processing. When joining two large tables, the data from one of the tables is divided into pieces, and each node processes only selected pieces. See [Joins in Impala SELECT Statements](#) on page 306 for details about join processing, [Performance Considerations for Join Queries](#) on page 526 for performance considerations, and [Query Hints in Impala SELECT Statements](#) on page 326 for how to fine-tune the join strategy.

What is Impala's aggregation strategy?

Impala currently only supports in-memory hash aggregation. In Impala 2.0 and higher, if the memory requirements for a join or aggregation operation exceed the memory limit for a particular host, Impala uses a temporary work area on disk to help the query complete successfully.

How is Impala metadata managed?

Impala uses two pieces of metadata: the catalog information from the Hive metastore and the file metadata from the NameNode. Currently, this metadata is lazily populated and cached when an `impalad` needs it to plan a query.

The `REFRESH` statement updates the metadata for a particular table after loading new data through Hive. The [INVALIDATE METADATA Statement](#) on page 294 statement refreshes all metadata, so that Impala recognizes new tables or other DDL and DML changes performed through Hive.

In Impala 1.2 and higher, a dedicated `catalogd` daemon broadcasts metadata changes due to Impala DDL or DML statements to all nodes, reducing or eliminating the need to use the `REFRESH` and `INVALIDATE METADATA` statements.

What load do concurrent queries produce on the NameNode?

The load Impala generates is very similar to MapReduce. Impala contacts the NameNode during the planning phase to get the file metadata (this is only run on the host the query was sent to). Every `impalad` will read files as part of normal processing of the query.

How does Impala achieve its performance improvements?

These are the main factors in the performance of Impala versus that of other Hadoop components and related technologies.

Impala avoids MapReduce. While MapReduce is a great general parallel processing model with many benefits, it is not designed to execute SQL. Impala avoids the inefficiencies of MapReduce in these ways:

Impala Frequently Asked Questions

- Impala does not materialize intermediate results to disk. SQL queries often map to multiple MapReduce jobs with all intermediate data sets written to disk.
- Impala avoids MapReduce start-up time. For interactive queries, the MapReduce start-up time becomes very noticeable. Impala runs as a service and essentially has no start-up time.
- Impala can more naturally disperse query plans instead of having to fit them into a pipeline of map and reduce jobs. This enables Impala to parallelize multiple stages of a query and avoid overheads such as sort and shuffle when unnecessary.

Impala uses a more efficient execution engine by taking advantage of modern hardware and technologies:

- Impala generates runtime code. Impala uses LLVM to generate assembly code for the query that is being run. Individual queries do not have to pay the overhead of running on a system that needs to be able to execute arbitrary queries.
- Impala uses available hardware instructions when possible. Impala uses the supplemental SSE3 (SSSE3) instructions which can offer tremendous speedups in some cases. (Impala 2.0 and 2.1 required the SSE4.1 instruction set; Impala 2.2 and higher relax the restriction again so only SSSE3 is required.)
- Impala uses better I/O scheduling. Impala is aware of the disk location of blocks and is able to schedule the order to process blocks to keep all disks busy.
- Impala is designed for performance. A lot of time has been spent in designing Impala with sound performance-oriented fundamentals, such as tight inner loops, inlined function calls, minimal branching, better use of cache, and minimal memory usage.

What happens when the data set exceeds available memory?

Currently, if the memory required to process intermediate results on a node exceeds the amount available to Impala on that node, the query is cancelled. You can adjust the memory available to Impala on each node, and you can fine-tune the join strategy to reduce the memory required for the biggest queries. We do plan on supporting external joins and sorting in the future.

Keep in mind though that the memory usage is not directly based on the input data set size. For aggregations, the memory usage is the number of rows *after* grouping. For joins, the memory usage is the combined size of the tables *excluding* the biggest table, and Impala can use join strategies that divide up large joined tables among the various nodes rather than transmitting the entire table to each node.

What are the most memory-intensive operations?

If a query fails with an error indicating “memory limit exceeded”, you might suspect a memory leak. The problem could actually be a query that is structured in a way that causes Impala to allocate more memory than you expect, exceeded the memory allocated for Impala on a particular node. Some examples of query or table structures that are especially memory-intensive are:

- `INSERT` statements using dynamic partitioning, into a table with many different partitions. (Particularly for tables using Parquet format, where the data for each partition is held in memory until it reaches the full block size in size before it is written to disk.) Consider breaking up such operations into several different `INSERT` statements, for example to load data one year at a time rather than for all years at once.
- `GROUP BY` on a unique or high-cardinality column. Impala allocates some handler structures for each different value in a `GROUP BY` query. Having millions of different `GROUP BY` values could exceed the memory limit.
- Queries involving very wide tables, with thousands of columns, particularly with many `STRING` columns. Because Impala allows a `STRING` value to be up to 32 KB, the intermediate results during such queries could require substantial memory allocation.

When does Impala hold on to or return memory?

Impala allocates memory using `tcmalloc`, a memory allocator that is optimized for high concurrency. Once Impala allocates memory, it keeps that memory reserved to use for future queries. Thus, it is normal for Impala to show high memory usage when idle. If Impala detects that it is about to exceed its memory limit (defined by the `-mem_limit` startup option or the `MEM_LIMIT` query option), it deallocates memory not needed by the current queries.

When issuing queries through the JDBC or ODBC interfaces, make sure to call the appropriate close method afterwards. Otherwise, some memory associated with the query is not freed.

SQL

Is there an UPDATE statement?

Impala does not currently have an `UPDATE` statement, which would typically be used to change a single row, a small group of rows, or a specific column. The HDFS-based files used by typical Impala queries are optimized for bulk operations across many megabytes of data at a time, making traditional `UPDATE` operations inefficient or impractical.

You can use the following techniques to achieve the same goals as the familiar `UPDATE` statement, in a way that preserves efficient file layouts for subsequent queries:

- Replace the entire contents of a table or partition with updated data that you have already staged in a different location, either using `INSERT OVERWRITE`, `LOAD DATA`, or manual HDFS file operations followed by a `REFRESH` statement for the table. Optionally, you can use built-in functions and expressions in the `INSERT` statement to transform the copied data in the same way you would normally do in an `UPDATE` statement, for example to turn a mixed-case string into all uppercase or all lowercase.
- To update a single row, use an HBase table, and issue an `INSERT ... VALUES` statement using the same key as the original row. Because HBase handles duplicate keys by only returning the latest row with a particular key value, the newly inserted row effectively hides the previous one.

Can Impala do user-defined functions (UDFs)?

Impala 1.2 and higher does support UDFs and UDAs. You can either write native Impala UDFs and UDAs in C++, or reuse UDFs (but not UDAs) originally written in Java for use with Hive. See [Impala User-Defined Functions \(UDFs\)](#) on page 487 for details.

Why do I have to use REFRESH and INVALIDATE METADATA, what do they do?

In Impala 1.2 and higher, there is much less need to use the `REFRESH` and `INVALIDATE METADATA` statements:

- The new `impala-catalog` service, represented by the `catalogd` daemon, broadcasts the results of Impala DDL statements to all Impala nodes. Thus, if you do a `CREATE TABLE` statement in Impala while connected to one node, you do not need to do `INVALIDATE METADATA` before issuing queries through a different node.
- The catalog service only recognizes changes made through Impala, so you must still issue a `REFRESH` statement if you load data through Hive or by manipulating files in HDFS, and you must issue an `INVALIDATE METADATA` statement if you create a table, alter a table, add or drop partitions, or do other DDL statements in Hive.
- Because the catalog service broadcasts the results of `REFRESH` and `INVALIDATE METADATA` statements to all nodes, in the cases where you do still need to issue those statements, you can do that on a single node rather than on every node, and the changes will be automatically recognized across the cluster, making it more convenient to load balance by issuing queries through arbitrary Impala nodes rather than always using the same coordinator node.

Why is space not freed up when I issue DROP TABLE?

Impala deletes data files when you issue a `DROP TABLE` on an internal table, but not an external one. By default, the `CREATE TABLE` statement creates internal tables, where the files are managed by Impala. An external table is created with a `CREATE EXTERNAL TABLE` statement, where the files reside in a location outside the control of Impala. Issue a `DESCRIBE FORMATTED` statement to check whether a table is internal or external. The keyword `MANAGED_TABLE` indicates an internal table, from which Impala can delete the data files. The keyword `EXTERNAL_TABLE` indicates an external table, where Impala will leave the data files untouched when you drop the table.

Even when you drop an internal table and the files are removed from their original location, you might not get the hard drive space back immediately. By default, files that are deleted in HDFS go into a special trashcan directory, from which they are purged after a period of time (by default, 6 hours). For background information on the trashcan

Impala Frequently Asked Questions

mechanism, see <https://archive.cloudera.com/cdh4/cdh/4/hadoop/hadoop-project-dist/hadoop-hdfs/HdfsDesign.html>. For information on purging files from the trashcan, see <https://archive.cloudera.com/cdh4/cdh/4/hadoop/hadoop-project-dist/hadoop-common/FileSystemShell.html>.

When Impala deletes files and they are moved to the HDFS trashcan, they go into an HDFS directory owned by the `impala` user. If the `impala` user does not have an HDFS home directory where a trashcan can be created, the files are not deleted or moved, as a safety measure. If you issue a `DROP TABLE` statement and find that the table data files are left in their original location, create an HDFS directory `/user/impala`, owned and writeable by the `impala` user. For example, you might find that `/user/impala` is owned by the `hdfs` user, in which case you would switch to the `hdfs` user and issue a command such as:

```
hdfs dfs -chown -R impala /user/impala
```

Is there a DUAL table?

You might be used to running queries against a single-row table named `DUAL` to try out expressions, built-in functions, and UDFs. Impala does not have a `DUAL` table. To achieve the same result, you can issue a `SELECT` statement without any table name:

```
select 2+2;
select substr('hello',2,1);
select pow(10,6);
```

Partitioned Tables

How do I load a big CSV file into a partitioned table?

To load a data file into a partitioned table, when the data file includes fields like year, month, and so on that correspond to the partition key columns, use a two-stage process. First, use the `LOAD DATA` or `CREATE EXTERNAL TABLE` statement to bring the data into an unpartitioned text table. Then use an `INSERT ... SELECT` statement to copy the data from the unpartitioned table to a partitioned one. Include a `PARTITION` clause in the `INSERT` statement to specify the partition key columns. The `INSERT` operation splits up the data into separate data files for each partition. For examples, see [Partitioning for Impala Tables](#) on page 568. For details about loading data into partitioned Parquet tables, a popular choice for high-volume data, see [Loading Data into Parquet Tables](#) on page 585.

Can I do INSERT ... SELECT * into a partitioned table?

When you use the `INSERT ... SELECT *` syntax to copy data into a partitioned table, the columns corresponding to the partition key columns must appear last in the columns returned by the `SELECT *`. You can create the table with the partition key columns defined last. Or, you can use the `CREATE VIEW` statement to create a view that reorders the columns: put the partition key columns last, then do the `INSERT ... SELECT *` from the view.

HBase

What kinds of Impala queries or data are best suited for HBase?

HBase tables are ideal for queries where normally you would use a key-value store. That is, where you retrieve a single row or a few rows, by testing a special unique key column using the `=` or `IN` operators.

HBase tables are not suitable for queries that produce large result sets with thousands of rows. HBase tables are also not suitable for queries that perform full table scans because the `WHERE` clause does not request specific values from the unique key column.

Use HBase tables for data that is inserted one row or a few rows at a time, such as by the `INSERT . . . VALUES` syntax. Loading data piecemeal like this into an HDFS-backed table produces many tiny files, which is a very inefficient layout for HDFS data files.

If the lack of an `UPDATE` statement in Impala is a problem for you, you can simulate single-row updates by doing an `INSERT . . . VALUES` statement using an existing value for the key column. The old row value is hidden; only the new row value is seen by queries.

HBase tables are often wide (containing many columns) and sparse (with most column values `NULL`). For example, you might record hundreds of different data points for each user of an online service, such as whether the user had registered for an online game or enabled particular account features. With Impala and HBase, you could look up all the information for a specific customer efficiently in a single query. For any given customer, most of these columns might be `NULL`, because a typical customer might not make use of most features of an online service.

Impala Release Notes

These release notes provide information on the [new features](#) and [known issues and limitations](#) for Impala versions up to Impala 2.7.x / CDH 5.9.x. For users upgrading from earlier Impala releases, or using Impala in combination with specific versions of other Cloudera software, [Incompatible Changes and Limitations in Apache Impala](#) on page 686 lists any changes to file formats, SQL syntax, or software dependencies to take into account.

Once you are finished reviewing these release notes, for more information about using Impala, see <http://www.cloudera.com/documentation/enterprise/latest/topics/impala.html>.

Impala Release Notes

These release notes provide information on the [new features](#) and [known issues and limitations](#) for Impala versions up to Impala 2.7.x / CDH 5.9.x. For users upgrading from earlier Impala releases, or using Impala in combination with specific versions of other Cloudera software, [Incompatible Changes and Limitations in Apache Impala](#) on page 686 lists any changes to file formats, SQL syntax, or software dependencies to take into account.

Once you are finished reviewing these release notes, for more information about using Impala, see <http://www.cloudera.com/documentation/enterprise/latest/topics/impala.html>.

New Features in Apache Impala

This release of Impala contains the following changes and enhancements from previous releases.

New Features in Impala 2.7.x / CDH 5.9.x

- Performance improvements:
 - [\[IMPALA-3206\]](#) Speedup for queries against `DECIMAL` columns in Avro tables. The code that parses `DECIMAL` values from Avro now uses native code generation.
 - [\[IMPALA-3674\]](#) Improved efficiency in LLVM code generation can reduce codegen time, especially for short queries.
 - [\[IMPALA-2979\]](#) Improvements to scheduling on worker nodes, enabled by the `REPLICA_PREFERENCE` query option. See [REPLICA_PREFERENCE Query Option \(CDH 5.9 or higher only\)](#) on page 351 for details.
- [\[IMPALA-1683\]](#) The `REFRESH` statement can be applied to a single partition, rather than the entire table. See [REFRESH Statement](#) on page 300 and [Refreshing a Single Partition](#) on page 569 for details.
- Improvements to the Impala web user interface:
 - [\[IMPALA-2767\]](#) You can now force a session to expire by clicking a link in the web UI, on the `/sessions` tab.
 - [\[IMPALA-3715\]](#) The `/memz` tab includes more information about Impala memory usage.
 - [\[IMPALA-3716\]](#) The `Details` page for a query now includes a **Memory** tab.
- [\[IMPALA-3499\]](#) Scalability improvements to the catalog server. Impala handles internal communication more efficiently for tables with large numbers of columns and partitions, where the size of the metadata exceeds 2 GiB.
- [\[IMPALA-3677\]](#) You can send a `SIGUSR1` signal to any Impala-related daemon to write a Breakpad minidump. For advanced troubleshooting, you can now produce a minidump without triggering a crash. See [Breakpad Minidumps for Impala \(CDH 5.8 or higher only\)](#) on page 636 for details about the Breakpad minidump feature.
- [\[IMPALA-3687\]](#) The schema reconciliation rules for Avro tables have changed slightly for `CHAR` and `VARCHAR` columns. Now, if the definition of such a column is changed in the Avro schema file, the column retains its `CHAR`

or `VARCHAR` type as specified in the SQL definition, but the column name and comment from the Avro schema file take precedence. See [Creating Avro Tables](#) on page 597 for details about column definitions in Avro tables.

- [\[IMPALA-3575\]](#) Some network operations now have additional timeout and retry settings. The extra configuration helps avoid failed queries for transient network problems, to avoid hangs when a sender or receiver fails in the middle of a network transmission, and to make cancellation requests more reliable despite network issues.

New Features in Impala 2.6.x / CDH 5.8.x

- Improvements to Impala support for the Amazon S3 filesystem:
 - Impala can now write to S3 tables through the `INSERT` or `LOAD DATA` statements. See [Using Impala with the Amazon S3 Filesystem](#) on page 617 for general information about using Impala with S3.
 - A new query option, `S3_SKIP_INSERT_STAGING`, lets you trade off between fast `INSERT` performance and slower `INSERTS` that are more consistent if a problem occurs during the statement. The new behavior is enabled by default. See [S3_SKIP_INSERT_STAGING Query Option \(CDH 5.8 or higher only\)](#) on page 354 for details about this option.
- Performance improvements for the runtime filtering feature:
 - The default for the `RUNTIME_FILTER_MODE` query option is changed to `GLOBAL` (the highest setting). See [RUNTIME_FILTER_MODE Query Option \(CDH 5.7 or higher only\)](#) on page 353 for details about this option.
 - The `RUNTIME_BLOOM_FILTER_SIZE` setting is now only used as a fallback if statistics are not available; otherwise, Impala uses the statistics to estimate the appropriate size to use for each filter. See [RUNTIME_BLOOM_FILTER_SIZE Query Option \(CDH 5.7 or higher only\)](#) on page 351 for details about this option.
 - New query options `RUNTIME_FILTER_MIN_SIZE` and `RUNTIME_FILTER_MAX_SIZE` let you fine-tune the sizes of the Bloom filter structures used for runtime filtering. If the filter size derived from Impala internal estimates or from the `RUNTIME_FILTER_BLOOM_SIZE` falls outside the size range specified by these options, any too-small filter size is adjusted to the minimum, and any too-large filter size is adjusted to the maximum. See [RUNTIME_FILTER_MIN_SIZE Query Option \(CDH 5.8 or higher only\)](#) on page 353 and [RUNTIME_FILTER_MAX_SIZE Query Option \(CDH 5.8 or higher only\)](#) on page 352 for details about these options.
 - Runtime filter propagation now applies to all the operands of `UNION` and `UNION ALL` operators.
 - Runtime filters can now be produced during join queries even when the join processing activates the spill-to-disk mechanism.

See [Runtime Filtering for Impala Queries](#) on page 545 for general information about the runtime filtering feature.

- Admission control and dynamic resource pools are enabled by default. See [Admission Control and Query Queuing](#) on page 77 for details about admission control.
- Impala can now manually set column statistics, using the `ALTER TABLE` statement with a `SET COLUMN STATS` clause. See [Setting Column Stats Manually through ALTER TABLE](#) on page 541 for details.
- Impala can now write lightweight “minidump” files, rather than large core files, to save diagnostic information when any of the Impala-related daemons crash. This feature uses the open source `breakpad` framework. See [Breakpad Minidumps for Impala \(CDH 5.8 or higher only\)](#) on page 636 for details.
- New query options improve interoperability with Parquet files:
 - The `PARQUET_FALLBACK_SCHEMA_RESOLUTION` query option lets Impala locate columns within Parquet files based on column name rather than ordinal position. This enhancement improves interoperability with applications that write Parquet files with a different order or subset of columns than are used in the Impala table. See [PARQUET_FALLBACK_SCHEMA_RESOLUTION Query Option \(CDH 5.8 or higher only\)](#) on page 349 for details.

- The `PARQUET_ANNOTATE_STRINGS_UTF8` query option makes Impala include the UTF-8 annotation metadata for `STRING`, `CHAR`, and `VARCHAR` columns in Parquet files created by `INSERT` or `CREATE TABLE AS SELECT` statements. See [PARQUET_ANNOTATE_STRINGS_UTF8 Query Option \(CDH 5.8 or higher only\)](#) on page 349 for details.

See [Using the Parquet File Format with Impala Tables](#) on page 584 for general information about working with Parquet files.

- Improvements to security and reduction in overhead for secure clusters:
 - Overall performance improvements for secure clusters. (TPC-H queries on a secure cluster were benchmarked at roughly 3x as fast as the previous release.)
 - Impala now recognizes the `auth_to_local` setting, specified through the HDFS configuration setting `hadoop.security.auth_to_local`. This feature is disabled by default; to enable it, specify `--load_auth_to_local_rules=true` in the `impalad` configuration settings. See [Mapping Kerberos Principals to Short Names for Impala](#) on page 119 for details.
 - Timing improvements in the mechanism for the `impalad` daemon to acquire Kerberos tickets. This feature spreads out the overhead on the KDC during Impala startup, especially for large clusters.
 - For Kerberized clusters, the Catalog service now uses the Kerberos principal instead of the operating system user that runs the `catalogd` daemon. This eliminates the requirement to configure a `hadoop.user.group.static.mapping.overrides` setting to put the OS user into the Sentry administrative group, on clusters where the principal and the OS user name for this user are different.
- Overall performance improvements for join queries, by using a prefetching mechanism while building the in-memory hash table to evaluate join predicates. See [PREFETCH_MODE Query Option \(CDH 5.8 or higher only\)](#) on page 350 for the query option to control this optimization.
- The `impala-shell` interpreter has a new command, `SOURCE`, that lets you run a set of SQL statements or other `impala-shell` commands stored in a file. You can run additional `SOURCE` commands from inside a file, to set up flexible sequences of statements for use cases such as schema setup, ETL, or reporting. See [impala-shell Command Reference](#) on page 520 for details and [Running Commands and SQL Statements in impala-shell](#) on page 517 for examples.
- The `millisecond()` built-in function lets you extract the fractional seconds part of a `TIMESTAMP` value. See [Impala Date and Time Functions](#) on page 398 for details.
- If an Avro table is created without column definitions in the `CREATE TABLE` statement, and columns are later added through `ALTER TABLE`, the resulting table is now queryable. Missing values from the newly added columns now default to `NULL`. See [Using the Avro File Format with Impala Tables](#) on page 597 for general details about working with Avro files.
- The mechanism for interpreting `DECIMAL` literals is improved, no longer going through an intermediate conversion step to `DOUBLE`:
 - Casting a `DECIMAL` value to `TIMESTAMP DOUBLE` produces a more precise value for the `TIMESTAMP` than formerly.
 - Certain function calls involving `DECIMAL` literals now succeed, when formerly they failed due to lack of a function signature with a `DOUBLE` argument.
 - Faster runtime performance for `DECIMAL` constant values, through improved native code generation for all combinations of precision and scale.

See [DECIMAL Data Type \(CDH 5.1 or higher only\)](#) on page 135 for details about the `DECIMAL` type.

- Improved type accuracy for `CASE` return values. If all `WHEN` clauses of the `CASE` expression are of `CHAR` type, the final result is also `CHAR` instead of being converted to `STRING`. See [Impala Conditional Functions](#) on page 427 for details about the `CASE` function.

- Uncorrelated queries using the `NOT EXISTS` operator are now supported. Formerly, the `NOT EXISTS` operator was only available for correlated subqueries.
- Improved performance for reading Parquet files.
- Improved performance for **top-N** queries, that is, those including both `ORDER BY` and `LIMIT` clauses.
- Impala optionally skips an arbitrary number of header lines from text input files on HDFS based on the `skip.header.line.count` value in the `TBLPROPERTIES` field of the table metadata. See [Data Files for Text Tables](#) on page 578 for details.
- Trailing comments are now allowed in queries processed by the `impala-shell` options `-q` and `-f`.
- Impala can run `COUNT` queries for RCFile tables that include complex type columns. See [Complex Types \(CDH 5.5 or higher only\)](#) on page 167 for general information about working with complex types, and [ARRAY Complex Type \(CDH 5.5 or higher only\)](#) on page 127, [MAP Complex Type \(CDH 5.5 or higher only\)](#) on page 146, and [STRUCT Complex Type \(CDH 5.5 or higher only\)](#) on page 153 for syntax details of each type.

New Features in Impala 2.5.x / CDH 5.7.x



Note: Impala 2.5.x is available as part of CDH 5.7.x and is not available for CDH 4. Cloudera does not intend to release future versions of Impala for CDH 4 outside patch and maintenance releases if required. Given the end-of-maintenance status for CDH 4, Cloudera recommends all customers to migrate to a recent CDH 5 release.

- **Dynamic partition pruning.** When a query refers to a partition key column in a `WHERE` clause, and the exact set of column values are not known until the query is executed, Impala evaluates the predicate and skips the I/O for entire partitions that are not needed. For example, if a table was partitioned by year, Impala would apply this technique to a query such as `SELECT c1 FROM partitioned_table WHERE year = (SELECT MAX(year) FROM other_table)`. See [Dynamic Partition Pruning](#) on page 571 for details.

The dynamic partition pruning optimization technique lets Impala avoid reading data files from partitions that are not part of the result set, even when that determination cannot be made in advance. This technique is especially valuable when performing join queries involving partitioned tables. For example, if a join query includes an `ON` clause and a `WHERE` clause that refer to the same columns, the query can find the set of column values that match the `WHERE` clause, and only scan the associated partitions when evaluating the `ON` clause.

Dynamic partition pruning is controlled by the same settings as the runtime filtering feature. By default, this feature is enabled at a medium level, because the maximum setting can use slightly more memory for queries than in previous releases. To fully enable this feature, set the query option `RUNTIME_FILTER_MODE=GLOBAL`.

- **Runtime filtering.** This is a wide-ranging set of optimizations that are especially valuable for join queries. Using the same technique as with dynamic partition pruning, Impala uses the predicates from `WHERE` and `ON` clauses to determine the subset of column values from one of the joined tables could possibly be part of the result set. Impala sends a compact representation of the filter condition to the hosts in the cluster, instead of the full set of values or the entire table.

By default, this feature is enabled at a medium level, because the maximum setting can use slightly more memory for queries than in previous releases. To fully enable this feature, set the query option `RUNTIME_FILTER_MODE=GLOBAL`.

This feature involves some new query options: [RUNTIME_FILTER_MODE](#), [MAX_NUM_RUNTIME_FILTERS](#), [RUNTIME_BLOOM_FILTER_SIZE](#), [RUNTIME_FILTER_WAIT_TIME_MS](#), and [DISABLE_ROW_RUNTIME_FILTERING](#).

- **More efficient use of the HDFS caching feature,** to avoid hotspots and bottlenecks that could occur if heavily used cached data blocks were always processed by the same host. By default, Impala now randomizes which host processes each cached HDFS data block, when cached replicas are available on multiple hosts. (Remember to use the `WITH REPLICATION` clause with the `CREATE TABLE` or `ALTER TABLE` statement when enabling HDFS caching for a table or partition, to cache the same data blocks across multiple hosts.) The new query option `SCHEDULE_RANDOM_REPLICA` lets you fine-tune the interaction with HDFS caching even more.

- The `TRUNCATE TABLE` statement now accepts an `IF EXISTS` clause, making `TRUNCATE TABLE` easier to use in setup or ETL scripts where the table might or might not exist.
- Improved performance and reliability for the `DECIMAL` data type:
 - Using `DECIMAL` values in a `GROUP BY` clause now triggers the native code generation optimization, speeding up queries that group by values such as prices.
 - Checking for overflow in `DECIMAL` multiplication is now substantially faster, making `DECIMAL` a more practical data type in some use cases where formerly `DECIMAL` was much slower than `FLOAT` or `DOUBLE`.
 - Multiplying a mixture of `DECIMAL` and `FLOAT` or `DOUBLE` values now returns the `DOUBLE` rather than `DECIMAL`. This change avoids some cases where an intermediate value would underflow or overflow and become `NULL` unexpectedly.
- For UDFs written in Java, or Hive UDFs reused for Impala, Impala now allows parameters and return values to be primitive types. Formerly, these things were required to be one of the “Writable” object types.
- Performance improvements for HDFS I/O. Impala now caches HDFS file handles to avoid the overhead of repeatedly opening the same file.
- Performance improvements for queries involving nested complex types. Certain basic query types, such as counting the elements of a complex column, now use an optimized code path.
- Improvements to the memory reservation mechanism for the Impala admission control feature. You can specify more settings, such as the timeout period and maximum aggregate memory used, for each resource pool instead of globally for the Impala instance. The default limit for concurrent queries (the **max requests** setting) is now unlimited instead of 200. The Cloudera Manager user interface for admission control has been reworked, with the settings available under the **Dynamic Resource Pools** window.
- Performance improvements related to code generation. Even in queries where code generation is not performed for some phases of execution (such as reading data from Parquet tables), Impala can still use code generation in other parts of the query, such as evaluating functions in the `WHERE` clause.
- Performance improvements for queries using aggregation functions on high-cardinality columns. Formerly, Impala could do unnecessary extra work to produce intermediate results for operations such as `DISTINCT` or `GROUP BY` on columns that were unique or had few duplicate values. Now, Impala decides at run time whether it is more efficient to do an initial aggregation phase and pass along a smaller set of intermediate data, or to pass raw intermediate data back to next phase of query processing to be aggregated there. This feature is known as **streaming pre-aggregation**. In case of performance regression, this feature can be turned off using the `DISABLE_STREAMING_PREAGGREGATIONS` query option.
- Spill-to-disk feature now always recommended. In earlier releases, the spill-to-disk feature could be turned off using a pair of configuration settings, `enable_partitioned_aggregation=false` and `enable_partitioned_hash_join=false`. The latest improvements in the spill-to-disk mechanism, and related features that interact with it, make this feature robust enough that disabling it is now no longer needed or supported. In particular, some new features in CDH 5.7 / Impala 2.5 and higher do not work when the spill-to-disk feature is disabled.
- Improvements to scripting capability for the `impala-shell` command, through user-specified substitution variables that can appear in statements processed by `impala-shell`:
 - The `--var` command-line option lets you pass key-value pairs to `impala-shell`. The shell can substitute the values into queries before executing them, where the query text contains the notation `${var:varname}`. For example, you might prepare a SQL file containing a set of DDL statements and queries containing variables for database and table names, and then pass the applicable names as part of the `impala-shell -f filename` command.
 - The `SET` and `UNSET` commands within the `impala-shell` interpreter now work with user-specified substitution variables, as well as the built-in query options. The two kinds of variables are divided in the `SET` output. As with variables defined by the `--var` command-line option, you refer to the user-specified

substitution variables in queries by using the notation `${var:varname}` in the query text. Because the substitution variables are processed by `impala-shell` instead of the `impalad` backend, you cannot define your own substitution variables through the `SET` statement in a JDBC or ODBC application.

- Performance improvements for query startup. Impala better parallelizes certain work when coordinating plan distribution between `impalad` instances, which improves startup time for queries involving tables with many partitions on large clusters, or complicated queries with many plan fragments.
- Performance and scalability improvements for tables with many partitions. The memory requirements on the coordinator node are reduced, making it substantially faster and less resource-intensive to do joins involving several tables with thousands of partitions each.
- Whitelisting for access to internal APIs. For applications that need direct access to Impala APIs, without going through the HiveServer2 or Beeswax interfaces, you can specify a list of Kerberos users who are allowed to call those APIs. By default, the `impala` and `hdfs` users are the only ones authorized for this kind of access. Any users not explicitly authorized through the `internal_principals_whitelist` configuration setting are blocked from accessing the APIs. This setting applies to all the Impala-related daemons, although currently it is primarily used for HDFS to control the behavior of the catalog server.
- Improvements to Impala integration and usability for Hue. (The code changes are actually on the Hue side.)
 - The list of tables now refreshes dynamically.
- Usability improvements for case-insensitive queries. You can now use the operators `ILIKE` and `IREGEXP` to perform case-insensitive wildcard matches or regular expression matches, rather than explicitly converting column values with `UPPER` or `LOWER`.
- Performance and reliability improvements for DDL and insert operations on partitioned tables with a large number of partitions. Impala only re-evaluates metadata for partitions that are affected by a DDL operation, not all partitions in the table. While a DDL or insert statement is in progress, other Impala statements that attempt to modify metadata for the same table wait until the first one finishes.
- Reliability improvements for the `LOAD DATA` statement. Previously, this statement would fail if the source HDFS directory contained any subdirectories at all. Now, the statement ignores any hidden subdirectories, for example `._impala_insert_staging`.
- A new operator, `IS [NOT] DISTINCT FROM`, lets you compare values and always get a `true` or `false` result, even if one or both of the values are `NULL`. The `IS NOT DISTINCT FROM` operator, or its equivalent `<=>` notation, improves the efficiency of join queries that treat key values that are `NULL` in both tables as equal.
- Security enhancements for the `impala-shell` command. A new option, `--ldap_password_cmd`, lets you specify a command to retrieve the LDAP password. The resulting password is then used to authenticate the `impala-shell` command with the LDAP server.
- The `CREATE TABLE AS SELECT` statement now accepts a `PARTITIONED BY` clause, which lets you create a partitioned table and insert data into it with a single statement.
- User-defined functions (UDFs and UDAFs) written in C++ now persist automatically when the `catalogd` daemon is restarted. You no longer have to run the `CREATE FUNCTION` statements again after a restart.
- User-defined functions (UDFs) written in Java can now persist when the `catalogd` daemon is restarted, and can be shared transparently between Impala and Hive. You must do a one-time operation to recreate these UDFs using new `CREATE FUNCTION` syntax, without a signature for arguments or the return value. Afterwards, you no longer have to run the `CREATE FUNCTION` statements again after a restart. Although Impala does not have visibility into the UDFs that implement the Hive built-in functions, user-created Hive UDFs are now automatically available for calling through Impala.
- Reliability enhancements for memory management. Some aggregation and join queries that formerly might have failed with an out-of-memory error due to memory contention, now can succeed using the spill-to-disk mechanism.

- The `SHOW DATABASES` statement now returns two columns rather than one. The second column includes the associated comment string, if any, for each database. Adjust any application code that examines the list of databases and assumes the result set contains only a single column.
- A new optimization speeds up aggregation operations that involve only the partition key columns of partitioned tables. For example, a query such as `SELECT COUNT(DISTINCT k), MIN(k), MAX(k) FROM t1` can avoid reading any data files if `T1` is a partitioned table and `k` is one of the partition key columns. Because this technique can produce different results in cases where HDFS files in a partition are manually deleted or are empty, you must enable the optimization by setting the query option `OPTIMIZE_PARTITION_KEY_SCANS`.
- The `DESCRIBE` statement can now display metadata about a database, using the syntax `DESCRIBE DATABASE db_name`.
- The `uuid()` built-in function generates an alphanumeric value that you can use as a guaranteed unique identifier. The uniqueness applies even across tables, for cases where an ascending numeric sequence is not suitable.

New Features in Impala 2.4.x / CDH 5.6.x



Note: Impala 2.4.0 is available as part of CDH 5.6.0 and is not available for CDH 4. Cloudera does not intend to release future versions of Impala for CDH 4 outside patch and maintenance releases if required. Given the end-of-maintenance status for CDH 4, Cloudera recommends all customers to migrate to a recent CDH 5 release.

- Impala can be used on the DSSD D5 Storage Appliance. From a user perspective, the Impala features are the same as in CDH 5.5 / Impala 2.3.

New Features in Impala 2.3.x / CDH 5.5.x



Note: Impala 2.3.x is available as part of CDH 5.5.x and is not available for CDH 4. Cloudera does not intend to release future versions of Impala for CDH 4 outside patch and maintenance releases if required. Given the end-of-maintenance status for CDH 4, Cloudera recommends all customers to migrate to a recent CDH 5 release.

The following are the major new features in Impala 2.3.x. This major release, available as part of CDH 5.5.x, contains improvements to SQL syntax (particularly new support for complex types), performance, manageability, security.

- **Complex data types:** `STRUCT`, `ARRAY`, and `MAP`. These types can encode multiple named fields, positional items, or key-value pairs within a single column. You can combine these types to produce nested types with arbitrarily deep nesting, such as an `ARRAY` of `STRUCT` values, a `MAP` where each key-value pair is an `ARRAY` of other `MAP` values, and so on. Currently, complex data types are only supported for the Parquet file format.
- **Column-level authorization** lets you define access to particular columns within a table, rather than the entire table. This feature lets you reduce the reliance on creating views to set up authorization schemes for subsets of information.
- The `TRUNCATE TABLE` statement removes all the data from a table without removing the table itself.
- **Nested loop join queries.** Some join queries that formerly required equality comparisons can now use operators such as `<` or `>=`. This same join mechanism is used internally to optimize queries that retrieve values from complex type columns.
- **Reduced memory usage and improved performance and robustness for spill-to-disk feature.**
- **Performance improvements for querying Parquet data files containing multiple row groups and multiple data blocks:**
 - For files written by Hive, SparkSQL, and other Parquet MR writers and spanning multiple HDFS blocks, Impala now scans the extra data blocks locally when possible, rather than using remote reads.

- Impala queries benefit from the improved alignment of row groups with HDFS blocks for Parquet files written by Hive, MapReduce, and other components in CDH 5.5 and higher. (Impala itself never writes multiblock Parquet files, so the alignment change does not apply to Parquet files produced by Impala.) These Parquet writers now add padding to Parquet files that they write to align row groups with HDFS blocks. The `parquet.writer.max-padding` setting specifies the maximum number of bytes, by default 8 megabytes, that can be added to the file between row groups to fill the gap at the end of one block so that the next row group starts at the beginning of the next block. If the gap is larger than this size, the writer attempts to fit another entire row group in the remaining space. Include this setting in the `hive-site` configuration file to influence Parquet files written by Hive, or the `hdfs-site` configuration file to influence Parquet files written by all non-Impala components.
- Many new built-in scalar functions, for convenience and enhanced portability of SQL that uses common industry extensions.

Math functions:

- ATAN2
- COSH
- COT
- DCEIL
- DEXP
- DFLOOR
- DLOG10
- DPOW
- DROUND
- DSQRT
- DTRUNC
- FACTORIAL, and corresponding ! operator
- FPOW
- RADIANS
- RANDOM
- SINH
- TANH

String functions:

- BTRIM
- CHR
- REGEXP_LIKE
- SPLIT_PART

Date and time functions:

- INT_MONTHS_BETWEEN
- MONTHS_BETWEEN
- TIMEOFDAY
- TIMESTAMP_CMP

Bit manipulation functions:

- BITAND
- BITNOT
- BITOR
- BITXOR
- COUNTSET
- GETBIT

- ROTATELEFT
- ROTATERIGHT
- SETBIT
- SHIFLEFT
- SHIFTRIGHT

Type conversion functions:

- TYPEOF

The `effective_user()` function.

- New built-in analytic functions: `PERCENT_RANK`, `NTILE`, `CUME_DIST`.
- The `DROP DATABASE` statement now works for a non-empty database. When you specify the optional `CASCADE` clause, any tables in the database are dropped before the database itself is removed.
- The `DROP TABLE` and `ALTER TABLE DROP PARTITION` statements have a new optional keyword, `PURGE`. This keyword causes Impala to immediately remove the relevant HDFS data files rather than sending them to the HDFS trashcan. This feature can help to avoid out-of-space errors on storage devices, and to avoid files being left behind in case of a problem with the HDFS trashcan, such as the trashcan not being configured or being in a different HDFS encryption zone than the data files.
- The `impala-shell` command has a new feature for live progress reporting. This feature is enabled through the `--live_progress` and `--live_summary` command-line options, or during a session through the `LIVE_SUMMARY` and `LIVE_PROGRESS` query options.
- The `impala-shell` command also now displays a random “tip of the day” when it starts.
- The `impala-shell` option `-f` now recognizes a special filename `-` to accept input from stdin.
- Format strings for the `unix_timestamp()` function can now include numeric timezone offsets.
- Impala can now run a specified command to obtain the password to decrypt a private-key PEM file, rather than having the private-key file be unencrypted on disk.
- Impala components now can use SSL for more of their internal communication. SSL is used for communication between all three Impala-related daemons when the configuration option `ssl_server_certificate` is enabled. SSL is used for communication with client applications when the configuration option `ssl_client_ca_certificate` is enabled.

Currently, you can only use one of server-to-server TLS/SSL encryption or Kerberos authentication. This limitation is tracked by the issue [IMPALA-2598](#).
- Improved flexibility for intermediate data types in user-defined aggregate functions (UDAFs).

In CDH 5.5.2 / Impala 2.3.2, the bug fix for [IMPALA-2598](#) removes the restriction on using both Kerberos and SSL for internal communication between Impala components.

New Features in Impala 2.2.x for CDH 5.4.3 and 5.4.4

No new features added to the Impala code. The certification of Impala with EMC Isilon under CDH 5.4.4 means that now you can query data stored on Isilon storage devices through Impala. See http://www.cloudera.com/documentation/enterprise/latest/topics/cm_mc_isilon_service.html for details. The same level of Impala is included with both CDH 5.4.3 and 5.4.4.



Note: The Impala 2.2.x maintenance releases now use the CDH 5.4.x numbering system rather than increasing the Impala version numbers. Impala 2.2 and higher are not available under CDH 4.

New Features in Impala 2.2.x / CDH 5.4.x



Note: Impala 2.2.0 is available as part of CDH 5.4.0 and is not available for CDH 4. Cloudera does not intend to release future versions of Impala for CDH 4 outside patch and maintenance releases if required. Given the end-of-maintenance status for CDH 4, Cloudera recommends all customers to migrate to a recent CDH 5 release.

The following are the major new features in Impala 2.2.x. This release, available as part of CDH 5.4.x, contains improvements to performance, manageability, security, and SQL syntax.

- Several improvements to date and time features enable higher interoperability with Hive and other database systems, provide more flexibility for handling time zones, and future-proof the handling of `TIMESTAMP` values:
 - The `WITH REPLICATION` clause for the `CREATE TABLE` and `ALTER TABLE` statements lets you control the replication factor for HDFS caching for a specific table or partition. By default, each cached block is only present on a single host, which can lead to CPU contention if the same host processes each cached block. Increasing the replication factor lets Impala choose different hosts to process different cached blocks, to better distribute the CPU load.
 - Startup flags for the `impalad` daemon enable a higher level of compatibility with `TIMESTAMP` values written by Hive, and more flexibility for working with date and time data using the local time zone instead of UTC. To enable these features, set the `impalad` startup flags
 - `-use_local_tz_for_unix_timestamp_conversions=true` and
 - `-convert_legacy_hive_parquet_utc_timestamps=true`.

The `-use_local_tz_for_unix_timestamp_conversions` setting controls how the `unix_timestamp()`, `from_unixtime()`, and `now()` functions handle time zones. By default (when this setting is turned off), Impala considers all `TIMESTAMP` values to be in the UTC time zone when converting to or from Unix time values. When this setting is enabled, Impala treats `TIMESTAMP` values passed to or returned from these functions to be in the local time zone. When this setting is enabled, take particular care that all hosts in the cluster have the same timezone settings, to avoid inconsistent results depending on which host reads or writes `TIMESTAMP` data.

The `-convert_legacy_hive_parquet_utc_timestamps` setting causes Impala to convert `TIMESTAMP` values to the local time zone when it reads them from Parquet files written by Hive. This setting only applies to data using the Parquet file format, where Impala can use metadata in the files to reliably determine that the files were written by Hive. If in the future Hive changes the way it writes `TIMESTAMP` data in Parquet, Impala will automatically handle that new `TIMESTAMP` encoding.

See [TIMESTAMP Data Type](#) on page 158 for details about time zone handling and the configuration options for Impala / Hive compatibility with Parquet format.

- In Impala 2.2.0 and higher, built-in functions that accept or return integers representing `TIMESTAMP` values use the `BIGINT` type for parameters and return values, rather than `INT`. This change lets the date and time functions avoid an overflow error that would otherwise occur on January 19th, 2038 (known as the “[Year 2038 problem](#)” or “[Y2K38 problem](#)”). This change affects the `from_unixtime()` and `unix_timestamp()` functions. You might need to change application code that interacts with these functions, change the types of columns that store the return values, or add `CAST()` calls to SQL statements that call these functions.

See [Impala Date and Time Functions](#) on page 398 for the current function signatures.

- The `SHOW FILES` statement lets you view the names and sizes of the files that make up an entire table or a specific partition. See [SHOW FILES Statement](#) on page 357 for details.
- Impala can now run queries against Parquet data containing columns with complex or nested types, as long as the query only refers to columns with scalar types.
- Performance improvements for queries that include `IN()` operators and involve partitioned tables.

- The new `-max_log_files` configuration option specifies how many log files to keep at each severity level. The default value is 10, meaning that Impala preserves the latest 10 log files for each severity level (INFO, WARNING, and ERROR) for each Impala-related daemon (`impalad`, `stated`, and `catalogd`). Impala checks to see if any old logs need to be removed based on the interval specified in the `logbufsecs` setting, every 5 seconds by default. See [Rotating Impala Logs](#) on page 628 for details.
- Redaction of sensitive data from Impala log files. This feature protects details such as credit card numbers or tax IDs from administrators who see the text of SQL statements in the course of monitoring and troubleshooting a Hadoop cluster. See [Redacting Sensitive Information from Impala Log Files](#) on page 630 for background information for Impala users, and [the CDH 5 Security Guide](#) for usage details.
- Lineage information is available for data created or queried by Impala. This feature lets you track who has accessed data through Impala SQL statements, down to the level of specific columns, and how data has been propagated between tables. See [Viewing Lineage Information for Impala Data](#) on page 124 for background information for Impala users, http://www.cloudera.com/documentation/enterprise/latest/topics/datamgmt_impala_lineage_log.html for usage details, and http://www.cloudera.com/documentation/enterprise/latest/topics/cn_iu_lineage.html for how to interpret the lineage information.
- Impala tables and partitions can now be located on the Amazon Simple Storage Service (S3) filesystem, for convenience in cases where data is already located in S3 and you prefer to query it in-place. Queries might have lower performance than when the data files reside on HDFS, because Impala uses some HDFS-specific optimizations. Impala can query data in S3, but cannot write to S3. Therefore, statements such as `INSERT` and `LOAD DATA` are not available when the destination table or partition is in S3. See [Using Impala with the Amazon S3 Filesystem](#) on page 617 for details.



Important:

Impala query support for Amazon S3 is included in CDH 5.4.0, but is not currently supported or recommended for production use. To try this feature, use it in a test environment until Cloudera resolves currently existing issues and limitations to make it ready for production use.

- Improved support for HDFS encryption. The `LOAD DATA` statement now works when the source directory and destination table are in different encryption zones.
- Additional arithmetic function `mod()`. See [Impala Mathematical Functions](#) on page 374 for details.
- Flexibility to interpret `TIMESTAMP` values using the UTC time zone (the traditional Impala behavior) or using the local time zone (for compatibility with `TIMESTAMP` values produced by Hive).
- Enhanced support for ETL using tools such as Flume. Impala ignores temporary files typically produced by these tools (filenames with suffixes `.copying` and `.tmp`).
- The CPU requirement for Impala, which had become more restrictive in Impala 2.0.x and 2.1.x, has now been relaxed.

The prerequisite for CPU architecture has been relaxed in Impala 2.2.0 and higher. From this release onward, Impala works on CPUs that have the SSSE3 instruction set. The SSE4 instruction set is no longer required. This relaxed requirement simplifies the upgrade planning from Impala 1.x releases, which also worked on SSSE3-enabled processors.
- Enhanced support for `CHAR` and `VARCHAR` types in the `COMPUTE STATS` statement.
- The amount of memory required during setup for “spill to disk” operations is greatly reduced. This enhancement reduces the chance of a memory-intensive join or aggregation query failing with an out-of-memory error.
- Several new conditional functions provide enhanced compatibility when porting code that uses industry extensions. The new functions are: `isfalse()`, `isnotfalse()`, `isnottrue()`, `istrue()`, `nonnullvalue()`, and `nullvalue()`. See [Impala Conditional Functions](#) on page 427 for details.

- The Impala debug web UI now can display a visual representation of the query plan. On the **/queries** tab, select **Details** for a particular query. The **Details** page includes a **Plan** tab with a plan diagram that you can zoom in or out (using scroll gestures through mouse wheel or trackpad).

New Features in Impala 2.1.8 / CDH 5.3.10

This point release is exclusively a bug fix release.



Note: This Impala maintenance release is only available as part of CDH 5, not under CDH 4.

New Features in Impala 2.1.7 / CDH 5.3.9

This point release is exclusively a bug fix release.



Note: This Impala maintenance release is only available as part of CDH 5, not under CDH 4.

New Features in Impala 2.1.6 / CDH 5.3.8

This point release is exclusively a bug fix release.



Note: This Impala maintenance release is only available as part of CDH 5, not under CDH 4.

New Features in Impala 2.1.5 / CDH 5.3.6

This point release is exclusively a bug fix release.



Note: This Impala maintenance release is only available as part of CDH 5, not under CDH 4.

New Features in Impala 2.1.4 / CDH 5.3.4

No new features. This point release is exclusively a bug fix release. Because CDH 5.3.5 does not include any code changes for Impala, Impala 2.1.4 is included with both CDH 5.3.4 and 5.3.5.



Note: This Impala maintenance release is only available as part of CDH 5, not under CDH 4.

New Features in Impala 2.1.3 / CDH 5.3.3

No new features. This point release is exclusively a bug fix release.



Note: Impala 2.1.3 is available as part of CDH 5.3.3, not under CDH 4.

New Features in Impala 2.1.2 / CDH 5.3.2

No new features. This point release is exclusively a bug fix release.



Note: Impala 2.1.2 is available as part of CDH 5.3.2, not under CDH 4.

New Features in Impala 2.1.1 / CDH 5.3.1

No new features. This point release is exclusively a bug fix release.

New Features in Impala 2.1.0 / CDH 5.3.0

This release contains the following enhancements to query performance and system scalability:

- Impala can now collect statistics for individual partitions in a partitioned table, rather than processing the entire table for each `COMPUTE STATS` statement. This feature is known as incremental statistics, and is controlled by the `COMPUTE INCREMENTAL STATS` syntax. (You can still use the original `COMPUTE STATS` statement for nonpartitioned tables or partitioned tables that are unchanging or whose contents are entirely replaced all at once.) See [COMPUTE STATS Statement](#) on page 241 and [Table and Column Statistics](#) on page 533 for details.
- Optimization for small queries lets Impala process queries that process very few rows without the unnecessary overhead of parallelizing and generating native code. Reducing this overhead lets Impala clear small queries quickly, keeping YARN resources and admission control slots available for data-intensive queries. The number of rows considered to be a “small” query is controlled by the `EXEC_SINGLE_NODE_ROWS_THRESHOLD` query option. See [EXEC_SINGLE_NODE_ROWS_THRESHOLD Query Option \(CDH 5.3 or higher only\)](#) on page 335 for details.
- An enhancement to the statestore component lets it transmit heartbeat information independently of broadcasting metadata updates. This optimization improves reliability of health checking on large clusters with many tables and partitions.
- The memory requirement for querying gzip-compressed text is reduced. Now Impala decompresses the data as it is read, rather than reading the entire gzipped file and decompressing it in memory.

New Features in Impala 2.0.5 / CDH 5.2.6

No new features. This point release is exclusively a bug fix release.



Note: Impala 2.0.5 is available as part of CDH 5.2.6, not under CDH 4.

New Features in Impala 2.0.4 / CDH 5.2.5

No new features. This point release is exclusively a bug fix release.



Note: Impala 2.0.4 is available as part of CDH 5.2.5, not under CDH 4.

New Features in Impala 2.0.3 / CDH 5.2.4

No new features. This point release is exclusively a bug fix release.



Note: Impala 2.0.3 is available as part of CDH 5.2.4, not under CDH 4.

New Features in Impala 2.0.2 / CDH 5.2.3

No new features. This point release is exclusively a bug fix release.



Note: Impala 2.0.2 is available as part of CDH 5.2.3, not under CDH 4.

New Features in Impala 2.0.1 / CDH 5.2.1

No new features. This point release is exclusively a bug fix release.

New Features in Impala 2.0.0 / CDH 5.2.0

The following are the major new features in Impala 2.0. This major release, available both with CDH 5.2 and for CDH 4, contains improvements to performance, scalability, security, and SQL syntax.

- Queries with joins or aggregation functions involving high volumes of data can now use temporary work areas on disk, reducing the chance of failure due to out-of-memory errors. When the required memory for the intermediate result set exceeds the amount available on a particular node, the query automatically uses a temporary work area on disk. This “spill to disk” mechanism is similar to the `ORDER BY` improvement from Impala 1.4. For details, see [SQL Operations that Spill to Disk](#) on page 562.
- Subquery enhancements:
 - Subqueries are now allowed in the `WHERE` clause, for example with the `IN` operator.
 - The `EXISTS` and `NOT EXISTS` operators are available. They are always used in conjunction with subqueries.
 - The `IN` and `NOT IN` queries can now operate on the result set from a subquery, not just a hardcoded list of values.
 - Uncorrelated subqueries let you compare against one or more values for equality, `IN`, and `EXISTS` comparisons. For example, you might use `WHERE` clauses such as `WHERE column = (SELECT MAX(some_other_column) FROM table)` or `WHERE column IN (SELECT some_other_column FROM table WHERE conditions)`.
 - Correlated subqueries let you cross-reference values from the outer query block and the subquery.
 - Scalar subqueries let you substitute the result of single-value aggregate functions such as `MAX()`, `MIN()`, `COUNT()`, or `AVG()`, where you would normally use a numeric value in a `WHERE` clause.

For details about subqueries, see [Subqueries in Impala SELECT Statements](#) on page 322. For information about new and improved operators, see [EXISTS Operator](#) on page 203 and [IN Operator](#) on page 207.

- Analytic functions such as `RANK()`, `LAG()`, `LEAD()`, and `FIRST_VALUE()` let you analyze sequences of rows with flexible ordering and grouping. Existing aggregate functions such as `MAX()`, `SUM()`, and `COUNT()` can also be used in an analytic context. See [Impala Analytic Functions](#) on page 470 for details. See [Impala Aggregate Functions](#) on page 443 for enhancements to existing aggregate functions.
- New data types provide greater compatibility with source code from traditional database systems:
 - `VARCHAR` is like the `STRING` data type, but with a maximum length. See [VARCHAR Data Type \(CDH 5.2 or higher only\)](#) on page 165 for details.
 - `CHAR` is like the `STRING` data type, but with a precise length. Short values are padded with spaces on the right. See [CHAR Data Type \(CDH 5.2 or higher only\)](#) on page 132 for details.
- Security enhancements:
 - Formerly, Impala was restricted to using either Kerberos or LDAP / Active Directory authentication within a cluster. Now, Impala can freely accept either kind of authentication request, allowing you to set up some hosts with Kerberos authentication and others with LDAP or Active Directory. See [Using Multiple Authentication Methods with Impala](#) on page 122 for details.
 - `GRANT` statement. See [GRANT Statement \(CDH 5.2 or higher only\)](#) on page 285 for details.
 - `REVOKE` statement. See [REVOKE Statement \(CDH 5.2 or higher only\)](#) on page 304 for details.
 - `CREATE ROLE` statement. See [CREATE ROLE Statement \(CDH 5.2 or higher only\)](#) on page 253 for details.
 - `DROP ROLE` statement. See [DROP ROLE Statement \(CDH 5.2 or higher only\)](#) on page 277 for details.
 - `SHOW ROLES` and `SHOW ROLE GRANT` statements. See [SHOW Statement](#) on page 356 for details.

- To complement the HDFS encryption feature, a new Impala configuration option, `--disk_spill_encryption` secures sensitive data from being observed or tampered with when temporarily stored on disk.

The new security-related SQL statements work along with the Sentry authorization framework. See [Enabling Sentry Authorization for Impala](#) for details.

- Impala can now read compressed text files compressed by gzip, bzip, or Snappy. These files do not require any special table settings to work in an Impala text table. Impala recognizes the compression type automatically based on file extensions of `.gz`, `.bz2`, and `.snappy` respectively. These types of compressed text files are intended for convenience with existing ETL pipelines. Their non-splittable nature means they are not optimal for high-performance parallel queries. See [Using gzip, bzip2, or Snappy-Compressed Text Files](#) on page 583 for details.
- Query hints can now use comment notation, `/* +hint_name */` or `-- +hint_name`, at the same places in the query where the hints enclosed by `[]` are recognized. This enhancement makes it easier to reuse Impala queries on other database systems. See [Query Hints in Impala SELECT Statements](#) on page 326 for details.

- A new query option, `QUERY_TIMEOUT_S`, lets you specify a timeout period in seconds for individual queries.

The working of the `--idle_query_timeout` configuration option is extended. If no `QUERY_OPTION_S` query option is in effect, `--idle_query_timeout` works the same as before, setting the timeout interval. When the `QUERY_OPTION_S` query option is specified, its maximum value is capped by the value of the `--idle_query_timeout` option.

That is, the system administrator sets the default and maximum timeout through the `--idle_query_timeout` startup option, and then individual users or applications can set a lower timeout value if desired through the `QUERY_TIMEOUT_S` query option. See [Setting Timeout Periods for Daemons, Queries, and Sessions](#) on page 91 and [QUERY_TIMEOUT_S Query Option \(CDH 5.2 or higher only\)](#) on page 350 for details.

- New functions `VAR_SAMP()` and `VAR_POP()` are aliases for the existing `VARIANCE_SAMP()` and `VARIANCE_POP()` functions.
- A new date and time function, `DATE_PART()`, provides similar functionality to `EXTRACT()`. You can also call the `EXTRACT()` function using the SQL-99 syntax, `EXTRACT(unit FROM timestamp)`. These enhancements simplify the porting process for date-related code from other systems. See [Impala Date and Time Functions](#) on page 398 for details.
- New approximation features provide a fast way to get results when absolute precision is not required:
 - The `APPX_COUNT_DISTINCT` query option lets Impala rewrite `COUNT(DISTINCT)` calls to use `NDV()` instead, which speeds up the operation and allows multiple `COUNT(DISTINCT)` operations in a single query. See [APPX_COUNT_DISTINCT Query Option \(CDH 5.2 or higher only\)](#) on page 332 for details.

The `APPX_MEDIAN()` aggregate function produces an estimate for the median value of a column by using sampling. See [APPX_MEDIAN Function](#) on page 443 for details.

- Impala now supports a `DECODE()` function. This function works as a shorthand for a `CASE()` expression, and improves compatibility with SQL code containing vendor extensions. See [Impala Conditional Functions](#) on page 427 for details.
- The `STDDEV()`, `STDDEV_POP()`, `STDDEV_SAMP()`, `VARIANCE()`, `VARIANCE_POP()`, `VARIANCE_SAMP()`, and `NDV()` aggregate functions now all return `DOUBLE` results rather than `STRING`. Formerly, you were required to `CAST()` the result to a numeric type before using it in arithmetic operations.
- The default settings for Parquet block size, and the associated `PARQUET_FILE_SIZE` query option, are changed. Now, Impala writes Parquet files with a size of 256 MB and an HDFS block size of 256 MB. Previously, Impala attempted to write Parquet files with a size of 1 GB and an HDFS block size of 1 GB. In practice, Impala used a conservative estimate of the disk space needed for each Parquet block, leading to files that were typically 512 MB anyway. Thus, this change will make the file size more accurate if you specify a value for the `PARQUET_FILE_SIZE` query option. It also reduces the amount of memory reserved during `INSERT` into Parquet tables, potentially avoiding out-of-memory errors and improving scalability when inserting data into Parquet tables.

- Anti-joins are now supported, expressed using the `LEFT ANTI JOIN` and `RIGHT ANTI JOIN` clauses. These clauses returns results from one table that have no match in the other table. You might use this type of join in the same sorts of use cases as the `NOT EXISTS` and `NOT IN` operators. See [Joins in Impala SELECT Statements](#) on page 306 for details.
- The `SET` command in `impala-shell` has been promoted to a real SQL statement. You can now set query options such as `PARQUET_FILE_SIZE`, `MEM_LIMIT`, and `SYNC_DDL` within JDBC, ODBC, or any other kind of application that submits SQL without going through the `impala-shell` interpreter. See [SET Statement](#) on page 329 for details.
- The `impala-shell` interpreter now reads settings from an optional configuration file, named `$HOME/.impalarc` by default. See [impala-shell Configuration File](#) on page 514 for details.
- The library used for regular expression parsing has changed from Boost to Google RE2. This implementation change adds support for non-greedy matches using the `. * ?` notation. This and other changes in the way regular expressions are interpreted means you might need to re-test queries that use functions such as `regexp_extract()` or `regexp_replace()`, or operators such as `REGEXP` or `RLIKE`. See [Incompatible Changes and Limitations in Apache Impala](#) on page 686 for those details.

New Features in Impala 1.4.4 / CDH 5.1.5

No new features. This point release is exclusively a bug fix release.



Note: Impala 1.4.4 is available as part of CDH 5.1.5, not under CDH 4.

New Features in Impala 1.4.3 / CDH 5.1.4

No new features. This point release is exclusively a bug fix release for an SSL security issue.



Note: Impala 1.4.3 is available as part of CDH 5.1.4, and under CDH 4.

New Features in Impala 1.4.2 / CDH 5.1.3

Impala 1.4.2 is purely a bug-fix release. It does not include any new features.



Note: Impala 1.4.2 is only available as part of CDH 5.1.3, not under CDH 4.

New Features in Impala 1.4.1 / CDH 5.1.2

Impala 1.4.1 is purely a bug-fix release. It does not include any new features.

New Features in Impala 1.4.0 / CDH 5.1.0

The following are the major new features in Impala 1.4.

- The `DECIMAL` data type lets you store fixed-precision values, for working with currency or other fractional values where it is important to represent values exactly and avoid rounding errors. This feature includes enhancements to built-in functions, numeric literals, and arithmetic expressions.
- On CDH 5, Impala can take advantage of the HDFS caching feature to “pin” entire tables or individual partitions in memory, to speed up queries on frequently accessed data and reduce the CPU overhead of memory-to-memory copying. When HDFS files are cached in memory, Impala can read the cached data without any disk reads, and without making an additional copy of the data in memory. Other Hadoop components that read the same data files also experience a performance benefit.

- Impala can now use Sentry-based authorization based either on the original policy file, or on rules defined by `GRANT` and `REVOKE` statements issued through Hive.
- For interoperability with Parquet files created through other Hadoop components, such as Pig or MapReduce jobs, you can create an Impala table that automatically sets up the column definitions based on the layout of an existing Parquet data file.
- `ORDER BY` queries no longer require a `LIMIT` clause. If the size of the result set to be sorted exceeds the memory available to Impala, Impala uses a temporary work space on disk to perform the sort operation.
- LDAP connections can be secured through either SSL or TLS.
- The following new built-in scalar and aggregate functions are available:
 - A new built-in function, `EXTRACT()`, returns one date or time field from a `TIMESTAMP` value.
 - A new built-in function, `TRUNC()`, truncates date/time values to a particular granularity, such as year, month, day, hour, and so on.
 - `ADD_MONTHS()` built-in function, an alias for the existing `MONTHS_ADD()` function.
 - A new built-in function, `ROUND()`, rounds `DECIMAL` values to a specified number of fractional digits.
 - Several built-in aggregate functions for computing properties for statistical distributions: `STDDEV()`, `STDDEV_SAMP()`, `STDDEV_POP()`, `VARIANCE()`, `VARIANCE_SAMP()`, and `VARIANCE_POP()`.
 - Several new built-in functions, such as `MAX_INT()`, `MIN_SMALLINT()`, and so on, let you conveniently check whether data values are in an expected range. You might be able to switch a column to a smaller type, saving memory during processing.
 - New built-in functions, `IS_INF()` and `IS_NAN()`, check for the special values infinity and “not a number”. These values could be specified as `inf` or `nan` in text data files, or be produced by certain arithmetic expressions.
- The `SHOW PARTITIONS` statement displays information about the structure of a partitioned table.
- New configuration options for the `impalad` daemon let you specify initial memory usage for all queries. The initial resource requests handled by Llama and YARN can be expanded later if needed, avoiding unnecessary over-allocation and reducing the chance of out-of-memory conditions.
- The Impala `CREATE TABLE` statement now has a `STORED AS AVRO` clause, allowing you to create Avro tables through Impala.
- New `impalad` configuration options let you fine-tune the calculations Impala makes to estimate resource requirements for each query. These options can help avoid problems due to overconsumption due to too-low estimates, or underutilization due to too-high estimates.
- A new `SUMMARY` command in the `impala-shell` interpreter provides a high-level summary of the work performed at each stage of the explain plan. The summary is also included in output from the `PROFILE` command.
- Performance improvements for the `COMPUTE STATS` statement:
 - The `NDV` function is speeded up through native code generation.
 - Because the `NULL` count is not currently used by the Impala query planner, in Impala 1.4.0 and higher, `COMPUTE STATS` does not count the `NULL` values for each column. (The `#Nulls` field of the stats table is left as `-1`, signifying that the value is unknown.)
- Performance improvements for partition pruning. This feature reduces the time spent in query planning, for partitioned tables with thousands of partitions. Previously, Impala typically queried tables with up to approximately 3000 partitions. With the performance improvement in partition pruning, now Impala can comfortably handle tables with tens of thousands of partitions.
- The documentation provides additional guidance for planning tasks.

- The `impala-shell` interpreter now supports UTF-8 characters for input and output. You can control whether `impala-shell` ignores invalid Unicode code points through the `--strict_unicode` option. (Although this option is removed in Impala 2.0.)

New Features in Impala 1.3.3 / CDH 5.0.5

No new features. This point release is exclusively a bug fix release for an SSL security issue.



Note: Impala 1.3.3 is only available as part of CDH 5.0.5, not under CDH 4.

New Features in Impala 1.3.2 / CDH 5.0.4

No new features. This point release is exclusively a bug fix release for the IMPALA-1019 issue related to HDFS caching.



Note: Impala 1.3.2 is only available as part of CDH 5.0.4, not under CDH 4.

New Features in Impala 1.3.1 / CDH 5.0.3

This point release is primarily a vehicle to deliver bug fixes. Any new features are minor changes resulting from fixes for performance, reliability, or usability issues.

Because 1.3.1 is the first 1.3.x release for CDH 4, if you are on CDH 4, also consult [New Features in Impala 1.3.0 / CDH 5.0.0](#) on page 678 for more features that are new to you.



Note:

- The Impala 1.3.1 release is available for both CDH 4 and CDH 5. This is the first release in the 1.3.x series for CDH 4.

- A new `impalad` startup option, `--insert_inherit_permissions`, causes Impala `INSERT` statements to create each new partition with the same HDFS permissions as its parent directory. By default, `INSERT` statements create directories for new partitions using default HDFS permissions. See [INSERT Statement](#) on page 286 for examples of `INSERT` statements for partitioned tables.
- The `SHOW FUNCTIONS` statement now displays the return type of each function, in addition to the types of its arguments. See [SHOW Statement](#) on page 356 for examples.
- You can now specify the clause `FIELDS TERMINATED BY '\0'` with a `CREATE TABLE` statement to use text data files that use ASCII 0 (`\nul`) characters as a delimiter. See [Using Text Data Files with Impala Tables](#) on page 576 for details.
- In Impala 1.3.1 and higher, the `REGEXP` and `RLIKE` operators now match a regular expression string that occurs anywhere inside the target string, the same as if the regular expression was enclosed on each side by `.*`. See [REGEXP Operator](#) on page 216 for examples. Previously, these operators only succeeded when the regular expression matched the entire target string. This change improves compatibility with the regular expression support for popular database systems. There is no change to the behavior of the `regexp_extract()` and `regexp_replace()` built-in functions.

New Features in Impala 1.3.0 / CDH 5.0.0

**Note:**

- The Impala 1.3.1 release is available for both CDH 4 and CDH 5. This is the first release in the 1.3.x series for CDH 4.

- The admission control feature lets you control and prioritize the volume and resource consumption of concurrent queries. This mechanism reduces spikes in resource usage, helping Impala to run alongside other kinds of workloads on a busy cluster. It also provides more user-friendly conflict resolution when multiple memory-intensive queries are submitted concurrently, avoiding resource contention that formerly resulted in out-of-memory errors. See [Admission Control and Query Queuing](#) on page 77 for details.
- Enhanced EXPLAIN plans provide more detail in an easier-to-read format. Now there are four levels of verbosity: the EXPLAIN_LEVEL option can be set from 0 (most concise) to 3 (most verbose). See [EXPLAIN Statement](#) on page 283 for syntax and [Understanding Impala Query Performance - EXPLAIN Plans and Query Profiles](#) on page 556 for usage information.
- The TIMESTAMP data type accepts more kinds of input string formats through the UNIX_TIMESTAMP function, and produces more varieties of string formats through the FROM_UNIXTIME function. The documentation now also lists more functions for date arithmetic, used for adding and subtracting INTERVAL expressions from TIMESTAMP values. See [Impala Date and Time Functions](#) on page 398 for details.
- New conditional functions, NULLIF(), NULLIFZERO(), and ZEROIFNULL(), simplify porting SQL containing vendor extensions to Impala. See [Impala Conditional Functions](#) on page 427 for details.
- New utility function, CURRENT_DATABASE(). See [Impala Miscellaneous Functions](#) on page 442 for details.
- Integration with the YARN resource management framework. Only available in combination with CDH 5. This feature makes use of the underlying YARN service, plus an additional service (Llama) that coordinates requests to YARN for Impala resources, so that the Impala query only proceeds when all requested resources are available. See [Resource Management for Impala](#) on page 85 for full details.

On the Impala side, this feature involves some new startup options for the `impalad` daemon:

- `-enable_rm`
- `-llama_host`
- `-llama_port`
- `-llama_callback_port`
- `-cgroup_hierarchy_path`

For details of these startup options, see [Modifying Impala Startup Options](#) on page 45.

This feature also involves several new or changed query options that you can set through the `impala-shell` interpreter and apply within a specific session:

- `MEM_LIMIT`: the function of this existing option changes when Impala resource management is enabled.
- `REQUEST_POOL`: a new option. (Renamed to `RESOURCE_POOL` in Impala 1.3.0.)
- `V_CPU_CORES`: a new option.
- `RESERVATION_REQUEST_TIMEOUT`: a new option.

For details of these query options, see [impala-shell Query Options for Resource Management](#) on page 86.

New Features in Impala 1.2.4



Note: Impala 1.2.4 works with CDH 4. It is primarily a bug fix release for Impala 1.2.3, plus some performance enhancements for the catalog server to minimize startup and DDL wait times for Impala deployments with large numbers of databases, tables, and partitions.

- On Impala startup, the metadata loading and synchronization mechanism has been improved and optimized, to give more responsiveness when starting Impala on a system with a large number of databases, tables, or partitions. The initial metadata loading happens in the background, allowing queries to be run before the entire process is finished. When a query refers to a table whose metadata is not yet loaded, the query waits until the metadata for that table is loaded, and the load operation for that table is prioritized to happen first.
- Formerly, if you created a new table in Hive, you had to issue the `INVALIDATE METADATA` statement (with no table name) which was an expensive operation that reloaded metadata for all tables. Impala did not recognize the name of the Hive-created table, so you could not do `INVALIDATE METADATA new_table` to get the metadata for just that one table. Now, when you issue `INVALIDATE METADATA table_name`, Impala checks to see if that name represents a table created in Hive, and if so recognizes the new table and loads the metadata for it. Additionally, if the new table is in a database that was newly created in Hive, Impala also recognizes the new database.
- If you issue `INVALIDATE METADATA table_name` and the table has been dropped through Hive, Impala will recognize that the table no longer exists.
- New startup options let you control the parallelism of the metadata loading during startup for the `catalogd` daemon:
 - `--load_catalog_in_background` makes Impala load and cache metadata using background threads after startup. It is `true` by default. Previously, a system with a large number of databases, tables, or partitions could be unresponsive or even time out during startup.
 - `--num_metadata_loading_threads` determines how much parallelism Impala devotes to loading metadata in the background. The default is 16. You might increase this value for systems with huge numbers of databases, tables, or partitions. You might lower this value for busy systems that are CPU-constrained due to jobs from components other than Impala.

New Features in Impala 1.2.3



Note: Impala 1.2.3 works with CDH 4 and with CDH 5 beta 2. The resource management feature requires CDH 5 beta.

Impala 1.2.3 contains exactly the same feature set as Impala 1.2.2. Its only difference is one additional fix for compatibility with Parquet files generated outside of Impala by components such as Hive, Pig, or MapReduce. If you are upgrading from Impala 1.2.1 or earlier, see [New Features in Impala 1.2.2](#) on page 679 for the latest added features.

New Features in Impala 1.2.2



Note: Impala 1.2.2 works with CDH 4. Its feature set is a superset of features in the Impala 1.2.0 beta, with the exception of resource management, which relies on CDH 5.

Impala 1.2.2 includes new features for performance, security, and flexibility. The major enhancements over 1.2.1 are performance related, primarily for join queries.

New user-visible features include:

- Join order optimizations. This highly valuable feature automatically distributes and parallelizes the work for a join query to minimize disk I/O and network traffic. The automatic optimization reduces the need to use query hints or to rewrite join queries with the tables in a specific order based on size or cardinality. The new `COMPUTE STATS` statement gathers statistical information about each table that is crucial for enabling the join optimizations. See [Performance Considerations for Join Queries](#) on page 526 for details.
- `COMPUTE STATS` statement to collect both table statistics and column statistics with a single statement. Intended to be more comprehensive, efficient, and reliable than the corresponding Hive `ANALYZE TABLE` statement, which collects statistics in multiple phases through MapReduce jobs. These statistics are important for query planning

for join queries, queries on partitioned tables, and other types of data-intensive operations. For optimal planning of join queries, you need to collect statistics for each table involved in the join. See [COMPUTE STATS Statement](#) on page 241 for details.

- Reordering of tables in a join query can be overridden by the `STRAIGHT_JOIN` operator, allowing you to fine-tune the planning of the join query if necessary, by using the original technique of ordering the joined tables in descending order of size. See [Overriding Join Reordering with STRAIGHT_JOIN](#) on page 527 for details.
- The `CROSS JOIN` clause in the `SELECT` statement to allow Cartesian products in queries, that is, joins without an equality comparison between columns in both tables. Because such queries must be carefully checked to avoid accidental overconsumption of memory, you must use the `CROSS JOIN` operator to explicitly select this kind of join. See [Cross Joins and Cartesian Products with the CROSS JOIN Operator](#) on page 63 for examples.
- The `ALTER TABLE` statement has new clauses that let you fine-tune table statistics. You can use this technique as a less-expensive way to update specific statistics, in case the statistics become stale, or to experiment with the effects of different data distributions on query planning.
- LDAP username/password authentication in JDBC/ODBC. See [Enabling LDAP Authentication for Impala](#) on page 119 for details.
- [GROUP_CONCAT\(\)](#) aggregate function to concatenate column values across all rows of a result set.
- The `INSERT` statement now accepts hints, `[SHUFFLE]` and `[NOSHUFFLE]`, to influence the way work is redistributed during `INSERT...SELECT` operations. The hints are primarily useful for inserting into partitioned Parquet tables, where using the `[SHUFFLE]` hint can avoid problems due to memory consumption and simultaneous open files in HDFS, by collecting all the new data for each partition on a specific node.
- Several built-in functions and operators are now overloaded for more numeric data types, to reduce the requirement to use `CAST()` for type coercion in `INSERT` statements. For example, the expression `2+2` in an `INSERT` statement formerly produced a `BIGINT` result, requiring a `CAST()` to be stored in an `INT` variable. Now, addition, subtraction, and multiplication only produce a result that is one step “bigger” than their arguments, and numeric and conditional functions can return `SMALLINT`, `FLOAT`, and other smaller types rather than always `BIGINT` or `DOUBLE`.
- New `fnv_hash()` built-in function for constructing hashed values. See [Impala Mathematical Functions](#) on page 374 for details.
- The clause `STORED AS PARQUET` is accepted as an equivalent for `STORED AS PARQUETFILE`. This more concise form is recommended for new code.

Because Impala 1.2.2 builds on a number of features introduced in 1.2.1, if you are upgrading from an older 1.1.x release straight to 1.2.2, also review [New Features in Impala 1.2.1](#) on page 680 to see features such as the `SHOW TABLE STATS` and `SHOW COLUMN STATS` statements, and user-defined functions (UDFs).

New Features in Impala 1.2.1



Note: Impala 1.2.1 works with CDH 4. Its feature set is a superset of features in the Impala 1.2.0 beta, with the exception of resource management, which relies on CDH 5.

Impala 1.2.1 includes new features for security, performance, and flexibility.

New user-visible features include:

- `SHOW TABLE STATS table_name` and `SHOW COLUMN STATS table_name` statements, to verify that statistics are available and to see the values used during query planning.
- `CREATE TABLE AS SELECT` syntax, to create a new table and transfer data into it in a single operation.
- `OFFSET` clause, for use with the `ORDER BY` and `LIMIT` clauses to produce “paged” result sets such as items 1-10, then 11-20, and so on.
- `NULLS FIRST` and `NULLS LAST` clauses to ensure consistent placement of `NULL` values in `ORDER BY` queries.

- New [built-in functions](#): `least()`, `greatest()`, `initcap()`.
- New aggregate function: `ndv()`, a fast alternative to `COUNT(DISTINCT col)` returning an approximate result.
- The `LIMIT` clause can now accept a numeric expression as an argument, rather than only a literal constant.
- The `SHOW CREATE TABLE` statement displays the end result of all the `CREATE TABLE` and `ALTER TABLE` statements for a particular table. You can use the output to produce a simplified setup script for a schema.
- The `--idle_query_timeout` and `--idle_session_timeout` options for `impalad` control the time intervals after which idle queries are cancelled, and idle sessions expire. See [Setting Timeout Periods for Daemons, Queries, and Sessions](#) on page 91 for details.
- User-defined functions (UDFs). This feature lets you transform data in very flexible ways, which is important when using Impala as part of an ETL or ELT pipeline. Prior to Impala 1.2, using UDFs required switching into Hive. Impala 1.2 can run scalar UDFs and user-defined aggregate functions (UDAs). Impala can run high-performance functions written in C++, or you can reuse existing Hive functions written in Java.

You create UDFs through the `CREATE FUNCTION` statement and drop them through the `DROP FUNCTION` statement. See [Impala User-Defined Functions \(UDFs\)](#) on page 487 for instructions about coding, building, and deploying UDFs, and [CREATE FUNCTION Statement](#) on page 248 and [DROP FUNCTION Statement](#) on page 275 for related SQL syntax.

- A new service automatically propagates changes to table data and metadata made by one Impala node, sending the new or updated metadata to all the other Impala nodes. The automatic synchronization mechanism eliminates the need to use the `INVALIDATE METADATA` and `REFRESH` statements after issuing Impala statements such as `CREATE TABLE`, `ALTER TABLE`, `DROP TABLE`, `INSERT`, and `LOAD DATA`.

For even more precise synchronization, you can enable the [SYNC DDL](#) query option before issuing a DDL, `INSERT`, or `LOAD DATA` statement. This option causes the statement to wait, returning only after the catalog service has broadcast the applicable changes to all Impala nodes in the cluster.



Note:

Because the catalog service only monitors operations performed through Impala, `INVALIDATE METADATA` and `REFRESH` are still needed on the Impala side after creating new tables or loading data through the Hive shell or by manipulating data files directly in HDFS. Because the catalog service broadcasts the result of the `REFRESH` and `INVALIDATE METADATA` statements to all Impala nodes, when you do need to use those statements, you can do so a single time rather than on every Impala node.

This service is implemented by the `catalogd` daemon. See [The Impala Catalog Service](#) on page 20 for details.

- `CREATE TABLE ... AS SELECT` syntax, to create a table and copy data into it in a single operation. See [CREATE TABLE Statement](#) on page 254 for details.
- The `CREATE TABLE` and `ALTER TABLE` statements have new clauses `TBLPROPERTIES` and `WITH SERDEPROPERTIES`. The `TBLPROPERTIES` clause lets you associate arbitrary items of metadata with a particular table as key-value pairs. The `WITH SERDEPROPERTIES` clause lets you specify the serializer/deserializer (SerDes) classes that read and write data for a table; although Impala does not make use of these properties, sometimes particular values are needed for Hive compatibility. See [CREATE TABLE Statement](#) on page 254 and [ALTER TABLE Statement](#) on page 230 for details.
- Delegation support lets you authorize certain OS users associated with applications (for example, `hue`), to submit requests using the credentials of other users. Only available in combination with CDH 5. See [Configuring Impala Delegation for Hue and BI Tools](#) on page 122 for details.
- Enhancements to `EXPLAIN` output. In particular, when you enable the new `EXPLAIN_LEVEL` query option, the `EXPLAIN` and `PROFILE` statements produce more verbose output showing estimated resource requirements and

whether table and column statistics are available for the applicable tables and columns. See [EXPLAIN Statement](#) on page 283 for details.

- `SHOW CREATE TABLE` summarizes the effects of the original `CREATE TABLE` statement and any subsequent `ALTER TABLE` statements, giving you a `CREATE TABLE` statement that will re-create the current structure and layout for a table.
- The `LIMIT` clause for queries now accepts an arithmetic expression, in addition to numeric literals.

New Features in Impala 1.2.0 (Beta)



Note: The Impala 1.2.0 beta release only works in combination with the beta version of CDH 5. The Impala 1.2.0 software is bundled together with the CDH 5 beta 1 download.

The Impala 1.2.0 beta includes new features for security, performance, and flexibility.

New user-visible features include:

- User-defined functions (UDFs). This feature lets you transform data in very flexible ways, which is important when using Impala as part of an ETL or ELT pipeline. Prior to Impala 1.2, using UDFs required switching into Hive. Impala 1.2 can run scalar UDFs and user-defined aggregate functions (UDAs). Impala can run high-performance functions written in C++, or you can reuse existing Hive functions written in Java.

You create UDFs through the `CREATE FUNCTION` statement and drop them through the `DROP FUNCTION` statement. See [Impala User-Defined Functions \(UDFs\)](#) on page 487 for instructions about coding, building, and deploying UDFs, and [CREATE FUNCTION Statement](#) on page 248 and [DROP FUNCTION Statement](#) on page 275 for related SQL syntax.

- A new service automatically propagates changes to table data and metadata made by one Impala node, sending the new or updated metadata to all the other Impala nodes. The automatic synchronization mechanism eliminates the need to use the `INVALIDATE METADATA` and `REFRESH` statements after issuing Impala statements such as `CREATE TABLE`, `ALTER TABLE`, `DROP TABLE`, `INSERT`, and `LOAD DATA`.



Note:

Because this service only monitors operations performed through Impala, `INVALIDATE METADATA` and `REFRESH` are still needed on the Impala side after creating new tables or loading data through the Hive shell or by manipulating data files directly in HDFS. Because the catalog service broadcasts the result of the `REFRESH` and `INVALIDATE METADATA` statements to all Impala nodes, when you do need to use those statements, you can do so a single time rather than on every Impala node.

This service is implemented by the `catalogd` daemon. See [The Impala Catalog Service](#) on page 20 for details.

- Integration with the YARN resource management framework. Only available in combination with CDH 5. This feature makes use of the underlying YARN service, plus an additional service (Llama) that coordinates requests to YARN for Impala resources, so that the Impala query only proceeds when all requested resources are available. See [Resource Management for Impala](#) on page 85 for full details.

On the Impala side, this feature involves some new startup options for the `impalad` daemon:

- `-enable_rm`
- `-llama_host`
- `-llama_port`
- `-llama_callback_port`
- `-cgroup_hierarchy_path`

For details of these startup options, see [Modifying Impala Startup Options](#) on page 45.

This feature also involves several new or changed query options that you can set through the `impala-shell` interpreter and apply within a specific session:

- `MEM_LIMIT`: the function of this existing option changes when Impala resource management is enabled.
- `YARN_POOL`: a new option. (Renamed to `RESOURCE_POOL` in Impala 1.3.0.)
- `V_CPU_CORES`: a new option.
- `RESERVATION_REQUEST_TIMEOUT`: a new option.

For details of these query options, see [impala-shell Query Options for Resource Management](#) on page 86.

- `CREATE TABLE ... AS SELECT` syntax, to create a table and copy data into it in a single operation. See [CREATE TABLE Statement](#) on page 254 for details.
- The `CREATE TABLE` and `ALTER TABLE` statements have a new `TBLPROPERTIES` clause that lets you associate arbitrary items of metadata with a particular table as key-value pairs. See [CREATE TABLE Statement](#) on page 254 and [ALTER TABLE Statement](#) on page 230 for details.
- Delegation support lets you authorize certain OS users associated with applications (for example, `hue`), to submit requests using the credentials of other users. Only available in combination with CDH 5. See [Configuring Impala Delegation for Hue and BI Tools](#) on page 122 for details.
- Enhancements to `EXPLAIN` output. In particular, when you enable the new `EXPLAIN_LEVEL` query option, the `EXPLAIN` and `PROFILE` statements produce more verbose output showing estimated resource requirements and whether table and column statistics are available for the applicable tables and columns. See [EXPLAIN Statement](#) on page 283 for details.

New Features in Impala 1.1.1

Impala 1.1.1 includes new features for security and stability.

New user-visible features include:

- Additional security feature: auditing. New startup options for `impalad` let you capture information about Impala queries that succeed or are blocked due to insufficient privileges. To take full advantage of this feature with Cloudera Manager, upgrade to Cloudera Manager 4.7 or higher. For details, see [Impala Security](#) on page 100.
- Parquet data files generated by Impala 1.1.1 are now compatible with the Parquet support in Hive. See [Incompatible Changes and Limitations in Apache Impala](#) on page 686 for the procedure to update older Impala-created Parquet files to be compatible with the Hive Parquet support.
- Additional improvements to stability and resource utilization for Impala queries.
- Additional enhancements for compatibility with existing file formats.

New Features in Impala 1.1

Impala 1.1 includes new features for security, performance, and usability.

New user-visible features include:

- Extensive new security features, built on top of the Sentry open source project. Impala now supports fine-grained authorization based on roles. A policy file determines which privileges on which schema objects (servers, databases, tables, and HDFS paths) are available to users based on their membership in groups. By assigning privileges for views, you can control access to table data at the column level. For details, see [Impala Security](#) on page 100.
- Impala 1.1 works with Cloudera Manager 4.6 or higher. To use Cloudera Manager to manage authorization for the Impala web UI (the web pages served from port 25000 by default), use Cloudera Manager 4.6.2 or higher.
- Impala can now create, alter, drop, and query views. Views provide a flexible way to set up simple aliases for complex queries; hide query details from applications and users; and simplify maintenance as you rename or reorganize databases, tables, and columns. See the overview section [Overview of Impala Views](#) on page 224 and the statements [CREATE VIEW Statement](#) on page 263, [ALTER VIEW Statement](#) on page 240, and [DROP VIEW Statement](#) on page 282.

- Performance is improved through a number of automatic optimizations. Resource consumption is also reduced for Impala queries. These improvements apply broadly across all kinds of workloads and file formats. The major areas of performance enhancement include:
 - Improved disk and thread scheduling, which applies to all queries.
 - Improved hash join and aggregation performance, which applies to queries with large build tables or a large number of groups.
 - Dictionary encoding with Parquet, which applies to Parquet tables with short string columns.
 - Improved performance on systems with SSDs, which applies to all queries and file formats.
- Some new built-in functions are implemented: [translate\(\)](#) to substitute characters within strings, [user\(\)](#) to check the login ID of the connected user.
- The new `WITH` clause for `SELECT` statements lets you simplify complicated queries in a way similar to creating a view. The effects of the `WITH` clause only last for the duration of one query, unlike views, which are persistent schema objects that can be used by multiple sessions or applications. See [WITH Clause](#) on page 324.
- An enhancement to `DESCRIBE` statement, `DESCRIBE FORMATTED table_name`, displays more detailed information about the table. This information includes the file format, location, delimiter, ownership, external or internal, creation and access times, and partitions. The information is returned as a result set that can be interpreted and used by a management or monitoring application. See [DESCRIBE Statement](#) on page 264.
- You can now insert a subset of columns for a table, with other columns being left as all `NULL` values. Or you can specify the columns in any order in the destination table, rather than having to match the order of the corresponding columns in the source. `VALUES` clause. This feature is known as “column permutation”. See [INSERT Statement](#) on page 286.
- The new `LOAD DATA` statement lets you load data into a table directly from an HDFS data file. This technique lets you minimize the number of steps in your ETL process, and provides more flexibility. For example, you can bring data into an Impala table in one step. Formerly, you might have created an external table where the data files are not entirely under your control, or copied the data files to Impala data directories manually, or loaded the original data into one table and then used the `INSERT` statement to copy it to a new table with a different file format, partitioning scheme, and so on. See [LOAD DATA Statement](#) on page 297.
- Improvements to Impala-HBase integration:
 - New query options for HBase performance: [HBASE_CACHE_BLOCKS](#) and [HBASE_CACHING](#).
 - Support for binary data types in HBase tables. See [Supported Data Types for HBase Columns](#) on page 609 for details.
- You can issue `REFRESH` as a SQL statement through any of the programming interfaces that Impala supports. `REFRESH` formerly had to be issued as a command through the `impala-shell` interpreter, and was not available through a JDBC or ODBC API call. As part of this change, the functionality of the `REFRESH` statement is divided between two statements. In Impala 1.1, `REFRESH` requires a table name argument and immediately reloads the metadata; the new `INVALIDATE METADATA` statement works the same as the Impala 1.0 `REFRESH` did: the table name argument is optional, and the metadata for one or all tables is marked as stale, but not actually reloaded until the table is queried. When you create a new table in the Hive shell or through a different Impala node, you must enter `INVALIDATE METADATA` with no table parameter before you can see the new table in `impala-shell`. See [REFRESH Statement](#) on page 300 and [INVALIDATE METADATA Statement](#) on page 294.

New Features in Impala 1.0.1

The primary enhancements in Impala 1.0.1 are internal, for compatibility with the new Cloudera Manager 4.6 release. Try out the new **Impala Query Monitoring** feature in Cloudera Manager 4.6, which requires Impala 1.0.1.

New user-visible features include:

- The `VALUES` clause lets you `INSERT` one or more rows using literals, function return values, or other expressions. For performance and scalability, you should still use `INSERT ... SELECT` for bringing large quantities of data into an Impala table. The `VALUES` clause is a convenient way to set up small tables, particularly for initial testing of SQL features that do not require large amounts of data. See [VALUES Clause](#) on page 291 for details.
- The `-B` and `-o` options of the `impala-shell` command can turn query results into delimited text files and store them in an output file. The plain text results are useful for using with other Hadoop components or Unix tools. In

benchmark tests, it is also faster to produce plain rather than pretty-printed results, and write to a file rather than to the screen, giving a more accurate picture of the actual query time.

- Several bug fixes. See [Issues Fixed in the 1.0.1 Release](#) on page 749 for details.

New Features in Impala 1.0

This version has multiple performance improvements and adds the following functionality:

- Several bug fixes. See [Issues Fixed in the 1.0 GA Release](#) on page 750.
- `ALTER TABLE` statement.
- [Hints](#) to allow specifying a particular join strategy.
- `REFRESH` for a single table.
- Dynamic resource management, allowing high concurrency for Impala queries.

New Features in Version 0.7 of the Impala Beta Release

This version has multiple performance improvements and adds the following functionality:

- Several bug fixes. See [Issues Fixed in Version 0.7 of the Beta Release](#) on page 753.
- Support for the Parquet file format. For more information on file formats, see [How Impala Works with Hadoop File Formats](#) on page 575.
- Added support for Avro.
- Support for the memory limits. For more information, see the example on modifying memory limits in [Modifying Impala Startup Options](#) on page 45.
- Bigger and faster joins through the addition of partitioned joins to the already supported broadcast joins.
- Fully distributed aggregations.
- Fully distributed top-n computation.
- Support for creating and altering tables.
- Support for GROUP BY with floats and doubles.

In this version, both CDH 4.1 and 4.2 are supported, but due to performance improvements added, we highly recommend you use CDH 4.2 or higher to see the full benefit. If you are using Cloudera Manager, version 4.5 is required.

New Features in Version 0.6 of the Impala Beta Release

- Several bug fixes. See [Issues Fixed in Version 0.6 of the Beta Release](#) on page 754.
- Added support for Impala on SUSE and Debian/Ubuntu. Impala is now supported on:
 - RHEL5.7/6.2 and Centos5.7/6.2
 - SUSE 11 with Service Pack 1 or higher
 - Ubuntu 10.04/12.04 and Debian 6.03
- Cloudera Manager 4.5 and CDH 4.2 support Impala 0.6.
- Support for the RCFile file format. For more information on file formats, see [Understanding File Formats](#).

New Features in Version 0.5 of the Impala Beta Release

- Several bug fixes. See [Issues Fixed in Version 0.5 of the Beta Release](#) on page 755.
- Added support for a JDBC driver that allows you to access Impala from a Java client. To use this feature, follow the instructions in [Configuring Impala to Work with JDBC](#) on page 36 to install the JDBC driver JARs on the client machine and modify the `CLASSPATH` on the client to include the JARs.

New Features in Version 0.4 of the Impala Beta Release

- Several bug fixes. See [Issues Fixed in Version 0.4 of the Beta Release](#) on page 755.
- Added support for Impala on RHEL5.7/Centos5.7. Impala is now supported on RHEL5.7/6.2 and Centos5.7/6.2.
- Cloudera Manager 4.1.3 supports Impala 0.4.

- The Impala debug webserver now has the ability to serve static files from `${IMPALA_HOME}/www`. This can be disabled by setting `--enable_webserver_doc_root=false` on the command line. As a result, Impala now uses the Twitter Bootstrap library to style its debug webpages, and the `/queries` page now tracks the last 25 queries run by each Impala daemon.
- Additional metrics available on the Impala Debug Webpage.

New Features in Version 0.3 of the Impala Beta Release

- Several bug fixes. See [Issues Fixed in Version 0.3 of the Beta Release](#) on page 756.
- The `state-store-service` binary has been renamed `statedstored`.
- The location of the Impala configuration files has changed from the `/usr/lib/impala/conf` directory to the `/etc/impala/conf` directory.

New Features in Version 0.2 of the Impala Beta Release

- Several bug fixes. See [Issues Fixed in Version 0.2 of the Beta Release](#) on page 756.
- **Added Default Query Options** Default query options override all default QueryOption values when starting `impalad`. The format is:

```
-default_query_options='key=value;key=value'
```

Incompatible Changes and Limitations in Apache Impala

The Impala version covered by this documentation library contains the following incompatible changes. These are things such as file format changes, removed features, or changes to implementation, default configuration, dependencies, or prerequisites that could cause issues during or after an Impala upgrade.

Even added SQL statements or clauses can produce incompatibilities, if you have databases, tables, or columns whose names conflict with the new keywords.

Incompatible Changes Introduced in Impala for CDH 5.9.x / Impala 2.7.x

- Bug fixes related to parsing of floating-point values (IMPALA-1731 and IMPALA-3868) can change the results of casting strings that represent invalid floating-point values. For example, formerly a string value beginning or ending with `inf`, such as `1.23inf` or `infinite`, now are converted to `NULL` when interpreted as a floating-point value. Formerly, they were interpreted as the special “infinity” value when converting from string to floating-point. Similarly, now only the string `NaN` (case-sensitive) is interpreted as the special “not a number” value. String values containing multiple dots, such as `3. .141` or `3.1.4.1`, are now interpreted as `NULL` rather than being converted to valid floating-point values.
- The column types shown in the `DESCRIBE FORMATTED` output are in uppercase, where formerly they were in lowercase. This is not an intended change and could be reverted in the future, when IMPALA-4372 is resolved.

Incompatible Changes Introduced in Impala for CDH 5.8.x / Impala 2.6.x

- The default for the `RUNTIME_FILTER_MODE` query option is changed to `GLOBAL` (the highest setting).
- The `RUNTIME_BLOOM_FILTER_SIZE` setting is now only used as a fallback if statistics are not available; otherwise, Impala uses the statistics to estimate the appropriate size to use for each filter.
- Admission control and dynamic resource pools are enabled by default. When upgrading from an earlier release, you must turn on these settings yourself if they are not already enabled. See [Admission Control and Query Queuing](#) on page 77 for details about admission control.
- Impala reserves some new keywords, in preparation for support for Kudu syntax: `buckets`, `delete`, `distribute`, `hash`, `ignore`, `split`, and `update`.

- For Kerberized clusters, the Catalog service now uses the Kerberos principal instead of the operating system user that runs the `catalogd` daemon. This eliminates the requirement to configure a `hadoop.user.group.static.mapping.overrides` setting to put the OS user into the Sentry administrative group, on clusters where the principal and the OS user name for this user are different.
- The mechanism for interpreting `DECIMAL` literals is improved, no longer going through an intermediate conversion step to `DOUBLE`:
 - Casting a `DECIMAL` value to `TIMESTAMP DOUBLE` produces a more precise value for the `TIMESTAMP` than formerly.
 - Certain function calls involving `DECIMAL` literals now succeed, when formerly they failed due to lack of a function signature with a `DOUBLE` argument.
- Improved type accuracy for `CASE` return values. If all `WHEN` clauses of the `CASE` expression are of `CHAR` type, the final result is also `CHAR` instead of being converted to `STRING`.
- The initial release of CDH 5.7 / Impala 2.5 sometimes has a higher peak memory usage than in previous releases while reading Parquet files. The following query options might help to reduce memory consumption in the Parquet scanner:
 - Reduce the number of scanner threads, for example: `set num_scanner_threads=30`
 - Reduce the batch size, for example: `set batch_size=512`
 - Increase the memory limit, for example: `set mem_limit=64g`

You can track the status of the fix for this issue at [IMPALA-3662](#).

- The `S3_SKIP_INSERT_STAGING` query option, which is enabled by default, increases the speed of `INSERT` operations for S3 tables. The speedup applies to regular `INSERT`, but not `INSERT OVERWRITE`. The tradeoff is the possibility of inconsistent output files left behind if a node fails during `INSERT` execution. See [S3_SKIP_INSERT_STAGING Query Option \(CDH 5.8 or higher only\)](#) on page 354 for details.

Certain features are turned off by default, to avoid regressions or unexpected behavior following an upgrade. Consider turning on these features after suitable testing:

- Impala now recognizes the `auth_to_local` setting, specified through the HDFS configuration setting `hadoop.security.auth_to_local`. This feature is disabled by default; to enable it, specify `--load_auth_to_local_rules=true` in the `impalad` configuration settings.
- A new query option, `PARQUET_ANNOTATE_STRINGS_UTF8`, makes Impala include the UTF-8 annotation metadata for `STRING`, `CHAR`, and `VARCHAR` columns in Parquet files created by `INSERT` or `CREATE TABLE AS SELECT` statements.
- A new query option, `PARQUET_FALLBACK_SCHEMA_RESOLUTION`, lets Impala locate columns within Parquet files based on column name rather than ordinal position. This enhancement improves interoperability with applications that write Parquet files with a different order or subset of columns than are used in the Impala table.

Incompatible Changes Introduced in Impala for CDH 5.7.x / Impala 2.5.x

- The admission control default limit for concurrent queries (the `max requests` setting) is now unlimited instead of 200.
- Multiplying a mixture of `DECIMAL` and `FLOAT` or `DOUBLE` values now returns `DOUBLE` rather than `DECIMAL`. This change avoids some cases where an intermediate value would underflow or overflow and become `NULL` unexpectedly. The results of multiplying `DECIMAL` and `FLOAT` or `DOUBLE` might now be slightly less precise than before. Previously, the intermediate types and thus the final result depended on the exact order of the values of different types being multiplied, which made the final result values difficult to reason about.
- Previously, the `_` and `%` wildcard characters for the `LIKE` operator would not match characters on the second or subsequent lines of multi-line string values. The fix for issue [IMPALA-2204](#) causes the wildcard matching to apply

to the entire string for values containing embedded `\n` characters. This could cause different results than in previous Impala releases for identical queries on identical data.

- Formerly, all Impala UDFs and UDAs required running the `CREATE FUNCTION` statements to re-create them after each `catalogd` restart. In CDH 5.7 / Impala 2.5 and higher, functions written in C++ are persisted across restarts, and the requirement to re-create functions only applies to functions written in Java. Adapt any function-reloading logic that you have added to your Impala environment.
- `CREATE TABLE LIKE` no longer inherits HDFS caching settings from the source table.
- The `SHOW DATABASES` statement now returns two columns rather than one. The second column includes the associated comment string, if any, for each database. Adjust any application code that examines the list of databases and assumes the result set contains only a single column.
- The output of the `SHOW FUNCTIONS` statement includes two new columns, showing the kind of the function (for example, `BUILTIN`) and whether or not the function persists across catalog server restarts. For example, the `SHOW FUNCTIONS` output for the `_impala_builtins` database starts with:

```


+-----+-----+-----+-----+
| return type | signature | binary type | is
persistent |          |              |
+-----+-----+-----+-----+
| BIGINT      | abs(BIGINT) | BUILTIN     | true
| DECIMAL(*,*) | abs(DECIMAL(*,*)) | BUILTIN     | true
| DOUBLE      | abs(DOUBLE) | BUILTIN     | true
| ...

```

Incompatible Changes Introduced in Impala for CDH 5.6.x / Impala 2.4.x

Other than support for DSSD storage, the Impala feature set for CDH 5.6 is the same as for CDH 5.5. Therefore, there are no incompatible changes for Impala introduced in CDH 5.6.

Incompatible Changes Introduced in Impala for CDH 5.5.x / Impala 2.3.x

 **Note:**

The use of the Llama component for integrated resource management within YARN is no longer supported with CDH 5.5 / Impala 2.3 and higher.

For clusters running Impala alongside other data management components, you define static service pools to define the resources available to Impala and other components. Then within the area allocated for Impala, you can create dynamic service pools, each with its own settings for the Impala admission control feature.

- If Impala encounters a Parquet file that is invalid because of an incorrect magic number, the query skips the file. This change is caused by the fix for issue [IMPALA-2130](#). Previously, Impala would attempt to read the file despite the possibility that the file was corrupted.
- Previously, calls to overloaded built-in functions could treat parameters as `DOUBLE` or `FLOAT` when no overload had a signature that matched the exact argument types. Now Impala prefers the function signature with `DECIMAL` parameters in this case. This change avoids a possible loss of precision in function calls such as `greatest(0, 99999.8888)`; now both parameters are treated as `DECIMAL` rather than `DOUBLE`, avoiding any loss of precision in the fractional value. This could cause slightly different results than in previous Impala releases for certain function calls.
- Formerly, adding or subtracting a large interval value to a `TIMESTAMP` could produce a nonsensical result. Now when the result goes outside the range of `TIMESTAMP` values, Impala returns `NULL`.

- Formerly, it was possible to accidentally create a table with identical row and column delimiters. This could happen unintentionally, when specifying one of the delimiters and using the default value for the other. Now an attempt to use identical delimiters still succeeds, but displays a warning message.
- Formerly, Impala could include snippets of table data in log files by default, for example when reporting conversion errors for data values. Now any such log messages are only produced at higher logging levels that you would enable only during debugging.

Incompatible Changes Introduced in Impala for CDH 5.4.x



Note: Impala 2.2.0 is available as part of CDH 5.4.0 and is not available for CDH 4. Cloudera does not intend to release future versions of Impala for CDH 4 outside patch and maintenance releases if required. Given the end-of-maintenance status for CDH 4, Cloudera recommends all customers to migrate to a recent CDH 5 release.

Changes to File Handling

Impala queries ignore files with extensions commonly used for temporary work files by Hadoop tools. Any files with extensions `.tmp` or `.copying` are not considered part of the Impala table. The suffix matching is case-insensitive, so for example Impala ignores both `.copying` and `.COPYING` suffixes.

The log rotation feature in Impala 2.2.0 and higher means that older log files are now removed by default. The default is to preserve the latest 10 log files for each severity level, for each Impala-related daemon. If you have set up your own log rotation processes that expect older files to be present, either adjust your procedures or change the Impala `-max_log_files` setting.

Changes to Prerequisites

The prerequisite for CPU architecture has been relaxed in Impala 2.2.0 and higher. From this release onward, Impala works on CPUs that have the SSE3 instruction set. The SSE4 instruction set is no longer required. This relaxed requirement simplifies the upgrade planning from Impala 1.x releases, which also worked on SSE3-enabled processors.

Incompatible Changes Introduced in Impala for CDH 5.3.x

Changes to Prerequisites

Currently, Impala 2.1.x does not function on CPUs without the SSE4.1 instruction set. This minimum CPU requirement is higher than in previous versions, which relied on the older SSE3 instruction set. Check the CPU level of the hosts in your cluster before upgrading to Impala 2.1.x or CDH 5.3.x.

Changes to Output Format

The “small query” optimization feature introduces some new information in the `EXPLAIN` plan, which you might need to account for if you parse the text of the plan output.

New Reserved Words

New SQL syntax introduces additional reserved words: `FOR`, `GRANT`, `REVOKE`, `ROLE`, `ROLES`, `INCREMENTAL`.

Incompatible Changes Introduced in Impala 2.0.5 / CDH 5.2.6

No incompatible changes.



Note: Impala 2.0.5 is available as part of CDH 5.2.6, not under CDH 4.

Incompatible Changes Introduced in Impala 2.0.4 / CDH 5.2.5

No incompatible changes.



Note: Impala 2.0.4 is available as part of CDH 5.2.5, not under CDH 4.

Incompatible Changes Introduced in Impala 2.0.3 / CDH 5.2.4



Note: Impala 2.0.3 is available as part of CDH 5.2.4, not under CDH 4.

Incompatible Changes Introduced in Impala 2.0.2 / CDH 5.2.3

No incompatible changes.



Note: Impala 2.0.2 is available as part of CDH 5.2.3, not under CDH 4.

Incompatible Changes Introduced in Impala 2.0.1 / CDH 5.2.1

- The `INSERT` statement has always left behind a hidden work directory inside the data directory of the table. Formerly, this hidden work directory was named `.impala_insert_staging`. In Impala 2.0.1 and later, this directory name is changed to `_impala_insert_staging`. (While HDFS tools are expected to treat names beginning either with underscore and dot as hidden, in practice names beginning with an underscore are more widely supported.) If you have any scripts, cleanup jobs, and so on that rely on the name of this work directory, adjust them to use the new name.
- The `abs()` function now takes a broader range of numeric types as arguments, and the return type is the same as the argument type.
- Shorthand notation for character classes in regular expressions, such as `\d` for digit, are now available again in regular expression operators and functions such as `regexp_extract()` and `regexp_replace()`. Some other differences in regular expression behavior remain between Impala 1.x and Impala 2.x releases. See [Incompatible Changes Introduced in Impala 2.0.0 / CDH 5.2.0](#) on page 690 for details.

Incompatible Changes Introduced in Impala 2.0.0 / CDH 5.2.0

Changes to Prerequisites

Currently, Impala 2.0.x does not function on CPUs without the SSE4.1 instruction set. This minimum CPU requirement is higher than in previous versions, which relied on the older SSSE3 instruction set. Check the CPU level of the hosts in your cluster before upgrading to Impala 2.0.x or CDH 5.2.x.

Changes to Query Syntax

The new syntax where query hints are allowed in comments causes some changes in the way comments are parsed in the `impala-shell` interpreter. Previously, you could end a `--` comment line with a semicolon and `impala-shell` would treat that as a no-op statement. Now, a comment line ending with a semicolon is passed as an empty statement to the Impala daemon, where it is flagged as an error.

Impala 2.0 and later uses a different support library for regular expression parsing than in earlier Impala versions. Now, Impala uses the [Google RE2 library](#) rather than Boost for evaluating regular expressions. This implementation change causes some differences in the allowed regular expression syntax, and in the way certain regex operators are interpreted. The following are some of the major differences (not necessarily a complete list):

- `. * ?` notation for non-greedy matches is now supported, where it was not in earlier Impala releases.
- By default, `^` and `$` now match only begin/end of buffer, not begin/end of each line. This behavior can be overridden in the regex itself using the `m` flag.
- By default, `.` does not match newline. This behavior can be overridden in the regex itself using the `s` flag.
- `\z` is not supported.
- `<` and `>` for start of word and end of word are not supported.
- Lookahead and lookbehind are not supported.
- Shorthand notation for character classes, such as `\d` for digit, is not recognized. (This restriction is lifted in Impala 2.0.1, which restores the shorthand notation.)

Changes to Output Format

In Impala 2.0 and later, `user()` returns the full Kerberos principal string, such as `user@example.com`, in a Kerberized environment.

The changed format for the user name in secure environments is also reflected where the user name is displayed in the output of the `PROFILE` command.

In the output from `SHOW FUNCTIONS`, `SHOW AGGREGATE FUNCTIONS`, and `SHOW ANALYTIC FUNCTIONS`, arguments and return types of arbitrary `DECIMAL` scale and precision are represented as `DECIMAL(*,*)`. Formerly, these items were displayed as `DECIMAL(-1,-1)`.

Changes to Query Options

The `PARQUET_COMPRESSION_CODEC` query option has been replaced by the `COMPRESSION_CODEC` query option.

Changes to Configuration Options

The meaning of the `--idle_query_timeout` configuration option is changed, to accommodate the new `QUERY_TIMEOUT_S` query option. Rather than setting an absolute timeout period that applies to all queries, it now sets a maximum timeout period, which can be adjusted downward for individual queries by specifying a value for the `QUERY_TIMEOUT_S` query option. In sessions where no `QUERY_TIMEOUT_S` query option is specified, the `--idle_query_timeout` timeout period applies the same as in earlier versions.

The `--strict_unicode` option of `impala-shell` was removed. To avoid problems with Unicode values in `impala-shell`, define the following locale setting before running `impala-shell`:

```
export LC_CTYPE=en_US.UTF-8
```

New Reserved Words

Some new SQL syntax requires the addition of new reserved words: `ANTI`, `ANALYTIC`, `OVER`, `PRECEDING`, `UNBOUNDED`, `FOLLOWING`, `CURRENT`, `ROWS`, `RANGE`, `CHAR`, `VARCHAR`.

Changes to Data Files

The default Parquet block size for Impala is changed from 1 GB to 256 MB. This change could have implications for the sizes of Parquet files produced by `INSERT` and `CREATE TABLE AS SELECT` statements.

Although older Impala releases typically produced files that were smaller than the old default size of 1 GB, now the file size matches more closely whatever value is specified for the `PARQUET_FILE_SIZE` query option. Thus, if you use a non-default value for this setting, the output files could be larger than before. They still might be somewhat smaller than the specified value, because Impala makes conservative estimates about the space needed to represent each column as it encodes the data.

When you do not specify an explicit value for the `PARQUET_FILE_SIZE` query option, Impala tries to keep the file size within the 256 MB default size, but Impala might adjust the file size to be somewhat larger if needed to accommodate the layout for *wide* tables, that is, tables with hundreds or thousands of columns.

This change is unlikely to affect memory usage while writing Parquet files, because Impala does not pre-allocate the memory needed to hold the entire Parquet block.

Incompatible Changes Introduced in Impala 1.4.4 / CDH 5.1.5

No incompatible changes.



Note: Impala 1.4.4 is available as part of CDH 5.1.5, not under CDH 4.

Incompatible Changes Introduced in Impala 1.4.3 / CDH 5.1.4

No incompatible changes. The TLS/SSL security fix does not require any change in the way you interact with Impala.



Note: Impala 1.4.3 is available as part of CDH 5.1.4, and under CDH 4.

Incompatible Changes Introduced in Impala 1.4.2 / CDH 5.1.3

None. Impala 1.4.2 is purely a bug-fix release. It does not include any incompatible changes.



Note: Impala 1.4.2 is only available as part of CDH 5.1.3, not under CDH 4.

Incompatible Changes Introduced in Impala 1.4.1 / CDH 5.1.2

None. Impala 1.4.1 is purely a bug-fix release. It does not include any incompatible changes.

Incompatible Changes Introduced in Impala 1.4.0 / CDH 5.1.0

- There is a slight change to required security privileges in the Sentry framework. To create a new object, now you need the `ALL` privilege on the parent object. For example, to create a new table, view, or function requires having the `ALL` privilege on the database containing the new object.
- With the ability of `ORDER BY` queries to process unlimited amounts of data with no `LIMIT` clause, the query options `DEFAULT_ORDER_BY_LIMIT` and `ABORT_ON_DEFAULT_LIMIT_EXCEEDED` are now deprecated and have no effect.
- There are some changes to the list of reserved words. The following keywords are new:
 - `API_VERSION`
 - `BINARY`
 - `CACHED`
 - `CLASS`
 - `PARTITIONS`
 - `PRODUCED`
 - `UNCACHED`

The following were formerly reserved keywords, but are no longer reserved:

- `COUNT`
- `GROUP_CONCAT`

- NDV
- SUM
- The fix for issue [IMPALA-973](#) changes the behavior of the `INVALIDATE METADATA` statement regarding nonexistent tables. In Impala 1.4.0 and higher, the statement returns an error if the specified table is not in the metastore database at all. It completes successfully if the specified table is in the metastore database but not yet recognized by Impala, for example if the table was created through Hive. Formerly, you could issue this statement for a completely nonexistent table, with no error.

Incompatible Changes Introduced in Impala 1.3.3 / CDH 5.0.5

No incompatible changes. The TLS/SSL security fix does not require any change in the way you interact with Impala.



Note: Impala 1.3.3 is only available as part of CDH 5.0.5, not under CDH 4.

Incompatible Changes Introduced in Impala 1.3.2 / CDH 5.0.4

With the fix for [IMPALA-1019](#), you can use HDFS caching for files that are accessed by Impala.



Note: Impala 1.3.2 is only available as part of CDH 5.0.4, not under CDH 4.

Incompatible Changes Introduced in Impala 1.3.1 / CDH 5.0.3

- In Impala 1.3.1 and higher, the `REGEXP` and `RLIKE` operators now match a regular expression string that occurs anywhere inside the target string, the same as if the regular expression was enclosed on each side by `.*`. See [REGEXP Operator](#) on page 216 for examples. Previously, these operators only succeeded when the regular expression matched the entire target string. This change improves compatibility with the regular expression support for popular database systems. There is no change to the behavior of the `regexp_extract()` and `regexp_replace()` built-in functions.
- The result set for the `SHOW FUNCTIONS` statement includes a new first column, with the data type of the return value.

Incompatible Changes Introduced in Impala 1.3.0 / CDH 5.0.0

- The `EXPLAIN_LEVEL` query option now accepts numeric options from 0 (most concise) to 3 (most verbose), rather than only 0 or 1. If you formerly used `SET EXPLAIN_LEVEL=1` to get detailed explain plans, switch to `SET EXPLAIN_LEVEL=3`. If you used the mnemonic keyword (`SET EXPLAIN_LEVEL=verbose`), you do not need to change your code because now level 3 corresponds to `verbose`.
- The keyword `DECIMAL` is now a reserved word. If you have any databases, tables, columns, or other objects already named `DECIMAL`, quote any references to them using backticks (```) to avoid name conflicts with the keyword.



Note: Although the `DECIMAL` keyword is a reserved word, currently Impala does not support `DECIMAL` as a data type for columns.

- The query option named `YARN_POOL` during the CDH 5 beta period is now named `REQUEST_POOL` to reflect its broader use with the Impala admission control feature.
- There are some changes to the list of reserved words.
 - The names of aggregate functions are no longer reserved words, so you can have databases, tables, columns, or other objects named `AVG`, `MIN`, and so on without any name conflicts.

- The internal function names `DISTINCTPC` and `DISTINCTPCSA` are no longer reserved words, although `DISTINCT` is still a reserved word.
- The keywords `CLOSE_FN` and `PREPARE_FN` are now reserved words.
- The HDFS property `dfs.client.file-block-storage-locations.timeout` was renamed to `dfs.client.file-block-storage-locations.timeout.millis`, to emphasize that the unit of measure is milliseconds, not seconds. Impala requires a timeout of at least 10 seconds, making the minimum value for this setting 10000. On systems not managed by Cloudera Manager, you might need to edit the `hdfs-site.xml` file in the Impala configuration directory for the new name and minimum value.

Incompatible Changes Introduced in Impala 1.2.4

There are no incompatible changes introduced in Impala 1.2.4.

Previously, after creating a table in Hive, you had to issue the `INVALIDATE METADATA` statement with no table name, a potentially expensive operation on clusters with many databases, tables, and partitions. Starting in Impala 1.2.4, you can issue the statement `INVALIDATE METADATA table_name` for a table newly created through Hive. Loading the metadata for only this one table is faster and involves less network overhead. Therefore, you might revisit your setup DDL scripts to add the table name to `INVALIDATE METADATA` statements, in cases where you create and populate the tables through Hive before querying them through Impala.

Incompatible Changes Introduced in Impala 1.2.3

Because the feature set of Impala 1.2.3 is identical to Impala 1.2.2, there are no new incompatible changes. See [Incompatible Changes Introduced in Impala 1.2.2](#) on page 694 if you are upgrading from Impala 1.2.1 or 1.1.x.

Incompatible Changes Introduced in Impala 1.2.2

The following changes to SQL syntax and semantics in Impala 1.2.2 could require updates to your SQL code, or schema objects such as tables or views:

- With the addition of the `CROSS JOIN` keyword, you might need to rewrite any queries that refer to a table named `CROSS` or use the name `CROSS` as a table alias:

```
-- Formerly, 'cross' in this query was an alias for t1
-- and it was a normal join query.
-- In 1.2.2 and higher, CROSS JOIN is a keyword, so 'cross'
-- is not interpreted as a table alias, and the query
-- uses the special CROSS JOIN processing rather than a
-- regular join.
select * from t1 cross join t2...

-- Now if CROSS is used in other context such as a table or column name,
-- use backticks to escape it.
create table `cross` (x int);
select * from `cross`;
```

- Formerly, a `DROP DATABASE` statement in Impala would not remove the top-level HDFS directory for that database. The `DROP DATABASE` has been enhanced to remove that directory. (You still need to drop all the tables inside the database first; this change only applies to the top-level directory for the entire database.)
- The keyword `PARQUET` is introduced as a synonym for `PARQUETFILE` in the `CREATE TABLE` and `ALTER TABLE` statements, because that is the common name for the file format. (As opposed to `SequenceFile` and `RCFile` where the “File” suffix is part of the name.) Documentation examples have been changed to prefer the new shorter keyword. The `PARQUETFILE` keyword is still available for backward compatibility with older Impala versions.
- New overloads are available for several operators and built-in functions, allowing you to insert their result values into smaller numeric columns such as `INT`, `SMALLINT`, `TINYINT`, and `FLOAT` without using a `CAST()` call. If you remove the `CAST()` calls from `INSERT` statements, those statements might not work with earlier versions of Impala.

Because many users are likely to upgrade straight from Impala 1.x to Impala 1.2.2, also read [Incompatible Changes Introduced in Impala 1.2.1](#) on page 695 for things to note about upgrading to Impala 1.2.x in general.

In a Cloudera Manager environment, the catalog service is not recognized or managed by Cloudera Manager versions prior to 4.8. Cloudera Manager 4.8 and higher require the catalog service to be present for Impala. Therefore, if you upgrade to Cloudera Manager 4.8 or higher, you must also upgrade Impala to 1.2.1 or higher. Likewise, if you upgrade Impala to 1.2.1 or higher, you must also upgrade Cloudera Manager to 4.8 or higher.

Incompatible Changes Introduced in Impala 1.2.1

The following changes to SQL syntax and semantics in Impala 1.2.1 could require updates to your SQL code, or schema objects such as tables or views:

- In Impala 1.2.1 and higher, all `NULL` values come at the end of the result set for `ORDER BY . . . ASC` queries, and at the beginning of the result set for `ORDER BY . . . DESC` queries. In effect, `NULL` is considered greater than all other values for sorting purposes. The original Impala behavior always put `NULL` values at the end, even for `ORDER BY . . . DESC` queries. The new behavior in Impala 1.2.1 makes Impala more compatible with other popular database systems. In Impala 1.2.1 and higher, you can override or specify the sorting behavior for `NULL` by adding the clause `NULLS FIRST` or `NULLS LAST` at the end of the `ORDER BY` clause.

Impala 1.2.1 goes along with CDH 4.5 and Cloudera Manager 4.8. If you used the beta version Impala 1.2.0 that came with the beta of CDH 5, Impala 1.2.1 includes all the features of Impala 1.2.0 except for resource management, which relies on the YARN framework from CDH 5.

The new `catalogd` service might require changes to any user-written scripts that stop, start, or restart Impala services, install or upgrade Impala packages, or issue `REFRESH` or `INVALIDATE METADATA` statements:

- See [Installing Impala](#) on page 29, [Upgrading Impala](#) on page 40 and [Starting Impala](#) on page 44, for usage information for the `catalogd` daemon.
- The `REFRESH` and `INVALIDATE METADATA` statements are no longer needed when the `CREATE TABLE`, `INSERT`, or other table-changing or data-changing operation is performed through Impala. These statements are still needed if such operations are done through Hive or by manipulating data files directly in HDFS, but in those cases the statements only need to be issued on one Impala node rather than on all nodes. See [REFRESH Statement](#) on page 300 and [INVALIDATE METADATA Statement](#) on page 294 for the latest usage information for those statements.
- See [The Impala Catalog Service](#) on page 20 for background information on the `catalogd` service.

In a Cloudera Manager environment, the catalog service is not recognized or managed by Cloudera Manager versions prior to 4.8. Cloudera Manager 4.8 and higher require the catalog service to be present for Impala. Therefore, if you upgrade to Cloudera Manager 4.8 or higher, you must also upgrade Impala to 1.2.1 or higher. Likewise, if you upgrade Impala to 1.2.1 or higher, you must also upgrade Cloudera Manager to 4.8 or higher.

Incompatible Changes Introduced in Impala 1.2.0 (Beta)

There are no incompatible changes to SQL syntax in Impala 1.2.0 (beta).

Because Impala 1.2.0 is bundled with the CDH 5 beta download and depends on specific levels of Apache Hadoop components supplied with CDH 5, you can only install it in combination with the CDH 5 beta.

The new `catalogd` service might require changes to any user-written scripts that stop, start, or restart Impala services, install or upgrade Impala packages, or issue `REFRESH` or `INVALIDATE METADATA` statements:

- See [Installing Impala](#) on page 29, [Upgrading Impala](#) on page 40 and [Starting Impala](#) on page 44, for usage information for the `catalogd` daemon.
- The `REFRESH` and `INVALIDATE METADATA` statements are no longer needed when the `CREATE TABLE`, `INSERT`, or other table-changing or data-changing operation is performed through Impala. These statements are still needed if such operations are done through Hive or by manipulating data files directly in HDFS, but in those cases the statements only need to be issued on one Impala node rather than on all nodes. See [REFRESH Statement](#) on page 300 and [INVALIDATE METADATA Statement](#) on page 294 for the latest usage information for those statements.

- See [The Impala Catalog Service](#) on page 20 for background information on the `catalogd` service.

The new resource management feature interacts with both YARN and Llama services, which are available in CDH 5. These services are set up for you automatically in a Cloudera Manager (CM) environment. For information about setting up the YARN and Llama services, see the instructions for [YARN](#) and [Llama](#) in the *CDH 5 Documentation*.

Incompatible Changes Introduced in Impala 1.1.1

There are no incompatible changes in Impala 1.1.1.

Previously, it was not possible to create Parquet data through Impala and reuse that table within Hive. Now that Parquet support is available for Hive 10, reusing existing Impala Parquet data files in Hive requires updating the table metadata. Use the following command if you are already running Impala 1.1.1:

```
ALTER TABLE table_name SET FILEFORMAT PARQUETFILE;
```

If you are running a level of Impala that is older than 1.1.1, do the metadata update through Hive:

```
ALTER TABLE table_name SET SERDE 'parquet.hive.serde.ParquetHiveSerDe';  
ALTER TABLE table_name SET FILEFORMAT  
  INPUTFORMAT "parquet.hive.DeprecatedParquetInputFormat "  
  OUTPUTFORMAT "parquet.hive.DeprecatedParquetOutputFormat ";
```

Impala 1.1.1 and higher can reuse Parquet data files created by Hive, without any action required.

As usual, make sure to upgrade the Impala LZO support package to the latest level at the same time as you upgrade the Impala server.

Incompatible Change Introduced in Impala 1.1

- The `REFRESH` statement now requires a table name; in Impala 1.0, the table name was optional. This syntax change is part of the internal rework to make `REFRESH` a true Impala SQL statement so that it can be called through the JDBC and ODBC APIs. `REFRESH` now reloads the metadata immediately, rather than marking it for update the next time any affected table is accessed. The previous behavior, where omitting the table name caused a refresh of the entire Impala metadata catalog, is available through the new `INVALIDATE METADATA` statement. `INVALIDATE METADATA` can be specified with a table name to affect a single table, or without a table name to affect the entire metadata catalog; the relevant metadata is reloaded the next time it is requested during the processing for a SQL statement. See [REFRESH Statement](#) on page 300 and [INVALIDATE METADATA Statement](#) on page 294 for the latest details about these statements.

Incompatible Changes Introduced in Impala 1.0

- If you use LZO-compressed text files, when you upgrade Impala to version 1.0, also update the `impala-lzo-cdh4` to the latest level. See [Using LZO-Compressed Text Files](#) on page 580 for details.
- Cloudera Manager 4.5.2 and higher only supports Impala 1.0 and higher, and vice versa. If you upgrade to Impala 1.0 or higher managed by Cloudera Manager, you must also upgrade Cloudera Manager to version 4.5.2 or higher. If you upgrade from an earlier version of Cloudera Manager, and were using Impala, you must also upgrade Impala to version 1.0 or higher. The beta versions of Impala are no longer supported as of the release of Impala 1.0.

Incompatible Change Introduced in Version 0.7 of the Impala Beta Release

- The defaults for the `-nn` and `-nn_port` flags have changed and are now read from `core-site.xml`. Impala prints the values of `-nn` and `-nn_port` to the log when it starts. The ability to set `-nn` and `-nn_port` on the command line is deprecated in 0.7 and may be removed in Impala 0.8.

Incompatible Change Introduced in Version 0.6 of the Impala Beta Release

- Cloudera Manager 4.5 supports only version 0.6 of the Impala Beta Release. It does not support the earlier beta versions. If you upgrade your Cloudera Manager installation, you must also upgrade Impala to beta version 0.6. If you upgrade Impala to beta version 0.6, you must upgrade Cloudera Manager to 4.5.

Incompatible Change Introduced in Version 0.4 of the Impala Beta Release

- Cloudera Manager 4.1.3 supports only version 0.4 of the Impala Beta Release. It does not support the earlier beta versions. If you upgrade your Cloudera Manager installation, you must also upgrade Impala to beta version 0.4. If you upgrade Impala to beta version 0.4, you must upgrade Cloudera Manager to 4.1.3.

Incompatible Change Introduced in Version 0.3 of the Impala Beta Release

- Cloudera Manager 4.1.2 supports only version 0.3 of the Impala Beta Release. It does not support the earlier beta versions. If you upgrade your Cloudera Manager installation, you must also upgrade Impala to beta version 0.3. If you upgrade Impala to beta version 0.3, you must upgrade Cloudera Manager to 4.1.2.

Known Issues and Workarounds in Impala

The following sections describe known issues and workarounds in Impala, as of the current production release. This page summarizes the most serious or frequently encountered issues in the current release, to help you make planning decisions about installing and upgrading. Any workarounds are listed here. The bug links take you to the Impala issues site, where you can see the diagnosis and whether a fix is in the pipeline.



Note: The online issue tracking system for Impala contains comprehensive information and is updated in real time. To verify whether an issue you are experiencing has already been reported, or which release an issue is fixed in, search on the [issues.cloudera.org JIRA tracker](https://issues.cloudera.org).

For issues fixed in various Impala releases, see [Fixed Issues in Apache Impala](#) on page 708.

Impala Known Issues: Crashes and Hangs

These issues can cause Impala to quit or become unresponsive.

Setting BATCH_SIZE query option too large can cause a crash

Using a value in the millions for the BATCH_SIZE query option, together with wide rows or large string values in columns, could cause a memory allocation of more than 2 GB resulting in a crash.

Bug: [IMPALA-3069](#)

Severity: High

Resolution: Fixed in CDH 5.9.0 / Impala 2.7.0.

Malformed Avro data, such as out-of-bounds integers or values in the wrong format, could cause a crash when queried.

Bug: [IMPALA-3441](#)

Severity: High

Resolution: Fixed in CDH 5.9.0 / Impala 2.7.0 and CDH 5.8.2 / Impala 2.6.2.

Queries may hang on server-to-server exchange errors

The `DataStreamSender::Channel::CloseInternal()` does not close the channel on an error. This causes the node on the other side of the channel to wait indefinitely, causing a hang.

Bug: [IMPALA-2592](#)

Resolution: Fixed in CDH 5.7.0 / Impala 2.5.0.

Impala Release Notes

Impalad is crashing if udf jar is not available in hdfs location for first time

If the JAR file corresponding to a Java UDF is removed from HDFS after the Impala `CREATE FUNCTION` statement is issued, the `impalad` daemon crashes.

Bug: [IMPALA-2365](#)

Resolution: Fixed in CDH 5.7.0 / Impala 2.5.0.

Impala Known Issues: Performance

These issues involve the performance of operations such as queries or DDL statements.

Slow DDL statements for tables with large number of partitions

DDL statements for tables with a large number of partitions might be slow.

Bug: <https://issues.cloudera.org/browse/IMPALA-1480>IMPALA-1480

Workaround: Run the DDL statement in Hive if the slowness is an issue.

Resolution: Fixed in CDH 5.7.0 / Impala 2.5.0.

Impala Known Issues: Usability

These issues affect the convenience of interacting directly with Impala, typically through the Impala shell or Hue.

Unexpected privileges in show output

Due to a timing condition in updating cached policy data from Sentry, the `SHOW` statements for Sentry roles could sometimes display out-of-date role settings. Because Impala rechecks authorization for each SQL statement, this discrepancy does not represent a security issue for other statements.

Bug: [IMPALA-3133](#)

Severity: High

Resolution: Fixes have been issued for some but not all CDH / Impala releases. Check the JIRA for details of fix releases.

Resolution: Fixed in CDH 5.8.0 / Impala 2.6.0 and CDH 5.7.1 / Impala 2.5.1.

Less than 100% progress on completed simple SELECT queries

Simple `SELECT` queries show less than 100% progress even though they are already completed.

Bug: [IMPALA-1776](#)

Unexpected column overflow behavior with INT datatypes

Impala does not return column overflows as `NULL`, so that customers can distinguish between `NULL` data and overflow conditions similar to how they do so with traditional database systems. Impala returns the largest or smallest value in the range for the type. For example, valid values for a `tinyint` range from -128 to 127. In Impala, a `tinyint` with a value of -200 returns -128 rather than `NULL`. A `tinyint` with a value of 200 returns 127.

Bug: [IMPALA-3123](#)

Impala Known Issues: JDBC and ODBC Drivers

These issues affect applications that use the JDBC or ODBC APIs, such as business intelligence tools or custom-written applications in languages such as Java or C++.

ImpalaODBC: Can not get the value in the `SQLGetData(m-x th column)` after the `SQLBindCol(m th column)`

If the ODBC `SQLGetData` is called on a series of columns, the function calls must follow the same order as the columns. For example, if data is fetched from column 2 then column 1, the `SQLGetData` call for column 1 returns `NULL`.

Bug: [IMPALA-1792](#)

Workaround: Fetch columns in the same order they are defined in the table.

Impala Known Issues: Security

These issues relate to security features, such as Kerberos authentication, Sentry authorization, encryption, auditing, and redaction.

Kerberos tickets must be renewable

In a Kerberos environment, the `impalad` daemon might not start if Kerberos tickets are not renewable.

Workaround: Configure your KDC to allow tickets to be renewed, and configure `krb5.conf` to request renewable tickets.

Impala Known Issues: Resources

These issues involve memory or disk usage, including out-of-memory conditions, the spill-to-disk feature, and resource management features.

Impala catalogd heap issues when upgrading to 5.7

The default heap size for Impala `catalogd` has changed in CDH 5.7 / Impala 2.5 and higher:

- Before 5.7, by default `catalogd` was using the JVM's default heap size, which is the smaller of 1/4th of the physical memory or 32 GB.
- Starting with CDH 5.7.0, the default `catalogd` heap size is 4 GB.

For example, on a host with 128GB physical memory this will result in `catalogd` heap decreasing from 32GB to 4GB. This can result in out-of-memory errors in `catalogd` and leading to query failures.

Severity: High

Workaround: Increase the `catalogd` memory limit as follows.

For schemas with large numbers of tables, partitions, and data files, the `catalogd` daemon might encounter an out-of-memory error. To increase the memory limit for the `catalogd` daemon:

1. Check current memory usage for the `catalogd` daemon by running the following commands on the host where that daemon runs on your cluster:

```

jcmd catalogd_pid VM.flags
jmap -heap catalogd_pid

```

2. Decide on a large enough value for the `catalogd` heap. You express it as an environment variable value as follows:

```

JAVA_TOOL_OPTIONS="-Xmx8g"

```

3. On systems managed by Cloudera Manager, include this value in the configuration field **Java Heap Size of Catalog Server in Bytes** (Cloudera Manager 5.7 and higher), or **Impala Catalog Server Environment Advanced Configuration Snippet (Safety Valve)** (prior to Cloudera Manager 5.7). Then restart the Impala service.
4. On systems not managed by Cloudera Manager, put this environment variable setting into the startup script for the `catalogd` daemon, then restart the `catalogd` daemon.
5. Use the same `jcmd` and `jmap` commands as earlier to verify that the new settings are in effect.

Breakpad minidumps can be very large when the thread count is high

The size of the breakpad minidump files grows linearly with the number of threads. By default, each thread adds 8 KB to the minidump size. Minidump files could consume significant disk space when the daemons have a high number of threads.

Bug: [IMPALA-3509](#)

Severity: High

Workaround: Add `--minidump_size_limit_hint_kb=size` to set a soft upper limit on the size of each minidump file. If the minidump file would exceed that limit, Impala reduces the amount of information for each thread from 8 KB to 2 KB. (Full thread information is captured for the first 20 threads, then 2 KB per thread after that.) The minidump file can still grow larger than the “hinted” size. For example, if you have 10,000 threads, the minidump file can be more than 20 MB.

Parquet scanner memory increase after IMPALA-2736

The initial release of CDH 5.8 / Impala 2.6 sometimes has a higher peak memory usage than in previous releases while reading Parquet files.

CDH 5.8 / Impala 2.6 addresses the issue IMPALA-2736, which improves the efficiency of Parquet scans by up to 2x. The faster scans may result in a higher peak memory consumption compared to earlier versions of Impala due to the new column-wise row materialization strategy. You are likely to experience higher memory consumption in any of the following scenarios:

- Very wide rows due to projecting many columns in a scan.
- Very large rows due to big column values, for example, long strings or nested collections with many items.
- Producer/consumer speed imbalances, leading to more rows being buffered between a scan (producer) and downstream (consumer) plan nodes.

Bug: [IMPALA-3662](#)

Severity: High

Workaround: The following query options might help to reduce memory consumption in the Parquet scanner:

- Reduce the number of scanner threads, for example: `set num_scanner_threads=30`
- Reduce the batch size, for example: `set batch_size=512`
- Increase the memory limit, for example: `set mem_limit=64g`

Process mem limit does not account for the JVM's memory usage

Some memory allocated by the JVM used internally by Impala is not counted against the memory limit for the `impalad` daemon.

Bug: [IMPALA-691](#)

Workaround: To monitor overall memory usage, use the `top` command, or add the memory figures in the Impala web UI `/memz` tab to JVM memory usage shown on the `/metrics` tab.

Fix issues with the legacy join and agg nodes using `--enable_partitioned_hash_join=false` and `--enable_partitioned_aggregation=false`

Bug: [IMPALA-2375](#)

Workaround: Transition away from the “old-style” join and aggregation mechanism if practical.

Resolution: Fixed in CDH 5.7.0 / Impala 2.5.0.

Impala Known Issues: Correctness

These issues can cause incorrect or unexpected results from queries. They typically only arise in very specific circumstances.

Incorrect assignment of NULL checking predicate through an outer join of a nested collection.

A query could return wrong results (too many or too few NULL values) if it referenced an outer-joined nested collection and also contained a null-checking predicate (`IS NULL`, `IS NOT NULL`, or the `<=>` operator) in the `WHERE` clause.

Bug: [IMPALA-3084](#)

Severity: High

Resolution: Fixed in CDH 5.9.0 / Impala 2.7.0.

Incorrect result due to constant evaluation in query with outer join

An `OUTER JOIN` query could omit some expected result rows due to a constant such as `FALSE` in another join clause. For example:

```
explain SELECT 1 FROM alltypestiny a1
  INNER JOIN alltypesagg a2 ON a1.smallint_col = a2.year AND false
  RIGHT JOIN alltypes a3 ON a1.year = a1.bigint_col;
+-----+
| Explain String |
+-----+
| Estimated Per-Host Requirements: Memory=1.00KB VCores=1 |
| 00:EMPTYSET |
+-----+
```

Bug: [IMPALA-3094](#)

Severity: High

Resolution:

Workaround:

Incorrect assignment of an inner join On-clause predicate through an outer join.

Impala may return incorrect results for queries that have the following properties:

- There is an `INNER JOIN` following a series of `OUTER JOINS`.
- The `INNER JOIN` has an `On`-clause with a predicate that references at least two tables that are on the nullable side of the preceding `OUTER JOINS`.

The following query demonstrates the issue:

```
select 1 from functional.alltypes a left outer join
  functional.alltypes b on a.id = b.id left outer join
  functional.alltypes c on b.id = c.id right outer join
  functional.alltypes d on c.id = d.id inner join functional.alltypes e
  on b.int_col = c.int_col;
```

The following listing shows the incorrect `EXPLAIN` plan:

```
+-----+
| Explain String |
+-----+
| Estimated Per-Host Requirements: Memory=480.04MB VCores=4 |
+-----+
```

```

14:EXCHANGE [UNPARTITIONED]
|
08:NESTED LOOP JOIN [CROSS JOIN, BROADCAST]
|
--13:EXCHANGE [BROADCAST]
|
04:SCAN HDFS [functional.alltypes e]
   partitions=24/24 files=24 size=478.45KB
|
07:HASH JOIN [RIGHT OUTER JOIN, PARTITIONED]
   hash predicates: c.id = d.id
   runtime filters: RF000 <- d.id
|
--12:EXCHANGE [HASH(d.id)]
|
03:SCAN HDFS [functional.alltypes d]
   partitions=24/24 files=24 size=478.45KB
|
06:HASH JOIN [LEFT OUTER JOIN, PARTITIONED]
   hash predicates: b.id = c.id
   other predicates: b.int_col = c.int_col    <--- incorrect placement; should be at
node 07 or 08
   runtime filters: RF001 <- c.int_col
|
--11:EXCHANGE [HASH(c.id)]
|
02:SCAN HDFS [functional.alltypes c]
   partitions=24/24 files=24 size=478.45KB
   runtime filters: RF000 -> c.id
|
05:HASH JOIN [RIGHT OUTER JOIN, PARTITIONED]
   hash predicates: b.id = a.id
   runtime filters: RF002 <- a.id
|
--10:EXCHANGE [HASH(a.id)]
|
00:SCAN HDFS [functional.alltypes a]
   partitions=24/24 files=24 size=478.45KB
|
09:EXCHANGE [HASH(b.id)]
|
01:SCAN HDFS [functional.alltypes b]
   partitions=24/24 files=24 size=478.45KB
   runtime filters: RF001 -> b.int_col, RF002 -> b.id

```

Bug: [IMPALA-3126](#)

Severity: High

Workaround: High

For some queries, this problem can be worked around by placing the problematic ON clause predicate in the WHERE clause instead, or changing the preceding OUTER JOINS to INNER JOINS (if the ON clause predicate would discard NULLS). For example, to fix the problematic query above:

```

select 1 from functional.alltypes a
  left outer join functional.alltypes b
    on a.id = b.id
  left outer join functional.alltypes c
    on b.id = c.id
  right outer join functional.alltypes d
    on c.id = d.id
  inner join functional.alltypes e
where b.int_col = c.int_col

```

```

+-----+
| Explain String |
+-----+

```

```

Estimated Per-Host Requirements: Memory=480.04MB VCores=4
14:EXCHANGE [UNPARTITIONED]
|
08:NESTED LOOP JOIN [CROSS JOIN, BROADCAST]
|
--13:EXCHANGE [BROADCAST]
|
04:SCAN HDFS [functional.alltypes e]
    partitions=24/24 files=24 size=478.45KB
|
07:HASH JOIN [RIGHT OUTER JOIN, PARTITIONED]
    hash predicates: c.id = d.id
    other predicates: b.int_col = c.int_col      <-- correct assignment
    runtime filters: RF000 <- d.id
|
--12:EXCHANGE [HASH(d.id)]
|
03:SCAN HDFS [functional.alltypes d]
    partitions=24/24 files=24 size=478.45KB
|
06:HASH JOIN [LEFT OUTER JOIN, PARTITIONED]
    hash predicates: b.id = c.id
|
--11:EXCHANGE [HASH(c.id)]
|
02:SCAN HDFS [functional.alltypes c]
    partitions=24/24 files=24 size=478.45KB
    runtime filters: RF000 -> c.id
|
05:HASH JOIN [RIGHT OUTER JOIN, PARTITIONED]
    hash predicates: b.id = a.id
    runtime filters: RF001 <- a.id
|
--10:EXCHANGE [HASH(a.id)]
|
00:SCAN HDFS [functional.alltypes a]
    partitions=24/24 files=24 size=478.45KB
|
09:EXCHANGE [HASH(b.id)]
|
01:SCAN HDFS [functional.alltypes b]
    partitions=24/24 files=24 size=478.45KB
    runtime filters: RF001 -> b.id

```

Impala may use incorrect bit order with BIT_PACKED encoding

Parquet BIT_PACKED encoding as implemented by Impala is LSB first. The parquet standard says it is MSB first.

Bug: [IMPALA-3006](#)

Severity: High, but rare in practice because BIT_PACKED is infrequently used, is not written by Impala, and is deprecated in Parquet 2.0.

BST between 1972 and 1995

The calculation of start and end times for the BST (British Summer Time) time zone could be incorrect between 1972 and 1995. Between 1972 and 1995, BST began and ended at 02:00 GMT on the third Sunday in March (or second Sunday when Easter fell on the third) and fourth Sunday in October. For example, both function calls should return 13, but actually return 12, in a query such as:

```

select
  extract(from_utc_timestamp(cast('1970-01-01 12:00:00' as timestamp), 'Europe/London'),
    "hour") summer70start,
  extract(from_utc_timestamp(cast('1970-12-31 12:00:00' as timestamp), 'Europe/London'),
    "hour") summer70end;

```

Bug: [IMPALA-3082](#)

Severity: High

`parse_url()` returns incorrect result if @ character in URL

If a URL contains an @ character, the `parse_url()` function could return an incorrect value for the hostname field.

Bug: <https://issues.cloudera.org/browse/IMPALA-1170>IMPALA-1170

Resolution: Fixed in CDH 5.7.0 / Impala 2.5.0 and CDH 5.5.4 / Impala 2.3.4.

% escaping does not work correctly when occurs at the end in a LIKE clause

If the final character in the RHS argument of a `LIKE` operator is an escaped `\%` character, it does not match a % final character of the LHS argument.

Bug: [IMPALA-2422](#)

`ORDER BY rand()` does not work.

Because the value for `rand()` is computed early in a query, using an `ORDER BY` expression involving a call to `rand()` does not actually randomize the results.

Bug: [IMPALA-397](#)

Duplicated column in inline view causes dropping null slots during scan

If the same column is queried twice within a view, `NULL` values for that column are omitted. For example, the result of `COUNT(*)` on the view could be less than expected.

Bug: [IMPALA-2643](#)

Workaround: Avoid selecting the same column twice within an inline view.

Resolution: Fixed in CDH 5.7.0 / Impala 2.5.0, CDH 5.5.2 / Impala 2.3.2, and CDH 5.4.10 / Impala 2.2.10.

Incorrect assignment of predicates through an outer join in an inline view.

A query involving an `OUTER JOIN` clause where one of the table references is an inline view might apply predicates from the `ON` clause incorrectly.

Bug: [IMPALA-1459](#)

Resolution: Fixed in CDH 5.7.0 / Impala 2.5.0, CDH 5.5.2 / Impala 2.3.2, and CDH 5.4.9 / Impala 2.2.9.

Crash: `impala::Coordinator::ValidateCollectionSlots`

A query could encounter a serious error if includes multiple nested levels of `INNER JOIN` clauses involving subqueries.

Bug: [IMPALA-2603](#)

Incorrect assignment of On-clause predicate inside inline view with an outer join.

A query might return incorrect results due to wrong predicate assignment in the following scenario:

1. There is an inline view that contains an outer join
2. That inline view is joined with another table in the enclosing query block
3. That join has an On-clause containing a predicate that only references columns originating from the outer-joined tables inside the inline view

Bug: [IMPALA-2665](#)

Resolution: Fixed in CDH 5.7.0 / Impala 2.5.0, CDH 5.5.2 / Impala 2.3.2, and CDH 5.4.9 / Impala 2.2.9.

Wrong assignment of having clause predicate across outer join

In an `OUTER JOIN` query with a `HAVING` clause, the comparison from the `HAVING` clause might be applied at the wrong stage of query processing, leading to incorrect results.

Bug: [IMPALA-2144](#)

Resolution: Fixed in CDH 5.7.0 / Impala 2.5.0.

Wrong plan of NOT IN aggregate subquery when a constant is used in subquery predicate

A `NOT IN` operator with a subquery that calls an aggregate function, such as `NOT IN (SELECT SUM(...))`, could return incorrect results.

Bug: [IMPALA-2093](#)

Resolution: Fixed in CDH 5.7.0 / Impala 2.5.0 and CDH 5.5.4 / Impala 2.3.4.

Impala Known Issues: Metadata

These issues affect how Impala interacts with metadata. They cover areas such as the metastore database, the `COMPUTE STATS` statement, and the Impala `catalogd` daemon.

Catalogd may crash when loading metadata for tables with many partitions, many columns and with incremental stats

Incremental stats use up about 400 bytes per partition for each column. For example, for a table with 20K partitions and 100 columns, the memory overhead from incremental statistics is about 800 MB. When serialized for transmission across the network, this metadata exceeds the 2 GB Java array size limit and leads to a `catalogd` crash.

Bugs: [IMPALA-2647](#), [IMPALA-2648](#), [IMPALA-2649](#)

Workaround: If feasible, compute full stats periodically and avoid computing incremental stats for that table. The scalability of incremental stats computation is a continuing work item.

Can't update stats manually via alter table after upgrading to CDH 5.2

Bug: [IMPALA-1420](#)

Workaround: On CDH 5.2, when adjusting table statistics manually by setting the `numRows`, you must also enable the Boolean property `STATS_GENERATED_VIA_STATS_TASK`. For example, use a statement like the following to set both properties with a single `ALTER TABLE` statement:

```
ALTER TABLE table_name SET TBLPROPERTIES('numRows'='new_value',
'STATS_GENERATED_VIA_STATS_TASK' = 'true');
```

Resolution: The underlying cause is the issue [HIVE-8648](#) that affects the metastore in Hive 0.13. The workaround is only needed until the fix for this issue is incorporated into a CDH release.

Impala Known Issues: Interoperability

These issues affect the ability to interchange data between Impala and other database systems. They cover areas such as data types and file formats.

DESCRIBE FORMATTED gives error on Avro table

This issue can occur either on old Avro tables (created prior to Hive 1.1 / CDH 5.4) or when changing the Avro schema file by adding or removing columns. Columns added to the schema file will not show up in the output of the `DESCRIBE FORMATTED` command. Removing columns from the schema file will trigger a `NullPointerException`.

As a workaround, you can use the output of `SHOW CREATE TABLE` to drop and recreate the table. This will populate the Hive metastore database with the correct column definitions.



Warning: Only use this for external tables, or Impala will remove the data files. In case of an internal table, set it to external first:

```
ALTER TABLE table_name SET TBLPROPERTIES('EXTERNAL'='TRUE');
```

(The part in parentheses is case sensitive.) Make sure to pick the right choice between internal and external when recreating the table. See [Overview of Impala Tables](#) on page 222 for the differences between internal and external tables.

Severity: High

Deviation from Hive behavior: Impala does not do implicit casts between string and numeric and boolean types.

Anticipated Resolution: None

Workaround: Use explicit casts.

Deviation from Hive behavior: Out of range values float/double values are returned as maximum allowed value of type (Hive returns NULL)

Impala behavior differs from Hive with respect to out of range float/double values. Out of range values are returned as maximum allowed value of type (Hive returns NULL).

Workaround: None

Configuration needed for Flume to be compatible with Impala

For compatibility with Impala, the value for the Flume HDFS Sink `hdfs.writeFormat` must be set to `Text`, rather than its default value of `Writable`. The `hdfs.writeFormat` setting must be changed to `Text` before creating data files with Flume; otherwise, those files cannot be read by either Impala or Hive.

Resolution: This information has been requested to be added to the upstream Flume documentation.

Avro Scanner fails to parse some schemas

The default value in Avro schema must match the first union type. For example, if the default value is `null`, then the first type in the `UNION` must be `"null"`.

Bug: [IMPALA-635](#)

Workaround: Swap the order of the fields in the schema specification. For example, use `["null", "string"]` instead of `["string", "null"]`. Note that the files written with the problematic schema must be rewritten with the new schema because Avro files have embedded schemas.

Impala BE cannot parse Avro schema that contains a trailing semi-colon

If an Avro table has a schema definition with a trailing semicolon, Impala encounters an error when the table is queried.

Bug: [IMPALA-1024](#)

Severity: Remove trailing semicolon from the Avro schema.

Fix decompressor to allow parsing gzips with multiple streams

Currently, Impala can only read gzipped files containing a single stream. If a gzipped file contains multiple concatenated streams, the Impala query only processes the data from the first stream.

Bug: [IMPALA-2154](#)

Workaround: Use a different gzip tool to compress file to a single stream file.

Resolution: Fixed in CDH 5.7.0 / Impala 2.5.0.

Impala incorrectly handles text data when the new line character `\n\r` is split between different HDFS block

If a carriage return / newline pair of characters in a text table is split between HDFS data blocks, Impala incorrectly processes the row following the `\n\r` pair twice.

Bug: [IMPALA-1578](#)

Workaround: Use the Parquet format for large volumes of data where practical.

Resolution: Fixed in CDH 5.8.0 / Impala 2.6.0.

Invalid bool value not reported as a scanner error

In some cases, an invalid `BOOLEAN` value read from a table does not produce a warning message about the bad value. The result is still `NULL` as expected. Therefore, this is not a query correctness issue, but it could lead to overlooking the presence of invalid data.

Bug: [IMPALA-1862](#)

Incorrect results with basic predicate on CHAR typed column.

When comparing a `CHAR` column value to a string literal, the literal value is not blank-padded and so the comparison might fail when it should match.

Bug: [IMPALA-1652](#)

Workaround: Use the `RPAD()` function to blank-pad literals compared with `CHAR` columns to the expected length.

Impala Known Issues: Limitations

These issues are current limitations of Impala that require evaluation as you plan how to integrate Impala into your data management workflow.

Impala does not support running on clusters with federated namespaces

Impala does not support running on clusters with federated namespaces. The `impalad` process will not start on a node running such a filesystem based on the `org.apache.hadoop.fs.viewfs.ViewFs` class.

Bug: [IMPALA-77](#)

Anticipated Resolution: Limitation

Workaround: Use standard HDFS on all Impala nodes.

Impala Known Issues: Miscellaneous / Older Issues

These issues do not fall into one of the above categories or have not been categorized yet.

A failed CTAS does not drop the table if the insert fails.

If a `CREATE TABLE AS SELECT` operation successfully creates the target table but an error occurs while querying the source table or copying the data, the new table is left behind rather than being dropped.

Bug: [IMPALA-2005](#)

Workaround: Drop the new table manually after a failed `CREATE TABLE AS SELECT`.

Casting scenarios with invalid/inconsistent results

Using a `CAST()` function to convert large literal values to smaller types, or to convert special values such as `NaN` or `Inf`, produces values not consistent with other database systems. This could lead to unexpected results from queries.

Bug: [IMPALA-1821](#)

Support individual memory allocations larger than 1 GB

The largest single block of memory that Impala can allocate during a query is 1 GiB. Therefore, a query could fail or Impala could crash if a compressed text file resulted in more than 1 GiB of data in uncompressed form, or if a string function such as `group_concat()` returned a value greater than 1 GiB.

Bug: [IMPALA-1619](#)

Resolution: Fixed in CDH 5.9.0 / Impala 2.7.0 and CDH 5.8.3 / Impala 2.6.3.

Impala Parser issue when using fully qualified table names that start with a number.

A fully qualified table name starting with a number could cause a parsing error. In a name such as `db.571_market`, the decimal point followed by digits is interpreted as a floating-point number.

Bug: [IMPALA-941](#)

Workaround: Surround each part of the fully qualified name with backticks (```).

Impala should tolerate bad locale settings

If the `LC_*` environment variables specify an unsupported locale, Impala does not start.

Bug: [IMPALA-532](#)

Workaround: Add `LC_ALL="C"` to the environment settings for both the Impala daemon and the Statestore daemon. See [Modifying Impala Startup Options](#) on page 45 for details about modifying these environment settings.

Resolution: Fixing this issue would require an upgrade to Boost 1.47 in the Impala distribution.

Log Level 3 Not Recommended for Impala

The extensive logging produced by log level 3 can cause serious performance overhead and capacity issues.

Workaround: Reduce the log level to its default value of 1, that is, `GLLOG_V=1`. See [Setting Logging Levels](#) on page 629 for details about the effects of setting different logging levels.

Fixed Issues in Apache Impala

The following sections describe the major issues fixed in each Impala release.

For known issues that are currently unresolved, see [Known Issues and Workarounds in Impala](#) on page 697.

Issues Fixed in Impala for CDH 5.9.0

For the full list of Impala fixed issues in Impala 2.7.0, see [this report in the Impala JIRA tracker](#).

For the full list of fixed issues for all CDH components in CDH 5.9.0, see [the CDH 5.9.x release notes](#).

- [IMPALA-1112](#) - Remove some unnecessary code from cross-compilation
- [IMPALA-1240](#) - add back spilling sort now that sorter is not flaky
- [IMPALA-1440](#) - test for insert mem limit
- [IMPALA-3018](#) - Address various small memory allocation related bugs
- [IMPALA-1619](#) - Support 64-bit allocations.
- [IMPALA-1633](#) - GetOperationStatus should set errorMessage and sqlState
- [IMPALA-1671](#) - Print time and link to coordinator web UI once query is submitted in shell
- [IMPALA-1683](#) - Allow REFRESH on a single partition
- [IMPALA-2347](#) - Reuse metastore client connections in Catalog
- [IMPALA-2459](#) - Implement next_day date/time UDF
- [IMPALA-2700](#) - ASCII NUL characters are doubled on insert into text tables
- [IMPALA-2767](#) - Web UI call to force expire sessions
- [IMPALA-2878](#) - Fix Base64Decode error and remove duplicate codes.

- [IMPALA-2885](#) - ScannerContext::Stream objects should be owned by ScannerContext
- [IMPALA-2979](#) - Fix scheduling on remote hosts
- [IMPALA-3018](#) - Don't return NULL on zero length allocations.
- [IMPALA-3063](#) - Separate join inversion from join ordering.
- [IMPALA-3084](#) - Cache the sequence of table ref and materialized tuple ids during analysis.
- [IMPALA-3181](#) - Add noexcept to some functions
- [IMPALA-3201](#) - buffer pool header only
- [IMPALA-3206](#) - Enable codegen for AVRO_DECIMAL
- [IMPALA-3210](#) - last/first_value() support for IGNORE NULLS
- [IMPALA-3223](#) - Supports download of CDH components from S3.
- [IMPALA-3223](#) - Removal of non-toolchain builds.
- [IMPALA-3223](#) - Relocate squeasel and mustache directories
- [IMPALA-3223](#) - Update path to Postgres JDBC driver
- [IMPALA-3223](#) - Remove boost multiprecision in thirdparty.
- [IMPALA-3225](#) - Fix and update push_to_asf.py to match the new Impala-ASF project
- [IMPALA-3225](#) - Make a gerrit instance that can push to git.apache.org
- [IMPALA-3225](#) - Add script to push from gerrit to ASF
- [IMPALA-3227](#) - generate test TPC data sets during data load
- [IMPALA-3253](#) - Modify gen_build_version.sh to always output the right version
- [IMPALA-3336](#) - qgen: do not randomly generate query options
- [IMPALA-3376](#) - Extra definition level when writing Parquet files
- [IMPALA-3418](#) - The Impala FE project relies on Z-tools snapshot builds
- [IMPALA-3442](#) - Replace '> >' with '>>' in template decls
- [IMPALA-3449](#) - Kudu deploy.py should find clusters by displayName
- [IMPALA-3454](#) - Kudu deletes may fail if subqueries are used
- [IMPALA-3470](#) - DecompressorTest is flaky.
- [IMPALA-3491](#) - Use unique_database fixture in test_shell_commandline.py.
- [IMPALA-3491](#) - Use unique_database fixture in test_catalog_service_client.py.
- [IMPALA-3491](#) - Use unique_database fixture in test_local_fs.py
- [IMPALA-3491](#) - Use unique_database fixture in test_last_ddl_time_update.py.
- [IMPALA-3491](#) - Use unique_database fixture in test_delimited_text.py.
- [IMPALA-3491](#) - Use unique_database fixture in test_metadata_query_statements.py.
- [IMPALA-3491](#) - Use unique_database fixture in test_data_errors.py.
- [IMPALA-3491](#) - Merge test_hbase_metadata.py into compute_stats.py. Use unique db fixture.
- [IMPALA-3501](#) - ee tests: detect build type and support different timeouts based on the same
- [IMPALA-3507](#) - update binutils version to fix slow linking
- [IMPALA-3521](#) - Impalad should communicate with the statestore after binding to the hs2 and besswax ports
- [IMPALA-3530](#) - Clean up test_ddl.py. Part 1.
- [IMPALA-3567](#) - Part 1: groundwork to make Join build sides DataSinks
- [IMPALA-3575](#) - Add retry to backend connection request and rpc timeout
- [IMPALA-3587](#) - Get rid of not_default_fs skip marker
- [IMPALA-3600](#) - Add missing admission control tests
- [IMPALA-3606](#) - Fix Java NPE when trying to add an existing partition
- [IMPALA-3611](#) - track unused Disk IO buffer memory
- [IMPALA-3627](#) - Clean up RPC structures in ImpalaInternalService
- [IMPALA-3632](#) - Add script for running cppclean over the BE code.
- [IMPALA-3647](#) - track runtime filter memory in separate tracker
- [IMPALA-3656](#) - Hitting DCHECK/CHECK does not write minidumps
- [IMPALA-3664](#) - S3A test_keys_do_not_work fails
- [IMPALA-3674](#) - Lazy materialization of LLVM module bitcode.

- [IMPALA-3677](#) - Write minidump on SIGUSR1
- [IMPALA-3682](#) - Don't retry unrecoverable socket creation errors
- [IMPALA-3687](#) - Prefer Avro field name during schema reconciliation
- [IMPALA-3715](#) - Include total usage of JVM memory
- [IMPALA-3715](#) - Include more info by default in Impala debug memz webpage
- [IMPALA-3716](#) - Add Memory Tab in query's Details page
- [IMPALA-3727](#) - Change microbenchmarks to use percentile-based reporting
- [IMPALA-3729](#) - batch_size=1 coverage for avro scanner
- [IMPALA-3734](#) - C++11 - Replace boost:shared_ptr with std:: equivalent
- [IMPALA-3736](#) - Move Impala HTTP handlers to a separate class
- [IMPALA-3737](#) - Local filesystem build failed loading custom schemas
- [IMPALA-3751](#) - fix clang build errors and warnings
- [IMPALA-3753](#) - Disable create table test for old aggs and joins
- [IMPALA-3756](#) - Fix wrong argument type in HiveStringsTest
- [IMPALA-3757](#) - Add missing lock in RuntimeProfile::ComputeTimeInProfile
- [IMPALA-3762](#) - Download Python requirements before they are needed.
- [IMPALA-3763](#) - download_requirements fixes
- [IMPALA-3764](#) - ,3914: fuzz test HDFS scanners and fix parquet bugs found
- [IMPALA-3767](#) - bootstrap_virtualenv fails to find cython distribution
- [IMPALA-3774](#) - fix download_requirements for older Python versions
- [IMPALA-3778](#) - Fix ASF packaging build
- [IMPALA-3779](#) - Disable cache pool reader thread when HDFS isn't running
- [IMPALA-3780](#) - avoid many small reads past end of block
- [IMPALA-3786](#) - Remove "Cloudera" from impalad webpage title
- [IMPALA-3790](#) - Fix admission control flaky stress test
- [IMPALA-3790](#) - AC tests timeout in codecoverage builds
- [IMPALA-3799](#) - Make MAX_SCAN_RANGE_LENGTH accept formatted quantities
- [IMPALA-3806](#) - remove a few modern shell idioms to improve RHEL5 support
- [IMPALA-3817](#) - Ensure filter hash function is the same on all hardware.
- [IMPALA-3829](#) - OpenSession() logs errors on valid configuration keys
- [IMPALA-3839](#) - Fix race condition in impala_cluster.py
- [IMPALA-3843](#) - Update warning for non-SSSE3 CPUs
- [IMPALA-3845](#) - Split up hdfs-parquet-scanner.cc into more files/components.
- [IMPALA-3852](#) - Remove Derby and Shiro FE dependencies
- [IMPALA-3854](#) - Fix use-after-free in HdfsTextScanner::Close()
- [IMPALA-3856](#) - ,IMPALA-3871: Fix BinaryPredicate normalization for Kudu
- [IMPALA-3857](#) - KuduScanNode race on returning "optional" threads
- [IMPALA-3864](#) - qgen: reduce likelihood of create_query() exceptions
- [IMPALA-3866](#) - consistent user-facing terminology for scratch dirs
- [IMPALA-3881](#) - Add DataTables 1.10.12 to www/
- [IMPALA-3886](#) - Improve log of pip_download.py
- [IMPALA-3892](#) - qgen: always run Impala with -convert_legacy_hive_parquet_utc_timestamps=true
- [IMPALA-3905](#) - Add HdfsScanner::GetNext() interface and implementation for Parquet.
- [IMPALA-3906](#) - Materialize implicitly referenced IR functions
- [IMPALA-3914](#) - SKIP_TOOLCHAIN_BOOTSTRAP skips Python package downloads
- [IMPALA-3918](#) - remove Cloudera copyright from the shell welcome message
- [IMPALA-3918](#) - Remove Cloudera copyrights and add ASF license header
- [IMPALA-3918](#) - Remove Cloudera copyrights and add ASF license header
- [IMPALA-3923](#) - fix overflow in BufferedTupleStream::GetRows()
- [IMPALA-3924](#) - Ubuntu16 support

- [IMPALA-3936](#) - BufferedBlockMgr fixes for Pin() while write in flight.
- [IMPALA-3939](#) - Data loading may fail on tpch kudu
- [IMPALA-3943](#) - Do not throw scan errors for empty Parquet files.
- [IMPALA-3946](#) - fix MemPool integrity issues with empty chunks
- [IMPALA-3952](#) - Clear scratch batch mem pool if Open() failed.
- [IMPALA-3953](#) - Fixes for KuduScanNode BE test failure
- [IMPALA-3954](#) - Add unique_database to scanner test
- [IMPALA-3957](#) - Test failure in S3 build: TestLoadData.test_load
- [IMPALA-3964](#) - Fix crash when a count(*) is performed on a nested collection.
- [IMPALA-3969](#) - stress test: add option to set common query options
- [IMPALA-3972](#) - Improve display of /varz page
- [IMPALA-3992](#) - bad shell error message when running nonexistent file

Issues Fixed in Impala for CDH 5.8.2

For the full list of fixed issues for all CDH components, see [the CDH 5.8.x release notes](#).

- [IMPALA-1346](#) - /1590/2344: fix sorter buffer mgmt when spilling
- [IMPALA-3159](#) - impala-shell does not accept wildcard or SAN certificates
- [IMPALA-3344](#) - Simplify sorter and document/enforce invariants.
- [IMPALA-3441](#) - , IMPALA-3659: check for malformed Avro data
- [IMPALA-3499](#) - Split catalog update.
- [IMPALA-3628](#) - Fix cancellation from shell when security is enabled
- [IMPALA-3633](#) - cancel fragment if coordinator is gone
- [IMPALA-3646](#) - Handle corrupt RLE literal or repeat counts of 0.
- [IMPALA-3670](#) - fix sorter buffer mgmt bugs
- [IMPALA-3678](#) - Fix migration of predicates into union operands with an order by + limit.
- [IMPALA-3680](#) - Cleanup the scan range state after failed hdfs cache reads
- [IMPALA-3711](#) - Remove unnecessary privilege checks in getDbsMetadata().
- [IMPALA-3732](#) - handle string length overflow in avro files
- [IMPALA-3745](#) - parquet invalid data handling
- [IMPALA-3754](#) - fix TestParquet.test_corrupt_rle_counts flakiness
- [IMPALA-3772](#) - Fix admission control stress test.
- [IMPALA-3776](#) - fix 'describe formatted' for Avro tables
- [IMPALA-3820](#) - Handle linkage errors while loading Java UDFs in Catalog
- [IMPALA-3861](#) - Replace BetweenPredicates with their equivalent CompoundPredicate.
- [IMPALA-3915](#) - Register privilege and audit requests when analyzing resolved table refs.
- [IMPALA-3930](#) - ,IMPALA-2570: Fix shuffle insert hint with constant partition exprs.
- [IMPALA-3940](#) - Fix getting column stats through views.
- [IMPALA-3965](#) - TSSLSocketWithWildcardSAN.py not exported as part of impala-shell build lib
- [IMPALA-4020](#) - Handle external conflicting changes to HMS gracefully
- [IMPALA-4049](#) - fix empty batch handling NLJ build side

Issues Fixed in Impala for CDH 5.8.0

The following list contains the most critical fixed issues (`priority='Blocker'`) from the JIRA system. For the full list of fixed issues in CDH 5.8.0 / Impala 2.6.0, see [this report in the Impala JIRA tracker](#).

`RuntimeState::error_log_crashes`

A crash could occur, with stack trace pointing to `impala::RuntimeState::ErrorLog`.

Bug: [IMPALA-3385](#)

Severity: High

HiveUdfCall::Open() produces unsynchronized access to JNIUtil::global_refs_vector

A crash could occur because of contention between multiple calls to Java UDFs.

Bug: [IMPALA-3378](#)

Severity: High

HBaseTableWriter::CreatePutList() produces unsynchronized access to JNIUtil::global_refs_vector

A crash could occur because of contention between multiple concurrent statements writing to HBase.

Bug: [IMPALA-3379](#)

Severity: High

Stress test failure: sorter.cc:745] Check failed: i == 0 (1 vs. 0)

A crash or wrong results could occur if the spill-to-disk mechanism encountered a zero-length string at the very end of a data block.

Bug: [IMPALA-3317](#)

Severity: High

String data coming out of agg can be corrupted by blocking operators

If a query plan contains an aggregation node producing string values anywhere within a subplan (that is, if in the SQL statement, the aggregate function appears within an inline view over a collection column), the results of the aggregation may be incorrect.

Bug: [IMPALA-3311](#)

Severity: High

CTAS with subquery throws AuthzException

A CREATE TABLE AS SELECT operation could fail with an authorization error, due to a slight difference in the privilege checking for the CTAS operation.

Bug: [IMPALA-3269](#)

Severity: High

Crash on inserting into table with binary and parquet

Impala incorrectly allowed BINARY to be specified as a column type, resulting in a crash during a write to a Parquet table with a column of that type.

Bug: [IMPALA-3237](#)

Severity: High

RowBatch::MaxTupleBufferSize() calculation incorrect, may lead to memory corruption

A crash could occur while querying tables with very large rows, for example wide tables with many columns or very large string values. This problem was identified in Impala 2.3, but had low reproducibility in subsequent releases. The fix ensures the memory allocation size is correct.

Bug: [IMPALA-3105](#)

Severity: High

Thrift buffer overflows when serialize more than 3355443200 bytes in impala

A very large memory allocation within the catalogd daemon could exceed an internal Thrift limit, causing a crash.

Bug: [IMPALA-3494](#)

Severity: High

Altering table partition's storage format is not working and crashing the daemon

If a partitioned table used a file format other than Avro, and the file format of an individual partition was changed to Avro, subsequent queries could encounter a crash.

Bug: [IMPALA-3314](#)

Severity: High

Race condition may cause scanners to spin with runtime filters on Avro or Sequence files

A timing problem during runtime filter processing could cause queries against Avro or SequenceFile tables to hang.

Bug: [IMPALA-3798](#)

Severity: High

Issues Fixed in Impala for CDH 5.7.4

For the full list of fixed issues for all CDH components, see [the CDH 5.7.x release notes](#).

- [IMPALA-3081](#) - Increase memory limit for TestWideRow
- [IMPALA-3311](#) - Fix string data coming out of aggs in subplans
- [IMPALA-3575](#) - Add retry to backend connection request and rpc timeout
- [IMPALA-3678](#) - Fix migration of predicates into union operands with an order by + limit.
- [IMPALA-3682](#) - Do not retry unrecoverable socket creation errors
- [IMPALA-3687](#) - Fix test failure introduced by backporting
- [IMPALA-3687](#) - Prefer Avro field name during schema reconciliation
- [IMPALA-3820](#) - Handle linkage errors while loading Java UDFs in Catalog
- [IMPALA-3930](#) - Fix shuffle insert hint with constant partition exprs.
- [IMPALA-3940](#) - Fix getting column stats through views.
- [IMPALA-4020](#) - Handle external conflicting changes to HMS gracefully
- [IMPALA-4049](#) - Fix empty batch handling NLJ build side

Issues Fixed in Impala for CDH 5.7.2

For the full list of fixed issues for all CDH components, see [the CDH 5.7.x release notes](#).

- [IMPALA-1928](#) - Fix Thrift client transport wrapping order
- [IMPALA-2660](#) - Respect auth_to_local configs from hdfs configs
- [IMPALA-3276](#) - Consistently handle pin failure in BTS::PrepareForRead()
- [IMPALA-3369](#) - Add ALTER TABLE SET COLUMN STATS statement.
- [IMPALA-3441](#) - Impala should not crash for invalid avro serialized data
- [IMPALA-3499](#) - Split catalog update
- [IMPALA-3502](#) - Fix race in the coordinator while updating filter routing table
- [IMPALA-3633](#) - Cancel fragment if coordinator is gone
- [IMPALA-3732](#) - Handle string length overflow in Avro files
- [IMPALA-3745](#) - Corrupt encoded values in parquet files can cause crashes
- [IMPALA-3751](#) - Fix clang build errors and warnings
- [IMPALA-3754](#) - Fix TestParquet.test_corrupt_rle_counts flakiness

Issues Fixed in Impala for CDH 5.7.1

For the full list of fixed issues for all CDH components, see [the CDH 5.7.x release notes](#).

- [IMPALA-2076](#) - Correct execution time tracking for DataStreamSender
- [IMPALA-2502](#) - Don't redundantly repartition grouping aggregations

- [IMPALA-2892](#) - Buffered-tuple-stream-ir.cc is not cross-compiled
- [IMPALA-3133](#) - Wrong privileges after a REVOKE ALL ON SERVER statement
- [IMPALA-3139](#) - Fix drop table statement to not drop views and vice versa
- [IMPALA-3141](#) - Send dummy filters when filter production is disabled
- [IMPALA-3194](#) - Allow queries materializing scalar type columns in RC/sequence files
- [IMPALA-3220](#) - Skip logging empty ScannerContext's stream in parse error
- [IMPALA-3236](#) - Increase timeout for runtime filter tests
- [IMPALA-3238](#) - Avoid log spam for very large hash tables
- [IMPALA-3245](#), [IMPALA-3305](#): Fix crash with global filters when NUM_NODES=1
- [IMPALA-3269](#) - Remove authz checks on default table location in CTAS queries
- [IMPALA-3285](#) - Fix ASAN failure in webservice-test
- [IMPALA-3317](#) - Fix crash in sorter when spilling zero-length strings
- [IMPALA-3334](#) - Fix some bugs in query options' parsing.
- [IMPALA-3367](#) - Ensure runtime filters tests run on 3 nodes
- [IMPALA-3378](#), [IMPALA-3379](#): fix various JNI issues
- [IMPALA-3385](#) - Fix crashes on accessing error_log
- [IMPALA-3395](#) - Old HT filter code uses wrong expr type
- [IMPALA-3396](#) - Fix ConcurrentTimerCounter unit test "TimerCounterTest" failure.
- [IMPALA-3412](#) - Fix CHAR codegen crash in tuple comparator
- [IMPALA-3420](#) - Set IMPALA_THRIFT_VERSION patch level to +4

Issues Fixed in Impala for CDH 5.7.0

The following list contains the most critical issues (`priority='Blocker'`) from the JIRA system. For the full list of fixed issues in CDH 5.7.0 / Impala 2.5.0, see [this report in the Impala JIRA tracker](#).

Stress test hit assert in LLVM: external function could not be resolved

Bug: [IMPALA-2683](#)

The stress test was running a build with the TPC-H, TPC-DS, and TPC-H nested queries with scale factor 3.

Impalad is crashing if udf jar is not available in hdfs location for first time

Bug: [IMPALA-2365](#)

If a UDF JAR was not available in the HDFS location specified in the `CREATE FUNCTION` statement, the `impalad` daemon could crash.

PAGG hits `mem_limit` when switching to I/O buffers

Bug: [IMPALA-2535](#)

A join query could fail with an out-of-memory error despite the apparent presence of sufficient memory. The cause was the internal ordering of operations that could cause a later phase of the query to allocate memory required by an earlier phase of the query. The workaround was to either increase or decrease the `MEM_LIMIT` query option, because the issue would only occur for a specific combination of memory limit and data volume.

Prevent migrating incorrectly inferred identity predicates into inline views

Bug: [IMPALA-2643](#)

Referring to the same column twice in a view definition could cause the view to omit rows where that column contained a `NULL` value. This could cause incorrect results due to an inaccurate `COUNT(*)` value or rows missing from the result set.

Fix migration/assignment of On-clause predicates inside inline views

Bug: [IMPALA-1459](#)

Some combinations of `ON` clauses in join queries could result in comparisons being applied at the wrong stage of query processing, leading to incorrect results. Wrong predicate assignment could happen under the following conditions:

- The query includes an inline view that contains an outer join.
- That inline view is joined with another table in the enclosing query block.
- That join has an `ON` clause containing a predicate that only references columns originating from the outer-joined tables inside the inline view.

Wrong plan of `NOT IN` aggregate subquery when a constant is used in subquery predicate

Bug: [IMPALA-2093](#)

`IN` subqueries might return wrong results if the left-hand side of the `IN` is a constant. For example:

```
select * from alltypestiny t1
  where 10 not in (select sum(int_col) from alltypestiny);
```

Parquet DictDecoders accumulate throughout query

Bug: [IMPALA-2940](#)

Parquet dictionary decoders can accumulate throughout query execution, leading to excessive memory usage. One decoder is created per-column per-split.

Planner doesn't set the `has_local_target` field correctly

Bug: [IMPALA-3056](#)

MemPool allocation growth behavior

Bug: [IMPALA-2742](#)

Currently, the MemPool would always double the size of the last allocation. This can lead to bad behavior if the MemPool transferred the ownership of all its data except the last chunk. In the next allocation, the next allocated chunk would double the size of this large chunk, which can be undesirable.

Drop partition operations don't follow the catalog's locking protocol

Bug: [IMPALA-3035](#)

The `CatalogOpExecutor.alterTableDropPartition()` function violates the locking protocol used in the catalog that requires `catalogLock_` to be acquired before any table-level lock. That may cause deadlocks when `ALTER TABLE DROP PARTITION` is executed concurrently with other DDL operations.

`HAVING` clause without aggregation not applied properly

Bug: [IMPALA-2215](#)

A query with a `HAVING` clause but no `GROUP BY` clause was not being rejected, despite being invalid syntax. For example:

```
select case when 1=1 then 'didit' end as c1 from (select 1 as one) a having 1!=1;
```

Hit `DCHECK` Check failed: `HasDateOrTime()`

Bug: [IMPALA-2914](#)

`TimestampValue::ToTimestampVal()` requires a valid `TimestampValue` as input. This requirement was not enforced in some places, leading to serious errors.

Aggregation spill loop gives up too early leading to mem limit exceeded errors

Bug: [IMPALA-2986](#)

An aggregation query could fail with an out-of-memory error, despite sufficient memory being reported as available.

`DataStreamSender::Channel::CloseInternal()` does not close the channel on an error.

Bug: [IMPALA-2592](#)

Some queries do not close an internal communication channel on an error. This will cause the node on the other side of the channel to wait indefinitely, causing the query to hang. For example, this issue could happen on a Kerberos-enabled system if the credential cache was outdated. Although the affected query hangs, the `impalad` daemons continue processing other queries.

Codegen does not catch exceptions in `FROM_UNIXTIME()`

Bug: [IMPALA-2184](#)

Querying for the min or max value of a timestamp cast from a bigint via `from_unixtime()` fails silently and crashes instances of `impalad` when the input includes a value outside of the valid range.

Workaround: Disable native code generation with:

```
SET disable_codegen=true;
```

Impala returns wrong result for function `'conv(bigint, from_base, to_base)'`

Bug: [IMPALA-2788](#)

Impala returns wrong result for function `conv()`. Function `conv(bigint, from_base, to_base)` returns an correct result, while `conv(string, from_base, to_base)` returns the correct value. For example:

```
select 2061013007, conv(2061013007, 16, 10), conv('2061013007', 16, 10);
+-----+-----+-----+
| 2061013007 | conv(2061013007, 16, 10) | conv('2061013007', 16, 10) |
+-----+-----+-----+
| 2061013007 | 1627467783                | 139066421255                |
+-----+-----+-----+
Fetched 1 row(s) in 0.65s

select 2061013007, conv(cast(2061013007 as bigint), 16, 10), conv('2061013007', 16, 10);
+-----+-----+-----+
| 2061013007 | conv(cast(2061013007 as bigint), 16, 10) | conv('2061013007', 16, 10) |
+-----+-----+-----+
| 2061013007 | 1627467783                | 139066421255                |
+-----+-----+-----+

select 2061013007, conv(cast(2061013007 as string), 16, 10), conv('2061013007', 16, 10);
+-----+-----+-----+
| 2061013007 | conv(cast(2061013007 as string), 16, 10) | conv('2061013007', 16, 10) |
+-----+-----+-----+
| 2061013007 | 139066421255              | 139066421255              |
+-----+-----+-----+

select 2061013007, conv(cast(cast(2061013007 as decimal(20,0)) as bigint), 16, 10),
conv('2061013007', 16, 10);
+-----+-----+-----+
| 2061013007 | conv(cast(cast(2061013007 as decimal(20,0)) as bigint), 16, 10) |
conv('2061013007', 16, 10) |
+-----+-----+-----+
| 2061013007 | 1627467783                |                               |
139066421255 |                               |                               |
+-----+-----+-----+
```

Workaround: Cast the value to string and use `conv(string, from_base, to_base)` for conversion.

Issues Fixed in Impala for CDH 5.6.1

For the full list of fixed issues for all CDH components, see [the CDH 5.6.x release notes](#).

- [IMPALA-852](#), [IMPALA-2215](#) - Analyze HAVING clause before aggregation
- [IMPALA-1092](#) - Fix estimates for trivial coord-only queries
- [IMPALA-1170](#) - Fix URL parsing when path contains '@'
- [IMPALA-1934](#) - Allow shell to retrieve LDAP password from shell cmd
- [IMPALA-2093](#) - Disallow NOT IN aggregate subqueries with a constant lhs expr
- [IMPALA-2184](#) - don't inline timestamp methods with try/catch blocks in IR
- [IMPALA-2425](#) - Broadcast join hint not enforced when low memory limit is set
- [IMPALA-2503](#) - Add missing String.format() arg in error message
- [IMPALA-2539](#) - Unmark collections slots of empty union operands
- [IMPALA-2554](#) - Change default buffer size for RPC servers and clients
- [IMPALA-2565](#) - Planner tests are flaky due to file size mismatches
- [IMPALA-2592](#) - DataStreamSender::Channel::CloseInternal() does not close the channel on an error
- [IMPALA-2599](#) - Pseudo-random sleep before acquiring kerberos ticket possibly not really pseudo-random
- [IMPALA-2711](#) - Fix memory leak in Rand()
- [IMPALA-2732](#) - Timestamp formats with non-padded values
- [IMPALA-2734](#) - Correlated EXISTS subqueries with HAVING clause return wrong results
- [IMPALA-2742](#) - Avoid unbounded MemPool growth with AcquireData()
- [IMPALA-2749](#) - Fix decimal multiplication overflow
- [IMPALA-2765](#) - Preserve return type of subexpressions substituted in isTrueWithNullSlots()
- [IMPALA-2788](#) - conv(bigint num, int from_base, int to_base) returns wrong result
- [IMPALA-2798](#) - Bring in AVRO-1617 fix and add test case for it
- [IMPALA-2818](#) - Fix cancellation crashes/hangs due to BlockOnWait() race
- [IMPALA-2820](#) - Support unquoted keywords as struct-field names
- [IMPALA-2832](#) - Fix cloning of FunctionCallExpr
- [IMPALA-2844](#) - Allow count(*) on RC files with complex types
- [IMPALA-2870](#) - Fix failing metadata.test_ddl.TestDdlStatements.test_create_table test
- [IMPALA-2894](#) - Move regression test into a different .test file
- [IMPALA-2906](#) - Fix an edge case with materializing TupleIsNotNullPredicates in analytic sorts
- [IMPALA-2914](#) - Fix DCHECK Check failed: HasDateOrTime()
- [IMPALA-2926](#) - Fix off-by-one bug in SelectNode::CopyRows()
- [IMPALA-2940](#) - Fix leak of dictionaries in Parquet scanner
- [IMPALA-3000](#) - Fix BitReader::Reset()
- [IMPALA-3034](#) - Verify all consumed memory of a MemTracker is always released at destruction time
- [IMPALA-3047](#) - Separate create table test with nested types
- [IMPALA-3054](#) - Disable probe side filters when spilling
- [IMPALA-3071](#) - Fix assignment of On-clause predicates belonging to an inner join
- [IMPALA-3085](#) - Unregister data sinks' MemTrackers at their Close() functions
- [IMPALA-3093](#) - ReopenClient() could NULL out 'client_key' causing a crash
- [IMPALA-3095](#) - Add configurable whitelist of authorized internal principals
- [IMPALA-3151](#) - Impala crash for avro table when casting to char data type
- [IMPALA-3194](#) - Allow queries materializing scalar type columns in RC/sequence files

Issues Fixed in Impala for CDH 5.6.0

The set of fixes for Impala in CDH 5.6.0 is the same as in CDH 5.5.2. See for details.

Issues Fixed in Impala for CDH 5.5.4

For the full list of fixed issues for all CDH components, see [the CDH 5.5.x release notes](#).



Note: Impala 2.3.x is available as part of CDH 5.5.x and is not available for CDH 4. Cloudera does not intend to release future versions of Impala for CDH 4 outside patch and maintenance releases if required. Given the end-of-maintenance status for CDH 4, Cloudera recommends all customers to migrate to a recent CDH 5 release.

- [IMPALA-852](#) - ,IMPALA-2215: Analyze HAVING clause before aggregation
- [IMPALA-1092](#) - Fix estimates for trivial coord-only queries
- [IMPALA-1170](#) - Fix URL parsing when path contains '@'
- [IMPALA-1934](#) - Allow shell to retrieve LDAP password from shell cmd
- [IMPALA-2093](#) - Disallow NOT IN aggregate subqueries with a constant lhs expr
- [IMPALA-2184](#) - Don't inline timestamp methods with try/catch blocks in IR
- [IMPALA-2425](#) - Broadcast join hint not enforced when low memory limit is set
- [IMPALA-2503](#) - Add missing String.format() arg in error message
- [IMPALA-2539](#) - Unmark collections slots of empty union operands
- [IMPALA-2554](#) - Change default buffer size for RPC servers and clients
- [IMPALA-2565](#) - Planner tests are flaky due to file size mismatches
- [IMPALA-2592](#) - DataStreamSender::Channel::CloseInternal() does not close the channel on an error
- [IMPALA-2599](#) - Pseudo-random sleep before acquiring kerberos ticket possibly not really pseudo-random
- [IMPALA-2711](#) - Fix memory leak in Rand()
- [IMPALA-2719](#) - test_parquet_max_page_header fails on Isilon
- [IMPALA-2732](#) - Timestamp formats with non-padded values
- [IMPALA-2734](#) - Correlated EXISTS subqueries with HAVING clause return wrong results
- [IMPALA-2742](#) - Avoid unbounded MemPool growth with AcquireData()
- [IMPALA-2749](#) - Fix decimal multiplication overflow
- [IMPALA-2765](#) - Preserve return type of subexpressions substituted in isTrueWithNullSlots()
- [IMPALA-2788](#) - conv(bigint num, int from_base, int to_base) returns wrong result
- [IMPALA-2798](#) - Bring in AVRO-1617 fix and add test case for it
- [IMPALA-2818](#) - Fix cancellation crashes/hangs due to BlockOnWait() race
- [IMPALA-2820](#) - Support unquoted keywords as struct-field names
- [IMPALA-2832](#) - Fix cloning of FunctionCallExpr
- [IMPALA-2844](#) - Allow count(*) on RC files with complex types
- [IMPALA-2870](#) - Fix failing metadata.test_ddl.TestDdlStatements.test_create_table test
- [IMPALA-2894](#) - Move regression test into a different .test file
- [IMPALA-2906](#) - Fix an edge case with materializing TuplelsNullPredicates in analytic sorts
- [IMPALA-2914](#) - Fix DCHECK Check failed: HasDateOrTime()
- [IMPALA-2926](#) - Fix off-by-one bug in SelectNode::CopyRows()
- [IMPALA-2940](#) - Fix leak of dictionaries in Parquet scanner
- [IMPALA-3000](#) - Fix BitReader::Reset()
- [IMPALA-3034](#) - Verify all consumed memory of a MemTracker is always released at destruction time
- [IMPALA-3047](#) - Separate create table test with nested types
- [IMPALA-3054](#) - Disable probe side filters when spilling
- [IMPALA-3071](#) - Fix assignment of On-clause predicates belonging to an inner join
- [IMPALA-3085](#) - Unregister data sinks' MemTrackers at their Close() functions
- [IMPALA-3093](#) - ReopenClient() could NULL out 'client_key' causing a crash
- [IMPALA-3095](#) - Add configurable whitelist of authorized internal principals
- [IMPALA-3151](#) - Impala crash for avro table when casting to char data type
- [IMPALA-3194](#) - Allow queries materializing scalar type columns in RC/sequence files

Issues Fixed in Impala for CDH 5.5.2

This section lists the most serious or frequently encountered customer issues fixed in CDH 5.5.2 / Impala 2.3.2. For the full list of fixed Impala issues, see [the CDH 5.5.x release notes](#).

SEGV in AnalyticEvalNode touching NULL input_stream_

A query involving an analytic function could encounter a serious error. This issue was encountered infrequently, depending upon specific combinations of queries and data.

Bug: [IMPALA-2829](#)

Free local allocations per row batch in non-partitioned AGG and HJ

An outer join query could fail unexpectedly with an out-of-memory error when the “spill to disk” mechanism was turned off.

Bug: [IMPALA-2722](#)

Free local allocations once for every row batch when building hash tables

A join query could encounter a serious error due to an internal failure to allocate memory, which resulted in dereferencing a NULL pointer.

Bug: [IMPALA-2612](#)

Prevent migrating incorrectly inferred identity predicates into inline views

Referring to the same column twice in a view definition could cause the view to omit rows where that column contained a NULL value. This could cause incorrect results due to an inaccurate COUNT (*) value or rows missing from the result set.

Bug: [IMPALA-2643](#)

Fix GRANTs on URIs with uppercase letters

A GRANT statement for a URI could be ineffective if the URI contained uppercase letters, for example in an uppercase directory name. Subsequent statements, such as CREATE EXTERNAL TABLE with a LOCATION clause, could fail with an authorization exception.

Bug: [IMPALA-2695](#)

Avoid sending large partition stats objects over thrift

The catalogd daemon could encounter a serious error when loading the incremental statistics metadata for tables with large numbers of partitions and columns. The problem occurred when the internal representation of metadata for the table exceeded 2 GB, for example in a table with 20K partitions and 77 columns. The fix causes a COMPUTE INCREMENTAL STATS operation to fail if it would produce metadata that exceeded the maximum size.

Bug: [IMPALA-2664](#), [IMPALA-2648](#)

Throw AnalysisError if table properties are too large (for the Hive metastore)

CREATE TABLE or ALTER TABLE statements could fail with metastore database errors due to length limits on the SERDEPROPERTIES and TBLPROPERTIES clauses. (The limit on key size is 256, while the limit on value size is 4000.) The fix makes Impala handle these error conditions more cleanly, by detecting too-long values rather than passing them to the metastore database.

Bug: [IMPALA-2226](#)

Make MAX_PAGE_HEADER_SIZE configurable

Impala could fail to access Parquet data files with page headers larger than 8 MB, which could occur, for example, if the minimum or maximum values for a column were long strings. The fix adds a configuration setting `--max_page_header_size`, which you can use to increase the Impala size limit to a value higher than 8 MB.

Bug: [IMPALA-2273](#)

reduce scanner memory usage

Queries on Parquet tables could consume excessive memory (potentially multiple gigabytes) due to producing large intermediate data values while evaluating groups of rows. The workaround was to reduce the size of the `NUM_SCANNER_THREADS` query option, the `BATCH_SIZE` query option, or both.

Bug: [IMPALA-2473](#)

Handle error when distinct and aggregates are used with a having clause

A query that included a `DISTINCT` operator and a `HAVING` clause, but no aggregate functions or `GROUP BY`, would fail with an uninformative error message.

Bug: [IMPALA-2113](#)

Handle error when star based select item and aggregate are incorrectly used

A query that included `*` in the `SELECT` list, in addition to an aggregate function call, would fail with an uninformative message if the query had no `GROUP BY` clause.

Bug: [IMPALA-2225](#)

Refactor MemPool usage in HBase scan node

Queries involving HBase tables used substantially more memory than in earlier Impala versions. The problem occurred starting in Impala 2.2.8, as a result of the changes for [IMPALA-2284](#). The fix for this issue involves removing a separate memory work area for HBase queries and reusing other memory that was already allocated.

Bug: [IMPALA-2731](#)

Fix migration/assignment of On-clause predicates inside inline views

Some combinations of `ON` clauses in join queries could result in comparisons being applied at the wrong stage of query processing, leading to incorrect results. Wrong predicate assignment could happen under the following conditions:

- The query includes an inline view that contains an outer join.
- That inline view is joined with another table in the enclosing query block.
- That join has an `ON` clause containing a predicate that only references columns originating from the outer-joined tables inside the inline view.

Bug: [IMPALA-1459](#)

DCHECK in parquet scanner after block read error

A debug build of Impala could encounter a serious error after encountering some kinds of I/O errors for Parquet files. This issue only occurred in debug builds, not release builds.

Bug: [IMPALA-2558](#)

PAGG hits mem_limit when switching to I/O buffers

A join query could fail with an out-of-memory error despite the apparent presence of sufficient memory. The cause was the internal ordering of operations that could cause a later phase of the query to allocate memory required by an earlier phase of the query. The workaround was to either increase or decrease the `MEM_LIMIT` query option, because the issue would only occur for a specific combination of memory limit and data volume.

Bug: [IMPALA-2535](#)

Fix check failed: sorter_runs_.back()->is_pinned_

A query could fail with an internal error while calculating the memory limit. This was an infrequent condition uncovered during stress testing.

Bug: [IMPALA-2559](#)

Don't ignore Status returned by `DataStreamRecv::CreateMerger()`

A query could fail with an internal error while calculating the memory limit. This was an infrequent condition uncovered during stress testing.

Bug: [IMPALA-2614](#), [IMPALA-2559](#)

`DataStreamSender::Send()` does not return an error status if `SendBatch()` failed

Bug: [IMPALA-2591](#)

Re-enable SSL and Kerberos on server-server

These fixes lift the restriction on using SSL encryption and Kerberos authentication together for internal communication between Impala components.

Bug: [IMPALA-2598](#), [IMPALA-2747](#)

Issues Fixed in Impala for CDH 5.5.1

The version of Impala that is included with CDH 5.5.1 is identical to the Impala for CDH 5.5.0. There are no new bug fixes, new features, or incompatible changes.

Issues Fixed in Impala for CDH 5.5.0

This section lists the most serious or frequently encountered customer issues fixed in CDH 5.5.0 / Impala 2.3.0. Any issues already fixed in CDH 5.4 maintenance releases (up through CDH 5.4.8) are also included. Those issues are listed under the respective CDH 5.4 sections and are not repeated here. For the full list of fixed Impala issues, see [the CDH 5.5.x release notes](#).

Fixes for Serious Errors

A number of issues were resolved that could result in serious errors when encountered. The most critical or commonly encountered are listed here.

Bugs: [IMPALA-2168](#), [IMPALA-2378](#), [IMPALA-2369](#), [IMPALA-2357](#), [IMPALA-2319](#), [IMPALA-2314](#), [IMPALA-2016](#)

Fixes for Correctness Errors

A number of issues were resolved that could result in wrong results when encountered. The most critical or commonly encountered are listed here.

Bugs: [IMPALA-2192](#), [IMPALA-2440](#), [IMPALA-2090](#), [IMPALA-2086](#), [IMPALA-1947](#), [IMPALA-1917](#)

Issues Fixed in Impala for CDH 5.4.10

For the full list of fixed issues for all CDH components, see [the CDH 5.4.x release notes](#).



Note: The Impala 2.2.x maintenance releases now use the CDH 5.4.x numbering system rather than increasing the Impala version numbers. Impala 2.2 and higher are not available under CDH 4.

- [IMPALA-1702](#) - Check for duplicate table IDs at the end of analysis (issue not entirely fixed, but now fails gracefully)
- [IMPALA-2264](#) - Implicit casts to integers from decimals with higher precision sometimes allowed
- [IMPALA-2473](#) - Excessive memory usage by scan nodes
- [IMPALA-2621](#) - Fix flaky `UNIX_TIMESTAMP()` test
- [IMPALA-2643](#) - Nested inline view produces incorrect result when referencing the same column implicitly
- [IMPALA-2765](#) - `AnalysisException`: operands of type `BOOLEAN` and `TIMESTAMP` are not comparable when `OUTER JOIN` with `CASE` statement
- [IMPALA-2798](#) - After adding a column to avro table, Impala returns weird result if codegen is enabled.
- [IMPALA-2861](#) - Fix flaky scanner test added via `IMPALA-2473` backport
- [IMPALA-2914](#) - Hit `DCHECK Check failed: HasDateOrTime()`

- [IMPALA-3034](#) - MemTracker leak on PHJ failure to spill
- [IMPALA-3085](#) - DataSinks' MemTrackers need to unregister themselves from parent
- [IMPALA-3093](#) - ReopenClient() could NULL out 'client_key' causing a crash
- [IMPALA-3095](#) - Allow additional Kerberos users to be authorized to access internal APIs

Issues Fixed in Impala for CDH 5.4.9

This section lists the most frequently encountered customer issues fixed in Impala for CDH 5.4.9.



Note: The Impala 2.2.x maintenance releases now use the CDH 5.4.x numbering system rather than increasing the Impala version numbers. Impala 2.2 and higher are not available under CDH 4.

For the full list of fixed issues, see [the CDH 5.4.x release notes](#).

Query return empty result if it contains NullLiteral in inlineview

If an inline view in a FROM clause contained a NULL literal, the result set was empty.

Bug: [IMPALA-1917](#)

HBase scan node uses 2-4x memory after upgrade to Impala 2.2.8

Queries involving HBase tables used substantially more memory than in earlier Impala versions. The problem occurred starting in Impala 2.2.8, as a result of the changes for IMPALA-2284. The fix for this issue involves removing a separate memory work area for HBase queries and reusing other memory that was already allocated.

Bug: [IMPALA-2731](#)

Fix migration/assignment of On-clause predicates inside inline views

Some combinations of ON clauses in join queries could result in comparisons being applied at the wrong stage of query processing, leading to incorrect results. Wrong predicate assignment could happen under the following conditions:

- The query includes an inline view that contains an outer join.
- That inline view is joined with another table in the enclosing query block.
- That join has an ON clause containing a predicate that only references columns originating from the outer-joined tables inside the inline view.

Bug: [IMPALA-1459](#)

Fix wrong predicate assignment in outer joins

The join predicate for an OUTER JOIN clause could be applied at the wrong stage of query processing, leading to incorrect results.

Bug: [IMPALA-2446](#)

Avoid sending large partition stats objects over thrift

The catalogd daemon could encounter a serious error when loading the incremental statistics metadata for tables with large numbers of partitions and columns. The problem occurred when the internal representation of metadata for the table exceeded 2 GB, for example in a table with 20K partitions and 77 columns. The fix causes a COMPUTE INCREMENTAL STATS operation to fail if it would produce metadata that exceeded the maximum size.

Bug: [IMPALA-2648](#), [IMPALA-2664](#)

Avoid overflow when adding large intervals to TIMESTAMPS

Adding or subtracting a large INTERVAL value to a TIMESTAMP value could produce an incorrect result, with the value wrapping instead of returning an out-of-range error.

Bug: [IMPALA-1675](#)

Analysis exception when a binary operator contains an IN operator with values

An `IN` operator with literal values could cause a statement to fail if used as the argument to a binary operator, such as an equality test for a `BOOLEAN` value.

Bug: [IMPALA-1949](#)

Make `MAX_PAGE_HEADER_SIZE` configurable

Impala could fail to access Parquet data files with page headers larger than 8 MB, which could occur, for example, if the minimum or maximum values for a column were long strings. The fix adds a configuration setting `--max_page_header_size`, which you can use to increase the Impala size limit to a value higher than 8 MB.

Bug: [IMPALA-2273](#)

Fix spilling sorts with var-len slots that are NULL or empty.

A query that activated the spill-to-disk mechanism could fail if it contained a sort expression involving certain combinations of fixed-length or variable-length types.

Bug: [IMPALA-2357](#)

Work-around IMPALA-2344: Fail query with OOM in case `block->Pin()` fails

Some queries that activated the spill-to-disk mechanism could produce a serious error if there was insufficient memory to set up internal work areas. Now those queries produce normal out-of-memory errors instead.

Bug: [IMPALA-2344](#)

Crash (likely race) tearing down `BufferedBlockMgr` on query failure

A serious error could occur under rare circumstances, due to a race condition while freeing memory during heavily concurrent workloads.

Bug: [IMPALA-2252](#)

`QueryExecState` doesn't check for query cancellation or errors

A call to `SetError()` in a user-defined function (UDF) would not cause the query to fail as expected.

Bug: [IMPALA-1746](#)

Impala throws `IllegalStateException` when inserting data into a partition while select subquery group by partition columns

An `INSERT ... SELECT` operation into a partitioned table could fail if the `SELECT` query included a `GROUP BY` clause referring to the partition key columns.

Bug: [IMPALA-2533](#)

Issues Fixed in Impala for CDH 5.4.8

This section lists the most frequently encountered customer issues fixed in Impala for CDH 5.4.8.



Note: The Impala 2.2.x maintenance releases now use the CDH 5.4.x numbering system rather than increasing the Impala version numbers. Impala 2.2 and higher are not available under CDH 4.

For the full list of fixed issues, see [the CDH 5.4.x release notes](#).

Impala is unable to read hive tables created with the "STORED AS AVRO" clause

Impala could not read Avro tables created in Hive with the `STORED AS AVRO` clause.

Bug: [IMPALA-1136](#), [IMPALA-2161](#)

make Parquet scanner fail query if the file size metadata is stale

If a Parquet file in HDFS was overwritten by a smaller file, Impala could encounter a serious error. Issuing a `INVALIDATE METADATA` statement before a subsequent query would avoid the error. The fix allows Impala to handle such inconsistencies in Parquet file length cleanly regardless of whether the table metadata is up-to-date.

Bug: [IMPALA-2213](#)

Avoid allocating `StringBuffer > 1GB` in `ScannerContext::Stream::GetBytesInternal()`

Impala could encounter a serious error when reading compressed text files larger than 1 GB. The fix causes Impala to issue an error message instead in this case.

Bug: [IMPALA-2249](#)

Disallow long ($1 < \text{length} < 30$) strings in `group_concat()`

A query using the `group_concat()` function could encounter a serious error if the returned string value was larger than 1 GB. Now the query fails with an error message in this case.

Bug: [IMPALA-2284](#)

avoid `FnvHash64to32` with empty inputs

An edge case in the algorithm used to distribute data among nodes could result in uneven distribution of work for some queries, with all data sent to the same node.

Bug: [IMPALA-2270](#)

The catalog does not close the connection to HMS during table invalidation

A communication error could occur between Impala and the Hive metastore database, causing Impala operations that update table metadata to fail.

Bug: [IMPALA-2348](#)

Wrong `DCHECK` in `PHJ::ProcessProbeBatch`

Certain queries could encounter a serious error if the spill-to-disk mechanism was activated.

Bug: [IMPALA-2364](#)

Avoid cardinality 0 in scan nodes of small tables and low selectivity

Impala could generate a suboptimal query plan for some queries involving small tables.

Bug: [IMPALA-2165](#)

Issues Fixed in Impala for CDH 5.4.7

This section lists the most frequently encountered customer issues fixed in Impala for CDH 5.4.7.



Note: The Impala 2.2.x maintenance releases now use the CDH 5.4.x numbering system rather than increasing the Impala version numbers. Impala 2.2 and higher are not available under CDH 4.

For the full list of fixed issues, see [the CDH 5.4.x release notes](#).

Warn if table stats are potentially corrupt.

Impala warns if it detects a discrepancy in table statistics: a table considered to have zero rows even though there are data files present. In this case, Impala also skips query optimizations that are normally applied to very small tables.

Bug: [IMPALA-1983](#)

Pass correct child node in 2nd phase merge aggregation.

A query could encounter a serious error if it included a particular combination of aggregate functions and inline views.

Bug: [IMPALA-2266](#)

Set the output smap of an EmptySetNode produced from an empty inline view.

A query could encounter a serious error if it included an inline view whose subquery had no FROM clause.

Bug: [IMPALA-2216](#)

Set an InsertStmt's result exprs from the source statement's result exprs.

A CREATE TABLE AS SELECT or INSERT . . . SELECT statement could produce different results than a SELECT statement, for queries including a FULL JOIN clause and including literal values in the select list.

Bug: [IMPALA-2203](#)

Fix planning of empty union operands with analytics.

A query could return incorrect results if it contained a UNION clause, calls to analytic functions, and a constant expression that evaluated to FALSE.

Bug: [IMPALA-2088](#)

Retain eq predicates bound by grouping slots with complex grouping exprs.

A query containing an INNER JOIN clause could return undesired rows. Some predicate specified in the ON clause could be omitted from the filtering operation.

Bug: [IMPALA-2089](#)

Row count not set for empty partition when spec is used with compute incremental stats

A COMPUTE INCREMENTAL STATS statement could leave the row count for an empty partition as -1, rather than initializing the row count to 0. The missing statistic value could result in reduced query performance.

Bug: [IMPALA-2199](#)

Explicit aliases + ordinals analysis bug

A query could encounter a serious error if it included column aliases with the same names as table columns, and used ordinal numbers in an ORDER BY or GROUP BY clause.

Bug: [IMPALA-1898](#)

Fix TupleIsNullPredicate to return false if no tuples are nullable.

A query could return incorrect results if it included an outer join clause, inline views, and calls to functions such as coalesce() that can generate NULL values.

Bug: [IMPALA-1987](#)

fix Expr::ComputeResultsLayout() logic

A query could return incorrect results if the table contained multiple CHAR columns with length of 2 or less, and the query included a GROUP BY clause that referred to multiple such columns.

Bug: [IMPALA-2178](#)

Substitute an InsertStmt's partition key exprs with the root node's smap.

An INSERT statement could encounter a serious error if the SELECT portion called an analytic function.

Bug: [IMPALA-1737](#)

Issues Fixed in Impala for CDH 5.4.5

This section lists the most frequently encountered customer issues fixed in Impala for CDH 5.4.5.



Note: The Impala 2.2.x maintenance releases now use the CDH 5.4.x numbering system rather than increasing the Impala version numbers. Impala 2.2 and higher are not available under CDH 4.

For the full list of fixed issues, see [the CDH 5.4.x release notes](#).

Impala DML/DDL operations corrupt table metadata leading to Hive query failures

When the Impala `COMPUTE STATS` statement was run on a partitioned Parquet table that was created in Hive, the table subsequently became inaccessible in Hive. The table was still accessible to Impala. Regaining access in Hive required a workaround of creating a new table. The error displayed in Hive was:

```
Error: Error while compiling statement: FAILED: SemanticException Class not found:
com.cloudera.impala.hive.serde.ParquetInputFormat (state=42000,code=40000)
```

Bug: [IMPALA-2048](#)

Avoiding a DCHECK of NULL hash table in spilled right joins

A query could encounter a serious error if it contained a `RIGHT OUTER`, `RIGHT ANTI`, or `FULL OUTER` join clause and approached the memory limit on a host so that the “spill to disk” mechanism was activated.

Bug: [IMPALA-1929](#)

Bug in PrintTColumnValue caused wrong stats for TINYINT partition cols

Declaring a partition key column as a `TINYINT` caused problems with the `COMPUTE STATS` statement. The associated partitions would always have zero estimated rows, leading to potential inefficient query plans.

Bug: [IMPALA-2136](#)

Where clause does not propagate to joins inside nested views

A query that referred to a view whose query referred to another view containing a join, could return incorrect results. `WHERE` clauses for the outermost query were not always applied, causing the result set to include additional rows that should have been filtered out.

Bug: [IMPALA-2018](#)

Add `effective_user()` builtin

The `user()` function returned the name of the logged-in user, which might not be the same as the user name being checked for authorization if, for example, delegation was enabled.

Bug: [IMPALA-2064](#)

Resolution: Rather than change the behavior of the `user()` function, the fix introduces an additional function `effective_user()` that returns the user name that is checked during authorization.

Make UTC to local `TimestampValue` conversion faster.

Query performance was improved substantially for Parquet files containing `TIMESTAMP` data written by Hive, when the `-convert_legacy_hive_parquet_utc_timestamps=true` setting is in effect.

Bug: [IMPALA-2125](#)

Workaround [IMPALA-1619](#) in `BufferedBlockMgr::ConsumeMemory()`

A join query could encounter a serious error if the query approached the memory limit on a host so that the “spill to disk” mechanism was activated, and data volume in the join was large enough that an internal memory buffer exceeded 1 GB in size on a particular host. (Exceeding this limit would only happen for huge join queries, because Impala could

split this intermediate data into 16 parts during the join query, and the buffer only contains compact bookkeeping data rather than the actual join column data.)

Bug: [IMPALA-2065](#)

Issues Fixed in Impala for CDH 5.4.3

This section lists the most frequently encountered customer issues fixed in Impala for CDH 5.4.3.



Note: The Impala 2.2.x maintenance releases now use the CDH 5.4.x numbering system rather than increasing the Impala version numbers. Impala 2.2 and higher are not available under CDH 4.

For the full list of fixed issues, see [the CDH 5.4.1 release notes](#).

Enable using Isilon as the underlying filesystem.

The certification of CDH and Impala with the Isilon filesystem involves a number of fixes to performance and flexibility for dealing with I/O using remote reads. See [Using Impala with Isilon Storage](#) on page 625 for details on using Impala and Isilon together.

Bug: [IMPALA-1968](#), [IMPALA-1730](#)

Expand set of supported timezones.

The set of timezones recognized by Impala was expanded. You can always find the latest list of supported timezones in the Impala source code, in the file [timezone_db.cc](#).

Bug: [IMPALA-1381](#)

Impala Timestamp ISO-8601 Support.

Impala can now process `TIMESTAMP` literals including a trailing `z`, signifying “Zulu” time, a synonym for UTC.

Bug: [IMPALA-1963](#)

Fix wrong warning when insert overwrite to empty table

An `INSERT OVERWRITE` operation would encounter an error if the `SELECT` portion of the statement returned zero rows, such as with a `LIMIT 0` clause.

Bug: [IMPALA-2008](#)

Expand parsing of decimals to include scientific notation

`DECIMAL` literals can now include `e` scientific notation. For example, now `CAST(1e3 AS DECIMAL(5,3))` is a valid expression. Formerly it returned `NULL`. Some scientific expressions might have worked before in `DECIMAL` context, but only when the scale was 0.

Bug: [IMPALA-1952](#)

Issues Fixed in Impala for CDH 5.4.1

This section lists the most frequently encountered customer issues fixed in Impala for CDH 5.4.1.



Note: The Impala 2.2.x maintenance releases now use the CDH 5.4.x numbering system rather than increasing the Impala version numbers. Impala 2.2 and higher are not available under CDH 4.

For the full list of fixed issues, see [the CDH 5.4.1 release notes](#).

Issues Fixed in the 2.2.0 Release / CDH 5.4.0

This section lists the most frequently encountered customer issues fixed in Impala 2.2.0.

For the full list of fixed issues in Impala 2.2.0, including over 40 critical issues, see [this report in the JIRA system](#).



Note: Impala 2.2.0 is available as part of CDH 5.4.0 and is not available for CDH 4. Cloudera does not intend to release future versions of Impala for CDH 4 outside patch and maintenance releases if required. Given the end-of-maintenance status for CDH 4, Cloudera recommends all customers to migrate to a recent CDH 5 release.

Altering a column's type causes column stats to stop sticking for that column

When the type of a column was changed in either Hive or Impala through `ALTER TABLE CHANGE COLUMN`, the metastore database did not correctly propagate that change to the table that contains the column statistics. The statistics (particularly the `NDV`) for that column were permanently reset and could not be changed by Impala's `COMPUTE STATS` command. The underlying cause is a Hive bug (HIVE-9866).

Bug: [IMPALA-1607](#)

Resolution: Resolved by incorporating the fix for [HIVE-9866](#).

Workaround: On systems without the corresponding Hive fix, change the column back to its original type. The stats reappear and you can recompute or drop them.

Impala may leak or use too many file descriptors

If a file was truncated in HDFS without a corresponding `REFRESH` in Impala, Impala could allocate memory for file descriptors and not free that memory.

Bug: [IMPALA-1854](#)

Spurious stale block locality messages

Impala could issue messages stating the block locality metadata was stale, when the metadata was actually fine. The internal “remote bytes read” counter was not being reset properly. This issue did not cause an actual slowdown in query execution, but the spurious error could result in unnecessary debugging work and unnecessary use of the `INVALIDATE METADATA` statement.

Bug: [IMPALA-1712](#)

DROP TABLE fails after COMPUTE STATS and ALTER TABLE RENAME to a different database.

When a table was moved from one database to another, the column statistics were not pointed to the new database. This could result in lower performance for queries due to unavailable statistics, and also an inability to drop the table.

Bug: [IMPALA-1711](#)

IMPALA-1556 causes memory leak with secure connections

`impalad` daemons could experience a memory leak on clusters using Kerberos authentication, with memory usage growing as more data is transferred across the secure channel, either to the client program or between Impala nodes. The same issue affected LDAP-secured clusters to a lesser degree, because the LDAP security only covers data transferred back to client programs.

Bug: [IMPALA-1674](#)

unix_timestamp() does not return correct time

The `unix_timestamp()` function could return an incorrect value (a constant value of 1).

Bug: [IMPALA-1623](#)

Impala incorrectly handles text data missing a newline on the last line

Some queries did not recognize the final line of a text data file if the line did not end with a newline character. This could lead to inconsistent results, such as a different number of rows for `SELECT COUNT(*)` as opposed to `SELECT *`.

Bug: [IMPALA-1476](#)

Impala's ACLs check do not consider all group ACLs, only checked first one.

If the HDFS user ID associated with the `impalad` process had read or write access in HDFS based on group membership, Impala statements could still fail with HDFS permission errors if that group was not the first listed group for that user ID.

Bug: [IMPALA-1805](#)

Fix infinite loop opening or closing file with invalid metadata

Truncating a file in HDFS, after Impala had cached the file metadata, could produce a hang when Impala queried a table containing that file.

Bug: [IMPALA-1794](#)

Cannot write Parquet files when values are larger than 64KB

Impala could sometimes fail to `INSERT` into a Parquet table if a column value such as a `STRING` was larger than 64 KB.

Bug: [IMPALA-1705](#)

Impala Will Not Run on Certain Intel CPUs

This fix relaxes the CPU requirement for Impala. Now only the SSE3 instruction set is required. Formerly, SSE4.1 instructions were generated, making Impala refuse to start on some older CPUs.

Bug: [IMPALA-1646](#)

Issues Fixed in Impala for CDH 5.3.10

For the full list of fixed issues for all CDH components, see [the CDH 5.3.x release notes](#).



Note: This Impala maintenance release is only available as part of CDH 5, not under CDH 4.

- [IMPALA-1702](#) - "invalidate metadata" can cause duplicate TableIds (issue not entirely fixed, but now fails gracefully)
- [IMPALA-2125](#) - Improve perf when reading timestamps from parquet files written by hive
- [IMPALA-2565](#) - Planner tests are flaky due to file size mismatches
- [IMPALA-3095](#) - Allow additional Kerberos users to be authorized to access internal APIs

Issues Fixed in the 2.1.7 Release / CDH 5.3.9

This section lists the most significant Impala issues fixed in Impala 2.1.7 for CDH 5.3.9.

For the full list of Impala fixed issues in this release, see [the CDH 5.3.9 release notes](#).



Note: This Impala maintenance release is only available as part of CDH 5, not under CDH 4.

Query return empty result if it contains NullLiteral in inlineview

If an inline view in a `FROM` clause contained a `NULL` literal, the result set was empty.

Bug: [IMPALA-1917](#)

Fix edge cases for decimal/integer cast

A value of type `DECIMAL(3,0)` could be incorrectly cast to `TINYINT`. The resulting out-of-range value could be incorrect. After the fix, the smallest type that is allowed for this cast is `INT`, and attempting to use `DECIMAL(3,0)` in a `TINYINT` context produces a "loss of precision" error.

Bug: [IMPALA-2264](#)

Constant filter expressions are not checked for errors and state cleanup on exception / DCHECK on destroying an ExprContext

An invalid constant expression in a `WHERE` clause (for example, an invalid regular expression pattern) could fail to clean up internal state after raising a query error. Therefore, certain combinations of invalid expressions in a query could cause a crash, or cause a query to continue when it should halt with an error.

Bug: [IMPALA-1756](#), [IMPALA-2514](#)

QueryExecState does not check for query cancellation or errors

A call to `setError()` in a user-defined function (UDF) would not cause the query to fail as expected.

Bug: [IMPALA-1746](#), [IMPALA-2141](#)

Issues Fixed in the 2.1.6 Release / CDH 5.3.8

This section lists the most significant Impala issues fixed in Impala 2.1.6 for CDH 5.3.8.

For the full list of Impala fixed issues in this release, see [the CDH 5.3.8 release notes](#).



Note: This Impala maintenance release is only available as part of CDH 5, not under CDH 4.

Wrong DCHECK in PHJ::ProcessProbeBatch

Certain queries could encounter a serious error if the spill-to-disk mechanism was activated.

Bug: [IMPALA-2364](#)

LargestSpilledPartition was not checking if partition is closed

Certain queries could encounter a serious error if the spill-to-disk mechanism was activated.

Bug: [IMPALA-2314](#)

Avoid cardinality 0 in scan nodes of small tables and low selectivity

Impala could generate a suboptimal query plan for some queries involving small tables.

Bug: [IMPALA-2165](#)

fix Expr::ComputeResultsLayout() logic

Queries using the `GROUP BY` operator on multiple `CHAR` columns with length less than or equal to 2 characters could return incorrect results for some columns.

Bug: [IMPALA-2178](#)

Properly unescape string value for HBase filters

Queries against HBase tables could return incomplete results if the `WHERE` clause included string comparisons using literals containing escaped quotation marks.

Bug: [IMPALA-2133](#)

Avoiding a DCHECK of NULL hash table in spilled right joins

A query could encounter a serious error if it contained a `RIGHT OUTER`, `RIGHT ANTI`, or `FULL OUTER` join clause and approached the memory limit on a host so that the “spill to disk” mechanism was activated.

Bug: [IMPALA-1929](#)

Issues Fixed in the 2.1.5 Release / CDH 5.3.6

This section lists the most significant Impala issues fixed in Impala 2.1.5 for CDH 5.3.6.

For the full list of Impala fixed issues in this release, see [the CDH 5.3.6 release notes](#).



Note: This Impala maintenance release is only available as part of CDH 5, not under CDH 4.

Avoid calling ProcessBatch with out_batch->AtCapacity in right joins

Queries including `RIGHT OUTER JOIN`, `RIGHT ANTI JOIN`, or `FULL OUTER JOIN` clauses and involving a high volume of data could encounter a serious error.

Bug: [IMPALA-1919](#)

Issues Fixed in the 2.1.4 Release / CDH 5.3.4

This section lists the most significant Impala issues fixed in Impala 2.1.4 for CDH 5.3.4. Because CDH 5.3.5 does not include any code changes for Impala, Impala 2.1.4 is included with both CDH 5.3.4 and 5.3.5.

For the full list of Impala fixed issues in Impala 2.1.4 for CDH 5.3.4, see [the CDH 5.3.4 release notes](#).



Note: This Impala maintenance release is only available as part of CDH 5, not under CDH 4.

Crash: impala::TuplesIsNullPredicate::Prepare

When expressions that tested for `NULL` were used in combination with analytic functions, an error could occur. (The original crash issue was fixed by an earlier patch.)

Bug: [IMPALA-1519](#)

Expand parsing of decimals to include scientific notation

`DECIMAL` literals could include `e` scientific notation. For example, now `CAST(1e3 AS DECIMAL(5,3))` is a valid expression. Formerly it returned `NULL`. Some scientific expressions might have worked before in `DECIMAL` context, but only when the scale was 0.

Bug: [IMPALA-1952](#)

INSERT/CTAS evaluates and applies constant predicates.

An `INSERT OVERWRITE` statement would write new data, even if a constant clause such as `WHERE 1 = 0` should have prevented it from writing any rows.

Bug: [IMPALA-1860](#)

Assign predicates below analytic functions with a compatible partition by clause

If the `PARTITION BY` clause in an analytic function refers to partition key columns in a partitioned table, now Impala can perform partition pruning during the analytic query.

Bug: [IMPALA-1900](#)

FIRST_VALUE may produce incorrect results with preceding windows

A query using the `FIRST_VALUE` analytic function and a window defined with the `PRECEDING` keyword could produce wrong results.

Bug: [IMPALA-1888](#)

FIRST_VALUE rewrite fn type might not match slot type

A query referencing a `DECIMAL` column with the `FIRST_VALUE` analytic function could encounter an error.

Bug: [IMPALA-1559](#)

AnalyticEvalNode cannot handle partition/order by exprs with NaN

A query using an analytic function could encounter an error if the evaluation of an analytic `ORDER BY` or `PARTITION` expression resulted in a NaN value, for example if the `ORDER BY` or `PARTITION` contained a division operation where both operands were zero.

Bug: [IMPALA-1808](#)

AnalyticEvalNode not properly handling nullable tuples

An analytic function containing only an `OVER` clause could encounter an error if another part of the query (specifically an outer join) produced all-NULL tuples.

Bug: [IMPALA-1562](#)

Issues Fixed in the 2.1.3 Release / CDH 5.3.3

This section lists the most significant issues fixed in Impala 2.1.3.

For the full list of fixed issues in Impala 2.1.3, see [the CDH 5.3.3 release notes](#).



Note: Impala 2.1.3 is available as part of CDH 5.3.3, not under CDH 4.

Add compatibility flag for Hive-Parquet-Timestamps

When Hive writes `TIMESTAMP` values, it represents them in the local time zone of the server. Impala expects `TIMESTAMP` values to always be in the UTC time zone, possibly leading to inconsistent results depending on which component created the data files. This patch introduces a new startup flag, `-convert_legacy_hive_parquet_utc_timestamps` for the `impalad` daemon. Specify `-convert_legacy_hive_parquet_utc_timestamps=true` to make Impala recognize Parquet data files written by Hive and automatically adjust `TIMESTAMP` values read from those files into the UTC time zone for compatibility with other Impala `TIMESTAMP` processing. Although this setting is currently turned off by default, consider enabling it if practical in your environment, for maximum interoperability with Hive-created Parquet files.

Bug: [IMPALA-1658](#)

Use `snprintf()` instead of `lexical_cast()` in float-to-string casts

Converting a floating-point value to a `STRING` could be slower than necessary.

Bug: [IMPALA-1738](#)

Fix partition spilling cleanup when new stream OOMs

Certain calls to aggregate functions with `STRING` arguments could encounter a serious error when the system ran low on memory and attempted to activate the spill-to-disk mechanism. The error message referenced the function `impala::AggregateFunctions::StringValGetValue`.

Bug: [IMPALA-1865](#)

Impala's ACLs check do not consider all group ACLs, only checked first one.

If the HDFS user ID associated with the `impalad` process had read or write access in HDFS based on group membership, Impala statements could still fail with HDFS permission errors if that group was not the first listed group for that user ID.

Bug: [IMPALA-1805](#)

Fix infinite loop opening or closing file with invalid metadata

Truncating a file in HDFS, after Impala had cached the file metadata, could produce a hang when Impala queried a table containing that file.

Bug: [IMPALA-1794](#)

external-data-source-executor leaking global jni refs

Successive calls to the data source API could result in excessive memory consumption, with memory allocated but never freed.

Bug: [IMPALA-1801](#)

Spurious stale block locality messages

Impala could issue messages stating the block locality metadata was stale, when the metadata was actually fine. The internal “remote bytes read” counter was not being reset properly. This issue did not cause an actual slowdown in query execution, but the spurious error could result in unnecessary debugging work and unnecessary use of the `INVALIDATE METADATA` statement.

Bug: [IMPALA-1712](#)

Issues Fixed in the 2.1.2 Release / CDH 5.3.2

This section lists the most significant issues fixed in Impala 2.1.2.

For the full list of fixed issues in Impala 2.1.2, see [this report in the JIRA system](#).



Note: Impala 2.1.2 is available as part of CDH 5.3.2, not under CDH 4.

Impala incorrectly handles double numbers with more than 19 significant decimal digits

When a floating-point value was read from a text file and interpreted as a `FLOAT` or `DOUBLE` value, it could be incorrectly interpreted if it included more than 19 significant digits.

Bug: [IMPALA-1622](#)

unix_timestamp() does not return correct time

The `unix_timestamp()` function could return an incorrect value (a constant value of 1).

Bug: [IMPALA-1623](#)

Row Count Mismatch: Partition pruning with NULL

A query against a partitioned table could return incorrect results if the `WHERE` clause compared the partition key to `NULL` using operators such as `=` or `!=`.

Bug: [IMPALA-1535](#)

Fetch column stats in bulk using new (Hive .13) HMS APIs

The performance of the `COMPUTE STATS` statement and queries was improved, particularly for wide tables.

Bug: [IMPALA-1120](#)

Issues Fixed in the 2.1.1 Release / CDH 5.3.1

This section lists the most significant issues fixed in Impala 2.1.1.

For the full list of fixed issues in Impala 2.1.1, see [this report in the JIRA system](#).

IMPALA-1556 causes memory leak with secure connections

`impalad` daemons could experience a memory leak on clusters using Kerberos authentication, with memory usage growing as more data is transferred across the secure channel, either to the client program or between Impala nodes. The same issue affected LDAP-secured clusters to a lesser degree, because the LDAP security only covers data transferred back to client programs.

Bug: <https://issues.cloudera.org/browse/IMPALA-1674> IMPALA-1674

TSaslServerTransport::Factory::getTransport() leaks transport map entries

`impalad` daemons in clusters secured by Kerberos or LDAP could experience a slight memory leak on each connection. The accumulation of unreleased memory could cause problems on long-running clusters.

Bug: [IMPALA-1668](#)

Issues Fixed in the 2.1.0 Release / CDH 5.3.0

This section lists the most significant issues fixed in Impala 2.1.0.

For the full list of fixed issues in Impala 2.1.0, see [this report in the JIRA system](#).

Kerberos fetches 3x slower

Transferring large result sets back to the client application on Kerberos

Bug: [IMPALA-1455](#)

Compressed file needs to be hold on entirely in Memory

Queries on gzipped text files required holding the entire data file and its uncompressed representation in memory at the same time. `SELECT` and `COMPUTE STATS` statements could fail or perform inefficiently as a result. The fix enables streaming reads for gzipped text, so that the data is uncompressed as it is read.

Bug: [IMPALA-1556](#)

Cannot read hbase metadata with NullPointerException: null

Impala might not be able to access HBase tables, depending on the associated levels of Impala and HBase on the system.

Bug: [IMPALA-1611](#)

Serious errors / crashes

Improved code coverage in Impala testing uncovered a number of potentially serious errors that could occur with specific query syntax. These errors are resolved in Impala 2.1.

Bug: [IMPALA-1553](#) , [IMPALA-1528](#) , [IMPALA-1526](#) , [IMPALA-1524](#) , [IMPALA-1508](#) , [IMPALA-1493](#) , [IMPALA-1501](#) , [IMPALA-1483](#)

Issues Fixed in the 2.0.5 Release / CDH 5.2.6

For the full list of fixed issues in Impala 2.0.5, see [this report in the JIRA system](#).



Note: Impala 2.0.5 is available as part of CDH 5.2.6, not under CDH 4.

Issues Fixed in the 2.0.4 Release / CDH 5.2.5

This section lists the most significant issues fixed in Impala 2.0.4.

For the full list of fixed issues in Impala 2.0.4, see [this report in the JIRA system](#).



Note: Impala 2.0.4 is available as part of CDH 5.2.5, not under CDH 4.

Add compatibility flag for Hive-Parquet-Timestamps

When Hive writes `TIMESTAMP` values, it represents them in the local time zone of the server. Impala expects `TIMESTAMP` values to always be in the UTC time zone, possibly leading to inconsistent results depending on which component created the data files. This patch introduces a new startup flag, `-convert_legacy_hive_parquet_utc_timestamps` for the `impalad` daemon. Specify `-convert_legacy_hive_parquet_utc_timestamps=true` to make Impala recognize Parquet data files written by Hive and automatically adjust `TIMESTAMP` values read from those files into the UTC time zone for compatibility with other Impala `TIMESTAMP` processing. Although this setting is currently turned off by default, consider enabling it if practical in your environment, for maximum interoperability with Hive-created Parquet files.

Bug: [IMPALA-1658](#)

IoMgr infinite loop opening/closing file when shorter than cached metadata size

If a table data file was replaced by a shorter file outside of Impala, such as with `INSERT OVERWRITE` in Hive producing an empty output file, subsequent Impala queries could hang.

Bug: [IMPALA-1794](#)

Issues Fixed in the 2.0.3 Release / CDH 5.2.4

This section lists the most significant issues fixed in Impala 2.0.3.

For the full list of fixed issues in Impala 2.0.3, see [this report in the JIRA system](#).



Note: Impala 2.0.3 is available as part of CDH 5.2.4, not under CDH 4.

Anti join could produce incorrect results when spilling

An anti-join query (or a `NOT EXISTS` operation that was rewritten internally into an anti-join) could produce incorrect results if Impala reached its memory limit, causing the query to write temporary results to disk.

Bug: [IMPALA-1471](#)

Row Count Mismatch: Partition pruning with NULL

A query against a partitioned table could return incorrect results if the `WHERE` clause compared the partition key to `NULL` using operators such as `=` or `!=`.

Bug: [IMPALA-1535](#)

Fetch column stats in bulk using new (Hive .13) HMS APIs

The performance of the `COMPUTE STATS` statement and queries was improved, particularly for wide tables.

Bug: [IMPALA-1120](#)

Issues Fixed in the 2.0.2 Release / CDH 5.2.3

This section lists the most significant issues fixed in Impala 2.0.2.

For the full list of fixed issues in Impala 2.0.2, see [this report in the JIRA system](#).



Note: Impala 2.0.2 is available as part of CDH 5.2.3, not under CDH 4.

GROUP BY on STRING column produces inconsistent results

Some operations in queries submitted through Hue or other HiveServer2 clients could produce inconsistent results.

Bug: [IMPALA-1453](#)

Fix leaked file descriptor and excessive file descriptor use

Impala could encounter an error from running out of file descriptors. The fix reduces the amount of time file descriptors are kept open, and avoids leaking file descriptors when read operations encounter errors.

unix_timestamp() does not return correct time

The `unix_timestamp()` function could return a constant value 1 instead of a representation of the time.

Bug: [IMPALA-1623](#)

Impala should randomly select cached replica

To avoid putting too heavy a load on any one node, Impala now randomizes which scan node processes each HDFS data block rather than choosing the first cached block replica.

Bug: [IMPALA-1586](#)

Impala does not always give short name to Llama.

In clusters secured by Kerberos or LDAP, a discrepancy in internal transmission of user names could cause a communication error with Llama.

Bug: [IMPALA-1606](#)

accept unmangled native UDF symbols

The `CREATE FUNCTION` statement could report that it could not find a function entry point within the `.so` file for a UDF written in C++, even if the corresponding function was present.

Bug: [IMPALA-1475](#)

Issues Fixed in the 2.0.1 Release / CDH 5.2.1

This section lists the most significant issues fixed in Impala 2.0.1.

For the full list of fixed issues in Impala 2.0.1, see [this report in the JIRA system](#).

Queries fail with metastore exception after upgrade and compute stats

After running the `COMPUTE STATS` statement on an Impala table, subsequent queries on that table could fail with the exception message `Failed to load metadata for table: default.stats_test`.

Bug: <https://issues.cloudera.org/browse/IMPALA-1416> IMPALA-1416

Workaround: Upgrading to CDH 5.2.1, or another level of CDH that includes the fix for HIVE-8627, prevents the problem from affecting future `COMPUTE STATS` statements. On affected levels of CDH, or for Impala tables that have become inaccessible, the workaround is to disable the `hive.metastore.try.direct.sql` setting in the Hive metastore `hive-site.xml` file and issue the `INVALIDATE METADATA` statement for the affected table. You do not need to rerun the `COMPUTE STATS` statement for the table.

Issues Fixed in the 2.0.0 Release / CDH 5.2.0

This section lists the most significant issues fixed in Impala 2.0.0.

For the full list of fixed issues in Impala 2.0.0, see [this report in the JIRA system](#).

Join Hint is dropped when used inside a view

Hints specified within a view query did not take effect when the view was queried, leading to slow performance. As part of this fix, Impala now supports hints embedded within comments.

Bug: [IMPALA-995"](#)

WHERE condition ignored in simple query with RIGHT JOIN

Potential wrong results for some types of queries.

Bug: [IMPALA-1101"](#)

Query with self joined table may produce incorrect results

Potential wrong results for some types of queries.

Bug: [IMPALA-1102"](#)

Incorrect plan after reordering predicates (inner join following outer join)

Potential wrong results for some types of queries.

Bug: [IMPALA-1118"](#)

Combining fragments with compatible data partitions can lead to incorrect results due to type incompatibilities (missing casts).

Potential wrong results for some types of queries.

Bug: [IMPALA-1123"](#)

Predicate dropped: Inline view + DISTINCT aggregate in outer query

Potential wrong results for some types of queries.

Bug: [IMPALA-1165"](#)

Reuse of a column in JOIN predicate may lead to incorrect results

Potential wrong results for some types of queries.

Bug: [IMPALA-1353"](#)

Usage of TRUNC with string timestamp reliably crashes node

Serious error for certain combinations of function calls and data types.

Bug: [IMPALA-1105"](#)

Timestamp Cast Returns invalid TIMESTAMP

Serious error for certain combinations of function calls and data types.

Bug: [IMPALA-1109"](#)

IllegalStateException upon JOIN of DECIMAL columns with different precision

DECIMAL columns with different precision could not be compared in join predicates.

Bug: [IMPALA-1121"](#)

Allow creating Avro tables without column definitions. Allow COMPUTE STATS to always work on Impala-created Avro tables.

Hive-created Avro tables with columns specified by a JSON file or literal could produce errors when queried in Impala, and could not be used with the COMPUTE STATS statement. Now you can create such tables in Impala to avoid such errors.

Bug: [IMPALA-1104](#)"

Ensure all webserver output is escaped

The Impala debug web UI did not properly encode all output.

Bug: [IMPALA-1133](#)"

Queries with union in inline view have empty resource requests

Certain queries could run without obeying the limits imposed by resource management.

Bug: [IMPALA-1236](#)"

Impala does not employ ACLs when checking path permissions for LOAD and INSERT

Certain INSERT and LOAD DATA statements could fail unnecessarily, if the target directories in HDFS had restrictive HDFS permissions, but those permissions were overridden by HDFS extended ACLs.

Bug: [IMPALA-1279](#)"

Impala does not map principals to lowercase, affecting Sentry authorisation

In a Kerberos environment, the principal name was not mapped to lowercase, causing issues when a user logged in with an uppercase principal name and Sentry authorization was enabled.

Bug: [IMPALA-1334](#)"

Issues Fixed in the 1.4.4 Release / CDH 5.1.5

For the list of fixed issues, see [Issues Fixed in CDH 5.1.5](#) in the *CDH 5 Release Notes*.



Note: Impala 1.4.4 is available as part of CDH 5.1.5, not under CDH 4.

Issues Fixed in the 1.4.3 Release / CDH 5.1.4

Impala 1.4.3 includes fixes to address what is known as the POODLE vulnerability in SSLv3. SSLv3 access is disabled in the Impala debug web UI.



Note: Impala 1.4.3 is available as part of CDH 5.1.4, and under CDH 4.

Issues Fixed in the 1.4.2 Release / CDH 5.1.3

This section lists the most significant issues fixed in Impala 1.4.2.

For the full list of fixed issues in Impala 1.4.2, see [this report in the JIRA system](#).



Note: Impala 1.4.3 is available as part of CDH 5.1.4, and under CDH 4.

Issues Fixed in the 1.4.1 Release / CDH 5.1.2

This section lists the most significant issues fixed in Impala 1.4.1.

For the full list of fixed issues in Impala 1.4.1, see [this report in the JIRA system](#).



Note: Impala 1.4.1 is only available as part of CDH 5.1.2, not under CDH 4.

impalad terminating with Boost exception

Occasionally, a non-trivial query run through Llama could encounter a serious error. The detailed error in the log was:

```
boost::exception_detail::clone_impl
<boost::exception_detail::error_info_injector<boost::lock_error> >
```

Severity: High

Impalad uses wrong string format when writing logs

Impala log files could contain internal error messages due to a problem formatting certain strings. The messages consisted of a Java call stack starting with:

```
jni-util.cc:177] java.util.MissingFormatArgumentException: Format specifier 's'
```

Update HS2 client API.

A downlevel version of the HiveServer2 API could cause difficulty retrieving the precision and scale of a `DECIMAL` value.

Bug: [IMPALA-1107](#)

Impalad catalog updates can fail with error: "IllegalArgumentException: fromKey out of range" at `com.cloudera.impala.catalog.CatalogDeltaLog`

The error in the title could occur following a DDL statement. This issue was discovered during internal testing and has not been reported in customer environments.

Bug: [IMPALA-1093](#)

"Total" time counter does not capture all the network transmit time

The time for some network operations was not counted in the report of total time for a query, making it difficult to diagnose network-related performance issues.

Bug: [IMPALA-1131](#)

Impala will crash when reading certain Avro files containing bytes data

Certain Avro fields for byte data could cause Impala to be unable to read an Avro data file, even if the field was not part of the Impala table definition. With this fix, Impala can now read these Avro data files, although Impala queries cannot refer to the "bytes" fields.

Bug: [IMPALA-1149](#)

Support specifying a custom AuthorizationProvider in Impala

The `--authorization_policy_provider_class` option for `impalad` was added back. This option specifies a custom `AuthorizationProvider` class rather than the default `HadoopGroupAuthorizationProvider`. It had been used for internal testing, then removed in Impala 1.4.0, but it was considered useful by some customers.

Bug: [IMPALA-1142](#)

Issues Fixed in the 1.4.0 Release / CDH 5.1.0

This section lists the most significant issues fixed in Impala 1.4.0.

For the full list of fixed issues in Impala 1.4.0, see [this report in the JIRA system](#).

Failed DCHECK in disk-io-mgr-reader-context.cc:174

The serious error in the title could occur, with the supplemental message:

```
num_used_buffers_ < 0: #used=-1 during cancellation HDFS cached data
```

The issue was due to the use of HDFS caching with data files accessed by Impala. Support for HDFS caching in Impala was introduced in Impala 1.4.0 for CDH 5.1.0. The fix for this issue was backported to Impala 1.3.x, and is the only change in Impala 1.3.2 for CDH 5.0.4.

Bug: [IMPALA-1019](#)

Workaround: On CDH 5.0.x, upgrade to CDH 5.0.4 with Impala 1.3.2, where this issue is fixed. In Impala 1.3.0 or 1.3.1 on CDH 5.0.x, do not use HDFS caching for Impala data files in Impala internal or external tables. If some of these data files are cached (for example because they are used by other components that take advantage of HDFS caching), set the query option `DISABLE_CACHED_READS=true`. To set that option for all Impala queries across all sessions, start `impalad` with the `-default_query_options` option and include this setting in the option argument, or on a cluster managed by Cloudera Manager, fill in this option setting on the **Impala Daemon** options page.

Resolution: This issue is fixed in Impala 1.3.2 for CDH 5.0.4. The addition of HDFS caching support in Impala 1.4 means that this issue does not apply to any new level of Impala on CDH 5.

impala-shell only works with ASCII characters

The `impala-shell` interpreter could encounter errors processing SQL statements containing non-ASCII characters.

Bug: [IMPALA-489](#)

The extended view definition SQL text in Views created by Impala should always have fully-qualified table names

When a view was accessed while inside a different database, references to tables were not resolved unless the names were fully qualified when the view was created.

Bug: [IMPALA-962](#)

Impala forgets about partitions with non-existent locations

If an `ALTER TABLE` specified a non-existent HDFS location for a partition, afterwards Impala would not be able to access the partition at all.

Bug: [IMPALA-741](#)

CREATE TABLE LIKE fails if source is a view

The `CREATE TABLE LIKE` clause was enhanced to be able to create a table with the same column definitions as a view. The resulting table is a text table unless the `STORED AS` clause is specified, because a view does not have an associated file format to inherit.

Bug: [IMPALA-834](#)

Improve partition pruning time

Operations on tables with many partitions could be slow due to the time to evaluate which partitions were affected. The partition pruning code was speeded up substantially.

Bug: [IMPALA-887](#)

Improve compute stats performance

The performance of the `COMPUTE STATS` statement was improved substantially. The efficiency of its internal operations was improved, and some statistics are no longer gathered because they are not currently used for planning Impala queries.

Bug: [IMPALA-1003](#)

When I run `CREATE TABLE new_table LIKE avro_table`, the schema does not get mapped properly from an avro schema to a hive schema

After a `CREATE TABLE LIKE` statement using an Avro table as the source, the new table could have incorrect metadata and be inaccessible, depending on how the original Avro table was created.

Bug: [IMPALA-185](#)

Race condition in IoMgr. Blocked ranges enqueued after cancel.

Impala could encounter a serious error after a query was cancelled.

Bug: [IMPALA-1046](#)

Deadlock in scan node

A deadlock condition could make all `impalad` daemons hang, making the cluster unresponsive for Impala queries.

Bug: [IMPALA-1083](#)

Issues Fixed in the 1.3.3 Release / CDH 5.0.5

Impala 1.3.3 includes fixes to address what is known as the POODLE vulnerability in SSLv3. SSLv3 access is disabled in the Impala debug web UI.



Note: Impala 1.3.3 is only available as part of CDH 5.0.5, not under CDH 4.

Issues Fixed in the 1.3.2 Release / CDH 5.0.4

This backported bug fix is the only change between Impala 1.3.1 and Impala 1.3.2.



Note: Impala 1.3.3 is only available as part of CDH 5.0.5, not under CDH 4.

Failed DCHECK in disk-io-mgr-reader-context.cc:174

The serious error in the title could occur, with the supplemental message:

```
num_used_buffers_ < 0: #used=-1 during cancellation HDFS cached data
```

The issue was due to the use of HDFS caching with data files accessed by Impala. Support for HDFS caching in Impala was introduced in Impala 1.4.0 for CDH 5.1.0. The fix for this issue was backported to Impala 1.3.x, and is the only change in Impala 1.3.2 for CDH 5.0.4.

Bug: [IMPALA-1019](#)

Workaround: On CDH 5.0.x, upgrade to CDH 5.0.4 with Impala 1.3.2, where this issue is fixed. In Impala 1.3.0 or 1.3.1 on CDH 5.0.x, do not use HDFS caching for Impala data files in Impala internal or external tables. If some of these data files are cached (for example because they are used by other components that take advantage of HDFS caching), set the query option `DISABLE_CACHED_READS=true`. To set that option for all Impala queries across all sessions, start `impalad` with the `-default_query_options` option and include this setting in the option argument, or on a cluster managed by Cloudera Manager, fill in this option setting on the **Impala Daemon** options page.

Resolution: This issue is fixed in Impala 1.3.2 for CDH 5.0.4. The addition of HDFS caching support in Impala 1.4 means that this issue does not apply to any new level of Impala on CDH 5.

Issues Fixed in the 1.3.1 Release / CDH 5.0.3

This section lists the most significant issues fixed in Impala 1.3.1.

For the full list of fixed issues in Impala 1.3.1, see [this report in the JIRA system](#). Because 1.3.1 is the first 1.3.x release for CDH 4, if you are on CDH 4, also consult [Issues Fixed in the 1.3.0 Release / CDH 5.0.0](#) on page 743.

Impalad crashes when left joining inline view that has aggregate using distinct

Impala could encounter a severe error in a query combining a left outer join with an inline view containing a `COUNT(DISTINCT)` operation.

Bug: [IMPALA-904](#)

Incorrect result with group by query with null value in group by data

If the result of a `GROUP BY` operation is `NULL`, the resulting row might be omitted from the result set. This issue depends on the data values and data types in the table.

Bug: [IMPALA-901](#)

Drop Function does not clear local library cache

When a UDF is dropped through the `DROP FUNCTION` statement, and then the UDF is re-created with a new `.so` library or JAR file, the original version of the UDF is still used when the UDF is called from queries.

Bug: [IMPALA-786](#)

Workaround: Restart the `impalad` daemon on all nodes.

Compute stats doesn't propagate underlying error correctly

If a `COMPUTE STATS` statement encountered an error, the error message is “Query aborted” with no further detail. Common reasons why a `COMPUTE STATS` statement might fail include network errors causing the coordinator node to lose contact with other `impalad` instances, and column names that match Impala [reserved words](#). (Currently, if a column name is an Impala reserved word, `COMPUTE STATS` always returns an error.)

Bug: [IMPALA-762](#)

Inserts should respect changes in partition location

After an `ALTER TABLE` statement that changes the `LOCATION` property of a partition, a subsequent `INSERT` statement would always use a path derived from the base data directory for the table.

Bug: [IMPALA-624](#)

Text data with carriage returns generates wrong results for count(*)

A `COUNT(*)` operation could return the wrong result for text tables using nul characters (ASCII value 0) as delimiters.

Bug: [IMPALA-13](#)

Workaround: Impala adds support for ASCII 0 characters as delimiters through the clause `FIELDS TERMINATED BY '\0'`.

IO Mgr should take instance memory limit into account when creating io buffers

Impala could allocate more memory than necessary during certain operations.

Bug: [IMPALA-488](#)

Workaround: Before issuing a `COMPUTE STATS` statement for a Parquet table, reduce the number of threads used in that operation by issuing `SET NUM_SCANNER_THREADS=2` in `impala-shell`. Then issue `UNSET NUM_SCANNER_THREADS` before continuing with queries.

Impala should provide an option for new sub directories to automatically inherit the permissions of the parent directory

When new subdirectories are created underneath a partitioned table by an `INSERT` statement, previously the new subdirectories always used the default HDFS permissions for the `impala` user, which might not be suitable for directories intended to be read and written by other components also.

Bug: [IMPALA-827](#)

Resolution: In Impala 1.3.1 and higher, you can specify the `--insert_inherit_permissions` configuration when starting the `impalad` daemon.

Illegal state exception (or crash) in query with UNION in inline view

Impala could encounter a severe error in a query where the `FROM` list contains an inline view that includes a `UNION`. The exact type of the error varies.

Bug: [IMPALA-888](#)

INSERT column reordering doesn't work with SELECT clause

The ability to specify a subset of columns in an `INSERT` statement, with order different than in the target table, was not working as intended.

Bug: [IMPALA-945](#)

Issues Fixed in the 1.3.0 Release / CDH 5.0.0

This section lists the most significant issues fixed in Impala 1.3.0, primarily issues that could cause wrong results, or cause problems running the `COMPUTE STATS` statement, which is very important for performance and scalability.

For the full list of fixed issues, see [this report in the JIRA system](#).

Inner join after right join may produce wrong results

The automatic join reordering optimization could incorrectly reorder queries with an outer join or semi join followed by an inner join, producing incorrect results.

Bug: [IMPALA-860](#)

Workaround: Including the `STRAIGHT_JOIN` keyword in the query prevented the issue from occurring.

Incorrect results with codegen on multi-column group by with NULLs.

A query with a `GROUP BY` clause referencing multiple columns could introduce incorrect `NULL` values in some columns of the result set. The incorrect `NULL` values could appear in rows where a different `GROUP BY` column actually did return `NULL`.

Bug: [IMPALA-850](#)

Using distinct inside aggregate function may cause incorrect result when using having clause

A query could return incorrect results if it combined an aggregate function call, a `DISTINCT` operator, and a `HAVING` clause, without a `GROUP BY` clause.

Bug: [IMPALA-845](#)

Aggregation on union inside (inline) view not distributed properly.

An aggregation query or a query with `ORDER BY` and `LIMIT` could be executed on a single node in some cases, rather than distributed across the cluster. This issue affected queries whose `FROM` clause referenced an inline view containing a `UNION`.

Bug: [IMPALA-831](#)

Wrong expression may be used in aggregate query if there are multiple similar expressions

If a `GROUP BY` query referenced the same columns multiple times using different operators, result rows could contain multiple copies of the same expression.

Bug: [IMPALA-817](#)

Incorrect results when changing the order of aggregates in the select list with codegen enabled

Referencing the same columns in both a `COUNT()` and a `SUM()` call in the same query, or some other combinations of aggregate function calls, could incorrectly return a result of 0 from one of the aggregate functions. This issue affected references to `TINYINT` and `SMALLINT` columns, but not `INT` or `BIGINT` columns.

Bug: [IMPALA-765](#)

Workaround: Setting the query option `DISABLE_CODEGEN=TRUE` prevented the incorrect results. Switching the order of the function calls could also prevent the issue from occurring.

Union queries give Wrong result in a UNION followed by SIGSEGV in another union

A `UNION` query could produce a wrong result, followed by a serious error for a subsequent `UNION` query.

Bug: [IMPALA-723](#)

String data in MR-produced parquet files may be read incorrectly

Impala could return incorrect string results when reading uncompressed Parquet data files containing multiple row groups. This issue only affected Parquet data files produced by MapReduce jobs.

Bug: [IMPALA-729](#)

Compute stats need to use quotes with identifiers that are Impala keywords

Using a column or table name that conflicted with Impala keywords could prevent running the `COMPUTE STATS` statement for the table.

Bug: [IMPALA-777](#)

COMPUTE STATS child queries do not inherit parent query options.

The `COMPUTE STATS` statement did not use the setting of the `MEM_LIMIT` query option in `impala-shell`, potentially causing problems gathering statistics for wide Parquet tables.

Bug: [IMPALA-903](#)

COMPUTE STATS should update partitions in batches

The `COMPUTE STATS` statement could be slow or encounter a timeout while analyzing a table with many partitions.

Bug: [IMPALA-880](#)

Fail early (in analysis) when COMPUTE STATS is run against Avro table with no columns

If the columns for an Avro table were all defined in the `TBLPROPERTIES` or `SERDEPROPERTIES` clauses, the `COMPUTE STATS` statement would fail after completely analyzing the table, potentially causing a long delay. Although the `COMPUTE STATS` statement still does not work for such tables, now the problem is detected and reported immediately.

Bug: [IMPALA-867](#)

Workaround: Re-create the Avro table with columns defined in SQL style, using the output of `SHOW CREATE TABLE`. (See the JIRA page for detailed steps.)

Issues Fixed in the 1.2.4 Release

This section lists the most significant issues fixed in Impala 1.2.4. For the full list of fixed issues, see [this report in the JIRA system](#).

The Catalog Server exits with an OOM error after a certain number of CREATE statements

A large number of concurrent `CREATE TABLE` statements can cause the `catalogd` process to consume excessive memory, and potentially be killed due to an out-of-memory condition.

Bug: [IMPALA-818](#)

Workaround: Restart the `catalogd` service and re-try the DDL operations that failed.

Catalog Server consumes excessive cpu cycle

A large number of tables and partitions could result in unnecessary CPU overhead during Impala idle time and background operations.

Bug: [IMPALA-821](#)

Resolution: Catalog server processing was optimized in several ways.

Query against Avro table crashes Impala with codegen enabled

A query against a `TIMESTAMP` column in an Avro table could encounter a serious issue.

Bug: [IMPALA-828](#)

Workaround: Set the query option `DISABLE_CODEGEN=TRUE`

Statestore seems to send concurrent heartbeats to the same subscriber leading to repeated "Subscriber '*hostname*' is registering with statestore, ignoring update" messages

Impala nodes could produce repeated error messages after recovering from a communication error with the statestore service.

Bug: [IMPALA-809](#)

Join predicate incorrectly ignored

A join query could produce wrong results if multiple equality comparisons between the same tables referred to the same column.

Bug: [IMPALA-805](#)

Query result differing between Impala and Hive

Certain outer join queries could return wrong results. If one of the tables involved in the join was an inline view, some tests from the `WHERE` clauses could be applied to the wrong phase of the query.

ArrayIndexOutOfBoundsException / Invalid query handle when reading large HBase cell

An HBase cell could contain a value larger than 32 KB, leading to a serious error when Impala queries that table. The error could occur even if the applicable row is not part of the result set.

Bug: [IMPALA-715](#)

Workaround: Use smaller values in the HBase table, or exclude the column containing the large value from the result set.

select with distinct and full outer join, impalad coredump

A query involving a `DISTINCT` operator combined with a `FULL OUTER JOIN` could encounter a serious error.

Bug: [IMPALA-735](#)

Workaround: Set the query option `DISABLE_CODEGEN=TRUE`

Impala cannot load tables with more than Short.MAX_VALUE number of partitions

If a table had more than 32,767 partitions, Impala would not recognize the partitions above the 32K limit and query results could be incomplete.

Bug: [IMPALA-749](#)

Various issues with HBase row key specification

Queries against HBase tables could fail with an error if the row key was compared to a function return value rather than a string constant. Also, queries against HBase tables could fail if the `WHERE` clause contained combinations of comparisons that could not possibly match any row key.

Resolution: Queries now return appropriate results when function calls are used in the row key comparison. For queries involving non-existent row keys, such as `WHERE row_key IS NULL` or where the lower bound is greater than the upper bound, the query succeeds and returns an empty result set.

Issues Fixed in the 1.2.3 Release

This release is a fix release that supercedes Impala 1.2.2, with the same features and fixes as 1.2.2 plus one additional fix for compatibility with Parquet files generated outside of Impala by components such as Hive, Pig, or MapReduce.

Impala cannot read Parquet files with multiple row groups

The `parquet-mr` library included with CDH4.5 writes files that are not readable by Impala, due to the presence of multiple row groups. Queries involving these data files might result in a crash or a failure with an error such as “Column chunk should not contain two dictionary pages”.

This issue does not occur for Parquet files produced by Impala `INSERT` statements, because Impala only produces files with a single row group.

Bug: [IMPALA-720](#)

Issues Fixed in the 1.2.2 Release

This section lists the most significant issues fixed in Impala 1.2.2. For the full list of fixed issues, see [this report in the JIRA system](#).

Order of table references in FROM clause is critical for optimal performance

Impala does not currently optimize the join order of queries; instead, it joins tables in the order in which they are listed in the `FROM` clause. Queries that contain one or more large tables on the right hand side of joins (either an explicit join expressed as a `JOIN` statement or a join implicit in the list of table references in the `FROM` clause) may run slowly or crash Impala due to out-of-memory errors. For example:

```
SELECT ... FROM small_table JOIN large_table
```

Anticipated Resolution: Fixed in Impala 1.2.2.

Workaround: In Impala 1.2.2 and higher, use the `COMPUTE STATS` statement to gather statistics for each table involved in the join query, after data is loaded. Prior to Impala 1.2.2, modify the query, if possible, to join the largest table first. For example:

```
SELECT ... FROM small_table JOIN large_table
```

should be modified to:

```
SELECT ... FROM large_table JOIN small_table
```

Parquet in CDH4.5 writes data files that are sometimes unreadable by Impala

Some Parquet files could be generated by other components that Impala could not read.

Bug: [IMPALA-694](#)

Resolution: The underlying issue is being addressed by a fix in the CDH Parquet libraries. Impala 1.2.2 works around the problem and reads the existing data files.

Deadlock in statestore when unregistering a subscriber and building a topic update

The statestore service could experience an internal error leading to a hang.

Bug: [IMPALA-699](#)

IllegalStateException when doing a union involving a group by

A UNION query where one side involved a GROUP BY operation could cause a serious error.

Bug: [IMPALA-687](#)

Impala Parquet Writer hit DCHECK in RleEncoder

A serious error could occur when doing an INSERT into a Parquet table.

Bug: [IMPALA-689](#)

Hive UDF jars cannot be loaded by the FE

If the JAR file for a Java-based Hive UDF was not in the CLASSPATH, the UDF could not be called during a query.

Bug: [IMPALA-695](#)

Issues Fixed in the 1.2.1 Release

This section lists the most significant issues fixed in Impala 1.2.1. For the full list of fixed issues, see [this report in the JIRA system](#).

Scanners use too much memory when reading past scan range

While querying a table with long column values, Impala could over-allocate memory leading to an out-of-memory error. This problem was observed most frequently with tables using uncompressed RCFile or text data files.

Bug: [IMPALA-525](#)

Resolution: Fixed in 1.2.1

Join node consumes memory way beyond mem-limit

A join query could allocate a temporary work area that was larger than needed, leading to an out-of-memory error. The fix makes Impala return unused memory to the system when the memory limit is reached, avoiding unnecessary memory errors.

Bug: [IMPALA-657](#)

Resolution: Fixed in 1.2.1

Excessive memory consumption when query tables with 1k columns (Parquet file)

Impala could encounter an out-of-memory condition setting up work areas for Parquet tables with many columns. The fix reduces the size of the allocated memory when not actually needed to hold table data.

Bug: [IMPALA-652](#)

Resolution: Fixed in 1.2.1

Issues Fixed in the 1.2.0 Beta Release

This section lists the most significant issues fixed in Impala 1.2 (beta). For the full list of fixed issues, see [this report in the JIRA system](#).

Issues Fixed in the 1.1.1 Release

This section lists the most significant issues fixed in Impala 1.1.1. For the full list of fixed issues, see [this report in the JIRA system](#).

Unexpected LLVM Crash When Querying Doubles on CentOS 5.x

Certain queries involving `DOUBLE` columns could fail with a serious error. The fix improves the generation of native machine instructions for certain chipsets.

Bug: [IMPALA-477](#)

"block size is too big" error with Snappy-compressed RCFile containing null

Queries could fail with a "block size is too big" error, due to `NULL` values in RCFile tables using Snappy compression.

Bug: [IMPALA-482](#)

Cannot query RC file for table that has more columns than the data file

Queries could fail if an Impala RCFile table was defined with more columns than in the corresponding RCFile data files.

Bug: [IMPALA-510](#)

Views Sometimes Not Utilizing Partition Pruning

Certain combinations of clauses in a view definition for a partitioned table could result in inefficient performance and incorrect results.

Bug: [IMPALA-495](#)

Update the serde name we write into the metastore for Parquet tables

The SerDes class string written into Parquet data files created by Impala was updated for compatibility with Parquet support in Hive. See [Incompatible Changes Introduced in Impala 1.1.1](#) on page 696 for the steps to update older Parquet data files for Hive compatibility.

Bug: [IMPALA-485](#)

Selective queries over large tables produce unnecessary memory consumption

A query returning a small result sets from a large table could tie up memory unnecessarily for the duration of the query.

Bug: [IMPALA-534](#)

Impala stopped to query AVRO tables

Queries against Avro tables could fail depending on whether the Avro schema URL was specified in the `TBLPROPERTIES` or `SERDEPROPERTIES` field. The fix causes Impala to check both fields for the schema URL.

Bug: [IMPALA-538](#)

Impala continues to allocate more memory even though it has exceed its mem-limit

Queries could allocate substantially more memory than specified in the `impalad -mem_limit` startup option. The fix causes more frequent checking of the limit during query execution.

Bug: [IMPALA-520](#)

Issues Fixed in the 1.1.0 Release

This section lists the most significant issues fixed in Impala 1.1. For the full list of fixed issues, see [this report in the JIRA system](#).

10-20% perf regression for most queries across all table formats

This issue is due to a performance tradeoff between systems running many queries concurrently, and systems running a single query. Systems running only a single query could experience lower performance than in early beta releases. Systems running many queries simultaneously should experience higher performance than in the beta releases.

planner fails with "Join requires at least one equality predicate between the two tables" when "from" table order does not match "where" join order

A query could fail if it involved 3 or more tables and the last join table was specified as a subquery.

Bug: [IMPALA-85](#)

Parquet writer uses excessive memory with partitions

INSERT statements against partitioned tables using the Parquet format could use excessive amounts of memory as the number of partitions grew large.

Bug: [IMPALA-257](#)

Comments in impala-shell in interactive mode are not handled properly causing syntax errors or wrong results

The `impala-shell` interpreter did not accept comment entered at the command line, making it problematic to copy and paste from scripts or other code examples.

Bug: [IMPALA-192](#)

Cancelled queries sometimes aren't removed from the inflight query list

The Impala web UI would sometimes display a query as if it were still running, after the query was cancelled.

Bug: [IMPALA-364](#)

Impala's 1.0.1 Shell Broke Python 2.4 Compatibility (AttributeError: 'module' object has no attribute 'field_size_limit')

The `impala-shell` command in Impala 1.0.1 does not work with Python 2.4, which is the default on Red Hat 5.

For the `impala-shell` command in Impala 1.0, the `-o` option (pipe output to a file) does not work with Python 2.4.

Bug: [IMPALA-396](#)

Issues Fixed in the 1.0.1 Release

This section lists the most significant issues fixed in Impala 1.0.1. For the full list of fixed issues, see [this report in the JIRA system](#).

Impala parquet scanner cannot read all data files generated by other frameworks

Impala might issue an erroneous error message when processing a Parquet data file produced by a non-Impala Hadoop component.

Bug: [IMPALA-333](#)

Resolution: Fixed

Impala is unable to query RCFile tables which describe fewer columns than the file's header.

If an RCFile table definition had fewer columns than the fields actually in the data files, queries would fail.

Bug: [IMPALA-293](#)

Resolution: Fixed

Impala does not correctly substitute `_HOST` with hostname in `--principal`

The `_HOST` placeholder in the `--principal` startup option was not substituted with the correct hostname, potentially leading to a startup error in setups using Kerberos authentication.

Bug: [IMPALA-351](#)

Resolution: Fixed

HBase query missed the last region

A query for an HBase table could omit data from the last region.

Bug: [IMPALA-356](#)

Resolution: Fixed

Hbase region changes are not handled correctly

After a region in an HBase table was split or moved, an Impala query might return incomplete or out-of-date results.

Bug: [IMPALA-300](#)

Resolution: Fixed

Query state for successful create table is EXCEPTION

After a successful CREATE TABLE statement, the corresponding query state would be incorrectly reported as EXCEPTION.

Bug: [IMPALA-349](#)

Resolution: Fixed

Double check release of JNI-allocated byte-strings

Operations involving calls to the Java JNI subsystem (for example, queries on HBase tables) could allocate memory but not release it.

Bug: [IMPALA-358](#)

Resolution: Fixed

Impala returns 0 for bad time values in UNIX_TIMESTAMP, Hive returns NULL

Impala returns 0 for bad time values in UNIX_TIMESTAMP, Hive returns NULL.

Impala:

```
impala> select UNIX_TIMESTAMP('10:02:01') ;
impala> 0
```

Hive:

```
hive> select UNIX_TIMESTAMP('10:02:01') FROM tmp;
hive> NULL
```

Bug: [IMPALA-16](#)

Anticipated Resolution: Fixed

INSERT INTO TABLE SELECT <constant> does not work.

Insert INTO TABLE SELECT <constant> will not insert any data and may return an error.

Anticipated Resolution: Fixed

Issues Fixed in the 1.0 GA Release

Here are the major user-visible issues fixed in Impala 1.0. For a full list of fixed issues, see [this report in the public issue tracker](#).

Undeterministically receive "ERROR: unknown row batch destination..." and "ERROR: Invalid query handle" from impala shell when running union query

A query containing both UNION and LIMIT clauses could intermittently cause the `impalad` process to halt with a segmentation fault.

Bug: [IMPALA-183](#)

Resolution: Fixed

Insert with NULL partition keys results in SIGSEGV.

An INSERT statement specifying a NULL value for one of the partitioning columns could cause the `impalad` process to halt with a segmentation fault.

Bug: [IMPALA-190](#)

Resolution: Fixed

INSERT queries don't show completed profiles on the debug webpage

In the Impala web user interface, the profile page for an INSERT statement showed obsolete information for the statement once it was complete.

Bug: [IMPALA-217](#)

Resolution: Fixed

Impala HBase scan is very slow

Queries involving an HBase table could be slower than expected, due to excessive memory usage on the Impala nodes.

Bug: [IMPALA-231](#)

Resolution: Fixed

Add some library version validation logic to `impalad` when loading `impala-lzo` shared library

No validation was done to check that the `impala-lzo` shared library was compatible with the version of Impala, possibly leading to a crash when using LZO-compressed text files.

Bug: [IMPALA-234](#)

Resolution: Fixed

Workaround: Always upgrade the `impala-lzo` library at the same time as you upgrade Impala itself.

Problems inserting into tables with TIMESTAMP partition columns leading table metadata loading failures and failed dchecks

INSERT statements for tables partitioned on columns involving datetime types could appear to succeed, but cause errors for subsequent queries on those tables. The problem was especially serious if an improperly formatted timestamp value was specified for the partition key.

Bug: [IMPALA-238](#)

Resolution: Fixed

Ctrl-C sometimes interrupts shell in system call, rather than cancelling query

Pressing Ctrl-C in the `impala-shell` interpreter could sometimes display an error and return control to the shell, making it impossible to cancel the query.

Bug: [IMPALA-243](#)

Resolution: Fixed

Empty string partition value causes metastore update failure

Specifying an empty string or `NULL` for a partition key in an `INSERT` statement would fail.

Bug: [IMPALA-252](#)

Resolution: Fixed. The behavior for empty partition keys was made more compatible with the corresponding Hive behavior.

Round() does not output the right precision

The `round()` function did not always return the correct number of significant digits.

Bug: [IMPALA-266](#)

Resolution: Fixed

Cannot cast string literal to string

Casting from a string literal back to the same type would cause an “invalid type cast” error rather than leaving the original value unchanged.

Bug: [IMPALA-267](#)

Resolution: Fixed

Excessive mem usage for certain queries which are very selective

Some queries that returned very few rows experienced unnecessary memory usage.

Bug: [IMPALA-288](#)

Resolution: Fixed

HdfsScanNode crashes in UpdateCounters

A serious error could occur for relatively small and inexpensive queries.

Bug: [IMPALA-289](#)

Resolution: Fixed

Parquet performance issues on large dataset

Certain aggregation queries against Parquet tables were inefficient due to lower than required thread utilization.

Bug: [IMPALA-292](#)

Resolution: Fixed

impala not populating hive metadata correctly for create table

The Impala `CREATE TABLE` command did not fill in the `owner` and `tbl_type` columns in the Hive metastore database.

Bug: [IMPALA-295](#)

Resolution: Fixed. The metadata was made more Hive-compatible.

impala daemons die if statestore goes down

The `impalad` instances in a cluster could halt when the `statestore` process became unavailable.

Bug: [IMPALA-312](#)

Resolution: Fixed

Constant SELECT clauses do not work in subqueries

A subquery would fail if the `SELECT` statement inside it returned a constant value rather than querying a table.

Bug: [IMPALA-67](#)

Resolution: Fixed

Right outer Join includes NULLs as well and hence wrong result count

The result set from a right outer join query could include erroneous rows containing NULL values.

Bug: [IMPALA-90](#)

Resolution: Fixed

Parquet scanner hangs for some queries

The Parquet scanner non-deterministically hangs when executing some queries.

Bug: [IMPALA-204](#)

Resolution: Fixed

Issues Fixed in Version 0.7 of the Beta Release

Impala does not gracefully handle unsupported Hive table types (INDEX and VIEW tables)

When attempting to load metadata from an unsupported Hive table type (INDEX and VIEW tables), Impala fails with an unclear error message.

Bug: [IMPALA-167](#)

Resolution: Fixed in 0.7

DDL statements (CREATE/ALTER/DROP TABLE) are not supported in the Impala Beta Release

Resolution: Fixed in 0.7

Avro is not supported in the Impala Beta Release

Resolution: Fixed in 0.7

Workaround: None

Impala does not currently allow limiting the memory consumption of a single query

It is currently not possible to limit the memory consumption of a single query. All tables on the right hand side of JOIN statements need to be able to fit in memory. If they do not, Impala may crash due to out of memory errors.

Resolution: Fixed in 0.7

Aggregate of a subquery result set returns wrong results if the subquery contains a 'limit' and data is distributed across multiple nodes

Aggregate of a subquery result set returns wrong results if the subquery contains a 'limit' clause and data is distributed across multiple nodes. From the query plan, it looks like we are just summing the results from each worker node.

Bug: [IMPALA-20](#)

Resolution: Fixed in 0.7

Partition pruning for arbitrary predicates that are fully bound by a particular partition column

We currently cannot utilize a predicate like "country_code in ('DE', 'FR', 'US')" to do partitioning pruning, because that requires an equality predicate or a binary comparison.

We should create a superclass of `planner.ValueRange`, `ValueSet`, that can be constructed with an arbitrary predicate, and whose `isInRange(analyzer, valueExpr)` constructs a literal predicate by substitution of the `valueExpr` into the predicate.

Bug: [IMPALA-144](#)

Resolution: Fixed in 0.7

Issues Fixed in Version 0.6 of the Beta Release

Impala reads the NameNode address and port as command line parameters

Impala reads the NameNode address and port as command line parameters rather than reading them from `core-site.xml`. Updating the NameNode address in the `core-site.xml` file does not propagate to Impala.

Severity: Low

Resolution: Fixed in 0.6 - Impala reads the namenode location and port from the Hadoop configuration files, though setting `-nn` and `-nn_port` overrides this. Users are advised not to set `-nn` or `-nn_port`.

Queries may fail on secure environment due to `impalad` Kerberos ticket expiration

Queries may fail on secure environment due to `impalad` Kerberos tickets expiring. This can happen if the Impala `-kerberos_reinit_interval` flag is set to a value ten minutes or less. This may lead to an `impalad` requesting a ticket with a lifetime that is less than the time to the next ticket renewal.

Bug: [IMPALA-64](#)

Resolution: Fixed in 0.6

Concurrent queries may fail when Impala uses Thrift to communicate with the Hive Metastore

Concurrent queries may fail when Impala is using Thrift to communicate with part of the Hive Metastore such as the Hive Metastore Service. In such a case, the error `get_fields failed: out of sequence response` may occur because Impala shared a single Hive Metastore Client connection across threads. With Impala 0.6, a separate connection is used for each metadata request.

Bug: [IMPALA-48](#)

Resolution: Fixed in 0.6

`impalad` fails to start if unable to connect to the Hive Metastore

Impala fails to start if it is unable to establish a connection with the Hive Metastore. This behavior was fixed, allowing Impala to start, even when no Metastore is available.

Bug: [IMPALA-58](#)

Resolution: Fixed in 0.6

Impala treats database names as case-sensitive in some contexts

In some queries (including "USE database" statements), database names are treated as case-sensitive. This may lead queries to fail with an `IllegalStateException`.

Bug: [IMPALA-44](#)

Resolution: Fixed in 0.6

Impala does not ignore hidden HDFS files

Impala does not ignore hidden HDFS files, meaning those files prefixed with a period `'.'` or underscore `'_'`. This diverges from Hive/MapReduce, which skips these files.

Bug: [IMPALA-18](#)

Resolution: Fixed in 0.6

Issues Fixed in Version 0.5 of the Beta Release

Impala may have reduced performance on tables that contain a large number of partitions

Impala may have reduced performance on tables that contain a large number of partitions. This is due to extra overhead reading/parsing the partition metadata.

Resolution: Fixed in 0.5

Backend client connections not getting cached causes an observable latency in secure clusters

Backend impalads do not cache connections to the coordinator. On a secure cluster, this introduces a latency proportional to the number of backend clients involved in query execution, as the cost of establishing a secure connection is much higher than in the non-secure case.

Bug: [IMPALA-38](#)

Resolution: Fixed in 0.5

Concurrent queries may fail with error: "Table object has not been initialised : `PARTITIONS`"

Concurrent queries may fail with error: "Table object has not been initialised : `PARTITIONS`". This was due to a lack of locking in the Impala table/database metadata cache.

Bug: [IMPALA-30](#)

Resolution: Fixed in 0.5

UNIX_TIMESTAMP format behaviour deviates from Hive when format matches a prefix of the time value

The Impala UNIX_TIMESTAMP(val, format) operation compares the length of format and val and returns NULL if they do not match. Hive instead effectively truncates val to the length of the format parameter.

Bug: [IMPALA-15](#)

Resolution: Fixed in 0.5

Issues Fixed in Version 0.4 of the Beta Release

Impala fails to refresh the Hive metastore if a Hive temporary configuration file is removed

Impala is impacted by Hive bug [HIVE-3596](#) which may cause metastore refreshes to fail if a Hive temporary configuration file is deleted (normally located at /tmp/hive-`<user>`-`<tmp_number>`.xml). Additionally, the impala-shell will incorrectly report that the failed metadata refresh completed successfully.

Anticipated Resolution: To be fixed in a future release

Workaround: Restart the `impalad` service. Use the `impalad` log to check for metadata refresh errors.

`lpad/rpad` builtin functions is not correct.

The `lpad/rpad` builtin functions generate the wrong results.

Resolution: Fixed in 0.4

Files with `.gz` extension reported as 'not supported'

Compressed files with extensions incorrectly generate an exception.

Bug: [IMPALA-14](#)

Resolution: Fixed in 0.4

Queries with large limits would hang.

Some queries with large limits were hanging.

Resolution: Fixed in 0.4

Order by on a string column produces incorrect results if there are empty strings

Resolution: Fixed in 0.4

Issues Fixed in Version 0.3 of the Beta Release

All table loading errors show as unknown table

If Impala is unable to load the metadata for a table for any reason, a subsequent query referring to that table will return an `unknown table` error message, even if the table is known.

Resolution: Fixed in 0.3

A table that cannot be loaded will disappear from SHOW TABLES

After failing to load metadata for a table, Impala removes that table from the list of known tables returned in `SHOW TABLES`. Subsequent attempts to query the table returns 'unknown table', even if the metadata for that table is fixed.

Resolution: Fixed in 0.3

Impala cannot read from HBase tables that are not created as external tables in the hive metastore.

Attempting to select from these tables fails.

Resolution: Fixed in 0.3

Certain queries that contain OUTER JOINS may return incorrect results

Queries that contain OUTER JOINS may not return the correct results if there are predicates referencing any of the joined tables in the WHERE clause.

Resolution: Fixed in 0.3.

Issues Fixed in Version 0.2 of the Beta Release

Subqueries which contain aggregates cannot be joined with other tables or Impala may crash

Subqueries that contain an aggregate cannot be joined with another table or Impala may crash. For example:

```
SELECT * FROM (SELECT sum(col1) FROM some_table GROUP BY col1) t1 JOIN other_table ON (...);
```

Resolution: Fixed in 0.2

An insert with a limit that runs as more than one query fragment inserts more rows than the limit.

For example:

```
INSERT OVERWRITE TABLE test SELECT * FROM test2 LIMIT 1;
```

Resolution: Fixed in 0.2

Query with limit clause might fail.

For example:

```
SELECT * FROM test2 LIMIT 1;
```

Resolution: Fixed in 0.2

Files in unsupported compression formats are read as plain text.

Attempting to read such files does not generate a diagnostic.

Resolution: Fixed in 0.2

Impala server raises a null pointer exception when running an HBase query.

When querying an HBase table whose row-key is string type, the Impala server may raise a null pointer exception.

Resolution: Fixed in 0.2

Appendix: Apache License, Version 2.0

SPDX short identifier: Apache-2.0

Apache License
Version 2.0, January 2004
<http://www.apache.org/licenses/>

TERMS AND CONDITIONS FOR USE, REPRODUCTION, AND DISTRIBUTION

1. Definitions.

"License" shall mean the terms and conditions for use, reproduction, and distribution as defined by Sections 1 through 9 of this document.

"Licensor" shall mean the copyright owner or entity authorized by the copyright owner that is granting the License.

"Legal Entity" shall mean the union of the acting entity and all other entities that control, are controlled by, or are under common control with that entity. For the purposes of this definition, "control" means (i) the power, direct or indirect, to cause the direction or management of such entity, whether by contract or otherwise, or (ii) ownership of fifty percent (50%) or more of the outstanding shares, or (iii) beneficial ownership of such entity.

"You" (or "Your") shall mean an individual or Legal Entity exercising permissions granted by this License.

"Source" form shall mean the preferred form for making modifications, including but not limited to software source code, documentation source, and configuration files.

"Object" form shall mean any form resulting from mechanical transformation or translation of a Source form, including but not limited to compiled object code, generated documentation, and conversions to other media types.

"Work" shall mean the work of authorship, whether in Source or Object form, made available under the License, as indicated by a copyright notice that is included in or attached to the work (an example is provided in the Appendix below).

"Derivative Works" shall mean any work, whether in Source or Object form, that is based on (or derived from) the Work and for which the editorial revisions, annotations, elaborations, or other modifications represent, as a whole, an original work of authorship. For the purposes of this License, Derivative Works shall not include works that remain separable from, or merely link (or bind by name) to the interfaces of, the Work and Derivative Works thereof.

"Contribution" shall mean any work of authorship, including the original version of the Work and any modifications or additions to that Work or Derivative Works thereof, that is intentionally submitted to Licensor for inclusion in the Work by the copyright owner or by an individual or Legal Entity authorized to submit on behalf of the copyright owner. For the purposes of this definition, "submitted" means any form of electronic, verbal, or written communication sent to the Licensor or its representatives, including but not limited to communication on electronic mailing lists, source code control systems, and issue tracking systems that are managed by, or on behalf of, the Licensor for the purpose of discussing and improving the Work, but excluding communication that is conspicuously marked or otherwise designated in writing by the copyright owner as "Not a Contribution."

"Contributor" shall mean Licensor and any individual or Legal Entity on behalf of whom a Contribution has been received by Licensor and subsequently incorporated within the Work.

2. Grant of Copyright License.

Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable copyright license to reproduce, prepare Derivative Works of, publicly display, publicly perform, sublicense, and distribute the Work and such Derivative Works in Source or Object form.

3. Grant of Patent License.

Subject to the terms and conditions of this License, each Contributor hereby grants to You a perpetual, worldwide, non-exclusive, no-charge, royalty-free, irrevocable (except as stated in this section) patent license to make, have made, use, offer to sell, sell, import, and otherwise transfer the Work, where such license applies only to those patent claims

licensable by such Contributor that are necessarily infringed by their Contribution(s) alone or by combination of their Contribution(s) with the Work to which such Contribution(s) was submitted. If You institute patent litigation against any entity (including a cross-claim or counterclaim in a lawsuit) alleging that the Work or a Contribution incorporated within the Work constitutes direct or contributory patent infringement, then any patent licenses granted to You under this License for that Work shall terminate as of the date such litigation is filed.

4. Redistribution.

You may reproduce and distribute copies of the Work or Derivative Works thereof in any medium, with or without modifications, and in Source or Object form, provided that You meet the following conditions:

1. You must give any other recipients of the Work or Derivative Works a copy of this License; and
2. You must cause any modified files to carry prominent notices stating that You changed the files; and
3. You must retain, in the Source form of any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form of the Work, excluding those notices that do not pertain to any part of the Derivative Works; and
4. If the Work includes a "NOTICE" text file as part of its distribution, then any Derivative Works that You distribute must include a readable copy of the attribution notices contained within such NOTICE file, excluding those notices that do not pertain to any part of the Derivative Works, in at least one of the following places: within a NOTICE text file distributed as part of the Derivative Works; within the Source form or documentation, if provided along with the Derivative Works; or, within a display generated by the Derivative Works, if and wherever such third-party notices normally appear. The contents of the NOTICE file are for informational purposes only and do not modify the License. You may add Your own attribution notices within Derivative Works that You distribute, alongside or as an addendum to the NOTICE text from the Work, provided that such additional attribution notices cannot be construed as modifying the License.

You may add Your own copyright statement to Your modifications and may provide additional or different license terms and conditions for use, reproduction, or distribution of Your modifications, or for any such Derivative Works as a whole, provided Your use, reproduction, and distribution of the Work otherwise complies with the conditions stated in this License.

5. Submission of Contributions.

Unless You explicitly state otherwise, any Contribution intentionally submitted for inclusion in the Work by You to the Licensor shall be under the terms and conditions of this License, without any additional terms or conditions. Notwithstanding the above, nothing herein shall supersede or modify the terms of any separate license agreement you may have executed with Licensor regarding such Contributions.

6. Trademarks.

This License does not grant permission to use the trade names, trademarks, service marks, or product names of the Licensor, except as required for reasonable and customary use in describing the origin of the Work and reproducing the content of the NOTICE file.

7. Disclaimer of Warranty.

Unless required by applicable law or agreed to in writing, Licensor provides the Work (and each Contributor provides its Contributions) on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied, including, without limitation, any warranties or conditions of TITLE, NON-INFRINGEMENT, MERCHANTABILITY, or FITNESS FOR A PARTICULAR PURPOSE. You are solely responsible for determining the appropriateness of using or redistributing the Work and assume any risks associated with Your exercise of permissions under this License.

8. Limitation of Liability.

In no event and under no legal theory, whether in tort (including negligence), contract, or otherwise, unless required by applicable law (such as deliberate and grossly negligent acts) or agreed to in writing, shall any Contributor be liable to You for damages, including any direct, indirect, special, incidental, or consequential damages of any character arising as a result of this License or out of the use or inability to use the Work (including but not limited to damages for loss of goodwill, work stoppage, computer failure or malfunction, or any and all other commercial damages or losses), even if such Contributor has been advised of the possibility of such damages.

9. Accepting Warranty or Additional Liability.

Appendix: Apache License, Version 2.0

While redistributing the Work or Derivative Works thereof, You may choose to offer, and charge a fee for, acceptance of support, warranty, indemnity, or other liability obligations and/or rights consistent with this License. However, in accepting such obligations, You may act only on Your own behalf and on Your sole responsibility, not on behalf of any other Contributor, and only if You agree to indemnify, defend, and hold each Contributor harmless for any liability incurred by, or claims asserted against, such Contributor by reason of your accepting any such warranty or additional liability.

END OF TERMS AND CONDITIONS

APPENDIX: How to apply the Apache License to your work

To apply the Apache License to your work, attach the following boilerplate notice, with the fields enclosed by brackets "[]" replaced with your own identifying information. (Don't include the brackets!) The text should be enclosed in the appropriate comment syntax for the file format. We also recommend that a file or class name and description of purpose be included on the same "printed page" as the copyright notice for easier identification within third-party archives.

```
Copyright [yyyy] [name of copyright owner]

Licensed under the Apache License, Version 2.0 (the "License");
you may not use this file except in compliance with the License.
You may obtain a copy of the License at

    http://www.apache.org/licenses/LICENSE-2.0

Unless required by applicable law or agreed to in writing, software
distributed under the License is distributed on an "AS IS" BASIS,
WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied.
See the License for the specific language governing permissions and
limitations under the License.
```