

# Cloudera JDBC Driver for Apache Hive Version 2.5.12



## Important Notice

© 2010-2015 Cloudera, Inc. All rights reserved.

Cloudera, the Cloudera logo, Cloudera Impala, Impala, and any other product or service names or slogans contained in this document, except as otherwise disclaimed, are trademarks of Cloudera and its suppliers or licensors, and may not be copied, imitated or used, in whole or in part, without the prior written permission of Cloudera or the applicable trademark holder.

Hadoop and the Hadoop elephant logo are trademarks of the Apache Software Foundation. All other trademarks, registered trademarks, product names and company names or logos mentioned in this document are the property of their respective owners. Reference to any products, services, processes or other information, by trade name, trademark, manufacturer, supplier or otherwise does not constitute or imply endorsement, sponsorship or recommendation thereof by us.

Complying with all applicable copyright laws is the responsibility of the user. Without limiting the rights under copyright, no part of this document may be reproduced, stored in or introduced into a retrieval system, or transmitted in any form or by any means (electronic, mechanical, photocopying, recording, or otherwise), or for any purpose, without the express written permission of Cloudera.

Cloudera may have patents, patent applications, trademarks, copyrights, or other intellectual property rights covering subject matter in this document. Except as expressly provided in any written license agreement from Cloudera, the furnishing of this document does not give you any license to these patents, trademarks copyrights, or other intellectual property.

The information in this document is subject to change without notice. Cloudera shall not be liable for any damages resulting from technical errors or omissions which may be present in this document, or from use of this document.

**Cloudera, Inc.**  
**1001 Page Mill Road, Building 2**  
**Palo Alto, CA 94304-1008**  
[info@cloudera.com](mailto:info@cloudera.com)  
**US: 1-888-789-1488**  
**Intl: 1-650-843-0595**  
[www.cloudera.com](http://www.cloudera.com)

## Release Information

Version: 2.5.12

Date: May 6, 2015

## Table of Contents

<b>INTRODUCTION</b> .....	<b>5</b>
<b>SYSTEM REQUIREMENTS</b> .....	<b>5</b>
<b>CLOUDERA JDBC DRIVER FOR APACHE HIVE FILES</b> .....	<b>6</b>
<b>USING THE CLOUDERA JDBC DRIVER FOR APACHE HIVE</b> .....	<b>7</b>
SETTING THE CLASS PATH .....	7
INITIALIZING THE DRIVER CLASS .....	8
BUILDING THE CONNECTION URL .....	8
<b>JAVA SAMPLE CODE</b> .....	<b>9</b>
<b>CONFIGURING AUTHENTICATION</b> .....	<b>13</b>
USING NO AUTHENTICATION .....	14
USING KERBEROS .....	14
USING USER NAME .....	14
USING USER NAME AND PASSWORD .....	15
<b>CONFIGURING SSL</b> .....	<b>15</b>
<b>FEATURES</b> .....	<b>16</b>
SQL QUERY VERSUS HIVEQL QUERY .....	16
DATA TYPES .....	16
CATALOG AND SCHEMA SUPPORT .....	17
INTERFACES AND SUPPORTED METHODS .....	18
<b>CONTACT Us</b> .....	<b>74</b>
<b>APPENDIX A AUTHENTICATION OPTIONS</b> .....	<b>75</b>
USING NO AUTHENTICATION .....	76
USING KERBEROS .....	76
USING USER NAME .....	76
USING USER NAME AND PASSWORD .....	76
<b>APPENDIX B CONFIGURING KERBEROS AUTHENTICATION FOR WINDOWS</b> .....	<b>77</b>
DOWNLOADING AND INSTALLING MIT KERBEROS FOR WINDOWS .....	77
USING THE MIT KERBEROS TICKET MANAGER TO GET TICKETS .....	77
USING THE DRIVER TO GET TICKETS .....	78
USING AN EXISTING SUBJECT TO AUTHENTICATE THE CONNECTION .....	79
<b>APPENDIX C DRIVER CONFIGURATION OPTIONS</b> .....	<b>82</b>
ALLOWSELFsignedCERTS .....	82
AUTHMECH .....	82
CAISSUEDCERTNAMESMISMATCH .....	82
CATALOGSCHEMASWITCH .....	83

DECIMALCOLUMNSCALE .....	83
DEFAULTSTRINGCOLUMNLENGTH .....	83
DELEGATIONUID .....	84
KRBHOSTFQDN .....	84
KRBREALM .....	84
KRBSERVICENAME .....	85
PREPAREDMETALIMITZERO .....	85
PWD .....	85
ROWSFETCHEDPERBLOCK .....	85
SOCKETTIMEOUT .....	86
SSL .....	86
SSLKEYSTORE .....	86
SSLKEYSTOREPWD .....	87
SSLTRUSTSTORE .....	87
SSLTRUSTSTOREPWD .....	87
UID .....	88
USENATIVEQUERY .....	88
ZK .....	88

## Introduction

The Cloudera JDBC Driver for Apache Hive is used for direct SQL and HiveQL access to Apache Hadoop / Hive distributions, enabling Business Intelligence (BI), analytics, and reporting on Hadoop / Hive-based data. The driver efficiently transforms an application's SQL query into the equivalent form in HiveQL, which is a subset of SQL-92. If an application is Hive-aware, then the driver is configurable to pass the query through to the database for processing. The driver interrogates Hive to obtain schema information to present to a SQL-based application. Queries, including joins, are translated from SQL to HiveQL. For more information about the differences between HiveQL and SQL, see "Features" on page 16.

The Cloudera JDBC Driver for Apache Hive complies with the JDBC 3.0, 4.0 and 4.1 data standards. JDBC is one of the most established and widely supported APIs for connecting to and working with databases. At the heart of the technology is the JDBC driver, which connects an application to the database. For more information about JDBC, see <http://www.simba.com/resources/data-access-standards-library>.

This guide is suitable for users who want to access data residing within Hive from their desktop environment. Application developers may also find the information helpful. Refer to your application for details on connecting via JDBC.

## System Requirements

Each computer where you use the Cloudera JDBC Driver for Apache Hive must have Java Runtime Environment (JRE) installed. The version of JRE that must be installed depends on the version of the JDBC API you are using with the driver. Table 1 lists the required version of JRE for each version of the JDBC API.

**Table 1. Cloudera JDBC Driver for Apache Hive System Requirements**

JDBC API Version	JRE Version
3.0	4.0 or 5.0
4.0	6.0 or later
4.1	7.0 or later

The Cloudera JDBC Driver for Apache Hive supports Hive Server 1 and Hive Server 2, and is tested using Hive 0.10, 0.11, 0.12, 0.13, and 0.14.

## Cloudera JDBC Driver for Apache Hive Files

The Cloudera JDBC Driver for Apache Hive is delivered in the following ZIP archives, where *version* is the version number of the driver:

- Cloudera\_HiveJDBC3\_*version*.zip
- Cloudera\_HiveJDBC4\_*version*.zip
- Cloudera\_HiveJDBC41\_*version*.zip

Each archive contains the driver supporting the JDBC API version indicated in the archive name.

The Cloudera\_HiveJDBC3\_*version*.zip archive contains the following file and folder structure:

- HiveJDBC3
  - hive\_metastore.jar
  - hive\_service.jar
  - HiveJDBC3.jar
  - libfb303-0.9.0.jar
  - libthrift-0.9.0.jar
  - log4j-1.2.14.jar
  - ql.jar
  - slf4j-api-1.5.11.jar
  - slf4j-log4j12-1.5.11.jar
  - TCLIServiceClient.jar
  - zookeeper-3.4.6.jar

The Cloudera\_HiveJDBC4\_*version*.zip archive contains the following file and folder structure:

- HiveJDBC4
  - hive\_metastore.jar
  - hive\_service.jar
  - HiveJDBC4.jar
  - libfb303-0.9.0.jar
  - libthrift-0.9.0.jar
  - log4j-1.2.14.jar
  - ql.jar
  - slf4j-api-1.5.11.jar
  - slf4j-log4j12-1.5.11.jar
  - TCLIServiceClient.jar
  - zookeeper-3.4.6.jar

The Cloudera\_HiveJDBC41\_*version*.zip archive contains the following file and folder structure:

- HiveJDBC41
  - hive\_metastore.jar
  - hive\_service.jar
  - HiveJDBC41.jar
  - libfb303-0.9.0.jar
  - libthrift-0.9.0.jar
  - log4j-1.2.14.jar
  - ql.jar
  - slf4j-api-1.5.11.jar
  - slf4j-log4j12-1.5.11.jar
  - TCLIServiceClient.jar
  - zookeeper-3.4.6.jar

## Using the Cloudera JDBC Driver for Apache Hive

To access a Hive data warehouse using the Cloudera JDBC Driver for Apache Hive, you need to set the following:

- Class path
- Driver class
- Connection URL

For sample code that demonstrates how to use the driver, see "Java Sample Code" on page 9.

### Important:

The Cloudera JDBC Driver for Apache Hive is a forward-only, read-only driver with no transaction support. Because the driver does not support transactions, auto-commit is always set to **true**

## Setting the Class Path

To use the Cloudera JDBC Driver for Apache Hive, you must set the class path to include all the JAR files from the ZIP archive containing the driver that you are using.

The class path is the path that the Java Runtime Environment searches for classes and other resource files. For more information, see the topic *Setting the Class Path* in the Java SE Documentation at

<http://docs.oracle.com/javase/7/docs/technotes/tools/windows/classpath.html>.

## Initializing the Driver Class

Before connecting to the Hive server, initialize the appropriate class for the Hive server instance and your application.

The following is a list of the classes used to connect the Cloudera JDBC Driver for Apache Hive to Hive Server 1 and Hive Server 2 instances. The Driver classes extend `java.sql.Driver`, and the DataSource classes extend `javax.sql.DataSource` and `javax.sql.ConnectionPoolDataSource`

To support JDBC 3.0, classes with the following fully-qualified class names (FQCNs) are available:

- `com.cloudera.hive.jdbc3.HS1Driver`
- `com.cloudera.hive.jdbc3.HS2Driver`
- `com.cloudera.hive.jdbc3.HS1DataSource`
- `com.cloudera.hive.jdbc3.HS2DataSource`

To support JDBC 4.0, classes with the following FQCNs are available:

- `com.cloudera.hive.jdbc4.HS1Driver`
- `com.cloudera.hive.jdbc4.HS2Driver`
- `com.cloudera.hive.jdbc4.HS1DataSource`
- `com.cloudera.hive.jdbc4.HS2DataSource`

To support JDBC 4.1, classes with the following FQCNs are available:

- `com.cloudera.hive.jdbc41.HS1Driver`
- `com.cloudera.hive.jdbc41.HS2Driver`
- `com.cloudera.hive.jdbc41.HS1DataSource`
- `com.cloudera.hive.jdbc41.HS2DataSource`

## Building the Connection URL

Use the connection URL to supply connection information to the data source that you are accessing. The connection URL for the Cloudera JDBC Driver for Apache Hive takes the following form:

```
jdbc:Subprotocol://Host:Port  
[/Schema];Property1=Value;Property2=Value;...
```

The placeholders in the connection URL are defined as follows:

- *Subprotocol* is the value **hive** if you are connecting to a Hive Server 1 instance. If you are connecting to a Hive Server 2 instance, then use the value **hive2**
- *Host* is the DNS or IP address of the server hosting the Hive data warehouse.
- *Port* is the port to connect to on *Host*.
- *Schema* is the name of the schema/database you want to access. Specifying a schema is optional. If you do not specify a schema, then the schema named **default** is used.



**Note:**

You can still issue queries on other schemas by explicitly specifying the schema in the query. To inspect your databases and determine the appropriate schema to use, type the **show databases** command at the Hive command prompt.

- *Property* is any one of the connection properties that you can specify. For information about the properties available in the driver, see "Driver Configuration Options" on page 82.

**Important:**

Properties are case-sensitive. Do not duplicate properties in the connection URL.

If a connection property key does not match any of the connection properties specified in "Driver Configuration Options" on page 82, then the driver will attempt to apply the property as a Hive server-side property for the client session.

For example, to connect to a Hive Server 2 instance installed on the local computer and authenticate the connection using a user name and password, you would use the following connection URL:

```
jdbc:hive2://localhost:10000;AuthMech=3;UID=UserName;PWD=Password
```

*UserName* and *Password* specify credentials for an existing user on the host running Hive Server 2.

**Note:**

If you use Hive Server 2 (**hive2**) and no parameters are specified, the UID will default to **hive** and AuthMech will default to **2**.

For more information about the properties that you can use in the connection URL, see "Driver Configuration Options" on page 82.

## Java Sample Code

The following Java code provides an example demonstrating how to use the JDBC API to do the following:

- Register the Cloudera JDBC Driver for Apache Hive
- Establish a connection to a Hive database
- Query the database
- Parse a result set
- Handle exceptions
- Clean up to avoid memory leakage

**Important:**

To use the Cloudera JDBC Driver for Apache Hive in an application, you must include all the JAR files from the ZIP archive in the class path for your Java project.

```
// java.sql packages are required
import java.sql.*;
class ClouderaJDBCHiveExample {

    // Define a string as the fully qualified class name
    // (FQCN) of the desired JDBC driver
    static String JDBCdriver = "com.cloudera.hive.jdbc3.HS1Driver";
    // Define a string as the connection URL
    private static final String CONNECTION_URL =
        "jdbc:hive://192.168.1.1:10000";

    public static void main(String[] args) {

        Connection con = null;
        Statement stmt = null;
        ResultSet rs = null;

        // Define a plain query
        String query = "SELECT first_name, last_name, emp_id FROM
        default.emp";
        // Define a parametrized query
        String prepQuery = "SELECT first_name, last_name, emp_id
        FROM default.emp where store_id = ?";

        try {

            // Register the driver using the class name
            Class.forName(JDBC_DRIVER);

            // Establish a connection using the connection
            // URL
            con = DriverManager.getConnection(CONNECTION_URL);

            // Create a Statement object for sending SQL
```

```

// statements to the database
stmt = con.createStatement();

// Execute the SQL statement
rs = stmt.executeQuery(query);

// Display a header line for output appearing in
// the Console View
System.out.printf("%20s%20s%20s\r\n", "FIRST NAME",
"LAST NAME" , "EMPLOYEE ID");

// Step through each row in the result set
// returned from the database
while(rs.next()) {
    // Retrieve values from the row where the
    // cursor is currently positioned using
    // column names
    String FirstName = rs.getString("first_name");
    String LastName = rs.getString("last_name");
    String EmployeeID = rs.getString("emp_id");

    // Display values in columns 20 characters
    // wide in the Console View using the
    // Formatter
    System.out.printf("%20s%20s%20s\r\n", FirstName,
LastName, EmployeeID);
}
// Create a prepared statement
PreparedStatement prep = m_conn.prepareStatement
(preparedStatement);

// Bind the query parameter with a value
prep.setInt(1, 204);
// Execute the query
rs = prep.execute();
// Step through each row in the result set
// returned from the database
while(rs.next()) {

```

```

        // Retrieve values from the row where the
        // cursor is currently positioned using
        // column names
        String FirstName = rs.getString("first_name");
        String LastName = rs.getString("last_name");
        String EmployeeID = rs.getString("emp_id");

        // Display values in columns 20 characters
        // wide in the Console View using the
        // Formatter
        System.out.printf("%20s%20s%20s\r\n", FirstName,
            LastName, EmployeeID);
    }

} catch (SQLException se) {
    // Handle errors encountered during interaction
    // with the data source
} catch (Exception e) {
    // Handle other errors
} finally {
    // Perform clean up
    try {
        if (rs != null) {
            rs.close();
        }
    } catch (SQLException se1) {
        // Log this
    }

    try {
        if (stmt != null) {
            stmt.close();
        }
    } catch (SQLException se2) {
        // Log this
    }

    try {

```

```

        if (prep != null) {
            prep.close();
        }
    } catch (SQLException se3) {
        // Log this
    }

    try {
        if (con != null) {
            con.close();
        }
    } catch (SQLException se4) {
        // Log this
    } // End try
} // End try
} // End main
} // End ClouderaJDBCHiveExample

```

## Configuring Authentication

The Cloudera JDBC Driver for Apache Hive supports the following authentication mechanisms:

- No Authentication
- Kerberos
- User Name
- User Name and Password

You configure the authentication mechanism that the driver uses to connect to Hive by specifying the relevant properties in the connection URL.

For information about selecting an appropriate authentication mechanism when using the Cloudera JDBC Driver for Apache Hive, see "Authentication Options" on page 75.

For information about the properties you can use in the connection URL, see "Driver Configuration Options" on page 82.

**Note:**

In addition to authentication, you can configure the driver to connect over SSL. For more information, see "Configuring SSL" on page 15.

## Using No Authentication

**Note:**

When connecting to a Hive server of type Hive Server 1, you must use No Authentication.

**To configure a connection without authentication:**

- Set the AuthMech property to 0

For example:

```
jdbc:hive2://localhost:10000;AuthMech=0
```

## Using Kerberos

Kerberos must be installed and configured before you can use this authentication mechanism. For information about configuring and operating Kerberos on Windows, see "Configuring Kerberos Authentication for Windows" on page 77. For other operating systems, refer to the MIT Kerberos documentation.

**Note:**

This authentication mechanism is available only for Hive Server 2.

**To configure Kerberos authentication:**

1. Set the AuthMech property to 1
2. If your Kerberos setup does not define a default realm or if the realm of your Hive server is not the default, then set the KrbRealm property to the realm of the Hive server.

OR

To use the default realm defined in your Kerberos setup, do not set the KrbRealm property.

3. Set the KrbHostFQDN property to the fully qualified domain name of the Hive server host.
4. Set the KrbServiceName property to the service name of the Hive server.

For example:

```
jdbc:hive2://localhost:10000;AuthMech=1;KrbRealm=EXAMPLE.COM;  
KrbHostFQDN=hs2.example.com;KrbServiceName=hive
```

## Using User Name

This authentication mechanism requires a user name but does not require a password. The user name labels the session, facilitating database tracking.

**Note:**

This authentication mechanism is available only for Hive Server 2. Most default configurations of Hive Server 2 require User Name authentication.

**To configure User Name authentication:**

1. Set the AuthMech property to 2
2. Set the UID property to an appropriate user name for accessing the Hive server.

For example:

```
jdbc:hive2://localhost:10000;AuthMech=2;UID=hs2
```

**Using User Name and Password**

This authentication mechanism requires a user name and a password.

**Note:**

This authentication mechanism is available only for Hive Server 2.

**To configure User Name and Password authentication:**

1. Set the AuthMech property to 3
2. Set the UID property to an appropriate user name for accessing the Hive server.
3. Set the PWD property to the password corresponding to the user name you provided in step 2.

For example:

```
jdbc:hive2://localhost:10000;AuthMech=3;UID=hs2;PWD=*****
```

**Configuring SSL**

If you are connecting to a Hive server that has Secure Sockets Layer (SSL) enabled, then you can configure the driver to connect to an SSL-enabled socket.

SSL connections require a KeyStore and a TrustStore. You can create a TrustStore and configure the driver to use it, or allow the driver to use one of the default TrustStores. If you do not configure the driver to use a specific TrustStore, then the driver uses the Java TrustStore `jssecacerts`. If `jssecacerts` is not available, then the driver uses `cacerts` instead.

**To configure SSL:**

1. To create a KeyStore and configure the driver to use it, do the following:
  - a) Create a KeyStore containing your signed, trusted SSL certificate.
  - b) Set the `SSLKeyStore` property to the full path of the KeyStore, including the file name.
  - c) Set the `SSLKeyStorePwd` property to the password for the KeyStore.
2. Optionally, to create a TrustStore and configure the driver to use it, do the following:
  - a) Create a TrustStore containing your signed, trusted SSL certificate.
  - b) Set the `SSLTrustStore` property to the full path of the TrustStore, including the file name.

- c) Set the SSLTrustStorePwd property to the password for the TrustStore.
- 3. Set the SSL property to 1
- 4. Optionally, to allow the SSL certificate used by the server to be self-signed, set the AllowSelfSignedCerts property to 1
- 5. Optionally, to allow the common name of a CA-issued certificate to not match the host name of the Hive server, set the CAIssuedCertNamesMismatch property to 1

**Note:**

For self-signed certificates, the driver always allows the common name of the certificate to not match the host name.

For example:

```
jdbc:hive2://localhost:10000;AuthMech=3;SSL=1;
SSLKeyStore=C:\\Users\\bsmith\\Desktop\\keystore.jks;
SSLKeyStorePwd=*****;UID=hs2;PWD=*****
```

**Note:**

For more information about the connection properties used in SSL connections, see "Driver Configuration Options" on page 82

## Features

### SQL Query versus HiveQL Query

The native query language supported by Hive is HiveQL. HiveQL is a subset of SQL-92. However, the syntax is different enough that most applications do not work with native HiveQL.

### Data Types

The Cloudera JDBC Driver for Apache Hive supports many common data formats, converting between Hive, SQL, and Java data types.

Table 2 lists the supported data type mappings.

Table 2. Supported Data Types

Hive Type	SQL Type	Java Type
BIGINT	BIGINT	java.math.BigInteger
BINARY	VARBINARY	byte[]
BOOLEAN	BOOLEAN	Boolean
CHAR	CHAR	String



Hive Type	SQL Type	Java Type
(Available only in Hive 0.13.0 or later)		
DATE	DATE	java.sql.Date
DECIMAL (In Hive 0.13 and later, you can specify scale and precision when creating tables using the DECIMAL data type.)	DECIMAL	java.math.BigDecimal
DOUBLE	DOUBLE	Double
INT	INTEGER	Long
FLOAT	REAL	Float
SMALLINT	SMALLINT	Integer
TINYINT	TINYINT	Short
TIMESTAMP	TIMESTAMP	java.sql.Timestamp
VARCHAR (Available only in Hive 0.12.0 or later)	VARCHAR	String

The aggregate types (ARRAY, MAP, STRUCT, and UNIONTYPE) are not yet supported. Columns of aggregate types are treated as VARCHAR columns in SQL and STRING columns in Java.

## Catalog and Schema Support

The Cloudera JDBC Driver for Apache Hive supports both catalogs and schemas in order to make it easy for the driver to work with various JDBC applications. Since Hive only organizes tables into schemas/databases, the driver provides a synthetic catalog called “HIVE” under which all of the schemas/databases are organized. The driver also maps the JDBC schema to the Hive schema/database.

**Note:**

Setting the CatalogSchemaSwitch connection property to 1 will cause Hive catalogs to be treated as schemas in the driver as a restriction for filtering.

## Interfaces and Supported Methods

The Cloudera JDBC Driver for Apache Hive implements the following JDBC interfaces:

- "CallableStatement" on page 18
- "Connection" on page 28
- "DatabaseMetaData" on page 33
- "DataSource" on page 45
- "Driver" on page 46
- "ParameterMetaData" on page 47
- "PooledConnection" on page 48
- "PreparedStatement" on page 49
- "ResultSet" on page 54
- "ResultSetMetaData" on page 69
- "Statement" on page 70

However, the driver does not support every method from these interfaces. For information about whether a specific method is supported by the driver and which version of the JDBC API is the earliest version that supports the method, refer to the following sections.

The driver does **not** support the following JDBC features:

- Array
- Blob
- Clob
- Ref
- Savepoint
- SQLData
- SQLInput
- SQLOutput
- Struct

### CallableStatement

The CallableStatement interface extends the PreparedStatement interface.

Table 3 lists the methods that belong to the CallableStatement interface, and describes whether each method is supported by the Cloudera JDBC Driver for Apache Hive and which version of the JDBC API is the earliest version that supports the method.

For detailed information about each method in the CallableStatement interface, see the Java API documentation available at <http://docs.oracle.com/javase/1.5.0/docs/api/java/sql/CallableStatement.html>

**Table 3. Methods in the CallableStatement Class Interface**

Method	Supported Since JDBC Version	Supported by the Driver	Notes
Array <code>getArray(int i)</code>	3.0	No	
Array <code>getArray(String parameterName)</code>	3.0	No	
BigDecimal <code>getBigDecimal(int parameterIndex)</code>	3.0	Yes	
BigDecimal <code>getBigDecimal(int parameterIndex, int scale)</code>	3.0	Yes	Deprecated
BigDecimal <code>getBigDecimal(String parameterName)</code>	3.0	Yes	
Blob <code>getBlob(int i)</code>	3.0	No	
Blob <code>getBlob(String parameterName)</code>	3.0	No	
boolean <code>getBoolean(int parameterIndex)</code>	3.0	Yes	
boolean <code>getBoolean(String parameterName)</code>	3.0	Yes	
byte <code>getByte(int parameterIndex)</code>	3.0	Yes	
byte <code>getByte(String parameterName)</code>	3.0	Yes	
byte[] <code>getBytes(int parameterIndex)</code>	3.0	Yes	
byte[] <code>getBytes(String parameterName)</code>	3.0	Yes	
Clob <code>getClob(int i)</code>	3.0	No	
Clob <code>getClob(String</code>	3.0	No	

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
parameterName)			
Date getDate(int parameterIndex)	3.0	Yes	
Date getDate(int parameterIndex, Calendar cal)	3.0	Yes	
Date getDate(String parameterName)	3.0	Yes	
Date getDate(String parameterName, Calendar cal)	3.0	Yes	
double getDouble(int parameterIndex)	3.0	Yes	
double getDouble(String parameterName)	3.0	Yes	
float getFloat(int parameterIndex)	3.0	Yes	
float getFloat(String parameterName)	3.0	Yes	
int getInt(int parameterIndex)	3.0	Yes	
int getInt(String parameterName)	3.0	Yes	
long getLong(int parameterIndex)	3.0	Yes	
long getLong(String parameterName)	3.0	Yes	
Reader getNCharacterStream(int parameterIndex)	4.0	No	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
Reader getNCharacterStream (String parameterName)	4.0	No	
NClob getNClob(int parameterIndex)	4.0	No	
NClob getNClob(String parameterName)	4.0	No	
String getNString(int parameterIndex)	4.0	No	
String getNString(String parameterName)	4.0	No	
Object getObject(int parameterIndex)	3.0	Yes	
<T> T getObject(int parameterIndex, Class<T> type)	4.1	No	
Object getObject(int i, Map<String,Class<?>> map)	3.0	No	
Object getObject(String parameterName)	3.0	Yes	
<T> T getObject(String parameterName, Class<T> type)	4.1	No	
Object getObject(String parameterName, Map<String,Class<?>> map)	3.0	Yes	
Ref getRef(int i)	3.0	No	
Ref getRef(String parameterName)	3.0	No	

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
RowId getRowId(int parameterIndex)	4.0	No	
RowId getRowId(String parameterName)	4.0	No	
short getShort(int parameterIndex)	3.0	Yes	
short getShort(String parameterName)	3.0	Yes	
SQLXML getSQLXML(int parameterIndex)	4.0	No	
SQLXML getSQLXML(String parameterName)	4.0	No	
String getString(int parameterIndex)	3.0	Yes	
String getString(String parameterName)	3.0	Yes	
Time getTime(int parameterIndex)	3.0	Yes	
Time getTime(int parameterIndex, Calendar cal)	3.0	Yes	
Time getTime(String parameterName)	3.0	Yes	
Time getTime(String parameterName, Calendar cal)	3.0	Yes	
Timestamp getTimestamp(int parameterIndex)	3.0	Yes	
Timestamp getTimestamp(int parameterIndex,	3.0	Yes	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
Calendar cal)			
Timestamp getTimestamp (String parameterName)	3.0	Yes	
Timestamp getTimestamp (String parameterName, Calendar cal)	3.0	Yes	
URL getURL(int parameterIndex)	3.0	No	
URL getURL(String parameterName)	3.0	No	
void registerOutParameter(int parameterIndex, int sqlType)	3.0	Yes	
void registerOutParameter(int parameterIndex, int sqlType, int scale)	3.0	Yes	
void registerOutParameter(int paramIndex, int sqlType, String typeName)	3.0	Yes	
void registerOutParameter (String parameterName, int sqlType)	3.0	Yes	
void registerOutParameter (String parameterName, int sqlType, int scale)	3.0	Yes	
void registerOutParameter (String parameterName, int sqlType, String	3.0	Yes	

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
typeName)			
void setAsciiStream (String parameterName, InputStream x)	4.0	Yes	
void setAsciiStream (String parameterName, InputStream x, int length)	3.0	Yes	
void setAsciiStream (String parameterName, InputStream x, long length)	4.0	Yes	
void setBigDecimal (String parameterName, BigDecimal x)	3.0	Yes	
void setBinaryStream (String parameterName, InputStream x)	4.0	Yes	
setBinaryStream (String parameterName, InputStream x, int length)	3.0	Yes	
void setBinaryStream (String parameterName, InputStream x, long length)	4.0	Yes	
void setBlob (String parameterName, Blob x)	4.0	Yes	
void setBlob (String parameterName, InputStream inputStream)	4.0	Yes	
void setBlob (String parameterName, InputStream inputStream,	4.0	Yes	



Method	Supported Since JDBC Version	Supported by the Driver	Notes
long length)			
void setBoolean(String parameterName, boolean x)	3.0	Yes	
void setByte(String parameterName, byte x)	3.0	Yes	
void setBytes(String parameterName, byte[] x)	3.0	Yes	
void setCharacterStream(String parameterName, Reader reader)	4.0	Yes	
void setCharacterStream(String parameterName, Reader reader, int length)	3.0	Yes	
void setCharacterStream(String parameterName, Reader reader, long length)	4.0	Yes	
void setClob(String parameterName, Clob x)	4.0	Yes	
void setClob(String parameterName, Reader reader)	4.0	Yes	
void setClob(String parameterName, Reader reader, long length)	4.0	Yes	
void setDate(String parameterName, Date x)	3.0	Yes	
void setDate(String parameterName, Date x, Calendar cal)	3.0	Yes	

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>void setDouble(String parameterName, double x)</code>	3.0	Yes	
<code>void setFloat(String parameterName, float x)</code>	3.0	Yes	
<code>void setInt(String parameterName, int x)</code>	3.0	Yes	
<code>void setLong(String parameterName, long x)</code>	3.0	Yes	
<code>void setNCharacterStream(String parameterName, Reader value)</code>	4.0	Yes	
<code>void setNCharacterStream(String parameterName, Reader value, long length)</code>	4.0	Yes	
<code>void setNClob(String parameterName, NClob value)</code>	4.0	Yes	
<code>void setNClob(String parameterName, Reader reader)</code>	4.0	Yes	
<code>void setNClob(String parameterName, Reader reader, long length)</code>	4.0	Yes	
<code>void setNString(String parameterName, String value)</code>	4.0	Yes	
<code>void setNull(String parameterName, int sqlType)</code>	3.0	Yes	
<code>void setNull(String parameterName, int</code>	3.0	Yes	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>sqlType, String typeName)</code>			
<code>void setObject(String parameterName, Object x)</code>	3.0	Yes	
<code>void setObject(String parameterName, Object x, int targetSqlType)</code>	3.0	Yes	
<code>void setObject(String parameterName, Object x, int targetSqlType, int scale)</code>	3.0	Yes	
<code>void setRowId(String parameterName, RowId x)</code>	4.0	Yes	
<code>void setShort(String parameterName, short x)</code>	3.0	Yes	
<code>void setSQLXML(String parameterName, SQLXML xmlObject)</code>	4.0	Yes	
<code>void setString(String parameterName, String x)</code>	3.0	Yes	
<code>void setTime(String parameterName, Time x)</code>	3.0	Yes	
<code>void setTime(String parameterName, Time x, Calendar cal)</code>	3.0	Yes	
<code>void setTimestamp(String parameterName, Timestamp x)</code>	3.0	Yes	
<code>void setTimestamp(String parameterName, Timestamp x, Calendar cal)</code>	3.0	Yes	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>void setURL(String parameterName, URL val)</code>	3.0	Yes	
<code>boolean wasNull()</code>	3.0	Yes	
<code>boolean isWrapperFor(Class&lt;?&gt; iface)</code>	4.0	Yes	
<code>&lt;T&gt; T unwrap(Class&lt;T&gt; iface)</code>	4.0	Yes	

## Connection

Table 4 lists the methods that belong to the Connection interface, and describes whether each method is supported by the Cloudera JDBC Driver for Apache Hive and which version of the JDBC API is the earliest version that supports the method.

For detailed information about each method in the Connection interface, see the Java API documentation available at

<http://docs.oracle.com/javase/1.5.0/docs/api/java/sql/Connection.html>

Table 4. Methods in the Connection Interface

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>void clearWarnings()</code>	3.0	Yes	
<code>void close()</code>	3.0	Yes	
<code>void commit()</code>	3.0	Yes	Auto-commit cannot be set to false because it is hard-coded as true
<code>Array createArrayOf(String typeName, Object [] elements)</code>	4.0	No	
<code>Blob createBlob()</code>	4.0	No	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
Clob createClob()	4.0	No	
NClob createNClob()	4.0	No	
SQLXML createSQLXML()	4.0	No	
Statement createStatement()	3.0	Yes	
Statement createStatement(int resultSetType, int resultSetConcurrency)	3.0	No	
Statement createStatement(int resultSetType, int resultSetConcurrency, int resultSetHoldability)	3.0	No	
Struct createStruct(String typeName, Object[] attributes)	4.0	No	
boolean getAutoCommit()	3.0	Yes	Hard-coded to true
String getCatalog()	3.0	Yes	
Properties getClientInfo()	4.0	Yes	
String getClientInfo(String name)	4.0	Yes	
int getHoldability()	3.0	Yes	Hard-coded to CLOSE_CURSORS_AT_COMMIT
DatabaseMetaData getMetaData()	3.0	Yes	
int getNetworkTimeout()	4.1	No	
String getSchema()	4.1	Yes	The returned schema name does not always match the

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
			one used by statements. Statements use the schema name defined in the connection URL.
<code>int getTransactionIsolation()</code>	3.0	Yes	Hard-coded to TRANSACTION_READ_UNCOMMITTED
<code>Map&lt;String,Class&lt;?&gt;&gt; getTypeMap()</code>	3.0	No	
<code>SQLWarning getWarnings()</code>	3.0	Yes	
<code>boolean isClosed()</code>	3.0	Yes	
<code>boolean isReadOnly()</code>	3.0	Yes	Returns true
<code>boolean isValid(int timeout)</code>	4.0	Yes	
<code>String nativeSQL(String sql)</code>	3.0	Yes	
<code>CallableStatement prepareCall(String sql)</code>	3.0	No	
<code>CallableStatement prepareCall(String sql, int resultSetType, int resultSetConcurrency)</code>	3.0	No	
<code>CallableStatement prepareCall(String sql, int resultSetType, int resultSetConcurrency, int resultSetHoldability)</code>	3.0	No	
<code>PreparedStatement prepareStatement(String sql)</code>	3.0	Yes	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>PreparedStatement prepareStatement(String sql, int autoGeneratedKeys)</code>	3.0	No	
<code>PreparedStatement prepareStatement(String sql, int[] columnIndexes)</code>	3.0	No	
<code>PreparedStatement prepareStatement(String sql, int resultSetType, int resultSetConcurrency)</code>	3.0	No	
<code>PreparedStatement prepareStatement(String sql, int resultSetType, int resultSetConcurrency, int resultSetHoldability)</code>	3.0	No	
<code>PreparedStatement prepareStatement(String sql, String[] columnNames)</code>	3.0	No	
<code>void releaseSavepoint (Savepoint savepoint)</code>	3.0	No	Savepoints are not available because transactions are not supported.
<code>void rollback()</code>	3.0	No	Savepoints are not available because transactions are not supported.
<code>void rollback(Savepoint savepoint)</code>	3.0	No	Savepoints are not available because transactions are not supported.
<code>void setAutoCommit (boolean autoCommit)</code>	3.0	Yes	Ignored because auto-commit is hard-coded to true
<code>void setCatalog(String catalog)</code>	3.0	Yes	

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>void setClientInfo(Properties properties)</code>	4.0	Yes	
<code>void setClientInfo(String name, String value)</code>	4.0	Yes	
<code>void setHoldability(int holdability)</code>	3.0	Yes	
<code>void setNetworkTimeout(Executor executor, int milliseconds)</code>	4.1	No	
<code>void setReadOnly(boolean readOnly)</code>	3.0	Yes	
<code>Savepoint setSavepoint()</code>	3.0	No	Savepoints are not available because transactions are not supported.
<code>Savepoint setSavepoint(String name)</code>	3.0	No	Savepoints are not available because transactions are not supported.
<code>void setSchema(String schema)</code>	4.1	Yes	Does not actually change the schema name used by newly created statements; only changes the value returned by <code>getSchema()</code>
<code>void setTransactionIsolation(int level)</code>	3.0	Yes	
<code>void setTypeMap(Map&lt;String, Class&lt;?&gt;&gt; map)</code>	3.0	No	
<code>boolean isWrapperFor(Class&lt;?&gt; iface)</code>	4.0	Yes	
<code>&lt;T&gt; T unwrap(Class&lt;T&gt; iface)</code>	4.0	Yes	



## DatabaseMetaData

Table 5 lists the methods that belong to the DatabaseMetaData interface, and describes whether each method is supported by the Cloudera JDBC Driver for Apache Hive and which version of the JDBC API is the earliest version that supports the method.

For detailed information about each method in the DatabaseMetaData interface, see the Java API documentation available at

<http://docs.oracle.com/javase/1.5.0/docs/api/java/sql/DatabaseMetaData.html>

**Table 5. Methods in the DatabaseMetaData Interface**

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>boolean allProceduresAreCallable()</code>	3.0	Yes	Returns true
<code>boolean allTablesAreSelectable()</code>	3.0	Yes	Returns true
<code>boolean autoCommitFailureClosesAllResultSets()</code>	4.0	Yes	Returns true
<code>boolean dataDefinitionCausesTransactionCommit()</code>	3.0	Yes	Returns false
<code>boolean dataDefinitionIgnoredInTransactions()</code>	3.0	Yes	Returns false
<code>boolean deletesAreDetected(int type)</code>	3.0	Yes	Returns true
<code>boolean doesMaxRowSizeIncludeBlobs()</code>	3.0	Yes	Returns false
<code>boolean generatedKeyAlwaysReturned()</code>	4.1	Yes	
<code>ResultSet getAttributes(String catalog, String schemaPattern, String typeNamePattern, String attributeNamePattern)</code>	3.0	Yes	
<code>ResultSet getBestRowIdentifier(String catalog, String schema, String table, int scope, boolean nullable)</code>	3.0	Yes	

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>ResultSet getCatalogs()</code>	3.0	Yes	
<code>String getCatalogSeparator()</code>	3.0	Yes	
<code>String getCatalogTerm()</code>	3.0	Yes	
<code>ResultSet getClientInfoProperties()</code>	4.0	Yes	
<code>ResultSet getColumnPrivileges(String catalog, String schema, String table, String columnNamePattern)</code>	3.0	Yes	
<code>ResultSet getColumns(String catalog, String schemaPattern, String tableNamePattern, String columnNamePattern)</code>	3.0	Yes	
<code>Connection getConnection()</code>	3.0	Yes	
<code>ResultSet getCrossReference(String primaryCatalog, String primarySchema, String primaryTable, String foreignCatalog, String foreignSchema, String foreignTable)</code>	3.0	Yes	
<code>int getDatabaseMajorVersion()</code>	3.0	Yes	
<code>int getDatabaseMinorVersion()</code>	3.0	Yes	
<code>String getDatabaseProductName()</code>	3.0	Yes	Hard-coded to Cloudera Impala
<code>String getDatabaseProductVersion()</code>	3.0	Yes	
<code>int getDefaultTransactionIsolation()</code>	3.0	Yes	Hard-coded to TRANSACTION_READ_UNCOMMITTED
<code>int getDriverMajorVersion()</code>	3.0	Yes	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>int getDriverMinorVersion()</code>	3.0	Yes	
<code>String getDriverName()</code>	3.0	Yes	Hard-coded to ImpalaJDBC
<code>String getDriverVersion()</code>	3.0	Yes	
<code>ResultSet getExportedKeys(String catalog, String schema, String table)</code>	3.0	Yes	
<code>String getExtraNameCharacters()</code>	3.0	Yes	Returns an empty String.
<code>ResultSet getFunctionColumns(String catalog, String schemaPattern, String functionNamePattern, String columnNamePattern)</code>	4.0	Yes	
<code>ResultSet getFunctions(String catalog, String schemaPattern, String functionNamePattern)</code>	4.0	Yes	
<code>String getIdentifierQuoteString()</code>	3.0	Yes	Returns a backquote (`)
<code>ResultSet getImportedKeys(String catalog, String schema, String table)</code>	3.0	Yes	
<code>ResultSet getIndexInfo(String catalog, String schema, String table, boolean unique, boolean approximate)</code>	3.0	Yes	
<code>int getJDBCMajorVersion()</code>	3.0	Yes	
<code>int getJDBCMinorVersion()</code>	3.0	Yes	
<code>int getMaxBinaryLiteralLength()</code>	3.0	Yes	Returns 0
<code>int getMaxCatalogNameLength()</code>	3.0	Yes	Returns 128

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>int getMaxCharLiteralLength()</code>	3.0	Yes	Returns 0
<code>int getMaxColumnNameLength()</code>	3.0	Yes	Returns 128
<code>int getMaxColumnsInGroupBy()</code>	3.0	Yes	Returns 0
<code>int getMaxColumnsInIndex()</code>	3.0	Yes	Returns 0
<code>int getMaxColumnsInOrderBy()</code>	3.0	Yes	Returns 0
<code>int getMaxColumnsInSelect()</code>	3.0	Yes	Returns 0
<code>int getMaxColumnsInTable()</code>	3.0	Yes	Returns 0
<code>int getMaxConnections()</code>	3.0	Yes	Returns 0
<code>int getMaxCursorNameLength()</code>	3.0	Yes	Returns 0
<code>int getMaxIndexLength()</code>	3.0	Yes	Returns 0
<code>int getMaxProcedureNameLength()</code>	3.0	Yes	Returns 0
<code>int getMaxRowSize()</code>	3.0	Yes	Returns 0
<code>int getMaxSchemaNameLength()</code>	3.0	Yes	Returns 128
<code>int getMaxStatementLength()</code>	3.0	Yes	Returns 0
<code>int getMaxStatements()</code>	3.0	Yes	Returns 0
<code>int getMaxTableNameLength()</code>	3.0	Yes	Returns 128
<code>int getMaxTablesInSelect()</code>	3.0	Yes	Returns 0
<code>int getMaxUserNameLength()</code>	3.0	Yes	Returns 0
<code>String getNumericFunctions()</code>	3.0	Yes	Returns the Numeric Functions list

Method	Supported Since JDBC Version	Supported by the Driver	Notes
			from the specification related to the JDBC version of the driver.
<code>ResultSet getPrimaryKeys(String catalog, String schema, String table)</code>	3.0	Yes	
<code>ResultSet getProcedureColumns(String catalog, String schemaPattern, String procedureNamePattern, String columnNamePattern)</code>	3.0	Yes	
<code>ResultSet getProcedures(String catalog, String schemaPattern, String procedureNamePattern)</code>	3.0	Yes	
<code>String getProcedureTerm()</code>	3.0	Yes	Returns procedure
<code>ResultSet getPseudoColumns(String catalog, String schemaPattern, String tableNamePattern, String columnNamePattern)</code>	4.1	Yes	
<code>int getResultSetHoldability()</code>	3.0	Yes	Returns CLOSE_CURSORS_AT_COMMIT
<code>RowIdLifetime getRowIdLifetime()</code>	4.0	Yes	Returns ROWID_UNSUPPORTED
<code>ResultSet getSchemas()</code>	3.0	Yes	
<code>ResultSet getSchemas(String catalog, String schemaPattern)</code>	4.0	Yes	
<code>String getSchemaTerm()</code>	3.0	Yes	Returns schema

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>String getSearchStringEscape()</code>	3.0	Yes	Returns a backslash (\)
<code>String getSQLKeywords()</code>	3.0	Yes	Returns an empty String.
<code>int getSQLStateType()</code>	3.0	Yes	Returns <code>sqlStateSQL99</code>
<code>String getStringFunctions()</code>	3.0	Yes	Returns the String Functions list from the specification related to the JDBC version of the driver.
<code>ResultSet getSuperTables(String catalog, String schemaPattern, String tableNamePattern)</code>	3.0	Yes	
<code>ResultSet getSuperTypes(String catalog, String schemaPattern, String typeNamePattern)</code>	3.0	Yes	
<code>String getSystemFunctions()</code>	3.0	Yes	Returns <code>DATABASE,IFNULL,USER</code>
<code>ResultSet getTablePrivileges(String catalog, String schemaPattern, String tableNamePattern)</code>	3.0	Yes	
<code>ResultSet getTables(String catalog, String schemaPattern, String tableNamePattern, String[] types)</code>	3.0	Yes	
<code>ResultSet getTableTypes()</code>	3.0	Yes	
<code>String getTimeDateFunctions()</code>	3.0	Yes	Returns the

Method	Supported Since JDBC Version	Supported by the Driver	Notes
			Time and Date Functions list from the specification related to the JDBC version of the driver.
<code>ResultSet getTypeInfo()</code>	3.0	Yes	
<code>ResultSet getUDTs(String catalog, String schemaPattern, String typeNamePattern, int[] types)</code>	3.0	Yes	
<code>String getURL()</code>	3.0	Yes	
<code>String getUsername()</code>	3.0	Yes	
<code>ResultSet getVersionColumns(String catalog, String schema, String table)</code>	3.0	Yes	
<code>boolean insertsAreDetected(int type)</code>	3.0	Yes	
<code>boolean isCatalogAtStart()</code>	3.0	Yes	
<code>boolean isReadOnly()</code>	3.0	Yes	Returns true
<code>boolean locatorsUpdateCopy()</code>	3.0	Yes	Returns false
<code>boolean nullPlusNonNullIsNull()</code>	3.0	Yes	Returns true
<code>boolean nullsAreSortedAtEnd()</code>	3.0	Yes	Returns false
<code>boolean nullsAreSortedAtStart()</code>	3.0	Yes	Returns false
<code>boolean nullsAreSortedHigh()</code>	3.0	Yes	Returns false
<code>boolean nullsAreSortedLow()</code>	3.0	Yes	Returns true
<code>boolean othersDeletesAreVisible(int</code>	3.0	Yes	

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
type)			
boolean othersInsertsAreVisible(int type)	3.0	Yes	
boolean othersUpdatesAreVisible(int type)	3.0	Yes	
boolean ownDeletesAreVisible(int type)	3.0	Yes	
boolean ownInsertsAreVisible(int type)	3.0	Yes	
boolean ownUpdatesAreVisible(int type)	3.0	Yes	
boolean storesLowerCaseIdentifiers()	3.0	Yes	Returns false
boolean storesLowerCaseQuotedIdentifiers()	3.0	Yes	Returns false
boolean storesMixedCaseIdentifiers()	3.0	Yes	Returns true
boolean storesMixedCaseQuotedIdentifiers()	3.0	Yes	Returns true
boolean storesUpperCaseIdentifiers()	3.0	Yes	Returns false
boolean storesUpperCaseQuotedIdentifiers()	3.0	Yes	Returns false
boolean supportsAlterTableWithAddColumn()	3.0	Yes	Returns false
boolean supportsAlterTableWithDropColumn()	3.0	Yes	Returns false
boolean supportsANSI92EntryLevelSQL()	3.0	Yes	Returns true
boolean supportsANSI92FullSQL()	3.0	Yes	Returns false
boolean supportsANSI92IntermediateSQL	3.0	Yes	Returns false



Method	Supported Since JDBC Version	Supported by the Driver	Notes
()			
boolean supportsBatchUpdates()	3.0	Yes	Returns false
boolean supportsCatalogsInDataManipulation()	3.0	Yes	Returns true
boolean supportsCatalogsInIndexDefinitions()	3.0	Yes	Returns true
boolean supportsCatalogsInPrivilegeDefinitions()	3.0	Yes	Returns true
boolean supportsCatalogsInProcedureCalls()	3.0	Yes	Returns true
boolean supportsCatalogsInTableDefinitions()	3.0	Yes	Returns true
boolean supportsColumnAliasing()	3.0	Yes	Returns true
boolean supportsConvert()	3.0	Yes	Returns true
boolean supportsConvert(int fromType, int toType)	3.0	Yes	
boolean supportsCoreSQLGrammar()	3.0	Yes	Returns true
boolean supportsCorrelatedSubqueries()	3.0	Yes	Returns true
boolean supportsDataDefinitionAndDataManipulationTransactions()	3.0	Yes	Returns false
boolean supportsDataManipulationTransactionsOnly()	3.0	Yes	Returns false
boolean supportsDifferentTableCorrelationNames	3.0	Yes	Returns false

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
()			
boolean supportsExpressionsInOrderBy()	3.0	Yes	Returns true
boolean supportsExtendedSQLGrammar()	3.0	Yes	Returns false
boolean supportsFullOuterJoins()	3.0	Yes	Returns true
boolean supportsGetGeneratedKeys()	3.0	Yes	Returns false
boolean supportsGroupBy()	3.0	Yes	Returns true
boolean supportsGroupByBeyondSelect()	3.0	Yes	Returns true
boolean supportsGroupByUnrelated()	3.0	Yes	Returns false
boolean supportsIntegrityEnhancementFacility()	3.0	Yes	Returns false
boolean supportsLikeEscapeClause()	3.0	Yes	Returns true
boolean supportsLimitedOuterJoins()	3.0	Yes	Returns false
boolean supportsMinimumSQLGrammar()	3.0	Yes	Returns true
boolean supportsMixedCaseIdentifiers()	3.0	Yes	Returns false
boolean supportsMixedCaseQuotedIdentifiers()	3.0	Yes	Returns true
boolean supportsMultipleOpenResults()	3.0	Yes	Returns false
boolean supportsMultipleResultSets()	3.0	Yes	Returns false
boolean supportsMultipleTransactions()	3.0	Yes	Returns true
boolean supportsNamedParameters()	3.0	Yes	Returns false
boolean supportsNonNullableColumns()	3.0	Yes	Returns false

Method	Supported Since JDBC Version	Supported by the Driver	Notes
boolean supportsOpenCursorsAcrossCommit()	3.0	Yes	Returns false
boolean supportsOpenCursorsAcrossRollback()	3.0	Yes	Returns false
boolean supportsOpenStatementsAcrossCommit()	3.0	Yes	Returns true
boolean supportsOpenStatementsAcrossRollback()	3.0	Yes	Returns true
boolean supportsOrderByUnrelated()	3.0	Yes	Returns false
boolean supportsOuterJoins()	3.0	Yes	Returns false
boolean supportsPositionedDelete()	3.0	Yes	Returns false
boolean supportsPositionedUpdate()	3.0	Yes	Returns false
boolean supportsResultSetConcurrency(int type, int concurrency)	3.0	Yes	
boolean supportsResultSetHoldability(int holdability)	3.0	Yes	
boolean supportsResultSetType(int type)	3.0	Yes	
boolean supportsSavepoints()	3.0	Yes	Returns false
boolean supportsSchemasInDataManipulation()	3.0	Yes	Returns true
boolean supportsSchemasInIndexDefinitions()	3.0	Yes	Returns true
boolean supportsSchemasInPrivilegeDefinitions()	3.0	Yes	Returns true

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
boolean supportsSchemasInProcedureCalls()	3.0	Yes	Returns false
boolean supportsSchemasInTableDefinitions()	3.0	Yes	Returns true
boolean supportsSelectForUpdate()	3.0	Yes	Returns false
boolean supportsStatementPooling()	3.0	Yes	Returns false
boolean supportsStoredFunctionsUsingCallSyntax()	4.0	Yes	Returns false
boolean supportsStoredProcedures()	3.0	Yes	Returns true
boolean supportsSubqueriesInComparisons()	3.0	Yes	Returns true
boolean supportsSubqueriesInExists()	3.0	Yes	Returns true
boolean supportsSubqueriesInIns()	3.0	Yes	Returns true
boolean supportsSubqueriesInQuantifieds()	3.0	Yes	Returns true
boolean supportsTableCorrelationNames()	3.0	Yes	Returns true
boolean supportsTransactionIsolationLevel(int level)	3.0	Yes	
boolean supportsTransactions()	3.0	Yes	Returns false
boolean supportsUnion()	3.0	Yes	Returns true
boolean supportsUnionAll()	3.0	Yes	Returns true
boolean updatesAreDetected(int type)	3.0	Yes	Returns true

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>boolean usesLocalFilePerTable()</code>	3.0	Yes	Returns false
<code>boolean usesLocalFiles()</code>	3.0	Yes	Returns false
<code>boolean isWrapperFor(Class&lt;?&gt; iface)</code>	4.0	Yes	
<code>&lt;T&gt; T unwrap(Class&lt;T&gt; iface)</code>	4.0	Yes	

## DataSource

Table 6 lists the methods that belong to the DataSource interface, and describes whether each method is supported by the Cloudera JDBC Driver for Apache Hive and which version of the JDBC API is the earliest version that supports the method.

For detailed information about each method in the DataSource interface, see the Java API documentation available at

<http://docs.oracle.com/javase/1.5.0/docs/api/javax/sql/DataSource.html>

**Table 6. Methods in the DataSource Interface**

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>Connection getConnection()</code>	3.0	Yes	
<code>Connection getConnection(String username, String password)</code>	3.0	Yes	
<code>int getLoginTimeout()</code>	3.0	Yes	
<code>PrintWriter getLogWriter()</code>	3.0	Yes	
<code>Logger getParentLogger()</code>	4.1	No	The driver does not use <code>java.util.logging</code>

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>void setLoginTimeout(int seconds)</code>	3.0	Yes	
<code>void setLogWriter(PrintWriter out)</code>	3.0	Yes	
<code>boolean isWrapperFor(Class&lt;?&gt; iface)</code>	4.0	Yes	
<code>&lt;T&gt; T unwrap(Class&lt;T&gt; iface)</code>	4.0	Yes	

## Driver

Table 7 lists the methods that belong to the Driver interface, and describes whether each method is supported by the Cloudera JDBC Driver for Apache Hive and which version of the JDBC API is the earliest version that supports the method.

For detailed information about each method in the Driver interface, see the Java API documentation available at <http://docs.oracle.com/javase/1.5.0/docs/api/java/sql/Driver.html>

**Table 7. Methods in the Driver Interface**

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>boolean acceptsURL(String url)</code>	3.0	Yes	
<code>Connection connect(String url, Properties info)</code>	3.0	Yes	
<code>int getMajorVersion()</code>	3.0	Yes	
<code>int getMinorVersion()</code>	3.0	Yes	
<code>Logger getParentLogger()</code>	4.1	No	
<code>DriverPropertyInfo[]</code>	3.0	Yes	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>getPropertyInfo(String url, Properties info)</code>			
<code>boolean jdbcCompliant()</code>	3.0	Yes	

### ParameterMetaData

Table 8 lists the methods that belong to the ParameterMetaData interface, and describes whether each method is supported by the Cloudera JDBC Driver for Apache Hive and which version of the JDBC API is the earliest version that supports the method.

For detailed information about each method in the ParameterMetaData interface, see the Java API documentation available at

<http://docs.oracle.com/javase/1.5.0/docs/api/java/sql/ParameterMetaData.html>

**Table 8. Methods in the ParameterMetaData Interface**

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>String getParameterClassName(int param)</code>	3.0	Yes	
<code>int getParameterCount()</code>	3.0	Yes	
<code>int getParameterMode(int param)</code>	3.0	Yes	
<code>int getParameterType(int param)</code>	3.0	Yes	
<code>String getParameterTypeName(int param)</code>	3.0	Yes	
<code>int getPrecision(int param)</code>	3.0	Yes	
<code>int getScale(int param)</code>	3.0	Yes	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>int isNullable(int param)</code>	3.0	Yes	
<code>boolean isSigned(int param)</code>	3.0	Yes	
<code>boolean isWrapperFor(Class&lt;?&gt; iface)</code>	4.0	Yes	
<code>&lt;T&gt; T unwrap(Class&lt;T&gt; iface)</code>	4.0	Yes	

### PooledConnection

Table 9 lists the methods that belong to the PooledConnection interface, and describes whether each method is supported by the Cloudera JDBC Driver for Apache Hive and which version of the JDBC API is the earliest version that supports the method.

For detailed information about each method in the PooledConnection interface, see the Java API documentation available at

<http://docs.oracle.com/javase/1.5.0/docs/api/javax/sql/PooledConnection.html>

**Table 9. Methods in the PooledConnection Interface**

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>void addConnectionEventListener(ConnectionEventListener listener)</code>	3.0	Yes	
<code>void addStatementEventListener(StatementEventListener listener)</code>	4.0	Yes	
<code>void close()</code>	3.0	Yes	



Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>Connection getConnection()</code>	3.0	Yes	
<code>void removeConnectionEventListener(ConnectionEventListener listener)</code>	3.0	Yes	
<code>void removeStatementEventListener(StatementEventListener listener)</code>	4.0	Yes	Removes the specified <code>StatementEventListener</code> from the list of components that will be notified when the driver detects that a <code>PreparedStatement</code> has been closed or is invalid.

## PreparedStatement

The `PreparedStatement` interface extends the `Statement` interface.

Table 10 lists the methods that belong to the `PreparedStatement` interface, and describes whether each method is supported by the Cloudera JDBC Driver for Apache Hive and which version of the JDBC API is the earliest version that supports the method.

For detailed information about each method in the `PooledConnection` interface, see the Java API documentation available at

<http://docs.oracle.com/javase/1.5.0/docs/api/java/sql/PreparedStatement.html>

**Table 10. Methods in the PreparedStatement Interface**

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>void addBatch()</code>	3.0	Yes	
<code>void clearParameters()</code>	3.0	Yes	

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>boolean execute()</code>	3.0	Yes	
<code>ResultSet executeQuery()</code>	3.0	Yes	
<code>int executeUpdate()</code>	3.0	Yes	
<code>ResultSetMetaData getMetaData()</code>	3.0	Yes	
<code>ParameterMetaData getParameterMetaData()</code>	3.0	Yes	
<code>void setArray(int parameterIndex, Array x)</code>	3.0	No	
<code>void setAsciiStream(int parameterIndex, InputStream x)</code>	4.0	Yes	
<code>void setAsciiStream(int parameterIndex, InputStream x, int length)</code>	3.0	Yes	
<code>void setAsciiStream(int parameterIndex, InputStream x, long length)</code>	4.0	Yes	
<code>void setBigDecimal(int parameterIndex, BigDecimal x)</code>	3.0	Yes	
<code>void setBinaryStream(int parameterIndex, InputStream x)</code>	4.0	Yes	
<code>void setBinaryStream(int parameterIndex, InputStream x, int length)</code>	3.0	Yes	
<code>void setBinaryStream(int</code>	4.0	Yes	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
parameterIndex, InputStream x, long length)			
void setBlob(int parameterIndex, Blob x)	3.0	No	
void setBlob(int parameterIndex, InputStream inputStream)	4.0	No	
void setBlob(int parameterIndex, InputStream inputStream, long length)	4.0	No	
void setBoolean(int parameterIndex, boolean x)	3.0	Yes	
void setByte(int parameterIndex, byte x)	3.0	Yes	
void setBytes(int parameterIndex, byte[] x)	3.0	Yes	
void setCharacterStream (int parameterIndex, Reader reader)	4.0	Yes	
void setCharacterStream (int parameterIndex, Reader reader, int length)	3.0	Yes	
void setCharacterStream (int parameterIndex, Reader reader, long length)	4.0	Yes	
void setClob(int parameterIndex, Clob x)	3.0	No	

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>void setClob(int parameterIndex, Reader reader)</code>	4.0	No	
<code>void setClob(int parameterIndex, Reader reader, long length)</code>	4.0	No	
<code>void setDate(int parameterIndex, Date x)</code>	3.0	Yes	
<code>void setDate(int parameterIndex, Date x, Calendar cal)</code>	3.0	Yes	
<code>void setDouble(int parameterIndex, double x)</code>	3.0	Yes	
<code>void setFloat(int parameterIndex, float x)</code>	3.0	Yes	
<code>void setInt(int parameterIndex, int x)</code>	3.0	Yes	
<code>void setLong(int parameterIndex, long x)</code>	3.0	Yes	
<code>void setNCharacterStream(int parameterIndex, Reader value)</code>	4.0	No	
<code>void setNCharacterStream(int parameterIndex, Reader value, long length)</code>	4.0	No	
<code>void setNClob(int parameterIndex, NClob value)</code>	4.0	No	
<code>void setNClob(int parameterIndex, Reader reader)</code>	4.0	No	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>void setNClob(int parameterIndex, Reader reader, long length)</code>	4.0	No	
<code>void setNString(int parameterIndex, String value)</code>	4.0	No	
<code>void setNull(int paramIndex, int sqlType, String typeName)</code>	3.0	Yes	
<code>void setObject(int parameterIndex, Object x)</code>	3.0	Yes	
<code>void setObject(int parameterIndex, Object x, int targetSqlType)</code>	3.0	Yes	
<code>void setObject(int parameterIndex, Object x, int targetSqlType, int scale)</code>	3.0	Yes	
<code>void setRef(int parameterIndex, Ref x)</code>	3.0	No	
<code>void setRowId(int parameterIndex, RowId x)</code>	4.0	No	
<code>void setShort(int parameterIndex, short x)</code>	3.0	No	
<code>void setSQLXML(int parameterIndex, SQLXML xmlObject)</code>	4.0	Yes	
<code>void setString(int parameterIndex, String x)</code>	3.0	Yes	
<code>void setTime(int parameterIndex, Time x)</code>	3.0	Yes	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>void setTime(int parameterIndex, Time x, Calendar cal)</code>	3.0	Yes	
<code>void setTimestamp(int parameterIndex, Timestamp x)</code>	3.0	Yes	
<code>void setTimestamp(int parameterIndex, Timestamp x, Calendar cal)</code>	3.0	Yes	
<code>void setUnicodeStream(int parameterIndex, InputStream x, int length)</code>	3.0	Yes	Deprecated
<code>void setURL(int parameterIndex, URL x)</code>	3.0	No	
<code>boolean isWrapperFor(Class&lt;?&gt; iface)</code>	4.0	Yes	
<code>&lt;T&gt; T unwrap(Class&lt;T&gt; iface)</code>	4.0	Yes	

## ResultSet

Table 11 lists the methods that belong to the `ResultSet` interface, and describes whether each method is supported by the Cloudera JDBC Driver for Apache Hive and which version of the JDBC API is the earliest version that supports the method.

For detailed information about each method in the `ResultSet` interface, see the Java API documentation available at

<http://docs.oracle.com/javase/1.5.0/docs/api/java/sql/ResultSet.html>

Table 11. Methods in the ResultSet Interface

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>boolean absolute(int row)</code>	3.0	No	
<code>void afterLast()</code>	3.0	No	
<code>void beforeFirst()</code>	3.0	No	
<code>void cancelRowUpdates()</code>	3.0	No	Not valid because the driver is read-only.
<code>void clearWarnings()</code>	3.0	Yes	
<code>void close()</code>	3.0	Yes	
<code>void deleteRow()</code>	3.0	No	Not valid because the driver is read-only.
<code>int findColumn(String columnName)</code>	3.0	Yes	
<code>boolean first()</code>	3.0	No	
<code>Array getArray(int i)</code>	3.0	No	
<code>Array getArray(String colName)</code>	3.0	No	
<code>InputStream getAsciiStream(int columnIndex)</code>	3.0	Yes	
<code>InputStream getAsciiStream(String columnName)</code>	3.0	Yes	
<code>BigDecimal getBigDecimal(int columnIndex)</code>	3.0	Yes	
<code>BigDecimal getBigDecimal(int columnIndex, int scale)</code>	3.0	Yes	Deprecated

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
BigDecimal getBigDecimal (String columnName)	3.0	Yes	
BigDecimal getBigDecimal (String columnName, int scale)	3.0	Yes	Deprecated
InputStream getBinaryStream(int columnIndex)	3.0	Yes	
InputStream getBinaryStream(String columnName)	3.0	Yes	
Blob getBlob(int i)	3.0	No	
Blob getBlob(String colName)	3.0	No	
boolean getBoolean(int columnIndex)	3.0	Yes	
boolean getBoolean(String columnName)	3.0	Yes	
getBytes(int columnIndex)	3.0	Yes	
byte getByte(String columnName)	3.0	Yes	
byte[] getBytes(int columnIndex)	3.0	Yes	
byte[] getBytes(String columnName)	3.0	Yes	
Reader getCharacterStream (int columnIndex)	3.0	Yes	
Reader getCharacterStream (String columnName)	3.0	Yes	



Method	Supported Since JDBC Version	Supported by the Driver	Notes
Clob getClob(int i)	3.0	No	
Clob getClob(String colName)	3.0	No	
int getConcurrency()	3.0	Yes	
String getCursorName()	3.0	Yes	
Date getDate(int columnIndex)	3.0	Yes	
Date getDate(int columnIndex, Calendar cal)	3.0	Yes	
Date getDate(String columnName)	3.0	Yes	
Date getDate(String columnName, Calendar cal)	3.0	Yes	
double getDouble(int columnIndex)	3.0	Yes	
double getDouble(String columnName)	3.0	Yes	
int getFetchDirection()	3.0	Yes	
int getFetchSize()	3.0	Yes	
float getFloat(int columnIndex)	3.0	Yes	
float getFloat(String columnName)	3.0	Yes	
int getHoldability()	4.0	Yes	
int getInt(int columnIndex)	3.0	Yes	

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>int getInt(String columnName)</code>	3.0	Yes	
<code>long getLong(int columnIndex)</code>	3.0	Yes	
<code>long getLong(String columnName)</code>	3.0	Yes	
<code>ResultSetMetaData getMetaData()</code>	3.0	Yes	
<code>Reader getNCharacterStream(int columnIndex)</code>	4.0	No	
<code>Reader getNCharacterStream(String columnName)</code>	4.0	No	
<code>NClob getNClob(int columnIndex)</code>	4.0	No	
<code>NClob getNClob(String columnName)</code>	4.0	No	
<code>String getNString(int columnIndex)</code>	4.0	No	
<code>String getNString(String columnName)</code>	4.0	No	
<code>Object getObject(int columnIndex)</code>	3.0	Yes	
<code>&lt;T&gt; T getObject(int columnIndex, Class&lt;T&gt; type)</code>	4.1	No	
<code>Object getObject(int i, Map&lt;String, Class&lt;?&gt;&gt; map)</code>	3.0	No	
<code>Object getObject(String columnName)</code>	3.0	No	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
columnName)			
<T> T getObject(String columnName, Class<T> type)	4.1	No	
Object getObject(String colName, Map<String,Class<?>> map)	3.0	Yes	
Ref getRef(int i)	3.0	No	
Ref getRef(String colName)	3.0	No	
int getRow()	3.0	Yes	
RowId getRowId(int columnIndex)	4.0	No	
RowId getRowId(String columnLabel)	4.0	No	
short getShort(int columnIndex)	3.0	Yes	
short getShort(String columnName)	3.0	Yes	
SQLXML getSQLXML(int columnIndex)	4.0	No	
SQLXML getSQLXML(String columnLabel)	4.0	No	
Statement getStatement()	3.0	Yes	
String getString(int columnIndex)	3.0	Yes	
String getString(String columnName)	3.0	Yes	

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
Time getTime(int columnIndex)	3.0	Yes	
Time getTime(int columnIndex, Calendar cal)	3.0	Yes	
Time getTime(String columnName)	3.0	Yes	
Time getTime(String columnName, Calendar cal)	3.0	Yes	
Timestamp getTimestamp(int columnIndex)	3.0	Yes	
Timestamp getTimestamp(int columnIndex, Calendar cal)	3.0	Yes	
Timestamp getTimestamp(String columnName)	3.0	Yes	
Timestamp getTimestamp(String columnName, Calendar cal)	3.0	Yes	
int getType()	3.0	Yes	
InputStream getUnicodeStream(int columnIndex)	3.0	Yes	Deprecated
InputStream getUnicodeStream(String columnName)	3.0	Yes	Deprecated
URL getURL(int columnIndex)	3.0	No	
URL getURL(String columnName)	3.0	No	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
SQLWarning getWarnings()	3.0	Yes	
void insertRow()	3.0	No	Not valid because the driver is read-only.
boolean isAfterLast()	3.0	Yes	
boolean isBeforeFirst()	3.0	Yes	
boolean isClosed()	4.0	Yes	
boolean isFirst()	3.0	Yes	
boolean isLast()	3.0	No	
boolean last()	3.0	No	
void moveToCurrentRow()	3.0	No	Not valid because the driver is read-only.
void moveToInsertRow()	3.0	No	Not valid because the driver is read-only.
boolean next()	3.0	Yes	
boolean previous()	3.0	No	
void refreshRow()	3.0	No	
boolean relative(int rows)	3.0	No	
boolean rowDeleted()	3.0	Yes	Hard-coded to false
boolean rowInserted()	3.0	Yes	Hard-coded to false
boolean rowUpdated()	3.0	Yes	Hard-coded to false
void setFetchDirection(int direction)	3.0	No	Not valid because the driver is forward-only.

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>void setFetchSize(int rows)</code>	3.0	Yes	
<code>void updateArray(int columnIndex, Array x)</code>	3.0	No	
<code>void updateArray(String columnName, Array x)</code>	3.0	No	
<code>void updateAsciiStream(int columnIndex, InputStream x)</code>	4.0	No	Not valid because the driver is read-only.
<code>void updateAsciiStream(int columnIndex, InputStream x, int length)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateAsciiStream(int columnIndex, InputStream x, long length)</code>	4.0	No	Not valid because the driver is read-only.
<code>void updateAsciiStream(String columnName, InputStream x)</code>	4.0	No	Not valid because the driver is read-only.
<code>void updateAsciiStream(String columnName, InputStream x, int length)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateAsciiStream(String columnName, InputStream x, long length)</code>	4.0	No	Not valid because the driver is read-only.
<code>void updateBigDecimal(int columnIndex, BigDecimal x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateBigDecimal(String columnName, BigDecimal x)</code>	3.0	No	Not valid because the driver is read-only.

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>void updateBinaryStream(int columnIndex, InputStream x)</code>	4.0	No	Not valid because the driver is read-only.
<code>void updateBinaryStream(int columnIndex, InputStream x, int length)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateBinaryStream(int columnIndex, InputStream x, long length)</code>	4.0	No	Not valid because the driver is read-only.
<code>void updateBinaryStream(String columnName, InputStream x)</code>	4.0	No	Not valid because the driver is read-only.
<code>void updateBinaryStream(String columnName, InputStream x, int length)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateBinaryStream(String columnName, InputStream x, long length)</code>	4.0	No	Not valid because the driver is read-only.
<code>void updateBlob(int columnIndex, InputStream inputStream)</code>	4.0	No	
<code>void updateBlob(int columnIndex, Blob x)</code>	3.0	No	
<code>void updateBlob(int columnIndex, InputStream inputStream, long length)</code>	4.0	No	
<code>void updateBlob(String columnName, InputStream inputStream)</code>	4.0	No	
<code>void updateBlob(String</code>	3.0	No	

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>columnName, Blob x)</code>			
<code>void updateBlob(String columnLabel, InputStream inputStream, long length)</code>	4.0	No	
<code>void updateBoolean(int columnIndex, boolean x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateBoolean(String columnName, boolean x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateByte(int columnIndex, byte x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateByte(String columnName, byte x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateBytes(int columnIndex, byte[] x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateBytes(String columnName, byte[] x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateCharacterStream(int columnIndex, Reader x, int length)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateCharacterStream(String columnName, Reader reader, int length)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateBlob(int columnIndex, InputStream inputStream)</code>	4.0	No	
<code>void updateClob(int columnIndex, Clob x)</code>	3.0	No	
<code>void updateBlob(int</code>	4.0	No	



Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>columnIndex, InputStream inputStream, long length)</code>			
<code>void updateBlob(String columnName, InputStream inputStream)</code>	4.0	No	
<code>void updateClob(String columnName, Clob x)</code>	3.0	No	
<code>void updateBlob(String columnName, InputStream inputStream, long length)</code>	4.0	No	
<code>void updateDate(int columnIndex, Date x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateDate(String columnName, Date x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateDouble(int columnIndex, double x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateDouble(String columnName, double x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateFloat(int columnIndex, float x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateFloat(String columnName, float x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateInt(int columnIndex, int x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateInt(String columnName, int x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateLong(int columnIndex, long x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateLong(String</code>	3.0	No	Not valid because the driver

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>columnName, long x)</code>			is read-only.
<code>void updateNCharacterStream (int columnIndex, Reader x)</code>	4.0	No	
<code>void updateNCharacterStream (int columnIndex, Reader x, long length)</code>	4.0	No	
<code>void updateNCharacterStream (String columnName, Reader reader)</code>	4.0	No	
<code>void updateNCharacterStream (String columnName, Reader reader, long length)</code>	4.0	No	
<code>void updateNClob(int columnIndex, NClob nClob)</code>	4.0	No	
<code>void updateNClob(int columnIndex, Reader reader)</code>	4.0	No	
<code>void updateNClob(int columnIndex, Reader reader, long length)</code>	4.0	No	
<code>void updateNClob(String columnName, NClob nClob)</code>	4.0	No	
<code>void updateNClob(String columnName, Reader reader)</code>	4.0	No	
<code>void updateNClob(String columnName, Reader reader, long length)</code>	4.0	No	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>void updateNString(int columnIndex, String nString)</code>	4.0	No	
<code>void updateNString(String columnName, String nString)</code>	4.0	No	
<code>void updateNull(int columnIndex)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateNull(String columnName)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateObject(int columnIndex, Object x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateObject(int columnIndex, Object x, int scale)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateObject(String columnName, Object x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateObject(String columnName, Object x, int scale)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateRef(int columnIndex, Ref x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateRef(String columnName, Ref x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateRow()</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateRowId(int columnIndex, RowId x)</code>	4.0	No	
<code>void updateRowId(String columnName, RowId x)</code>	4.0	No	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>void updateShort(int columnIndex, short x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateShort(String columnName, short x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateSQLXML(int columnIndex, SQLXML xmlObject)</code>	4.0	No	
<code>void updateSQLXML(String columnName, SQLXML xmlObject)</code>	4.0	No	
<code>void updateString(int columnIndex, String x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateString(String columnName, String x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateTime(int columnIndex, Time x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateTime(String columnName, Time x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateTimeStamp(int columnIndex, Timestamp x)</code>	3.0	No	Not valid because the driver is read-only.
<code>void updateTimeStamp(String columnName, Timestamp x)</code>	3.0	No	Not valid because the driver is read-only.
<code>boolean wasNull()</code>	3.0	Yes	
<code>boolean isWrapperFor(Class&lt;?&gt; iface)</code>	4.0	Yes	
<code>&lt;T&gt; T unwrap(Class&lt;T&gt; iface)</code>	4.0	Yes	

## ResultSetMetaData

Table 12 lists the methods that belong to the ResultSetMetaData interface, and describes whether each method is supported by the Cloudera JDBC Driver for Apache Hive and which version of the JDBC API is the earliest version that supports the method.

For detailed information about each method in the ResultSetMetaData interface, see the Java API documentation available at

<http://docs.oracle.com/javase/1.5.0/docs/api/java/sql/ResultSetMetaData.html>

**Table 12. Methods in the ResultSetMetaData Interface**

Method	Supported Since JDBC Version	Supported by the Driver	Notes
String getCatalogName (int column)	3.0	Yes	
String getColumnClassName (int column)	3.0	Yes	
int getColumnCount ()	3.0	Yes	
int getColumnDisplaySize (int column)	3.0	Yes	
String getColumnLabel (int column)	3.0	Yes	
String getColumnName (int column)	3.0	Yes	
int getColumnType (int column)	3.0	Yes	
String getColumnTypeName (int column)	3.0	Yes	
int getPrecision (int column)	3.0	Yes	
int getScale (int column)	3.0	Yes	
String getSchemaName (int column)	3.0	Yes	

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>String getTableName(int column)</code>	3.0	Yes	
<code>boolean isAutoIncrement(int column)</code>	3.0	Yes	
<code>boolean isCaseSensitive(int column)</code>	3.0	Yes	
<code>boolean isCurrency(int column)</code>	3.0	Yes	
<code>boolean isDefinitelyWritable(int column)</code>	3.0	Yes	
<code>int isNullable(int column)</code>	3.0	Yes	
<code>boolean isReadOnly(int column)</code>	3.0	Yes	
<code>boolean isSearchable(int column)</code>	3.0	Yes	
<code>boolean isSigned(int column)</code>	3.0	Yes	
<code>boolean isWritable(int column)</code>	3.0	Yes	
<code>boolean isWrapperFor(Class&lt;?&gt; iface)</code>	4.0	Yes	
<code>&lt;T&gt; T unwrap(Class&lt;T&gt; iface)</code>	4.0	Yes	

### Statement

Table 13 lists the methods that belong to the Statement interface, and describes whether each method is supported by the Cloudera JDBC Driver for Apache Hive and which version of the JDBC API is the earliest version that supports the method.

For detailed information about each method in the Statement interface, see the Java API documentation available at <http://docs.oracle.com/javase/1.5.0/docs/api/java/sql/Statement.html>

**Table 13. Methods in the Statement Interface**

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>void addBatch(String sql)</code>	3.0	Yes	
<code>void cancel()</code>	3.0	Yes	
<code>void clearBatch()</code>	3.0	Yes	
<code>void clearWarnings()</code>	3.0	Yes	
<code>void close()</code>	3.0	Yes	
<code>void closeOnCompletion()</code>	4.1	Yes	
<code>boolean execute(String sql)</code>	3.0	Yes	
<code>boolean execute(String sql, int autoGeneratedKeys)</code>	3.0	No	
<code>boolean execute(String sql, int[] columnIndexes)</code>	3.0	No	
<code>boolean execute(String sql, String[] columnNames)</code>	3.0	No	
<code>int[] executeBatch()</code>	3.0	No	
<code>ResultSet executeQuery(String sql)</code>	3.0	Yes	
<code>int executeUpdate(String sql)</code>	3.0	Yes	
<code>int executeUpdate(String sql, int autoGeneratedKeys)</code>	3.0	No	

## Features

Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>int executeUpdate(String sql, int[] columnIndexes)</code>	3.0	No	
<code>int executeUpdate(String sql, String[] columnNames)</code>	3.0	No	
<code>Connection getConnection()</code>	3.0	Yes	
<code>int getFetchDirection()</code>	3.0	Yes	
<code>int getFetchSize()</code>	3.0	Yes	
<code>ResultSet getGeneratedKeys()</code>	3.0	Yes	
<code>int getMaxFieldSize()</code>	3.0	Yes	
<code>int getMaxRows()</code>	3.0	Yes	
<code>boolean getMoreResults()</code>	3.0	Yes	
<code>boolean getMoreResults(int current)</code>	3.0	No	
<code>int getQueryTimeout()</code>	3.0	Yes	
<code>ResultSet getResultSet()</code>	3.0	Yes	
<code>int getResultSetConcurrency()</code>	3.0	Yes	Hard-coded to CONCUR_READ_ONLY
<code>int getResultSetHoldability()</code>	3.0	Yes	Hard-coded to CLOSE_CURSORS_AT_COMMIT
<code>int getResultSetType()</code>	3.0	Yes	Hard-coded to TYPE_FORWARD_ONLY
<code>int getUpdateCount()</code>	3.0	Yes	



Method	Supported Since JDBC Version	Supported by the Driver	Notes
<code>SQLWarning getWarnings()</code>	3.0	Yes	
<code>boolean isClosed()</code>	4.0	Yes	
<code>boolean isCloseOnCompletion()</code>	4.1	Yes	
<code>boolean isPoolable()</code>	4.0	Yes	
<code>void setCursorName(String name)</code>	3.0	No	
<code>void setEscapeProcessing(boolean enable)</code>	3.0	Yes	
<code>void setFetchDirection(int direction)</code>	3.0	No	
<code>void setFetchSize(int rows)</code>	3.0	Yes	
<code>void setMaxFieldSize(int max)</code>	3.0	Yes	
<code>void setMaxRows(int max)</code>	3.0	Yes	
<code>void setPoolable(boolean poolable)</code>	4.0	Yes	
<code>void setQueryTimeout(int seconds)</code>	3.0	Yes	
<code>boolean isWrapperFor(Class&lt;?&gt; iface)</code>	4.0	Yes	
<code>&lt;T&gt; T unwrap(Class&lt;T&gt; iface)</code>	4.0	Yes	

## Contact Us

If you have difficulty using the driver, please contact our Technical Support staff. We welcome your questions, comments, and feature requests.

**Important:**

To help us assist you, prior to contacting Technical Support please prepare a detailed summary of the client and server environment including operating system version, patch level, and configuration.

For details on contacting Technical Support, see

<http://www.cloudera.com/content/cloudera/en/products/cloudera-support.html>

## Appendix A Authentication Options

Hive Server 1 does not support authentication. You must configure the driver to use No Authentication.

Hive Server 2 supports the following authentication mechanisms:

- No Authentication
- Kerberos
- User Name
- User Name and Password

Most default configurations of Hive Server 2 require User Name authentication. If you are unable to connect to your Hive server using User Name authentication, then verify the authentication mechanism configured for your Hive server by examining the `hive-site.xml` file. Examine the following properties to determine which authentication mechanism your server is set to use:

- **hive.server2.authentication**—This property sets the authentication mode for Hive Server 2. The following values are available:
  - **NOSASL** disables the Simple Authentication and Security Layer (SASL).
  - **KERBEROS** enables Kerberos authentication.
  - **NONE** enables plain SASL transport. **NONE** is the default value.
  - **PLANSASL** enables user name and password authentication using a cleartext password mechanism.
- **hive.server2.enable.doAs**—If this property is set to the default value of **TRUE**, then Hive processes queries as the user who submitted the query. If this property is set to **FALSE**, then queries are run as the user that runs the `hiveserver2` process.

Table 14 lists authentication mechanisms to configure for the driver based on the settings in the `hive-site.xml` file.

**Table 14. Hive Authentication Mechanism Configurations**

<code>hive.server2.authentication</code>	<code>hive.server2.enable.doAs</code>	Driver Authentication Mechanism
NOSASL	FALSE	No Authentication
KERBEROS	TRUE or FALSE	Kerberos
NONE	TRUE or FALSE	User Name
LDAP	TRUE or FALSE	User Name and Password

**Note:**

It is an error to set `hive.server2.authentication` to `NOSASL` and `hive.server2.enable.doAs` to `true`. This configuration will not prevent the service from starting up, but results in an unusable service.

For more information about authentication mechanisms, refer to the documentation for your Hadoop / Hive distribution. See also *Running Hadoop in Secure Mode* at [http://hadoop.apache.org/docs/r0.23.7/hadoop-project-dist/hadoop-common/ClusterSetup.html#Running\\_Hadoop\\_in\\_Secure\\_Mode](http://hadoop.apache.org/docs/r0.23.7/hadoop-project-dist/hadoop-common/ClusterSetup.html#Running_Hadoop_in_Secure_Mode)

## Using No Authentication

When `hive.server2.authentication` is set to `NOSASL`, you must configure your connection to use No Authentication.

## Using Kerberos

When connecting to a Hive server of type Hive Server 2 and `hive.server2.authentication` is set to `KERBEROS`, you must configure your connection to use Kerberos authentication.

## Using User Name

When connecting to a Hive server of type Hive Server 2 and `hive.server2.authentication` is set to `NONE`, you must configure your connection to use User Name authentication. Validation of the credentials that you include depends on `hive.server2.enable.doAs`:

- If `hive.server2.enable.doAs` is set to `TRUE`, then the user name in the driver configuration must be an existing operating system user on the host that is running Hive Server 2.
- If `hive.server2.enable.doAs` is set to `FALSE`, then the user name in the driver configuration is ignored.

If no user name is specified in the driver configuration, then the driver defaults to using "hive" as the user name.

## Using User Name and Password

When connecting to a Hive server of type Hive Server 2 and the server is configured to use the SASL-PLAIN authentication mechanism with a user name and a password, you must configure your connection to use User Name and Password authentication.

## Appendix B Configuring Kerberos Authentication for Windows

You can configure your Kerberos setup so that you use the MIT Kerberos Ticket Manager to get the Ticket Granting Ticket (TGT), or configure the setup so that you can use the driver to get the ticket directly from the Key Distribution Center (KDC). Also, if a client application obtains a Subject with a TGT, it is possible to use that Subject to authenticate the connection.

### Downloading and Installing MIT Kerberos for Windows

**To download and install MIT Kerberos for Windows:**

1. To download the Kerberos installer for 64-bit computers, use the following download link from the MIT Kerberos website: <http://web.mit.edu/kerberos/dist/kfw/4.0/kfw-4.0.1-amd64.msi>

The 64-bit installer includes both 32-bit and 64-bit libraries.

OR

To download the Kerberos installer for 32-bit computers, use the following download link from the MIT Kerberos website: <http://web.mit.edu/kerberos/dist/kfw/4.0/kfw-4.0.1-i386.msi>

The 32-bit installer includes 32-bit libraries only.

2. To run the installer, double-click the .msi file that you downloaded in step 1.
3. Follow the instructions in the installer to complete the installation process.
4. When the installation completes, click **Finish**

### Using the MIT Kerberos Ticket Manager to Get Tickets

#### Setting the KRB5CCNAME Environment Variable

You must set the KRB5CCNAME environment variable to your credential cache file.

**To set the KRB5CCNAME environment variable:**

1. Click the **Start** button, then right-click **Computer**, and then click **Properties**
2. Click **Advanced System Settings**
3. In the System Properties dialog box, click the **Advanced** tab, and then click **Environment Variables**
4. In the Environment Variables dialog box, under the System variables list, click **New**
5. In the New System Variable dialog box, in the Variable name field, type **KRB5CCNAME**
6. In the Variable value field, type the path for your credential cache file. For example, type **C:\KerberosTickets.txt**
7. Click **OK** to save the new variable.
8. Ensure that the variable appears in the System variables list.
9. Click **OK** to close the Environment Variables dialog box, and then click **OK** to close the System Properties dialog box.

10. To ensure that Kerberos uses the new settings, restart your computer.

### Getting a Kerberos Ticket

#### To get a Kerberos ticket:

1. Click the **Start** button, then click **All Programs**, and then click the **Kerberos for Windows (64-bit)** or **Kerberos for Windows (32-bit)** program group.
2. Click **MIT Kerberos Ticket Manager**
3. In the MIT Kerberos Ticket Manager, click **Get Ticket**
4. In the Get Ticket dialog box, type your principal name and password, and then click **OK**

If the authentication succeeds, then your ticket information appears in the MIT Kerberos Ticket Manager.

### Authenticating to the Hive Server

#### To authenticate to the Hive server:

- Use a connection string that has the following properties defined:
  - AuthMech
  - KrbHostFQDN
  - KrbRealm
  - KrbServiceName

For detailed information about these properties, see "Driver Configuration Options" on page 82.

### Using the Driver to Get Tickets

#### Deleting the KRB5CCNAME Environment Variable

To enable the driver to get Ticket Granting Tickets (TGTs) directly, you must ensure that the KRB5CCNAME environment variable has not been set.

#### To delete the KRB5CCNAME environment variable:

1. Click the **Start** button, then right-click **Computer**, and then click **Properties**
2. Click **Advanced System Settings**
3. In the System Properties dialog box, click the **Advanced** tab and then click **Environment Variables**
4. In the Environment Variables dialog box, check if the KRB5CCNAME variable appears in the System variables list. If the variable appears in the list, then select the variable and click **Delete**
5. Click **OK** to close the Environment Variables dialog box, and then click **OK** to close the System Properties dialog box.

## Setting Up the Kerberos Configuration File

### To set up the Kerberos configuration file:

1. Create a standard krb5.ini file and place it in the C:\Windows directory.
2. Ensure that the KDC and Admin server specified in the krb5.ini file can be resolved from your terminal. If necessary, modify "C:\Windows\System32\drivers\etc\hosts".

## Setting Up the JAAS Login Configuration File

### To set up the JAAS login configuration file:

1. Create a JAAS login configuration file that specifies a keytab file and "doNotPrompt=true"

For example:

```
Client {
    com.sun.security.auth.module.Krb5LoginModule required
        useKeyTab=true
        keyTab="PathToTheKeyTab"
        principal="cloudera@CLLOUDERA"
        doNotPrompt=true;
};
```

2. Set the java.security.auth.login.config environment variable to the location of the JAAS file.

For example: C:\KerberosLoginConfig.ini

## Authenticating to the Hive Server

### To authenticate to the Hive server:

- Use a connection string that has the following properties defined:
  - AuthMech
  - KrbHostFQDN
  - KrbRealm
  - KrbServiceName

For detailed information about these properties, see "Driver Configuration Options" on page 82.

## Using an Existing Subject to Authenticate the Connection

If the client application obtains a Subject with a TGT, then that Subject can be used to authenticate the connection to the server.

### To use an existing Subject to authenticate the connection:

1. Create a PrivilegedAction for establishing the connection to the database.

**For example:**

```
// Contains logic to be executed as a privileged action
public class AuthenticateDriverAction
implements PrivilegedAction<Void>
{
    // The connection, which is established as a
    // PrivilegedAction
    Connection con;

    // Define a string as the connection URL
    static String ConnectionURL =
    "jdbc:hive2://192.168.1.1:10000";

    /**
     * Logic executed in this method will have access to the
     * Subject that is used to "doAs". The driver will get
     * the Subject and use it for establishing a connection
     * with the server.
     */
    @Override
    public Void run()
    {
        try
        {
            // Establish a connection using the connection
            // URL
            con = DriverManager.getConnection(ConnectionURL);
        }
        catch (SQLException e)
        {
            // Handle errors that are encountered during
            // interaction with the data source
            e.printStackTrace();
        }
        catch (Exception e)
        {
            // Handle other errors
        }
    }
}
```



```
        e.printStackTrace();
    }
    return null;
}
}
```

2. Run the PrivilegedAction using the existing Subject, and then use the connection.

For example:

```
// Create the action
AuthenticateDriverAction authenticateAction = new
AuthenticateDriverAction();
// Establish the connection using the Subject for
// authentication.
Subject.doAs(loginConfig.getSubject(), authenticateAction);
// Use the established connection.
authenticateAction.con;
```

## Appendix C Driver Configuration Options

Appendix C lists and describes the properties that you can use to configure the behavior of the Cloudera JDBC Driver for Apache Hive.

**Note:**

You can set configuration properties using the connection URL. For more information, see "Using the Cloudera JDBC Driver for Apache Hive" on page 7.

### AllowSelfSignedCerts

Default Value	Required
0	No

#### Description

When this property is set to 0, the SSL certificate used by the server cannot be self-signed.

When this property is set to 1, the SSL certificate used by the server can be self-signed.

**Note:**

This property is applicable only when SSL connections are enabled.

### AuthMech

Default Value	Required
0	No

#### Description

The authentication mechanism to use. Set the value to one of the following numbers:

- **0** for No Authentication
- **1** for Kerberos
- **2** for User Name
- **3** for User Name and Password

### CAIssuedCertNamesMismatch

Default Value	Required
0	No

## Description

When this property is set to 0, the name of the CA-issued SSL certificate must match the host name of the Hive server.

When this property is set to 1, the names of the certificate and the host name of the server are allowed to mismatch.

**Note:**

This property is applicable only when SSL connections are enabled.

## CatalogSchemaSwitch

Default Value	Required
0	No

## Description

When this property is set to 1, the driver treats Hive catalogs as schemas as a restriction for filtering.

When this property is set to 0, Hive catalogs are treated as catalogs, and Hive schemas are treated as schemas.

## DecimalColumnScale

Default Value	Required
10	No

## Description

The maximum number of digits to the right of the decimal point for numeric data types.

## DefaultStringColumnLength

Default Value	Required
255	No

## Description

The maximum data length for STRING columns. The range of DefaultStringColumnLength is 0 to 32,767.

By default, the columns metadata for Hive does not specify a maximum data length for STRING columns.

## DelegationUID

Default Value	Required
None	No

### Description

Use this option to delegate all operations against Hive to a user that is different than the authenticated user for the connection.

**Note:**

This option is applicable only when connecting to a Hive Server 2 instance that supports this feature.

## KrbHostFQDN

Default Value	Required
None	Yes, if AuthMech=1 (Kerberos)

### Description

The fully qualified domain name of the Hive Server 2 host.

## KrbRealm

Default Value	Required
Depends on Kerberos configuration.	No

### Description

The realm of the Hive Server 2 host.

If your Kerberos configuration already defines the realm of the Hive Server 2 host as the default realm, then you do not need to configure this option.

**KrbServiceName**

Default Value	Required
None	Yes, if AuthMech=1 (Kerberos)

**Description**

The Kerberos service principal name of the Hive server.

**PreparedMetaLimitZero**

Default Value	Required
0	No

**Description**

When this property is set to 1, the `PreparedStatement.getMetadata()` call will request metadata from the server with "LIMIT 0".

**PWD**

Default Value	Required
None	Yes, if AuthMech=3 (User Name and Password)

**Description**

The password corresponding to the user name that you provided using the property "UID" on page 88.

**RowsFetchedPerBlock**

Default Value	Required
10000	No

**Description**

The maximum number of rows that a query returns at a time.

Any positive 32-bit integer is a valid value, but testing has shown that performance gains are marginal beyond the default value of 10000 rows.

## SocketTimeout

Default Value	Required
0	No

### Description

The number of seconds after which Hive closes the connection with the client application if the connection is idle. The default value of 0 indicates that an idle connection is not closed.

## SSL

Default Value	Required
0	No

### Description

When this property is set to 1, the driver communicates with the Hive server through an SSL-enabled socket.

When this property is set to 0, the driver does not connect to SSL-enabled sockets.

**Note:**

SSL is configured independently of authentication. When authentication and SSL are both enabled, the driver performs the specified authentication method over an SSL connection.

## SSLKeyStore

Default Value	Required
None	Yes, if SSL=1

### Description

The full path and file name of the Java KeyStore containing an SSL certificate to use during authentication.

See also the property "SSLKeyStorePwd" on page 87.

## SSLKeyStorePwd

Default Value	Required
None	Yes, if SSL=1

### Description

The password for accessing the Java KeyStore that you specified using the property "SSLKeyStore" on page 86.

## SSLTrustStore

Default Value	Required
jssecacerts, if it exists.  If jssecacerts does not exist, then cacerts is used. The default location of cacerts is jre\lib\security\	No

### Description

The full path and file name of the Java TrustStore containing an SSL certificate to use during authentication.

See also the property "SSLTrustStorePwd" on page 87.

## SSLTrustStorePwd

Default Value	Required
None	Yes, if using a TrustStore.

### Description

The password for accessing the Java TrustStore that you specified using the property "SSLTrustStore" on page 87.

**UID**

Default Value	Required
hive	Yes, if AuthMech=3 (User Name and Password)  No, if AuthMech=2 (User Name)

**Description**

The user name that you use to access the Hive server.

**UseNativeQuery**

Default Value	Required
0	No

**Description**

When this option is enabled (1), the driver does not transform the queries emitted by an application, so the native query is used.

When this option is disabled (0), the driver transforms the queries emitted by an application and converts them into an equivalent form in HiveQL.

**Note:**

If the application is Hive-aware and already emits HiveQL, then enable this option to avoid the extra overhead of query transformation.

**zk**

Default Value	Required
None	No

**Description**

The connection string to one or more ZooKeeper quorums, written in the following format:

*ZK\_IP:ZK\_Port/ZK\_Namespace*

For example:

`jdbc:hive2://zk=192.168.0.1:2181/hiveserver2`



Use this option to enable the Dynamic Service Discovery feature, which allows you to connect to Hive servers that are registered against a ZooKeeper service by connecting to the ZooKeeper service.

You can specify multiple quorums in a comma-separated list. If connection to a quorum fails, the driver will attempt to connect to the next quorum in the list.