

Cloudera ODBC Driver for Apache Hive Version 2.5.12



Important Notice

© 2010-2014 Cloudera, Inc. All rights reserved.

Cloudera, the Cloudera logo, Cloudera Impala, Impala, and any other product or service names or slogans contained in this document, except as otherwise disclaimed, are trademarks of Cloudera and its suppliers or licensors, and may not be copied, imitated or used, in whole or in part, without the prior written permission of Cloudera or the applicable trademark holder.

Hadoop and the Hadoop elephant logo are trademarks of the Apache Software Foundation. All other trademarks, registered trademarks, product names and company names or logos mentioned in this document are the property of their respective owners. Reference to any products, services, processes or other information, by trade name, trademark, manufacturer, supplier or otherwise does not constitute or imply endorsement, sponsorship or recommendation thereof by us.

Complying with all applicable copyright laws is the responsibility of the user. Without limiting the rights under copyright, no part of this document may be reproduced, stored in or introduced into a retrieval system, or transmitted in any form or by any means (electronic, mechanical, photocopying, recording, or otherwise), or for any purpose, without the express written permission of Cloudera.

Cloudera may have patents, patent applications, trademarks, copyrights, or other intellectual property rights covering subject matter in this document. Except as expressly provided in any written license agreement from Cloudera, the furnishing of this document does not give you any license to these patents, trademarks copyrights, or other intellectual property.

The information in this document is subject to change without notice. Cloudera shall not be liable for any damages resulting from technical errors or omissions which may be present in this document, or from use of this document.

Cloudera, Inc.
1001 Page Mill Road, Building 2
Palo Alto, CA 94304-1008
info@cloudera.com
US: 1-888-789-1488
Intl: 1-650-843-0595
www.cloudera.com

Release Information

Version: 2.5.12

Date: September 19, 2014

Table of Contents

- INTRODUCTION..... 1**
- WINDOWS DRIVER..... 1**
 - SYSTEM REQUIREMENTS 1
 - INSTALLING THE DRIVER 2
 - CONFIGURING ODBC CONNECTIONS 2
 - CONFIGURING AUTHENTICATION 8
 - Using No Authentication* 8
 - Using Kerberos* 8
 - Using User Name* 9
 - Using User Name and Password* 9
 - Using User Name and Password (SSL)* 9
 - Using Windows Azure HDInsight Emulator* 10
 - Using Windows Azure HDInsight Service* 10
 - Using HTTP* 10
 - Using HTTPS* 10
 - Using Kerberos over HTTP* 11
 - Using Kerberos over HTTPS* 12
 - CONFIGURING DSN-LESS AUTHENTICATION 13
- LINUX DRIVER 14**
 - SYSTEM REQUIREMENTS 14
 - INSTALLATION 14
 - Setting the LD_LIBRARY_PATH Environment Variable* 15
- MAC OS X DRIVER 16**
 - SYSTEM REQUIREMENTS 16
 - INSTALLATION 16
 - Setting the DYLD_LIBRARY_PATH Environment Variable* 16
- AIX DRIVER 17**
 - SYSTEM REQUIREMENTS 17
 - INSTALLATION 17
 - SETTING THE LD_LIBRARY_PATH ENVIRONMENT VARIABLE 18

CONFIGURING ODBC CONNECTIONS FOR LINUX, MAC OS X AND AIX	18
FILES.....	18
SAMPLE FILES.....	18
CONFIGURING THE ENVIRONMENT.....	18
CONFIGURING THE ODBC.INI FILE.....	19
CONFIGURING THE ODBCINST.INI FILE.....	20
CONFIGURING THE CLUDERA.HIVEODBC.INI FILE.....	21
CONFIGURING AUTHENTICATION.....	22
<i>Using No Authentication</i>	22
<i>Using Kerberos</i>	23
<i>Using User Name</i>	23
<i>Using User Name and Password</i>	23
<i>Using User Name and Password (SSL)</i>	23
<i>Using HTTP</i>	24
<i>Using HTTPS</i>	24
<i>Using Kerberos over HTTP</i>	25
<i>Using Kerberos over HTTPS</i>	25
FEATURES	26
SQL QUERY VERSUS HIVEQL QUERY.....	26
SQL CONNECTOR.....	27
DATA TYPES.....	27
CATALOG AND SCHEMA SUPPORT.....	28
HIVE SYSTEM TABLE.....	28
SERVER-SIDE PROPERTIES.....	28
ACTIVE DIRECTORY.....	28
GET TABLES WITH QUERY.....	28
TEMPORARY TABLE.....	29
CONTACT US	29
APPENDIX A: AUTHENTICATION OPTIONS	30
USING NO AUTHENTICATION.....	32
USING KERBEROS.....	32
USING USER NAME.....	32

USING USER NAME AND PASSWORD.....	32
USING USER NAME AND PASSWORD (SSL)	32
USING HTTP.....	32
USING HTTPS.....	32
USING KERBEROS OVER HTTP	32
USING KERBEROS OVER HTTPS	33
APPENDIX B: CONFIGURING KERBEROS AUTHENTICATION FOR WINDOWS.....	34
ACTIVE DIRECTORY	34
MIT KERBEROS.....	34
<i>Download and install MIT Kerberos for Windows 4.0.1.....</i>	<i>34</i>
<i>Set up the Kerberos configuration file in the default location</i>	<i>34</i>
<i>Set up the Kerberos configuration file in another location</i>	<i>34</i>
<i>Set up the Kerberos credential cache file.....</i>	<i>35</i>
<i>Obtain a ticket for a Kerberos principal using password</i>	<i>35</i>
<i>Obtain a ticket for a Kerberos principal using a keytab file</i>	<i>36</i>
<i>Obtain a ticket for a Kerberos principal using the default keytab file.....</i>	<i>36</i>
APPENDIX C: DRIVER CONFIGURATION OPTIONS.....	38
APPENDIX D: TEMPORARY TABLE CREATE TABLE AND INSERT STATEMENTS	49
TEMPORARY TABLE CREATE TABLE STATEMENT	49
TEMPORARY TABLE INSERT STATEMENT.....	49
APPENDIX E: ODBC API CONFORMANCE LEVEL	51

Introduction

Welcome to the Cloudera ODBC Driver for Hive. ODBC is one of the most established and widely supported APIs for connecting to and working with databases. At the heart of the technology is the ODBC driver, which connects an application to the database.

Cloudera ODBC Driver for Hive is used for direct SQL and HiveQL access to Apache Hadoop / Hive distributions, enabling Business Intelligence (BI), analytics and reporting on Hadoop / Hive-based data. The driver efficiently transforms an application's SQL query into the equivalent form in HiveQL. Hive Query Language is a subset of SQL-92. If an application is Hive-aware, then the driver is configurable to pass the query through. The driver interrogates Hive to obtain schema information to present to a SQL-based application. Queries, including joins, are translated from SQL to HiveQL. For more information about the differences between HiveQL and SQL, refer to the section "Features" on page 26.

Cloudera ODBC Driver for Hive is available for Microsoft Windows, Linux, and Mac OS X. It complies with the ODBC 3.52 data standard and adds important functionality such as Unicode and 32- and 64-bit support for high-performance computing environments on all platforms. Any version of the ODBC driver will connect to a Hive server irrespective of the server's host OS.

This guide is suitable for users who are looking to access data residing within Hive from their desktop environment. Application developers may also find the information helpful. Refer to your application for details on connecting via ODBC.

Windows Driver

System Requirements

You install Cloudera ODBC Driver for Hive on client computers accessing data in a Hadoop cluster with the Hive service installed and running. Each computer where you install the driver must meet the following minimum system requirements:

- One of the following operating systems (32- and 64-bit editions are supported):
 - Windows® XP with SP3
 - Windows® Vista
 - Windows® 7 Professional
 - Windows® Server 2008 R2
- 25 MB of available disk space

The driver is suitable for use with all versions of Apache Hive.

Important:

To install the driver, you need Administrator privileges on the computer.

Installing the Driver

On 64-bit Windows operating systems, you can execute 32- and 64-bit applications transparently. You must use the version of the driver matching the bitness of the client application accessing data in Hadoop / Hive:

- **ClouderaHiveODBC32.msi** for 32-bit applications
- **ClouderaHiveODBC64.msi** for 64-bit applications

You can install both versions of the driver on the same computer.

Note:

For an explanation of how to use ODBC on 64-bit editions of Windows, see

<http://www.simba.com/wp-content/uploads/2010/10/HOW-TO-32-bit-vs-64-bit-ODBC-Data-Source-Administrator.pdf>

To install Cloudera ODBC Driver for Hive:

1. Depending on the bitness of your client application, double-click to run **ClouderaHiveODBC32.msi** or **ClouderaHiveODBC64.msi**.
2. Click **Next**.
3. Select the check box to accept the terms of the License Agreement if you agree, and then click **Next**.
4. To change the installation location, click the **Change** button, then browse to the desired folder, and then click **OK**. To accept the installation location, click **Next**.
5. Click **Install**.
6. When the installation completes, click **Finish**.

Configuring ODBC Connections

To create a Data Source Name (DSN):

1. Click the **Start** button , then click **All Programs**, then click the **Cloudera ODBC Driver for Apache Hive 2.5 (64-bit)** or the **Cloudera ODBC Driver for Apache Hive 2.5 (32-bit)** program group.

If you installed both versions of the driver, you will see two program groups. Because DSNs are bit-specific, select the version that matches the bitness of your application. For example, a DSN that is defined for the 32-bit driver will only be accessible from 32-bit applications.

2. Click **64-bit ODBC Administrator** or **32-bit ODBC Administrator**.
The ODBC Data Source Administrator window opens.
3. Click the **Drivers** tab and verify that the Cloudera Hive ODBC Driver appears in the list of ODBC drivers that are installed on your system.
4. Click the **System DSN** tab to create a system DSN or click the **User DSN** tab to create a user DSN.

Note:

A system DSN is available for all users who log in to a workstation. A user DSN is available only to the user who creates the DSN.

5. Click **Add**.
The Create New Data Source window opens.
6. Select **Cloudera ODBC Driver for Apache Hive** and then click **Finish**.
The Cloudera Hive ODBC Driver DSN Setup window opens.
7. Use the options in the Cloudera Hive ODBC Driver DSN Setup window to configure your DSN:
 - a. In the **Data Source Name** field, type a name for your DSN.
 - b. Optionally, in the **Description** field, type a description.
 - c. In the **Host** field, type the IP address or hostname of the Hive server.
 - d. In the **Port** field, type the listening port for the service.
 - e. In the **Database** field, type the name of the database schema to use when a schema is not explicitly specified in a query. Queries on other schemas can still be issued by explicitly specifying the schema in the query. To determine the appropriate database schema to use, type the show databases command at the Hive command prompt to inspect your databases.
 - f. Click the drop-down arrow next to the Hive Server Type field and select either **Hive Server 1** or **Hive Server 2**.
 - g. Optionally, if the operations against Hive are to be done on behalf of a user that is different than the authenticated user for the connection, enter the user name of the user to be delegated in the **Delegation UID** text box.

Note:

This setting is only applicable when connecting to a Hive Server 2 that supports this feature. Otherwise this setting will not take any effect.

8. Optionally, if you selected Hive Server 2 as the Hive server type, you can configure authentication. For detailed instructions, refer to the section “Configuring Authentication” on page 8.
9. Optionally, in the Cloudera Hive ODBC Driver DSN Setup window, click **Advanced Options** to configure advanced options for your DSN:
 - a. Select the **Use Native Query** check box to disable the SQL Connector feature.

Note:

The SQL Connector feature allows the driver to apply transformations to the queries emitted by an application to convert them into an equivalent form in HiveQL. If the application is Hive aware and already emits HiveQL, then turning off the SQL Connector feature avoids the extra overhead of query transformation.

- b. Select the **Fast SQLPrepare** check box to defer query execution to SQLExecute.

Note:

When using Native Query mode, the driver will execute the HiveQL query to retrieve the result set metadata for SQLPrepare. As a result, SQLPrepare might be slow. If the result set metadata is not required after calling SQLPrepare, then enable this option.

- c. Select the **Driver Config Take Precedence** check box to allow driver-wide configurations to take precedence over connection string and DSN settings.
- d. Select the **Use Async Exec** check box to use the asynchronous version of the Hive client API call for executing a query.

Note:

This setting only takes effect when connecting to a Hive cluster running Hive 0.12.0 or higher.

Note:

Due to a problem in Hive 0.12.0 (see <https://issues.apache.org/jira/browse/HIVE-5230>), Hive returns generic error messages for errors that occur during query execution when using asynchronous query execution. To see the actual error message relevant to the problem, turn off asynchronous query execution and execute the query again.

- e. Select the **Get Tables With Query** check box to retrieve the names of tables in a particular database using the GET TABLES query when retrieving metadata from Hive Server 2.

Note:

This setting is only applicable when connecting to Hive Server 2.

- f. Select the **Unicode SQL character types** check box to enable the driver to return SQL_WVARCHAR instead of SQL_VARCHAR for STRING and VARCHAR columns, and SQL_WCHAR instead of SQL_CHAR for CHAR columns.
- g. Select the **Show HIVE_SYSTEM Table** check box to enable the driver to return the HIVE_SYSTEM table for catalog function calls such as SQLTables and SQLColumns.
- h. In the **Rows Fetched Per Block** field, type the number of rows to be fetched per block.

Note:

Any positive 32-bit integer is a valid value but testing has shown that performance gains are marginal beyond the default value of 10000 rows.

- i. In the **Default String Column Length** field, type the default string column length to use.

Note:

Hive does not provide the length for String columns in its column metadata. This option allows you to tune the length of String columns.

- j. In the **Binary column length** field, type the maximum data length for binary columns.

Note:

Hive does not provide the maximum data length for binary columns in the columns metadata. The option allows you to tune the maximum data length for binary columns.

- k. In the **Decimal Column Scale** field, type the maximum number of digits to the right of the decimal point for numeric data types.

Note:

This setting only takes effect when connecting to a server running Hive earlier than 0.12.0. For Hive 0.12.0 and later, the driver uses the DECIMAL(p,s) semantic and the values for precision and scale are retrieved from the server.

- l. In the **Async Exec Poll Interval** field, type the time in milliseconds between each poll of the query execution status.

Note:

Asynchronous query execution is only available starting with Hive 0.12.0.

- m. To allow the common name of a CA-issued SSL certificate to not match the hostname of the Hive server, select the **Allow Common Name Hostname Mismatch** check box.

Note:

This setting is only applicable to the **User Name and Password (SSL) authentication** mechanism and will be ignored by other authentication mechanisms.

- n. In the **Trusted Certificate** field, enter the path to the file containing the list of trusted CA certificates in the PEM format.

Note:

This is only applicable to the **User Name and Password (SSL)** and **HTTPS** authentication mechanisms, and will be ignored by other authentication mechanisms.

Note:

SSL certificates in the trusted certificates file have to be in the **PEM** format.

Note:

If this setting is not set the driver will default to using the trusted CA certificates PEM file installed by the driver.

10. Optionally, in the Advanced Options window, click **Server Side Properties** to configure server-side properties for your DSN:

- a. To create a server-side property, click the **Add** button, then type appropriate values in the Key and Value fields, and then click **OK**

OR

To edit a server-side property, select the property from the list, then click the **Edit** button, then update the Key and Value fields as needed, and then click **OK**

OR

To delete a server-side property, select the from the list, and then click the **Remove** button. In the confirmation dialog, click **Yes**

Note:

For a list of all Hadoop and Hive server-side properties that your implementation supports, type `set -v` at the Hive CLI command line or Beeline. You can also execute the `set -v` query after connecting using the driver.

- b. If you selected Hive Server 2 as the Hive server type, then select or clear the **Apply Server Side Properties with Queries** check box as needed.

Note:

If you selected Hive Server 2, then the Apply Server Side Properties with Queries check box is selected by default. Selecting the check box configures the driver to apply each server-side property you set by executing a query when opening a session to the Hive server. Clearing the check box configures the driver to use a more efficient method to apply server-side properties that does not involve additional network round tripping. Some Hive Server 2 builds are not compatible with the more efficient method. If the server-side properties you set do not take effect when the check box is clear, then select the check box. If you selected Hive Server 1 as the Hive server type, then the **Apply Server Side Properties with Queries** check box is selected and unavailable.

- c. Select the **Convert SSP Key Name to Lower Case** check box to force the driver to convert the server-side property key name to all lower case characters.
 - d. Click **OK**
11. Optionally, in the Advanced Options window, click **Temporary Table Configuration** to configure the Temporary Table feature for your DSN:
 - a. Select the **Enable Temporary Table** check box to enable the temporary table feature.
 - b. In the **Web HDFS Host** text box, enter the hostname or IP address of the machine hosting both the NameNode of your Hadoop cluster and the WebHDFS service. If this field is left blank the hostname of the Hive Server will be used.
 - c. In the **Web HDFS Port** text box, enter the WebHDFS port for the NameNode.
 - d. In the **HDFS User** text box, enter the name of the HDFS user that the driver will use to create the necessary files for supporting the Temporary Table feature.
 - e. In the **Data file HDFS dir** text box, enter the HDFS directory that the driver will use to store the necessary files for supporting the Temporary Table feature.

Note:

Due to a problem in Hive (see <https://issues.apache.org/jira/browse/HIVE-4554>), space characters in HDFS path will not work with versions of Hive prior to 0.12.0.

- f. In the **Temp Table TTL** text box, enter the number of minutes a temporary table is guaranteed to exist in Hive after it is created.
 - g. Click **OK**.
12. In the Advanced Options Window, click **OK**.
 13. In the Cloudera Hive ODBC Driver DSN Setup window, click **Test** to test the connection, and then click **OK**.

For details on configuration options available to control the behavior of DSNs using Cloudera ODBC Driver for Hive, see “Appendix C: Driver Configuration Options” on page 38.

Configuring Authentication

For details on selecting the appropriate authentication for a DSN using Cloudera ODBC Driver for Hive, see “Appendix A: Authentication Options” on page 30. The authentication methods available are as follows:

- No Authentication
- Kerberos
- User Name
- User Name and Password
- HTTP
- HTTPS
- Kerberos over HTTP
- Kerberos over HTTPS

Using No Authentication

No additional details are required when using **No Authentication**.

Using Kerberos

To use **Kerberos** authentication, Kerberos must be configured prior to use. See “Appendix B: Configuring Kerberos Authentication for Windows” on page 34 for details.

After Kerberos has been installed and configured, then set the following options in the **Authentication** group in the Cloudera Hive ODBC Driver dialog box:

1. In the **Mechanism** field, select **Kerberos**.
2. If there is no default realm configured for your Kerberos setup, then type the value for the Kerberos realm of the Hive Server 2 host. Otherwise leave it blank. The **Realm** is only needed if

your Kerberos setup does not define a default realm or if the realm of your Hive Server 2 is not the default.

3. In the **Host FQDN** field, type the value for the fully qualified domain name of the Hive Server 2 host.
4. In the **Service Name** field, type the value for the service name of the Hive Server 2. For example, if the principle for the Hive Server 2 is "hive/[fully.qualified.domain.name@YOUR-REALM.COM](#)", then the value in the service name field should be **hive**. If you are unsure of the correct service name to use for your particular Hadoop deployment, see your Hadoop administrator.

Using User Name

For **User Name** authentication, select **User Name** in the **Mechanism** field in the **Cloudera Hive ODBC Driver** dialog box, and then type a user name in the **User Name** field.

Using User Name and Password

To configure your DSN for **User Name and Password** authentication:

1. In the Cloudera Hive ODBC Driver DSN Setup dialog, click the drop-down arrow next to the **Mechanism** field, and then select **User Name and Password**.
2. In the **User Name** field, type an appropriate credential.
3. In the **Password** field, type the password corresponding to the user name you typed in step 2.

Using User Name and Password (SSL)

To configure **User Name and Password (SSL)** authentication:

1. Click the drop-down arrow next to the **Mechanism** field, and then select **User Name and Password (SSL)**.
2. In the **User Name** field, type an appropriate credential.
3. In the **Password** field, type the password corresponding to the user name you typed in step 2.

Note:

The driver always accepts the use of self-signed SSL certificate for this authentication mechanism.

Note:

Optionally you can configure the **Allow Common Name Host Name Mismatch** setting to control whether the driver allows the common name of a CA issued certificate to not match the host name of the Hive server. For self-signed certificates the driver always allows the common name of the certificate to not match the host name.

Note:

Optionally, you can configure the **Trusted Certificates** setting to specify the file listing the SSL certificate authorities (CAs) you would like the driver to trust. The content of this file should be the CAs' certificates encoded in PEM format. These trusted CA certificates are used by the driver during SSL handshake to verify the server certificate and determine if the server can be trusted. By default, the driver trusts the certificate authorities listed in the cacerts.pem file that comes with the driver.

Using Windows Azure HDInsight Emulator

This authentication mechanism is not supported in **Cloudera's Distribution Including Apache Hadoop**.

Using Windows Azure HDInsight Service

This authentication mechanism is not supported in **Cloudera's Distribution Including Apache Hadoop**.

Using HTTP

To configure **HTTP** authentication:

1. In the Cloudera Hive ODBC Driver DSN Setup dialog, click the drop-down arrow next to the **Mechanism** field in the **Authentication** area, and then select **HTTP**.
2. In the **HTTP Path** field, type the partial URL corresponding to the Hive server.

Note:

HTTP is only available starting with Hive 0.12.0.

Using HTTPS

To use **HTTPS** authentication:

1. In the Cloudera Hive ODBC Driver DSN Setup dialog, click the drop-down arrow next to the **Mechanism** field in the **Authentication** area, and then select **HTTPS**.
2. In the **HTTP Path** field, type the partial URL corresponding to the Hive server.
3. In the **User Name** field, type an appropriate user name for accessing the Hive server.
4. In the **Password** field, type the password corresponding to the user name you typed in step 3.

Note:

HTTPS is only available starting with Hive 0.13.0.

Note:

The driver always accepts the use of self-signed SSL certificate for this authentication mechanism.

Note:

Optionally, you can configure the **Allow Common Name Host Name Mismatch** setting to control whether the driver allows the common name of a CA issued certificate to not match the host name of the Hive server. For self-signed certificates, the driver always allows the common name of the certificate to not match the host name.

Note:

Optionally, you can configure the **Trusted Certificates** setting to specify the file listing the SSL certificate authorities (CAs) you would like the driver to trust. The content of this file should be the CAs' certificates encoded in PEM format. These trusted CA certificates are used by the driver during SSL handshake to verify the server certificate and determine if the server can be trusted. By default, the driver trusts the certificate authorities listed in the cacerts.pem file that comes with the driver.

Using Kerberos over HTTP

To use **Kerberos** authentication, Kerberos must be configured prior to use. See “Appendix B: Configuring Kerberos Authentication for Windows” on page 34 for details.

After Kerberos has been installed and configured, then set the following options in the **Authentication** group in the Cloudera Hive ODBC Driver dialog box:

1. In the **Mechanism** field, select **Kerberos over HTTP**.
2. If there is no default realm configured for your Kerberos setup, then type the value for the Kerberos realm of the Hive Server 2 host. Otherwise leave it blank. The **Realm** is only needed if your Kerberos setup does not define a default realm or if the realm of your Hive Server 2 is not the default.
3. In the **Host FQDN** field, type the value for the fully-qualified domain name of the Hive Server 2 host.
4. In the **Service Name** field, type the value for the service name of the Hive Server 2. For example, if the principle for the Hive Server 2 is "hive/[fully.qualified.domain.name@YOUR-REALM.COM](#)", then the value in the service name field should be **hive**. If you are unsure of the correct service name to use for your particular Hadoop deployment, see your Hadoop administrator.
5. In the **HTTP Path** field, type the partial URL corresponding to the Hive server.

Note:

Kerberos over HTTP is only available starting with Hive 0.13.0.

Using Kerberos over HTTPS

To use **Kerberos** authentication, Kerberos must be configured prior to use. See “Appendix B: Configuring Kerberos Authentication for Windows” on page 34 for details.

After Kerberos has been installed and configured, then set the following options in the **Authentication** group in the Cloudera Hive ODBC Driver dialog box:

1. In the **Mechanism** field, select **Kerberos over HTTPS**.
2. If there is no default realm configured for your Kerberos setup, then type the value for the Kerberos realm of the Hive Server 2 host. Otherwise leave it blank. The **Realm** is only needed if your Kerberos setup does not define a default realm or if the realm of your Hive Server 2 is not the default.
3. In the **Host FQDN** field, type the value for the fully-qualified domain name of the Hive Server 2 host.
4. In the **Service Name** field, type the value for the service name of the Hive Server 2. For example, if the principle for the Hive Server 2 is "hive/[fully.qualified.domain.name@YOUR-REALM.COM](#)", then the value in the service name field should be **hive**. If you are unsure of the correct service name to use for your particular Hadoop deployment, see your Hadoop administrator.
5. In the **HTTP Path** field, type the partial URL corresponding to the Hive server.

Note:

Kerberos over HTTPS is only available starting with Hive 0.13.0.

Note:

The driver always accepts the use of self-signed SSL certificate for this authentication mechanism.

Note:

Optionally, you can configure the **Allow Common Name Host Name Mismatch** setting to control whether the driver allows the common name of a CA issued certificate to not match the host name of the Hive server. For self-signed certificates, the driver always allows the common name of the certificate to not match the host name.

Note:

Optionally, you can configure the **Trusted Certificates** setting to specify the file listing the SSL certificate authorities (CAs) you would like the driver to trust. The content of this file should be the CAs' certificates encoded in PEM format. These trusted CA certificates are used by the driver during SSL handshake to verify the server certificate and determine if the server can be trusted. By default, the driver trusts the certificate authorities listed in the cacerts.pem file that comes with the driver.

Configuring DSN-Less Authentication


Some client applications, such as Tableau, provide some support for connecting to a data source using a driver without a DSN.

Applications that connect using ODBC data sources work with Hive Server 2 by sending the appropriate authentication credentials defined in the data source. Applications that are Hive Server 1 aware but not Hive Server 2 aware and that connect using a DSN-less connection will *not* have a facility for sending authentication credentials to Hive Server 2. However, you can configure Cloudera ODBC Driver for Hive with authentication credentials using the Driver Configuration tool.

Important:

Credentials defined in a data source take precedence over credentials configured using the Driver Configuration tool. Credentials configured using the Driver Configuration tool apply for all connections made using a DSN-less connection unless the client application is Hive Server 2 aware and requests credentials from the user.

To configure driver authentication for a DSN-less connection:

1. Click the **Start** button .
2. Click **All Programs**.
3. Click the **Cloudera ODBC Driver for Apache Hive 2.5 (64-bit)** or the **Cloudera ODBC Driver for Apache Hive 2.5 (32-bit)** program group. If you installed both versions of the driver, you will see two program groups.

Because drivers are bit-specific, select the version that matches the bitness of your application. For example, a 32-bit driver will only be accessible from 32-bit applications.
4. Click **Driver Configuration**, and then click **OK** if prompted for administrator permission to make modifications to the computer.

Note:

You must have administrator access to the computer in order to run this application because it makes changes to the registry.

Linux Driver

5. Follow the procedure for configuring the Advanced Options on page 3 and the section “Configuring Authentication” on page 8 to complete the Cloudera Hive ODBC Driver Configuration dialog.
6. In the Cloudera Hive ODBC Driver Configuration dialog, click **OK**.

Linux Driver

System Requirements

- One of the following distributions (32- and 64-bit editions are supported):
 - Red Hat® Enterprise Linux® (RHEL) 5.0/6.0
 - CentOS 5.0/6.0
 - SUSE Linux Enterprise Server (SLES) 11
- 45 MB of available disk space.
- An installed ODBC driver manager:
 - iODBC 3.52.7 or above
 - OR
 - unixODBC 2.2.12 or above

Cloudera ODBC Driver for Hive requires a Hadoop cluster with the Hive service installed and running. Cloudera ODBC Driver for Hive is suitable for use with all versions of Hive.

Installation

There are two versions of the driver for Linux:

- **ClouderaHiveODBC-Version-Release.i686.rpm** for 32-bit
- **ClouderaHiveODBC-Version-Release.x86_64.rpm** for 64-bit

The version of the driver that you select should match the bitness of the client application accessing your Hadoop / Hive-based data. For example, if the client application is 64-bit, then you should install the 64-bit driver. Note that 64-bit editions of Linux support both 32- and 64-bit applications. Verify the bitness of your intended application and install the appropriate version of the driver.

Important:

Ensure that you install the driver using the RPM corresponding to your Linux distribution.

Cloudera ODBC Driver for Hive driver files are installed in the following directories:

- **/opt/cloudera/hiveodbc/ErrorMessage**—Error messages files directory
- **/opt/cloudera/hiveodbc/Setup**—Sample configuration files directory
- **/opt/cloudera/hiveodbc/lib/32**—32-bit shared libraries directory

- `/opt/cloudera/hiveodbc/lib/64`—64-bit shared libraries directory

To install Cloudera ODBC Driver for Hive:

- In Red Hat Enterprise Linux 5.0/6.0 or CentOS 5.0/6.0, log in as the root user, then navigate to the folder containing the driver RPM packages to install, and then type the following at the command line, where *RPMFileName* is the file name of the RPM package containing the version of the driver that you want to install:

```
yum --nogpgcheck localinstall RPMFileName
```

OR

In SUSE Linux Enterprise Server 11, log in as the root user, then navigate to the folder containing the driver RPM packages to install, and then type the following at the command line, where *RPMFileName* is the file name of the RPM package containing the version of the driver that you want to install:

```
zypper install RPMFileName
```

Cloudera ODBC Driver for Hive depends on the following resources:

- `cyrus-sasl-2.1.22-7` or above
- `cyrus-sasl-gssapi-2.1.22-7` or above
- `cyrus-sasl-plain-2.1.22-7` or above

If the package manager in your Linux distribution cannot resolve the dependencies automatically when installing the driver, then download and manually install the packages required by the version of the driver that you want to install.

Setting the `LD_LIBRARY_PATH` Environment Variable

The `LD_LIBRARY_PATH` environment variable must include the path to the installed ODBC driver manager libraries.

For example, if you are using a 64-bit client application and ODBC driver manager libraries are installed in `/usr/local/lib`, then set `LD_LIBRARY_PATH` as follows:

```
export LD_LIBRARY_PATH=$LD_LIBRARY_PATH:/usr/local/lib
```

Refer to your Linux shell documentation for details on how to set environment variables permanently.

For details on creating ODBC connections using Cloudera ODBC Driver for Hive, see “Configuring ODBC Connections for Linux, Mac OS X and AIX” on page 18.

Mac OS X Driver

System Requirements

- Mac OS X version 10.6.8 or later
- 100 MB of available disk space
- iODBC 3.52.7 or above

Cloudera ODBC Driver for Hive requires a Hadoop cluster with the Hive service installed and running.

Cloudera ODBC Driver for Hive is suitable for use with all versions of Hive. The driver supports both 32- and 64-bit client applications.

Installation

Cloudera ODBC Driver for Hive driver files are installed in the following directories:

- **/opt/cloudera/hiveodbc/ErrorMessages**—Error messages files directory
- **/opt/cloudera/hiveodbc/Setup**—Sample configuration files directory
- **/opt/cloudera/hiveodbc/lib/universal**—Binaries directory

To install Cloudera ODBC Driver for Hive:

1. Double-click to mount the **ClouderaHiveODBC.dmg** disk image.
2. Double-click **ClouderaHiveODBC.pkg** to run the Installer.
3. Follow the instructions in the Installer to complete the installation process.
4. When the installation completes, click **Close**.

Setting the DYLD_LIBRARY_PATH Environment Variable

The DYLD_LIBRARY_PATH environment variable must include the path to the installed ODBC driver manager libraries.

For example, if ODBC driver manager libraries are installed in `/usr/local/lib`, then set DYLD_LIBRARY_PATH as follows:

```
export DYLD_LIBRARY_PATH=$DYLD_LIBRARY_PATH:/usr/local/lib
```

Refer to your Mac OS X shell documentation for details on how to set environment variables permanently.

For details on creating ODBC connections using Cloudera ODBC Driver for Hive, see “Configuring ODBC Connections for Linux, Mac OS X and AIX” on page 18.

AIX Driver

System Requirements

- IBM AIX 5.3, 6.1, or 7.1 (32- and 64-bit editions are supported)
- 150 MB of available disk space
- An installed ODBC driver manager:
 - iODBC 3.52.7 or above
 - OR
 - unixODBC 2.3.0 or above

Cloudera ODBC Driver for Hive requires a Hadoop cluster with the Hive service installed and running.

The driver is suitable for use with all versions of Hive.

Installation

There are two versions of the driver for AIX:

- **ClouderaHiveODBC-32bit-Version-Release.ppc.rpm** for 32-bit
- **ClouderaHiveODBC-Version-Release.ppc.rpm** for 64-bit

The version of the driver that you select should match the bitness of the client application accessing your Hadoop / Hive-based data. For example, if the client application is 64-bit, then you should install the 64-bit driver. Note that 64-bit editions of AIX support both 32- and 64-bit applications. Verify the bitness of your intended application and install the appropriate version of the driver.

Cloudera ODBC Driver for Hive driver files are installed in the following directories:

- **/opt/cloudera/hiveodbc/ErrorMessage**—Error messages files directory
- **/opt/cloudera/hiveodbc/Setup**—Sample configuration files directory
- **/opt/cloudera/hiveodbc/lib/32**—32-bit shared libraries directory
- **/opt/cloudera/hiveodbc/lib/64**—64-bit shared libraries directory

To install Cloudera ODBC Driver for Hive:

1. Log in as root user, then navigate to the folder containing the driver RPM packages to install, and then type the following at the command line, where *RPMFileName* is the file name of the RPM package containing the version of the driver that you want to install:

```
rpm --install RPMFileName
```

Setting the LD_LIBRARY_PATH Environment Variable

The LD_LIBRARY_PATH environment variable must include the path to the installed ODBC driver manager libraries.

For details on creating ODBC connections using Cloudera ODBC Driver for Hive, see “Configuring ODBC Connections for Linux, Mac OS X and AIX” on page 18.

Configuring ODBC Connections for Linux, Mac OS X and AIX

Files

ODBC driver managers use configuration files to define and configure ODBC data sources and drivers. By default, the following configuration files residing in the user’s home directory are used:

- **.odbc.ini** – The file used to define ODBC data sources (required)
- **.odbcinst.ini** – The file used to define ODBC drivers (optional)

By default, the **cloudera.hiveodbc.ini** in the `/opt/cloudera/hiveodbc/lib/32` directory for 32-bit AIX/Linux drivers, `/opt/cloudera/hiveodbc/lib/64` directory for 64-bit AIX/Linux drivers or `/opt/cloudera/hiveodbc/lib/universal` directory for Mac OS X driver is used to configure Cloudera ODBC Driver for Hive (required).

Sample Files

The driver installation contains the following sample configuration files in the Setup directory:

- **odbc.ini**
- **odbcinst.ini**

The names of the sample configuration files do not begin with a period (.) so that they will appear in directory listings by default. A filename beginning with a period (.) is hidden. For `odbc.ini` and `odbcinst.ini`, if the default location is used, then the filenames must begin with a period (.).

If the configuration files do not already exist in the user’s home directory, then the sample configuration files can be copied to that directory and renamed. If the configuration files already exist in the user’s home directory, then the sample configuration files should be used as a guide for modifying the existing configuration files.

Configuring the Environment

By default, the configuration files reside in the user’s home directory. However, two environment variables, `ODBCINI` and `ODBCSYSINI`, can be used to specify different locations for the `odbc.ini` and `odbcinst.ini` configuration files. Set `ODBCINI` to point to your `odbc.ini` file. Set `ODBCSYSINI` to point to the directory containing the `odbcinst.ini` file.

The driver’s configuration file (`cloudera.hiveodbc.ini`) is installed to the driver’s `lib` directory and used by the driver by default. The `CLOUDERAHIVEINI` environment variable can be used to specify a different location for the `cloudera.hiveodbc.ini` file.

For example, if your `odbc.ini` and `cloudera.hiveodbc.ini` files are located in `/etc` and your `odbcinst.ini` file is located in `/usr/local/odbc`, then set the environment variables as follows:

```
export ODBCINI=/etc/odbc.ini
export ODBCSYSINI=/usr/local/odbc
export CLODERAHIVEINI=/etc/cloudera.hiveodbc.ini
```

The search order for the `cloudera.hiveodbc.ini` file is as follows:

1. If the `CLODERAHIVEINI` environment variable is defined, then the driver searches for the file specified by the environment variable.

Important:

`CLODERAHIVEINI` must specify the full path, including the filename.

2. The directory containing the driver's binary is searched for a file named `cloudera.hiveodbc.ini` **not** beginning with a period.
3. The current working directory of the application is searched for a file named `cloudera.hiveodbc.ini` **not** beginning with a period.
4. The directory `~/` (i.e. `$HOME`) is searched for a hidden file named `.cloudera.hiveodbc.ini`
5. The directory `/etc` is searched for a file named `cloudera.hiveodbc.ini` **not** beginning with a period.

Configuring the `odbc.ini` File

ODBC Data Sources are defined in the `odbc.ini` configuration file. The file is divided into several sections:

- **[ODBC]** is optional and used to control global ODBC configuration, such as ODBC tracing.
- **[ODBC Data Sources]** is required, listing DSNs and associating DSNs with a driver.
- A section having the same name as the data source specified in the `[ODBC Data Sources]` section is required to configure the data source.

Here is an example `odbc.ini` configuration file for Linux or AIX:

```
[ODBC Data Sources]
Sample Cloudera Hive DSN 32=Cloudera Hive ODBC Driver 32-bit
[Sample Cloudera Hive DSN 32]
Driver=/opt/cloudera/hiveodbc/lib/32/libclouderahiveodbc32.so
HOST=MyHiveServer
PORT=10000
```

Note:

To connect to Hive Server 2 you must add **HiveServerType=2** in the DSN.

Here is an example `odbc.ini` configuration file for Mac OS X:

```
[ODBC Data Sources]
Sample Cloudera Hive DSN=Cloudera Hive ODBC Driver

[Sample Cloudera Hive DSN]
Driver=/opt/cloudera/hiveodbc/lib/universal/libclouderahiveodbc.dylib
HOST=MyHiveServer
PORT=10000
```

Note:

To connect to Hive Server 2 you must add **HiveServerType=2** in the DSN.

To create a data source:

1. Open the `.odbc.ini` configuration file in a text editor.
2. Add a new entry to the [ODBC Data Sources] section. Type the data source name (DSN) and the driver name.
3. To set configuration options, add a new section that has a name that matches the data source name (DSN) you specified in step 2. Specify configuration options as key-value pairs.
4. Save the `.odbc.ini` configuration file.

For details on configuration options available to control the behavior of DSNs using Cloudera ODBC Driver for Hive, see “Appendix C: Driver Configuration Options” on page 38.

Configuring the `odbcinst.ini` File

ODBC Drivers are defined in the `odbcinst.ini` configuration file. The configuration file is optional because drivers can be specified directly in the `odbc.ini` configuration file, as described in “Configuring the `odbc.ini` File” on page 19.

The `odbcinst.ini` file is divided into the following sections:

- **[ODBC Drivers]** lists the names of all the installed ODBC drivers.
- A section having the same name as the driver name specified in the [ODBC Drivers] section lists driver attributes and values.

Here is an example `odbcinst.ini` file for Linux or AIX:

```
[ODBC Drivers]
Cloudera Hive ODBC Driver 32-bit=Installed
Cloudera Hive ODBC Driver 64-bit=Installed
[Cloudera Hive ODBC Driver 32-bit]
Description=Cloudera Hive ODBC Driver (32-bit)
Driver=/opt/cloudera/hiveodbc/lib/32/libclouderahiveodbc32.so
[Cloudera Hive ODBC Driver 64-bit]
Description=Cloudera Hive ODBC Driver (64-bit)
Driver=/opt/cloudera/hiveodbc/lib/64/libclouderahiveodbc64.so
```

Here is an example `odbcinst.ini` file for Mac OS X:

```
[ODBC Drivers]
Cloudera Hive ODBC Driver=Installed
[Cloudera Hive ODBC Driver]
Description=Cloudera Hive ODBC Driver
Driver=/opt/cloudera/hiveodbc/lib/universal/libclouderahiveodbc.dylib
```

To define a driver:

1. Open the `.odbcinst.ini` configuration file in a text editor.
2. Add a new entry to the [ODBC Drivers] section. Type the driver name, and then type the following: **=Installed**

Note:

Assign the driver name as the value of the Driver attribute in the data source definition instead of the driver shared library name.

3. In `.odbcinst.ini`, add a new section that has a name that matches the driver name you typed in step 2, and then add configuration options to the section based on the sample `odbcinst.ini` file provided with Cloudera ODBC Driver for Hive in the Setup directory. Specify configuration options as key-value pairs.
4. Save the `.odbcinst.ini` configuration file.

Configuring the `cloudera.hiveodbc.ini` File

To configure Cloudera ODBC Driver for Hive to work with your ODBC driver manager:

1. Open the `.cloudera.hiveodbc.ini` configuration file in a text editor.

Configuring ODBC Connections for Linux, Mac OS X and AIX

2. Edit the DriverManagerEncoding setting. If you are using Linux or Mac OS X, the value usually must be **UTF-16** or **UTF-32** depending on the ODBC driver manager you use. iODBC uses **UTF-32** and unixODBC uses **UTF-16**. Consult your ODBC Driver Manager documentation for the correct setting to use.

OR

If you are using AIX, then set the value to **UTF-16** if you are using the unixODBC driver manager. If you are using the iODBC driver manager, then set the value to **UTF-16** if you are using the 32-bit driver, or set the value to **UTF-32** if you are using the 64-bit driver.

3. Edit the ODBCInstLib setting. The value is the name of the ODBCInst shared library for the ODBC driver manager you use. The configuration file defaults to the shared library for iODBC. In Linux, the shared library name for iODBC is libiodbcinst.so. In Mac OS X, the shared library name for iODBC is libiodbcinst.dylib.

Note:

Consult your ODBC driver manager documentation for the correct library to specify. You can specify an absolute or relative filename for the library. If you intend to use the relative filename, then the path to the library must be included in the library path environment variable. In Linux, the library path environment variable is named LD_LIBRARY_PATH. In Mac OS X, the library path environment variable is named DYLD_LIBRARY_PATH.

4. Save the .cloudera.hiveodbc.ini configuration file.

Configuring Authentication

For details on selecting the appropriate authentication for a DSN using Cloudera ODBC Driver for Hive, see “Appendix A: Authentication Options” on page 30.

For details on the keys involved in configuring authentication, see “Appendix A: Authentication Options” on page 30. The authentication methods available are as follows:

- No Authentication
- Kerberos
- User Name
- User Name and Password
- User Name and Password (SSL)
- HTTP
- HTTPS
- Kerberos over HTTP
- Kerberos over HTTPS

Using No Authentication

No additional details are required when using **No Authentication**.

Using Kerberos

For information on operating Kerberos, refer to the documentation for your operating system.

To configure a DSN using Cloudera ODBC Driver for Hive to use Kerberos authentication:

1. Set the AuthMech configuration key for the DSN to 1.
2. If your Kerberos setup does not define a default realm or if the realm of your Hive server is not the default, then set the appropriate realm using the KrbRealm key.
3. Set the KrbHostFQDN key to the fully qualified domain name of the Hive Server 2 host.
4. Set the KrbServiceName key to the service name of the Hive Server 2. For example, if the principle for the Hive Server 2 is "hive/[fully.qualified.domain.name@YOUR-REALM.COM](#)", then the value in the service name field should be **hive**. If you are unsure of the correct service name to use for your particular Hadoop deployment, see your Hadoop administrator

Using User Name

To configure User Name authentication:

1. Set the AuthMech configuration key for the DSN to 2.
2. Set the UserName key to the appropriate credential recognized by the Hive server.

To configure User Name authentication:

1. Set the AuthMech configuration key for the DSN to 2.
2. Set the UID key to the appropriate user name recognized by the Hive server.

Using User Name and Password

To configure User Name and Password authentication:

1. Set the AuthMech configuration key for the DSN to 3.
2. Set the UID key to the appropriate user name recognized by the Hive server.
3. Set the PWD key to the password corresponding to the user name you provided in step 2.

Using User Name and Password (SSL)

To configure User Name and Password (SSL) authentication:

1. Set the AuthMech configuration key for the DSN to 4.
2. Set the UID key to the appropriate user name recognized by the Hive server.
3. Set the PWD key to the password corresponding to the user name you provided in step 2.

Note:

The driver always accepts the use of self-signed SSL certificate for this authentication mechanism.

Note:

Optionally, you can configure the **CAIssuedCertNamesMismatch** setting to control whether the driver allows the common name of a CA-issued certificate to not match the host name of the Hive server. For self-signed certificates the driver always allows the common name of the certificate to not match the host name. See “Appendix C: Driver Configuration Options” on page 38.

Note:

Optionally, you can configure the **TrustedCerts** setting to specify the file listing the SSL certificate authorities (CAs) you would like the driver to trust. The content of this file should be the CAs’ certificates encoded in PEM format. These trusted CA certificates are used by the driver during SSL handshake to verify the server certificate and determine if the server can be trusted. By default the driver trusts the certificate authorities listed in the cacerts.pem file that comes with the driver. See “Appendix C: Driver Configuration Options” on page 38.

Using HTTP

To configure HTTP authentication:

1. Set the AuthMech configuration key for the DSN to 7.
2. Set the HTTPPath key to the partial URL corresponding to the Hive server.

Note:

HTTP is only available starting with Hive 0.12.0.

Using HTTPS

To configure HTTPS authentication:

1. Set the AuthMech configuration key for the DSN to 8.
2. Set the HTTPPath key to the partial URL corresponding to the Hive server.
3. Set the UID key to an appropriate user name for accessing the Hive server.
4. Set the PWD key to the password corresponding to the user name you typed in step 3.

Note:

HTTPS is only available starting with Hive 0.13.0.

Note:

The driver always accepts the use of self-signed SSL certificate for this authentication mechanism.

Note:

Optionally, you can configure the **CAIssuedCertNamesMismatch** setting to control whether the driver allows the common name of a CA-issued certificate to not match the host name of the Hive server. For self-signed certificates, the driver always allows the common name of the certificate to not match the host name. See “Appendix C: Driver Configuration Options” on page 38.

Note:

Optionally, you can configure the **TrustedCerts** setting to specify the file listing the SSL certificate authorities (CAs) you would like the driver to trust. The content of this file should be the CAs’ certificates encoded in PEM format. These trusted CA certificates are used by the driver during SSL handshake to verify the server certificate and determine if the server can be trusted. By default the driver trusts the certificate authorities listed in the cacerts.pem file that comes with the driver. See “Appendix C: Driver Configuration Options” on page 38.

Using Kerberos over HTTP

For information on operating Kerberos, refer to the documentation for your operating system.

To configure a DSN using Cloudera ODBC Driver for Hive to use Kerberos over HTTP authentication:

1. Set the AuthMech configuration key for the DSN to 9.
2. If your Kerberos setup does not define a default realm or if the realm of your Hive server is not the default, then set the appropriate realm using the KrbRealm key.
3. Set the KrbHostFQDN key to the fully qualified domain name of the Hive Server 2 host.
4. Set the KrbServiceName key to the service name of the Hive Server 2. For example, if the principle for the Hive Server 2 is "hive/[fully.qualified.domain.name@YOUR-REALM.COM](#)", then the value in the service name field should be **hive**. If you are unsure of the correct service name to use for your particular Hadoop deployment, see your Hadoop administrator.
5. Set the HTTPPath key to the partial URL corresponding to the Hive server.

Note:

Kerberos over HTTP is only available starting with Hive 0.13.0.

Using Kerberos over HTTPS

For information on operating Kerberos, refer to the documentation for your operating system.

To configure a DSN using Cloudera ODBC Driver for Hive to use Kerberos over HTTPS authentication:

1. Set the AuthMech configuration key for the DSN to 10.

Features

2. If your Kerberos setup does not define a default realm or if the realm of your Hive server is not the default, then set the appropriate realm using the KrbRealm key.
3. Set the KrbHostFQDN key to the fully qualified domain name of the Hive Server 2 host.
4. Set the KrbServiceName key to the service name of the Hive Server 2. For example, if the principle for the Hive Server 2 is "hive/[fully.qualified.domain.name@YOUR-REALM.COM](#)", then the value in the service name field should be **hive**. If you are unsure of the correct service name to use for your particular Hadoop deployment, see your Hadoop administrator.
5. Set the HTTPPath key to the partial URL corresponding to the Hive server.

Note:

Kerberos over HTTPS is only available starting with Hive 0.13.0.

Note:

The driver always accepts the use of self-signed SSL certificate for this authentication mechanism.

Note:

Optionally, you can configure the **CAIssuedCertNamesMismatch** setting to control whether the driver allows the common name of a CA-issued certificate to not match the host name of the Hive server. For self-signed certificates the driver always allows the common name of the certificate to not match the host name. See “Appendix C: Driver Configuration Options” on page 38.

Note:

Optionally, you can configure the **TrustedCerts** setting to specify the file listing the SSL certificate authorities (CAs) you would like the driver to trust. The content of this file should be the CAs’ certificates encoded in PEM format. These trusted CA certificates are used by the driver during SSL handshake to verify the server certificate and determine if the server can be trusted. By default the driver trusts the certificate authorities listed in the cacerts.pem file that comes with the driver. See “Appendix C: Driver Configuration Options” on page 38.

Features

SQL Query versus HiveQL Query

The native query language supported by Hive is HiveQL. For simple queries, HiveQL is a subset of SQL-92. However, for most applications, the syntax is different enough that most applications do not work with native HiveQL.

SQL Connector

To bridge the difference between SQL and HiveQL, the SQL Connector feature translates standard SQL-92 queries into equivalent HiveQL queries. The SQL Connector performs syntactical translations and structural transformations. For example:

- **Quoted Identifiers**—When quoting identifiers, HiveQL uses back quotes (`) while SQL uses double quotes ("). Even when a driver reports the back quote as the quote character, some applications still generate double-quoted identifiers.
- **Table Aliases**—HiveQL does not support the AS keyword between a table reference and its alias.
- **JOIN, INNER JOIN and CROSS JOIN**—SQL INNER JOIN and CROSS JOIN syntax is translated to HiveQL JOIN syntax.
- **TOP N/LIMIT**—SQL TOP N queries are transformed to HiveQL LIMIT queries.

Data Types

The following data types are supported:

- TINYINT
- SMALLINT
- INT
- BIGINT
- FLOAT
- DOUBLE
- DECIMAL
- BOOLEAN
- STRING
- TIMESTAMP
- VARCHAR(n)
- DATE
- DECIMAL(p,s)
- CHAR(n)

Note:

The aggregate types (ARRAY, MAP and STRUCT) are not yet supported. Columns of aggregate types are treated as STRING columns.

Features

Catalog and Schema Support

Cloudera ODBC Driver for Hive supports both catalogs and schemas in order to make it easy for the driver to work with various ODBC applications. Since Hive only organizes tables into schema/database, we have added a synthetic catalog, called “HIVE” under which all of the schemas/databases are organized. The driver also maps the ODBC schema to the Hive schema/database.

Hive System Table

A pseudo-table called **HIVE_SYSTEM** can be used to query for Hive cluster system environment information. The pseudo table is under the pseudo schema **HIVE_SYSTEM**. The table has two String type columns **ENVKEY** and **ENVVALUE**. Standard SQL can be executed against the Hive system table. For example:

```
SELECT * FROM HIVE_SYSTEM.HIVE_SYSTEM WHERE ENVKEY LIKE '%hive%'
```

The example query returns all of the Hive system environment entries whose key contains the word “hive.” A special query, “`set -v`”, is executed to fetch system environment information and is not supported by all Hive versions. For versions of Hive that do not support querying system environment information, the driver returns an empty result set.

Server-side Properties

The Cloudera ODBC Driver for Hive allows you to set server-side properties via a DSN. Server-side properties specified in a DSN affect only the connection established using the DSN.

For details on setting server-side properties for a DSN using the Windows driver, see *Configuring ODBC Connections* on page 2. For details related to the Linux and Mac OS X drivers, see “Appendix C: Driver Configuration Options” on page 38.

Active Directory

Cloudera ODBC Driver for Hive supports Active Directory Kerberos on Windows. There are two prerequisites for using Active Directory Kerberos on Windows:

1. MIT Kerberos is **not** installed on client Windows machine.
2. The MIT Kerberos Hadoop realm has been configured to trust the Active Directory realm, according to Cloudera’s documentation, so that users in the Active Directory realm can access services in the MIT Kerberos Hadoop realm.

Get Tables With Query

The **Get Tables With Query** configuration option allows you to choose whether to use the SHOW TABLES query or the GetTables API call to retrieve table names from a database.

Hive Server 2 has a limit on the number of tables that can be in a database when handling the GetTables API call. When the number of tables in a database is above the limit, the API call will return a stack overflow error or a timeout error. The exact limit and the error that appears depend on the JVM settings.

As a workaround for this issue, enable the **Get Tables with Query** (or **GetTablesWithQuery**) configuration option to use the query instead of the API call.

Temporary Table

The Temporary Table feature adds support for creating temporary tables and inserting literal values into temporary tables. Temporary tables are only accessible by the ODBC connection that created them and they will be dropped upon disconnect. For temporary table CREATE TABLE and INSERT statement syntax see “Appendix D: Temporary Table CREATE TABLE and INSERT Statements” on page 49.

Contact Us

If you have difficulty using the driver, you can contact Cloudera Technical Support. We welcome your questions, comments and feature requests.

Important:

To help us assist you, prior to contacting Technical Support please prepare a detailed summary of the client and server environment including operating system version, patch level and configuration.

For details on contacting Technical Support, see <http://www.cloudera.com/content/cloudera/en/products/cloudera-support.html>

Appendix A: Authentication Options

Note:

Authentication is only available for servers of type Hive Server 2. Authentication is not available for servers of type Hive Server 1.

Hive Server 2 supports multiple authentication mechanisms. You must determine the authentication type your server is using. The authentication methods available are as follows:

- No Authentication
- Kerberos
- User Name
- User Name and Password
- User Name and Password (SSL)
- HTTP
- HTTPS
- Kerberos over HTTP
- Kerberos over HTTPS

To discover how your Hive Server 2 is configured, examine your hive-site.xml file. Examine the following properties to determine which authentication mechanism your server is set to use:

- hive.server2.authentication
- hive.server2.enable.doAs

hive.server2.authentication	hive.server2.enable.doAs	Driver Authentication Mechanism
NOSASL	False	No Authentication
KERBEROS	True or False	Kerberos
NONE	True or False	User Name
LDAP	True or False	User Name and Password OR User Name and Password (SSL) Note: User Name and Password (SSL) can only be used if your Hive server is configured with SSL.

Note:

It is an error to set `hive.server2.authentication` to `NOSASL` and `hive.server2.enable.doAs` to `true`. This configuration will not prevent the service from starting up but results in an unusable service.

Hive Server 2 uses SASL (Simple Authentication and Security Layer) to support some of the authentication methods. The following table shows which authentication methods are supported by SASL.

SASL mechanisms	Non-SASL mechanisms
Kerberos	No Authentication
User Name	HTTP
User Name and Password	HTTPS
User Name and Password (SSL)	Kerberos over HTTP
	Kerberos over HTTPS

Kerberos is supported by the SASL GSSAPI mechanism, while **User Name**, **User Name and Password**, and **User Name and Password (SSL)** are supported by the SASL PLAIN mechanism.

Note:

Remote process communication between the Cloudera ODBC Driver for Hive and the Hive Server is handled by a layer called Thrift. Thrift cannot detect combinations of both non-SASL and SASL mechanisms being used between the driver and the server. For example, if the driver is using a non-SASL mechanism but the server is using a SASL mechanism, then the driver will hang when attempting to establish a connection. Ensure that the driver and the server both use mechanisms of the same type.

Note:

The default configuration of Hive Server 2 uses the SASL PLAIN mechanism and requires you to use either the **User Name** or **User Name and Password** authentication mechanism for the Cloudera ODBC Driver for Hive.

For more detail on authentication mechanisms, see the documentation for your Hadoop / Hive distribution. See also “Running Hadoop in Secure Mode” at

Appendix A: Authentication Options

http://hadoop.apache.org/docs/r0.23.7/hadoop-project-dist/hadoop-common/ClusterSetup.html#Running_Hadoop_in_Secure_Mode

Using No Authentication

When `hive.server2.authentication` is set to `NOSASL`, you must configure your connection to use **No Authentication**.

Using Kerberos

When `hive.server2.authentication` is set to `KERBEROS`, then you must configure your connection to use **Kerberos**.

Using User Name

When `hive.server2.authentication` is set to `NONE`, you must configure your connection to use **User Name**. Validation of the credentials that you include depends on `hive.server2.enable.doAs`:

- If `hive.server2.enable.doAs` is set to `true`, then the User Name in the DSN or driver configuration must be an **existing OS user** on the host running Hive Server 2.
- If `hive.server2.enable.doAs` is set to `false`, then the User Name in the DSN or driver configuration is ignored.

If the User Name in the DSN or driver configuration is not supplied, then the driver defaults to using “anonymous” as the user name.

Using User Name and Password

When connecting to a Hive server of type Hive Server 2 configured to use SASL-PLAIN authentication with user name and password, then you must configure your connection to use **User Name and Password**.

Using User Name and Password (SSL)

When connecting to a Hive server of type Hive Server 2 configured to use SASL-PLAIN authentication with user name and password, and with SSL enabled, then you must configure your connection to use **User Name and Password**.

Using HTTP

When connecting to Hive Server 2 configured to use the Thrift HTTP transport over a TCP socket then you must configure your connection to use **HTTP** authentication mechanism.

Using HTTPS

When connecting to Hive Server 2 configured to use the Thrift HTTP transport over a SSL socket then you must configure your connection to use **HTTPS** authentication mechanism.

Using Kerberos over HTTP

When connecting to a Kerberos enabled Hive Server 2 configured to use the Thrift HTTP transport over a TCP socket, you must configure your connection to use **Kerberos over HTTP** authentication mechanism.

Using Kerberos over HTTPS

When connecting to Kerberos enabled Hive Server 2 configured to use the Thrift HTTP transport over a SSL socket, you must configure your connection to use **Kerberos over HTTPS** authentication mechanism.

Appendix B: Configuring Kerberos Authentication for Windows

Active Directory

Cloudera ODBC Driver for Hive supports Active Directory Kerberos on Windows. There are two prerequisites for using Active Directory Kerberos on Windows:

1. MIT Kerberos is **not** installed on client Windows machine.
2. The MIT Kerberos Hadoop realm has been configured to trust the Active Directory realm, according to Cloudera's documentation, so that users in the Active Directory realm can access services in the MIT Kerberos Hadoop realm.

MIT Kerberos

Download and install MIT Kerberos for Windows 4.0.1

1. For 64-bit computers: <http://web.mit.edu/kerberos/dist/kfw/4.0/kfw-4.0.1-amd64.msi>. The installer includes both 32-bit and 64-bit libraries.
2. For 32-bit computers: <http://web.mit.edu/kerberos/dist/kfw/4.0/kfw-4.0.1-i386.msi>. The installer includes 32-bit libraries only.

Set up the Kerberos configuration file in the default location

1. Obtain a **krb5.conf** configuration file from your Kerberos administrator. The configuration file should also be present at **/etc/krb5.conf** on the machine hosting the Hive Server 2.
2. The default location is **C:\ProgramData\MIT\Kerberos5** but this is normally a hidden directory. Consult your Windows documentation if you wish to view and use this hidden directory.
3. Rename the configuration file from **krb5.conf** to **krb5.ini**.
4. Copy **krb5.ini** to the default location and overwrite the empty sample file.

Consult the MIT Kerberos documentation for more information on configuration.

Set up the Kerberos configuration file in another location

If you do not want to put the Kerberos configuration file in the default location then you can use another location. The steps required to do this are as follows:

1. Obtain a **krb5.conf** configuration file for your Kerberos setup.
2. Store **krb5.conf** in an accessible directory and make note of the full path name.
3. Click the Windows **Start** menu.
4. Right-click **Computer**.
5. Click **Properties**.
6. Click **Advanced system settings**.
7. Click **Environment Variables**.
8. Click **New** for System variables.

9. In the **Variable Name** field, type **KRB5_CONFIG**.
10. In the **Variable Value** field, type the absolute path to the krb5.conf file you stored in step 2.
11. Click **OK** to save the new variable.
12. Ensure the variable is listed in the **System variables** list.
13. Click **OK** to close Environment Variables Window.
14. Click **OK** to close System Properties Window.

Set up the Kerberos credential cache file

1. Create a new directory where you want to save the Kerberos credential cache file. For example, you may create the C:\temp directory.
2. Click the Windows **Start** menu.
3. Right-click **Computer**.
4. Click **Properties**.
5. Click **Advanced system settings**.
6. Click **Environment Variables**.
7. Click **New** for System variables.
8. In the **Variable Name** field, type **KRB5CCNAME**
9. In the **Variable Value** field, type the path to the directory you created in step 1, and then append the file name **krb5cache**. For example, if you created the C:\temp directory in step 1, then type: C:\temp\krb5cache

Note:

krb5cache is a file—not a directory—managed by the Kerberos software and should not be created by the user. If you receive a permission error when you first use Kerberos, check to ensure that the krb5cache file does not exist as a file or a directory.

10. Click **OK** to save the new variable.
11. Ensure the variable appears in the System variables list.
12. Click **OK** to close Environment Variables Window.
13. Click **OK** to close System Properties Window.
14. Restart your computer to ensure that MIT Kerberos for Windows uses the new settings.

Obtain a ticket for a Kerberos principal using password

Note:


If your Kerberos environment uses keytab files please see the next section.

1. Click the **Start** button .

Appendix B: Configuring Kerberos Authentication for Windows

2. Click **All Programs**.
3. Click the **Kerberos for Windows (64-bit)** or the **Kerberos for Windows (32-bit)** program group.
4. Use **MIT Kerberos Ticket Manager** to obtain a ticket for the principal that will be connecting to Hive Server 2.

Obtain a ticket for a Kerberos principal using a keytab file

1. Click the **Start** button .
2. Click **All Programs**.
3. Click **Accessories**.
4. Click **Command Prompt**.
5. Type: `kinit -k -t <keytab pathname> <principal>`

`<keytab pathname>` is the full pathname to the keytab file. For example, `C:\mykeytabs\hiveserver2.keytab`

`<principal>` is the Kerberos principal to use for authentication. For example, hive/hiveserver2.example.com@EXAMPLE.COM

On some Windows systems, the cache location KRB5CCNAME is either not set or not used. In this case, use the '-c' option of the kinit command to specify the proper ticket cache that needs to be populated.

The command syntax is:


```
kinit -k -t C:\mykeytabs\hive.keytab hive/HOST@HADOOP.NET -c c:\ProgramData\MIT\krbcache  
(krbcache is the kerberos cache file, not a directory.)
```

Note:

The order of the options shown above is important because the '-c' argument must be last.

Obtain a ticket for a Kerberos principal using the default keytab file

A default keytab file can be set for your Kerberos configuration. Consult the MIT Kerberos documentation for instructions on configuring a default keytab file.

1. Click the **Start** button .
2. Click **All Programs**.
3. Click **Accessories**.
4. Click **Command Prompt**.

5. Type: `kinit -k <principal>`

`<principal>` is the Kerberos principal to use for authentication. For example,
`hive/hiveserver2.example.com@EXAMPLE.COM`

On some Windows systems, the cache location `KRB5CCNAME` is either not set or not used. In this case, use the `-c` option of the `kinit` command to specify the proper ticket cache that needs to be populated.

The command syntax is:

```
kinit -k hive/HOST@HADOOP.NET -c c:\ProgramData\MIT\krbcache
```

(krbcache is the kerberos cache file, not a directory.)

Note:

The order of the options shown above is important because the `-c` argument must be last.

Appendix C: Driver Configuration Options

The configuration options available to control the behavior of Cloudera ODBC Driver for Hive are listed and described in *Table 1*.

Note:

You can set configuration options in your `odbc.ini` and `cloudera.hiveodbc.ini` files. Configuration options set in a `cloudera.hiveodbc.ini` file apply to all connections, whereas configuration options set in an `odbc.ini` file are specific to a connection. Configuration options set in `odbc.ini` take precedence over configuration options set in `cloudera.hiveodbc.ini`

Table 1 Driver Configuration Options

Key	Default Value	Description
Driver		The location of the Cloudera ODBC Driver for Hive shared object file. (Required)
HOST		The IP address or hostname of the Hive server. (Required)
PORT	10000	The listening port for the service. (Required)
Schema	default	The name of the database schema to use when a schema is not explicitly specified in a query. <div data-bbox="1045 1283 1427 1766" style="border: 1px solid black; padding: 5px;"> <p>Note:</p> <p>Queries on other schemas can still be issued by explicitly specifying the schema in the query. To determine the appropriate database schema to use, type <code>show databases</code> at the Hive command prompt to inspect your databases.</p> </div> (Optional)

Key	Default Value	Description
DefaultStringLength	255	<p>The default string column length to use. Hive does not provide the length for String columns in its column metadata. This option allows you to tune the length of String columns.</p> <p>(Optional)</p>
BinaryColumnLength	32767	<p>The maximum data length for binary columns.</p> <div data-bbox="1045 606 1427 938" style="border: 1px solid orange; padding: 5px;"> <p>Note:</p> <p>Hive does not provide the maximum data length for binary columns in the columns metadata. The option allows you to tune the maximum data length for binary columns.</p> </div> <p>(Optional)</p>
UseNativeQuery	0	<p>Enabling the UseNativeQuery option using a value of 1 disables the SQL Connector feature. The SQL Connector feature allows the driver to apply transformations to the queries emitted by an application to convert them into an equivalent form in HiveQL. If the application is Hive-aware and already emits HiveQL, then turning off the SQL Connector feature avoids the extra overhead of query transformation.</p> <p>(Optional)</p>

Appendix C: Driver Configuration Options

Key	Default Value	Description
FastSQLPrepare	0	<p>To enable the FastSQLPrepare option, use a value of 1. Enabling FastSQLPrepare defers query execution to SQLExecute. When using Native Query mode, the driver will execute the HiveQL query to retrieve the result set metadata for SQLPrepare. As a result, SQLPrepare might be slow. If the result set metadata is not required after calling SQLPrepare, then enable FastSQLPrepare.</p> <p>(Optional)</p>
EnableAsyncExec	0	<p>Enable/disable the use of asynchronous query execution.</p> <p>Note: This option only takes effect when connecting to Hive cluster running Hive 0.12.0 or higher.</p> <div style="border: 1px solid black; padding: 5px; margin: 10px 0;"> <p>Note:</p> <p>Due to a problem in Hive 0.12.0 (see https://issues.apache.org/jira/browse/HIVE-5230), Hive returns generic error messages for errors that occur during query execution. To see the actual error message relevant to the problem, turn off asynchronous query execution and execute the query again.</p> </div> <p>Set to 1 to enable. Set to 0 to disable.</p> <p>(Optional)</p>

Key	Default Value	Description
RowsFetchedPerBlock	10000	<p>The maximum number of rows that a query returns at a time. Any positive 32-bit integer is a valid value but testing has shown that performance gains are marginal beyond the default value of 10000 rows.</p> <p>(Optional)</p>
DecimalColumnScale	10	<p>The maximum number of digits to the right of the decimal point for numeric data types.</p> <p>(Optional)</p>
SSP_		<p>To set a server-side property, use the following syntax where <i>SSPKey</i> is the name of the server-side property to set and <i>SSPValue</i> is the value to assign to the server-side property:</p> <p><i>SSP_SSPKey=SSPValue</i></p> <p>For example: SSP_mapred.queue.names=myQueue</p> <p>After the driver applies the server-side property, the SSP_ prefix is removed from the DSN entry leaving an entry of <i>SSPKey=SSPValue</i></p> <div data-bbox="1045 1297 1430 1476" style="border: 1px solid orange; padding: 5px;"> <p>Important:</p> <p>The SSP_ prefix is case sensitive.</p> </div> <p>(Optional)</p>

Appendix C: Driver Configuration Options

Key	Default Value	Description
ApplySSPWithQueries	1	<p>When set to the default value of 1 (enabled), each server-side property you set is applied by executing a set SSPKey=SSPValue query when opening a session to the Hive server.</p> <p>Applying server-side properties using queries involves an additional network round trip per server-side property when establishing a session to the Hive server. Some Hive Server 2 builds are not compatible with the more efficient method of setting server-side properties that the driver uses when ApplySSPWithQueries is disabled by this to 0.</p> <div style="border: 1px solid orange; padding: 5px; margin: 10px 0;"> <p>Note: When connecting to a Hive Server 1, ApplySSPWithQueries is always enabled.</p> </div> <p>Set to 1 to enable. Set to 0 to disable. (Optional)</p>
LCCaseSspKeyName	1	<p>Controls whether the driver will convert server-side property key name to all lower case characters.</p> <p>Set to 1 to enable. Set to 0 to disable. (Optional)</p>
HiveServerType	1	<p>The Hive Server Type.</p> <p>Set to 1 for Hive Server 1. Set to 2 for Hive Server 2. (Optional)</p>

Appendix C: Driver Configuration Options

Key	Default Value	Description
AuthMech	0	<p>The authentication mechanism to use. Set the value to one of the following:</p> <ul style="list-style-type: none"> • 0 for no authentication • 1 for Kerberos • 2 for User Name • 3 for User Name and Password • 4 for User Name and Password (SSL) • 5 (Reserved) • 6 (Reserved) • 7 for HTTP • 8 for HTTPS • 9 for Kerberos over HTTP • 10 for Kerberos over HTTPS <p>(Optional)</p>
KrbHostFQDN		<p>The fully qualified domain name of the Hive Server 2 host used.</p> <p>(Required if AuthMech is Kerberos)</p>
KrbServiceName		<p>The Kerberos service principal name of the Hive Server 2. By convention the service name is <code>hive</code>, but the name may be different in your server environment.</p> <p>(Required if AuthMech is Kerberos)</p>

Appendix C: Driver Configuration Options

Key	Default Value	Description
KrbRealm		If there is no default realm configured or the realm of the Hive Server 2 host is different from the default realm for your Kerberos setup, then define the realm of the Hive Server 2 host using this option. (Optional)
HTTPPath		The partial URL corresponding to Hive server configured to use HTTP or HTTPS . (Optional)
UID	anonymous	The user name of the user credential. (Required if AuthMech is User Name and Password, User Name and Password (SSL), or HTTPS) (Optional if AuthMech is User Name)
PWD		The password of the user credential. (Required if AuthMech is User Name and Password, User Name and Password (SSL), or HTTPS)
CAIssuedCertNamesMismatch	0	Control whether to allow CA issued SSL certificate's common name to not match the host name of the Hive server. Set to 1 to enable. Set to 0 to disable. Note: This setting is only applicable to User Name and Password (SSL) authentication mechanism and will be ignored by other authentication mechanisms. (Optional)

Key	Default Value	Description
TrustedCerts	<p>For 32 bit driver: /opt/cloudera/hiveodbc/lib/32/ca certs.pem</p> <p>For 64 bit driver: /opt/cloudera/hiveodbc/lib/64/ca certs.pem</p>	<p>Used to specify the location of the file containing trusted CA certificates for authenticating the Hive server when using SSL.</p> <div data-bbox="1032 403 1414 739" style="border: 1px solid orange; padding: 5px;"> <p>Note:</p> <p>This setting is only applicable to User Name and Password (SSL) and HTTPS authentication mechanisms, and will be ignored by other authentication mechanisms.</p> </div> <div data-bbox="1032 793 1414 1087" style="border: 1px solid orange; padding: 5px;"> <p>Note:</p> <p>If this setting is not set, then the driver will default to using the trusted CA certificates file installed by the driver.</p> </div> <p>(Optional)</p>
ForceSynchronousExec	0	<p>Used to force the driver to do synchronous query execution when connected to a Hive cluster capable of asynchronous query execution.</p> <p>Set to 1 to enable. Set to 0 to disable.</p> <p>(Optional)</p>

Appendix C: Driver Configuration Options

Key	Default Value	Description
DelegationUID		<p>Used to delegate all operation against Hive to a user that is different than the authenticated user for the connection.</p> <div data-bbox="1032 422 1416 716" style="border: 1px solid #f0e68c; padding: 5px;"> <p>Note:</p> <p>This setting is only applicable when connecting to a Hive Server 2 that supports this feature. Otherwise this setting will not take any effect.</p> </div> <p>(Optional)</p>
AsyncExecPollInterval	100	<p>The time in millisecond between each poll for the status of an asynchronous query execution.</p> <div data-bbox="1032 894 1416 1150" style="border: 1px solid #f0e68c; padding: 5px;"> <p>Note:</p> <p>This configuration is only applicable to Hive 0.12.0 or above, and is ignored otherwise.</p> </div> <div data-bbox="1032 1220 1416 1593" style="border: 1px solid #f0e68c; padding: 5px;"> <p>Note:</p> <p>Asynchronous execution here doesn't mean ODBC asynchronous operations are supported; it only means the RPC call used to execute a query against Hive is asynchronous.</p> </div> <p>(Optional)</p>

Appendix C: Driver Configuration Options

Key	Default Value	Description
DriverConfigTakePrecedence	0	<p>Allow driver wide configurations to take precedence over connection string and DSN settings.</p> <p>Set to 1 to enable. Set to 0 to disable. (Optional)</p>
GetTablesWithQuery	0	<p>Controls whether to retrieve the names of tables in a database using the GET TABLES query instead of the GetTables Thrift API call.</p> <div style="border: 1px solid orange; padding: 5px; margin: 5px 0;"> <p>Note: This setting is only applicable when connecting to Hive Server 2.</p> </div> <p>Set to 1 to enable. Set to 0 to disable. (Optional)</p>
EnableTempTable	0	<p>Controls whether to enable or disable the temporary table feature.</p> <p>Set to 1 to enable. Set to 0 to disable. (Optional)</p>
WebHDFSHost	The Hive Server host.	<p>The hostname or IP address of the machine hosting both the NameNode of your Hadoop cluster and the WebHDFS service. (Optional)</p>
WebHDFSPort	50070	<p>The name of the HDFS user that the driver will use to create the necessary files for supporting the Temporary Table feature. (Optional)</p>

Appendix C: Driver Configuration Options

Key	Default Value	Description
HDFSTempTableDir	/tmp/simba	<p>The HDFS directory that the driver will use to store the necessary files for supporting the Temporary Table feature.</p> <div style="border: 1px solid orange; padding: 5px;"> <p>Note: Due to a problem in Hive (see https://issues.apache.org/jira/browse/HIVE-4554), space characters in HDFS path will not work with versions of Hive prior to 0.12.0.</p> </div> <p>(Optional)</p>
TempTableTTL	10	<p>The number of minutes a temporary table is guaranteed to exist in Hive after it is created.</p> <p>(Optional)</p>
ShowHiveSystemTable	0	<p>Controls whether the driver returns the HIVE_SYSTEM table for catalog function calls such as SQLTables and SQLColumns.</p> <p>Set to 0 to not return the HIVE_SYSTEM table.</p> <p>Set to 1 to return the HIVE_SYSTEM table.</p> <p>(Optional)</p>
UseUnicodeSqlCharacterTypes	0	<p>Controls whether the driver returns SQL_WVARCHAR or SQL_VARCHAR for STRING and VARCHAR columns, and SQL_WCHAR or SQL_CHAR for CHAR columns.</p> <p>Set to 0 to return SQL_VARCHAR/SQL_CHAR.</p> <p>Set to 1 to return SQL_WVARCHAR/SQL_WCHAR.</p> <p>(Optional)</p>

Appendix D: Temporary Table CREATE TABLE and INSERT Statements

Temporary Table CREATE TABLE Statement

The following DDL syntax for creating temporary table is supported:

<create table statement> := CREATE TABLE <temporary table name> <left paren><column definition list><right paren>

<column definition list> := <column definition>[, <column definition>]*

<column definition> := <column name> <data type>

<temporary table name> := <double quote><number sign><table name><double quote>

<left paren> := (

<right paren> :=)

<double quote> := "

<number sign> := #

The following is an example of a CREATE TABLE SQL statement for creating a temporary table:

```
CREATE TABLE "#TEMPTABLE1" (C1 DATATYPE_1, C2 DATATYPE_2, ..., Cn DATATYPE_n)
```

Note:

The temporary table name in a SQL query must be surrounded by double quotes, and the name must begin with a number sign.

Note:

Data types are limited by the set of data types supported by Hive.

Temporary Table INSERT Statement

The following is the supported INSERT syntax for temporary table:

<insert statement> := INSERT INTO <temporary table name> <left paren><column name list><right paren> VALUES <left paren><literal value list><right paren>

<column name list> := <column name>[, <column name>]*

<literal value list> := <literal value>[, <literal value>]*

<temporary table name> := <double quote><number sign><table name><double quote>

Appendix D: Temporary Table CREATE TABLE and INSERT Statements

<left paren> := (

<right paren> :=)

<double quote> := "

<number sign> := #

The following is an example of temporary table INSERT statement:

```
INSERT INTO "#TEMPTABLE1" values (VAL(C1), VAL(C2) ... VAL(Cn) )
```

VAL(C1) is the literal value for the first column in the table, and VAL(Cn) is the literal value for the nth column in the table.

Note:

The INSERT statement is only supported for temporary tables.

Appendix E: ODBC API Conformance Level

Conformance Level ^[1]	INTERFACES ^[2]		Conformance Level ¹	INTERFACES ^[2]
Core	SQLAllocHandle		Core	SQLGetStmtAttr
Core	SQLBindCol		Core	SQLGetTypeInfo
Core	SQLBindParameter		Core	SQLNativeSql
Core	SQLCancel		Core	SQLNumParams
Core	SQLCloseCursor		Core	SQLNumResultCols
Core	SQLColAttribute		Core	SQLParamData
Core	SQLColumns		Core	SQLPrepare
Core	SQLConnect		Core	SQLPutData
Core	SQLCopyDesc		Core	SQLRowCount
Core	SQLDescribeCol		Core	SQLSetConnectAttr
Core	SQLDisconnect		Core	SQLSetCursorName
Core	SQLDriverconnect		Core	SQLSetDescField
Core	SQLEndTran		Core	SQLSetDescRec
Core	SQLExecDirect		Core	SQLSetEnvAttr
Core	SQLExecute		Core	SQLSetStmtAttr
Core	SQLFetch		Core	SQLSpecialColumns
Core	SQLFetchScroll		Core	SQLStatistics
Core	SQLFreeHandle		Core	SQLTables
Core	SQLFreeStmt		Core	SQLBrowseConnect
Core	SQLGetConnectAttr		Level 1	SQLPrimaryKeys

^[1] ODBC Compliance levels are Core, Level 1 and Level 2. These are defined in the ODBC Specification published with the Interface SDK from Microsoft.

^[2] Interfaces include both the Unicode and non-unicode versions. See <http://msdn.microsoft.com/en-us/library/ms716246%28VS.85%29.aspx> for more details.

Appendix E: ODBC API Conformance Level

Conformance Level ^[1]	INTERFACES ^[2]		Conformance Level ¹	INTERFACES ^[2]
Core	SQLGetCursorName		Core	SQLGetInfo
Core	SQLGetData		Level 1	SQLProcedureColumns
Core	SQLGetDescField		Level 1	SQLProcedures
Core	SQLGetDescRec		Level 1	SQLProcedureColumns
Core	SQLGetDiagField		Level 2	SQLColumnPrivileges
Core	SQLGetDiagRec		Level 2	SQLDescribeParam
Core	SQLGetEnvAttr		Level 2	SQLForeignKeys
Core	SQLGetFunctions		Level 2	SQLTablePrivileges

^[1] ODBC Compliance levels are Core, Level 1 and Level 2. These are defined in the ODBC Specification published by Microsoft.

^[2] Interfaces include both the Unicode and non-unicode versions. See <http://msdn.microsoft.com/en-us/library/ms716246%28VS.85%29.aspx> for more details.